

Electromagnetic Engineering Services, Inc.			11696 Sorrento Valley Road, Suite. F, San Diego, CA 92121 (619) 259-4940 Voice (619) 259-7170 Fax		
Revision	Date	Document Name	Document #	FCC ID#	Page #
A	3/31/98	Cubic Transportation System – San Diego MK5 FCC 'C' Certification Report	98-065	LVCMK5	A-1

APPENDIX A

EESI'S TEST EQUIPMENT & TEST FACILITIES CALIBRATION PROGRAM

EESI operates a comprehensive equipment calibration program in order to ensure the validity of all test data. EESI's calibration program is fully compliant to the requirements of ANSI/NCSL Z540-1 (1994) and of ISO 10012-1 (1993-05-01). EESI's calibration program therefore meets or exceeds the US national commercial and military requirements (N.B. ANSI/NCSL Z540-1 (1994) replaces MIL-STD-45662A) and meets the requirements of ISO-9000. Specifically, all of EESI's primary reference standard devices (e.g., resistor and capacitor decade boxes, vector voltmeters, multimeters, attenuators and terminations, RF power meters (and their detector heads), oscilloscope mainframes and plug-ins, spectrum analyzers, RF preselectors, quasi-peak adapters, interference analyzers, impulse generators, signal generators and pulse/function generators, etc.) and certain secondary standard devices (e.g., RF preamplifiers used in CISPR 11/22 and FCC Part 15/18 tests) are calibrated by EESI-approved independent (third party) metrology laboratories, using NIST-traceable standards. In all cases, the metrology laboratory furnishes EESI with Certificates Of Calibration on each item of equipment that has been successfully recalibrated.

Calibration intervals are normally one year, except when the manufacturer advises a shorter interval (e.g., the HP 8568B Spectrum Analyzer is recalibrated every 6 months) or if US Government directives demand a shorter interval (e.g., the Eaton 533X-11 Impulse Generator is required to be recalibrated every six months for use in TEMPEST testing). Items of equipment which fail during routine use, or which suffer visible mechanical damage (during use or while in transit), are sidelined pending repair and recalibration. (Repairs are carried out either by the EESI-approved independent (third party) metrology laboratories, or by the manufacturer of the equipment.

EESI typically determines the Antenna Factors in its test antennas in-house. Antennas used for CISPR 11, CISPR 22, and FCC Part 15 and Part 18 Radiated Emissions testing (and for testing to the European Norms) are calibrated against NIST-traceable, FCC-approved Roberts™ Dipoles, using the methods specified in both Annex G.5 of CISPR 16-1 (1993) and ANSI C63.5 (1991), including the "Three-Antenna Method." Certain other antennas (e.g., log-conic spirals) are calibrated using the procedures specified in SAE ARP-958A. In accordance with FCC regulations, EESI recalibrates its suite of antennas used for FCC tests on an annual basis. These calibrations are performed as a precursor to the FCC-required annual revalidation of the Normalized Site Attenuation properties of EESI's Open Area Test Site¹. In those instances where antennas are acquired directly from the manufacturer, EESI will purchase an Antenna Factor Calibration Data Package. Finally, EESI may send antennas out to NIST-traceable/military-approved independent antenna range laboratories, or to the original equipment manufacturer.

¹ EESI uses the procedures contained in both Subclause 16.6 and Annex G.2 of CISPR 16-1 (1993), and ANSI C63.4 (1992) when performing Normalized Site Attenuation measurement for calibration of EESI's Open Area Test Site.