

Test Method:	FCC Part 15 Subpart C Radiated Emissions Paragraph 15.249						
Customer:	X-10 (USA), Inc			Job No.	R-8280-1		
Test Sample:	2.4Ghz wireless audio / video sender			FCC ID:	B4SXX10A		
Model No.:	XX10A			Serial No.	N/A		
Operating Mode:	Continuously Transmitter 2.4 Ghz Signal (Ch D)						
Technician:	Dennis Cortes			Date:	October 21, 1999		
Notes:	Test Distance: 3 Meters Detector: Peak						
Test Freq.	Antenna Pol./Height	EUT Orientation	Meter Reading	Correction Factor	Corrected Reading	Converted Reading	Limit
Ghz	(V/H) - Meters	X / Y / Z	DBuv	DB	dBuV/m	uV/m	uV/m
2.4717	H / 1.3	X	76.2	-0.2	76.0	6309.6	50000
2.4717	H / 1.0	Y	87.4	-0.2	87.2	22908.7	50000
2.4717	H / 1.2	Z	77.8	-0.2	77.6	7585.8	50000
2.4717	V / 1.2	X	84.7	-0.2	84.5	16788.0	50000
2.4717	V / 1.2	Y	74.0	-0.2	73.8	4897.8	50000
2.4717	V / 1.1	Z	85.7	-0.2	85.5	18836.5	50000
4.9434	H / 1.1	X	42.8	2.8	45.6	190.5	500
4.9434	H / 1.3	Y	44.6	2.8	47.4	234.4	500
4.9434	H / 1.0	Z	43.9	2.8	46.7	216.3	500
4.9434	V / 1.3	X	43.3	2.8	46.1	201.8	500
4.9434	V / 1.2	Y	43.2	2.8	46.0	199.5	500
4.9434	V / 1.1	Z	43.5	2.8	46.3	206.5	500
7.4151	H / 1.0	X	43.0	-4.0	39.0	*89.1	500
7.4151	H / 1.0	Y	43.0	-4.0	39.0	*89.1	500
7.4151	H / 1.0	Z	43.0	-4.0	39.0	*89.1	500
7.4151	V / 1.0	X	43.0	-4.0	39.0	*89.1	500
7.4151	V / 1.0	Y	43.0	-4.0	39.0	*89.1	500
7.4151	V / 1.0	Z	43.0	-4.0	39.0	*89.1	500
9.8868	H / 1.0	X	43.1	-1.3	41.8	*123.0	500
9.8868	H / 1.0	Y	43.1	-1.3	41.8	*123.0	500
9.8868	H / 1.0	Z	43.1	-1.3	41.8	*123.0	500
9.8868	V / 1.0	X	43.1	-1.3	41.8	*123.0	500
9.8868	V / 1.0	Y	43.1	-1.3	41.8	*123.0	500
9.8868	V / 1.0	Z	43.1	-1.3	41.8	*123.0	500
12.3585	H / 1.0	X	42.9	3.8	46.7	*216.3	500
12.3585	H / 1.0	Y	42.9	3.8	46.7	*216.3	500
12.3585	H / 1.0	Z	42.9	3.8	46.7	*216.3	500
12.3585	V / 1.0	X	42.9	3.8	46.7	*216.3	500
12.3585	V / 1.0	Y	42.9	3.8	46.7	*216.3	500
12.3585	V / 1.0	Z	42.9	3.8	46.7	*216.3	500
	The frequency range was scanned from 30 Mhz to 25.0 Ghz. All emissions not recorded were more Than 10 dB below the specified limit. Emissions from the EUT do not exceed the specified limits.						
	*=Noise Floor Measurements (Minimum system sensitivity)						

Test Method:	FCC Part 15 Subpart C Radiated Emissions Paragraph 15.249						
Customer:	X-10 (USA), Inc			Job No.	R-8280-1		
Test Sample:	2.4Ghz wireless audio / video sender			FCC ID:	B4SXX10A		
Model No.:	XX10A			Serial No.	N/A		
Operating Mode:	Continuously Transmitter 2.4 Ghz Signal (Ch D)						
Technician:	Dennis Cortes			Date:	October 21, 1999		
Notes:	Test Distance: 3 Meters Detector: Peak						
Test Freq.	Antenna Pol./Height	EUT Orientation	Meter Reading	Correction Factor	Corrected Reading	Converted Reading	Limit
Ghz	(V/H) / Degrees	X / Y / Z	dBuv	dB	dBuV/m	uV/m	uV/m
14.8302	H / 1.0	X	45.8	2.6	48.4	*263.0	500
14.8302	H / 1.0	Y	45.8	2.6	48.4	*263.0	500
14.8302	H / 1.0	Z	45.8	2.6	48.4	*263.0	500
14.8302	V / 1.0	X	45.8	2.6	48.4	*263.0	500
14.8302	V / 1.0	Y	45.8	2.6	48.4	*263.0	500
14.8302	V / 1.0	Z	45.8	2.6	48.4	*263.0	500
17.3019	H / 1.0	X	46.3	0.0	46.3	*206.5	500
17.3019	H / 1.0	Y	46.3	0.0	46.3	*206.5	500
17.3019	H / 1.0	Z	46.3	0.0	46.3	*206.5	500
17.3019	V / 1.0	X	46.3	0.0	46.3	*206.5	500
17.3019	V / 1.0	Y	46.3	0.0	46.3	*206.5	500
17.3019	V / 1.0	Z	46.3	0.0	46.3	*206.5	500
19.7736	H / 1.0	X	32.2	13.2	45.4	*186.2	500
19.7736	H / 1.0	Y	32.2	13.2	45.4	*186.2	500
19.7736	H / 1.0	Z	32.2	13.2	45.4	*186.2	500
19.7736	V / 1.0	X	32.2	13.2	45.4	*186.2	500
19.7736	V / 1.0	Y	32.2	13.2	45.4	*186.2	500
19.7736	V / 1.0	Z	32.2	13.2	45.4	*186.2	500
22.2453	H / 1.0	X	32.5	13.5	46.0	*199.5	500
22.2453	H / 1.0	Y	32.5	13.5	46.0	*199.5	500
22.2453	H / 1.0	Z	32.5	13.5	46.0	*199.5	500
22.2453	V / 1.0	X	32.5	13.5	46.0	*199.5	500
22.2453	V / 1.0	Y	32.5	13.5	46.0	*199.5	500
22.2453	V / 1.0	Z	32.5	13.5	46.0	*199.5	500
24.717	H / 1.0	X	32.9	13.9	46.8	*218.8	500
24.717	H / 1.0	Y	32.9	13.9	46.8	*218.8	500
24.717	H / 1.0	Z	32.9	13.9	46.8	*218.8	500
24.717	V / 1.0	X	32.9	13.9	46.8	*218.8	500
24.717	V / 1.0	Y	32.9	13.9	46.8	*218.8	500
24.717	V / 1.0	Z	32.9	13.9	46.8	*218.8	500
	The frequency range was scanned from 30 Mhz to 25.0 Ghz. All emissions not recorded were more						
	Than 10 dB below the specified limit. Emissions from the EUT do not exceed the specified limits.						
	*=Noise Floor Measurements (Minimum system sensitivity)						

