


FCC RF Test Report


APPLICANT : VERTU Corporation Limited
EQUIPMENT : GSM 4 Band/CDMA/EVDO 2 Band/TD-SCDMA
2 Band/UMTS 5 Band/HSUPA/HSDPA/LTE 21
Band/WLAN/BT/NFC mobile phone
BRAND NAME : VERTU
MODEL NAME : CONSTELLATION X
TYPE NAME : VM-08
FCC ID : P7QVM-08
STANDARD : FCC 47 CFR Part 2, 22(H), 24(E), 27(L)
CLASSIFICATION : PCS Licensed Transmitter Held to Ear (PCE)

The product was received on Jul. 20, 2016 and testing was completed on Dec. 20, 2016. We, SPORTON INTERNATIONAL (KUNSHAN) INC., would like to declare that the tested sample has been evaluated in accordance with the test procedures given in ANSI / TIA / EIA-603-D-2010 and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL (KUNSHAN) INC., the test report shall not be reproduced except in full.



Prepared by: James Huang / Manager



Approved by: Jones Tsai / Manager



SPORTON INTERNATIONAL (KUNSHAN) INC.
No. 3-2, PingXiang Road, Kunshan, Jiangsu Province, P. R. China



TABLE OF CONTENTS

REVISION HISTORY.....	3
SUMMARY OF TEST RESULT	4
1 GENERAL DESCRIPTION	5
1.1 Applicant.....	5
1.2 Manufacturer	5
1.3 Product Feature of Equipment Under Test	5
1.4 Product Specification of Equipment Under Test	6
1.5 Modification of EUT	7
1.6 Maximum ERP/EIRP Power, Frequency Tolerance, and Emission Designator	7
1.7 Testing Location	8
1.8 Applicable Standards	8
1.9 Specification of Accessory	9
2 TEST CONFIGURATION OF EQUIPMENT UNDER TEST	10
2.1 Test Mode.....	10
2.2 Connection Diagram of Test System	11
2.3 Support Unit used in test configuration	12
2.4 Measurement Results Explanation Example	12
3 CONDUCTED TEST RESULT.....	13
3.1 Measuring Instruments.....	13
3.2 Test Setup	13
3.3 Test Result of Conducted Test.....	13
3.4 Conducted Output Power and ERP/EIRP	14
3.5 Peak-to-Average Ratio	15
3.6 99% Occupied Bandwidth and 26dB Bandwidth Measurement.....	16
3.7 Conducted Band Edge	17
3.8 Conducted Spurious Emission	18
3.9 Frequency Stability	19
4 RADIATED TEST ITEMS	20
4.1 Measuring Instruments.....	20
4.2 Test Setup	20
4.3 Test Result of Radiated Test.....	20
4.4 Field Strength of Spurious Radiation Measurement	21
5 LIST OF MEASURING EQUIPMENT	22
6 UNCERTAINTY OF EVALUATION	23
APPENDIX A. TEST RESULTS OF CONDUCTED TEST	
APPENDIX B. TEST RESULTS OF RADIATED TEST	
APPENDIX C. TEST SETUP PHOTOGRAPHS	



REVISION HISTORY

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FG672003A	Rev. 01	Initial issue of report	Feb. 17, 2017

SUMMARY OF TEST RESULT

Report Section	FCC Rule	Description	Limit	Result	Remark
3.4	§2.1046	Conducted Output Power	Reporting Only	PASS	-
	§22.913(a)(2)	Effective Radiated Power	< 7 Watts	PASS	-
	§24.232(c)	Equivalent Isotropic Radiated Power	< 2 Watts	PASS	-
	§27.50(d)(4)	Equivalent Isotropic Radiated Power	< 1 Watts	PASS	-
3.5	§24.232(d)	Peak-to-Average Ratio	< 13 dB	PASS	-
3.6	§2.1049 §22.917(b) §24.238(b) §27.53(g)	Occupied Bandwidth	Reporting Only	PASS	-
3.7	§2.1051 §22.917(a) §24.238(a) §27.53(h)	Band Edge Measurement	< 43+10log10(P[Watts])	PASS	-
3.8	§2.1051 §22.917(a) §24.238(a) §27.53(h)	Conducted Emission	< 43+10log10(P[Watts])	PASS	-
3.9	§2.1055 §22.355	Frequency Stability for Temperature & Voltage	< 2.5 ppm for Part 22	PASS	-
	§2.1055 §24.235 §27.54		Within Authorized Band		
4.4	§2.1053 §22.917(a) §24.238(a) §27.53(h)	Field Strength of Spurious Radiation	< 43+10log10(P[Watts])	PASS	Under limit 23.61 dB at 1648.000 MHz



1 General Description

1.1 Applicant

VERTU Corporation Limited

Beacon Hill Road, Church Crookham, Hampshire GU52 8DY, United Kingdom.

1.2 Manufacturer

VERTU Corporation Limited

Beacon Hill Road, Church Crookham, Hampshire GU52 8DY, United Kingdom.

1.3 Product Feature of Equipment Under Test

Product Feature	
Equipment	GSM 4 Band/CDMA/EVDO 2 Band/TD-SCDMA 2 Band/UMTS 5 Band/HSUPA/HSDPA/LTE 21 Band/WLAN/BT/NFC mobile phone
Brand Name	VERTU
Model Name	CONSTELLATION X
Type Name	VM-08
FCC ID	P7QVM-08
GSM Operating Band(s)	GSM 850/900/1800/1900MHz
WCDMA Operating Band(s)	FDD Band I / II / IV / V /VIII
CDMA Operating Band(s)	CDMA2000 BC0/BC1
LTE Operating Band(s)	FDD Band 1/2/3/4/5/7/8/12/13/17/19/20/25/26/28/29/30 TDD Band 38/39/40/41
GPRS / EGPRS Multi Slot Class	GPRS Class 33, EGPRS Class 33
Wi-Fi Specification	2.4GHz 802.11b/g/n HT20 5GHz 802.11a/n HT20/HT40 5GHz 802.11ac VHT20/VHT40/VHT80
Bluetooth Version	Bluetooth v3.0 + EDR / Bluetooth v4.0 LE/ Bluetooth v4.2 LE
NFC Type	A, B, F, V
IMEI Code	Conducted : 004402550120756/004402550120764 Radiation : 004402550120533/004402550120541
HW Version	PIO2
SW Version	6.0.1_1.434.0.070
EUT Stage	Identical Prototype

Remark:

1. The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.
2. After pre-scan two SIM cards power, we found test result of the SIM1 was the worse, so we chose

dual SIM1 card to perform all tests

3. Manufacturer's declaration LTE band 40 disabled by software.

1.4 Product Specification of Equipment Under Test

Standards-related Product Specification	
Tx Frequency	GSM/GPRS/EDGE: 850: 824.2 MHz ~ 848.8 MHz 1900: 1850.2 MHz ~ 1909.8MHz WCDMA: Band V: 826.4 MHz ~ 846.6 MHz Band II: 1852.4 MHz ~ 1907.6 MHz Band IV: 1712.4 MHz ~ 1752.6 MHz CDMA2000: BC0: 824.70 MHz ~ 848.31 MHz BC1: 1851.25 MHz ~ 1908.75 MHz
Rx Frequency	GSM/GPRS/EDGE: 850: 869.2 MHz ~ 893.8 MHz 1900: 1930.2 MHz ~ 1989.8 MHz WCDMA: Band V: 871.4 MHz ~ 891.6 MHz Band II: 1932.4 MHz ~ 1987.6 MHz Band IV: 2112.4 MHz ~ 2152.6 MHz CDMA2000: BC0: 869.70 MHz ~ 893.31 MHz BC1: 1931.25 MHz ~ 1988.75 MHz
Maximum Output Power to Antenna	GSM/GPRS/EDGE: 850: 32.96 dBm 1900: 30.05 dBm WCDMA: Band V: 23.54 dBm Band II: 23.70 dBm Band IV: 23.68 dBm CDMA2000: BC0: 24.16 dBm BC1: 24.34 dBm
Antenna Type	PIFA Antenna
Antenna Gain	Cellular Band: 0.80 dBi PCS Band: -2.00 dBi AWS Band: -2.00 dBi
Type of Modulation	GSM: GMSK GPRS: GMSK EDGE: GMSK / 8PSK WCDMA : BPSK (Uplink) HSUPA : QPSK (Uplink) HSPA+ : 16QAM (uplink is not supported) DC-HSDPA : 64QAM



	CDMA2000 1xRTT: QPSK CDMA2000 1xEV-DO: QPSK/8PSK
--	---

1.5 Modification of EUT

No modifications are made to the EUT during all test items.

1.6 Maximum ERP/EIRP Power, Frequency Tolerance, and Emission Designator

FCC Rule	System	Type of Modulation	Maximum ERP/EIRP (W)	Frequency Tolerance (ppm)	Emission Designator
Part 22	GSM850 GSM	GMSK	1.4488	0.0096 ppm	242KGXW
Part 22	GSM850 EDGE class 8	8PSK	0.3926	0.0395 ppm	241KG7W
Part 22	WCDMA Band V RMC 12.2Kbps	BPSK	0.1656	0.0239 ppm	4M13F9W
Part 22	CDMA2000 BC0 1xRTT	QPSK	0.1910	0.0275 ppm	1M27F9W
Part 24	GSM1900 GSM	GMSK	0.6383	0.0191 ppm	242KGXW
Part 24	GSM1900 EDGE class 8	8PSK	0.2679	0.0218 ppm	246KG7W
Part 24	WCDMA Band II RMC 12.2Kbps	BPSK	0.1479	0.0064 ppm	4M14F9W
Part 24	CDMA2000 BC1 1xRTT	QPSK	0.1714	0.0128 ppm	1M27F9W
Part 27	WCDMA Band IV RMC 12.2Kbps	BPSK	0.1472	0.0139 ppm	4M13F9W

1.7 Testing Location

Test Site	SPORTON INTERNATIONAL (KUNSHAN) INC.		
Test Site Location	No. 3-2, PingXiang Road, Kunshan, Jiangsu Province, P. R. China TEL: +86-0512-5790-0158 FAX: +86-0512-5790-0958		
Test Site No.	Sporton Site No.		FCC Registration No.
	TH01-KS	03CH02-KS	418269

1.8 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- 47 CFR Part 2, 22(H), 24(E), 27(L)
- ANSI / TIA / EIA-603-D-2010
- FCC KDB 971168 D01 Power Meas. License Digital Systems v02r02
- FCC KDB 412172 D01 Determining ERP and EIRP v01r01

Remark:

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.

1.9 Specification of Accessory

Specification of Accessory			
AC Adapter	Brand Name	VERTU	Model Name
	Power Rating	I/P: 100-240Vac, 450mA, O/P: 5Vdc, 2000mA	
Battery	Brand Name	VERTU	Model Name
	Power Rating	3.82Vdc, 3200mAh	
USB Cable	Brand Name	VERTU	Model Name
	Signal Line Type	1.20m shielded cable, without ferrite core	
Earphone 1	Brand Name	VERTU	Model Name
	Signal Line Type	1.20m Unshielded cable, without ferrite core	
Earphone 2	Brand Name	VERTU	Model Name
	Signal Line Type	1.57m Unshielded cable, without ferrite core	
Earphone 3	Brand Name	VERTU	Model Name
	Signal Line Type	1.55m Unshielded cable, without ferrite core	
Wireless Charger Pad	Brand Name	VERTU	Model Name
	Power Rating	I/P: 5Vac, 1800mA	
Car Charger	Brand Name	VERTU	Model Name
	Power Rating	I/P: 12/24Vdc, 1.35A MAX, O/P: 5.15Vdc, 2.1AMAX	
Bluetooth Travel Speaker	Brand Name	VERTU	Model Name
	Power Rating	I/P: 5Vdc, 2Ah	
Portable Battery Charger	Brand Name	VERTU	Model Name
	Power Rating	I/P: 5Vdc, 2A, O/P: 5Vdc, 1.5/2.1A	

2 Test Configuration of Equipment Under Test

2.1 Test Mode

Antenna port conducted and radiated test items were performed according to KDB 971168 D01 Power Meas. License Digital Systems v02r02 with maximum output power.

Radiated measurements were performed with rotating EUT in different three orthogonal test planes to find the maximum emission.

Radiated emissions were investigated as following frequency range:

1. 30 MHz to 10th harmonic for GSM850 and WCDMA Band V and CDMA BC0.
2. 30 MHz to 10th harmonic for WCDMA Band IV.
3. 30 MHz to 10th harmonic for GSM1900 and WCDMA Band II and CDMA BC1.


All modes and data rates and positions were investigated.

Test modes are chosen to be reported as the worst case configuration below:


Test Modes		
Band	Radiated TCs	Conducted TCs
GSM 850	■ GSM Link ■ EDGE class 8 Link	■ GSM Link ■ EDGE class 8 Link
GSM 1900	■ GSM Link ■ EDGE class 8 Link	■ GSM Link ■ EDGE class 8 Link
WCDMA Band V	■ RMC 12.2Kbps Link	■ RMC 12.2Kbps Link
WCDMA Band II	■ RMC 12.2Kbps Link	■ RMC 12.2Kbps Link
WCDMA Band IV	■ RMC 12.2Kbps Link	■ RMC 12.2Kbps Link
CDMA BC0	■ 1xRTT Link	■ 1xRTT Link
CDMA BC1	■ 1xRTT Link	■ 1xRTT Link

2.2 Connection Diagram of Test System

For 22H (GSM/WCDMA)



For 22H (CDMA)/24E/27L



2.3 Support Unit used in test configuration

Item	Equipment	Trade Name	Model No.	FCC ID	Data Cable	Power Cord
1.	System Simulator	R&S	CMU 200	N/A	N/A	Unshielded, 1.8 m
2.	DC Power Supply	GW INSTEK	GPD-2303S	N/A	N/A	Unshielded, 1.8 m

2.4 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between RF conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level will be exactly the RF output level.

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

Offset = RF cable loss + attenuator factor.

The following shows an offset computation example with RF cable loss 4.5 dB and a 10dB attenuator.

Example :

$$\begin{aligned}\text{Offset(dB)} &= \text{RF cable loss(dB)} + \text{attenuator factor(dB)} \\ &= 4.5 + 10 = 14.5 \text{ (dB)}\end{aligned}$$


3 Conducted Test Result

3.1 Measuring Instruments


See list of measuring instruments of this test report.

3.2 Test Setup


3.2.1 Conducted Output Power



3.2.2 Peak-to-Average Ratio, Occupied Bandwidth, Conducted Band-Edge and Conducted Spurious Emission



3.2.3 Frequency Stability



3.3 Test Result of Conducted Test

Please refer to Appendix A.

3.4 Conducted Output Power and ERP/EIRP

3.4.1 Description of the Conducted Output Power and ERP/EIRP

A system simulator was used to establish communication with the EUT. Its parameters were set to enforce EUT transmitting at the maximum power. The measured power in the radio frequency on the transmitter output terminals shall be reported.

The ERP of mobile transmitters must not exceed 7 Watts for GSM850 and WCDMA Band V.

The EIRP of mobile transmitters must not exceed 2 Watts for GSM1900 and WCDMA Band II.

The EIRP of mobile transmitters must not exceed 1 Watts for WCDMA Band IV.

According to KDB 412172 D01 Power Approach,

$EIRP = P_T + G_T - L_C$, $ERP = EIRP - 2.15$, where

P_T = transmitter output power in dBm

G_T = gain of the transmitting antenna in dBi

L_C = signal attenuation in the connecting cable between the transmitter and antenna in dB

3.4.2 Test Procedures

1. The transmitter output port was connected to the system simulator.
2. Set EUT at maximum power through system simulator.
3. Select lowest, middle, and highest channels for each band and different modulation.
4. Measure the maximum burst average power for GSM and maximum average power for other modulation signal.



3.5 Peak-to-Average Ratio

3.5.1 Description of the PAR Measurement

The peak-to-average ratio (PAR) of the transmission may not exceed 13 dB.

3.5.2 Test Procedures

1. The testing follows FCC KDB 971168 D01 v02r02 Section 5.7.1.
2. The EUT was connected to spectrum analyzer and system simulator via a power divider.
3. Set EUT to transmit at maximum output power.
4. When the duty cycle is less than 98%, then signal gating will be implemented on the spectrum analyzer by triggering from the system simulator.
5. Set the CCDF (Complementary Cumulative Distribution Function) option of the spectrum analyzer.
Record the maximum PAPR level associated with a probability of 0.1%.

3.6 99% Occupied Bandwidth and 26dB Bandwidth Measurement

3.6.1 Description of 99% Occupied Bandwidth and 26dB Bandwidth Measurement

The occupied bandwidth is the width of a frequency band such that, below the lower and above the upper frequency limits, the mean powers emitted are each equal to a specified percentage 0.5% of the total mean transmitted power.

The 26 dB emission bandwidth is defined as the frequency range between two points, one above and one below the carrier frequency, at which the spectral density of the emission is attenuated 26 dB below the maximum in-band spectral density of the modulated signal. Spectral density (power per unit bandwidth) is to be measured with a detector of resolution bandwidth equal to approximately 1.0% of the emission bandwidth.

3.6.2 Test Procedures

1. The testing follows FCC KDB 971168 v02r02 Section 4.2.
2. The EUT was connected to spectrum analyzer and system simulator via a power divider.
3. The spectrum analyzer center frequency is set to the nominal EUT channel center frequency. The span range for the spectrum analyzer shall be between two and five times the anticipated OBW.
4. The nominal resolution bandwidth (RBW) shall be in the range of 1 to 5 % of the anticipated OBW, and the VBW shall be at least 3 times the RBW.
5. Set the detection mode to peak, and the trace mode to max hold.
6. Determine the reference value: Set the EUT to transmit a modulated signal. Allow the trace to stabilize. Set the spectrum analyzer marker to the highest level of the displayed trace.
(this is the reference value)
7. Determine the “-26 dB down amplitude” as equal to (Reference Value – X).
8. Place two markers, one at the lowest and the other at the highest frequency of the envelope of the spectral display such that each marker is at or slightly below the “-X dB down amplitude” determined in step 6. If a marker is below this “-X dB down amplitude” value it shall be placed as close as possible to this value. The OBW is the positive frequency difference between the two markers.
9. Use the 99 % power bandwidth function of the spectrum analyzer and report the measured bandwidth.

3.7 Conducted Band Edge

3.7.1 Description of Conducted Band Edge Measurement

The power of any emission outside of the authorized operating frequency ranges must be lower than the transmitter power (P) by a factor of at least $43 + 10 \log (P)$ dB.

3.7.2 Test Procedures

1. The testing follows FCC KDB 971168 D01 v02r02 Section 6.0.
2. The EUT was connected to the spectrum analyzer and system simulator via a power divider.
3. The RF output of EUT was connected to the spectrum analyzer by an RF cable and attenuator.
The path loss was compensated to the results for each measurement.
4. The band edges of low and high channels for the highest RF powers were measured.
5. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
6. The limit line is derived from $43 + 10\log(P)$ dB below the transmitter power P(Watts)
 $= P(W) - [43 + 10\log(P)]$ (dB)
 $= [30 + 10\log(P)]$ (dBm) - $[43 + 10\log(P)]$ (dB)
 $= -13\text{dBm}$.

3.8 Conducted Spurious Emission

3.8.1 Description of Conducted Spurious Emission Measurement

The power of any emission outside of the authorized operating frequency ranges must be lower than the transmitter power (P) by a factor of at least $43 + 10 \log (P)$ dB.

It is measured by means of a calibrated spectrum analyzer and scanned from 30 MHz up to a frequency including its 10th harmonic.

3.8.2 Test Procedures

1. The testing follows FCC KDB 971168 D01 v02r02 Section 6.0.
2. The EUT was connected to the spectrum analyzer and system simulator via a power divider.
3. The RF output of EUT was connected to the spectrum analyzer by an RF cable and attenuator. The path loss was compensated to the results for each measurement.
4. The middle channel for the highest RF power within the transmitting frequency was measured.
5. The conducted spurious emission for the whole frequency range was taken.
6. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
7. The limit line is derived from $43 + 10\log(P)$ dB below the transmitter power P(Watts)
= $P(W) - [43 + 10\log(P)]$ (dB)
= $[30 + 10\log(P)]$ (dBm) - $[43 + 10\log(P)]$ (dB)
= -13dBm.

3.9 Frequency Stability

3.9.1 Description of Frequency Stability Measurement

The frequency stability shall be measured by variation of ambient temperature and variation of primary supply voltage to ensure that the fundamental emission stays within the authorized frequency block. The frequency stability of the transmitter shall be maintained within $\pm 0.00025\%$ ($\pm 2.5\text{ppm}$) of the center frequency.

3.9.2 Test Procedures for Temperature Variation

1. The testing follows FCC KDB 971168 D01 v02r02 Section 9.0.
2. The EUT was set up in the thermal chamber and connected with the system simulator.
3. With power OFF, the temperature was decreased to -30°C and the EUT was stabilized before testing. Power was applied and the maximum change in frequency was recorded within one minute.
4. With power OFF, the temperature was raised in 10°C steps up to 50°C . The EUT was stabilized at each step for at least half an hour. Power was applied and the maximum frequency change was recorded within one minute.

3.9.3 Test Procedures for Voltage Variation

1. The testing follows FCC KDB 971168 D01 v02r02 Section 9.0.
2. The EUT was placed in a temperature chamber at $20\pm 5^{\circ}\text{C}$ and connected with the system simulator.
3. The power supply voltage to the EUT was varied from 85% to 115% of the nominal value measured at the input to the EUT.
4. The variation in frequency was measured for the worst case.


4 Radiated Test Items

4.1 Measuring Instruments


See list of measuring instruments of this test report.

4.2 Test Setup

4.2.1 For radiated test from 30MHz to 1GHz



4.2.2 For radiated test above 1GHz



4.3 Test Result of Radiated Test

Please refer to Appendix B.

4.4 Field Strength of Spurious Radiation Measurement

4.4.1 Description of Field Strength of Spurious Radiated Measurement

The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitter power (P) by a factor of at least $43 + 10 \log (P)$ dB. The spectrum is scanned from 30 MHz up to a frequency including its 10th harmonic.

4.4.2 Test Procedures

1. The testing follows FCC KDB 971168 D01 v02r02 Section 5.8 and ANSI / TIA-603-D-2010 Section 2.2.12.
2. The EUT was placed on a rotatable wooden table 0.8 meters for frequency below 1GHz and 1.5 meter for frequency above 1GHz above the ground.
3. The EUT was set 3 meters from the receiving antenna, which was mounted on the antenna tower.
4. The table was rotated 360 degrees to determine the position of the highest spurious emission.
5. The height of the receiving antenna is varied between one meter and four meters to search for the maximum spurious emission for both horizontal and vertical polarizations.
6. Make the measurement with the spectrum analyzer's RBW = 1MHz, VBW = 3MHz, taking record of maximum spurious emission.
7. A horn antenna was substituted in place of the EUT and was driven by a signal generator.
8. Tune the output power of signal generator to the same emission level with EUT maximum spurious emission.
9. Taking the record of output power at antenna port.
10. Repeat step 7 to step 8 for another polarization.
11. $EIRP \text{ (dBm)} = S.G. \text{ Power} - Tx \text{ Cable Loss} + Tx \text{ Antenna Gain}$
12. $ERP \text{ (dBm)} = EIRP - 2.15$
13. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
14. The limit line is derived from $43 + 10\log(P)$ dB below the transmitter power P(Watts)
 $= P(W) - [43 + 10\log(P)] \text{ (dB)}$
 $= [30 + 10\log(P)] \text{ (dBm)} - [43 + 10\log(P)] \text{ (dB)}$
 $= -13\text{dBm}.$



5 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Spectrum Analyzer	R&S	FSV40	101040	10Hz~40GHz	Aug. 09, 2016	Dec. 05, 2016~ Dec. 12, 2016	Aug. 08, 2017	Conducted (TH01-KS)
Thermal Chamber	Ten Billion	TTC-B3S	TBN-960502	-40~+150°C	Oct. 13, 2016	Dec. 05, 2016~ Dec. 12, 2016	Oct. 12, 2017	Conducted (TH01-KS)
EXA Spectrum Analyzer	Keysight	N9010A	MY55150208	10Hz~44GHz, MAX 30dB	Apr. 22, 2016	Dec. 11, 2016~ Dec. 20, 2016	Apr. 21, 2017	Radiation (03CH02-KS)
Bilog Antenna	TeseQ	CBL6112D	37879	30MHz~2GHz	Aug. 20, 2016	Dec. 11, 2016~ Dec. 20, 2016	Aug. 19, 2017	Radiation (03CH02-KS)
Double Ridge Horn Antenna	ETS-Lindgren	3117	75957	1GHz~18GHz	Oct. 22, 2016	Dec. 11, 2016~ Dec. 20, 2016	Oct. 21, 2017	Radiation (03CH02-KS)
SHF-EHF Horn	Schwarzbeck	BBHA 9170	BBHA170249	15GHz~40GHz	Mar. 03, 2016	Dec. 11, 2016~ Dec. 20, 2016	Mar. 02, 2017	Radiation (03CH02-KS)
Amplifier	com-power	PA-103A	161069	1kHz~1000MHz / 32 dB	Apr. 22, 2016	Dec. 11, 2016~ Dec. 20, 2016	Apr. 21, 2017	Radiation (03CH02-KS)
Amplifier	Agilent	8449B	3008A02384	1~26.5GHz Gain 30dB	Oct. 13, 2016	Dec. 11, 2016~ Dec. 20, 2016	Oct. 12, 2017	Radiation (03CH02-KS)
AC Power Source	Chroma	61601	61601000247 3	N/A	NCR	Dec. 11, 2016~ Dec. 20, 2016	NCR	Radiation (03CH02-KS)
Turn Table	MF	MF7802	N/A	0~360 degree	NCR	Dec. 11, 2016~ Dec. 20, 2016	NCR	Radiation (03CH02-KS)
Antenna Mast	MF	MF7802	N/A	1 m~4 m	NCR	Dec. 11, 2016~ Dec. 20, 2016	NCR	Radiation (03CH02-KS)
RF Cable	Rosnol	KIK50	K1K50-7.5M- 001	30MHz~40GHz	Jun. 22, 2016	Dec. 11, 2016~ Dec. 20, 2016	Jun. 21, 2017	Radiation (03CH02-KS)
RF Cable	Rosnol	KIK50	K1K50-4M-00 2	30MHz~40GHz	Jun. 22, 2016	Dec. 11, 2016~ Dec. 20, 2016	Jun. 21, 2017	Radiation (03CH02-KS)
High Pass Filter	Wainwright Instruments	WHKX12-28 05-3000-18	2	3G High Pass	Jun. 22, 2016	Dec. 11, 2016~ Dec. 20, 2016	Jun. 21, 2017	Radiation (03CH02-KS)

NCR: No Calibration Required

6 Uncertainty of Evaluation

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	5.1dB
---	-------

Uncertainty of Radiated Emission Measurement (1 GHz ~ 18 GHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	4.5dB
---	-------

Uncertainty of Radiated Emission Measurement (18 GHz ~ 40 GHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	5.1dB
---	-------

Appendix A. Test Results of Conducted Test

Conducted Output Power(Average power)

Conducted Power (*Unit: dBm)						
Band	GSM850			GSM1900		
Channel	128	189	251	512	661	810
Frequency	824.2	836.4	848.8	1850.2	1880.0	1909.8
GSM	32.81	32.92	32.96	29.56	29.99	30.05
GPRS class 8	32.80	32.90	32.94	29.56	29.98	30.04
GPRS class 10	31.49	31.43	31.44	28.52	28.72	28.82
GPRS class 11	30.30	30.33	30.30	27.32	27.56	27.67
GPRS class 12	29.00	28.86	28.88	26.19	26.24	26.25
EGPRS class 8	27.29	27.22	27.23	26.01	26.20	26.28
EGPRS class 10	27.06	27.10	27.04	26.00	26.01	26.05
EGPRS class 11	26.99	26.91	26.93	25.85	26.07	26.02
EGPRS class 12	26.89	26.70	26.62	25.78	25.65	25.80

Conducted Power (*Unit: dBm)									
Band	WCDMA Band V			WCDMA Band II			WCDMA Band IV		
Channel	4132	4182	4233	9262	9400	9538	1312	1413	1513
Frequency	826.4	836.4	846.6	1852.4	1880	1907.6	1712.4	1732.6	1752.6
AMR 12.2K	23.53	23.38	23.48	23.52	23.69	23.68	23.57	23.67	23.60
RMC 12.2K	23.54	23.39	23.49	23.54	23.70	23.69	23.57	23.68	23.63
HSDPA Subtest-1	22.50	22.32	22.45	22.54	22.67	22.70	22.55	22.71	22.59
HSDPA Subtest-2	22.49	22.06	22.50	22.51	22.69	22.67	22.53	22.69	22.62
HSDPA Subtest-3	22.07	21.89	22.02	22.01	22.18	22.24	22.08	22.18	22.15
HSDPA Subtest-4	22.05	21.88	21.99	22.04	22.22	22.19	22.08	22.27	22.14
DC-HSDPA Subtest-1	22.34	22.15	22.23	22.34	22.42	22.40	22.29	22.43	22.35
DC-HSDPA Subtest-2	22.35	22.09	22.22	22.33	22.43	22.41	22.31	22.42	22.35
DC-HSDPA Subtest-3	21.90	21.63	21.75	21.89	21.92	21.89	21.83	21.95	21.86
DC-HSDPA Subtest-4	21.88	21.60	21.74	21.85	21.90	21.91	21.80	21.92	21.88
HSUPA Subtest-1	22.53	22.39	22.48	22.53	22.64	22.68	22.55	22.70	22.58
HSUPA Subtest-2	20.55	20.38	20.49	20.56	20.72	20.69	20.57	20.68	20.59
HSUPA Subtest-3	21.56	21.29	21.48	21.51	21.75	21.65	21.54	21.70	21.63
HSUPA Subtest-4	20.55	20.34	20.50	20.53	20.72	20.68	20.58	20.68	20.60
HSUPA Subtest-5	22.60	22.40	22.50	22.50	22.60	22.70	22.60	22.70	22.60



Conducted Power (*Unit: dBm)						
Band	CDMA 2000 BC0			CDMA 2000 BC1		
Channel	1013	384	777	25	600	1175
Frequency	824.7	836.52	848.31	1851.25	1880	1908.75
1xRTT RC1 SO55	24.01	23.96	24.16	24.06	24.11	24.34
1xRTT RC3 SO55	24.07	24.01	24.11	23.81	23.88	24.09
1xRTT RC3 SO32 (+ F-SCH)	24.01	24.04	24.05	23.81	23.89	24.11
1xRTT RC3 SO32 (+SCH)	24.09	24.02	24.15	23.81	23.88	24.10
1xEVDO RTAP 153.6Kbps	24.10	24.03	24.13	23.82	23.89	24.10
1xEVDO RETAP 4096Bits	23.84	23.87	23.89	23.65	23.71	23.92

**ERP/EIRP**

GSM850 (GT – LC: 0.80)			
Channel	128	189	251
	(Low)	(Mid)	(High)
Frequency	824.2	836.4	848.8
(MHz)			
Conducted Power (dBm)	32.81	32.92	32.96
Conducted Power (Watts)	1.9099	1.9588	1.9770
ERP(dBm)	31.46	31.57	31.61
ERP(Watts)	1.3996	1.4355	1.4488

EDGE850 (GT – LC: 0.80)			
Channel	128	189	251
	(Low)	(Mid)	(High)
Frequency	824.2	836.4	848.8
(MHz)			
Conducted Power (dBm)	27.29	27.22	27.23
Conducted Power (Watts)	0.5358	0.5272	0.5284
ERP(dBm)	25.94	25.87	25.88
ERP(Watts)	0.3926	0.3864	0.3873



GSM1900 (GT – LC: -2.00)			
Channel	512	661	810
	(Low)	(Mid)	(High)
Frequency	1850.2	1880	1909.8
(MHz)			
Conducted Power (dBm)	29.56	29.99	30.05
Conducted Power (Watts)	0.9036	0.9977	1.0116
EIRP(dBm)	27.56	27.99	28.05
EIRP(Watts)	0.5702	0.6295	0.6383

EDGE1900 (GT – LC: -2.00)			
Channel	512	661	810
	(Low)	(Mid)	(High)
Frequency	1850.2	1880	1909.8
(MHz)			
Conducted Power (dBm)	26.01	26.20	26.28
Conducted Power (Watts)	0.3990	0.4169	0.4246
EIRP(dBm)	24.01	24.20	24.28
EIRP(Watts)	0.2518	0.2630	0.2679

WCDMA Band V (GT – LC: 0.80)			
Channel	4132	4182	4233
	(Low)	(Mid)	(High)
Frequency	826.4	836.4	846.6
(MHz)			
Conducted Power (dBm)	23.54	23.39	23.49
Conducted Power (Watts)	0.2259	0.2183	0.2234
ERP(dBm)	22.19	22.04	22.14
ERP(Watts)	0.1656	0.1600	0.1637

WCDMA Band II (GT – LC: -2.00)			
Channel	9262	9400	9538
	(Low)	(Mid)	(High)
Frequency	1852.4	1880	1907.6
(MHz)			
Conducted Power (dBm)	23.54	23.70	23.69
Conducted Power (Watts)	0.2259	0.2344	0.2339
EIRP(dBm)	21.54	21.70	21.69
EIRP(Watts)	0.1426	0.1479	0.1476

WCDMA Band IV (GT – LC: -2.00)			
Channel	9262	9400`	9538
	(Low)	(Mid)	(High)
Frequency	1852.4	1880	1907.6
(MHz)			
Conducted Power (dBm)	23.57	23.68	23.63
Conducted Power (Watts)	0.2275	0.2333	0.2307
EIRP(dBm)	21.57	21.68	21.63
EIRP(Watts)	0.1435	0.1472	0.1455



CDMA2000 BC0 (GT – LC: 0.80)			
Channel	1013	384	777
	(Low)	(Mid)	(High)
Frequency	824.7	836.52	848.31
(MHz)			
Conducted Power (dBm)	24.01	23.96	24.16
Conducted Power (Watts)	0.2518	0.2489	0.2606
EIRP(dBm)	22.66	22.61	22.81
EIRP(Watts)	0.1845	0.1824	0.1910

CDMA2000 BC1 (GT – LC: -2.00)			
Channel	25	600	1175
	(Low)	(Mid)	(High)
Frequency	1851.25	1880	1908.75
(MHz)			
Conducted Power (dBm)	24.06	24.11	24.34
Conducted Power (Watts)	0.2547	0.2576	0.2716
EIRP(dBm)	22.06	22.11	22.34
EIRP(Watts)	0.1607	0.1626	0.1714

Peak-to-Average Ratio

Mode	GSM850(dB)		Limit: 13dB
Mod.	GSM	EDGE class 8	Result
Lowest CH	0.17	3.54	PASS
Middle CH	0.20	3.51	
Highest CH	0.17	3.48	

Mode	GSM1900(dB)		Limit: 13dB
Mod.	GSM	EDGE class 8	Result
Lowest CH	0.14	3.48	PASS
Middle CH	0.20	3.33	
Highest CH	0.23	3.33	


Mode	WCDMA Band V(dB)	WCDMA Band II(dB)	WCDMA Band IV(dB)	Limit: 13dB
Mod.	RMC 12.2Kbps	RMC 12.2Kbps	RMC 12.2Kbps	Result
Lowest CH	3.45	3.30	2.84	PASS
Middle CH	3.42	3.30	3.30	
Highest CH	3.33	3.30	3.19	

Mode	CDMA BC0(dB)	CDMA BC1(dB)	Limit: 13dB
Mod.	RC1 SO55	RC1 SO55	Result
Lowest CH	3.74	3.48	PASS
Middle CH	3.59	3.54	
Highest CH	3.25	3.42	



GSM850 (GSM)


Lowest Channel



Date: 5 DEC 2016 21:48:51


GSM850 (EDGE class 8)

Lowest Channel



Date: 5 DEC 2016 22:08:13

Middle Channel




Date: 5 DEC 2016 21:49:03

Middle Channel




Date: 5 DEC 2016 22:08:27

Highest Channel



Date: 5 DEC 2016 21:49:18

Highest Channel




Date: 5 DEC 2016 22:08:40



GSM1900 (GSM)

Lowest Channel



Date: 5 DEC 2016 23:43:16


GSM1900 (EDGE class 8)

Lowest Channel



Date: 6 DEC 2016 00:10:03

Middle Channel




Date: 5 DEC 2016 23:43:28

Middle Channel



Date: 6 DEC 2016 00:10:19

Highest Channel



Date: 5 DEC 2016 23:43:39

Highest Channel




Date: 6 DEC 2016 00:10:32



WCDMA Band V (RMC 12.2Kbps)


Lowest Channel



Date: 5 DEC 2016 22:29:05

WCDMA Band II (RMC 12.2Kbps)

Lowest Channel



Date: 5 DEC 2016 22:55:03

Middle Channel



Date: 5 DEC 2016 22:29:18

Middle Channel



Date: 5 DEC 2016 22:55:15

Highest Channel



Date: 5 DEC 2016 22:29:30

Highest Channel




Date: 5 DEC 2016 22:55:27




WCDMA Band IV (RMC 12.2Kbps)


Lowest Channel




Middle Channel



Highest Channel





26dB Bandwidth

Mode	GSM850(MHz)	
Mod.	GSM	EDGE class 8
Lowest CH	0.312	0.306
Middle CH	0.316	0.311
Highest CH	0.315	0.311

Mode	GSM1900(MHz)	
Mod.	GSM	EDGE class 8
Lowest CH	0.314	0.316
Middle CH	0.313	0.312
Highest CH	0.314	0.312


Mode	WCDMA Band V(MHz)	WCDMA Band II(MHz)	WCDMA Band IV(MHz)
Mod.	RMC 12.2Kbps	RMC 12.2Kbps	RMC 12.2Kbps
Lowest CH	4.70	4.72	4.72
Middle CH	4.70	4.72	4.71
Highest CH	4.69	4.71	4.71

Mode	CDMA BC0(MHz)	CDMA BC1(MHz)
Mod.	RC1 SO55	RC1 SO55
Lowest CH	1.43	1.43
Middle CH	1.43	1.43
Highest CH	1.44	1.44



GSM850 (GSM)


Lowest Channel



Date: 5 DEC 2016 21:31:35


GSM850 (EDGE class 8)

Lowest Channel




Date: 5 DEC 2016 21:52:22

Middle Channel




Date: 5 DEC 2016 21:29:52

Middle Channel




Date: 5 DEC 2016 21:52:56

Highest Channel



Date: 5 DEC 2016 21:30:32

Highest Channel



Date: 5 DEC 2016 21:54:33



GSM1900 (GSM)


Lowest Channel



Date: 5 DEC 2016 23:18:31


GSM1900 (EDGE class 8)

Lowest Channel




Date: 5 DEC 2016 23:45:13

Middle Channel




Date: 5 DEC 2016 23:19:04

Middle Channel




Date: 5 DEC 2016 23:47:16

Highest Channel



Date: 5 DEC 2016 23:19:43

Highest Channel




Date: 5 DEC 2016 23:46:38



WCDMA Band V (RMC 12.2Kbps)


Lowest Channel



Date: 5 DEC 2016 22:11:20


WCDMA Band II (RMC 12.2Kbps)

Lowest Channel




Date: 5 DEC 2016 22:31:11

Middle Channel




Date: 5 DEC 2016 22:11:54

Middle Channel




Date: 5 DEC 2016 22:31:45

Highest Channel



Date: 5 DEC 2016 22:12:33

Highest Channel




Date: 5 DEC 2016 22:32:21




WCDMA Band IV (RMC 12.2Kbps)


Lowest Channel



Middle Channel




Highest Channel





CDMA BC0 (RC1 SO55)


Lowest Channel



Date: 12 DEC 2016 13:19:15


CDMA BC1 (RC1 SO55)

Lowest Channel




Date: 12 DEC 2016 14:23:59

Middle Channel




Date: 12 DEC 2016 13:20:33

Middle Channel




Date: 12 DEC 2016 14:24:32

Highest Channel



Date: 12 DEC 2016 13:21:08

Highest Channel



Date: 12 DEC 2016 14:25:07

Occupied Bandwidth

Mode	GSM850(MHz)	
Mod.	GSM	EDGE class 8
Lowest CH	0.242	0.241
Middle CH	0.242	0.237
Highest CH	0.242	0.238

Mode	GSM1900(MHz)	
Mod.	GSM	EDGE class 8
Lowest CH	0.242	0.246
Middle CH	0.242	0.243
Highest CH	0.242	0.243


Mode	WCDMA Band V(MHz)	WCDMA Band II(MHz)	WCDMA Band IV(MHz)
Mod.	RMC 12.2Kbps	RMC 12.2Kbps	RMC 12.2Kbps
Lowest CH	4.12	4.14	4.12
Middle CH	4.12	4.14	4.13
Highest CH	4.13	4.14	4.13

Mode	CDMA BC0(MHz)	CDMA BC1(MHz)
Mod.	RC1 SO55	RC1 SO55
Lowest CH	1.27	1.27
Middle CH	1.27	1.27
Highest CH	1.27	1.27




GSM850 (GSM)

Lowest Channel




GSM850 (EDGE class 8)


Lowest Channel




Middle Channel




Middle Channel



Highest Channel




Highest Channel






GSM1900 (GSM)

Lowest Channel



GSM1900 (EDGE class 8)


Lowest Channel




Middle Channel




Middle Channel



Highest Channel




Highest Channel





WCDMA Band V (RMC 12.2Kbps)


Lowest Channel



Date: 5 DEC 2016 22:15:55


WCDMA Band II (RMC 12.2Kbps)

Lowest Channel




Date: 5 DEC 2016 22:37:01

Middle Channel




Date: 5 DEC 2016 22:16:30

Middle Channel




Date: 5 DEC 2016 22:37:47

Highest Channel



Date: 5 DEC 2016 22:17:10

Highest Channel




Date: 5 DEC 2016 22:38:25




WCDMA Band IV (RMC 12.2Kbps)

Lowest Channel



Middle Channel



Highest Channel

