

# RF Exposure Evaluation Report

## 1 RF EXPOSURE

Product Name	Wireless Rechargeable Silent Mouse
Model No.	TK-MS001
Test Mode	TX
FCC ID	2AK8Q-TKMS001

## 1.1 LIMITS

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances  $\leq 50$  mm are determined by:

$$\left[ \frac{\text{[(max. power of channel, including tune-up tolerance, mW)]}}{\text{[(min. test separation distance, mm)]}} \cdot \sqrt{f(\text{GHz})} \right] \leq 3.0 \text{ for 1-g SAR and } \leq 7.5 \text{ for 10-g extremity SAR, where}$$

$f(\text{GHz})$  is the RF channel transmit frequency in GHz

Power and distance are rounded to the nearest mW and mm before calculation<sup>17</sup>

The result is rounded to one decimal place for comparison

The test exclusions are applicable only when the minimum test separation distance is  $\leq 50$  mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is  $< 5$  mm, a distance of 5 mm is applied to determine SAR test exclusion

## 1.2 EUT RF EXPOSURE EVALUATION

Operational Mode: BLE						
Channel	Maximum Peak Conducted Output Power (dBm)	Tune up tolerance (dB)	Maximum tune-up Power (dBm)	Maximum tune-up Power (mW)	Calculated value	Exclusion threshold
2402MHz	2.7	±1	3.7	2.34	0.73	3
2442MHz	2.73	±1	3.73	2.36	0.74	3
2480MHz	2.56	±1	3.56	2.27	0.71	3
Conclusion: the calculated value ≤3.0, SAR is exempted.						