



## Shenzhen Asia Test Technology Co., Ltd.

7 / F, Xinwei Building, Gushu Village, Xixiang Town, Baoan District, Shenzhen, China  
Tel: +86)-0755-23284990 Email: [att@att-lab.com](mailto:att@att-lab.com) Http: // [www.att-lab.cn](http://www.att-lab.cn)

# FCC RADIO TEST REPORT

## FCC ID: 2AMJYTC-X4DB-A

**Product :** Smart Video Door Phone

**Trade Name :** N/A

**Model Name :** TC-X4DB-A

**Serial Model :** TC-X6KT-DB, TC-X4DB-B, TC-X4DB-C,  
TC-X4DB-D, TC-X4DB-E, TC-X4DB-F

### Prepared for

Zhuhai Taichuan Cloud Technology Co., Ltd  
Bldg1 Taichuan Technopark No. 611 Huawei Road Qianshan Xiangzhou  
519075 Zhuhai Guangdong China

### Prepared by

Shenzhen Asia Test Technology Co.,Ltd.  
7 / F, Xinwei Building, Gushu Village, Xixiang Town, Baoan District,  
Shenzhen, China  
Tel: +(86)-0755-23284990 Fax: +(86)-0755-23284990  
Http: [www.att-lab.cn](http://www.att-lab.cn)



# Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT2017SZ0510132F2  
- Page 2 of 76 -

## TEST RESULT CERTIFICATION

**Manufacture's Name...** Zhuhai Taichuan Cloud Technology Co., Ltd

**Address .....** Bldg1 Taichuan Technopark No. 611 Huawei Road Qianshan Xiangzhou  
519075 Zhuhai Guangdong China

### Product description

**Product name .....** Smart Video Door Phone

**Model and/or type reference .....** TC-X4DB-A

**Additional Model .....** TC-X6KT-DB, TC-X4DB-B, TC-X4DB-C, TC-X4DB-D, TC-X4DB-E,  
TC-X4DB-F

**Standards .....** FCC Part15.247

**Test procedure .....** ANSI C63.10-2013

This device described above has been tested by ATT, and the test results show that the equipment under test (EUT) is in compliance with the FCC requirements. And it is applicable only to the tested sample identified in the report.

This report shall not be reproduced except in full, without the written approval of ATT, this document may be altered or revised by ATT, personal only, and shall be noted in the revision of the document.

**Date of Test .....**

**Date (s) of performance of tests .....** Jun. 01 2017 ~Jun. 12 2017

**Date of Issue.....** Jun. 12 2017

**Test Result.....** **Pass**

Testing Engineer :

*Jack Yu*

(Jack Yu)

Technical Manager :

*Jerry You*

(Jerry You)

Authorized Signatory :

*Can Liu*

(Can Liu)

This document cannot be reproduced except in full, without prior written approval of ATT. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.



# Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT2017SZ0510132F2  
- Page 3 of 76 -

Table of Contents	Page
<b>1 . SUMMARY OF TEST RESULTS</b>	<b>5</b>
1.1 TEST FACILITY	7
1.2 MEASUREMENT UNCERTAINTY	7
<b>2 . GENERAL INFORMATION</b>	<b>8</b>
2.1 GENERAL DESCRIPTION OF EUT	8
2.2 DESCRIPTION OF TEST MODES	9
2.3 BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED	11
2.4 DESCRIPTION OF SUPPORT UNITS(CONDUCTED MODE)	11
2.5 EQUIPMENTS LIST FOR ALL TEST ITEMS	13
<b>3 . EMC EMISSION TEST</b>	<b>15</b>
3.1 CONDUCTED EMISSION MEASUREMENT	15
3.1.1 POWER LINE CONDUCTED EMISSION LIMITS	15
3.1.2 TEST PROCEDURE	16
3.1.3 DEVIATION FROM TEST STANDARD	16
3.1.4 TEST SETUP	16
3.1.5 EUT OPERATING CONDITIONS	16
3.1.6 TEST RESULTS	17
3.2 RADIATED EMISSION MEASUREMENT	19
3.2.1 RADIATED EMISSION LIMITS	19
3.2.2 TEST PROCEDURE	19
3.2.3 DEVIATION FROM TEST STANDARD	23
3.2.4 TEST SETUP	24
3.2.5 EUT OPERATING CONDITIONS	25
3.2.6 TEST RESULTS (BETWEEN 9KHZ – 30 MHZ)	26
3.2.7 TEST RESULTS (BETWEEN 30MHZ – 1GHZ)	27
3.2.8 TEST RESULTS (ABOVE 1000 MHZ)	29
<b>4 . POWER SPECTRAL DENSITY TEST</b>	<b>53</b>
4.1 APPLIED PROCEDURES / LIMIT	53
4.1.1 TEST PROCEDURE	53
4.1.2 DEVIATION FROM STANDARD	53
4.1.3 TEST SETUP	53



# Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT2017SZ0510132F2  
- Page 4 of 76 -

Table of Contents	Page
4.1.4 EUT OPERATION CONDITIONS	53
4.1.5 TEST RESULTS	54
5 . BANDWIDTH TEST	60
5.1 APPLIED PROCEDURES / LIMIT	60
5.1.1 TEST PROCEDURE	60
5.1.2 EUT OPERATION CONDITIONS	60
5.1.3 TEST RESULTS	61
6 . PEAK OUTPUT POWER TEST	67
6.1 APPLIED PROCEDURES / LIMIT	67
6.1.1 TEST PROCEDURE	67
6.1.2 DEVIATION FROM STANDARD	67
6.1.3 TEST SETUP	67
6.1.4 EUT OPERATION CONDITIONS	67
6.1.5 TEST RESULTS	68
7 . 100 KHZ BANDWIDTH OF FREQUENCY BAND EDGE	69
7.1 DEVIATION FROM STANDARD	69
7.2 TEST SETUP	69
7.3 EUT OPERATION CONDITIONS	69
7.4 TEST RESULTS	70
8 . ANTENNA REQUIREMENT	74
8.1 STANDARD REQUIREMENT	74
8.2 EUT ANTENNA	74
9 . EUT TEST PHOTO	75
APPENDIX-PHOTOGRAPHS OF EUT CONSTRUCTIONAL DETAILS	



# Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT2017SZ0510132F2  
- Page 5 of 76 -

## 1. SUMMARY OF TEST RESULTS

Test procedures according to the technical standards:

Test Item	FCC Part No.	Requirements	Verdict
DTS (6 dB) Bandwidth	15.247(a)(2)	$\geq 500$ kHz.	PASS
Maximum Peak Conducted Output Power	15.247(b)(3)	For directional gain: $< 30\text{dBm} - (G[\text{dBi}] - 6[\text{dB}])$ , peak; Otherwise : $< 30\text{dBm}$ , peak.	PASS
Transmitter Power Spectral Density	15.247(e)	For directional gain : $< 8\text{dBm}/3\text{ kHz} - (G[\text{dBi}] - 6[\text{dB}])$ , peak. Otherwise : $< 8\text{dBm}/3\text{ kHz}$ , peak.	PASS
Conducted Out of band emission measurement	15.247(d)	$< -20\text{dBm}/100\text{ kHz}$ if total peak power $\leq$ power limit.	PASS
Spurious Radiated Emissions	15.247(d) 15.209 15.35(b)	FCC Part 15.209&15.35(b) field strength limit;	PASS
AC Power Line Conducted Emissions	15.207	FCC Part 15.207 conducted limit;	PASS

### NOTE:

(1) "N/A" denotes test is not applicable in this Test Report

### Summary of measurement results

Test Specification clause	Test case	Test Mode	Test Channel	Recorded In Report		Pass	Fail	NA	NP	Remark
§15.247(b)(4)	Antenna gain	802.11b	<input checked="" type="checkbox"/> Lowest <input checked="" type="checkbox"/> Middle <input checked="" type="checkbox"/> Highest	802.11b	<input checked="" type="checkbox"/> Lowest <input checked="" type="checkbox"/> Middle <input checked="" type="checkbox"/> Highest	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	complies
§15.247(e)	Power spectral density	802.11b 802.11g 802.11n HT20	<input checked="" type="checkbox"/> Lowest <input checked="" type="checkbox"/> Middle <input checked="" type="checkbox"/> Highest	802.11b 802.11g 802.11n HT20	<input checked="" type="checkbox"/> Lowest <input checked="" type="checkbox"/> Middle <input checked="" type="checkbox"/> Highest	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	complies
§15.247(a)(2)	Spectrum bandwidth - 6 dB bandwidth	802.11b 802.11g 802.11n HT20	<input checked="" type="checkbox"/> Lowest <input checked="" type="checkbox"/> Middle <input checked="" type="checkbox"/> Highest	802.11b 802.11g 802.11n HT20	<input checked="" type="checkbox"/> Lowest <input checked="" type="checkbox"/> Middle <input checked="" type="checkbox"/> Highest	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	complies
§15.247(b)(3)	Maximum output power	802.11b 802.11g 802.11n HT20	<input checked="" type="checkbox"/> Lowest <input checked="" type="checkbox"/> Middle <input checked="" type="checkbox"/> Highest	802.11b 802.11g 802.11n HT20	<input checked="" type="checkbox"/> Lowest <input checked="" type="checkbox"/> Middle <input checked="" type="checkbox"/> Highest	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	complies
§15.247(d)	Band edge complian	802.11b 802.11g 802.11n HT20	<input checked="" type="checkbox"/> Lowest <input checked="" type="checkbox"/> Highest	802.11b 802.11g 802.11n HT20	<input checked="" type="checkbox"/> Lowest <input checked="" type="checkbox"/> Highest	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	complies

This document cannot be reproduced except in full, without prior written approval of ATT. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.



## Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT2017SZ0510132F2  
- Page 6 of 76 -

	ce conducted									
§15.205	Band edge compliance radiated	802.11b 802.11g 802.11n HT20	<input checked="" type="checkbox"/> Lowest <input checked="" type="checkbox"/> Highest	802.11b 802.11g 802.11n HT20	<input checked="" type="checkbox"/> Lowest <input checked="" type="checkbox"/> Highest	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	complies
§15.247(d)	TX spurious emissions conducted	802.11b 802.11g 802.11n HT20	<input checked="" type="checkbox"/> Lowest <input checked="" type="checkbox"/> Middle <input checked="" type="checkbox"/> Highest	802.11b 802.11g 802.11n HT20	<input checked="" type="checkbox"/> Lowest <input checked="" type="checkbox"/> Middle <input checked="" type="checkbox"/> Highest	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	complies
§15.247(d)	TX spurious emissions radiated	802.11b 802.11g 802.11n HT20	<input checked="" type="checkbox"/> Lowest <input checked="" type="checkbox"/> Middle <input checked="" type="checkbox"/> Highest	802.11b	<input checked="" type="checkbox"/> Lowest <input checked="" type="checkbox"/> Middle <input checked="" type="checkbox"/> Highest	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	complies
§15.109	RX spurious emissions radiated	-/-	-/-	-/-	-/-	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	complies
§15.209(a)	TX spurious Emissions radiated < 30 MHz	802.11b	-/-	802.11b	-/-	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	complies
§15.107(a) §15.207	Conducted Emissions < 30 MHz	802.11b	-/-	802.11b	-/-	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	complies

This document cannot be reproduced except in full, without prior written approval of ATT. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.



# Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT2017SZ0510132F2  
- Page 7 of 76 -

## 1.1 TEST FACILITY

Shenzhen Asia Test Technology Co.,Ltd.

7 / F, Xinwei Building, Gushu Village, Xixiang Town, Baoan District, Shenzhen, China

FCC Registration No.: 348715

## 1.2 MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement  $y \pm U$ , where expanded uncertainty  $U$  is based on a standard uncertainty multiplied by a coverage factor of  $k=2$ , providing a level of confidence of approximately **95 %**.

No.	Item	Uncertainty
1	Conducted Emission Test	$\pm 1.38\text{dB}$
2	RF power,conducted	$\pm 0.16\text{dB}$
3	Spurious emissions,conducted	$\pm 0.21\text{dB}$
4	All emissions,radiated(<1G)	$\pm 4.68\text{dB}$
5	All emissions,radiated(>1G)	$\pm 4.89\text{dB}$
6	Temperature	$\pm 0.5^{\circ}\text{C}$
7	Humidity	$\pm 2\%$



## Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT2017SZ0510132F2  
- Page 8 of 76 -

### 2. GENERAL INFORMATION

#### 2.1 GENERAL DESCRIPTION OF EUT

Equipment	Smart Video Door Phone
Model Name	TC-X4DB-A
Serial number	N/A
Serial Model	TC-X6KT-DB, TC-X4DB-B, TC-X4DB-C, TC-X4DB-D, TC-X4DB-E, TC-X4DB-F
Model Difference	All models are identical except model name and colors.
WLAN FCC Operation frequency	IEEE 802.11b:2412-2462MHz IEEE 802.11g:2412-2462MHz IEEE 802.11n HT20:2412-2462MHz
WLAN FCC Modulation Type	IEEE 802.11b: DSSS(CCK,DQPSK,DBPSK) IEEE 802.11g: OFDM(64QAM, 16QAM, QPSK, BPSK) IEEE 802.11n HT20: OFDM (64QAM, 16QAM, QPSK,BPSK)
Antenna	0dbi, PCB antenna
Ratings	DC 12V, 1.5A
Adapter	M/N:RS-AB015J00-E Input:100-240V~, 50/60Hz, 0.6A Output:12Vdc, 1.5A
Battery	N/A
HW:	N/A
SW:	N/A





# Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT2017SZ0510132F2  
- Page 9 of 76 -

## 2.2 DESCRIPTION OF TEST MODES

IEEE 802.11b/g/n: The product support thirteen channels but only use Eleventh channels in USA.

Channel	Frequency(MHz)	Channel	Frequency(MHz)
1	2412	8	2447
2	2417	9	2452
3	2422	10	2457
4	2427	11	2462
5	2432		
6	2437		
7	2442		

### 2.2.1 TEST MODES

Test Case	Test Conditions	
	Configuration	Description
DTS (6 dB) Bandwidth	Measurement Method	FCC KDB 558074 §8.2 Option 2
	Test Environment	NTNV
	EUT Configuration	11b_L,11b_M,11b_H 11g_L,11g_M,11g_H 11n HT20_L, 11n HT20_M, 11n HT20_H
Maximum Peak Conducted Output Power	Measurement Method	FCC KDB 558074§9.1.2
	Test Environment	NTNV
	Test Setup	Test Setup 1
	EUT Configuration	11b_L,11b_M,11b_H 11g_L,11g_M,11g_H 11n HT20_L, 11n HT20_M, 11n HT20_H
Maximum Power Spectral Density Level	Measurement Method	FCC KDB 558074 §10.2 (peak PSD).
	Test Environment	NTNV
	EUT Configuration	11b_L,11b_M,11b_H 11g_L,11g_M,11g_H 11n HT20_L, 11n HT20_M, 11n HT20_H
Unwanted Emissions into Non-Restricted Frequency Bands	Measurement Method	FCC KDB 558074§11.0.
	Test Environment	NTNV
	Test Setup	Test Setup 1
	EUT Configuration	11b_L,11b_M,11b_H 11g_L,11g_M,11g_H 11n HT20_L, 11n HT20_M, 11n HT20_H
Unwanted Emissions into Restricted Frequency Bands (Conducted)	Measurement Method	FCC KDB 558074§12.2, Conducted (antenna-port).
	Test Environment	NTNV
	EUT Configuration	11b_L,11b_M,11b_H 11g_L,11g_M,11g_H

This document cannot be reproduced except in full, without prior written approval of ATT. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.



## Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT2017SZ0510132F2  
- Page 10 of 76 -

		11n HT20_L, 11n HT20_M, 11n HT20_H
Unwanted Emissions into Restricted	Measurement Method	FCC KDB 558074§12.1,Radiated(cabinet/case emissions with Impedance matching for antenna-port).
	Test Environment	NTNV
	EUT Configuration	11b_L,11b_M,11b_H 11g_L,11g_M,11g_H 11n HT20_L, 11n HT20_M, 11n HT20_H

Test Case	Test Conditions	
	Configuration	Description
AC Power Line Conducted Emissions	Measurement Method	AC mains conducted.
	Test Environment	NTNV
	EUT Configuration	11g_M (Worst Conf.).

### Remark:

1. For Radiated Emissions, By preliminary testing and verifying three axis (X, Y and Z) position of EUT transmitted status, it was found that "Z axis" position was the worst, then the final test was executed the worst condition and test data were recorded in this report.
2. Typical working modes for each IEEE 802.11mode are selected to perform tests. The manufacturer provide special test software(WLAN facility) to control TX duty cycle >98% for TX test. Set the output power to max(PK) as Prescribed by the manufacturer.

Test Mode	Test Modes Description
IEEE 802.11b	IEEE 802.11b with data rate of 1 Mbps using SISO mode.
IEEE 802.11g	IEEE 802.11g with data rate of 6 Mbps using SISO mode.
IEEE 802.11n HT20	IEEE 802.11n with data date of MCS0 and bandwidth of 20MHz using SISO mode.



## Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT2017SZ0510132F2  
- Page 11 of 76 -

### 2.2.2 EUT operation mode

Test Mode	RF Ch.	TX Freq. [MHz]	RX Freq. [MHz]	Ch. BW [MHz]
IEEE 802.11b	L	Ch No. 1 / 2412MHz	---	20
	M	Ch No. 6 / 2437 MHz	---	20
	H	Ch No. 11/ 2462MHz	---	20
IEEE 802.11g	L	Ch No. 1 / 2412MHz	---	20
	M	Ch No. 6 / 2437 MHz	---	20
	H	Ch No. 11/ 2462MHz	---	20
IEEE 802.11n HT20	L	Ch No. 1 / 2412MHz	---	20
	M	Ch No. 6 / 2437 MHz	---	20
	H	Ch No. 11/ 2462MHz	---	20

### 2.2.3 EUT configuratio


**The following peripheral devices and interface cables were connected during the measurement:**

● - supplied by the manufacturer

○ - supplied by the lab

○ Power Cable	Length (m) :	/
	Shield :	/
	Detachable :	/
○ Multimeter	Manufacturer :	/
	Model No. :	/

## 2.3 BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED



## 2.4 DESCRIPTION OF SUPPORT UNITS(CONDUCTED MODE)

This document cannot be reproduced except in full, without prior written approval of ATT. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.



## Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT2017SZ0510132F2

- Page 12 of 76 -

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Item	Equipment	Brand	Model/Type No.	Series No.	Note
E-1	Smart Video Door Phone	N/A	TC-X4DB-A	N/A	EUT
E-2	Adapter	N/A	RS-AB015J00-E	N/A	

Item	Shielded Type	Ferrite Core	Length	Note
C-1	NO	NO	0.8m	

**Note:**

- (1) The support equipment was authorized by Declaration of Confirmation.
- (2) For detachable type I/O cable should be specified the length in cm in 『Length』 column.



## Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT2017SZ0510132F2  
- Page 13 of 76 -

### 2.5 EQUIPMENTS LIST FOR ALL TEST ITEMS

Equipment No.	Instrument	Manufacturer	Model Name	Serial Number	Specification	Cal. Data	due date
1	Semi-anechoic chamber	Changzhou Chengyu	EC3088	N/A	9*6*6m	10/25/2016	10/24/2017
2	Broadband antenna	R&S	VULB 9160	VULB91 60-516	30MHz-1500 MHz	10/25/2016	10/24/2017
3	Horn antenna	R&S	BBHA 9120D	10087	1GHz-18GH z	06/05/2017	06/04/2018
4	Test receiver	R&S	ESCI	101686	9KHz-3GHz	10/25/2016	10/24/2017
5	EMI Measuring Receiver	R&S	ESR	101660	9KHz-40GHz	10/25/2016	10/24/2017
6	Multi-device controller	MF	MF-7868	MF78680 8762	N/A	10/25/2016	10/24/2017
7	Amplifier	EM	EM-30180	060538	1GHz-18GH z	10/25/2016	10/24/2017
8	Amplifier	Schwarzbeck	BBV 9475	BBV 9475-663	1GHz-18GH z	06/05/2017	06/04/2018
9	Spectrum Analyzer	agilent	E4440B	US44300368	1GHz-26.5GH z	06/05/2017	06/04/2018
10	Test receiver	R&S	ESCI	101689	9KHz-3GHz	10/25/2016	10/24/2017
11	LISN	R&S	NSLK81 26	8126466	9k-30MHz	10/25/2016	10/24/2017
12	LISN	Narda	L2-16B	5589756	9k-30MHz	10/25/2016	10/24/2017
13	Power Meter	Anritsu	ML2495A	N/A	40MHz	10/25/2016	10/24/2017
14	Power sensor	Anritsu	MA2411B	N/A	40MHz	10/25/2016	10/24/2017
15	Radiated Cable 1#	FUJIKURA	5D-2W	01	30MHz-1GHz	10/25/2016	10/24/2017

This document cannot be reproduced except in full, without prior written approval of ATT. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.



## Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT2017SZ0510132F2  
- Page 14 of 76 -

16	Radiated Cable 2#	FUJIKURA	10D2W	02	1GHz -25GHz	10/25/2016	10/24/2017
17	Conducted Cable 1#	FUJIKURA	1D-2W	01	9KHz-30MHz	10/25/2016	10/24/2017
18	SMA Antenna connector	Dosin	Dosin-SMA	N/A	N/A	10/25/2016	10/24/2017
Note: The SMA antenna connector is soldered on the PCB board in order to perform conducted tests and this SMA antenna connector is listed in the equipment list. The Cal.Interval was one year							



### 3. EMC EMISSION TEST

#### 3.1 CONDUCTED EMISSION MEASUREMENT

##### 3.1.1 POWER LINE CONDUCTED EMISSION Limits (Frequency Range 150KHz-30MHz)

FREQUENCY (MHz)			Standard
	Quasi-peak	Average	
0.15 -0.5	66 - 56 *	56 - 46 *	CISPR
0.50 -5.0	56.00	46.00	CISPR
5.0 -30.0	60.00	50.00	CISPR

0.15 -0.5	66 - 56 *	56 - 46 *	FCC
0.50 -5.0	56.00	46.00	FCC
5.0 -30.0	60.00	50.00	FCC

Note:

- (1) The tighter limit applies at the band edges.
- (2) The limit of " \* " marked band means the limitation decreases linearly with the logarithm of the frequency in the range.

The following table is the setting of the receiver

Receiver Parameters	Setting
Attenuation	10 dB
Start Frequency	0.15 MHz
Stop Frequency	30 MHz
IF Bandwidth	9 kHz




## 3.1.2 TEST PROCEDURE

- The EUT was placed 0.8 meters from the horizontal ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipments powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
- Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- LISN at least 80 cm from nearest part of EUT chassis.
- For the actual test configuration, please refer to the related Item –EUT Test Photos.

## 3.1.3 DEVIATION FROM TEST STANDARD

No deviation

## 3.1.4 TEST SETUP



**Note: 1.** Support units were connected to second LISN.

**2.** Both of LISNs (AMN) are 80 cm from EUT and at least 80 cm from other units and other metal planes

## 3.1.5 EUT OPERATING CONDITIONS

The EUT was configured for testing in a typical fashion (as a customer would normally use it). The EUT has been programmed to continuously transmit during test. This operating condition was tested and used to collect the included data.





# Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT2017SZ0510132F2  
- Page 17 of 76 -

## 3.1.6 TEST RESULTS

Phase : L Test Voltage : DC 12V from adapter AC 120V/60Hz


No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Detector	Comment
1		0.1539	45.86	11.84	57.70	65.78	-8.08	QP	
2		0.1539	28.24	11.84	40.08	55.78	-15.70	AVG	
3		0.7060	30.77	9.98	40.75	56.00	-15.25	QP	
4		0.7060	23.14	9.98	33.12	46.00	-12.88	AVG	
5	*	15.8900	34.00	10.54	44.54	50.00	-5.46	AVG	
6		16.4500	41.62	10.62	52.24	60.00	-7.76	QP	

Remark:

1. All readings are Quasi-Peak and Average values.

2. Factor = Insertion Loss + Cable Loss.

3. N/A means All Data have pass Limit



This document cannot be reproduced except in full, without prior written approval of ATT. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.



# Shenzhen Asia Test Technology Co., Ltd.


Report No. ATT2017SZ0510132F2  
- Page 18 of 76 -

Phase :	N	Test Voltage :	DC 12V from adapter AC 120V/60Hz
---------	---	----------------	----------------------------------

No. Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Detector	Comment
1	0.1539	44.60	11.84	56.44	65.78	-9.34	QP	
2	0.1539	32.66	11.84	44.50	55.78	-11.28	AVG	
3	0.7100	36.09	9.98	46.07	56.00	-9.93	QP	
4	0.7180	28.16	9.98	38.14	46.00	-7.86	AVG	
5 *	15.7420	34.49	10.52	45.01	50.00	-4.99	AVG	
6	16.1460	42.68	10.58	53.26	60.00	-6.74	QP	

## Remark:

1. All readings are Quasi-Peak and Average values.
2. Factor = Insertion Loss + Cable Loss.
3. N/A means All Data have pass Limit



This document cannot be reproduced except in full, without prior written approval of ATT. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.



## 3.2 RADIATED EMISSION MEASUREMENT

### 3.2.1 RADIATED EMISSION LIMITS (Frequency Range 9kHz-1000MHz)

20dBc in any 100 kHz bandwidth outside the operating frequency band. the 15.209(a) limit in the table below has to be followed.

Frequencies (MHz)	Field Strength (microvolt/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

Notes:

- (1) The limit for radiated test was performed according to FCC PART 15C.
- (2) The tighter limit applies at the band edges.
- (3) Emission level (dBuV/m)=20log Emission level (uV/m).

Spectrum Parameter	Setting
Attenuation	Auto
Start Frequency	1000 MHz
Stop Frequency	10th carrier harmonic
RB / VB (emission in restricted band)	1 MHz / 1 MHz for Peak, 1 MHz / 10Hz for Average
Receiver Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	9kHz~150kHz / RB 200Hz for QP
Start ~ Stop Frequency	150kHz~30MHz / RB 9kHz for QP
Start ~ Stop Frequency	30MHz~1000MHz / RB 120kHz for QP

### 3.2.2 TEST PROCEDURE

1. The EUT was placed on a turn table which is 0.8m above ground plane for below 1GHz and 1.50m above ground plane for above 1GHz.
2. Maximum procedure was performed by raising the receiving antenna from 1m to 4m and rotating the turn table from 0°C to 360°C to acquire the highest emissions from EUT.

This document cannot be reproduced except in full, without prior written approval of ATT. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.



## Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT2017SZ0510132F2  
- Page 20 of 76 -

3. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
4. Repeat above procedures until all frequency measurements have been completed.
5. The EUT minimum operation frequency was 12MHz and maximum operation frequency was 2480MHz.so radiated emission test frequency band from 9 KHz to 25GHz.
6. The distance between test antenna and EUT as following table states:

Test Frequency range	Test Antenna Type	Test Distance
9KHz-30MHz	Active Loop Antenna	3
30MHz-1GHz	Bilog Antenna	3
1GHz-18GHz	Horn Antenna	3
18GHz-25GHz	Horn Antenna	3

7. Setting test receiver/spectrum as following table states:

Test Frequency range	Test Receiver/Spectrum Setting	Detector
9KHz-150KHz	RBW=200Hz/VBW=3KHz,Sweep time=Auto	QP
150KHz-30MHz	RBW=9KHz/VBW=100KHz,Sweep time=Auto	QP
30MHz-1GHz	RBW=120KHz/VBW=1000KHz,Sweep time=Auto	QP
1GHz-40GHz	Peak Value: RBW=1MHz/VBW=3MHz, Sweep time=Auto	Peak
	Average Value: RBW=1MHz/VBW=10Hz, Sweep time=Auto	Peak

More procedure as follows;

### 1) Sequence of testing 9 kHz to 30 MHz

#### Setup:

- The equipment was set up to simulate a typical usage like described in the user manual or described by manufacturer.
- If the EUT is a tabletop system, a rotatable table with 0.8 m height is used.
- If the EUT is a floor standing device, it is placed on the ground.
- Auxiliary equipment and cables were positioned to simulate normal operation conditions.
- The AC power port of the EUT (if available) is connected to a power outlet below the turntable.
- The measurement distance is 3 meter.
- The EUT was set into operation.

#### Premeasurement:

- The turntable rotates from 0° to 315° using 45° steps.
- The antenna height is 1.0 meter.
- At each turntable position the analyzer sweeps with peak detection to find the maximum of all emissions

---

This document cannot be reproduced except in full, without prior written approval of ATT. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.



## Final measurement:

- Identified emissions during the premeasurement the software maximizes by rotating the turntable position (0° to 360°) and by rotating the elevation axes (0° to 360°).
- The final measurement will be done in the position (turntable and elevation) causing the highest emissions with QP detector.
- The final levels, frequency, measuring time, bandwidth, turntable position, correction factor, margin to the limit and limit will be recorded. Also a plot with the graph of the premeasurement and the limit will be stored.

## 2) Sequence of testing 30 MHz to 1 GHz

### Setup:

- The equipment was set up to simulate a typical usage like described in the user manual or described by manufacturer.
- If the EUT is a tabletop system, a table with 0.8 m height is used, which is placed on the ground plane.
- If the EUT is a floor standing device, it is placed on the ground plane with insulation between both.
- Auxiliary equipment and cables were positioned to simulate normal operation conditions
- The AC power port of the EUT (if available) is connected to a power outlet below the turntable.
- The measurement distance is 3 meter.
- The EUT was set into operation.

### Premeasurement:

- The turntable rotates from 0° to 315° using 45° steps.
- The antenna is polarized vertical and horizontal.
- The antenna height changes from 1 to 4 meter.
- At each turntable position, antenna polarization and height the analyzer sweeps three times in peak to find the maximum of all emissions.

### Final measurement:

- The final measurement will be performed with minimum the six highest peaks.
- According to the maximum antenna and turntable positions of premeasurement the software maximize the peaks by changing turntable position ( $\pm 45^\circ$ ) and antenna movement between 1 and 4 meter.
- The final measurement will be done with QP detector with an EMI receiver.
- The final levels, frequency, measuring time, bandwidth, antenna height, antenna polarization, turntable angle, correction factor, margin to the limit and limit will be recorded. Also a plot with the graph of the premeasurement with marked maximum final measurements and the limit will be stored.

## 3) Sequence of testing 1 GHz to 18 GHz

### Setup:

- The equipment was set up to simulate a typical usage like described in the user manual or described by manufacturer.
- If the EUT is a tabletop system, a rotatable table with 1.5 m height is used.
- If the EUT is a floor standing device, it is placed on the ground plane with insulation between both.



# Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT2017SZ0510132F2

- Page 22 of 76 -

- Auxiliary equipment and cables were positioned to simulate normal operation conditions
- The AC power port of the EUT (if available) is connected to a power outlet below the turntable.
- The measurement distance is 3 meter.
- The EUT was set into operation.

## Premeasurement:

- The turntable rotates from 0° to 315° using 45° steps.
- The antenna is polarized vertical and horizontal.
- The antenna height scan range is 1 meter to 2.5 meter.
- At each turntable position and antenna polarization the analyzer sweeps with peak detection to find the maximum of all emissions.

## Final measurement:

- The final measurement will be performed with minimum the six highest peaks.
- According to the maximum antenna and turntable positions of premeasurement the software maximize the peaks by changing turntable position ( $\pm 45^\circ$ ) and antenna movement between 1 and 4 meter. This procedure is repeated for both antenna polarizations.
- The final measurement will be done in the position (turntable, EUT-table and antenna polarization) causing the highest emissions with Peak and Average detector.
- The final levels, frequency, measuring time, bandwidth, turntable position, EUT-table position, antenna polarization, correction factor, margin to the limit and limit will be recorded. Also a plot with the graph of the premeasurement with marked maximum final measurements and the limit will be stored.

## 4) Sequence of testing above 18 GHz

### Setup:

- The equipment was set up to simulate a typical usage like described in the user manual or described by manufacturer.
- If the EUT is a tabletop system, a rotatable table with 1.5 m height is used.
- If the EUT is a floor standing device, it is placed on the ground plane with insulation between both.
- Auxiliary equipment and cables were positioned to simulate normal operation conditions
- The AC power port of the EUT (if available) is connected to a power outlet below the turntable.
- The measurement distance is 1 meter.
- The EUT was set into operation.

### Premeasurement:

- The antenna is moved spherical over the EUT in different polarizations of the antenna.

### Final measurement:

- The final measurement will be performed at the position and antenna orientation for all detected emissions that were found during the premeasurements with Peak and Average detector.
- The final levels, frequency, measuring time, bandwidth, correction factor, margin to the limit and limit will be recorded. Also a plot with the graph of the premeasurement and the limit will be stored.

## Field Strength Calculation

The field strength is calculated by adding the Antenna Factor and Cable Factor and subtracting the Amplifier Gain and Duty Cycle Correction Factor (if any) from the measured reading. The basic equation with a sample calculation is as follows:

---

This document cannot be reproduced except in full, without prior written approval of ATT. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.



## Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT2017SZ0510132F2

- Page 23 of 76 -

$$FS = RA + AF + CL - AG$$

Where FS = Field Strength	CL = Cable Attenuation Factor (Cable Loss)
RA = Reading Amplitude	AG = Amplifier Gain
AF = Antenna Factor	

For example

Frequency (MHz)	FS (dB $\mu$ V/m)	RA (dB $\mu$ V/m)	AF (dB)	CL (dB)	AG (dB)	Transd (dB)
300.00	40	58.1	12.2	1.6	31.90	-18.1

$$\text{Transd} = \text{AF} + \text{CL} - \text{AG}$$


### 3.2.3 DEVIATION FROM TEST STANDARD

No deviation




### 3.2.4 TEST SETUP

#### (A) Radiated Emission Test-Up Frequency Below 30MHz




#### (B) Radiated Emission Test-Up Frequency 30MHz~1GHz







(C) Radiated Emission Test-Up Frequency Above 1GHz



### 3.2.5 EUT OPERATING CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.



## Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT2017SZ0510132F2  
- Page 26 of 76 -

### 3.2.6 TEST RESULTS (BETWEEN 9KHZ – 30 MHZ)

EUT:	Smart Video Door Phone	Model Name. :	TC-X4DB-A
Temperature:	20 °C	Relative Humidity:	48%
Pressure:	1010 hPa	Test Voltage :	DC 12V from adapter AC 120V/60Hz
Test Mode :	TX	Polarization :	--

Freq.	Reading	Limit	Margin	State
(MHz)	(dBuV/m)	(dBuV/m)	(dB)	P/F
--	--	--	--	P
--	--	--	--	P

#### NOTE:

The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

Distance extrapolation factor =  $40 \log (\text{specific distance/test distance})$ (dB);

Limit line = specific limits(dBuV) + distance extrapolation factor.




# Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT2017SZ0510132F2  
- Page 27 of 76 -

## 3.2.7 TEST RESULTS (BETWEEN 30MHZ – 1GHZ)

Polarization:	Horizontal	Test Voltage :	DC 12V from adapter AC 120V/60Hz
Test Mode :	802.11B TX 2412		

No. Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	Antenna Height	Table Degree	
	MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	Comment
1	49.1865	30.04	-14.21	15.83	40.00	-24.17	QP		
2	65.8031	33.19	-17.65	15.54	40.00	-24.46	QP		
3	181.9201	29.89	-11.58	18.31	43.50	-25.19	QP		
4	480.5276	30.74	-5.90	24.84	46.00	-21.16	QP		
5	701.7607	30.72	0.32	31.04	46.00	-14.96	QP		
6 *	881.4067	29.71	2.48	32.19	46.00	-13.81	QP		



This document cannot be reproduced except in full, without prior written approval of ATT. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.




# Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT2017SZ0510132F2  
- Page 28 of 76 -

Polarization:	Vertical	Test Voltage :	DC 12V from adapter AC 120V/60Hz
Test Mode :	802.11B TX 2412		

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree
1		36.3813	34.13	-16.74	17.39	40.00	-22.61	QP		
2		64.4330	35.79	-19.22	16.57	40.00	-23.43	QP		
3		110.1816	31.34	-13.43	17.91	43.50	-25.59	QP		
4		148.9625	33.76	-15.56	18.20	43.50	-25.30	QP		
5		400.4318	30.17	-5.93	24.24	46.00	-21.76	QP		
6	*	916.0687	33.72	2.98	36.70	46.00	-9.30	QP		

80.0 dBuV/m



Note: test performed on 802.11b/g/n mode, "802.11b TX2412" mode is the worst mode and has been reported.

This document cannot be reproduced except in full, without prior written approval of ATT. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.




## Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT2017SZ0510132F2  
- Page 29 of 76 -

### 3.2.8 TEST RESULTS (ABOVE 1000 MHZ)

Polarization:	Horizontal	Test Voltage :	DC 12V from adapter AC 120V/60Hz
Test Mode :	802.11B TX 2412		



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Antenna Height cm	Table Degree degree	Comment
1		4824.150	44.25	5.08	49.33	74.00	-24.67	peak		
2	*	4824.150	33.67	5.08	38.75	54.00	-15.25	AVG		
3		7236.520	40.71	7.16	47.87	74.00	-26.13	peak		
4		7236.520	30.14	7.16	37.30	54.00	-16.70	AVG		
5		9542.500	33.83	10.24	44.07	74.00	-29.93	peak		
6		17532.50	24.26	25.01	49.27	74.00	-24.73	peak		


Note: test performed on 802.11b/g/n mode, "802.11b" mode is the worst mode and has been reported. spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported above 18G.



# Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT2017SZ0510132F2  
- Page 30 of 76 -

Polarization:	Vertical	Test Voltage :	DC 12V from adapter AC 120V/60Hz
Test Mode :	802.11B TX 2412		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV	dBuV	dB	cm	degree	Comment
1		4824.360	45.87	5.08	50.95	74.00	-23.05	peak		
2	*	4824.360	35.62	5.08	40.70	54.00	-13.30	AVG		
3		7236.220	32.91	7.16	40.07	74.00	-33.93	peak		
4		11200.00	29.87	16.99	46.86	74.00	-27.14	peak		

Note: test performed on 802.11b/g/n mode, "802.11b" mode is the worst mode and has been reported. spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported above 18G.




# Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT2017SZ0510132F2

- Page 31 of 76 -

Polarization:	Horizontal	Test Voltage :	DC 12V from adapter AC 120V/60Hz
Test Mode :	802.11B TX 2437		



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Antenna Height cm	Table Degree degree	Comment
1		4874.550	37.70	5.13	42.83	74.00	-31.17	peak		
2		7311.050	36.84	7.49	44.33	74.00	-29.67	peak		
3		11583.59	26.94	16.69	43.63	74.00	-30.37	peak		
4	*	17532.50	22.02	25.01	47.03	74.00	-26.97	peak		

Note: test performed on 802.11b/g/n mode, "802.11b" mode is the worst mode and has been reported. spurious emissions which are attenuated by more than 20dB below the permissible value have no need to be reported above 18G.




# Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT2017SZ0510132F2

- Page 32 of 76 -

Polarization:	Vertical	Test Voltage :	DC 12V from adapter AC 120V/60Hz
Test Mode :	802.11B TX 2437		



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Antenna Height cm	Table Degree degree	Comment
1		4874.340	44.13	5.13	49.26	74.00	-24.74	peak		
2		4874.340	32.17	5.13	37.30	54.00	-16.70	AVG		
3		7311.050	40.07	7.49	47.56	74.00	-26.44	peak		
4	*	7311.050	30.08	7.49	37.57	54.00	-16.43	AVG		
5		11200.00	29.36	16.99	46.35	74.00	-27.65	peak		
6		15832.50	28.74	16.57	45.31	74.00	-28.69	peak		

Note: test performed on 802.11b/g/n mode, "802.11b" mode is the worst mode and has been reported. spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported above 18G.






# Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT2017SZ0510132F2  
- Page 33 of 76 -

Polarization:	Horizontal	Test Voltage :	DC 12V from adapter AC 120V/60Hz
Test Mode :	802.11B TX 2462		



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Antenna Height cm	Table Degree degree	Comment
1		4924.140	43.59	5.18	48.77	74.00	-25.23	peak		
2	*	4924.140	31.97	5.18	37.15	54.00	-16.85	AVG		
3		7386.250	39.75	7.82	47.57	74.00	-26.43	peak		
4		7386.250	28.14	7.82	35.96	54.00	-18.04	AVG		
5		12909.70	28.31	17.66	45.97	74.00	-28.03	peak		
6		17022.50	26.99	20.68	47.67	74.00	-26.33	peak		

Note: test performed on 802.11b/g/n mode, "802.11b" mode is the worst mode and has been reported. spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported above 18G.




# Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT2017SZ0510132F2  
- Page 34 of 76 -

Polarization:	Vertical	Test Voltage :	DC 12V from adapter AC 120V/60Hz
Test Mode :	802.11B TX 2462		

80.0 dBuV



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV	dBuV	dB	Detector	cm	degree
1		4924.140	43.52	5.18	48.70	74.00	-25.30	peak		
2		4924.140	31.67	5.18	36.85	54.00	-17.15	AVG		
3		7386.160	37.88	7.82	45.70	74.00	-28.30	peak		
4	*	7386.160	29.34	7.82	37.16	54.00	-16.84	AVG		
5		11500.19	28.35	16.80	45.15	74.00	-28.85	peak		
6		13197.50	28.43	16.77	45.20	74.00	-28.80	peak		

Note: test performed on 802.11b/g/n mode, "802.11b" mode is the worst mode and has been reported. spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported above 18G.




# Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT2017SZ0510132F2


- Page 35 of 76 -

Conducted Spurious Emissions at Antenna Port:

802.11b Low Channel



Date: 11 JUN 2017 16:07:37



Date: 11 JUN 2017 16:07:25


This document cannot be reproduced except in full, without prior written approval of ATT. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.




# Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT2017SZ0510132F2

- Page 36 of 76 -



Date: 11 JUN 2017 16:07:51



Date: 11 JUN 2017 16:08:02


This document cannot be reproduced except in full, without prior written approval of ATT. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.




# Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT2017SZ0510132F2  
- Page 37 of 76 -

## 802.11b Middle Channel



Date: 11 JUN 2017 16:08:57



Date: 11 JUN 2017 16:08:47


This document cannot be reproduced except in full, without prior written approval of ATT. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.




# Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT2017SZ0510132F2

- Page 38 of 76 -



Date: 11 JUN 2017 16:09:09



Date: 11 JUN 2017 16:09:21

This document cannot be reproduced except in full, without prior written approval of ATT. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.




# Shenzhen Asia Test Technology Co., Ltd.


Report No. ATT2017SZ0510132F2

- Page 39 of 76 -

## 802.11b High Channel



Date: 11 JUN 2017 16:09:59



Date: 11 JUN 2017 16:09:45

This document cannot be reproduced except in full, without prior written approval of ATT. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.







# Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT2017SZ0510132F2

- Page 40 of 76 -



Date: 11 JUN 2017 16:10:10



Date: 11 JUN 2017 16:10:21

This document cannot be reproduced except in full, without prior written approval of ATT. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.







# Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT2017SZ0510132F2  
- Page 41 of 76 -

## 802.11g Low Channel



Date: 11 JUN 2017 16:15:33




Date: 11 JUN 2017 16:15:20

This document cannot be reproduced except in full, without prior written approval of ATT. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.




# Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT2017SZ0510132F2  
- Page 42 of 76 -



Date: 11 JUN 2017 16:15:42



Date: 11 JUN 2017 16:15:53

This document cannot be reproduced except in full, without prior written approval of ATT. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.




# Shenzhen Asia Test Technology Co., Ltd.


Report No. ATT2017SZ0510132F2

- Page 43 of 76 -

## 802.11g Middle Channel



Date: 11 JUN 2017 16:11:56



Date: 11 JUN 2017 16:11:41


This document cannot be reproduced except in full, without prior written approval of ATT. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.




# Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT2017SZ0510132F2

- Page 44 of 76 -



Date: 11 JUN 2017 16:12:09



Date: 11 JUN 2017 16:12:20


This document cannot be reproduced except in full, without prior written approval of ATT. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.




# Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT2017SZ0510132F2  
- Page 45 of 76 -

## 802.11g High Channel



Date: 11 JUN 2017 16:10:57




Date: 11 JUN 2017 16:10:45

This document cannot be reproduced except in full, without prior written approval of ATT. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.




# Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT2017SZ0510132F2  
- Page 46 of 76 -



Date: 11 JUN 2017 16:11:08



Date: 11 JUN 2017 16:11:18

This document cannot be reproduced except in full, without prior written approval of ATT. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.






# Shenzhen Asia Test Technology Co., Ltd.


Report No. ATT2017SZ0510132F2

- Page 47 of 76 -

## 802.11n(HT20) Low Channel



Date: 11 JUN 2017 16:16:32




Date: 11 JUN 2017 16:16:22

This document cannot be reproduced except in full, without prior written approval of ATT. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.




# Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT2017SZ0510132F2  
- Page 48 of 76 -



Date: 11 JUN 2017 16:16:41



Date: 11 JUN 2017 16:16:50

This document cannot be reproduced except in full, without prior written approval of ATT. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.







# Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT2017SZ0510132F2  
- Page 49 of 76 -

## 802.11n(HT20) Middle Channel



Date: 11 JUN 2017 16:17:32



Date: 11 JUN 2017 16:17:17


This document cannot be reproduced except in full, without prior written approval of ATT. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.




# Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT2017SZ0510132F2

- Page 50 of 76 -



Date: 11 JUN 2017 16:17:44



Date: 11 JUN 2017 16:17:53


This document cannot be reproduced except in full, without prior written approval of ATT. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.




# Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT2017SZ0510132F2  
- Page 51 of 76 -

## 802.11n(HT20) High Channel



Date: 11 JUN 2017 16:18:30



Date: 11 JUN 2017 16:18:19


This document cannot be reproduced except in full, without prior written approval of ATT. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.




# Shenzhen Asia Test Technology Co., Ltd.

Report No. ATT2017SZ0510132F2

- Page 52 of 76 -



Date: 11 JUN 2017 16:18:41



Date: 11 JUN 2017 16:18:56

This document cannot be reproduced except in full, without prior written approval of ATT. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.