



TEST REPORT

Applicant Name : JEM ACCESSORIES INC.
Address : 32 Brunswick Avenue, Edison, New Jersey, United States 08817
Report Number : RA221109-52746E-RF-00B
FCC ID: 2AHASXCS7-2002

Test Standard (s)

FCC PART 15.247

Sample Description

Product Type: Smart Snapshot Battery Doorbell
Model No.: XCS7-2002
Multiple Model(s) No.: N/A
Trade Mark: XTREME
Date Received: 2022/11/09
Report Date: 2022/12/05

Test Result:	Pass*
--------------	-------

* In the configuration tested, the EUT complied with the standards above.

Prepared and Checked By:

Andy Yu
EMC Engineer

Approved By:

Candy Li
EMC Engineer

Note: This report may contain data that are not covered by the A2LA accreditation and are marked with an asterisk "★".

Shenzhen Accurate Technology Co., Ltd. is not responsible for the authenticity of any test data provided by the applicant. Data included from the applicant that may affect test results are marked with an asterisk "★". Customer model name, addresses, names, trademarks etc. are not considered data.

This report cannot be reproduced except in full, without prior written approval of the Company. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested. This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0.

Shenzhen Accurate Technology Co., Ltd.

1/F., Building A, Changyuan New Material Port, Science & Industry Park, Nanshan District, Shenzhen, Guangdong, P.R. China
Tel: +86 755-26503290 Fax: +86 755-26503396 Web: www.atc-lab.com

TABLE OF CONTENTS

DOCUMENT REVISION HISTORY	4
GENERAL INFORMATION.....	5
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	5
OBJECTIVE	5
TEST METHODOLOGY	5
MEASUREMENT UNCERTAINTY	6
SYSTEM TEST CONFIGURATION	7
DESCRIPTION OF TEST CONFIGURATION	7
EQUIPMENT MODIFICATIONS	8
EUT EXERCISE SOFTWARE	8
DUTY CYCLE	8
SUPPORT EQUIPMENT LIST AND DETAILS	8
EXTERNAL I/O CABLE.....	8
BLOCK DIAGRAM OF TEST SETUP	9
SUMMARY OF TEST RESULTS	10
TEST EQUIPMENT LIST	11
FCC §15.247 (I) & §1.1307 (B) & §2.1091- MPE-BASED EXEMPTION	13
APPLICABLE STANDARD	13
RESULT	13
FCC §15.203 - ANTENNA REQUIREMENT.....	14
APPLICABLE STANDARD	14
ANTENNA CONNECTOR CONSTRUCTION	14
FCC §15.207 (A) – AC LINE CONDUCTED EMISSIONS	15
APPLICABLE STANDARD	15
EUT SETUP	15
EMI TEST RECEIVER SETUP.....	15
TEST PROCEDURE	15
TRANSD FACTOR & MARGIN CALCULATION.....	16
TEST DATA	16
FCC §15.209, §15.205 & §15.247(D) - SPURIOUS EMISSIONS	19
APPLICABLE STANDARD	19
EUT SETUP	19
EMI TEST RECEIVER & SPECTRUM ANALYZER SETUP	20
TEST PROCEDURE	20
FACTOR & MARGIN CALCULATION	20
TEST DATA	20
FCC §15.247(A) (2) – 6 DB EMISSION BANDWIDTH & OCCUPIED BANDWIDTH	30
APPLICABLE STANDARD	30
TEST PROCEDURE	30
TEST DATA	30

FCC §15.247(B) (3) - MAXIMUM CONDUCTED OUTPUT POWER	31
APPLICABLE STANDARD	31
TEST PROCEDURE	31
TEST DATA	31
FCC §15.247(D) – 100 KHZ BANDWIDTH OF FREQUENCY BAND EDGE	32
APPLICABLE STANDARD	32
TEST PROCEDURE	32
TEST DATA	32
FCC §15.247(E) - POWER SPECTRAL DENSITY.....	33
APPLICABLE STANDARD	33
TEST PROCEDURE	33
TEST DATA	33
APPENDIX WI-FI.....	34
APPENDIX A: DTS BANDWIDTH	34
APPENDIX B: OCCUPIED CHANNEL BANDWIDTH	38
APPENDIX C: MAXIMUM CONDUCTED OUTPUT POWER	42
APPENDIX D: MAXIMUM POWER SPECTRAL DENSITY	43
APPENDIX E: BAND EDGE MEASUREMENTS.....	47
APPENDIX F: DUTY CYCLE	49
APPENDIX BLE.....	51
APPENDIX A: DTS BANDWIDTH	51
APPENDIX B: OCCUPIED CHANNEL BANDWIDTH	54
APPENDIX C: MAXIMUM CONDUCTED OUTPUT POWER	57
APPENDIX D: MAXIMUM POWER SPECTRAL DENSITY	60
APPENDIX E: BAND EDGE MEASUREMENT	63
APPENDIX F: DUTY CYCLE	65

DOCUMENT REVISION HISTORY

Revision Number	Report Number	Description of Revision	Date of Revision
0	RA221109-52746E-RF-00B	Original Report	2022/12/05

GENERAL INFORMATION

Product Description for Equipment under Test (EUT)

Frequency Range	BLE: 2402-2480MHz Wi-Fi: 2412-2462MHz
Maximum Conducted Peak Output Power	BLE 1M: 1.84dBm, BLE 2M: 2.49dBm Wi-Fi: 13.00dBm(802.11b), 14.28dBm(802.11g), 14.56dBm(802.11n20)
Modulation Technique	BLE: GFSK Wi-Fi: DSSS, OFDM
Antenna Specification*	2.99dBi (provided by the applicant)
Voltage Range	DC 3.7V from battery or DC 5V from USB port
Sample serial number	1PK8-1 for Radiated Emissions Test and Conducted Emissions Test 1PK9-2 for RF conducted Test (Assigned by ATC)
Sample/EUT Status	Good condition

Objective

This test report is in accordance with Part 2-Subpart J, Part 15-Subparts A and C of the Federal Communication Commission's rules.

The tests were performed in order to determine compliance with FCC Part 15, Subpart C, and section 15.203, 15.205, 15.207, 15.209 and 15.247 rules.

Test Methodology

All measurements contained in this report were conducted with ANSI C63.10-2013, American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices.

And KDB 558074 D01 15.247 Meas Guidance v05r02.

All emissions measurement was performed at Shenzhen Accurate Technology Co., Ltd. The radiated testing was performed at an antenna-to-EUT distance of 3 meters.

Each test item follows test standards and with no deviation.

Measurement Uncertainty

Parameter		Uncertainty
Occupied Channel Bandwidth		5%
RF Frequency		0.082×10^{-7}
RF output power, conducted		0.73dB
Unwanted Emission, conducted		1.6dB
AC Power Lines Conducted Emissions		2.72dB
Emissions, Radiated	9kHz - 30MHz	2.66dB
	30MHz - 1GHz	4.28dB
	1GHz - 18GHz	4.98dB
	18GHz - 26.5GHz	5.06dB
	26.5GHz - 40GHz	4.72dB
Temperature		1°C
Humidity		6%
Supply voltages		0.4%

Note: The extended uncertainty given in this report is obtained by combining the standard uncertainty times the coverage factor K with the 95% confidence interval. Otherwise required by the applicant or Product Regulations, Decision Rule in this report did not consider the uncertainty.

Test Facility

The test site used by Shenzhen Accurate Technology Co., Ltd. to collect test data is located on the 1/F., Building A, Changyuan New Material Port, Science & Industry Park, Nanshan District, Shenzhen, Guangdong, P.R. China.

The test site has been approved by the FCC under the KDB 974614 D01 and is listed in the FCC Public Access Link (PAL) database, FCC Registration No.: 708358, the FCC Designation No.: CN1189. Accredited by American Association for Laboratory Accreditation (A2LA) The Certificate Number is 4297.01.

Listed by Innovation, Science and Economic Development Canada (ISED), the Registration Number is 5077A.

SYSTEM TEST CONFIGURATION

Description of Test Configuration

For 2.4GHz Wi-Fi, total 11 channels are provided to testing:

Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	2412	8	2447
2	2417	9	2452
3	2422	10	2457
4	2427	11	2462
5	2432	/	/
6	2437	/	/
7	2442	/	/

802.11b, 802.11g and 802.11n-HT20 mode was tested with Channel 1, 6 and 11.

For BLE mode, 40 channels are provided to testing:

Channel	Frequency (MHz)	Channel	Frequency (MHz)
0	2402	20	2442
1	2404	21	2444
2	2406	22	2446
3	2408	23	2448
4	2410	24	2450
5	2412	25	2452
6	2414	26	2454
7	2416	27	2456
8	2418	28	2458
9	2420	29	2460
10	2422	30	2462
11	2424	31	2464
12	2426	32	2466
13	2428	33	2468
14	2430	34	2470
15	2432	35	2472
16	2434	36	2474
17	2436	37	2476
18	2438	38	2478
19	2440	39	2480

EUT was tested with Channel 0, 19 and 39.

Equipment Modifications

No modification was made to the EUT tested.

EUT Exercise Software

“FCC_assist_v1.1.5”* exercise software was used, which provided by applicant.

The device was tested with the worst case was performed as below:

Mode	Data rate	Power Level*		
		Low Channel	Middle Channel	High Channel
802.11b	1Mbps	30	30	30
802.11g	6Mbps	30	30	30
802.11n-HT20	MCS0	30	30	30
BLE	1Mbps	6	6	6
BLE	2Mbps	6	6	6

Note: the power level were provided by applicant.

Duty cycle

Please refer to the Appendix Wi-Fi and Appendix BLE.

Support Equipment List and Details


Manufacturer	Description	Model	Serial Number
TECNO	Adapter	U180TSA	Unkown

External I/O Cable


Cable Description	Length (m)	From Port	To
Un-shielded Un-detachable USB cable	1.0	EUT	Adapter

Block Diagram of Test Setup

For conducted emission



For Radiated Emissions



SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Result
§15.247 (i) & §1.1307 (b) & §2.1091	MPE-Based Exemption	Compliant
§15.203	Antenna Requirement	Compliant
§15.207 (a)	AC Line Conducted Emissions	Compliant
§15.205, §15.209, §15.247(d)	Spurious Emissions	Compliant
§15.247 (a)(2)	6 dB Emission Bandwidth & Occupied Bandwidth	Compliant
§15.247(b)(3)	Maximum Conducted Output Power	Compliant
§15.247(d)	100 kHz Bandwidth of Frequency Band Edge	Compliant
§15.247(e)	Power Spectral Density	Compliant

TEST EQUIPMENT LIST

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Conducted Emissions Test					
Rohde& Schwarz	EMI Test Receiver	ESCI	100784	2021/12/13	2022/12/12
Rohde & Schwarz	L.I.S.N.	ENV216	101314	2021/12/13	2022/12/12
Anritsu Corp	50 Coaxial Switch	MP59B	6100237248	2021/12/13	2022/12/12
Unknown	RF Coaxial Cable	No.17	N0350	2021/12/14	2022/12/13
Conducted Emission Test Software: e3 19821b (V9)					
Radiated Emissions Test					
Rohde& Schwarz	Test Receiver	ESR	102725	2021/12/13	2022/12/12
Rohde&Schwarz	Spectrum Analyzer	FSV40	101949	2021/12/13	2022/12/12
SONOMA INSTRUMENT	Amplifier	310 N	186131	2022/11/08	2023/11/07
A.H. Systems, inc.	Preamplifier	PAM-0118P	135	2022/11/08	2023/11/07
Quinstar	Amplifier	QLW-18405536-J0	15964001002	2022/11/08	2023/11/07
Schwarzbeck	Bilog Antenna	VULB9163	9163-323	2021/07/06	2024/07/05
Schwarzbeck	Horn Antenna	BBHA9120D	9120D-1067	2020/01/05	2023/01/04
Schwarzbeck	HORN ANTENNA	BBHA9170	9170-359	2020/01/05	2023/01/04
Radiated Emission Test Software: e3 19821b (V9)					
Unknown	RF Coaxial Cable	No.10	N050	2021/12/14	2022/12/13
Unknown	RF Coaxial Cable	No.11	N1000	2021/12/14	2022/12/13
Unknown	RF Coaxial Cable	No.12	N040	2021/12/14	2022/12/13
Unknown	RF Coaxial Cable	No.13	N300	2021/12/14	2022/12/13
Unknown	RF Coaxial Cable	No.14	N800	2021/12/14	2022/12/13
Unknown	RF Coaxial Cable	No.15	N600	2021/12/14	2022/12/13
Unknown	RF Coaxial Cable	No.16	N650	2021/12/14	2022/12/13
Wainwright	High Pass Filter	WHKX3.6/18 G-10SS	5	2021/12/14	2022/12/13

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
RF Conducted Test					
Rohde&Schwarz	Spectrum Analyzer	FSV-40	101590	2022/01/19	2023/01/18
Tonscend	RF Control Unit	JS0806-2	19G8060182	2022/10/24	2023/10/23
WEINSCHTEL	10dB Attenuator	5324	AU 3842	2021/12/14	2022/12/13
Unknown	RF Coaxial Cable	No.31	RF-01	Each time	Each time

* **Statement of Traceability:** Shenzhen Accurate Technology Co., Ltd. attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

FCC §15.247 (i) & §1.1307 (b) & §2.1091- MPE-Based Exemption

Applicable Standard

According to subpart 15.247 (i) and subpart 2.1091 systems operating under the provisions of this section shall be operated in a manner that ensures the public is not exposed to RF energy level in excess of the communication guidelines.

According to KDB 447498 D04 Interim General RF Exposure Guidance

MPE-Based Exemption:

An alternative to the SAR-based exemption is provided in § 1.1307(b)(3)(i)(C), for a much wider frequency range, from 300 kHz to 100 GHz, applicable for separation distances greater or equal to $\lambda/2\pi$, where λ is the free-space operating wavelength in meters. The MPE-based test exemption condition is in terms of ERP, defined as the product of the maximum antenna gain and the delivered maximum time-averaged power. For this case, a RF source is an RF exempt device if its ERP (watts) is no more than a frequency-dependent value, as detailed tabular form in Appendix B. These limits have been derived based on the basic specifications on Maximum Permissible Exposure (MPE) considered for the FCC rules in § 1.1310(e)(1).

Table 1 to § 1.1307(b)(3)(i)(C) - Single RF Sources Subject to Routine Environmental Evaluation

RF Source frequency (MHz)	Threshold ERP (watts)
0.3-1.34	$1,920 R^2$.
1.34-30	$3,450 R^2/f^2$.
30-300	$3.83 R^2$.
300-1,500	$0.0128 R^2 f$.
1,500-100,000	$19.2 R^2$.

R is the minimum separation distance in meters

f = frequency in MHz

Result

For worst case:

Mode	Frequency (MHz)	Tune up Conducted Power	Antenna Gain		ERP		Evaluation Distance (m)	ERP Limit (mW)
		(dBm)	(dBi)	(dBd)	(dBm)	(mW)		
BLE	2402-2480	3.0	2.99	0.84	3.84	2.421	0.2	768
Wi-Fi	2412-2462	15.0	2.99	0.84	15.84	38.371	0.2	768

Note: 1. The tune up conducted power and antenna gain was declared by the applicant.

2. The BT, Wi-Fi and SRD function cannot simultaneous transmitting.

To maintain compliance with the FCC's RF exposure guidelines, place the equipment at least 20cm from nearby persons.

Result: Compliant.

FCC §15.203 - ANTENNA REQUIREMENT

Applicable Standard

According to § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the user of a standard antenna jack or electrical connector is prohibited. The structure and application of the EUT were analyzed to determine compliance with section §15.203 of the rules. §15.203 state that the subject device must meet the following criteria:

- a. Antenna must be permanently attached to the unit.
- b. Antenna must use a unique type of connector to attach to the EUT.

Unit must be professionally installed, and installer shall be responsible for verifying that the correct antenna is employed with the unit.

And according to FCC 47 CFR section 15.247 (b), if the transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

Antenna Connector Construction

The EUT has one internal antenna which was permanently attached, and the maximum antenna gain is 2.99dBi, fulfill the requirement of this section. Please refer to the EUT photos.


Result: Compliant.

FCC §15.207 (a) – AC LINE CONDUCTED EMISSIONS

Applicable Standard

FCC §15.207(a)

EUT Setup



Note: 1. Support units were connected to second LISN.
2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

The measurement procedure of EUT setup is according with ANSI C63.10-2013. The related limit was specified in FCC Part 15.207.

The spacing between the peripherals was 10 cm.

EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

Frequency Range	IF B/W
150 kHz – 30 MHz	9 kHz

Test Procedure

During the conducted emission test, the adapter was connected to the outlet of the LISN.

Maximizing procedure was performed on the six (6) highest emissions of the EUT.

All final data was recorded in the Quasi-peak and average detection mode.

Transd Factor & Margin Calculation

The Transd factor is calculated by adding LISN VDF (Voltage Division Factor) and Cable Loss. The basic equation is as follows:

$$\text{Transd Factor} = \text{LISN VDF} + \text{Cable Loss}$$

The “**Over limit**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, an Over limit of -7 dB means the emission is 7 dB below the limit. The equation for calculation is as follows:

$$\begin{aligned}\text{Over Limit} &= \text{Level} - \text{Limit} \\ \text{Level} &= \text{Read Level} + \text{Factor}\end{aligned}$$


Test Data

Environmental Conditions

Temperature:	23 °C
Relative Humidity:	60%
ATM Pressure:	101.0 kPa


The testing was performed by Lipa on 2022-11-25.

EUT operation mode: Transmitting (Worst case is 802.11g, low channel)

AC 120V/60 Hz, Line

Site : Shielding Room
 Condition: Line
 Job No. : RA221109-52746E-RF
 Mode : 2.4G WIFI
 Power : AC 120V 60Hz

	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dBuV	dBuV	dBuV	dB	
1	0.163	9.80	8.33	18.13	55.31	-37.18	Average
2	0.163	9.80	20.62	30.42	65.31	-34.89	QP
3	0.202	9.80	8.47	18.27	53.51	-35.24	Average
4	0.202	9.80	18.49	28.29	63.51	-35.22	QP
5	0.406	9.80	7.10	16.90	47.73	-30.83	Average
6	0.406	9.80	15.75	25.55	57.73	-32.18	QP
7	0.521	9.81	12.15	21.96	46.00	-24.04	Average
8	0.521	9.81	18.91	28.72	56.00	-27.28	QP
9	4.366	9.84	7.60	17.44	46.00	-28.56	Average
10	4.366	9.84	16.28	26.12	56.00	-29.88	QP
11	12.466	9.92	18.79	28.71	50.00	-21.29	Average
12	12.466	9.92	23.98	33.90	60.00	-26.10	QP

AC 120V/60 Hz, Neutral

Site : Shielding Room
 Condition: Neutral
 Job No. : RA221109-52746E-RF
 Mode : 2.4G WIFI
 Power : AC 120V 60Hz

	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dBuV	dBuV	dBuV	dB	
1	0.156	9.80	10.30	20.10	55.66	-35.56	Average
2	0.156	9.80	20.79	30.59	65.66	-35.07	QP
3	0.204	9.80	8.45	18.25	53.46	-35.21	Average
4	0.204	9.80	16.97	26.77	63.46	-36.69	QP
5	0.408	9.80	11.20	21.00	47.69	-26.69	Average
6	0.408	9.80	15.80	25.60	57.69	-32.09	QP
7	1.895	9.82	10.34	20.16	46.00	-25.84	Average
8	1.895	9.82	18.10	27.92	56.00	-28.08	QP
9	2.168	9.82	13.25	23.07	46.00	-22.93	Average
10	2.168	9.82	20.15	29.97	56.00	-26.03	QP
11	13.786	10.04	19.74	29.78	50.00	-20.22	Average
12	13.786	10.04	24.91	34.95	60.00	-25.05	QP


FCC §15.209, §15.205 & §15.247(d) - SPURIOUS EMISSIONS

Applicable Standard


FCC §15.247 (d); §15.209; §15.205;

EUT Setup

Below 1 GHz:



Above 1GHz:



The radiated emission tests were performed in the 3 meters test site, using the setup accordance with the ANSI C63.10-2013. The specification used was the FCC 15.209, and FCC 15.247 limits.

EMI Test Receiver & Spectrum Analyzer Setup

During the radiated emission test, the EMI test receiver & Spectrum Analyzer Setup were set with the following configurations:

Frequency Range	RBW	Video B/W	IF B/W	Measurement
30 MHz – 1000 MHz	100 kHz	300 kHz	120 kHz	QP
Above 1 GHz	1MHz	3 MHz	/	PK
	1MHz	10 Hz ^{Note 1}	/	Average
	1MHz	> 1/T ^{Note 2}	/	Average

Note 1: when duty cycle is no less than 98%

Note 2: when duty cycle is less than 98%

Test Procedure

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

Data was recorded in Quasi-peak detection mode for frequency range of 30 MHz-1 GHz, peak and Average detection modes for frequencies above 1 GHz.

Factor & Margin Calculation

The Factor is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain. The basic equation is as follows:

$$\text{Factor} = \text{Antenna Factor} + \text{Cable Loss} - \text{Amplifier Gain}$$

The “**Over Limit/Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, an Over Limit/margin of -7dB means the emission is 7dB below the limit. The equation for calculation is as follows:

$$\begin{aligned} \text{Over Limit/Margin} &= \text{Level} / \text{Corrected Amplitude} - \text{Limit} \\ \text{Level} / \text{Corrected Amplitude} &= \text{Read Level} + \text{Factor} \end{aligned}$$

Test Data

Environmental Conditions

Temperature:	24~25.5°C
Relative Humidity:	52~60%
ATM Pressure:	101.0 kPa

The testing was performed by Jimi Zheng on 2022-11-24 for below 1GHz, and on 2022-11-22 for above 1GHz


EUT operation mode: Transmitting

Note: Pre-scan in the X, Y and Z axes of orientation, the worst case X-axis of orientation was recorded

30MHz-1GHz: (Worst case is 802.11g, low channel)

Note: When the test result of Peak was less than the limit of QP, just the peak value was recorded.


Horizontal:



Site : chamber
Condition: 3m HORIZONTAL
Job No. : RA221109-52746E-RF
Test Mode: 2.4G WIFI

	Freq	Factor	Read Level	Level	Limit	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	44.431	-9.91	28.35	18.44	40.00	-21.56	Peak
2	57.670	-9.94	29.06	19.12	40.00	-20.88	Peak
3	105.595	-11.89	28.91	17.02	43.50	-26.48	Peak
4	276.003	-9.84	36.89	27.05	46.00	-18.95	Peak
5	640.050	-1.92	35.25	33.33	46.00	-12.67	Peak
6	768.075	-0.28	38.03	37.75	46.00	-8.25	Peak

Vertical



Site : chamber
Condition: 3m VERTICAL
Job No. : RA221109-52746E-RF
Test Mode: 2.4G WIFI

	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	46.851	-10.00	29.08	19.08	40.00	-20.92	Peak
2	104.307	-11.77	31.90	20.13	43.50	-23.37	Peak
3	189.572	-11.64	28.88	17.24	43.50	-26.26	Peak
4	276.003	-9.84	31.05	21.21	46.00	-24.79	Peak
5	388.843	-6.93	29.71	22.78	46.00	-23.22	Peak
6	780.633	0.07	29.17	29.24	46.00	-16.76	Peak

1-25 GHz:

Frequency (MHz)	Receiver		Turntable Angle Degree	Rx Antenna		Factor (dB/m)	Absolute Level (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	PK/Ave		Height (m)	Polar (H/V)				
BLE 1M									
Low Channel 2402MHz									
2310	60.88	PK	142	2.3	H	-7.24	53.64	74	-20.36
2310	49.00	AV	142	2.3	H	-7.24	41.76	54	-12.24
2310	60.76	PK	180	2.3	V	-7.24	53.52	74	-20.48
2310	48.89	AV	180	2.3	V	-7.24	41.65	54	-12.35
2390	65.44	PK	347	2	H	-7.22	58.22	74	-15.78
2390	53.22	AV	347	2	H	-7.22	46.00	54	-8.00
2390	64.75	PK	94	1.7	V	-7.22	57.53	74	-16.47
2390	52.61	AV	94	1.7	V	-7.22	45.39	54	-8.61
4804	61.57	PK	258	2.3	H	-3.51	58.06	74	-15.94
4804	51.16	AV	258	2.3	H	-3.51	47.65	54	-6.35
4804	61.78	PK	356	1.1	V	-3.51	58.27	74	-15.73
4804	51.39	AV	356	1.1	V	-3.51	47.88	54	-6.12
Middle Channel 2440MHz									
4880	61.09	PK	270	2.1	H	-3.38	57.71	74	-16.29
4880	50.80	AV	270	2.1	H	-3.38	47.42	54	-6.58
4880	61.32	PK	354	2	V	-3.38	57.94	74	-16.06
4880	51.05	AV	354	2	V	-3.38	47.67	54	-6.33
High Channel 2480MHz									
2483.5	66.83	PK	99	1	H	-7.20	59.63	74	-14.37
2483.5	53.89	AV	99	1	H	-7.20	46.69	54	-7.31
2483.5	65.54	PK	132	1.1	V	-7.20	58.34	74	-15.66
2483.5	52.98	AV	132	1.1	V	-7.20	45.78	54	-8.22
2500	62.95	PK	66	1.5	H	-7.18	55.77	74	-18.23
2500	50.69	AV	66	1.5	H	-7.18	43.51	54	-10.49
2500	62.84	PK	13	2.3	V	-7.18	55.66	74	-18.34
2500	50.57	AV	13	2.3	V	-7.18	43.39	54	-10.61
4960	60.36	PK	159	2	H	-3.01	57.35	74	-16.65
4960	49.93	AV	159	2	H	-3.01	46.92	54	-7.08
4960	60.64	PK	301	1.7	V	-3.01	57.63	74	-16.37
4960	50.47	AV	301	1.7	V	-3.01	47.46	54	-6.54

Frequency (MHz)	Receiver		Turntable Angle Degree	Rx Antenna		Factor (dB/m)	Absolute Level (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	PK/Ave		Height (m)	Polar (H/V)				
BLE 2M									
Low Channel 2402MHz									
2310	61.12	PK	131	1.9	H	-7.24	53.88	74	-20.12
2310	49.08	AV	131	1.9	H	-7.24	41.84	54	-12.16
2310	60.97	PK	95	1.5	V	-7.24	53.73	74	-20.27
2310	48.94	AV	95	1.5	V	-7.24	41.70	54	-12.30
2390	65.70	PK	234	1.9	H	-7.22	58.48	74	-15.52
2390	53.42	AV	234	1.9	H	-7.22	46.20	54	-7.80
2390	64.98	PK	156	2.2	V	-7.22	57.76	74	-16.24
2390	52.60	AV	156	2.2	V	-7.22	45.38	54	-8.62
4804	64.44	PK	336	1.1	H	-3.51	60.93	74	-13.07
4804	53.56	AV	336	1.1	H	-3.51	50.05	54	-3.95
4804	65.30	PK	333	1.4	V	-3.51	61.79	74	-12.21
4804	53.79	AV	333	1.4	V	-3.51	50.28	54	-3.72
Middle Channel 2440MHz									
4880	63.71	PK	47	1.4	H	-3.38	60.33	74	-13.67
4880	53.29	AV	47	1.4	H	-3.38	49.91	54	-4.09
4880	64.36	PK	130	1.5	V	-3.38	60.98	74	-13.02
4880	53.52	AV	130	1.5	V	-3.38	50.14	54	-3.86
High Channel 2480MHz									
2483.5	69.94	PK	32	1.7	H	-7.20	62.74	74	-11.26
2483.5	55.47	AV	32	1.7	H	-7.20	48.27	54	-5.73
2483.5	67.73	PK	202	2.4	V	-7.20	60.53	74	-13.47
2483.5	54.56	AV	202	2.4	V	-7.20	47.36	54	-6.64
2500	63.28	PK	52	1.5	H	-7.18	56.1	74	-17.90
2500	50.97	AV	52	1.5	H	-7.18	43.79	54	-10.21
2500	63.16	PK	316	1.7	V	-7.18	55.98	74	-18.02
2500	50.85	AV	316	1.7	V	-7.18	43.67	54	-10.33
4960	62.82	PK	292	1.2	H	-3.01	59.81	74	-14.19
4960	52.43	AV	292	1.2	H	-3.01	49.42	54	-4.58
4960	63.57	PK	198	1.3	V	-3.01	60.56	74	-13.44
4960	52.70	AV	198	1.3	V	-3.01	49.69	54	-4.31

Wi-Fi:

Frequency (MHz)	Receiver		Turntable Angle Degree	Rx Antenna		Factor (dB/m)	Absolute Level (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	PK/Ave		Height (m)	Polar (H/V)				
802.11b									
Low Channel 2412MHz									
2310	60.19	PK	326	1.3	H	-7.24	52.95	74	-21.05
2310	48.41	AV	326	1.3	H	-7.24	41.17	54	-12.83
2310	60.62	PK	209	2	V	-7.24	53.38	74	-20.62
2310	48.64	AV	209	2	V	-7.24	41.40	54	-12.60
2390	62.50	PK	123	2.1	H	-7.22	55.28	74	-18.72
2390	49.90	AV	123	2.1	H	-7.22	42.68	54	-11.32
2390	63.66	PK	129	2.3	V	-7.22	56.44	74	-17.56
2390	50.05	AV	129	2.3	V	-7.22	42.83	54	-11.17
4824	61.24	PK	92	2.3	H	-3.52	57.72	74	-16.28
4824	54.23	AV	92	2.3	H	-3.52	50.71	54	-3.29
4824	61.60	PK	171	1.8	V	-3.52	58.08	74	-15.92
4824	53.94	AV	171	1.8	V	-3.52	50.42	54	-3.58
Middle Channel 2437MHz									
4874	60.58	PK	194	1.9	H	-3.42	57.16	74	-16.84
4874	53.91	AV	194	1.9	H	-3.42	50.49	54	-3.51
4874	61.28	PK	128	1.5	V	-3.42	57.86	74	-16.14
4874	54.24	AV	128	1.5	V	-3.42	50.82	54	-3.18
High Channel 2462MHz									
2483.5	63.64	PK	213	2.3	H	-7.20	56.44	74	-17.56
2483.5	50.30	AV	213	2.3	H	-7.20	43.1	54	-10.90
2483.5	63.62	PK	170	2.1	V	-7.20	56.42	74	-17.58
2483.5	50.99	AV	170	2.1	V	-7.20	43.79	54	-10.21
2500	62.16	PK	174	1.3	H	-7.18	54.98	74	-19.02
2500	49.04	AV	174	1.3	H	-7.18	41.86	54	-12.14
2500	62.71	PK	131	2.2	V	-7.18	55.53	74	-18.47
2500	49.82	AV	131	2.2	V	-7.18	42.64	54	-11.36
4924	61.54	PK	53	1.7	H	-3.16	58.38	74	-15.62
4924	54.24	AV	53	1.7	H	-3.16	51.08	54	-2.92
4924	61.02	PK	112	1.7	V	-3.16	57.86	74	-16.14
4924	53.93	AV	112	1.7	V	-3.16	50.77	54	-3.23

Frequency (MHz)	Receiver		Turntable Angle Degree	Rx Antenna		Factor (dB/m)	Absolute Level (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	PK/Ave		Height (m)	Polar (H/V)				
802.11g									
Low Channel 2412MHz									
2310	60.32	PK	78	1.5	H	-7.24	53.08	74	-20.92
2310	48.80	AV	78	1.5	H	-7.24	41.56	54	-12.44
2310	60.86	PK	115	2.2	V	-7.24	53.62	74	-20.38
2310	48.19	AV	115	2.2	V	-7.24	40.95	54	-13.05
2390	72.47	PK	159	1.3	H	-7.22	65.25	74	-8.75
2390	55.23	AV	159	1.3	H	-7.22	48.01	54	-5.99
2390	70.60	PK	8	1.5	V	-7.22	63.38	74	-10.62
2390	53.87	AV	8	1.5	V	-7.22	46.65	54	-7.35
4824	59.02	PK	183	2.2	H	-3.52	55.50	74	-18.50
4824	45.01	AV	183	2.2	H	-3.52	41.49	54	-12.51
4824	58.57	PK	295	1.2	V	-3.52	55.05	74	-18.95
4824	45.13	AV	295	1.2	V	-3.52	41.61	54	-12.39
Middle Channel 2437MHz									
4874	57.95	PK	293	2.5	H	-3.42	54.53	74	-19.47
4874	45.26	AV	293	2.5	H	-3.42	41.84	54	-12.16
4874	58.18	PK	97	1.6	V	-3.42	54.76	74	-19.24
4874	45.86	AV	97	1.6	V	-3.42	42.44	54	-11.56
High Channel 2462MHz									
2483.5	76.48	PK	208	2.3	H	-7.20	69.28	74	-4.72
2483.5	58.05	AV	208	2.3	H	-7.20	50.85	54	-3.15
2483.5	75.15	PK	145	1.3	V	-7.20	67.95	74	-6.05
2483.5	56.95	AV	145	1.3	V	-7.20	49.75	54	-4.25
2500	62.63	PK	142	1.1	H	-7.18	55.45	74	-18.55
2500	49.65	AV	142	1.1	H	-7.18	42.47	54	-11.53
2500	62.48	PK	184	2.5	V	-7.18	55.3	74	-18.70
2500	49.72	AV	184	2.5	V	-7.18	42.54	54	-11.46
4924	58.77	PK	53	1	H	-3.16	55.61	74	-18.39
4924	44.97	AV	53	1	H	-3.16	41.81	54	-12.19
4924	57.95	PK	337	1.3	V	-3.16	54.79	74	-19.21
4924	45.35	AV	337	1.3	V	-3.16	42.19	54	-11.81

Frequency (MHz)	Receiver		Turntable Angle Degree	Rx Antenna		Factor (dB/m)	Absolute Level (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	PK/Ave		Height (m)	Polar (H/V)				
802.11n20									
Low Channel 2412MHz									
2310	60.48	PK	320	2.2	H	-7.24	53.24	74	-20.76
2310	48.37	AV	320	2.2	H	-7.24	41.13	54	-12.87
2310	60.79	PK	317	1	V	-7.24	53.55	74	-20.45
2310	48.21	AV	317	1	V	-7.24	40.97	54	-13.03
2390	75.97	PK	124	2.2	H	-7.22	68.75	74	-5.25
2390	56.20	AV	124	2.2	H	-7.22	48.98	54	-5.02
2390	76.15	PK	349	1.1	V	-7.22	68.93	74	-5.07
2390	55.87	AV	349	1.1	V	-7.22	48.65	54	-5.35
4824	57.26	PK	185	2.5	H	-3.52	53.74	74	-20.26
4824	43.83	AV	185	2.5	H	-3.52	40.31	54	-13.69
4824	56.94	PK	89	1.5	V	-3.52	53.42	74	-20.58
4824	44.43	AV	89	1.5	V	-3.52	40.91	54	-13.09
Middle Channel 2437MHz									
4874	57.72	PK	67	2.1	H	-3.42	54.3	74	-19.70
4874	44.82	AV	67	2.1	H	-3.42	41.4	54	-12.60
4874	57.06	PK	20	1	V	-3.42	53.64	74	-20.36
4874	44.79	AV	20	1	V	-3.42	41.37	54	-12.63
High Channel 2462MHz									
2483.5	78.11	PK	44	2.3	H	-7.20	70.91	74	-3.09
2483.5	57.97	AV	44	2.3	H	-7.20	50.77	54	-3.23
2483.5	77.26	PK	240	1.1	V	-7.20	70.06	74	-3.94
2483.5	57.49	AV	240	1.1	V	-7.20	50.29	54	-3.71
2500	62.86	PK	334	1.7	H	-7.18	55.68	74	-18.32
2500	49.18	AV	334	1.7	H	-7.18	42	54	-12.00
2500	62.93	PK	108	2.2	V	-7.18	55.75	74	-18.25
2500	50.00	AV	108	2.2	V	-7.18	42.82	54	-11.18
4924	56.67	PK	294	1.9	H	-3.16	53.51	74	-20.49
4924	43.75	AV	294	1.9	H	-3.16	40.59	54	-13.41
4924	57.05	PK	13	1.5	V	-3.16	53.89	74	-20.11
4924	43.74	AV	13	1.5	V	-3.16	40.58	54	-13.42

Note:

Corrected Factor = Antenna factor (RX) + Cable Loss – Amplifier Factor

Corrected Amplitude = Corrected Factor + Reading


Margin = Corrected. Amplitude - Limit

The other spurious emission which is in the noise floor level was not recorded.


1-18 GHz:

Pre-scan for 802.11 b, High channel

Horizontal




Vertical




18 -25GHz:

Pre-scan for 802.11 b, High channel

Horizontal



Vertical




FCC §15.247(a) (2) – 6 dB EMISSION BANDWIDTH & OCCUPIED BANDWIDTH

Applicable Standard

Systems using digital modulation techniques may operate in the 902–928 MHz, 2400–2483.5 MHz, and 5725–5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

Test Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.
3. Measure the frequency difference of two frequencies that were attenuated 6 dB from the reference level. Record the frequency difference as the emission bandwidth.
4. Repeat above procedures until all frequencies measured were complete.



Test Data

Environmental Conditions

Temperature:	25°C
Relative Humidity:	58%
ATM Pressure:	101.0 kPa

The testing was performed by Cat Kang on 2022-11-26.

EUT operation mode: Transmitting

Test Result: Compliant. Please refer to the Appendix Wi-Fi and Appendix BLE.

FCC §15.247(b) (3) - MAXIMUM CONDUCTED OUTPUT POWER


Applicable Standard

According to FCC §15.247(b) (3), for systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt. As an alternative to a peak power measurement, compliance with the one Watt limit can be based on a measurement of the maximum conducted output power. Maximum Conducted Output Power is defined as the total transmit power delivered to all antennas and antenna elements averaged across all symbols in the signaling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements. The average must not include any time intervals during which the transmitter is off or is transmitting at a reduced power level. If multiple modes of operation are possible (e.g., alternative modulation methods), the maximum conducted output power is the highest total transmit power occurring in any mode.

Test Procedure


1. Place the EUT on a bench and set it in transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to one test equipment.
3. Add a correction factor to the display.

For wifi mode:



Note: the RF control unit has a built-in power sensor.

For BLE mode:



Test Data

Environmental Conditions

Temperature:	25°C
Relative Humidity:	58%
ATM Pressure:	101.0 kPa

The testing was performed by Cat Kang on 2022-11-26.

EUT operation mode: Transmitting

Test Result: Compliant. Please refer to the Appendix Wi-Fi and Appendix BLE.


FCC §15.247(d) – 100 kHz BANDWIDTH OF FREQUENCY BAND EDGE

Applicable Standard

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

Test Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range, and make sure the instrument is operated in its linear range.
3. Set RBW to 100 kHz and VBW of spectrum analyzer to 300 kHz with a convenient frequency span including 100 kHz bandwidth from band edge.
4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
5. Repeat above procedures until all measured frequencies were complete.



Test Data

Environmental Conditions

Temperature:	25°C
Relative Humidity:	58%
ATM Pressure:	101.0 kPa

The testing was performed by Cat Kang on 2022-11-26.

EUT operation mode: Transmitting

Test Result: Compliant.

Conducted Band Edge Result:

Please refer to the Appendix Wi-Fi and Appendix BLE.


FCC §15.247(e) - POWER SPECTRAL DENSITY

Applicable Standard

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of paragraph (b) of this section. The same method of determining the conducted output power shall be used to determine the power spectral density.

Test Procedure

1. Use this procedure when the maximum peak conducted output power in the fundamental emission is used to demonstrate compliance.
2. Set the RBW to: $3\text{ kHz} \leq \text{RBW} \leq 100\text{ kHz}$.
3. Set the VBW $\geq 3 \times \text{RBW}$.
4. Set the span to 1.5 times the DTS bandwidth.
5. Detector = peak.
6. Sweep time = auto couple.
7. Trace mode = max hold.
8. Allow trace to fully stabilize.
9. Use the peak marker function to determine the maximum amplitude level within the RBW.
10. If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.



Test Data

Environmental Conditions

Temperature:	25°C
Relative Humidity:	58%
ATM Pressure:	101.0 kPa

The testing was performed by Cat Kang on 2022-11-26.

EUT operation mode: Transmitting


Test Result: Compliant. Please refer to the Appendix Wi-Fi and Appendix BLE.


APPENDIX Wi-Fi


Appendix A: DTS Bandwidth Test Result

Test Mode	Antenna	Frequency[MHz]	DTS BW [MHz]	FL[MHz]	FH[MHz]	Limit[MHz]	Verdict
11B	Ant1	2412	10.12	2406.92	2417.04	0.5	PASS
		2437	10.12	2431.92	2442.04	0.5	PASS
		2462	10.12	2456.92	2467.04	0.5	PASS
11G	Ant1	2412	15.36	2404.24	2419.60	0.5	PASS
		2437	15.48	2429.12	2444.60	0.5	PASS
		2462	15.48	2454.12	2469.60	0.5	PASS
11N20SISO	Ant1	2412	15.48	2404.12	2419.60	0.5	PASS
		2437	15.80	2429.12	2444.92	0.5	PASS
		2462	15.48	2454.12	2469.60	0.5	PASS

Test Graphs









**Appendix B: Occupied Channel Bandwidth
Test Result**

Test Mode	Antenna	Channel Frequency [MHz]	OCB [MHz]	FL[MHz]	FH[MHz]	Limit[MHz]	Verdict
11B	Ant1	2412	13.986	2405.087	2419.073	---	---
		2437	14.026	2429.847	2443.873	---	---
		2462	14.026	2454.887	2468.913	---	---
11G	Ant1	2412	17.303	2403.369	2420.671	---	---
		2437	17.343	2428.329	2445.671	---	---
		2462	17.303	2453.329	2470.631	---	---
11N20SISO	Ant1	2412	17.982	2403.009	2420.991	---	---
		2437	18.022	2428.009	2446.031	---	---
		2462	18.182	2452.929	2471.111	---	---


Test Graphs




11G_Ant1_2412




11G_Ant1_2437



11G_Ant1_2462






**Appendix C: Maximum conducted output power
Test Result**


Test Mode	Antenna	Frequency[MHz]	Peak Power[dBm]	Conducted Limit[dBm]	Verdict
11B	Ant1	2412	13.00	≤30.00	PASS
		2437	12.03	≤30.00	PASS
		2462	11.83	≤30.00	PASS
11G	Ant1	2412	14.28	≤30.00	PASS
		2437	13.74	≤30.00	PASS
		2462	13.95	≤30.00	PASS
11N20SISO	Ant1	2412	14.56	≤30.00	PASS
		2437	13.96	≤30.00	PASS
		2462	14.11	≤30.00	PASS


**Appendix D: Maximum power spectral density
Test Result**

Test Mode	Antenna	Frequency[MHz]	Result[dBm/3kHz]	Limit[dBm/3kHz]	Verdict
11B	Ant1	2412	-17.5	≤8.00	PASS
		2437	-18.45	≤8.00	PASS
		2462	-18.78	≤8.00	PASS
11G	Ant1	2412	-18.96	≤8.00	PASS
		2437	-20.52	≤8.00	PASS
		2462	-20.04	≤8.00	PASS
11N20SISO	Ant1	2412	-18.88	≤8.00	PASS
		2437	-18.94	≤8.00	PASS
		2462	-18.26	≤8.00	PASS

Test Graphs








Appendix E: Band edge measurements

Test Graphs


11B Ant1_Low_2412




11B Ant1_High_2462



11G Ant1_Low_2412




11G Ant1_High_2462




Date: 26.NOV.2022 05:16:16

11N20SISO Ant1_Low_2412



Date: 26.NOV.2022 05:17:56

11N20SISO Ant1_High_2462




Date: 26.NOV.2022 05:20:52

**Appendix F: Duty Cycle
Test Result**

Test Mode	Antenna	Frequency[MHz]	Transmission Duration [ms]	Transmission Period [ms]	Duty Cycle [%]
11B	Ant1	2437	4.53	4.80	94.38
11G	Ant1	2437	0.75	1.07	70.09
11N20SISO	Ant1	2437	0.71	0.90	78.89

Test Graphs




APPENDIX BLE

Appendix A: DTS Bandwidth Test Result

Test Mode	Antenna	Frequency[MHz]	DTS BW [MHz]	FL[MHz]	FH[MHz]	Limit[MHz]	Verdict
BLE_1M	Ant1	2402	0.65	2401.68	2402.33	0.5	PASS
		2440	0.65	2439.68	2440.33	0.5	PASS
		2480	0.65	2479.68	2480.33	0.5	PASS
BLE_2M	Ant1	2402	1.16	2401.43	2402.59	0.5	PASS
		2440	1.16	2439.43	2440.59	0.5	PASS
		2480	1.16	2479.42	2480.59	0.5	PASS

Test Graphs







**Appendix B: Occupied Channel Bandwidth
Test Result**

Test Mode	Antenna	Frequency[MHz]	OCB [MHz]	FL[MHz]	FH[MHz]	Limit[MHz]	Verdict
BLE_1M	Ant1	2402	1.027	2401.500	2402.527	---	---
		2440	1.031	2439.497	2440.527	---	---
		2480	1.027	2479.500	2480.527	---	---
BLE_2M	Ant1	2402	2.05	2401.005	2403.055	---	---
		2440	2.058	2438.997	2441.055	---	---
		2480	2.054	2479.001	2481.055	---	---

Test Graphs







**Appendix C: Maximum conducted output power
Test Result**

Test Mode	Antenna	Frequency[MHz]	Conducted Peak Power [dBm]	Conducted Limit [dBm]	Verdict
BLE_1M	Ant1	2402	1.84	≤30	PASS
		2440	1.07	≤30	PASS
		2480	0.65	≤30	PASS
BLE_2M	Ant1	2402	2.49	≤30	PASS
		2440	1.59	≤30	PASS
		2480	1.42	≤30	PASS

Test Graphs







**Appendix D: Maximum power spectral density
Test Result**


Test Mode	Antenna	Frequency[MHz]	Result[dBm/3kHz]	Limit[dBm/3kHz]	Verdict
BLE_1M	Ant1	2402	-15.44	≤8.00	PASS
		2440	-16.32	≤8.00	PASS
		2480	-16.68	≤8.00	PASS
BLE_2M	Ant1	2402	-18.15	≤8.00	PASS
		2440	-19.00	≤8.00	PASS
		2480	-19.27	≤8.00	PASS


Test Graphs





Appendix E: Band edge measurement Test Graphs





Appendix F: Duty Cycle Test Result

Test Mode	Antenna	Freq(MHz)	ON Time [ms]	Period [ms]	DC [%]
BLE_1M	Ant1	2440	2.12	2.50	84.80
BLE_2M	Ant1	2440	1.07	2.50	42.80

Test Graphs



***** END OF REPORT *****