



**EMC Technologies Pty Ltd**

ABN 82 057 105 549

57 Assembly Drive

Tullamarine Victoria Australia 3043

Ph: + 613 9335 3333

Fax: + 613 9338 9260

email: melb@emctech.com.au

**EMI TEST REPORT FOR CERTIFICATION  
to  
FCC PART 15 Subpart E (Section 15.407) & RSS-210**

**FCC ID:** EJE-WB0014

**Industry Canada ID:** 337J-WB0014

**Test Sample:** LifeBook E Series

**Model:** E8010 (Emilia2)

**Radio Modules:** Mini-PCI WLAN (Calexico2 11a+b/g), Model:  
WM3B2915ABG & Bluetooth, Model UGXZ5-102A

**Report Number** M040905\_Cert\_Emilia2\_Cal2\_11abg\_NII\_BT

**Tested for:** Fujitsu Australia Ltd.

**Issue Date:** 8<sup>th</sup> October 2004

EMC Technologies Pty Ltd reports apply only to the specific samples tested under stated test conditions. It is the manufacturer's responsibility to assure that additional production units of this model are manufactured with identical electrical and mechanical components. EMC Technologies Pty Ltd shall have no liability for any deductions, inferences or generalisations drawn by the client or others from EMC Technologies Pty Ltd issued reports. This report shall not be used to claim, constitute or imply product endorsement by EMC Technologies Pty Ltd.



The tests, calibrations or measurements covered by this document have been performed in accordance with NATA requirements which include the requirements of ISO/IEC 17025 and are traceable to national standards of measurement. This document shall not be reproduced, except in full.

**NATA Accredited Laboratory  
Number: 5292**

**EMI TEST REPORT FOR CERTIFICATION  
to  
FCC PART 15 Subpart E (Section 15.407) & RSS-210**

**EMC Technologies Report No. M040905\_Cert\_Emilia2\_Cal2\_11abg\_NII\_BT**

**Issue Date: 8<sup>th</sup> October 2004**

**CONTENTS**

- 1.0 INTRODUCTION**
- 2.0 GENERAL INFORMATION**

**RESULTS – WLAN, WM3B2915ABG (802.11a of Callexico2 11a+b/g)\***

- 1.0 CONDUCTED EMI MEASUREMENTS**
- 2.0 RADIATED EMI MEASUREMENTS**
- 3.0 PEAK OUTPUT POWER**
- 4.0 CHANNEL BANDWIDTH**
- 5.0 RADIO FREQUENCY EXPOSURE**
- 6.0 PEAK POWER SPECTRAL DENSITY**
- 7.0 PEAK EXCURSION**
- 8.0 FREQUENCY STABILITY**
- 9.0 ANTENNA REQUIREMENT**
- 10.0 COMPLIANCE STATEMENT**

**\*RESULTS of 802.11b/g and 802.11a (5725 – 5850 MHz):**

**Refer to Report No: M040905\_Cert\_Emilia2\_Cal2\_11abg\_DTS\_BT**

**RESULTS – Bluetooth, UGXZ5-102A**

**Refer to Report No: M040905\_Cert\_Emilia2\_BT\_Cal2\_11abg**

- APPENDIX A: MEASUREMENT INSTRUMENTATION DETAILS**
- APPENDIX B: REPORT PHOTOGRAPHS**
- APPENDIX C: FUNCTIONAL DESCRIPTION**
- APPENDIX D: BLOCK DIAGRAM**
- APPENDIX E: SCHEMATICS**
- APPENDIX F: ANTENNA INFORMATION (INVERTED-F ANTENNA)**
- APPENDIX G: FCC LABELLING DETAILS**
- APPENDIX H: USER MANUAL**
- APPENDIX I: GRAPHS of EMI MEASUREMENTS**
- APPENDIX J: CHANNEL BANDWIDTH PLOTS**
- APPENDIX K: BANDEDGE PLOTS**
- APPENDIX L: PEAK POWER SPECTRAL DENSITY PLOTS**
- APPENDIX M: PEAK EXCURSION PLOTS**
- APPENDIX N: HARMONICS PLOTS**
- APPENDIX O: PEAK POWER**

**Attachment 1: RF Exposure Information**

**Attachment 2: FCC DOC for LifeBook Emilia2 E Series (E8010)**



# EMI TEST REPORT FOR CERTIFICATION to FCC PART 15 Subpart E (Section 15.407) & RSS-210

**Report Number:** M040905\_Cert\_Emilia2\_Cal2\_11abg\_NII\_BT

**Test Sample:** LifeBook E Series  
**Model:** E8010 (Emilia2)

**Radio Modules:** Mini-PCI WLAN, Model: WM3B2915ABG (Intel Corp.)  
Bluetooth, Model: UGXZ5-102A (Fujitsu Ltd)

**FCC ID:** EJE-WB0014  
**Industry Canada ID:** 337J-WB0014  
**Equipment Type:** Intentional Radiator (Transceiver)

**Manufacturer (LifeBook):** Fujitsu Ltd  
**Address:** 1405, Ohamaru, Inagi-shi, Tokyo 206-8503, Japan  
**Contact:** Mr. Hirotaka Yakame

**Tested for:** Fujitsu Australia Ltd  
**Address:** 5 Lakeside Drive,  
Burwood East, VIC 3151 Australia  
**Phone:** +613 9845 4300  
**Fax:** +613 9845 4600  
**Contact:** Mr Praveen Rao – Senior Compliance Engineer

**Test Standards:** FCC Part 15, Subpart E – Unlicensed National Information,  
Infrastructure Devices  
FCC Part 15.407, General Technical Requirements  
ANSI C63.4 – 2003  
OET Bulletin No. 65  
  
RSS-210 Issue 5 Low Power Licence-Exempt RadioCommunication  
Devices: 6.2.2 (q1) 5150 - 5350 MHz & 5725-5825 MHz Local Area  
Network Devices  
  
RSS-102 Issue 1 (Provisional), Evaluation Procedure for Mobile and  
Portable Radio Transmitters with respect to Health Canada's Safety  
Code 6 for Exposure of Humans to Radio Frequency Fields

**Test Dates:** 11<sup>th</sup> August to 6<sup>th</sup> October 2004

**Test Officers:**

  
Chieu Huynh  
Jorge Lara

**B.Eng (Hons) Electronics**

**Attestation:**

*I hereby certify that the device(s) described herein were tested as described in this report and that the data included is that which was obtained during such testing.*

**Authorised Signatory:**

  
Chris Zombolas  
Technical Director  
EMC Technologies Pty Ltd



## EMI TEST REPORT FOR CERTIFICATION to FCC PART 15 Subpart E (Section 15.407) & RSS-210

### 1.0 INTRODUCTION

EMI testing was performed on test sample LifeBook E Series, Model E8010 (Emilia2) with Mini-PCI Wireless LAN Module (Calexico2 11a+b/g), Model WM3B2915ABG & Bluetooth, Model UGXZ5-102A.

The Calexico2 WLAN supports IEEE 802.11b, IEEE 802.11g and IEEE802.11a (DTS & U-NII) configurations. Tests were performed in all three configurations and also on the Bluetooth.

The results for configurations IEEE 802.11a (U-NII: 5150 – 5350 MHz) are reported in this test report.

The results for configurations IEEE 802.11b, IEEE 802.11g and IEEE802.11a (DTS: 5725 – 5850 MHz) and Bluetooth are reported separately.

Refer to EMC Technologies' test report: M040905\_Cert\_Emilia2\_Cal2\_11abg\_DTS\_BT (802.11b/g and 802.11a: DTS) and M040905\_Cert\_Emilia2\_BT\_Cal2\_11abg (Bluetooth).

Test results and procedures were performed in accordance with the following Federal Communications Commission (FCC) standards/regulations:

|                             |   |
|-----------------------------|---|
| 47 CFR, Part 15, Subpart E: | Unlicensed National Information Infrastructure Devices (U-NII) operating in the 5.15-5.35 GHz and 5.725-5.825 GHz frequency bands |
| Section 15.203:             | Antenna requirements  |
| Section 15.205:             | Restricted bands of operation   |
| Section 15.207:             | Conducted Emission Limits   |
| Section 15.209:             | Radiated Emission Limits (General requirements)   |
| Section 15.407:             | General Technical Requirements  |

The results and technical details of the test sample are detailed in this report. The test sample **complies** with the requirements of 47 CFR, Part 15 Subpart E - Section 15.407.

The test sample also complies with the Industry Canada RSS-210 issue 5 (Low Power Licence-Exempt Radiocommunication Devices (All Frequency Bands)) clause 6.2.2(q1) requirements and the RF exposure requirements of RSS-102.

### 1.1 Summary of Results

#### 1.1.1 WLAN, Calexico2 802.11a (U-NII) - FCC Subpart E, Section 15.407

| FCC Part 15, Subpart E Clauses | Industry Canada RSS-210 Clauses | Test Performed               | Result                |
|--------------------------------|---------------------------------|------------------------------|-----------------------|
| 15.203                         | 5.5                             | Antenna Requirement          | <b>Not Applicable</b> |
| 15.205                         | 6.3                             | Operation in Restricted Band | <b>Complies</b>       |
| 15.207                         | 6.6                             | Conducted Emissions          | <b>Complies</b>       |
| 15.209                         | 6.3                             | Radiated Emissions           | <b>Complies</b>       |
| 15.407 (a)(4)                  | 6.2.2(q1)                       | Peak Transmit Power          | <b>Complies</b>       |
| 15.407 (a)(5)                  | 6.2.2(q1)                       | Peak Power Spectral Density  | <b>Complies</b>       |
| 15.407 (a)(6)                  |                                 | Peak Excursion               | <b>Complies</b>       |
| 15.407 (b)                     | 6.2.2(q1)                       | Undesirable Emission         | <b>Complies</b>       |
| 15.407 (f)                     |                                 | Radio Frequency Hazard       | <b>Complies</b>       |
| 15.407 (g)                     | 6.4                             | Frequency Stability          | <b>Complies</b>       |



**1.1.2 WLAN, Calexico2 802.11b, 802.11g and 802.11a (DTS) - FCC Subpart C, Section 15.247**

| FCC Part 15, Subpart C Clauses | Industry Canada RSS-210 Clauses | Test Performed               | Result         |
|--------------------------------|---------------------------------|------------------------------|----------------|
| 15.203                         | 5.5                             | Antenna Requirement          | Not Applicable |
| 15.205                         | 6.3                             | Operation in Restricted Band | Complies       |
| 15.207                         | 6.6                             | Conducted Emissions          | Complies       |
| 15.209                         | 6.3                             | Radiated Emissions           | Complies       |
| 15.247 (a)(2)                  | 6.2.2(o)(iv)                    | Channel Bandwidth            | Complies       |
| 15.247 (b)(3)                  | 6.2.2(o)(b)                     | Peak Output Power            | Complies       |
| 15.247 (b)(5)                  |                                 | Radio Frequency Hazard       | Complies       |
| 15.247 (c)                     | 6.2.2(o)(e1)                    | Out of Band Emissions        | Complies       |
| 15.247 (d)                     | 6.2.2(o)(iv)                    | Peak Power Spectral Density  | Complies       |

Refer to EMC Technologies Report No: M040905\_Cert\_Emilia2\_Cal2\_11abg\_DTS\_BT

**1.1.3 Bluetooth - FCC Subpart C, Section 15.247**

| FCC Part 15, Subpart C Clauses | Industry Canada RSS-210 Clauses | Test Performed               | Result         |
|--------------------------------|---------------------------------|------------------------------|----------------|
| 15.203                         | 5.5                             | Antenna Requirement          | Not Applicable |
| 15.205                         | 6.3                             | Operation in Restricted Band | Complies       |
| 15.207                         | 6.6                             | Conducted Emissions          | Complies       |
| 15.209                         | 6.3                             | Radiated Emissions           | Complies       |
| 15.247 (a)(1)&(3)              | 6.2.2(o)(ii)                    | Channel Occupancy/Bandwidth  | Complies       |
| 15.247 (b)(1)                  | 6.2.2(o)(b)                     | Peak Output Power            | Complies       |
| 15.247 (b)(5)                  |                                 | Radio Frequency Hazard       | Complies       |
| 15.247 (c)                     | 6.2.2(o)(e1)                    | Out of Band Emissions        | Complies       |

Refer to EMC Technologies Report No: M040905\_Cert\_Emilia2\_BT\_Cal2\_11abg

The measurement procedure used was in accordance with ANSI C63.4-2003 and OET Bulletin No. 65. The instrumentation conformed to the requirements of ANSI C63.2-1996.

**1.2 Modifications by EMC Technologies**

No modifications were required.



## 2.0 GENERAL INFORMATION

(Information supplied by the Client)

### 2.1 Product Details

|                                    |   |
|------------------------------------|---|
| <b>Test Sample:</b>                | LifeBook E series   |
| <b>Codenames:</b>                  | E8010   |
| <b>Model Name:</b>                 | Emilia2   |
| <b>LifeBook rating:</b>            | 80W (19V, 4.22A)  |
| <b>Serial Number:</b>              | Pre-production Sample   |
| <b>Manufacturer:</b>               | FUJITSU LIMITED   |
|                                    |   |
| <b>CPU Type and Speed:</b>         | Dothan 2.1 GHz<br>Banias 1.7 GHz<br>Celeron-M 1.7 GHz               |
| <b>SDRAM:</b>                      | 1GB   |
| <b>LCD Screen:</b>                 | 14"XGA / 15"XGA / 15"SXGA / 15"UXGA<br>(Mg-Al alloy LCD back cover) |
| <b>Hard Disk Drive:</b>            | 20GB  |
| <b>Wired LAN:</b>                  | BroadCom5705(1000Base) / BroadCom5788(1000Base)                     |
| <b>Modem:</b>                      | MBH7MD33 / MBH7MD35   |
| <b>Wireless LAN (WLAN) Module:</b> | Calexico2 (11abg) WM3B2915ABG                                       |
| <b>Bluetooth:</b>                  | ALPS Bluetooth  |
| <b>Bluetooth Model Number:</b>     | UGXZ5-102A  |
| <b>Port Replicator Model:</b>      | FPCPR48   |
|                                    |   |
| <b>AC Adapter Model:</b>           | SEB100P2-19.0   |
| <b>Alternate Models:</b>           | CA01007-092X  |
| <b>Voltage:</b>                    | 19 V  |
| <b>Current Specs:</b>              | 4.22 A  |
| <b>Watts:</b>                      | 80 W  |
|                                    |   |
| <b>Radio Modules:</b>              | WLAN (Calexico2 11a+b/g) and Bluetooth                              |
| <b>WLAN Model Number:</b>          | WM3B2915ABG   |
| <b>WLAN Manufacturer:</b>          | Intel Corporation   |
| <b>Interface Type:</b>             | Mini-PCI Wireless LAN Module  |
| <b>Bluetooth Model Number:</b>     | UGXZ5-102A  |
| <b>Bluetooth Manufacturer:</b>     | Fujitsu Ltd   |
| <b>FCC ID:</b>                     | EJE-WB0014  |
| <b>Industry Canada ID:</b>         | 337J-WB0014   |
| <b>Equipment Type:</b>             | Intentional Radiator (Transceiver)                                  |



## 2.2 Technical Specifications

### 2.2.1 WLAN Transmitter Specifications

|                            |  |
|----------------------------|--|
| <b>Transmitter #1:</b>     | Mini-PCI Wireless LAN Module   |
| <b>Wireless Module:</b>    | Calexico2 (11a+b/g)  |
| <b>Model Number:</b>       | WM3B2915ABG  |
| <b>Manufacturer:</b>       | Intel Corporation  |
| <b>Modulation Type:</b>    | Direct Sequence Spread Spectrum (DSSS for 802.11b)<br>Orthogonal Frequency Division Multiplexing (OFDM for 802.11g)<br>Orthogonal Frequency Division Multiplexing (OFDM for 802.11a) |
| <b>802.11a</b>             | BPSK – 6Mbps, 9Mbps<br>QPSK – 12Mbps, 18Mbps<br>16QAM – 24Mbps, 36Mbps<br>64QAM – 48Mbps, 54Mbps   |
| <b>802.11g</b>             | BPSK – 6Mbps, 9Mbps<br>QPSK – 12Mbps, 18Mbps<br>16QAM – 24Mbps, 36Mbps<br>64QAM – 48Mbps, 54Mbps   |
| <b>802.11b</b>             | DBPSK – 1Mbps<br>DQPSK – 2Mbps<br>CCK – 5.5Mbps, 11Mbps  |
| <b>Maximum Data Rate:</b>  | 802.11b = 11Mbps, 802.11g and 802.11a = 54Mbps   |
| <b>Frequency Range:</b>    | 2.4 – 2483.5 GHz for 11b/g<br>5.15 - 5.35 GHz and 5.725 - 5.850 GHz for 11a  |
| <b>Number of Channels:</b> | 11 channels for 11b or 11g<br>13 channels for 11a  |
| <b>Antenna Types:</b>      | Inverted-F Antenna – PN: CP115412-01   |
| <b>Max. Output Power:</b>  | 802.11b = 15 dBm<br>802.11g = 14 dBm<br>802.11a = 10-14 dBm  |
| <b>Power Supply:</b>       | 3.3 VDC from PCI bus   |
| <b>Chipset Used:</b>       | 82533MDE and 82533RGE  |

#### Frequency allocation for 802.11b/g:

| Channel Number | Frequency (MHz) | EUT Power level setting dBm |         |
|----------------|-----------------|-----------------------------|---------|
|                |                 | 802.11b                     | 802.11g |
| 1              | 2412            | 15                          | 14      |
| 2              | 2417            | 15                          | 14      |
| 3              | 2422            | 15                          | 14      |
| 4              | 2427            | 15                          | 14      |
| 5              | 2432            | 15                          | 14      |
| 6              | 2437            | 15                          | 14      |
| 7              | 2442            | 15                          | 14      |
| 8              | 2447            | 15                          | 14      |
| 9              | 2452            | 15                          | 14      |
| 10             | 2457            | 15                          | 14      |
| 11             | 2462            | 15                          | 14      |



**Frequency allocation for 802.11a:**

| Channel Number                           | Frequency (MHz) | Power level setting dBm |
|--|-----------------|-------------------------|
| *Channels reported in the DTS submission |                 |                         |
| 149                                      | 5745*           | 14                      |
| 153                                      | 5765            | 14                      |
| 157                                      | 5785*           | 14                      |
| 161                                      | 5805            | 14                      |
| 165                                      | 5825*           | 14                      |
| *Channels reported in this report        |                 |                         |
| 36                                       | 5180*           | 10                      |
| 40                                       | 5200            | 10                      |
| 44                                       | 5220            | 10                      |
| 48                                       | 5240            | 10                      |
| 52                                       | 5260*           | 14                      |
| 56                                       | 5280            | 14                      |
| 60                                       | 5300            | 14                      |
| 64                                       | 5320*           | 14                      |

**2.2.2 Bluetooth Transmitter Specifications**

**Transmitter#2:** Bluetooth  
**Model Number:** UGXZ5-102A  
**Manufacturer:** Fujitsu Ltd  
**Network Standard:** Bluetooth™ RF Test Specification  
**Modulation Type:** Frequency Hopping Spread Spectrum (FHSS)  
**Frequency Range:** 2.4 –2483.5 GHz  
**Number of Channels:** 79  
**Carrier Spacing:** 1.0 MHz  
**Antenna Types:** Inverted-F Antenna – PN: CP115412-01  
**Max. Output Power:** 12 dBm  
**Reference Oscillator:** 16 MHz (Built-in)  
**Power Supply:** 3.3 VDC from host.

**Frequency allocation:**

| Channel Number | Frequency (MHz) |
|----------------|-----------------|
| 1              | 2402            |
| 2              | 2403            |
| 3              | 2404            |
| .              | .               |
| .              | .               |
| .              | .               |
| 39             | 2440            |
| 40             | 2441            |
| 41             | 2442            |
| .              | .               |
| .              | .               |
| .              | .               |
| 77             | 2478            |
| 78             | 2479            |
| 79             | 2480            |





## 2.3 Operational Description

The EUT is a LifeBook E Series, Model E8010 (Emilia2) installed with a Mini-PCI Wireless LAN (WLAN) Module (Calexico2 11a+b/g, Model WM3B2915ABG) & Bluetooth, Model UGXZ5-102A.

The WLAN module is an OEM product from Intel Corporation, which is already certified by the manufacturer FCC ID: PD9WM3B2915ABG and IC: 1000M-3B2915.

The ALPS Bluetooth has been previously certified by the manufacturer, Fujitsu Ltd under FCC ID: EJE-WB0002 and IC: 337J-WB0002 for a different host.

The intention of this application is to certify this WLAN and Bluetooth with a Inverted-F Antenna combination in host – LifeBook E Series, Model E8010 (Emilia2)

The measurements reported in this test report are for WLAN (Calexico2 11a+b/g, Model WM3B2915ABG) and Bluetooth (UGXZ5-102A) with Inverted-F Antenna in Host PC, LifeBook E Series, Model E8010 (Emilia2).

## 2.4 Test Configuration

The Intel WLAN software and the BlueSuiteCasira software were used to set-up the WLAN module and Bluetooth devices respectively to continuously transmit during the tests. The LCD screen was observed for the transmitter status shown for the respective software.

Data Transmission is always initiated by software, which is then passed down through the MAC, through the digital and analog baseband, finally to the RF chip. Several special packets (ACKs, CTS, PSpoll, etc) are initiated by the MAC. These are the only ways the digital baseband portion will turn on the RF transmitter, which then turns off at the end of the packet. Therefore, the transmitter will be ON only while one of the four mentioned packets is being transmitted.

### Antenna

The Calexico2 (11a+b/g) WLAN, Model WM3B2915ABG and ALPS Bluetooth device, Model UGXZ5-102A are configured with Inverted-F Antenna – PN: CP115412-01. The installation of the Intel WLAN module, Bluetooth Device and the Antenna in Fujitsu LifeBook E Series, Model E8010 (Emilia2) is in a controlled environment. The installation is performed during the production/assembly process at the Fujitsu factory.

Refer to Appendix F – Antenna Information.

There are two antennas: Main antenna is located on the right hand side of the LCD screen and Aux antenna is located on the left hand side of the LCD screen.

WLAN and Bluetooth simultaneous function: WLAN transmit via Main antenna and Bluetooth via Aux antenna

WLAN Only function: Transmit via Main antenna OR Aux antenna

Bluetooth Only function: Transmit via Aux antenna only

Refer to photos in Appendix B3 for Antenna locations.

### AC Adapter

The AC adapter SEB100P2-19.0 was used for all the tests. This adapter is also identified as CA01007-092X. The manufacturer has stated that all these adapters are identical electrically and mechanically.

## 2.5 Block Diagram

Refer to Appendix D - Block Diagram



## 2.6 Support Equipment

### External Monitor/s:

Conducted EMI Videocom, Model DCM-1588VAE, FCC ID: H79DCM-1588  
Radiated EMI Hewlett Packard 15" Color monitor, Model D2827A,  
FCC ID: C5F7NFCMC1515X

### Printer:

Diconix, Model: 150, FCC ID: E759WG-RBCN150

### USB Floppy Drives:

Fujitsu Model: FPCFDD11, P/N CP032173-01  
Fujitsu Model: FPCFDD12, P/N CP078720-01  
USB OMNI Floppy Drive Model # USB F3501 SN W316000096

### Headphones:

Verbatim Multimedia Stereo headset

### PS2 Keyboard

Logitech, Model: YBA9, S/N MCT94602411

### PS2 Mouse

A4 Tech M/N: SWW-25

### LAN Hub:

Kingston SOHO Hub Model: KNE8TP/H (FCC ID: JICKNE8TP-HO)

### Modem:

Maestro Companion Series 3

### PCMCIA Slot:

6 MB Compact flash card with Adapter, Apacer P/N 88.10200030

## 2.7 Test Procedure

Emissions measurements were performed in accordance with the procedures of ANSI C63.4-2003. Radiated emissions tests were performed at a distance of 3 and 10 metres from the EUT. OET Bulletin 65 dated June 2001 was used for reference.

## 2.8 Test Facility

### 2.8.1 General

Radiated Emission measurements were performed at EMC Technologies open area test site (OATS) situated at Lerderderg Gorge, near the township of Bacchus Marsh in Victoria, Australia. Conducted emission measurements were performed at EMC Technologies' laboratory in Tullamarine, Victoria Australia.

The above sites have been fully described in a report submitted to the FCC office, and accepted in a letter dated June 14, 2002, **FCC Registration Number 90560**.

EMC Technologies open area test site (OATS) has also been accepted by Industry Canada for the performance of radiated measurements in accordance with RSS 212, Issue 1 (Provisional).

**Industry Canada File Number, IC 4161**, (Registration Date - November 5<sup>th</sup> 2001).

### 2.8.2 NATA Accreditation

EMC Technologies is accredited in Australia to test to the following standards by the National Association of Testing Authorities (NATA).

***"FCC Part 15 unintentional and intentional emitters in the frequency range 9kHz to 18 GHz excluding TV receivers (15.117 and 15.119), TV interface devices (15.115), cable ready consumer electronic equipment (15.118), cable locating equipment (15.213) and unlicensed national information infrastructure devices (Sub part E)."***

The current full scope of accreditation can be found on the NATA website: [www.nata.asn.au](http://www.nata.asn.au)  
It also includes a large number of emission, immunity, SAR, EMR and Safety standards.

NATA is the Australian national laboratory accreditation body and has accredited EMC Technologies to operate to the IEC/ISO17025 requirements. A major requirement for accreditation is the assessment of the company and its personnel as being technically competent in testing to the standards. This requires fully documented test procedures, continued calibration of all equipment to the National Standard at the National Measurements Laboratory (NML) and an internal quality system to ISO 9002. NATA has mutual recognition agreements with the National Voluntary Laboratory Accreditation Program (NVLAP) and the American Association for Laboratory Accreditation (A<sup>2</sup>LA).



## **2.9 Units of Measurements**

### **2.9.1 Conducted Emissions**

Measurements are reported in units of dB relative to one microvolt. (dB $\mu$ V).

### **2.9.2 Radiated Emissions**

Measurements are reported in units of dB relative to one microvolt per metre (dB $\mu$ V/m).

## **2.10 Test Equipment Calibration**

All measurement instrumentation and transducers were calibrated in accordance with the applicable standards by an independent NATA registered laboratory such as Agilent Technologies (Australia) Pty Ltd or the National Measurement Laboratory (NML). All equipment calibration is traceable to Australia national standards at the National Measurements Laboratory. The reference antenna calibration was performed by NML and the working antennas (biconical and log-periodic) calibrated by the NATA approved procedures. The complete list of test equipment used for the measurements, including calibration dates and traceability is contained in Appendix A.

## **2.11 Ambients at OATS**

The Open Area Test Site (OATS) is an area of low background ambient signals. No significant broadband ambients are present however commercial radio and TV signals exceed the limit in the FM radio, VHF and UHF television bands. Radiated prescan measurements were performed in the shielded enclosure to check for possible radiated emissions at the frequencies where the OATS ambient signals exceeded the test limit.



## RESULTS

### WLAN Module – WM3B2915ABG (802.11a (NII) of Callexico2 11a+b/g)

#### 1.0 CONDUCTED EMISSION MEASUREMENTS

Testing was performed in accordance with the requirements of FCC Part 15.207

##### 1.1 Test Procedure

The arrangement specified in ANSI C63.4-2003 was adhered to for the conducted EMI measurements. The EUT was placed in the RF screened enclosure and a CISPR EMI Receiver as defined in ANSI C63.2-1996 was used to perform the measurements.

The EMI Receiver was operated under program control using the Max-Hold function and automatic frequency scanning, measurement and data logging techniques. The specified 0.15 MHz to 30 MHz frequency range was sub-divided into sub-ranges to ensure that all short duration peaks were captured.

##### 1.2 Peak Maximising Procedure

The various operating modes of the system were investigated. For each of the sub-ranges, the EMI receiver was set to continuous scan with the Peak detector set to Max-Hold mode. The Quasi-Peak detector and the Average detector were then invoked to measure the actual Quasi-Peak and Average level of the most significant peaks, which were detected.

##### 1.3 Calculation of Voltage Levels

The voltage levels were automatically measured in software and compared to the test limit. The method of calculation was as follows:

$$VEMI = VRx + LBPF$$

Where:

- VEMI** = the Measured EMI voltage in dBμV to be compared to the limit.
- VRx** = the Voltage in dBμV read directly at the EMI receiver.
- LBPF** = the insertion loss in dB of the cables and the Limiter and Pass Filter.

##### 1.4 Plotting of Conducted Emission Measurement Data

The measurement data pertaining to each frequency sub-range were then concatenated to form a single graph of (peak) amplitude versus frequency. This was performed for both Active and Neutral lines and the composite graph was subsequently plotted. A list of the highest relevant peaks and the respective Quasi-Peak and Average values were also plotted on the graph.

## 1.5 Results of Conducted Emission Measurements (AC Mains Ports)

Conducted Emission Measurements were performed on the LifeBook E Series, Model E8010 (Emilia2) with WLAN module and Bluetooth.

Initial investigations were performed with the WLAN in all configurations (802.11b, 801.11g and 802.11a) and all modulation types: (BPSK, QPSK, 16QAM, 64QAM, DBPSK, DQPSK and CCK). No significant differences in emissions were observed. Final testing was performed while the WLAN transmitter continuously operated with configuration 802.11a on the high (Channel 64, 5320 MHz) frequency channel with the modulation rate of 6 Mbps (BPSK) and the Bluetooth transmitter continuously operated on the low (Channel 1, 2402 MHz) frequency channel.

The reported frequencies in the tables below are mainly concerned with the Host PC emissions and not directly related to the WLAN & Bluetooth emissions.

| Frequency MHz | Line    | Measured QP Level dB $\mu$ V | QP Limit dB $\mu$ V | $\Delta$ QP $\pm$ dB | Measured AV Level dB $\mu$ V | AV Limit dB $\mu$ V | $\Delta$ AV $\pm$ dB |
|---------------|---------|------------------------------|---------------------|----------------------|------------------------------|---------------------|----------------------|
| 0.202         | Active  | 51.5                         | 63.5                | -12.0                | 47.0                         | 53.5                | -6.5                 |
| 0.208         | Neutral | 52.2                         | 63.3                | -11.1                | 45.3                         | 53.3                | -8.0                 |
| 0.303         | Neutral | 48.4                         | 60.2                | -11.7                | 40.1                         | 50.2                | -10.1                |
| 0.621         | Active  | 40.0                         | 56.0                | -16.0                | 31.8                         | 46.0                | -14.2                |
| 0.311         | Active  | 44.8                         | 59.9                | -15.2                | 35.6                         | 49.9                | -14.3                |
| 0.619         | Neutral | 40.0                         | 56.0                | -16.0                | 31.5                         | 46.0                | -14.5                |

The worst case conducted EMI occurred at 0.202 MHz and complied with the quasi peak and average limits by margins of 12.0 dB and 6.5 dB respectively. The measurement uncertainty was  $\pm 2.0$  dB. Refer to Appendix I (graphs 1 & 2) for plots of the conducted EMI measurements.

**Result:** Complies



## 2.0 RADIATED EMISSION MEASUREMENTS

### 2.1 Test Procedure

Testing was performed in accordance with the requirements of FCC Part 15.407(b).

Radiated emission measurements were performed to the limits as per section 15.209 and 15.407. The measurements were made at the open area test site.

The EUT was set up on the table top (placed on turntable) of total height 80 cm above the ground plane, and operated as described in section 2 of this report. The EMI Receiver was operated under software control via the PC Controller through the IEEE.488 Interface Bus Card Adaptor. The test frequency range was sub-divided into smaller bands with sufficient frequency resolution to permit reliable display and identification of possible EMI peaks while also permitting fast frequency scan times. A calibrated Biconical antenna was used for measurements between 30 MHz to 232 MHz and a calibrated Logperiodic antenna used for measurements between 230 MHz to 1000 MHz. Calibrated EMCO 3115 and EMCO 3116 Horn antennas were used for measurements between 1 to 40 GHz.

The measurement of emissions between 30 - 1000 MHz was measured with the resolution bandwidth of 120 kHz and the video bandwidth of 300 kHz.

The measurement of emissions above 1000 MHz, appearing in the restricted bands, was made using an average detector with a resolution bandwidth of 1.0 MHz.

The EUT was slowly rotated with the Peak Detector set to Max-Hold. This was performed for two antenna heights. When an emission was located, it was positively identified and its maximum level found by rotating the automated turntable, and by varying the antenna height. Each significant peak was investigated with the Quasi-Peak/Average Detectors. The measurement data for each frequency range was automatically corrected by the software for cable losses, antenna factors and preamplifier gain and all data was then stored on disk in sequential data files. This process was performed for both horizontal and vertical antenna polarisations.

### 2.2 Calculation of field strength

The field strength was calculated automatically by the software using all the pre-stored calibration data. The method of calculation is shown below:

**E = V + AF - G + L** Where:

**E** = Radiated Field Strength in dB $\mu$ V/m.

**V** = EMI Receiver Voltage in dB $\mu$ V. (measured value)

**AF** = Antenna Factor in dB(m<sup>-1</sup>). (stored as a data array)

**G** = Preamplifier Gain in dB. (stored as a data array)

**L** = Cable insertion loss in dB. (stored as a data array of Insertion Loss versus frequency)

- **Example Field Strength Calculation**

Assuming a receiver reading of 34.0 dB $\mu$ V is obtained at 90 MHz, the Antenna Factor at that frequency is 9.2 dB. The cable loss is 1.9 dB while the preamplifier gain is 20 dB. The resulting Field Strength is therefore as follows:

$$34.0 + 9.2 + 1.9 - 20 = 25.1 \text{ dB}\mu\text{V/m}$$

Measurement uncertainty with a confidence interval of 95% is:

- Free radiation tests (1000 MHz – 18,000 MHz)  $\pm$  4.1 dB  
(30 MHz – 1,000 MHz)  $\pm$  3.7 dB



## 2.3 Results - Out of Band Emissions (Spurious and Harmonics)

### 2.3.1 Frequency Band: 1 – 40 GHz

All measurements above 1 GHz were initially made over a distance of 3 metres. This was decreased to 1.0 metre as the emission levels from the device were very low.

The 54 dB $\mu$ V/m limit at 3 metres has been converted to 64 dB $\mu$ V/m at 1 metre using a factor of 20 dB per decade where emissions were located in the restricted bands.

The peak limits for undesirable emission outside of the restricted bands are –27 dBm (68.3 dB $\mu$ V/m @ 3m).

Measurements were performed on frequency band (5.15 - 5.35 GHz)

Testing was performed while both the WLAN transmitter and Bluetooth transmitter continuously operated. Harmonics related to the WLAN transmitter are reported below. For harmonics related to the Bluetooth transmitter, refer to M040905\_Cert\_Emilia2\_BT\_Cal2\_11abg.

Initial investigations were performed with four modulation types: (BPSK, QPSK, 16QAM and 64QAM). No significant differences in emissions were observed. Final testing was performed while the transmitter continuously operated with the modulation rate of 54 Mbps (64QAM).

The field strength at 5350 MHz when the EUT was operating at its highest channel (5320 MHz), was 59.2 dB $\mu$ V/m peak & 44.7 dB $\mu$ V/m average and was > 20 dB below the maximum field strength of the in-band carrier.

The field strength at 5150 MHz when the EUT was operating at its lowest channel (5180 MHz), was 60.1 dB $\mu$ V/m peak & 44.9 dB $\mu$ V/m average and was > 20 dB below the maximum field strength of the in-band carrier.

#### 2.3.1.1 Configuration 802.11a (5.150 – 5.350 MHz)

##### Channel 36 – 5180 MHz

| Frequency MHz | Level dB $\mu$ V/m |                  | Antenna Polarization | Peak Limit dB $\mu$ V/m | Average Limit dB $\mu$ V/m | Result |
|---------------|--------------------|------------------|----------------------|-------------------------|----------------------------|--------|
|               | Peak Detector      | Average Detector |                      |                         |                            |        |
| 5180          | Transmitter        | Fundamental      |                      |                         |                            |        |
| 10360         | 56.2**             | 42.7***          | Vert/Hort            | 68.3                    | -                          | Pass   |
| 15540         | 60.5**             | 47.3***          | Vert/Hort            | 74.0                    | 54.0                       | Pass   |
| 20720         | 64.2**             | 51.5***          | Vert/Hort            | 84.0* (1m)              | 64.0* (1m)                 | Pass   |
| 25900         | 67.6**             | 54.1***          | Vert/Hort            | 78.3* (1m)              | -                          | Pass   |
| 31080         | 75.9**             | 54.0***          | Vert/Hort            | 78.3* (1m)              | -                          | Pass   |
| 36260         | 80.7**             | 58.8***          | Vert/Hort            | 78.3* (1m)              | -                          | Pass   |

\*Measurement was performed at 1 metre distance and the limits were corrected accordingly.

\*\*These were noise floor levels. Measurements were made with a resolution bandwidth of 1MHz and a video bandwidth of 1MHz.

\*\*\*With a resolution bandwidth of 1MHz and a video bandwidth of 100Hz, harmonics were still low and recorded as average levels.



**Channel 52 – 5260 MHz**

| Frequency MHz | Level dBuV/m  |                  | Antenna Polarization | Peak Limit dBuV/m | Average Limit dBuV/m | Result |
|---------------|---------------|------------------|----------------------|-------------------|----------------------|--------|
|               | Peak Detector | Average Detector |                      |                   |                      |        |
| 5260          | Transmitter   | Fundamental      |                      |                   |                      |        |
| 10520         | 56.2**        | 42.7***          | Vert/Hort            | 68.3              | -                    | Pass   |
| 15780         | 60.5**        | 47.3***          | Vert/Hort            | 74.0              | 54.0                 | Pass   |
| 21040         | 64.2**        | 51.5***          | Vert/Hort            | 84.0* (1m)        | 64.0* (1m)           | Pass   |
| 26300         | 67.6**        | 54.1***          | Vert/Hort            | 78.3* (1m)        | -                    | Pass   |
| 31560         | 75.9**        | 54.0***          | Vert/Hort            | 84.0* (1m)        | 64.0* (1m)           | Pass   |
| 36820         | 80.7**        | 58.8***          | Vert/Hort            | 78.3* (1m)        | -                    | Pass   |

\*Measurement was performed at 1 metre distance and the limits were corrected accordingly.

\*\*These were noise floor levels. Measurements were made with a resolution bandwidth of 1MHz and a video bandwidth of 1MHz.

\*\*\*With a resolution bandwidth of 1MHz and a video bandwidth of 100Hz, harmonics were still low and recorded as average levels.

**Channel 64 – 5320 MHz**

| Frequency MHz | Level dBuV/m  |                  | Antenna Polarization | Peak Limit dBuV/m | Average Limit dBuV/m | Result |
|---------------|---------------|------------------|----------------------|-------------------|----------------------|--------|
|               | Peak Detector | Average Detector |                      |                   |                      |        |
| 5320          | Transmitter   | Fundamental      |                      |                   |                      |        |
| 10640         | 56.2**        | 42.7***          | Vert/Hort            | 74.0              | 54.0                 | Pass   |
| 15960         | 60.5**        | 47.3***          | Vert/Hort            | 74.0              | 54.0                 | Pass   |
| 21280         | 64.2**        | 51.5***          | Vert/Hort            | 84.0* (1m)        | 64.0* (1m)           | Pass   |
| 26600         | 67.6**        | 54.1***          | Vert/Hort            | 78.3* (1m)        | -                    | Pass   |
| 31920         | 75.9**        | 54.0***          | Vert/Hort            | 78.3* (1m)        | -                    | Pass   |
| 37240         | 80.7**        | 58.8***          | Vert/Hort            | 78.3* (1m)        | -                    | Pass   |

\*Measurement was performed at 1 metre distance and the limits were corrected accordingly.

\*\*These were noise floor levels. Measurements were made with a resolution bandwidth of 1MHz and a video bandwidth of 1MHz.

\*\*\*With a resolution bandwidth of 1MHz and a video bandwidth of 100Hz, harmonics were still low and recorded as average levels.

**Result:** No harmonics were recorded up to 40 GHz and complied with the FCC Class B limits. Harmonics were below the limit in section 15.209 and 15.407. The measurement uncertainty for radiated emissions in this band was  $\pm 4.1$  dB.

**2.3.1.2 Spurious Emissions Generated When Both (WLAN and BT) Transmitters Transmitting****WLAN (configuration 802.11a) - 5260MHz and BT – 2480MHz**

| Frequency MHz | Level dBuV/m  |                  | Antenna Polarization | Peak Limit dBuV/m | Average Limit dBuV/m | Result |
|---------------|---------------|------------------|----------------------|-------------------|----------------------|--------|
|               | Peak Detector | Average Detector |                      |                   |                      |        |
| 7728          | 51.4          | 40.7             | Vert/Hort            | 74.0              | 54.0                 | Pass   |

**Result:** Spurious emissions were recorded within the restricted bands of up to 40 GHz and complied with the FCC Class B limits by a margin of 13.3 dB. Harmonics were below the limit in section 15.209 and 15.407. The measurement uncertainty for radiated emissions in this band was  $\pm 4.1$  dB.





**2.3.2 Frequency Band: 30 - 1000 MHz**

Testing was performed at a distance of 10 metres.

Measurements were performed on the LifeBook E Series, Model E8010 (Emilia2) with WLAN module and Bluetooth.

Initial investigations were performed with the WLAN in both configurations (802.11b, 802.11g and 802.11a) and all modulation types: (BPSK, QPSK, 16QAM, 64QAM, DBPSK, DQPSK and CCK). No significant differences in emissions were observed. Final testing was performed while the WLAN transmitter continuously operated with configuration 802.11a on the high (Channel 64, 5320 MHz) frequency channel with the modulation rate of 6 Mbps (BPSK) and the Bluetooth transmitter continuously operated on the low (Channel 1, 2402 MHz) frequency channel.

The reported frequencies in the tables below are mainly concerned with the Host PC emissions and not directly related to the WLAN & Bluetooth emissions.

**Vertical Polarity**

| Frequency MHz | Polarisation | QP Measured dB $\mu$ V/m | QP Limit dB $\mu$ V/m | $\Delta$ QP $\pm$ dB |
|---------------|--------------|--------------------------|-----------------------|----------------------|
| 234.50        | Vertical     | 34.8                     | 35.5                  | -0.7                 |
| 231.38        | Vertical     | 33.6                     | 35.5                  | -1.9                 |
| 369.91        | Vertical     | 32.9                     | 35.5                  | -2.6                 |
| 203.64        | Vertical     | 29.7                     | 33.0                  | -3.3                 |
| 215.40        | Vertical     | 29.2                     | 33.0                  | -3.8                 |
| 184.30        | Vertical     | 28.6                     | 33.0                  | -4.4                 |
| 198.27        | Vertical     | 28.1                     | 33.0                  | -4.9                 |
| 165.82        | Vertical     | 26.7                     | 33.0                  | -6.4                 |
| 169.82        | Vertical     | 26.2                     | 33.0                  | -6.8                 |
| 162.51        | Vertical     | 24.4                     | 33.0                  | -8.7                 |

**Horizontal Polarity**

| Frequency MHz | Polarisation | QP Measured dB $\mu$ V/m | QP Limit dB $\mu$ V/m | $\Delta$ QP $\pm$ dB |
|---------------|--------------|--------------------------|-----------------------|----------------------|
| 203.67        | Horizontal   | 29.6                     | 33.0                  | -3.4                 |
| 363.41        | Horizontal   | 31.5                     | 35.5                  | -4.0                 |
| 234.51        | Horizontal   | 30.2                     | 35.5                  | -5.3                 |
| 432.01        | Horizontal   | 29.2                     | 35.5                  | -6.4                 |
| 212.48        | Horizontal   | 23.8                     | 33.0                  | -9.2                 |
| 198.84        | Horizontal   | 22.9                     | 33.0                  | -10.1                |
| 169.99        | Horizontal   | 22.0                     | 33.0                  | -11.0                |
| 171.07        | Horizontal   | 20.3                     | 33.0                  | -12.7                |
| 801.82        | Horizontal   | 22.6                     | 35.5                  | -12.9                |

**Result:** The highest radiated emission peak occurred at 234.5 MHz (Vertical Polarity) and complied with FCC quasi peak limit by a margin of 0.7 dB. The measurement uncertainty in this band was  $\pm 3.7$  dB. Refer to tables above for results.

### 2.3.3 RF Conducted Measurements at the antenna terminal

In the 100 kHz bandwidth within the operating band, the highest emissions (spurious/harmonics) level that is produced by the intentional radiator shall be at least 20 dB below.

The transmitter output was connected to the spectrum analyser in peak hold mode.

The resolution bandwidth of 300 kHz and the video bandwidth of 1000 kHz were utilised.

Refer to Appendix N for Harmonics plots

**Result:** Complies.

### 2.3.4 Band Edge Measurements

The transmitter output was connected to the spectrum analyser in peak hold mode.

The resolution bandwidth of 1000 kHz and the video bandwidth of 1000 kHz were utilised.

Testing was performed while transmitter continuously transmitted on a low and high frequency channel of frequency band (5.150 – 5.350 GHz)

Refer to Appendix K for Band Edge plots

*NB:* D1 indicates the limit line for undesirable emission frequencies outside the operation frequency band.

**Result:** Complies.



### 3.0 PEAK OUTPUT POWER - Section 15.407(a)

Testing was performed in accordance with the requirements of FCC Part 15.407(a)(4)

Measurements were performed while the WLAN transmitter continuously transmitted.

The transmitter output was connected to the spectrum analyser in peak hold mode.

The resolution bandwidth of 20 MHz and the video bandwidth of 20 MHz were utilised.

The Peak Output Power (P) was calculated as follows:

$$P = R + G \quad \text{where} \quad \begin{array}{l} R \text{ is the recorded peak power} \\ G \text{ is the antenna gain in dBi (with EUT cable loss)} \end{array}$$

Measurements were performed on frequency band (5.150 – 5.350 GHz)

Initial investigations were performed with four modulation types: (BPSK, QPSK, 16QAM and 64QAM). No significant differences in peak transmit power were observed. Final testing was performed while the transmitter continuously operated with the modulation rate of 54 Mbps (64QAM).

| Frequency MHz | A dBm | G dBi | P dBm | Limit dBm | P mW | Limit mW |
|---------------|-------|-------|-------|-----------|------|----------|
| 5180          | 15.49 | -2.33 | 13.16 | 17        | 20.7 | 50       |
| 5260          | 17.93 | -2.33 | 15.60 | 24        | 36.3 | 250      |
| 5320          | 19.07 | -2.33 | 16.74 | 24        | 47.2 | 250      |

Refer to Appendix O for Peak Power plots

Variation by +/- 15% of the supply voltage, in accordance with Section 15.31(e), to the computer power supply did not vary the output power observed.

**Result:** Complies.

### 4.0 CHANNEL BANDWIDTH

Testing was performed in accordance with the requirements of FCC Part 15.407(a)

The 26 dB bandwidth was measured while the transmitter continuously transmitted.

The transmitter output (antenna port) was connected to the spectrum analyser in peak hold mode.

The resolution bandwidth of 300 kHz and the video bandwidth of 1000 kHz were utilised

Measurements were performed on frequency band (5.150 – 5.350 GHz)

Initial investigations were performed with four modulation types: (BPSK, QPSK, 16QAM and 64QAM). No significant differences in bandwidth were observed. Final testing was performed while the transmitter continuously operated with the modulation rate of 54 Mbps (64QAM).

| Channel | Frequency MHz | Bandwidth MHz | 26 dB Bandwidth Plots |
|---------|---------------|---------------|-----------------------|
| 36      | 5180          | 22.2          | Appendix J            |
| 52      | 5260          | 22.0          | Appendix J            |
| 64      | 5320          | 22.4          | Appendix J            |



## 5.0 RADIO FREQUENCY EXPOSURE (HAZARD) INFORMATION

Testing was performed in accordance with the requirements of FCC Part 15.407(f)

Spread spectrum transmitters operating in the 5.150 – 5.350 GHz and 5.725 – 5.825 GHz bands are required to be operated in a manner that ensures that the public is not exposed to RF energy levels in accordance with CFR 47, Section 1.1307(b)(1).

In accordance with this section and also section 2.1091 this device has been defined as a mobile device whereby a distance of 20 cm normally can be maintained between the user and the device.

In accordance with Section 1.1310, the Maximum Permissible Exposure (MPE) limit for the General Population/Uncontrolled Exposure of 1.0 has been applied, i.e 1mW/cm<sup>2</sup>.

Friis transmission formula:  $P_d = (P \cdot G) / (4 \cdot \pi \cdot r^2)$

where:  $P_d$  = power density (mW/cm<sup>2</sup>)

$P$  = power input to the antenna (mW)

$G$  = antenna gain (numeric)

$r$  = distance to the center of radiation of the antenna (cm)

**The result was extracted from section 3.0 of this report. (WLAN Module):**

Maximum peak output power = 19.1dBm = 81.3mW

Antenna (Monopole Ceramic Chip) gain (typical) = -2.33 dBi = 0.58 numeric

Prediction distance = 20 cm

Prediction frequency = 5320 MHz

MPE limit for uncontrolled exposure at prediction frequency = 1 mW/cm<sup>2</sup>

Therefore, the power density at prediction frequency ( $P_d$ ) = 0.009 mW/cm<sup>2</sup>

**The result was extracted from section 3.0 of EMC Technologies Report No:**

**M040905\_Cert\_Emilia2\_BT\_Cal2\_11abg (Bluetooth):**

Maximum peak output power = 10.41dBm = 11.0 mW

Antenna (Inverted-F) gain (typical) = 1.06 dBi = 1.28 numeric

Prediction distance = 20 cm

Prediction frequency = 2402 MHz

MPE limit for uncontrolled exposure at prediction frequency = 1 mW/cm<sup>2</sup>

Therefore, the power density at prediction frequency ( $P_d$ ) = 0.003mW/cm<sup>2</sup>

The total power density (TPd) for WLAN and Bluetooth transmitters continuously operated:

$TP_d = 0.009 \text{ (WLAN)} + 0.003 \text{ (Bluetooth)} = 0.012 \text{ mW/cm}^2$

Calculations show that this device with described antenna does meet the MPE requirements for portable devices falling below the 20 cm clearance required.

**Results:           Complies**



**6.0 PEAK POWER SPECTRAL DENSITY - Section 15.407 (a)**

Testing was performed in accordance with the requirements of FCC Part 15.407(a)(5)

The peak power spectral density was measured over an interval of continuous transmission using a calibrated spectrum analyser with the resolution bandwidth of 1 MHz and the video bandwidth of 3 MHz.

The transmitter output was connected to the spectrum analyser with a span setting to capture the entire emission bandwidth of the signal. The peak power spectral density was recorded in dBm.

Measurements were performed on frequency bands (5.150 – 5.350 GHz)

Initial investigations were performed with four modulation types: (BPSK, QPSK, 16QAM and 64QAM). No significant differences in peak power spectral density were observed. Final testing was performed while the transmitter continuously operated with the modulation rate of 54 Mbps (64QAM).

| Channel | Frequency MHz | Peak Power Spectral Density (dBm) | Limit (dBm) | Result   | Spectral Density plots |
|---------|---------------|-----------------------------------|-------------|----------|------------------------|
| 36      | 5180          | 3.94                              | 4.0         | Complies | Appendix L             |
| 52      | 5260          | 6.62                              | 11.0        | Complies | Appendix L             |
| 64      | 5320          | 7.14                              | 11.0        | Complies | Appendix L             |

**Result:** Complies.

**7.0 PEAK EXCURSION - Section 15.407 (a)**

Testing was performed in accordance with the requirements of FCC Part 15.407(a)(6)

The transmitter output was connected to the spectrum analyser with a span setting to capture the entire emission bandwidth of the signal.

The peak power excursion was measured over an interval of continuous transmission using a calibrated spectrum analyser with the resolution bandwidth of 1 MHz and the video bandwidth of 3 MHz for Trace 1 and video bandwidth of 300 kHz for Trace 2. The difference between Trace 1 and Trace 2 was recorded.

Measurements were performed on frequency bands (5.150 – 5.350 GHz)

Initial investigations were performed with four modulation types: (BPSK, QPSK, 16QAM and 64QAM). No significant differences in peak excursion were observed. Final testing was performed while the transmitter continuously operated with the modulation rate of 54 Mbps (64QAM).

| Channel | Frequency MHz | Peak Power Excursion (dB) | Limit (dB) | Result   | Peak Excursion plots |
|---------|---------------|---------------------------|------------|----------|----------------------|
| 36      | 5180          | 3.02                      | 13.0       | Complies | Appendix M           |
| 52      | 5260          | 2.63                      | 13.0       | Complies | Appendix M           |
| 64      | 5320          | 3.27                      | 13.0       | Complies | Appendix M           |

**Result:** Complies.



## 8.0 FREQUENCY STABILITY

Testing was performed in accordance with the requirements of FCC Part 15.407(g)

The transmitter output was connected to the spectrum analyser in peak hold mode.

The measurements were made at ambient room temperature and extreme (-20 to +55 °C) test conditions.

The AC supply voltage to the computer was varied by  $\pm 15\%$ . This was observed to have no effect on the results obtained.

Measurements were performed on frequency bands (5.150 – 5.350 GHz)

Testing was performed while the transmitter continuously operated with the modulation rate of 54 Mbps (64QAM).

| Channel | Frequency MHz | Maximum Frequency Deviation kHz | Maximum Deviation % | $\pm 0.02\%$ Limit kHz | Result   |
|---------|---------------|---------------------------------|---------------------|------------------------|----------|
| 36      | 5180          | 354                             | 0.007               | 1036                   | Complies |
| 52      | 5260          | 418                             | 0.008               | 1052                   | Complies |
| 64      | 5320          | 393                             | 0.007               | 1064                   | Complies |

**Result:** Complies.

## 9.0 ANTENNA REQUIREMENT

Testing to the requirements of FCC Part 15.203 was not applicable as this intentional radiator was designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.



## 10.0 COMPLIANCE STATEMENT

The LifeBook E Series, Model E8010 (Emilia2) with Mini-PCI Wireless LAN Module (Calexico2 11a+b/g, Model WM3B2915ABG) & Bluetooth, Model UGXZ5-102A, tested on behalf of Fujitsu Australia Ltd, **comply** with the requirements of 47 CFR, Part 15 Subpart E -Section 15.407 (5.15-5.35 GHz and 5.725-5.825 GHz bands).

The test sample also complies with the Industry Canada RSS-210 issue 5 (Low Power Licence-Exempt Radiocommunication Devices (All Frequency Bands)) clause 6.2.2(q1) 5150-5350 MHz and 5725-5825 MHz Local Area Network Devices requirements and the RF exposure requirements of RSS-102.

**Results were as follows:**

### WLAN, Calexico2 802.11a (U-NII) - FCC Subpart E, Section 15.407

| FCC Part 15, Subpart E Clauses | Industry Canada RSS-210 Clauses | Test Performed               | Result                |
|--------------------------------|---------------------------------|------------------------------|-----------------------|
| 15.203                         | 5.5                             | Antenna Requirement          | <b>Not Applicable</b> |
| 15.205                         | 6.3                             | Operation in Restricted Band | <b>Complies</b>       |
| 15.207                         | 6.6                             | Conducted Emissions          | <b>Complies</b>       |
| 15.209                         | 6.3                             | Radiated Emissions           | <b>Complies</b>       |
| 15.407 (a)(4)                  | 6.2.2(q1)                       | Peak Transmit Power          | <b>Complies</b>       |
| 15.407 (a)(5)                  | 6.2.2(q1)                       | Peak Power Spectral Density  | <b>Complies</b>       |
| 15.407 (a)(6)                  |                                 | Peak Excursion               | <b>Complies</b>       |
| 15.407 (b)                     | 6.2.2(q1)                       | Undesirable Emission         | <b>Complies</b>       |
| 15.407 (f)                     |                                 | Radio Frequency Hazard       | <b>Complies</b>       |
| 15.407 (g)                     | 6.4                             | Frequency Stability          | <b>Complies</b>       |

**The results for configurations IEEE 802.11b, IEEE 802.11g and IEEE802.11a (DTS: 5725 – 5850 MHz) and Bluetooth are reported separately.**

Refer to EMC Technologies' test report: M040905\_Cert\_Emilia2\_Cal2\_11abg\_DTS\_BT (802.11b/g and 802.11a: DTS) and M040905\_Cert\_Emilia2\_BT\_Cal2\_11abg (Bluetooth).



## TEST REPORT APPENDICES

**APPENDIX A: MEASUREMENT INSTRUMENTATION DETAILS**  
**APPENDIX B: REPORT PHOTOGRAPHS**  
**APPENDIX C: FUNCTIONAL DESCRIPTION**  
**APPENDIX D: BLOCK DIAGRAM**  
**APPENDIX E: SCHEMATICS**  
**APPENDIX F: ANTENNA INFORMATION (INVERTED-F ANTENNA)**  
**APPENDIX G: FCC LABELLING DETAILS**  
**APPENDIX H: USER MANUAL**  
**APPENDIX I: GRAPHS of EMI MEASUREMENTS**  
**APPENDIX J: CHANNEL BANDWIDTH PLOTS**  
**APPENDIX K: BANDEDGE PLOTS**  
**APPENDIX L: PEAK POWER SPECTRAL DENSITY PLOTS**  
**APPENDIX M: PEAK EXCURSION PLOTS**  
**APPENDIX N: HARMONICS PLOTS**  
**APPENDIX O: PEAK POWER**

**Attachment 1: RF Exposure Information**

**Attachment 2: FCC DOC for LifeBook Emilia2 E Series (E8010)**

