

TEST REPORT

Product Name Model Number		 Micro Music System TAM4205/37, M4205/37, TAM4205x/yy, M4205x/yy (x = A -Z or blank, for different color or package; yy = 00 - 99, for country code)
FCC ID		: 2AR2STAM4205
Prepared for Address	:	MMD Hong Kong Holding Limited Units 1006-1007, 10th Floor, C-Bons International Center, 108 Wai Yip Street, Kwun Tong, Kowloon, Hong Kong
Prepared by Address	:	EMTEK (SHENZHEN) CO., LTD. Building 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, China
		Tel: (0755) 26954280 Fax: (0755) 26954282

Report Number	:	ES200708082W
Date(s) of Tests	•	July 08, 2020 to July 28, 2020
Date of issue		July 28, 2020

深圳信测标准技术服务股份有限公司地址:广东省深圳市南山区马家龙工业区69栋 网址:Http://www.emtek.com.cn 邮箱:cs.rep@emtek.com.cn



VERIFICATION OF COMPLIANCE

Applicant:	MMD Hong Kong Holding Limited
Manufacturer:	MMD Hong Kong Holding Limited
Factory:	Guangzhou Panyu Juda Car Audio Equipment Co., Ltd
Product Description:	Micro Music System
Trade Mark:	PHILIPS,
Model Number:	TAM4205/37, M4205/37, TAM4205x/yy, M4205x/yy (x = A -Z or blank, for different color or package; yy = 00 - 99, for country code)

We hereby certify that:

The above equipment was tested by EMTEK(SHENZHEN) CO., LTD. The test data, data evaluation, test procedures, and equipment configurations shown in this report were made in accordance with the procedures given in ANSI C63.10-2013 and the energy emitted by the sample EUT tested as described in this report is in compliance with conducted and radiated emission limits of FCC Rules Part 15.247(2018).

Date of Test :	July 08, 2020 to July 28, 2020
Prepared by :	Loven Luo Loren Luo /Editor
Reviewer :	Tim Dong /Supervisor
Approved & Authorized Signer :	Lisa Wang /Manager ESTING

深圳信测标准技术服务股份有限公司 地址:广东省深圳市南山区马家龙工业区69栋 网址:Http://www.emtek.com.cn 邮箱:cs.rep@emtek.com.cn EMTEK (Shenzhen) Co., Ltd. Add: Building 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, China Http://www.emtek.com.cn E-mail: cs.rep@emtek.com.cn

Report No. ES200708082W



Modified Information

Version	Summary	Revision Date	Report No.
Ver.1.0	Original Report	July 28, 2020	ES200708082W



深圳信测标准技术服务股份有限公司地址:广东省深圳市南山区马家龙工业区69栋 网址:Http://www.emtek.com.cn 邮箱:cs.rep@emtek.com.cn EMTEK (Shenzhen) Co., Ltd. Add: Building 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, China Http://www.emtek.com.cn E-mail: cs.rep@emtek.com.cn

Report No. ES200708082W



Table of Contents

TEST F	REPORT	1
1. GE	ENERAL INFORMATION	6
1.1 1.2 1.3	Product Description Test Methodology Test Facility	
2. SY	YSTEM TEST CONFIGURATION	9
2.1 2.2 2.3 2.4	EUT CONFIGURATION EUT EXERCISE TEST PROCEDURE CONFIGURATION OF TESTED SYSTEM	
3. SU	UMMARY OF TEST RESULTS	
4. DE	ESCRIPTION OF TEST MODES	
5. TE	EST SYSTEM UNCERTAINTY	
6. CC	ONDUCTED EMISSIONS TEST	14
6.1 6.2 6.3 6.4	MEASUREMENT PROCEDURE: TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION) MEASUREMENT EQUIPMENT USED: MEASUREMENT RESULT:	
7. RA	ADIATED EMISSION TEST	
7.1 7.2 7.3 7.4 7.5 7.5	MEASUREMENT PROCEDURE TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION) MEASUREMENT EQUIPMENT USED: RADIATED EMISSION LIMIT MEASUREMENT RESULT RADIATED MEASUREMENT PHOTOS:	
8. CH	HANNEL SEPARATION TEST	
8.1 8.2 8.3 8.4	Measurement Procedure Test SET-UP (Block Diagram of Configuration) Measurement Equipment Used: Measurement Results:	
9. 20	DB BANDWIDTH TEST	
9.1 9.2 9.3 9.4	Measurement Procedure Test SET-UP (Block Diagram of Configuration) Measurement Equipment Used: Measurement Results:	
10.	QUANTITY OF HOPPING CHANNEL TEST	
10.1 10.2 10.3 10.4	MEASUREMENT PROCEDURE TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION) MEASUREMENT EQUIPMENT USED: MEASUREMENT RESULTS:	

深圳信测标准技术服务股份有限公司 地址:广东省深圳市南山区马家龙工业区69栋 网址:Http://www.emtek.com.cn 邮箱:cs.rep@emtek.com.cn



11.	TIME OF OCCUPANCY (DWELL TIME) TEST	45
11.1 11.2 11.3 11.4 11.5	TEST DESCRIPTION	45 45 45 45 45 46
12.	MAXIMUM PEAK OUTPUT POWER TEST	48
12.1 12.2 12.3 12.4	MEASUREMENT PROCEDURE TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION) MEASUREMENT EQUIPMENT USED: MEASUREMENT RESULTS:	48 48 48 49
13.	BAND EDGE TEST	55
13.1 13.2 13.3 13.4	MEASUREMENT PROCEDURE. 2 TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION) 3 MEASUREMENT EQUIPMENT USED: 4 MEASUREMENT RESULTS:	55 56 56 57
14.	ANTENNA APPLICATION	73
14.1 14.2	ANTENNA REQUIREMENT	73 73
15.	PHOTOS OF EUT	73

深圳信测标准技术服务股份有限公司 地址:广东省深圳市南山区马家龙工业区69栋 网址:Http://www.emtek.com.cn 邮箱:cs.rep@emtek.com.cn



1. GENERAL INFORMATION

1.1 Product Description

Characteristics	Description		
Product Name	Micro Music System		
Model number	TAM4205/37, M4205/37, TAM4205x/yy, M4205x/yy (x = A -Z or blank, for different color or package; yy = 00 - 99, for country code);here we prepare TAM4205/37 for the all test.		
Power Supply	AC 100-240V, 50Hz/60Hz		
Modulation	GFSK, π/4-DQPSK, 8DPSK		
Operating Frequency Range	2402-2480MHz		
Number of Channels	79		
Transmit Power Max(PK)	2.69dBm(0.001858W)		
Antenna Type	Internal PCB antenna		
Antenna Gain	0dBi		

深圳信测标准技术服务股份有限公司地址:广东省深圳市南山区马家龙工业区69栋网址:Http://www.emtek.com.cn邮箱:cs.rep@emtek.com.cn



1.2 Test Methodology

Both conducted and radiated testing was performed according to the procedures in ANSI C63.10-2013. Radiated testing was performed at an antenna to EUT distance 3 meters.



濠圳信测标准技术服务股份有限公司地址:广东省深圳市南山区马家龙工业区69栋 网址:Http://www.emtek.com.cn 邮箱:cs.rep@emtek.com.cn



1.3Test Facility

Site Description		
EMC Lab.	:	Accredited by CNAS, 2016.10.24 The certificate is valid until 2022.10.28 The Laboratory has been assessed and proved to be in compliance with CNAS-CL01:2006 (identical to ISO/IEC 17025:2005) The Certificate Registration Number is L2291.
		Accredited by TUV Rheinland Shenzhen 2016.05.19 The Laboratory has been assessed according to the requirements ISO/IEC 17025. Accredited by FCC, August 06, 2018 Designation Number: CN1204 Test Firm Registration Number: 882943 Accredited by A2LA, August 31, 2020 The Certificate Registration Number is 4321.01.
		Accredited by Industry Canada, November 09, 2018 The Conformity Assessment Body Identifier is CN0008.
Name of Firm	:	EMTEK(SHENZHEN) CO., LTD.
Site Location	:	Building 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, China.

深圳信测标准技术服务股份有限公司地址:广东省深圳市南山区马家龙工业区69栋网址:Http://www.emtek.com.cn邮箱:cs.rep@emtek.com.cn



2. System Test Configuration

2.1 EUT Configuration

The EUT configuration for testing is installed on RF field strength measurement to meet the Commissions requirement and operating in a manner which intends to maximize its emission characteristics in a continuous normal application.

2.2 EUT Exercise

The Transmitter was operated in the normal operating mode. The Tx frequency was fixed which was for the purpose of the measurements.

2.3 Test Procedure

2.3.1 Conducted Emissions

The EUT is a placed on as turn table which is 0.8 m above ground plane. According to the requirements in Section 13.1.4.1 of ANSI C63.10-2013. Conducted emissions from the EUT measured in the frequency range between 0.15 MHz and 30MHz using CISPR Quasi-Peak and average detector mode.

2.3.2 Radiated Emissions

Below 1000MHz, The EUT was placed on a turn table which is 0.8m above ground plane. And above 1000MHz, The EUT was placed on a styrofoam table which is 1.5m above ground plane. The turn table shall rotate 360 degrees to determine the position of maximum emission level. EUT is set 3m away from the receiving antenna which varied from 1m to 4m to find out the highest emission. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical. In order to find out the max. emission, the relative positions of EUT was fixed in a particular direction according to the requirements in Section 13.1.4.1 of ANSI C63.10-2013.

深圳信测标准技术服务股份有限公司 地址:广东省深圳市南山区马家龙工业区69栋 网址:Http://www.emtek.com.cn 邮箱:cs.rep@emtek.com.cn



2.4 Configuration of Tested System

Fig. 2-1 Configuration of Tested System



Table 2-1 Equipment Used in Tested System

Item	Equipment	Model No.	FCC ID	Note
1.	Micro Music System	TAM4205/37	2AR2STAM4205	EUT

Note:

(1) Unless otherwise denoted as EUT in [Remark] column , device(s) used in tested system is a support equipment.

濠圳信测标准技术服务股份有限公司地址:广东省深圳市南山区马家龙工业区69栋 网址:Http://www.emtek.com.cn 邮箱:cs.rep@emtek.com.cn



FCC Rules	Description Of Test	Result
§15.207	AC Power Conducted Emission	Compliant
§15.247(d),§15.209	Radiated Emission	Compliant
§15.247(a)(1)	Channel Separation test	Compliant
§15.247(a)(1)	20dB Bandwidth	Compliant
§15.247(a)(1)(iii)	Quantity of Hopping Channel	Compliant
§15.247(a)(1)(iii)	Time of Occupancy(Dwell Time)	Compliant
§15.247(b)	Max Peak output Power test	Compliant
§15.247(d)	Band edge test	Compliant
§15.203	Antenna Requirement	Compliant

3. Summary of Test Results

深圳信测标准技术服务股份有限公司 地址:广东省深圳市南山区马家龙工业区69栋 网址:Http://www.emtek.com.cn 邮箱:cs.rep@emtek.com.cn



4. Description of test modes

The EUT has been tested under its typical operating condition and fully-charged battery for EUT tested alone. Pre-defined engineering program for regulatory testing used to control the EUT for staying in continuous transmitting. Only the worst case data were reported.

The EUT has been associated with peripherals pursuant to ANSI C63.10-2013 and configuration operated in a manner tended to maximize its emission characteristics in a typical application. Frequency range investigated: radiation (9 KHz to the 10th harmonics of the highest fundamental frequency or to 40 GHz, whichever is lower).

The EUT has been tested under TX operating condition.

This EUT is a FHSS system, were conducted to determine the final configuration from all possible combinations. We use software control the EUT, Let EUT hopping on and transmit with highest power, all the modes GFSK, $\Pi/4$ -DQPSK have been tested. 79 Channels are provided by EUT. The 3 channels of lower, medium and higher were chosen for test.

Channel List:

Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	
0	2402	39	2441			
1	2403	40	2442	76	2478	
2	2404	41	2443	77	2479	
				78	2480	
Note: fc=2402MHz+(k-1) \times 1MHz k=1 to 79						

Test Frequency and channe

Channel	Frequency(MHz)
0	2402
39	2441
78	2480

深圳信测标准技术服务股份有限公司。地址:广东省深圳市南山区马家龙工业区69栋 网址:Http://www.emtek.com.cn 邮箱:cs.rep@emtek.com.cn



5. TEST SYSTEM UNCERTAINTY

The following measurement uncertainty levels have been estimated for tests performed on the apparatus:

Parameter	Uncertainty
Radio Frequency	±1x10^-5
Maximum Peak Output Power Test	±1.0dB
Conducted Emissions Test	±2.0dB
Radiated Emission Test	±2.0dB
Power Density	±2.0dB
Occupied Bandwidth Test	±1.0dB
Band Edge Test	±3dB
All emission, radiated	±3dB
Antenna Port Emission	±3dB
Temperature	±0.5℃
Humidity	±3%

Remark: The coverage Factor (k=2), and measurement Uncertainty for a level of Confidence of 95%

深圳信测标准技术服务股份有限公司 地址:广东省深圳市南山区马家龙工业区69栋 网址:Http://www.emtek.com.cn 邮箱:cs.rep@emtek.com.cn



6. Conducted Emissions Test

6.1 Measurement Procedure:

- 1. The EUT was placed on a table, which is 0.8m above ground plane.
- 2. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
- 3. Repeat above procedures until all frequency measured was complete.

6.2 Test SET-UP (Block Diagram of Configuration)



6.3 Measurement Equipment Used:

Conducted Emission Test Site							
EQUIPMENT TYPE	MFR	MODEL NUMBER	SERIAL NUMBER	Characteristics	Last Cal.	Due date	
Test Receiver	Rohde & Schwarz	ESCS30	100018	9kHz~3GHz	05/22/2020	05/21/2021	
L.I.S.N	Rohde & Schwarz	ENV216	100017	9KHz-300MHz	05/22/2020	05/21/2021	
RF Switching Unit	CDS	RSU-M2	38401	9KHz-300MHz	05/22/2020	05/21/2021	
Coaxial Cable	CDS	79254	46107086	9kHz~3GHz	05/22/2020	05/21/2021	

深圳信测标准技术服务股份有限公司。地址:广东省深圳市南山区马家龙工业区69栋 网址:Http://www.emtek.com.cn 邮箱:cs.rep@emtek.com.cn



6.4 Measurement Result:

Operation Mode:	ТХ	Test Date :	July 20, 2020
Frequency Range:	0.15MHz~30MHz	Temperature :	28 ℃
Test Result:	PASS	Humidity :	65 %
Test By:	Loren		

Pass.

Conducted emission at both 120V & 240V, and emission at 120V represents the worst case. All the modulation modes were tested the data of the worst mode (GFSK TX 2402MHz) are recorded in the following pages and the others modulation methods do not exceed the limits.

Please refer to the following data.

潦圳信测标准技术服务股份有限公司地址:广东省深圳市南山区马家龙工业区69栋 网址:Http://www.emtek.com.cn 邮箱:cs.rep@emtek.com.cn





No.	Mk.	Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Over	0.2	
		MHz	dBuV	dB	dBuV	dBuV	dB	Detector	Comment
1	1.11	0.1500	37.49	10.01	47.50	66.00	-18.50	QP	
2	2.1.1	0.1500	21.68	10.01	31.69	56.00	-24.31	AVG	
3	ξŤ.	0.2380	36.05	10.05	46.10	62.17	-16.07	QP	
4	1.11	0.2380	23.12	10.05	33.17	52.17	-19.00	AVG	
5		0.5940	32.11	10.18	42.29	56.00	-13.71	QP	
6	*	0.5940	26.81	10.18	36.99	46.00	-9.01	AVG	
7		1.1820	28.44	10.18	38.62	56.00	-17.38	QP	
8		1.1820	20.40	10.18	30.58	46.00	-15.42	AVG	
9		2.4620	27.89	10.18	38.07	56.00	-17.93	QP	
10		2.4620	17.64	10.18	27.82	46.00	-18.18	AVG	
11		11.8860	25.34	10.22	35.56	60.00	-24.44	QP	
12		11.8860	18.03	10.22	28.25	50.00	-21.75	AVG	

*:Maximum data x:Over limit I:over margin

Comment: Factor build in receiver.

Operator: Lian

深圳信测标准技术服务股份有限公司 地址:广东省深圳市南山区马家龙工业区69栋 网址:Http://www.emtek.com.cn 邮箱:cs.rep@emtek.com.cn





No.	Mk.	Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Over		
		MHz	dBuV	dB	dBuV	dBuV	dB	Detector	Comment
1	1.1.1	0.1620	36.65	10.02	46.67	65.36	-18.69	QP	
2	113	0.1620	21.98	10.02	32.00	55.36	-23.36	AVG	
3		0.2300	35.42	10.05	45.47	62.45	-16.98	QP	
4	5	0.2300	23.75	10.05	33.80	52.45	- <mark>18</mark> .65	AVG	
5	-	0.5900	32.48	10.18	42.66	56.00	-13.34	QP	
6	*	0.5900	27.07	10.18	37.25	46.00	-8.75	AVG	
7	1.1	1.1820	28.72	10.18	38.90	56.00	-17.10	QP	
8	1.5	1.1820	22.30	10.18	32.48	46.00	-13.52	AVG	
9	1.1	2.5300	26.39	10.18	36.57	56.00	-19.43	QP	
10	10	2.5300	16.44	10.18	26.62	46.00	-19.38	AVG	
11		11.9940	24.77	10.22	34.99	60.00	-25.01	QP	
12	TP-	11.9940	16.95	10.22	27.17	50.00	-22.83	AVG	

*:Maximum data x:C

x:Over limit 1:over margin

Comment: Factor build in receiver. Operato

Operator: Lian

深圳信测标准技术服务股份有限公司 地址:广东省深圳市南山区马家龙工业区69栋 网址:Http://www.emtek.com.cn 邮箱:cs.rep@emtek.com.cn EMTEK (Shenzhen) Co., Ltd. Add: Building 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, China Http://www.emtek.com.cn E-mail; cs.rep@emtek.com.cn

Report No. ES200708082W



6.5 Conducted Measurement Photos:



深圳信测标准技术服务股份有限公司地址:广东省深圳市南山区马家龙工业区69栋 网址:Http://www.emtek.com.cn 邮箱:cs.rep@emtek.com.cn



7. Radiated Emission Test

7.1 Measurement Procedure

- 1. The testing follows the guidelines in Spurious Radiated Emissions of ANSI C63.10-2013.
- 2. Below 1000MHz, The EUT was placed on a turn table which is 0.8m above ground plane. And above 1000MHz, The EUT was placed on a styrofoam table which is 1.5m above ground plane.
- 3. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
- 4. For each suspected emission, the EUT was arranged to its worst case and then tune the Antenna tower (From 1m to 4m) and turntable (from 0 degree to 360 degree) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level to comply with the guidelines.
- 5. Set to the maximum power setting and enable the EUT transmit continuously.
- 6. Final measurement (Above 1GHz): The frequency range will be divided into different sub ranges depending of the frequency range of the used horn antenna. The EMI Receiver set to peak and average mode and a resolution bandwidth of 1MHz. The measurement will be performed in horizontal and vertical polarization of the measuring antenna and while rotating the EUT in its vertical axis in the range of 0 degree to 360 degree in order to have the antenna inside the cone of radiation.
- 7. Test Procedure of measurement (For Above 1GHz):
 - 1) Monitor the frequency range at horizontal polarization and move the antenna over all sides of the EUT(if necessary move the EUT to another orthogonal axis).
 - 2) Change the antenna polarization and repeat 1) with vertical polarization.
 - 3) Make a hardcopy of the spectrum.
 - 4) Measure the frequency of the detected emissions with a lower span and resolution bandwidth to increase the accuracy and note the frequency value.
 - 5) Change the analyser mode to Clear/ Write and found the cone of emission.
 - 6) Rotate and move the EUT, so that the measuring distance can be enlarged to 3m and the antenna will be still inside the cone of emission.
 - 7) Measure the level of the detected frequency with the correct resolution bandwidth, with the antenna polarization and azimuth and the peak and average detector, which causes the maximum emission.
 - 8) Repeat steps 1) to 7) for the next antenna spot if the EUT is larger than the antenna beamwidth.

深圳信测标准技术服务股份有限公司 地址:广东省深圳市南山区马家龙工业区69栋 网址:Http://www.emtek.com.cn 邮箱:cs.rep@emtek.com.cn



Use the following spectrum analyzer settings:

When spectrum scanned from 30MHz to 1GHz setting resolution bandwidth 120KHz and video bandwidth 300KHz:

EMI Test Receiver	Setting
Attenuation	Auto
RB	120KHz
VB	300KHz
Detector	QP
Trace	Max hold

When spectrum scanned above 1GHz setting resolution bandwidth 1MHz, video bandwidth 3MHz:

EMI Test Receiver	Setting
Attenuation	Auto
RB	1MHz
VB	3MHz
Detector	Peak
Trace	Max hold

When spectrum scanned above 1GHz setting resolution bandwidth 1MHz, video bandwidth 10Hz:

EMI Test Receiver	Setting
Attenuation	Auto
RB	1MHz
VB	10Hz
Detector	Average
Trace	Max hold

濠圳信测标准技术服务股份有限公司 地址:广东省深圳市南山区马家龙工业区69栋 网址:Http://www.emtek.com.cn 邮箱:cs.rep@emtek.com.cn



7.2 Test SET-UP (Block Diagram of Configuration)

(A) Radiated Emission Test Set-Up, Frequency Below 30MHz



(B) Radiated Emission Test Set-Up, Frequency Below 1000MHz



(C) Radiated Emission Test Set-Up, Frequency above 1000MHz



深圳信测标准技术服务股份有限公司地址:广东省深圳市南山区马家龙工业区69栋 网址:Http://www.emtek.com.cn 邮箱:cs.rep@emtek.com.cn



7.3 Measurement Equipment Used:

Item	Equipment	Manufacturer	Model No.	Serial No.	Characteristics	Last Cal.	Cal. Interval
1.	Test Receiver	Rohde & Schwarz	ESCI	1166.5950.0 3	9KHz-3GHz	05/22/2020	1 Year
2.	Loop Antenna	Schwarzbeck	FMZB 1519	012	9 KHz -30MHz	05/22/2020	1 Year
3.	Bilog Antenna	Schwarzbeck	VULB9163	000141	25MHz-2GHz	05/22/2020	1 Year
4.	Power Amplifier	CDS	RSU-M352	818	1MHz-1GHz	05/22/2020	1 Year
5.	Power Amplifier	HP	8447F	OPT H64	1GHz-26.5GHz	05/22/2020	1 Year
6.	Color Monitor	SUNSPO	SP-140A	N/A		05/22/2020	1 Year
7.	Single Line Filter	JIANLI	XL-3	N/A		05/22/2020	1 Year
8.	Single Phase Power Line Filter	JIANLI	DL-2X100B	N/A		05/22/2020	1 Year
9.	3 Phase Power Line Filter	JIANLI	DL-4X100B	N/A		05/22/2020	1 Year
10.	DC Power Filter	JIANLI	DL-2X50B	N/A		05/22/2020	1 Year
11.	Cable	Schwarzbeck	PLF-100	549489	9KHz-3GHz	05/22/2020	1 Year
12.	Cable	Rosenberger	CIL02	A0783566	9KHz-3GHz	05/22/2020	1 Year
13.	Cable	Rosenberger	RG 233/U	525178	9KHz-3GHz	05/22/2020	1 Year
14.	Signal Analyzer	Rohde & Schwarz	FSV30	103040	9KHz-40GHz	05/22/2020	1 Year
15.	Horn Antenna	Schwarzbeck	BBHA9120D	9120D-1272	1GHz-18GHz	05/22/2020	1 Year
16.	Horn Antenna	Schwarzbeck	BBHA 9170	BBHA91703 99	14GHz -26.5GHz	05/22/2020	1 Year
17.	Power Amplifier	LUNAR EM	LNA1G18-4 0	J101000000 81	1GHz-26.5GHz	05/22/2020	1 Year
18.	Cable	H+S	CBL-26	N/A	1GHz-26.5GHz	05/22/2020	1 Year
19.	Cable	H+S	CBL-26	N/A	1GHz-26.5GHz	05/22/2020	1 Year
20.	Cable	H+S	CBL-26	N/A	1GHz-26.5GHz	05/22/2020	1 Year

深圳信测标准技术服务股份有限公司地址:广东省深圳市南山区马家龙工业区69栋 网址:Http://www.emtek.com.cn 邮箱:cs.rep@emtek.com.cn



7.4 Radiated Emission Limit

The emissions from an intentional radiator shall not exceed the field strength levels specified in the following table 15.209(a):

Frequencies	Field Strength	Measurement Distance
(MHz)	(micorvolts/meter)	(meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

15.205 Restricted bands of operation

MHz	MHz	MHz	GHz
0.090 - 0.110	16.42 - 16.423	399.9 - 410	4.5 - 5.15
¹ 0.495 - 0.505	16.69475 - 16.69525	608 - 614	5.35 - 5.46
2.1735 - 2.1905	16.80425 - 16.80475	960 - 1240	7.25 - 7.75
4.125 - 4.128	25.5 - 25.67	1300 - 1427	8.025 - 8.5
4.17725 - 4.17775	37.5 - 38.25	1435 - 1626.5	9.0 - 9.2
4.20725 - 4.20775	73 - 74.6	1645.5 - 1646.5	9.3 - 9.5
6.215 - 6.218	74.8 - 75.2	1660 - 1710	10.6 - 12.7
6.26775 - 6.26825	108 - 121.94	1718.8 - 1722.2	13.25 - 13.4
6.31175 - 6.31225	123 - 138	2200 - 2300	14.47 - 14.5
8.291 - 8.294	149.9 - 150.05	2310 - 2390	15.35 - 16.2
8.362 - 8.366	156.52475 - 156.52525	2483.5 - 2500	17.7 - 21.4
8.37625 - 8.38675	156.7 - 156.9	2690 - 2900	22.01 - 23.12
8.41425 - 8.41475	162.0125 - 167.17	3260 - 3267	23.6 - 24.0
12.29 - 12.293	167.72 - 173.2	3332 - 3339	31.2 - 31.8
12.51975 - 12.52025	240 - 285	3345.8 - 3358	36.43 - 36.5
12.57675 - 12.57725	322 - 335.4	3600 - 4400	(2)

Remark: 1. Emission level in dBuV/m=20 log (uV/m)

2. Measurement was performed at an antenna to the closed point of EUT distance of meters.

3. Only spurious frequency is permitted to locate within the Restricted Bands specified in provision of ξ 15.205, and the emissions located in restricted bands also comply with 15.209 limit.

深圳信测标准技术服务股份有限公司地址:广东省深圳市南山区马家龙工业区69栋 网址:Http://www.emtek.com.cn 邮箱:cs.rep@emtek.com.cn



7.5 Measurement Result

Operation Mode:	ТХ	Test Date :	July 20, 2020
Test By:	Loren	Temperature :	28 ℃
Test Result:	PASS	Humidity :	65 %
Measured Distance:	3m		

Below 30MHz:

Freq.	Ant.Pol.	Emission	Limit 3m	Over
		Level		
(MHz)	H/V	(dBuV/m)	(dBuV/m)	(dB)

Note: The low frequency, which started from 9KHz-30MHz, was pre-scanned and the result which was 20dB lower than the limit line per 15.31(o) was not reported.

Below 1000MHz:

Pass.

All modulation modes have been tested, the worst mode is (GFSK TX 2402MHz), the data is recorded on the following page, other modulation modes do not exceed this limit.

Please refer to the following data.

深圳信测标准技术服务股份有限公司 地址:广东省深圳市南山区马家龙工业区69栋 网址:Http://www.emtek.com.cn 邮箱:cs.rep@emtek.com.cn





No.	Mk.	Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Over		Antenna Height	Table Degree	
1		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree	Comment
1		31.1797	41.53	-18.91	22.62	40.00	-17.38	QP			
2		104.1701	40.48	-18.25	22.23	43.50	-21.27	QP			
3		156.4577	39.58	-20.89	18.69	43.50	-24.81	QP			
4		271.3245	36.15	-14.88	21.27	46.00	-24.73	QP			
5		519.0650	34.39	-8.56	25.83	46.00	-20.17	QP			
6	*	945.4400	33.75	-0.62	33.13	46.00	-12.87	QP			

*:Maximum data x:Over limit I:over margin

Operator: Lian

深圳信测标准技术服务股份有限公司地址:广东省深圳市南山区马家龙工业区69栋网址:Http://www.emtek.com.cn邮箱:cs.rep@emtek.com.cn





No.	Mk.	Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Over		Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree	Comment
1		30.0000	42.58	-18.76	23.82	40.00	-16.18	QP			
2		35.8746	38.56	-18.24	20.32	40.00	-19.68	QP			
3		104.1701	37.95	-18.25	19.70	43.50	-23.80	QP			
4		173.8135	38.83	-20.03	18.80	43.50	-24.70	QP			
5	2	513.6331	35.78	-8.64	27.14	46.00	-18.86	QP			
6	*	945.4400	34.83	-0.62	34.21	46.00	-11.79	QP			

*:Maximum data x:Over limit I:over margin

Operator: Lian

深圳信测标准技术服务股份有限公司 地址:广东省深圳市南山区马家龙工业区69栋 网址:Http://www.emtek.com.cn 邮箱:cs.rep@emtek.com.cn



Julv 20. 2020

Above 1000MHz~10th Harmonics:

Operation Mode: GFSK (CH1: 2402MHz)

All modulation modes have been tested, the worst mode is (GFSK), the data is recorded on the following page, other modulation modes do not exceed this limit.Please refer to the following data.

Test Date :

•			,	,					,	
Freq.	Ant. Pol.	Rea Level(d	ding BuV/m)	Correct Factor	Emission Level(dBuV/m)		Limit 3m		Margin(dB)	
(MHz)	H/V	PK	AV	dB	PK	AV	ΡK	AV	PK	AV
4804	V	91.38	74.19	-32.3	59.08	41.89	74	54	-14.92	-12.11
7206	V	93.44	76.86	-37.2	56.24	39.66	74	54	-17.76	-14.34
9608	V	91.93	70.67	-39.8	52.13	30.87	74	54	-21.87	-23.13
12010	V	93.94	71.31	-40.5	53.44	30.81	74	54	-20.56	-23.19
14412	V	92.23	70.17	-41.7	50.53	28.47	74	54	-23.47	-25.53
16814	V	96.31	71.58	-40.0	56.31	31.58	74	54	-17.69	-22.42
4804	Н	92.80	76.73	-31.6	61.20	45.13	74	54	-12.80	-8.87
7206	H	93.71	76.74	-35.5	58.21	41.24	74	54	-15.79	-12.76
9608	H	91.20	73.40	-38.3	52.90	35.10	74	54	-21.10	-18.90
12010	Н	95.53	72.70	-39.0	56.53	33.70	74	54	-17.47	-20.30
14412	Н	94.78	75.97	-42.0	52.78	33.97	74	54	-21.22	-20.03
16814	Н	95.61	71.02	-39.3	56.31	31.72	74	54	-17.69	-22.28

Operation Mode: GFSK (CH40: 2441MHz)

Test Date : July 20, 2020

Freq.	Ant.	Rea	ding	Correct	Emis	sion	Li	mit	Marg	in(dB)
	Pol.	Level(d	BuV/m)	Factor	Level(d	BuV/m)	3m(dBuV/m)			
(MHz)	H/V	PK	AV	dB	PK	AV	PK	AV	PK	AV
4882	V	96.36	70.53	-32.3	64.06	38.23	74	54	-9.94	-15.77
7323	V	93.50	74.16	-37.2	56.3	36.96	74	54	-17.70	-17.04
9764	V	92.04	70.93	-39.8	52.24	31.13	74	54	-21.76	-22.87
12205	V	95.11	75.46	-40.5	54.61	34.96	74	54	-19.39	-19.04
14646	V	92.49	74.69	-41.0	51.49	33.69	74	54	-22.51	-20.31
17087	V	93.95	72.34	-41.1	52.85	31.24	74	54	-21.15	-22.76
4882	Н	95.02	70.68	-31.6	63.42	39.08	74	54	-10.58	-14.92
7323	Н	91.87	72.06	-35.5	56.37	36.56	74	54	-17.63	-17.44
9764	н	96.36	76.25	-38.3	58.06	37.95	74	54	-15.94	-16.05
12205	н	96.10	72.85	-39.0	57.1	33.85	74	54	-16.90	-20.15
14646	Н	94.19	70.35	-42.0	52.19	28.35	74	54	-21.81	-25.65
17087	H	98.34	71.49	-41.5	56.84	29.99	74	54	-17.16	-24.01

深圳信测标准技术服务股份有限公司 地址:广东省深圳市南山区马家龙工业区69栋 网址:Http://www.emtek.com.cn 邮箱:cs.rep@emtek.com.cn



Freq.	Ant.	Rea	Reading		Emis	ssion	Li	mit	Margin(dB)	
	Pol.	Level(d	BuV/m)	Factor	Level(d	BuV/m)	3m(dBuV/m)			
(MHz)	H/V	PK	AV	dB	PK	AV	PK	AV	PK	AV
4960	V	95.78	70.36	-32.3	63.48	38.06	74	54	-10.52	-15.94
7440	V	98.83	73.97	-37.2	61.63	36.77	74	54	-12.37	-17.23
9920	V	92.99	74.76	-39.8	53.19	34.96	74	54	-20.81	-19.04
12400	V	96.80	70.51	-40.5	56.3	30.01	74	54	-17.70	-23.99
14880	V	97.77	74.84	-41.0	56.77	33.84	74	54	-17.23	-20.16
17360	V	97.91	75.02	-41.1	56.81	33.92	74	54	-17.19	-20.08
4960	Н	97.63	70.27	-31.6	66.03	38.67	74	54	-7.97	-15.33
7440	H	95.75	76.44	-35.5	60.25	40.94	74	54	-13.75	-13.06
9920	H	98.32	70.56	-38.3	60.02	32.26	74	54	-13.98	-21.74
12400	H	93.41	71.42	-39.0	54.41	32.42	74	54	-19.59	-21.58
14880	H	91.62	72.77	-42.0	49.62	30.77	74	54	-24.38	-23.23
17360	Н	93.16	74.50	-41.5	51.66	33	74	54	-22.34	-21.00

Operation Mode: GFSK (CH79: 2480MHz)

Test Date : July 20, 2020

Other harmonics emissions are lower than 20dB below the allowable limit.

- **Note:** (1) All Readings are Peak Value and AV.
 - (2) Emission Level= Reading Level+ Probe Factor +Cable Loss.
 - (3) The average measurement was not performed when the peak measured data under the limit of average detection.
 - (4) Measuring frequencies from 1GHz to 25GHz.

深圳信测标准技术服务股份有限公司 地址:广东省深圳市南山区马家龙工业区59栋 网址:Http://www.emtek.com.cn 邮箱:cs.rep@emtek.com.cn



7.5 Radiated Measurement Photos:



深圳信测标准技术服务股份有限公司地址:广东省深圳市南山区马家龙工业区69栋 网址:Http://www.emtek.com.cn邮箱:cs.rep@emtek.com.cn



8. Channel Separation test

8.1 Measurement Procedure

The EUT was operating in hopping mode or could be controlled its channel. Printed out the test result from the spectrum by hard copy function.

8.2 Test SET-UP (Block Diagram of Configuration)

EUT Spectrum Analyzer

8.3 Measurement Equipment Used:

EQUIPMENT TYPE	MFR	MODEL NUMBER	SERIAL NUMBER	Characteristics	LAST CAL.	CAL DUE.
Spectrum Analyzer	Rohde & Schwarz	FSV30	1321.3008K	10Hz-30GHz	05/22/2020	05/21/2021
Coaxial Cable	CDS	79254	46107086	10Hz-30GHz	05/22/2020	05/21/2021
Antenna Connector	ARTHUR-YANG	2244-N1TG1	N/A	10Hz-30GHz	05/22/2020	05/21/2021

Remark: The temporary antenna connector is soldered on the PCB board in order to perform conducted tests and this temporary antenna connector is listed in the equipment list.

8.4 Measurement Results:

Refer to attached data chart.

Spectrum Detector:	PK	Test Date :	July 20, 2020
Test By:	Loren	Temperature :	24 °C
Test Result:	PASS	Humidity :	53 %
Modulation:	GFSK	-	

Channel number	Channel frequency (MHz)	Separation Read Value (kHz)	Separation Limit 2/3 20dB Down BW(kHz)		
1	2402	999	>747		
40	2441	999	>747		
79	2480	1003	>747		

深圳信测标准技术服务股份有限公司地址:广东省深圳市南山区马家龙工业区69栋 网址:Http://www.emtek.com.cn 邮箱:cs.rep@emtek.com.cn







深圳信测标准技术服务股份有限公司 地址:广东省深圳市南山区马家龙工业区69栋 网址:Http://www.emtek.com.cn 邮箱:cs.rep@emtek.com.cn



Spectrum		0#	0.50 40 -0						
Att	18.80 dBm 35 dB	SWT	19 µs 👄	VBW 300 kHz	Mode Aut	o FFT			
●1Pk Max									
10 dBm	MI				D2[1]			1.	-0.33 dB 00290 MHz -0.17 dBm 97540 GHz
0 dBm	- En	~		DE		_			
-10 dBm-		F	-				-	-	
-20 dBm	_	_				7			
-30 dBm	-		L - H - H				-		
-40 dBm		_					_		
-50 dBm		-					_		
-60 dBm	_							-	
-70 dBm							_		
CF 2.48 GH	z	-		691 pt:	s		_	Spa	n 3.0 MHz
	N					Measuri	ng (111)	10000 B 4	2

深圳信测标准技术服务股份有限公司 地址:广东省深圳市南山区马家龙工业区69栋 网址:Http://www.emtek.com.cn 邮箱:cs.rep@emtek.com.cn



Spectrum Detector:	PK
Test By:	Loren
Test Result:	PASS
Modulation:	П/4-DQPSK

Test Date : Temperature : Humidity : July 20, 2020 24℃ 53 %

Channel number	Channel frequency (MHz)	Separation Read Value (kHz)	Separation Limit 2/3 20dB Down BW(kHz)
1	2402	1003	>932
40	2441	1003	>932
79	2480	999	>938



深圳信测标准技术服务股份有限公司 地址:广东省深圳市南山区马家龙工业区69栋 网址:Http://www.emtek.com.cn 邮箱:cs.rep@emtek.com.cn



₩ Spectrum Ref Level 18.80 dBm Offset 0.50 dB 🖷 RBW 100 kHz Att 35 dB SWT 19 µs 🕳 VBW 300 kHz Mode Auto FFT 0 1Pk Max D2[1] -0.14 de 1.00290 MHz 10 dBm-M1[1] -1.74 dBm 2.44000580 GHz MI 0 dBm -10 dBm -20 dBm--30 dBm--40 dBm -50 dBm--60 dBm -70 dBm-CF 2.441 GHz 691 pts Span 3.0 MHz anasosa**m 4**0 Measuring...



深圳信测标准技术服务股份有限公司 地址:广东省深圳市南山区马家龙工业区69栋 网址:Http://www.emtek.com.cn 邮箱:cs.rep@emtek.com.cn



Spectrum Detector:	PK	Test Date :	July 20, 2020	
Test By:	Loren	Temperature :	24 °C	
Test Result:	PASS	Humidity :	53 %	
Modulation:	8DPSK	-		
Channel number	Channel	Separation Read	Separation Limit	
	frequency (MHz)	Value (kHz)	2/3 20dB Down BW(kHz)	
1 2402		999	>938	
40	2441	1003	>935	
79 2480		999	>941	

Att 35	dB SWT 19 µs	🖝 VBW 300 kHz M	ode Auto FFT		
1Pk Max 10 dBm			D2[1] M1[1]	-0.05 de 998.60 kH: -1.23 dBn	
0 dBm		MI		2.40207380 GH:	
-10 dBm					
-20 dBm			_		
-30 dBm					
-40 dBm		_			
-50 dBm					
-60 dBm					
-70 dBm					
0E 0 400 CUp		691 nts		Span 3.0 MHz	

深圳信测标准技术服务股份有限公司 地址:广东省深圳市南山区马家龙工业区69栋 网址:Http://www.emtek.com.cn 邮箱:cs.rep@emtek.com.cn



₩ Spectrum Ref Level 18.80 dBm Offset 0.50 dB 🖷 RBW 100 kHz Att 35 dB SWT 19 µs 🕳 VBW 300 kHz Mode Auto FFT 0 1Pk Max D2[1] -0.14 dB 1.00290 MHz 10 dBm-M1[1] -1.79 dBm 2.44007090 GHz 0 dBm -10 dBm -20 dBm--30 dBm--40 dBm -50 dBm--60 dBm -70 dBm CF 2.441 GHz 691 pts Span 3.0 MHz European 440 Measuring...



深圳信测标准技术服务股份有限公司 地址:广东省深圳市南山区马家龙工业区69栋 网址:Http://www.emtek.com.cn 邮箱:cs.rep@emtek.com.cn


9. 20dB Bandwidth test

9.1 Measurement Procedure

The EUT was operating in hopping mode or could be controlled its channel. Printed out the test result from the spectrum by hard copy function.

9.2 Test SET-UP (Block Diagram of Configuration)

EUT Spectrum Analyzer

9.3 Measurement Equipment Used:

EQUIPMENT	MFR	MODEL	SERIAL	Characteristics	LAST	CAL DUE.
TYPE		NUMBER	NUMBER	1 A.	CAL.	
Spectrum Analyzer	Rohde & Schwarz	FSV30	1321.3008K	10Hz-30GHz	05/22/2020	05/21/2021
Coaxial Cable	CDS	79254	46107086	10Hz-30GHz	05/22/2020	05/21/2021
Antenna Connector	ARTHUR-YANG	2244-N1TG1	N/A	10Hz-30GHz	05/22/2020	05/21/2021

Remark: The temporary antenna connector is soldered on the PCB board in order to perform conducted tests and this temporary antenna connector is listed in the equipment list.

9.4 Measurement Results:

Refer to attached data chart.

Spectrum Detector:	PK	Test Date :	July 20, 2020
Test By:	Loren	Temperature :	24 °C
Test Result:	PASS	Humidity :	53 %
Modulation:	GFSK	-	

Channel number	Channel frequency	20dB Down
	(MHz)	BW(kHz)
1	2402	1120
40	2441	1120
79	2480	1120

深圳信测标准技术服务股份有限公司 地址:广东省深圳市南山区马家龙工业区69栋 网址:Http://www.emtek.com.cn 邮箱:cs.rep@emtek.com.cn



Att	35 dB	3 SWT 19 µs	VBW 300 kHz	Mode Auto FF	T	_
10 dBm			Ma	M1[1] ndB Bw	-0 2.40197 1.120100	.17 dBr 830 GH 20,00 d
-10 dBm				Q factor	1 1 1	2144.
-20 dBm		1	1.		12	
-30 dBm	_					_
-40 dBm-						-
-50 dBm						
-60 dBm						
-70 dBm						
CF 2.402 GH	łz		691 pt	s	Span 3	.0 MHz
Type Ref	Trel	X-value	Y-value	Eunction	Function Result	
M1	1	2.4019783 GHz	-0.17 dBm	ndB down	1.12	01 MHz
T1 T2	1	2.4014182 GHz 2.4025384 GHz	-20.04 dBm -20.24 dBm	ndB Q factor	2	0.00 dB 2144.4

Spect	rum		2					
Ref Le	evel	18.80 dBr 35 d	n Offset B SWT	0.50 dB	 RBW 100 kHz VBW 300 kHz 	Mode Auto F	FT	
• 1Pk Ma	ах							
10 dBm-						M1[1]		-0.68 dBn 2.44097400 GH 20.00 dB
0 dBm—	+	-				Q factor		1.120100000 MH: 2179.3
-10 dBm		_	-	1	1 +			+
-20 dBm	+			1			Te	
-30 dBm	-	_			-		-	
-40 dBm	-	_	-		-			
-50 dBm	-							
-60 dBm								
-70 dBm								
CF 2.44	41 GH	Iz	-	-	691 p	ts		Span 3.0 MHz
Marker								
Туре	Ref	Trc	X-value	8	Y-value	Function	Fu	nction Result
M1	_	1	2.4409	74 GHz	-0.68 dBm	ndB down		1.1201 MHz
T2		1	2.44041 2.44153	82 GHZ 84 GHZ	-20.63 dBm -20.73 dBm	Q factor		20.00 dB 2179.2
)[]] Me	asuring 📲	1000000 400 Z



Spectrum						
Ref Level Att	18.80 dBm 35 dB	Offset 0.50 dB SWT 19 µs	RBW 100 kHz	Mode Auto FF	r.	
1Pk Max						
10 dBm				M1[1]		-0.35 dBm 2.47997400 GHz 20.00 dB
0 dBm			MI	Bw		1.120100000 MHz 2214.0
-10 dBm				X	1	
-20 dBm		1		~	2	
-30 dBm			-		-	
-40 dBm-	<		-		-	
-50 dBm						
-60 dBm						
-70 dBm						
CF 2.48 GH	z		691 pts		-	Span 3.0 MHz
Marker	Init	warter 1	Manatas 1	encertain 1	Film	No. Beach
M1	1	2 470074 CH2	-0.35 dBm	ndB down	Fun	1 1201 MHz
T1	i	2.4794182 GHz	-20.30 dBm	ndB		20.00 dB
T2	1	2.4805384 GHz	-20.49 dBm	Q factor		2214.0
T2		2.4805384 GHz	-20.49 dBm	Q factor Meas	uring	2214.0



Spectrum Detector: Test By: Test Result: Modulation: РК Loren PASS П/4-DQPSK Test Date : Temperature : Humidity : July 20, 2020 24℃ 53 %

Channel number	Channel frequency	20dB Down
Channel number	(MHz)	BW(kHz)
1	2402	1398
40	2441	1398
79	2480	1407

							rum	Spect
		Mode Auto FFT	RBW 100 kHz VBW 300 kHz	t 0.50 dB 🖷 19 µs 🖷	Offset SWT	18.80 dBm 35 dB	evel 1	Ref Lo Att
					-		ах	D1Pk Ma
-1.28 dB 2.40200870 GF 20,00 d		M1[1]					_	10 dBm
1.398000000 MH 1718		Bw Q factor	Mi				-	0 dBm—
				1			n	-10 dBm
2	A5				TY	-	n	-20 dBm
				_		-		-30 dBm
	-		-	-		-	n	-40 dBm
				_			n	-50 dBm
	-	_		_			n	-60 dBm
							n	-70 dBm
Span 3.0 MH	-		691 pts			z	02 GH	CF 2.4
	-		A 20402 1		200	- 1		Marker
Function Result	Fu	Function	Y-value	IUE	2 40200	Trc	Ref	Type
20.00 dE		ndB	-21.15 dBm	1275 GHz	2.4012	1		T1
1718.2		Q factor	-21.46 dBm	6729 GHz	2.40267	1		T2

深圳信测标准技术服务股份有限公司 地址:广东省深圳市南山区马家龙工业区69栋 网址:Http://www.emtek.com.cn 邮箱:cs.rep@emtek.com.cn



Spect	rum		2.12					
Ref Lo	evel :	18.80 dBr 35 d	n Offset B SWT	0.50 dB	 RBW 100 kHz VBW 300 kHz 	Mode Auto FF		
1Pk M	ах							
10 dBm 0 dBm-					MI	M1[1] ndB Bw O factor		-1.69 dBn 2.44100430 GH: 20,00 dE 1.398000000 MH: 1746.1
-10 dBm	n		1					
-20 dBm	-		TY				12	
-30 dBm		~	-					
-40 dBm		_					-	
-50 dBm		-					-	
-60 dBm	-+-					_		
-70 dBm	+							
CF 2.4	41 GH	z		-	691 pts	1	-	Span 3.0 MHz
Marker	Pof	Trol	V-ualu		Y-ushio	Eunction	Eup	ction Pocult
M1	Ker	1	2.44100	43 GHz	-1.69 dBm	ndB down	Pub	1.398 MHz
T1		1	2.4402	75 GHz	-21.54 dBm	ndB		20.00 dB
T2	-	1	2.44167	29 GHz	-21.89 dBm	Q factor		1746.1

Spect	rum							
Ref L	evel	18.80 dBm 35 dB	Offset SWT	0.50 dB 🖷 19 µs 🖷	RBW 100 kHz VBW 300 kHz	Mode Auto I	FFT	
01Pk M	ax							
10 dBm	_					M1[1] ndB		-1.54 dBm 2.48000870 GHz 20.00 dB
0 dBm-						Q factor		1.406700000 MH2 1763.1
-10 dBn	n		/	-	-		1	
-20 dBn	n		TY	-			Te	
-30 dBm				-			5	
-40 dBm	n-+-		_					
-50 dBn	n	_	_					
-60 dBn	n	_					-	
-70 dBn	n							
CF 2.4	8 GHz				691 p	ts	-	Span 3.0 MHz
Marker	Pof	Trel	Y-ualua	1	Y-ualuo	Eunction	1 Em	action Result
M1	Net	1	2.480008	37 GHz	-1.54 dBm	ndB down	Fu	1,4067 MHz
T1		1	2.479270	06 GHz	-21.63 dBm	ndB	1	20.00 dB
T2		1	2.480677	73 GHz	-21.73 dBm	Q factor		1763.1
)[]) Mi	easuring 🚺	harosara 🚧 🖉



Spectrum Detect Test By: Test Result: Modulation:	or: PK Loren PASS 8DPSK	Test Date : Temperature : Humidity :	July 20, 2020 24℃ 53 %
C	Channel number	Channel frequency	20dB Down

Channel number	(MHz)	BW(kHz)
1	2402	1407
40	2441	1402
79	2480	1411

Ref Le	vel :	18.80 dBr 35 d	m Offset B SWT	0.50 dB	RBW 100 kHz	Mode Auto FF	T	()
1Pk Ma	x					india india in		
10 dBm—					- b	M1[1] ndB 11 Bw		-1.22 dBr 2.40207380 GH 20.00 d 1.406700000 MH
-10 dBm-			1	~		Qlaster	1	1707.
-20 dBm-			TY				As	
-30 dBm-		/					~	
-40 dBm-		_						
-50 dBm-	+	-						
-60 dBm-	+							
-70 dBm-								
CF 2.40	2 GH	z			691 pt	5		Span 3.0 MHz
Marker	Pof	Tec	Y-ushu		Y-value	Eunction	Fun	tion Result
M1	NG1	1	2.40207	38 GHz	-1.22 dBm	ndB down	own 1.4067 M ndB 20.00 ctor 1700	
T1 T2	-	1	2.40128	36 GHz 03 GHz	-21.45 dBm -21.32 dBm	ndB Q factor		



Spectrur						
Ref Leve Att	18.80 dB 35 (dB SWT 19 μs	 RBW 100 kHz VBW 300 kHz 	Mode Auto FF		
1Pk Max						
10 dBm				M1[1]		-1.74 dBn 2.44106950 GH: 20.00 dB
0 dBm			MI	Bw		1.402300000 MHz
-10 dBm	-			- m	1	
-20 dBm	/	77			12	
-30 dBm						
-40 dBm-			-		-	
-50 dBm						
-60 dBm						
-70 dBm						
CF 2.441	SHz		691 pts		-	Span 3.0 MHz
Marker	el Tun l	Mustus I	Marshan I	Function 1	Film	tion Desult
M1	1	2.4410695 GHz	-1.74 dBm	ndB down	1 4023 Mi	
T1	1	2.440288 GHz	-21.42 dBm	ndB	20.00	
T2	1	2.4416903 GHz	-21.78 dBm	Q factor		1740.7

Att	35 d	B SWT 19 µs	VBW 300 kHz	Mode Auto FF1			
1Pk Max							
10 dBm				M1[1]		-1.55 dBr 2.48007380 GH 20.00 d	
0 dBm		-		Bw		1.41100000 MHz 1757.7	
-10 dBm				1			
-20 dBm		TH			12		
-30 dBm					~		
-40 dBm-							
-50 dBm							
-60 dBm					_		
-70 dBm							
CF 2.48 G	-Iz		691 pts		_	Span 3.0 MHz	
Marker							
Type Re	f Trc	X-value	Y-value	Function	Function Result		
T1	1	2.4800738 GHz	-1.55 aBm	nds down 1.		1.411 MHZ 20.00 dB	
T2	1	2.4806946 GHz	-21.62 dBm	Q factor		1757.7	



10. Quantity of Hopping Channel Test

10.1 Measurement Procedure

The EUT was operating in hopping mode or could be controlled its channel. Printed out the test result from the spectrum by hard copy function.

10.2Test SET-UP (Block Diagram of Configuration)

EUT		Spectrum Analyzer
-----	--	-------------------

10.3Measurement Equipment Used:

EQUIPMENT TYPE	MFR	MODEL NUMBER	SERIAL NUMBER	Characteristics	LAST CAL.	CAL DUE.
Spectrum Analyzer	Rohde & Schwarz	FSV30	1321.3008K	10Hz-30GHz	05/22/2020	05/21/2021
Coaxial Cable	CDS	79254	46107086	10Hz-30GHz	05/22/2020	05/21/2021
Antenna Connector	ARTHUR-YANG	2244-N1TG1	N/A	10Hz-30GHz	05/22/2020	05/21/2021

Remark: The temporary antenna connector is soldered on the PCB board in order to perform conducted tests and this temporary antenna connector is listed in the equipment list.

10.4 Measurement Results:

Refer to attached	l data chart.		
Worst Test Mode	GFSK	Test Date :	July 20, 2020
Test By:	Loren	Temperature :	25 ℃
Test Result:	PASS	Humidity :	50 %

Hopping Channel	Quantity of Hopping	Quantity of Hopping
Frequency Range	Channel	Channel
2402-2480	79	>15



深圳信测标准技术服务股份有限公司。地址:广东省深圳市南山区马家龙工业区69栋 网址:Http://www.emtek.com.cn 邮箱:cs.rep@emtek.com.cn



11. Time of Occupancy (Dwell Time) test

11.1 Test Description

The Equipment Under Test (EUT) was set up to perform the dwell time measurements. The EUT was connected to the spectrum analyzer via a short coax cable. The dwell time is calculated by:

Dwell time = time slot length * hop rate / number of hopping channels * 31.6s

with:

- hop rate = $1600 \times 1/s$ for DH1 packets = 1600 s^{-1}

- hop rate = 1600/3 * 1/s for DH3 packets = $533.33 s^{-1}$

- number of hopping channels = 79

- 31.6 s = 0.4 seconds multiplied by the number of hopping channels = 0.4 s * 79

The highest value of the dwell time is reported.

11.2 Test SET-UP (Block Diagram of Configuration)

EUT

Spectrum Analyzer

11.3 Measurement Equipment Used:

EQUIPMENT TYPE	MFR	MODEL NUMBER	SERIAL NUMBER	Characteristics	LAST CAL.	CAL DUE.
Spectrum Analyzer	Rohde & Schwarz	FSV30	1321.3008K	10Hz-30GHz	05/22/2020	05/21/2021
Coaxial Cable	CDS	79254	46107086	10Hz-30GHz	05/22/2020	05/21/2021
Antenna Connector	ARTHUR-YANG	2244-N1TG1	N/A	10Hz-30GHz	05/22/2020	05/21/2021

Remark: The temporary antenna connector is soldered on the PCB board in order to perform conducted tests and this temporary antenna connector is listed in the equipment list.

11.4 Test Requirements / Limits

FCC Part 15, Subpart C, §15.247 (a) (1) (iii)

Frequency hopping systems in the 2400-2483.5 MHz band shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Since the Bluetooth technology uses 79 channels this period is calculated to be 31.6seconds. Refer to attached data chart

深圳信测标准技术服务股份有限公司 地址:广东省深圳市南山区马家龙工业区69栋 网址:Http://www.emtek.com.cn 邮箱:cs.rep@emtek.com.cn



Modulation:	GFSK	Test Date :	July 20, 2020
Test By:	Loren	Temperature :	25 ℃
Test Result:	PASS	Humidity :	50 %

11.5 Test result

Mode	Number of transmission in a 31.6(79 Hopping*0.4)	Length of transmissions time(msec)	Result (msec)	Limit (msec)
DH1	1600/(2*79) x 31.6 = 320	0.378	120.96	400
DH3	1600/(4*79) x 31.6 =160	1.670	267.2	400
DH5	1600/(6*79) x 31.6 =106.67	2.909	310.30	400

Remark: The results of worst cased was recorded.

DH1:



深圳信测标准技术服务股份有限公司 地址:广东省深圳市南山区马家龙工业区69栋 网址:Http://www.emtek.com.cn 邮箱:cs.rep@emtek.com.cn



DH3:



DH5:



深圳信测标准技术服务股份有限公司 地址:广东省深圳市南山区马家龙工业区69栋 网址:Http://www.emtek.com.cn 邮箱:cs.rep@emtek.com.cn



12. MAXIMUM PEAK OUTPUT POWER TEST

12.1 Measurement Procedure

a. Check the calibration of the measuring instrument(SA) using either an internal calibrator or a known signal from an external generator.

b. Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.

c. The center frequency of the spectrum analyzer is set to the fundamental frequency and using proper RBW and VBW setting.

d. Measure the captured power within the band and recording the plot.

e. Repeat above procedures until all frequencies required were complete.

12.2 Test SET-UP (Block Diagram of Configuration)

	1	
EUT		Spectrum Analyzer

12.3 Measurement Equipment Used:

EQUIPMENT TYPE	MFR	MODEL NUMBER	SERIAL NUMBER	Characteristics	LAST CAL.	CAL DUE.
Spectrum Analyzer	Rohde & Schwarz	FSV30	1321.3008K	10Hz-30GHz	05/22/2020	05/21/2021
Coaxial Cable	CDS	79254	46107086	10Hz-30GHz	05/22/2020	05/21/2021
Antenna Connector	ARTHUR-YANG	2244-N1TG1	N/A	10Hz-30GHz	05/22/2020	05/21/2021

Remark: The temporary antenna connector is soldered on the PCB board in order to perform conducted tests and this temporary antenna connector is listed in the equipment list.

深圳信测标准技术服务股份有限公司 地址:广东省深圳市南山区马家龙工业区69栋 网址:Http://www.emtek.com.cn 邮箱:cs.rep@emtek.com.cn



12.4Measurement Results:

Refer to attached data chart.

Spectrum Detector:	PK	Test Date :	July 20, 2020
Test By:	Loren	Temperature :	25 ℃
Test Result:	PASS	Humidity :	50 %
Modulation:	GFSK	-	

Channel number	Channel Frequency (MHz)	Peak Power output(dBm)	Peak Power output(mW)	Peak Power Limit(mW)	Pass/Fail
01	2402	0.51	1.125	1000	PASS
40	2441	0.04	1.009	1000	PASS
79	2480	0.19	1.045	1000	PASS



深圳信测标准技术服务股份有限公司。地址:广东省深圳市南山区马家龙工业区69栋 网址:Http://www.emtek.com.cn 邮箱:cs.rep@emtek.com.cn



Ref Level 18.80 (Att 35	dBm Offset	t 0.50 dB 🖷 🖡 1.3 µs 🖶 🕻	BW 3 MH	iz iz Mode	Auto FFT			
1Pk Max	- f	-		-				
					M1[1]		2.44	0.04 dBn +12470 GH:
10 dBm		-	-		1	1		1
				MI				
-10 dBm-		_		-	-	_	_	
-20 dBm	_		-	-	-		-	
-30 dBm				1				
-40 dBm								
-50 dBm		-		-	-	-		
			1.1.1.1.1.1.1		N. Lawrence			1
-60 dBm				-				
-70 dBm								
CF 2.441 GHz	_	-	69	1 pts	1		Spa	an 9.0 MHz
T					Measu	ring 🚦		0





Spectrum Detector:	PK	Test Date :	July 20, 2020
Test By:	Loren	Temperature :	25 ℃
Test Result: Modulation:	PASS Π/4-DQPSK	Humidity :	50 %

Channel number	Channel Frequency (MHz)	Peak Power output(dBm)	Peak Power output(mW)	Peak Power Limit(mW)	Pass/Fail
01	2402	2.12	1.629	125	PASS
40	2441	1.88	1.542	125	PASS
79	2480	1.60	1.445	125	PASS

Spectrum						
Att 35	am Offset dB SWT	0.50 dB 🖷 RI 1.3 µs 🖶 VI	BW 3 MHz BW 10 MHz	Mode Auto FFT		
91Pk Max						
		· · · · · ·		M1[1]		2.12 dBn 2.4015440 GH:
10 dBm			Mì			
0 dBm			-			
-10 dBm		1.1	_			
-20.dBm	-	· · · · · ·				
-30 dBm	-					
-40 dBm					-	
-50 dBm						
-60 dBm	-				-	
-70 dBm						
CE 2.402 GHz	_		691 nl	ts		Snan 9.0 MHz
IT IT IT			051 p	Mea	uring	



₽ Spectrum Ref Level 18.80 dBm Offset 0.50 dB 🖷 RBW 3 MHz Att 35 dB SWT 1.3 µs 🛢 VBW 10 MHz Mode Auto FFT • 1Pk Max M1[1] 1.88 dBm 2.4405700 GHz 10 dBm MI 0 dBm -10 dBm -20 dBm--30 dBm -40 dBm--50 dBm--60 dBm -70 dBm-CF 2.441 GHz 691 pts Span 9.0 MHz Measuring... Encourse 440 ₩ Spectrum Ref Level 18.80 dBm Offset 0.50 dB . RBW 3 MHz Att 35 dB SWT 1.3 µs 曼 VBW 10 MHz Mode Auto FFT 0 1Pk Max

M1[1] 1.60 dBm 2.4796870 GHz 10 dBm-M1 0 dBm -10 dBm -20 dBm -30 dBm -40 dBm--50 dBm--60 dBm -70 dBm-CF 2.48 GHz 691 pts Span 9.0 MHz Measuring... 📲

深圳信测标准技术服务股份有限公司 地址:广东省深圳市南山区马家龙工业区69栋 网址:Http://www.emtek.com.cn 邮箱:cs.rep@emtek.com.cn



Spectrum Detector: Test By: Test Result: Modulation: PK Loren PASS 8DPSK Test Date : Temperature : Humidity : July 20, 2020 25 ℃ 50 %

Channel number	Channel Frequency (MHz)	Peak Power output(dBm)	Peak Power output(mW)	Peak Power Limit(mW)	Pass/Fail
01	2402	2.69	1.858	125	PASS
40	2441	2.11	1.626	125	PASS
79	2480	2.00	1.585	125	PASS



深圳信测标准技术服务股份有限公司 地址:广东省深圳市南山区马家龙工业区69栋 网址:Http://www.emtek.com.cn 邮箱:cs.rep@emtek.com.cn



Spectrum					
Ref Level 18.80 df	am Offset dB SWT	0.50 dB 🖷 RBW 1.3 µs 👼 VBW	3 MHz 10 MHz Mode	Áuto FFT	
🔵 1Pk Max					
			N	11[1]	2.11 dBm 2.4414300 GHz
10 dBm			MI		
0 dBm	_		-		
	-				
-10 dBm					
-20 dBm					
-30 dBm	-	-			
-40 dBm-	-				
-50 dBm	-	-			
-60 dBm-	-	1.1.1.1.1.1.1		1.1	and second in the second
-70 dBm					
CF 2.441 GHz			691 pts		Span 9.0 MHz
				Measuring	[

Att 35	dB SWT	1.3 µs 🖶 🕻	BW 10 MHz	Mode Auto	FFT	
1Pk Max	1	1	_	Milti		a aa da
				MILI		2.4795570 GH
10 dBm-			MI			
0 dBm			-		-	
-10 dBm-						
-20 dBm						
-30 dBm						
-40 dBm						
2021						
-50 dBm						
-60 dBm	-	-				
	11					
-70 dBm						
	_	_		_		
GF 2.48 GHZ		_	691	prs	Measuring	span 9.0 MHz



13. Band EDGE test

13.1 Measurement Procedure

For Conducted Test

- 1. The transmitter output is connected to a spectrum analyzer. The resolution bandwidth is set to 100KHz. The video bandwidth is set to 300KHz.
- 2. The spectrum from 30MHz to 26 GHz is investigated with the transmitter set to the lowest, middle, and highest channels.

J	
EMI Test Receiver	Setting
Attenuation	Auto
RBW	100KHz
VBW	300KHz
Detector	Peak
Trace	Max hold

For Radiated emission Test

The EUT was placed on a styrofoam table which is 1.5m above ground plane.

The measurement procedure at the ban edges was simplified by performing the measurement in just one plot. Both, the in-band-emission and the unwanted emission were be encompassed by the span. After trace stabilization, the maximum peak was be determined by a peak detector and the value was marked by an appropriate limit line. The second limit line, which is 20dB below the first, marks the limit for the emissions in the unrestricted band. A maximum-peak-detector marks the highest emission in the unrestricted band next to the band edge.

The measurements were performed at the lower end of the 2.4GHz band. Use the following spectrum analyzer settings:

For Restricted Band, When spectrum scanned above 1GHz setting resolution bandwidth 1MHz, video bandwidth 3MHz:

EMI Test Receiver	Setting
Attenuation	Auto
RBW	1MHz
VBW	3MHz
Detector	Peak
Trace	Max hold

For Non-Restricted Band, When spectrum scanned above 1GHz setting resolution bandwidth 100KHz, video bandwidth 300KHz:

EMI Test Receiver	Setting
Attenuation	Auto
RBW	100KHz
VBW	300KHz
Detector	Peak
Trace	Max hold

深圳信测标准技术服务股份有限公司 地址:广东省深圳市南山区马家龙工业区69栋 网址:Http://www.emtek.com.cn 邮箱:cs.rep@emtek.com.cn



13.2 Test SET-UP (Block Diagram of Configuration)

For Conducted Test



13.3 Measurement Equipment Used:

For Conducted Test

EQUIPMENT TYPE	MFR	MODEL NUMBER	SERIAL NUMBER	Characteristics	LAST CAL.	CAL DUE.
Spectrum Analyzer	Rohde & Schwarz	FSV30	1321.3008K	10Hz-30GHz	05/22/2020	05/21/2021
Coaxial Cable	CDS	79254	46107086	10Hz-30GHz	05/22/2020	05/21/2021
Antenna Connector	ARTHUR-YANG	2244-N1TG1	N/A	10Hz-30GHz	05/22/2020	05/21/2021

Remark: The temporary antenna connector is soldered on the PCB board in order to perform conducted tests and this temporary antenna connector is listed in the equipment list.

For Radiated emission Test

Item	Equipment	Manufacturer	Model No.	Serial No.	Characteristics	Last Cal.	Cal. Interval
1	Signal Analyzer	Rohde & Schwarz	FSV30	103040	9KHz-40GHz	05/22/2020	1 Year
2	Horn Antenna	Schwarzbeck	BBHA9120D	9120D-12 72	1GHz-18GHz	05/22/2020	1 Year
3	Power Amplifier	LUNAR EM	LNA1G18-40	J1010000 0081	1GHz-26.5GHz	05/22/2020	1 Year
4	Cable	H+S	CBL-26	N/A	1GHz-26.5GHz	05/22/2020	1 Year
5	Cable	H+S	CBL-26	N/A	1GHz-26.5GHz	05/22/2020	1 Year
6	Cable	H+S	CBL-26	N/A	1GHz-26.5GHz	05/22/2020	1 Year

深圳信测标准技术服务股份有限公司地址:广东省深圳市南山区马家龙工业区69栋 网址:Http://www.emtek.com.cn 邮箱:cs.rep@emtek.com.cn



13.4 Measurement Results:

Refer to attached data chart.

Spectrum Detector:	PK	Test Date :	July 20, 2020
Test By:	Loren	Temperature :	25 ℃
Test Result:	PASS	Humidity :	50 %

1. Conducted Test

For Non-Hopping Mode:

Frequency (MHz)	Modulation	Peak Power Output(dBm)	Result of Band edge(dBc)	Band edge Limit(dBc)
2401.98	GFSK	-0.27	42.53	>20dBc
2402.01	pi/4-DQPSK	-1.34	40.59	>20dBc
2402.07	8DPSK	-1.35	39.87	>20dBc
2479.97	GFSK	-0.41	48.87	>20dBc
2480.01	pi/4-DQPSK	-1.39	48.04	>20dBc
2480.07	8DPSK	-1.51	47.60	>20dBc

Test plots of GFSK



濠圳信测标准技术服务股份有限公司地址:广东省深圳市南山区马家龙工业区69栋 网址:Http://www.emtek.com.cn 邮箱:cs.rep@emtek.com.cn



Ref Le	vel 18	3.80 dBr	n Offset 0	.50 dB 🖷	RBW 100 kH	2	Mode Aut	FET			
1Pk Ma	эx	35 U	5 341	19 h2 🖷	ADM 200 KU	6	MODE AU	OFFI			
10 dBm-		MI					D3[1 	1		2.4	-48.87 d 3.5890 MH -0.41 dBr 799690 GH
-10 dBm		()					-	_			
-20 dBm	A	-				-	-	-		-	-
-30 dBr			1					- 1			-
-40 dBm	r			~		23					
-50 dBm					2			m	m		hum
-60 dBm											
Yo ubii				1				-	1		1
CF 2.48	335 G	Hz			691	pts				Spa	n 10.0 MHz
Tuno	Pof	Trol	V-ualuo	- 1	Y-ualuo	1	Eurotio	. 1	Em	oction Pocul	
M1	NG1	1	2,47996	9 GHz	-0.41 dB	m	Tunctio		1.01	iction Resul	
D2 D3	M1 M1	1	3.51 3.58	7 MHz 9 MHz	-48.73 c	IB IB					

Test plots of pi/4-DQPSK



深圳信测标准技术服务股份有限公司 地址:广东省深圳市南山区马家龙工业区69栋 网址:Http://www.emtek.com.cn 邮箱:cs.rep@emtek.com.cn





Test plots of 8DPSK



深圳信测标准技术服务股份有限公司 地址:广东省深圳市南山区马家龙工业区69栋 网址:Http://www.emtek.com.cn 邮箱:cs.rep@emtek.com.cn



opeeu	um								V
Ref Le	vel 1	25 dB	Offset	0.50 dB	RBW 100 kHz	Made	Auto FFT		
1Pk Ma	ax.	35 UD	awi	ta ha 🖷	VBW 300 KHZ	Mode	AULO FFT		
10 dBm-		Mi				D M	3[1] 1[1]		-47.60 dl 3.5460 MH -1.51 dBn
0 dBm—	-	m			-		1	1	2.4800700 GM
-10 dBm	A	1.000		-					
-20 dBm	++	_		-		_			
-30 dBm	-		T				-	-	
-40 dBm	-			1			_	-	
-50 dBm	-	_			003		m		
-60 dBm	-							- mrs	
-70 dBm		_				_		-	
CF 2.48	335 G	Hz	-	-	691 pt	s	_		Span 10.0 MHz
Marker		Trail	at weater		A STATUS	L emis		-	ation Description
M1	Ref	1	2.480	e 107 GHz	-1.51 dBm	Func	tion	Fur	iction Result
D2	M1	1	3.4	15 MHz	-47.43 dB				
D3	M1	1	3.5	46 MHz	-47.60 dB				



For Hopping Mode:

Frequency (MHz)	Modulation	Peak Power Output(dBm)	Result of Band edge(dBc)	Band edge Limit(dBc)
2401.98	GFSK	-0.30	43.88	>20dBc
2402.01	pi/4-DQPSK	-1.48	41.34	>20dBc
2403.07	8DPSK	-1.5	45.07	>20dBc
2478.94	GFSK	-0.61	54.68	>20dBc
2479.84	pi/4-DQPSK	-2.47	48.47	>20dBc
2480.01	8DPSK	-3.13	50.11	>20dBc

Test plots of GFSK



深圳信测标准技术服务股份有限公司 地址:广东省深圳市南山区马家龙工业区69栋 网址:Http://www.emtek.com.cn 邮箱:cs.rep@emtek.com.cn





Test plots of pi/4-DQPSK



深圳信测标准技术服务股份有限公司 地址:广东省深圳市南山区马家龙工业区69栋 网址:Http://www.emtek.com.cn 邮箱:cs.rep@emtek.com.cn





Test plots of 8DPSK



濠圳信测标准技术服务股份有限公司地址:广东省深圳市南山区马家龙工业区69栋 网址:Http://www.emtek.com.cn 邮箱:cs.rep@emtek.com.cn



Spect	rum						
Ref Le Att	vel 1	8.80 dBm 35 dB	Offset 0.50 dB	 RBW 100 kHz VBW 300 kHz 	Mode Auto FF	T	
1Pk M	ах						
10 dBm-		MA1.			D3[1] M1[1]		-50.11 di 3.7480 MH -3.13 dBn 2.4800120 GH
0 dBm-	ant	mm				1 1	Lindsofted any
-10 dBm		A					
-20 dBm	-						
-30 dBm							
-40 dBm			w	-			
-50 dBm			- m	mago	3		
-60 dBm		-			m	mm	minim
-70 dBm		_					
CF 2.4	335 G	Hz		691 pt:	s		Span 10.0 MHz
Marker				ALCORDS 1	L emberin 1	-	
Type M1	Ref	1 Irc	2 480012 GHz	-3.13 dBm	Function	Functi	on Result
D2	M1	1	3.502 MHz	-48.91 dB			
D3	M1	1	3.748 MHz	-50.11 dB			



2. Radiated emission Test Worst test modulation GFSK

For Non-Hopping Mode:



No.	Mk	. Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Over		Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree	Comment
1		2374.492	57.91	-11.69	46.22	74.00	-27.78	peak		0	
2		2400.000	64.89	-11.63	53.26	74.00	-20.74	peak		0	
3		2400.000	48.25	-11.63	36.62	54.00	-17.38	AVG		0	
4	*	2402.000	103.99	-11.63	92.36	74.00	18.36	peak		0	

*:Maximum data x:Over limit I:over margin

Operator: HUANG

深圳信测标准技术服务股份有限公司地址:广东省深圳市南山区马家龙工业区69栋 网址:Http://www.emtek.com.cn 邮箱:cs.rep@emtek.com.cn

EMTEK (Shenzhen) Co., Ltd. Add: Building 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, China Http://www.emtek.com.cn E-mail: cs.rep@emtek.com.cn

Page 65 of 74





No.	Mk	. Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Over		Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree	Comment
1		2376.424	58.13	-11.68	46.45	74.00	-27.55	peak		0	
2		2400.000	70.98	-11.63	59.35	74.00	-14.65	peak		0	
3		2400.000	53.65	-11.63	42.02	54.00	-11.98	AVG		0	
4	*	2401.816	104.52	-11.63	92.89	74.00	18.89	peak		0	

Operator: HUANG

深圳信测标准技术服务股份有限公司 地址:广东省深圳市南山区马家龙工业区69栋 网址:Http://www.emtek.com.cm 邮箱:cs.rep@emtek.com.cn





No.	N	Лk.	Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Over		Antenna Height	Table Degree	
			MHz	dBu∀	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree	Comment
1	*	2	480.340	110.01	-11.45	98.56	74.00	24.56	peak			
2		2	483.500	54.49	-11.46	43.03	74.00	-30.97	peak			
3		2	484.920	55.79	-11.44	44.35	74.00	-29.65	peak			

Operator: HUANG

深圳信测标准技术服务股份有限公司地址:广东省深圳市南山区马家龙工业区69栋网址:Http://www.emtek.com.cn邮箱:cs.rep@emtek.com.cn





No.	Ν	٨k.	Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Over		Antenna Height	Table Degree	¢
			MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree	Comment
1	*	2	2480.240	107.19	-10.02	97.17	74.00	23.17	peak			
2		2	2483.500	56.30	-10.01	46.29	74.00	-27.71	peak			
3	3	2	2495.420	58.88	-9.95	48.93	74.00	-25.07	peak			

Operator: HUANG

深圳信测标准技术服务股份有限公司 地址:广东省深圳市南山区马家龙工业区69栋 网址:Http://www.emtek.com.cn 邮箱:cs.rep@emtek.com.cn

EMTEK (Shenzhen) Co., Ltd. Add: Building 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, China Http://www.emtek.com.cn E-mail: cs.rep@emtek.com.cn

Page 68 of 74



For Hopping Mode: 100.0 dBuV/m limit1: limit2: 90 80 70 60 50 40 30 20.0 2310.000 (MHz) 2402.000 Site Chamber #1 Polarization: Horizontal Temperature: 25 Power: AC 120V/60Hz Limit: (RE)FCC PART 15 C 3m_PEAK Humidity: 55 % Mode: Hopping Note:

No.	Mk	. Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Over		Antenna Height	Table Degree	
5		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree	Comment
1	ŝ	2372.928	57.11	-11.69	45.42	74.00	-28.58	peak		0	
2	8	2400.000	69.69	-11.63	58.06	74.00	-15.94	peak		0	
3	10297	2400.000	51.36	-11.63	39.73	54.00	-14.27	AVG		0	
4	*	2402.000	103.73	-11.63	92.10	74.00	18.10	peak		0	

*:Maximum data x:Over limit I:over margin

Operator: HUANG

深圳信测标准技术服务股份有限公司地址:广东省深圳市南山区马家龙工业区69栋 网址:Http://www.emtek.com.cn 邮箱:cs.rep@emtek.com.cn EMTEK (Shenzhen) Co., Ltd. Add: Building 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, China Http://www.emtek.com.cn E-mail: cs.rep@emtek.com.cn





No.	Mk.	. Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Over		Antenna Height	Table Degree	
		MHz	dBu∨	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree	Comment
1		2393.444	56.41	-10.51	45.90	74.00	-28.10	peak			
2		2400.000	66.45	-10.47	55.98	74.00	-18.02	peak			
3		2400.000	50.36	-10.47	39.89	54.00	-14.11	AVG			
4	*	2402.000	107.22	-10.46	96.76	74.00	22.76	peak			

Operator: HUANG

深圳信测标准技术服务股份有限公司 地址:广东省深圳市南山区马家龙工业区69栋 网址:Http://www.emtek.com.cn 邮箱:cs.rep@emtek.com.cn EMTEK (Shenzhen) Co., Ltd. Add: Building 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, China Http://www.emtek.com.cn E-mail: cs.rep@emtek.com.cn





No.	Mk.		. Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Over		Antenna Height	Table Degree	
			MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree	Comment
1	1	*	2480.080	109.73	-11.45	98.28	74.00	24.28	peak			
2	2		2483.500	54.89	-11.46	43.43	74.00	-30.57	peak			
3	1		2483.500	38.66	-11.46	27.20	54.00	-26.80	AVG			
4			2495.100	56.98	-11.43	45.55	74.00	-28.45	peak			

Operator: HUANG

深圳信测标准技术服务股份有限公司 地址:广东省深圳市南山区马家龙工业区69栋 网址:Http://www.emtek.com.cn 邮箱:cs.rep@emtek.com.cn





No.	N	Мk	. Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Over		Antenna Height	Table Degree	
			MHz	dBu∀	dB	dBu∀/m	dBu∨/m	dB	Detector	cm	degree	Comment
1		*	2480.000	108.57	-10.02	98.55	74.00	24.55	peak	2 - 200 Ma		
2	ŝ.		2483.500	54.49	-10.01	44.48	74.00	-29.52	peak			
3	0		2483.500	37.98	-10.01	27.97	54.00	-26.03	AVG			
4	8		2493.540	58.57	-9.95	48.62	74.00	-25.38	peak			

Operator: HUANG

深圳信测标准技术服务股份有限公司 地址:广东省深圳市南山区马家龙工业区69栋 网址:Http://www.emtek.com.cn 邮箱:cs.rep@emtek.com.cn


14. Antenna Application

14.1 Antenna requirement

The EUT'S antenna is met the requirement of FCC part 15C section 15.203 and 15.247.

FCC part 15C section 15.247 requirements:

Systems operating in the 2402-2480MHz band that are used exclusively for fixed, point-to-point operations may employ transmitting antennas with directional gain greater than 6dBi provided the maximum peak output power of the intentional radiator is reduced by 1dB for every 3dB that the directional gain of the antenna exceeds 6dBi.

14.2 Result

The EUT's antenna, permanent attached antenna, used a PCB antenna and integrated on PCB, The antenna's gain is 0 dBi and meets the requirement.

15. Photos of EUT

Please refer to external photos and internal photos.

*** End of Report ***

深圳信测标准技术服务股份有限公司 地址:广东省深圳市南山区马家龙工业区69栋 网址:Http://www.emtek.com.cn 邮箱:cs.rep@emtek.com.cn

EMTEK (Shenzhen) Co., Ltd. Add: Building 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, China Http://www.emtek.com.cn E-mail: cs.rep@emtek.com.cn



声明

Statement

1. 本报告无授权批准人签字及"检验报告专用章"无效;

This report will be void without authorized signature or special seal for testing report.

2. 未经许可本报告不得部分复制;

This report shall not be copied partly without authorization.

3. 本报告的检测结果仅对送测样品有效,委托方对样品的代表性和资料的真实性负责;

The test results or observations are applicable only to tested sample. Client shall be responsible for representativeness of the sample and authenticity of the material.

 本检测报告中检测项目标注有特殊符号则该项目不在资质认定范围内,仅作为客户委托、科研、教学或内部质量 控制等目的使用;

The observations or tests with special mark fall outside the scope of accreditation, and are only used for purpose of commission, research, training, internal quality control etc.

5. 本检测报告以实测值进行符合性判定,未考虑不确定度所带来的风险,本实验室不承担相关责任,特别约定、标 准或规范中有明确规定的除外;

The test results or observations are provided in accordance with measured value, without taking risks caused by uncertainty into account. Without explicit stipulation in special agreements, standards or regulations, EMTEK shall not assume any responsibility.

6. 对本检测报告若有异议,请于收到报告之日起20日内提出;

Objections shall be raised within 20 days from the date receiving the report.

深圳信测标准技术服务股份有限公司地址:广东省深圳市南山区马家龙工业区69栋 网址:Http://www.emtek.com.cn 邮箱:cs.rep@emtek.com.cn

EMTEK (Shenzhen) Co., Ltd. Add: Building 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, China Http://www.emtek.com.cn E-mail: cs.rep@emtek.com.cn