FCC §15.247 (i) & §1.1310 & §2.1091- MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Applicable Standard

According to subpart 15.247(i)and subpart §1.1310, systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

Report No.: RDG170921008-00B

Limits for Maximum Permissible Exposure (MPE) (§1.1310, §2.1091)

(B) Limits for General Population/Uncontrolled Exposure										
Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm²)	Averaging Time (minutes)						
0.3-1.34	614	1.63	*(100)	30						
1.34–30	824/f	2.19/f	*(180/f²)	30						
30–300	27.5	0.073	0.2	30						
300–1500	/	/	f/1500	30						
1500-100,000	/	/	1.0	30						

f = frequency in MHz; * = Plane-wave equivalent power density;

According to §1.1310 and §2.1091 RF exposure is calculated.

Calculation formula:

Prediction of power density at the distance of the applicable MPE limit

 $S = PG/4\pi R^2 = power density (in appropriate units, e.g. mW/cm^2);$

P = power input to the antenna (in appropriate units, e.g., mW);

G = power gain of the antenna in the direction of interest relative to an isotropic radiator, the power gain factor, is normally numeric gain;

R = distance to the center of radiation of the antenna (appropriate units, e.g., cm);

For simultaneously transmit system, the calculated power density should comply with:

$$\sum_{i} \frac{S_{i}}{S_{Limit,i}} \le 1$$

FCC Part 15.247 Page 15 of 121

Calculated Data:

Radio	Description	Frequency (MHz)	Antenna Gain		Conducted output power including Tune- up Tolerance		Evaluation Distance (cm)	Power Density (mW/cm²)	MPE Limit (mW/cm²)
			(dBi)	(numeric)	(dBm)	(mW)			
0	WLAN 5G Low Band	5180-5320	2.8	1.91	22	158.49	20.00	0.06	1.0
1	WLAN	2412-2462	2	1.58	30	1000.00	20.00	0.32	1.0
	2.4G+5G Whole Band	5180-5825	2.8	1.91	25	316.23	20.00	0.12	1.0
2	BLE	2402-2480	4	2.51	3	2.00	20.00	0.001	1.0

Report No.: RDG170921008-00B

Note:

The Radio 1(WLAN 2.4G+5G Band) can transmit in 2.4G band, or 5G band, or transmit in both band simultaneously. Radio 1(WLAN 2.4G+5G Band) and Radio 0 can't transmit in 5150-5250MHz band simultaneously.

The 3 radios can transmit simultaneously, the maximum RF exposure condition as below:

$$\sum_{i} \frac{S_{i}}{S_{Limit,i}}$$

$$= S_{Radio1-2.4G}/S_{limit-Radio1-2.4G} + S_{Radio1-5G}/S_{limit-Radio1-5G} + S_{Radio0-5G}/S_{limit-Radio0-5G} + S_{Radio0-5G}/S_{limit-Radio0-5G}$$

$$=0.06/1+0.32/1+0.12/1+0.001/1$$

=0.50

< 1.0

Result: The device meet FCC MPE at 20 cm distance

FCC Part 15.247 Page 16 of 121