

RF Exposure Report

FCC ID: 2BBBFBF2407AB1

Applicant: Minami Acoustics Limited

Address: No.13, Maonan Road, Torch Development District, Zhongshan City,
Guangdong Province, P.R. China

Manufacturer: Minami Acoustics Limited

Address: No.13, Maonan Road, Torch Development District, Zhongshan City,
Guangdong Province, P.R. China

Product: Base speaker

Brand(s): N/A

Test Model(s): B12 SPK

Series Model(s): N/A

Test Date: Feb. 10, 2025 ~ Feb. 25, 2025

Issued Date: Feb. 26, 2025

Issued By: Hwa-Hsing (Dongguan) Testing Co., Ltd.

Address: No.101, Building N1, Yuyuan 2 Road, Yuyuan Industrial Park,
HuangJiang Town, Dongguan City, People's Republic of China

Test Firm Registration No.: 915896

Designation No.: CN1255

Standards: FCC Part 2 (Section 2.1091)
KDB 447498 D01

IEEE C95.1


The above equipment has been tested by **Hwa-Hsing (Dongguan) Testing Co., Ltd.**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

Prepared by :




Wendy Lee

Reviewed by :



Sye Yang

Approved by :



Scott He

"This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. Our report includes all the tests requested by you and the results thereof based upon the information that you provided to us. The report would be invalid without specific stamp of test institute and the signatures of tester and approver."

Lab: [Hwa-Hsing \(Dongguan\) Testing Co., Ltd.](#)Address: [No.101, Building N1, Yuyuan 2 Road, Yuyuan Industrial Park, HuangJiang Town, Dongguan City, People's Republic of China](#)Tel: [0769-83078199](#)Web.: [www.hwa-hsing.com](#)E-Mail: [customerservice.dg@hwa-hsing.com](#)Release
Ver. 1.5

Table of contents

Release control record 3

1 General Information 4

1.1 General Description of EUT4

2 RF exposure limit..... 5

2.1 MPE calculation formula5

3 Calculation result of maximum conducted power..... 6

Appendix – Information on the Testing Laboratories.....7

Test Report No.: 22502050066-SE-US-01

Release control record

Issue No.	Reason for change	Date issued
2502050066-SE-US-01	Original Release	Feb. 26, 2025

Test Report No.: 22502050066-SE-US-01

1 General Information**1.1 General Description of EUT**

Product	Base speaker
Test Model(s)	B12 SPK
Sample No.	HS2502050066-S002
Series Model(s)	N/A
Status of EUT	Engineering Prototype
Power Supply Rating	Input: 29.0Vdc 3.0A from adapter
Modulation Type	GFSK, $\pi/4$ DQPSK, 8DPSK
Transfer Rate	1Mbps, 2Mbps, 3Mbps
Operating Frequency	2402 ~ 2480MHz
Number of Channel	79
Maximum Output Power	0.02dBm-Peak
Antenna Type and Antenna Gain	PIFA Antenna; 2.79dBi Gain
Antenna Connector	N/A
Accessory Device	1* AC/DC Switching power supply

Note:

1. Please refer to the EUT photo document (Reference No.: 2502050066-01&02) for detailed product photo.
2. The above EUT information is declared by manufacturer and for more detailed features description, please refer to the manufacturer's specifications or User's Manual.
3. The EUT is powered by adapter as list as below:

Adapter (fixed plug)	
Brand:	N/A
Model:	W87RA07-290030
Input:	100-240V~ 4.0A 50/60Hz
Output:	29.0Vdc 3.0A 87.0W
DC Line:	Unshielded, Detachable, 80cm
AC Line:	Unshielded, Detachable, 240cm

2 RF exposure limit

Limits for maximum permissible exposure (MPE)

Limits for general population / uncontrolled exposure				
Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Average time (minutes)
300-1500	F/1500	30
1500-100,000	1.0	30
Note: F = Frequency in MHz				

2.1 MPE calculation formula

$$P_d = (P_{out} \cdot G) / (4 \cdot \pi \cdot r^2)$$

Where: P_d = power density in mW/cm² P_{out} = output power to antenna in mW G = gain of antenna in linear scale π = 3.1416 R = distance between observation point and center of the radiator in cm**Classification:**

The antenna of this product, under normal use condition, is at least 20cm away from the body of the user.

Test Report No.: 22502050066-SE-US-01

3 Calculation result of maximum conducted power

The antennas provided to the EUT, please refer to the following table:

Function	Frequency (MHz)	Antenna Gain (dBi)	Antenna Type	Transmit and Receive Chain	Maximum Peak Power
BT	2402-2480	2.79dBi	PIFA	1TX,1RX	0.02 dBm

Conclusion:

Therefore, the worst-case situation is 0.00038 mW/cm², which is less than "1". This confirmed that the device compliance with FCC 1.1310 MPE limit.

Appendix – Information on the Testing Laboratories

We, [Hwa-Hsing \(Dongguan\) Testing Co., Ltd.](#), A global provider of TESTING and CERTIFICATION services for consumer products, electronic products and wireless information technology products. Adhering to the core values “HONEST and TRUSTWORTHY, OBJECTIVE and IMPARTIALITY, RIGOROUS and AFFICIENT”, commitment to provide professional, perfect and efficient comprehensive ONE-STOP solution of TESTING and CERTIFICATION services for Manufacturers, Buyers, Traders, Brands, Retailers. Assist client to better manage risk, protect their brands, reduce costs and cut time to over 150 markets in global. Our laboratories are FCC recognized accredited test firms and accredited and approved according to ISO/IEC 17025.

If you have any comments, please feel free to contact us at the following:

Lab Address: [No.101, Building N1, Yuyuan 2 Road, Yuyuan Industrial Park, HuangJiang Town, Dongguan City, People's Republic of China](#)

Contact Tel: [0769-83078199](#)

Email: Customerservice.dg@hwa-hsing.com

Web Site: www.hwa-hsing.com

--- END ---