

Exhibit: RF Exposure -FCC

FCC ID: AS57705SARHMC-1 Contain FCC ID:2AU8H-MG401

Client	Nokia Canada Inc	
Product	7705 SAR-Hmc NA(3HE12472AA)	TÜV
Standard(s)	FCC KDB 447498:2015	Canada

RF Exposure - FCC

The EUT transmits in several bands as depicted in the table below.

Table 1. Worst-Case Scenario of Maximum Power Output – dBm/10MHz

Radio Type	Band	47 CFR Rule Part	Frequency (MHz)	Max Power (dBm)	Max Power (mW)
LTE		96	3560.0	16.52	44.87
	48		3625.0	19.46	88.31
			3690.0	15.42	34.83

Radiofrequency Radiation Exposure Evaluation: Mobile Devices

Mobile devices shall be evaluated for RF radiation exposure according to the provisions of <u>FCC §2.1091 (d) (2)</u> (with Amendment 85 <u>FR18146</u>, April 1, 2020) and the MPE guidelines identified in <u>FCC §1.1310</u>.

As per FCC §1.1310 Table 1(B), the limit for Maximum Permissible Exposure (MPE) to radiofrequency electromagnetic fields for General Population/Uncontrolled Exposure in the frequency range of:

✓ 1.5GHz to 100GHz is 1.0 mW/cm².

The power density can be calculate using the formula:

$$P_d = (P_{out}*G) / (4*pi*R^2)$$

where,

f = frequency in MHz

 $P_d = Power density in mW/cm^2$

Pout = Conducted output power to antenna in mW

G = Numeric Antenna Gain

Pi = 3.1416

R1 = 20 cm

G = 7.2 dBi

MPE Calculation:

For user general use at 20 cm distance, the maximum conducted output power of 18.32dBm, the EUT complies with limits of General Population/Uncontrolled Exposure according to Table 2.

Client	Nokia Canada Inc	
Product	7705 SAR-Hmc NA(3HE12472AA)	SUD
Standard(s)	FCC KDB 447498:2015	Canada

Table 2. Uncontrolled Exposure at 20cm distance and 2dBm Power Output

Туре	Lower (MHz)	Upper (MHz)	Output power (dBm)	Antenna Gain (dBi)	EIRP (dBm)	EIRP (mW)	Calculated (mW/cm^2)	Limit (mW/cm^2)	Pass/Fail
LTE	3560	3690	19.46	7.1	26.56	452.89	0.709	1.00 <note 1=""></note>	Pass
WLAN2.4GHz Band	2412	-	23 <note 2=""></note>	5.0 <note 2=""></note>	28	630.96	0.126	1.00 <note 1=""></note>	Pass
WLAN5GHz Band	5180	-	23 <note 2=""></note>	5.0 <note 2=""></note>	28	630.96	0.126	1.00 <note 1=""></note>	Pass
Bluetooth	2401	-	23 <note 2=""></note>	5.0 <note 2=""></note>	28	100.00	0.020	1.00 <note 1=""></note>	Pass

Note 1. Limit according to General Uncontrolled Exposure: Tabe 110 § 1.1310 (e)(2): 1 [mW/om]
Note 2. Page 9 in RF Exposure Evaluation Report (2AU8H-MG401).

The EUT meets the requirements