

PERSONAL COMMUNICATIONS SECTOR

PRODUCT SAFETY AND COMPLIANCE EMC LABORATORY

EMC TEST REPORT

Test Report Number – 11714-1

Report Date - August 28, 2003

Report Revised – September 18, 2003 per CRN230917A.QDJ

The test results contained herein relate only to the model(s) identified. It is the manufacturer's responsibility to assure that additional production units of this model are manufactured with identical electrical and mechanical characteristics.

As the responsible EMC Engineer, I hereby declare that the equipment tested as specified in this report conforms to the requirements indicated.

Michael E. Lief

Signature

Name: <u>Michael E. Hill</u>

Title: Senior Electrical Engineer

Date : <u>2003-08-28</u>

This report must not be reproduced, except in full, without written approval from this laboratory.

THIS REPORT MUST NOT BE USED TO CLAIM PRODUCT ENDORSEMENT BY A2LA OR ANY AGENCY OF THE U.S. GOVERNMENT.

A2LA Certificate Number: 1846-01



EXHIBIT 6

Table of Contents

Description	Page
Test Report Details	4
Applicable Standards	4
Summary of Testing	5
General and Special Conditions	5
Equipment and Cable Configurations	6
Moscuring Equipment and Calibration Information	0
Measurement Dress dures and Date	Ö
Measurement Procedures and Data	_
RF Power Output	7
Radiated Power (ERP)	8
Occupied Bandwidth	9
GSM 1900 Occupied Band Plot	10
GSM 1900 Reference Plot	10
GSM 1900 Lower Band Edge	11
GSM 1900 Upper Band Edge	11
GSM 1900 A Min Block Edge	12
GSM 1900 A Max Block Edge	12
GSW 1900 B Min. Block Edge	13
GSM 1900 D Max Block Edge	10
GSM 1900 C, C2, C3 Mill. Dick Edge	14
GSM 1900 C1 Min Block Edge	15
GSM 1900 C1 Max Block Edge	15
GSM 1900 C3 Max Block Edge	16
GSM 1900 C4 Max/C5 Min Block Edge	16
GSM 1900 C4 Max Block Edge	17
GSM1900 C5 Min Block Edge	17
GSM 1900 C5 Max Block Edge	18
GSM 1900 D Min. Block Edge	18
GSM 1900 D Max Block Edge	19
GSM 1900 E Min. Block Edge	19
GSM 1900 E Max Block Edge	20
GSM 1900 F Min. Block Edge	20
GSM 1900 F Max Block Edge	21
Spurious Emissions at Antenna Terminals	22
GSM 1900 Tabular and Graphical Data	23
Field Strength of Spurious Emissions	24
GSM 1900 Tabular and Graphical Data	25
Frequency Stability	26
GSM 1900 Tabular and Graphical Data	27

Field Strength of Spurious Emissions From Unintentional	
Radiators	28
GSM 1900 Tabular and Graphical Data	29
Appendix A - Radiated Emissions Test Setup Photos	
Figure A.1 – Radiated Emissions Measurement	30
Figure A.2 – Substitution Measurement	30

Test Report Details

Tests Performed By:	Motorola Personal Communications Sector Product Safety and Compliance Group 600 North US Hwy 45 Libertyville, IL 60048 PH (847) 523-6167 Fax (847) 523-4538 Motorola PCS FRN: 0004321311 FCC Registration Number: 316588 Industry Canada Number: IC3908
Tests Requested By:	Motorola Inc. Personal Communications Sector 600 North US Hwy 45 Libertyville, IL 60048
Product Type:	Cellular Phone
Signaling Capability:	GSM 1900
Model Number:	SUG3561AA
Serial Numbers:	330005171, 330005174, 330005207
Testing Complete Date:	August 27, 2003

Applicable Standards

All tests and measurements indicated in this document were performed in accordance with the Code of Federal Regulations Title 47 Part 2, Sub-part J as well as the following parts:

- X Part 15 Subpart B Unintentional Radiators
- Part 22 Subpart H Public Mobile Services
- X Part 24 Personal Communications Services
- Part 90 Private Land Mobile Radio Service

Applicable Standards: TIA EIA 137-A, TIA EIA 98-C, ANSI 63.4 2001, RSS-118 (AMPS), RSS-128 (TDMA), RSS-129 (CDMA), RSS-133 (PCS)

Summary of Testing

Test	Test Name	
#		Pass/Fail
1	RF Power Output	NA
2	ERP (Effective Radiated Power)	NA
3	Modulation Characteristics	Pass
4	Occupied Bandwidth	Pass
5	Spurious Emissions at Antenna Terminal	Pass
6	Field Strength of Spurious Emissions	Pass
7	Frequency Stability	Pass
8	Field Strength of Spurious Emissions	Pass
	from Unintentional Radiators	
_		
lest	lest Name	Margin with respect
#		to the Limit
1		ΝΔ
1	RF Power Output	NA
1 2 2	RF Power Output ERP (Effective Radiated Power)	NA NA
1 2 3	RF Power Output ERP (Effective Radiated Power) Modulation Characteristics	NA NA NA
1 2 3 4	RF Power Output ERP (Effective Radiated Power) Modulation Characteristics Occupied Bandwidth	NA NA NA See Plots
1 2 3 4 5	RF Power Output ERP (Effective Radiated Power) Modulation Characteristics Occupied Bandwidth Spurious Emissions at Antenna Terminal	NA NA NA See Plots 31.9 dB
1 2 3 4 5 6	RF Power Output ERP (Effective Radiated Power) Modulation Characteristics Occupied Bandwidth Spurious Emissions at Antenna Terminal Field Strength of Spurious Emissions	NA NA NA See Plots 31.9 dB 4.7 dB
1 2 3 4 5 6 7	RF Power Output ERP (Effective Radiated Power) Modulation Characteristics Occupied Bandwidth Spurious Emissions at Antenna Terminal Field Strength of Spurious Emissions Frequency Stability	NA NA See Plots 31.9 dB 4.7 dB 24.75 Hz
1 2 3 4 5 6 7 8	RF Power Output ERP (Effective Radiated Power) Modulation Characteristics Occupied Bandwidth Spurious Emissions at Antenna Terminal Field Strength of Spurious Emissions Frequency Stability Field Strength of Spurious Emissions	NA NA See Plots 31.9 dB 4.7 dB 24.75 Hz 3.3 dB

The margin with respect to the limit is the minimum margin for all modes and bands. () indicates the margin at which the product exceeds the limit.

General and Special Conditions

The EUT was tested using a fully charged battery when applicable. Where a battery could not be used due to the need for a controlled variation of input voltage, an external power supply was utilized.

All testing was done in an indoor controlled environment with an average temperature of 22° C and relative humidity of 50%.

Equipment and Cable Configurations

The EUT was tested in a stand-alone configuration that is representative of typical use.

Measuring Equipment and Calibration Information

EIS	DRG Horn Antenna	3115	6222	9/30/2003
A.H. Systems Inc.	DRG Horn Antenna	SAS-200/571	265	4/29/2004
ETS	Log-Periodic Antenna	3148	1189	4/29/2004
ETS	Biconical Antenna	3110B	3369	4/29/2004
ETS	Biconical Antenna	3110B	3370	10/25/2003
Attenuator	Weinschel	AS-6	6675	10/3/2003
Attenuator	Weinschel	AS-6	6677	10/3/2003
Rohde & Schwarz	Mobile Test Set	CMD 80	DE29008	N/A
Hewlett Packard	Signal Generator	83623B	3844A01195	5/20/2004
Thermotron	Environmental Chamber	S-4	31580	12/19/2003
Hewlett Packard	Pre-Amplifier	8347A		
Hewlett Packard	Pre-Amplifier	8447F	2805A03419	5/19/2004
Agilent	Power Meter	EE4418B		11/26/2003
Agilent	Sensor	E4412B		11/23/2004

All equipment is on a one-year calibration cycle.

Measurement Procedures and Data

RF POWER OUTPUT

Measurement Procedure

The RF output port of the equipment under test is directly coupled to the input of a HPE4406A Vector Signal Analyzer through a 10dB passive attenuator, adaptor (if needed), and specialized RF connector. The peak power output is measured for all channels.

CFR Part 2.1046

Measurement Results

* Data supplied by SAR Lab

GSM 1900

Frequency (MHz)	Power (dBm)
1850.20	30.81
1880.00	30.80
1909.80	30.80

RADIATED (ERP)

Measurement Procedure

The phone was tested in a 16' cubical anechoic chamber with a 2-axis position system that permits taking complete spherical scans of the EUT's radiation patterns. For all tests, the phone was supported in a free space type environment, vertically oriented in the chamber. Tests were done for GSM 1900 three frequencies (1850.2, 1880.00, and 1909.80 MHz) with antenna stubby.

GSM measurements were made with the phone placed in a call using the HP8922M mobile station test set. The phone was weakly coupled to the test set and configured to transmit in full data rate mode. Radiated power was measured at each 15 degree step. The radiated power was measured using a Gigatronics 8542C power meter in "Burst Avg" mode. From these measurements, the software calculates the angle at which maximum radiated power occurs for each case, and the radiated power at this angle was extracted from the data. The max radiated power results for the QDJ-03008LUG001 follows, as EIRP in dBm. To get ERP (effective radiated power referenced to a half-wave dipole), subtract 2.1 dB from these numbers.

Measurement Results

* Data not supplied by EMC Lab

GSM 1900

1850.2 MHz: 28.61 dBm 1880.0 MHz: 28.67 dBm 1909.8 MHz: 29.03 dBm

For all measurements, calibration was performed via gain substitution with a halfwave dipole.

Max EIRP in GSM 1900 is 29.03dBm mode (max ERP is 26.93 dBm)

OCCUPIED BANDWIDTH

CFR Part 2.1049, 24.238, 22.917

Measurement Procedure

The RF output port of the equipment under test is directly coupled to the input of the EMC analyzer through a specialized RF connector and a 10dB passive attenuator. The amplitude of the spectrum analyzer is corrected for the attenuator and any other applicable losses. A fully charged battery was used for the supply voltage.

The middle channel within the designated frequency block was measured. For digital modulation, the lower and upper band edge plots are displayed.

Measurement Results – GSM 1900



1900 GSM Occupied Band



1900 GSM Reference Plot



1900 GSM Lower Band Edge



1900 GSM Upper Band Edge



GSM 1900 A Min Block Edge



GSM 1900 A Max. Block Edge



GSM 1900 B Min. Block Edge



GSM 1900 B Max Block Edge



GSM 1900 C, C2, C3 Min. Block Edge



GSM 1900 C2 Max Block Edge







GSM 1900 C1 Max. Block Edge



GSM 1900 C3 Max Block Edge



GSM 1900 C4 Min Block Edge







GSM 1900 C5 Min. Block Edge



GSM 1900 C5 Max. Block Edge



GSM 1900 D Min. Block Edge



GSM 1900 D Max. Block Edge



GSM 1900 E Min. Block Edge



GSM 1900 E Max. Block Edge



GSM 1900 F Min. Block Edge



GSM 1900 F Max. Block Edge

SPURIOUS EMISSIONS AT ANTENNA TERMINALS

CFR Part 2.1051, 22.917, 24.238

Measurement Procedure

The RF output port of the Equipment Under Test is directly coupled to the input of the EMC analyzer through a specialized RF connector and a 10dB passive attenuator. A fully charged battery was used for the supply voltage.

The spectrum was investigated from the lowest frequency signal generated, without going below 9 kHz, up to at least the tenth harmonic of the fundamental or 40 GHz, whichever is lower.

Measurements were made at the middle channel within the frequency band and within the base station frequency range for PCS.

Instrument Settings

Resolution Bandwidth:	1 MHz
Video Bandwidth:	>= RBW
Detector:	Peak
Sweep:	Auto – Cal
Trace:	Max Hold

Measurement Results

Harmonic of Fundamental	FCC Maximum Limit (dBm)	Conducted Emission (dBm)
2nd harmonic	-13	-44.9
3rd harmonic	-13	-50.5
4th harmonic	-13	-48.7
5th harmonic	-13	-48.2
6th harmonic	-13	-44.9
7th harmonic	-13	-45.9
8th harmonic	-13	-44.9
9th harmonic	-13	*
10th harmonic	-13	*

Conducted Spurious and Harmonic Emissions



Notes:

- 1. * Indicates the spurious emission could not be detected due to noise limitations or ambients.
- 2. Each emission reported reflects the highest absolute level at the specific harmonic for the low, mid, and high channels at maximum power.
- 3. The Spectrum was investigated from 9 kHz to the tenth harmonic of the fundamental.

FIELD STRENGTH OF SPURIOUS EMISSIONS

CFR Part 2.1053, 22.917, 24.238

Measurement Procedure

The equipment under test is placed inside the semi-anechoic chamber on a wooden table at the turntable center. For each spurious frequency, the antenna mast is raised and lowered from 1 to 4 meters and the turntable is rotated 360 degrees to obtain a maximum reading on the spectrum analyzer. This is repeated for both horizontal and vertical polarizations of the receive antenna.

The equipment under test is then replaced with a substitution antenna fed by a signal generator. With the signal generator tuned to a particular spurious frequency, the antenna mast is raised and lowered from 1 to 4 meters to obtain a maximum reading at the spectrum analyzer. The output of the signal generator is then adjusted until a reading identical to that obtained with the actual transmitter is achieved.

The power in dBm of each spurious emission is calculated by correcting the signal generator level for cable loss and gain of the substitution antenna referenced to a dipole. A fully charged battery was used for the supply voltage.

Instrument Settings

Resolution Bandwidth: 1 MHz Video Bandwidth: >= RBW Detector: Peak Sweep: Auto – Cal Trace: Max Hold

Measurement Results

Frequency (MHz)	FCC Maximum Limit (dBm)	Horizontal Measured Emission Equiv. Pwr Into Ideal Dipole (dBm)	Vertical Measured Emission Equiv Pwr Into Ideal Dipole (dBm)
2nd harmonic	-13	-17.7	-19.9
3rd harmonic	-13	-29.0	-28.6
4th harmonic	-13	-43.9	-49.5
5th harmonic	-13	*	*
6th harmonic	-13	-31.7	-31.8
7th harmonic	-13	-37.6	-40.8
8th harmonic	-13	-34.7	*
9th harmonic	-13	*	*
10th harmonic	-13	*	*

Radiated Spurious and Harmonic Emissions



Notes:

- 1. * Indicates the spurious emission could not be detected due to noise limitations or ambients.
- 2. Each emission reported reflects the highest absolute level at the specific harmonic for the low, mid, and high channels at maximum power.
- 3. The Spectrum was investigated from 30 MHz to the tenth harmonic of the fundamental.

FREQUENCY STABILITY

CFR Part 2.1055, 22.355, 24.235

Measurement Procedure

The equipment under test is placed in an environmental chamber. The antenna port of the Equipment Under Test is directly coupled to the input of the measurement equipment through a specialized RF connector. A power supply is attached as the primary voltage supply.

Frequency measurements are made at the extremes of the temperature range -30° C to +60° C and at intervals of 10° C with the primary supply voltage set to the nominal battery operating voltage. A period of time sufficient to stabilize all components of the equipment is allowed at each frequency measurement. The maximum variation of frequency is measured.

At room temperature, the primary supply voltage is reduced to the battery operating endpoint of the equipment under test. The maximum variation of frequency is measured. A battery eliminator was used for the input supply voltage.

Measurement Results

Frequency Stability

Mode: GSM 1900 Channel: 661 Operating Frequency: 1880.0 MHz Deviation Limit (PPM): 0.1 ppm

Temperature	Frequency Error	Frequency Error	Voltage	Voltage
С	HZ	(PPM)	(%)	(VDC)
-30 C	18.49	0.010	100%	3.8 (3.6 Specified)
-20 C	20.44	0.011	100%	3.8 (3.6 Specified)
-10 C	21.06	0.011	100%	3.8 (3.6 Specified)
0 C	19.83	0.011	100%	3.8 (3.6 Specified)
10 C	17.26	0.009	100%	3.8 (3.6 Specified)
20 C	21.36	0.011	100%	3.8 (3.6 Specified)
30 C	18.94	0.010	100%	3.8 (3.6 Specified)
40 C	18.99	0.010	100%	3.8 (3.6 Specified)
50 C	20.81	0.011	100%	3.8 (3.6 Specified)
60 C	24.75	0.013	100%	3.8 (3.6 Specified)
20 C	24.14	0.013	Battery Endpoint	3.40



Engineer: Kien Date: 08/13/03 Product Name: MPX200 Submission #: 11707-1 S/N: 330005171

(Uncontrolled When Printed)

Form Control Number: FCD-0192, Rev. 3

FIELD STRENGTH OF EMISSIONS FROM UNINTENTIONAL RADIATORS

CFR Part 15.109

Measurement Procedure

The equipment under test is placed inside the semi-anechoic chamber on a wooden table at the turntable center. For each radiated emission, the antenna mast is raised and lowered from 1 to 4 meters and the turntable is rotated 360 degrees to obtain a maximum peak reading on the spectrum analyzer. The radiated emissions are then measured using an EMI receiver employing a CISPR quasi-peak detector function below 1000 MHz and an average detector function above 1000 MHz. This is repeated for both horizontal and vertical polarizations of the receive antenna. A fully charged battery was used for the supply voltage.

The field strength of each radiated emission is calculated by correcting the EMI receiver level for cable loss, amplifier gain, and antenna correction factors.

Field Strength (dBuV/m) = EMI Receiver Level (dBuV) + Cable Loss (dB) -Amplifier Gain (dB) + Antenna Correction Factor (1/m)

Instrument Settings

Resolution Bandwidth: 120 kHz (Below 1 GHz), 1 MHz (Above 1 GHz) Video Bandwidth: >= RBW Detector: QP (30 MHz – 1 GHz), Ave (> 1GHz), Peak to scan Sweep: Auto – Cal Trace: Max Hold

Measurement Results

Frequency (MHz)	FCC Maximum Limit (dBuV/m)	Horizontal Measured Field Strength (dBuV/m)	Vertical Measured Field Strength (dBuV/m)
Local Oscillator	54	*	*
2nd harmonic	54	42.8	42.7
3rd harmonic	54	46.1	46.2
4th harmonic	54	49.3	49.4
5th harmonic	54	50.5	50.7
6th harmonic	54	*	*
7th harmonic	54	*	*
8th harmonic	54	*	*
9th harmonic	54	*	*
10th harmonic	54	*	*

Receiver Radiated Spurious Emissions



Notes:

- 1. * Indicates the spurious emission could not be detected due to noise limitations or ambients.
- 2. Each emission reported reflects the highest absolute level at the specific frequency for the low, mid, and high channels.



Appendix A – Radiated Emissions Test Setup Photos

A.1 Radiated Emissions Measurement



A.2 Substitution Measurement

End of Test Report