

1. MAXIMUM PERMISSIBLE EXPOSURE (MPE)

1.1 Client Information

| | |
|--------------------------|--|
| Applicant: | Shenzhen Chuanghongyu Technology Co., Ltd. |
| Address of applicant: | 301 Jinjin Building, No. 242 Jihua Road, Jihua Street, Longgang District, Shenzhen, Guangdong Sheng, China |
| Manufacturer: | Shenzhen Chuanghongyu Technology Co., Ltd. |
| Address of manufacturer: | 301 Jinjin Building, No. 242 Jihua Road, Jihua Street, Longgang District, Shenzhen, Guangdong Sheng, China |

General Description of EUT

| | |
|----------------------|-------------------------|
| Product Name: | Driving Recorder |
| Trade Name: | / |
| Model No.: | V23 |
| Adding Model(s): | V20,V21,V22,V25,V26,V27 |
| Rated Voltage: | Battery DC3.7V/250mAh |
| Power Adapter Model: | / |
| Serial number: | 20243698547DD25 |
| FCC ID: | 2BFBD-V23 |

Technical Characteristics of EUT

| | |
|-----------------------|--|
| Support Standards: | 802.11b, 802.11g, 802.11n |
| Frequency Range: | 2412-2462MHz for 802.11b/g/n(HT20) 2422-2452MHz for 802.11n(HT40) |
| RF Output Power: | 16.41dBm (Conducted) |
| Type of Modulation: | DBPSK, BPSK, DQPSK, QPSK, 16QAM, 64QAM |
| Quantity of Channels: | 11 for 802.11b/g/n(HT20); 7 for 802.11n(HT40) |
| Channel Separation: | 5MHz |
| Type of Antenna: | Integral Antenna |
| Antenna Gain: | 2.73dBi |

1.2 Standard Applicable

According to §1.1307(b)(1) and KDB 447498 D01 General RF Exposure Guidance v06, system operating under the provisions of this section shall be operating in a manner that the public is not exposed to radio frequency energy level in excess limit for maximum permissible exposure.

(a) Limits for Occupational / Controlled Exposure

| Frequency range (MHz) | Electric Field Strength (E) (V/m) | Magnetic Field Strength (H) (A/m) | Power Density (S) (mW/cm ²) | Averaging Times E ² , H ² or S (minutes) |
|-----------------------|-----------------------------------|-----------------------------------|---|--|
| 0.3-3.0 | 614 | 1.63 | (100)* | 6 |
| 3.0-30 | 1842/f | 4.89/f | (900/f)* | 6 |
| 30-300 | 61.4 | 0.163 | 1.0 | 6 |
| 300-1500 | / | / | F/300 | 6 |
| 1500-100000 | / | / | 5 | 6 |

(b) Limits for General Population / Uncontrolled Exposure

| Frequency range (MHz) | Electric Field Strength (E) (V/m) | Magnetic Field Strength (H) (A/m) | Power Density (S) (mW/cm ²) | Averaging Times E ² , H ² or S (minutes) |
|-----------------------|-----------------------------------|-----------------------------------|---|--|
| 0.3-1.34 | 614 | 1.63 | (100)* | 30 |
| 1.34-30 | 824/f | 2.19/f | (180/f)* | 30 |
| 30-300 | 27.5 | 0.073 | 0.2 | 30 |
| 300-1500 | / | / | F/1500 | 30 |
| 1500-100000 | / | / | 1 | 30 |

Note: f = frequency in MHz: * = Plane-wave equivalents power density

1.3 MPE Calculation Method

$$S = (30 * P * G) / (377 * R^2)$$

S = power density (in appropriate units, e.g., mw/cm²)

P = power input to the antenna (in appropriate units, e.g., mw)

G = power gain of the antenna in the direction of interest relative to an isotropic radiator, the power gain factor is normally numeric gain.

R = distance to the center of radiation of the antenna (in appropriate units, e.g., cm)

1.4 MPE Calculation Result

Maximum peak output power: 17.0 (dBm)

Maximum peak output power at antenna input terminal: 43.75(mW)

Prediction distance: >20(cm)

Prediction frequency: 2437 (MHz)

Antenna gain: 2.73 (dBi)

Directional gain: 1.17 (numeric)

The worst case is power density at prediction frequency at 20cm: 0.01(mw/cm²)

MPE limit for general population exposure at prediction frequency: 1 (mw/cm²)

$$0.01(\text{mw}/\text{cm}^2) < 1 (\text{mw}/\text{cm}^2)$$

So the transmitter complies with the RF exposure requirements and the SAR is not required.