
## **Features**

- S-Band Antenna
- Handles up to 50W power
- Sleeve Dipole
- Broad Band Coverage
- Omni Radiation Pattern
- ► Integrated RF Co-Axial Gooseneck
- ▶ Black Chrome Non-Rotating RP-TNC Male Connector



**Elevation Pattern** Referenced to +5dBi

## **Specifications**

Frequency 2.1 - 2.5 GHz

Gain 2.15 dBi

**VSWR** <2:1

Impedance 50 Ohms

**Polarization** Vertical

Omni or Directional Omni

Horizontal Beamwidth 360°

**Vertical Beamwidth** 77°

**RF Connector Type** RP-TNC(m) Non-Rotating

RF Connector Finish Black Chrome

**Length** 7.07 in / 18 cm

Radome Diameter 0.562 in / 1.4 cm

Radome Length 3.53 in / 9 cm

Gooseneck Diameter 0.350 in / 0.89 cm

Gooseneck Length 3 in / 7.6 cm

**Weight** 1.8 oz / 51 g

## ONE SOLUTION. INFINITE POSSIBILITIES.

© 2016 Persistent Systems, LLC. All rights reserved. The Wave Relay® logo, the Persistent Systems, LLC logo and other designated trademarks and trade names are the property of Persistent Systems, LLC or their respective owners. Product specifications are subject to change without notice. This material is provided for informational purposes only; Persistent Systems, LLC assumes no liability related to its use and expressly disclaims any implied warranties of merchantability or fitness for any particular purpose.





