



FCC AND ISCED CERTIFICATION TEST REPORT

Applicant	:	Robert Bosch GmbH
Address of Applicant	:	Robert-Bosch-Strasse 200, Hildesheim 31139, Germany
Manufacturer	:	Robert Bosch GmbH
Address of Manufacturer	:	Robert-Bosch-Strasse 200, Hildesheim 31139, Germany
Equipment under Test	:	Coach smartInfotainment series
Model name	:	Coach smartRadio Gen2
Part Numbers	:	7620210052
FCC ID	:	2AUXS-SISGEN2
IC	:	25847-SISGEN2
Test Standard(s)	:	FCC Rules and Regulations Part 15 Subpart C, RSS-247 Issue 3 August 2023, ANSI C63.10:2020, RSS-Gen Issue 5, Apr. 2018, Amendment 2 (February 2021)
Report No.	:	DDT-RE24110530-4E01
Issue Date	:	2025/01/11
Issue By	:	Guangdong Dongdian Testing Service Co., Ltd. Unit 2, Building 1, No. 17, Zongbu 2nd Road, Songshan Lake Park, Dongguan, Guangdong, China, 523808

REPORT

Table of Contents

1.	Summary of Test Results	7
2.	General Test Information.....	8
2.1.	Description of EUT	8
2.2.	Accessories of EUT	9
2.3.	Block diagram of EUT configuration for test	9
2.4.	Decision of final test mode	9
2.5.	Deviations of test standard	10
2.6.	Test environment conditions	10
2.7.	Test laboratory	10
2.8.	Measurement uncertainty	11
3.	Equipment Used During Conductive Test	12
4.	20 dB Bandwidth	13
4.1.	Block diagram of test setup	13
4.2.	Limits.....	13
4.3.	Test procedure	13
4.4.	Test result	14
4.5.	Test graphs	15
5.	99% Bandwidth	18
5.1.	Block diagram of test setup	18
5.2.	Limits.....	18
5.3.	Test procedure	18
5.4.	Test result	19
5.5.	Test graphs	20
6.	Maximum Peak Output Power.....	23
6.1.	Block diagram of test setup	23
6.2.	Limits.....	23
6.3.	Test procedure	23
6.4.	Test result	24
6.5.	Test graphs	25
7.	Carrier Frequency Separation	28
7.1.	Block diagram of test setup	28
7.2.	Limits.....	28
7.3.	Test procedure	28
7.4.	Test result	29
7.5.	Test graphs	30
8.	Dwell Time	31

8.1.	Block diagram of test setup	31
8.2.	Limits	31
8.3.	Test procedure	31
8.4.	Test result	32
8.5.	Test graphs	33
9.	Number of Hopping Channel	39
9.1.	Block diagram of test setup	39
9.2.	Limits	39
9.3.	Test procedure	39
9.4.	Test result	40
9.5.	Test graphs	41
10.	Band Edge Compliance (Conducted Method)	42
10.1.	Block diagram of test setup	42
10.2.	Limit	42
10.3.	Test procedure	42
10.4.	Test result	43
10.5.	Test graphs	44
11.	RF Conducted Spurious Emissions	48
11.1.	Block diagram of test setup	48
11.2.	Limits	48
11.3.	Test procedure	48
11.4.	Test result	49
11.5.	Test graphs	50
12.	Duty cycle	59
12.1.	Block diagram of test setup	59
12.2.	Limit	59
12.3.	Test procedure	59
12.4.	Test result	60
12.5.	Test graphs	61
13.	Antenna Requirements	64
13.1.	Limit	64
13.2.	Result	64
14.	Radiated Emission	65
14.1.	Test equipment	65
14.2.	Block diagram of test setup	66
14.3.	Limits	67
14.4.	Assistant equipment used for test	68
14.5.	Test procedure	68

14.6.	Test result	70
14.7.	Test data	71
15.	Band Edge Compliance.....	73
15.1.	Test equipment.....	79
15.2.	Block diagram of test setup	80
15.3.	Limits.....	80
15.4.	Assistant equipment used for test	80
15.5.	Test procedure	80
15.6.	Test result	80
15.7.	Test data	81
16.	Power Line Conducted Emissions.....	87
16.1.	Test equipment.....	87
16.2.	Block diagram of test setup	87
16.3.	Limits.....	87
16.4.	Assistant equipment used for test	87
16.5.	Test procedure	88
16.6.	Test result	88
17.	Test Setup Photograph	89
18.	Photos of the EUT	91

Test Report Declare

Applicant	:	Robert Bosch GmbH
Address of Applicant	:	Robert-Bosch-Strasse 200, Hildesheim 31139, Germany
Equipment under Test	:	Coach smartInfotainment series
Model name	:	Coach smartRadio Gen2
Part Numbers	:	7620210052
Manufacturer	:	Robert Bosch GmbH
Address of Manufacturer	:	Robert-Bosch-Strasse 200, Hildesheim 31139, Germany

Test Standard Used:

FCC Rules and Regulations Part 15 Subpart C,

RSS-247 Issue 3 August 2023,

ANSI C63.10:2020,

RSS-Gen Issue 5, Apr. 2018, Amendment 2 (February 2021)

We Declare:

The equipment described above is tested by Guangdong Dongdian Testing Service Co., Ltd. and in the configuration tested the equipment complied with the standards specified above. The test results are contained in this test report and Guangdong Dongdian Testing Service Co., Ltd. is assumed of full responsibility for the accuracy and completeness of these tests.

Report No.:	DDT-RE24110530-4E01		
Date of Receipt:	2024/12/05	Date of Test:	2024/12/06 - 2024/12/16

Prepared By:**Jacky Huang/Engineer****Approved By:****Damon Hu/EMC Manager**

Note: This report applies to above tested sample only. This report shall not be reproduced in parts without written approval of Guangdong Dongdian Testing Service Co., Ltd.

Revision History

Rev.	Revisions	Issue Date	Revised By
---	Initial issue	2025/01/11	

1. Summary of Test Results

No.	Test Parameter	Clause No.	Condition	Result
1	Maximum Peak Output Power	FCC Part 15: 15.247(b)(1), RSS-247 Issue 3 clause 5.4(b)	/	Pass
2	20 dB Bandwidth	FCC Part 15: 15.247(a)(1), RSS-247 Issue 3 clause 5.1(a)	/	Pass
3	99% Bandwidth	RSS-Gen Issue 5 clause 6.7	/	Pass
4	Carrier Frequency Separation	FCC Part 15: 15.247(a)(1), RSS-247 Issue 3 clause 5.1(b)	/	Pass
5	Number of Hopping Channel	FCC Part 15: 15.247(a)(1)(iii), RSS-247 Issue 3 clause 5.1(d)	/	Pass
6	Dwell Time	FCC Part 15: 15.247(a)(1)(iii), RSS-247 Issue 3 clause 5.1(d)	/	Pass
7	RF Conducted Spurious Emissions	FCC Part 15: 15.247(d), RSS-247 Issue 3 clause 5.5	/	Pass
8	Radiated Emission	FCC Part 15: 15.205, FCC Part 15: 15.209, FCC Part 15: 15.247(d), RSS-247 Issue 3 clause 5.5, RSS-Gen Issue 5 clause 8.9, RSS-Gen Issue 5 clause 8.10	/	Pass
9	Band Edge Compliance	FCC Part 15: 15.205, FCC Part 15: 15.209, FCC Part 15: 15.247(d), RSS-247 Issue 3 clause 5.5, RSS-Gen Issue 5 clause 8.9, RSS-Gen Issue 5 clause 8.10	/	Pass
10	Antenna Requirement	FCC Part 15: 15.203, RSS-Gen Issue 5 clause 6.8	/	Pass
11	Power Line Conducted Emissions	FCC Part 15: 15.207(a), RSS-Gen Issue 5 clause 8.8	/	N/A
Note: N/A is an abbreviation for Not Applicable, and means this item is not applicable for this device or no need to test according to standard.				

2. General Test Information

2.1. Description of EUT

Equipment under Test	: Coach smartInfotainment series
Model name	: Coach smartRadio Gen2
Part Numbers	: 7620210052
EUT Function Description	: Please reference user manual of this device
Power Supply	: DC 24V
Antenna Type	: FPC antenna
Max Antenna Gain (dBi)	: 2.04

Note: This EUT support Bluetooth BR/EDR, this report only for Bluetooth BR/EDR.

Radio Specification	: Bluetooth BR/EDR
Operation Frequency	: 2402 MHz-2480 MHz
Modulation	: GFSK, $\pi/4$ -DQPSK, 8DPSK

Channel information					
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
0	2402	27	2429	54	2456
1	2403	28	2430	55	2457
2	2404	29	2431	56	2458
3	2405	30	2432	57	2459
4	2406	31	2433	58	2460
5	2407	32	2434	59	2461
6	2408	33	2435	60	2462
7	2409	34	2436	61	2463
8	2410	35	2437	62	2464
9	2411	36	2438	63	2465
10	2412	37	2439	64	2466
11	2413	38	2440	65	2467
12	2414	39	2441	66	2468
13	2415	40	2442	67	2469
14	2416	41	2443	68	2470
15	2417	42	2444	69	2471
16	2418	43	2445	70	2472
17	2419	44	2446	71	2473
18	2420	45	2447	72	2474
19	2421	46	2448	73	2475


20	2422	47	2449	74	2476
21	2423	48	2450	75	2477
22	2424	49	2451	76	2478
23	2425	50	2452	77	2479
24	2426	51	2453	78	2480
25	2427	52	2454		
26	2428	53	2455		

Note: The above EUT information is declared by manufacturer and for more detailed features description please refer to the manufacturer's specifications or User's Manual. The above Antenna information is declared by manufacturer and for more detailed features description please refer to the manufacturer's specifications, the laboratory shall not be held responsible.

2.2. Accessories of EUT

Accessories	Manufacturer	Model number	Description
/	/	/	/

2.3. Block diagram of EUT configuration for test



2.4. Decision of final test mode

According pre-test, the worst test modes were reported as below:

Test software: BlueSuite 3.2.exe

The test software was used to control EUT work in Continuous Tx mode, and select test channel, wireless mode as below table.

The pathloss of external cable: 0.5 dB (According to the manufacturer's claims)

Tested mode, channel, information			
Mode	Setting Tx Power	Channel	Frequency (MHz)
GFSK hopping on Tx mode	2/0/0	CH0 to CH78	2402 to 2480
$\pi/4$ -DQPSK hopping on Tx mode	2/0/0	CH0 to CH78	2402 to 2480
8DPSK hopping on Tx mode	2/0/0	CH0 to CH78	2402 to 2480
GFSK hopping off Tx mode	2/0/0	CH0	2402
	2/0/0	CH39	2441
	2/0/0	CH78	2480
$\pi/4$ -DQPSK hopping off Tx mode	2/0/0	CH0	2402
	2/0/0	CH39	2441
	2/0/0	CH78	2480
8DPSK hopping off Tx mode	2/0/0	CH0	2402
	2/0/0	CH39	2441
	2/0/0	CH78	2480
Worst-case data rates were: GFSK mode: DH5, $\pi/4$ -DQPSK mode: 2DH5, 8DPSK mode: 3DH5			

2.5. Deviations of test standard

No deviation.

2.6. Test environment conditions

During the measurement the environmental conditions were within the listed ranges:

Temperature range:	+15°C to +35 °C
Humidity range:	20% to 75%
Pressure range:	86 kPa to 106 kPa

Note: The specific temperature and humidity information of each test item refers to the temperature and humidity record in the corresponding test data.

2.7. Test laboratory

Guangdong Dongdian Testing Service Co., Ltd.

Add.: Unit 2, Building 1, No. 17, Zongbu 2nd Road, Songshan Lake Park, Dongguan, Guangdong, China, 523808.

Tel.: +86-0769-38826678, <http://www.dgddt.com>, Email: ddt@dgddt.com.

CNAS Accreditation No. L6451; A2LA Accreditation Number: 3870.01

FCC Designation Number: CN1182, Test Firm Registration Number: 540522

Innovation, Science and Economic Development Canada Site Registration Number: 10288A

Conformity Assessment Body identifier: CN0048

VCCI facility registration number: C-20087, T-20088, R-20123, R-20155, G-20118

2.8. Measurement uncertainty


Test Item	Uncertainty
Bandwidth	1.1%
Peak Output Power (Conducted) (Spectrum analyzer)	0.86 dB ($10 \text{ MHz} \leq f < 3.6 \text{ GHz}$);
	1.38 dB ($3.6 \text{ GHz} \leq f < 8 \text{ GHz}$)
Peak Output Power (Conducted) (Power Sensor)	0.74 dB
Power Spectral Density	0.74 dB ($10 \text{ MHz} \leq f < 3.6 \text{ GHz}$);
	1.38 dB ($3.6 \text{ GHz} \leq f < 8 \text{ GHz}$)
Frequencies Stability	6.7×10^{-8} (Antenna couple method)
	5.5×10^{-8} (Conducted method)
Conducted spurious emissions	0.86 dB ($10 \text{ MHz} \leq f < 3.6 \text{ GHz}$);
	1.40 dB ($3.6 \text{ GHz} \leq f < 8 \text{ GHz}$)
	1.66 dB ($8 \text{ GHz} \leq f < 26.5 \text{ GHz}$)
Uncertainty for radio frequency (RBW < 20 kHz)	3×10^{-8}
Temperature	0.4 °C
Humidity	2 %
Uncertainty for Radiation Emission test (9 kHz – 30 MHz)	3.44 dB
Uncertainty for Radiation Emission test (30 MHz - 1 GHz)	4.70 dB (Antenna Polarize: V)
	4.84 dB (Antenna Polarize: H)
Uncertainty for Radiation Emission test (1 GHz - 40 GHz)	4.10 dB (1 - 6 GHz)
	4.40 dB (6 GHz - 18 GHz)
	3.54 dB (18 GHz - 26 GHz)
	4.30 dB (26 GHz - 40 GHz)
Uncertainty for Power line conduction emission test	3.34dB (150KHz-30MHz)
	3.72dB (9KHz-150KHz)
Note: This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.	

3. Equipment Used During Conductive Test

Equipment	Manufacturer	Model No.	Serial Number	Due Date	Cal. Interval
☑ RF Connected Test (RF Measurement System 1#)					
SIGNAL ANALYZER	R&S	FSQ26	101272	2025/03/31	1 Year
Wideband Radio Communication Tester	R&S	CMW500	120259	2025/07/08	1 Year
MXG Vector Signal Generator	KEYSIGHT	N5182B	MY59100192	2025/03/31	1 Year
MXG Vector Signal Generator	Agilent	N5182A	MY19060405	2025/03/31	1 Year
RF Control Unit	Tonsend	JS0806-2	158060010	2025/03/31	1 Year
TEMP&HUMI Programmable Chamber	ZHIXIANG	ZXGDJS-150L	ZX170110-A	2025/04/22	1 Year
Test Software	Tonscend	JS1120-3	Ver.3.2.22	N/A	N/A

4. 20 dB Bandwidth

4.1. Block diagram of test setup



4.2. Limits

Intentional radiators operating under the alternative provisions to the general emission limits, as contained in § 15.217 through 15.257 and in Subpart E of this part, must be designed to ensure that the 20 dB bandwidth of the emission, or whatever bandwidth may otherwise be specified in the specific rule section under which the equipment operates, is contained within the frequency band designated in the rule section under which the equipment is operated.

4.3. Test procedure

- (1) The test according to ANSI C63.10-2020 clause 6.9.2.
- (2) Connect EUT's antenna output to spectrum analyzer by RF cable, the path loss was compensated to the results
- (3) Set the EUT as maximum power setting and enable the EUT transmit continuously
- (4) Use the following spectrum analyzer settings for the 20 dB bandwidth measurement:

RBW:	1% to 5% of the OBW
VBW:	approximately three times RBW
Span:	between 2 times and 5 times the OBW
Detector Mode:	Peak
Sweep time:	Auto
Trace mode:	Max hold


- (5) Measure and record the results in the report.


4.4. Test result


Test Engineer:	Zora Zhang	Test Site:	RF Measurement System 4#
Ambient Condition:	23.6℃, 48.3%RH	Test Date:	2024.12.16
Test Power Supply:	DC 24V	Sample Number:	S24111103-001

Test Mode	Antenna	Frequency [MHz]	20dB EBW [MHz]
DH5	Ant1	2402	0.96
		2441	0.96
		2480	0.96
2DH5	Ant1	2402	1.34
		2441	1.36
		2480	1.35
3DH5	Ant1	2402	1.30
		2441	1.30
		2480	1.31

4.5. Test graphs








5. 99% Bandwidth

5.1. Block diagram of test setup



5.2. Limits

Just for Report.

5.3. Test procedure

- (1) The test according to ANSI C63.10-2020 clause 6.9.3.
- (2) Connect EUT's antenna output to spectrum analyzer by RF cable, the path loss was compensated to the results
- (3) Set the EUT as maximum power setting and enable the EUT transmit continuously
- (4) Use the following spectrum analyzer settings for the 99% bandwidth measurement:


RBW:	1% to 5% of the OBW
VBW:	approximately three times RBW
Span:	between 1.5 times and 5.0 times the OBW
Detector Mode:	Peak
Sweep time:	Auto
Trace mode:	Max hold
- (5) Measure and record the results in the report.


5.4. Test result


Test Engineer:	Zora Zhang	Test Site:	RF Measurement System 4#
Ambient Condition:	23.6℃, 48.3%RH	Test Date:	2024.12.16
Test Power Supply:	DC 24V	Sample Number:	S24111103-001

Test Mode	Antenna	Frequency [MHz]	OCB [MHz]	FL [MHz]	FH [MHz]
DH5	Ant1	2402	0.882	2401.5530	2402.4350
		2441	0.882	2440.5500	2441.4320
		2480	0.873	2479.5530	2480.4260
2DH5	Ant1	2402	1.200	2401.3910	2402.5910
		2441	1.203	2440.3910	2441.5940
		2480	1.203	2479.3910	2480.5940
3DH5	Ant1	2402	1.194	2401.3940	2402.5880
		2441	1.197	2440.3880	2441.5850
		2480	1.191	2479.3940	2480.5850

5.5. Test graphs








6. Maximum Peak Output Power

6.1. Block diagram of test setup



6.2. Limits

For frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725-5850 MHz band: 1 watt. For all other frequency hopping systems in the 2400-2483.5 MHz band: 0.125 watts, the e.i.r.p shall not exceed 4W.

6.3. Test procedure

- (1) The test according to ANSI C63.10-2020 clause 7.8.5.
- (2) Connect EUT's antenna output to spectrum analyzer by RF cable, the path loss was compensated to the results.
- (3) Set the EUT as maximum power setting and enable the EUT transmit continuously.
- (4) Use the following spectrum analyzer settings for the maximum peak output power measurement:


RBW:	> 20 dB bandwidth of the emission being measured.
VBW:	VBW ≥ RBW.
Span:	Approximately five times the 20 dB bandwidth, centered on a hopping channel.
Detector Mode:	Peak
Sweep time:	Auto
Trace mode:	Max hold
- (5) Use the marker-to-peak function to set the marker to the peak of the emission and record the results in the report.


6.4. Test result




Test Engineer:	Zora Zhang	Test Site:	RF Measurement System 4#
Ambient Condition:	23.6℃, 48.3%RH	Test Date:	2024.12.16
Test Power Supply:	DC 24V	Sample Number:	S24111103-001

Test Mode	Antenna	Frequency [MHz]	Conducted Peak Power [dBm]	Conducted Limit [dBm]	EIRP [dBm]	EIRP Limit [dBm]	Verdict
DH5	Ant1	2402	6.84	≤30	8.88	≤36	PASS
		2441	6.87	≤30	8.91	≤36	PASS
		2480	6.54	≤30	8.58	≤36	PASS
2DH5	Ant1	2402	8.94	≤30	10.98	≤36	PASS
		2441	9.09	≤30	11.13	≤36	PASS
		2480	8.86	≤30	10.90	≤36	PASS
3DH5	Ant1	2402	9.78	≤30	11.82	≤36	PASS
		2441	9.79	≤30	11.83	≤36	PASS
		2480	9.62	≤30	11.66	≤36	PASS

6.5. Test graphs








7. Carrier Frequency Separation

7.1. Block diagram of test setup



7.2. Limits

Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW.

7.3. Test procedure

- (1) The test according to ANSI C63.10-2020 clause 7.8.2.
- (2) Connect EUT's antenna output to spectrum analyzer by RF cable, the path loss was compensated to the results.
- (3) Set the EUT as maximum power setting and enable the EUT transmit continuously.
- (4) Use the following spectrum analyzer settings for the maximum peak output power measurement:


RBW:	approximately 30% of the channel spacing
VBW:	$VBW \geq RBW$.
Span:	Wide enough to capture the peaks of two adjacent channels.
Detector Mode:	Peak
Sweep time:	Auto
Trace mode:	Max hold
- (5) Use the marker-delta function to determine the separation between the peaks of the adjacent channels and record the results in the report.

7.4. Test result

Test Engineer:	Zora Zhang	Test Site:	RF Measurement System 4#		
Ambient Condition:	24℃, 45%RH	Test Date:	2024.12.09		
Test Power Supply:	DC 24V	Sample Number:	S24111103-001		


Test Mode	Antenna	Frequency [MHz]	Result [MHz]	Limit [MHz]	Verdict
DH5	Ant1	Hop	0.994	≥0.640	PASS
2DH5	Ant1	Hop	1.006	≥0.907	PASS
3DH5	Ant1	Hop	1.003	≥0.893	PASS

7.5. Test graphs



8. Dwell Time

8.1. Block diagram of test setup



8.2. Limits

The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed.

8.3. Test procedure

- (1) The test according to ANSI C63.10-2020 clause 7.8.4.
- (2) Connect EUT's antenna output to spectrum analyzer by RF cable, the path loss was compensated to the results.
- (3) Set the EUT as maximum power setting and enable the EUT transmit continuously.
- (4) Use the following spectrum analyzer settings for the maximum peak output power measurement:


RBW:	$\leq$ channel spacing and where possible RBW should be set $\gg 1 / T$
VBW:	$VBW \geq RBW$.
Span:	Zero span, centered on a hopping channel.
Detector Mode:	Peak
Sweep time:	Auto
Trace mode:	Clear Write.
- (5) The test period: $T = 0.4 \text{ Second/Channel} \times 79 \text{ Channel} = 31.6 \text{ s}$
- (6) Measure the hopping number and on time of each pulse with spectrum analyzer in zero span set, and calculate dwell time with formula Dwell time = total hops * pulse's on time.
- (7) Measure and record the results in the report.


8.4. Test result


Test Engineer:	Zora Zhang	Test Site:	RF Measurement System 4#
Ambient Condition:	24℃, 45%RH	Test Date:	2024.12.09
Test Power Supply:	DC 24V	Sample Number:	S24111103-001




Test Mode	Antenna	Frequency [MHz]	Burst Width [ms]	Total Hops [Num]	Result [s]	Limit [s]	Verdict
DH1	Ant1	Hop	0.370	319	0.118	≤0.4	PASS
DH3	Ant1	Hop	1.620	158	0.256	≤0.4	PASS
DH5	Ant1	Hop	2.880	105	0.302	≤0.4	PASS
2DH1	Ant1	Hop	0.380	320	0.122	≤0.4	PASS
2DH3	Ant1	Hop	1.640	152	0.249	≤0.4	PASS
2DH5	Ant1	Hop	2.880	106	0.305	≤0.4	PASS
3DH1	Ant1	Hop	0.380	320	0.122	≤0.4	PASS
3DH3	Ant1	Hop	1.640	160	0.262	≤0.4	PASS
3DH5	Ant1	Hop	2.890	106	0.306	≤0.4	PASS


8.5. Test graphs

















3DH5_Ant1_Hop



9. Number of Hopping Channel

9.1. Block diagram of test setup



9.2. Limits

Frequency hopping systems in the 2400-2483.5 MHz band shall use at least 15 channels.

9.3. Test procedure

- (1) The test according to ANSI C63.10-2020 clause 7.8.3.
- (2) Connect EUT's antenna output to spectrum analyzer by RF cable, the path loss was compensated to the results.
- (3) Set the EUT as maximum power setting and enable the EUT transmit continuously.
- (4) Use the following spectrum analyzer settings for the maximum peak output power measurement:

RBW:	RBW to less than 30% of the channel spacing or the 20 dB bandwidth, whichever is smaller.
VBW:	$VBW \geq RBW$.
Span:	The frequency band of operation
Detector Mode:	Peak
Sweep time:	Auto
Trace mode:	Max hold

- (5) Measure the hopping number and record the results in the report.
- (6) Measure and record the results in the report.

9.4. Test result

Test Engineer:	Zora Zhang	Test Site:	RF Measurement System 4#		
Ambient Condition:	24℃, 45%RH	Test Date:	2024.12.09		
Test Power Supply:	DC 24V	Sample Number:	S24111103-001		

Test Mode	Antenna	Frequency [MHz]	Result [Num]	Limit [Num]	Verdict
DH5	Ant1	Hop	79	≥15	PASS
2DH5	Ant1	Hop	79	≥15	PASS
3DH5	Ant1	Hop	79	≥15	PASS

DH5 Ant1 Hop

Ref 30 dBm Att 40 dB RBW 300 kHz VBW 300 kHz SWF 2.5 ms

30 Offset 8.2 dB

1.5W View

Start 2.4 GHz 8.35 MHz/ Stop 2.4835 GHz

Date: 9.DEC.2024 10:01:28

2DH5 Ant1 Hop

Ref 30 dBm Att 40 dB RBW 300 kHz VBW 300 kHz SWF 2.5 ms

30 Offset 8.2 dB

1.5W View

Start 2.4 GHz 8.35 MHz/ Stop 2.4835 GHz

Date: 9.DEC.2024 10:04:35

3DH5 Ant1 Hop

Ref 30 dBm Att 40 dB RBW 300 kHz VBW 300 kHz SWF 2.5 ms

30 Offset 8.2 dB


1.5W View

Start 2.4 GHz 8.35 MHz/ Stop 2.4835 GHz

Date: 9.DEC.2024 10:08:09

10. Band Edge Compliance (Conducted Method)

10.1. Block diagram of test setup



10.2. Limit

All restriction band should comply with 15.209, other emission should be at least 20dB below the fundamental.

10.3. Test procedure

- (1) Connect EUT's antenna output to spectrum analyzer by RF cable.
- (2) Establish a reference level by using the following procedure:


RBW:	100 kHz
VBW:	300 kHz
Span	Encompass frequency range to be measured
Detector Mode:	Peak
Sweep time:	Auto
Trace mode	Max hold
- (3) Allow the trace to stabilize, use the peak marker function to determine the maximum peak power level to establish the reference level.
- (4) Then mark the maximum amplitude of all unwanted emissions outside of the authorized frequency band.


10.4. Test result




Test Engineer:	Zora Zhang	Test Site:	RF Measurement System 4#
Ambient Condition:	24℃, 45%RH	Test Date:	2024.12.09-2424.12.16
Test Power Supply:	DC 24V	Sample Number:	S24111103-001




Mode	Freq. (MHz)	Verdict
DH5	Hopping off 2402	Pass
	Hopping off 2480	Pass
	Hopping on	Pass
2DH5	Hopping off 2402	Pass
	Hopping off 2480	Pass
	Hopping on	Pass
3DH5	Hopping off 2402	Pass
	Hopping off 2480	Pass
	Hopping on	Pass

10.5. Test graphs









11. RF Conducted Spurious Emissions

11.1. Block diagram of test setup

Same as 10.1

11.2. Limits

In any 100 kHz bandwidth outside the frequency bands in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power.

11.3. Test procedure

(1) Connect EUT's antenna output to spectrum analyzer by RF cable.

(2) Establish a reference level by using the following procedure:

Center frequency	Test frequency
RBW:	100 kHz
VBW:	300 kHz
Span	Wide enough to capture the peak level of the in-band emission
Detector Mode:	Peak
Sweep time:	Auto
Trace mode	Max hold

(3) Allow the trace to stabilize, use the peak marker function to determine the maximum peak power level to establish the reference level.

(4) Set the spectrum analyzer as follows:

RBW:	100 kHz
VBW:	300 kHz
Span	Encompass frequency range to be measured
Number of measurement points	$\geq \text{Span/RBW}$
Detector Mode:	Peak
Sweep time:	Auto
Trace mode	Max hold

(5) Allow the trace to stabilize, use the peak marker function to determine the maximum amplitude of all unwanted emissions outside of the authorized frequency band


11.4. Test result

Test Engineer:	Zora Zhang	Test Site:	RF Measurement System 4#
Ambient Condition:	23.6℃, 48.3%RH	Test Date:	2024.12.16
Test Power Supply:	DC 24V	Sample Number:	S24111103-001


Mode	Freq. (MHz)	Verdict
DH5	Hopping off 2402	Pass
	Hopping off 2441	Pass
	Hopping off 2480	Pass
2DH5	Hopping off 2402	Pass
	Hopping off 2441	Pass
	Hopping off 2480	Pass
8DPSK	Hopping off 2402	Pass
	Hopping off 2441	Pass
	Hopping off 2480	Pass


11.5. Test graphs














2DH5_Ant1_2480_1000~26500

Ref 20 dBm

Att 20 dB

RBW 100 kHz

VBW 300 kHz

SWT 2.6 s

Marker 2 [T1]

-50.18 dBm

4.959300000 GHz

Marker 1 [T1]

-5.59 dBm

2.479850000 GHz




Start 1 GHz


2.55 GHz/

Stop 26.5 GHz

Date: 16.DEC.2024 21:45:44








12. Duty cycle

12.1. Block diagram of test setup



12.2. Limit

Just for Report.

12.3. Test procedure

- (1) Connected the EUT's antenna port to the Spectrum Analyzer by suitable attenuator, The cable loss and attenuator loss have been put into spectrum analyzer as amplitude offset.

set the Spectrum Analyzer as below:

Centre Frequency: The centre frequency of the middle hopping channel.

Resolution BW: 10 MHz.

Video BW: 10 MHz.

Span: Zero span.

Detector: Peak.

Trace Mode: Clear Write.

Sweep: Video Trigger

- (2) When the trace is complete, measure the sending time of 1 burst and the duty cycle of 1 burst cycle.

- (3) Calculate dwell time follow below formula:

Duty cycle= Pulse's on time / Burst cycle

12.4. Test result

Test Engineer:	Zora Zhang	Test Site:	RF Measurement System 4#
Ambient Condition:	23.6℃, 48.3%RH	Test Date:	2024.12.16
Test Power Supply:	DC 24V	Sample Number:	S24111103-001

Test Mode	Antenna	Frequency [MHz]	ON Time [ms]	Period [ms]	Duty Cycle [%]	Duty Cycle Factor [dB]
DH5	Ant1	2402	2.90	3.76	77.13	1.13
		2441	2.90	3.77	76.92	1.12
		2480	2.90	3.76	77.13	1.13
2DH5	Ant1	2402	2.91	3.76	77.39	1.13
		2441	2.91	3.77	77.19	1.14
		2480	2.90	3.77	76.92	1.14
3DH5	Ant1	2402	2.91	3.77	77.19	1.13
		2441	2.91	3.76	77.39	1.14
		2480	2.92	3.77	77.45	1.13

Figure 10 displays three plots showing the results of the 100% duty cycle test for the DH5 Ant1 antenna at 2402 MHz, 2441 MHz, and 2480 MHz. Each plot shows the power spectrum (dBm) versus frequency (MHz) for a 100% duty cycle signal. The plots are labeled "DH5 Ant1 2402", "DH5 Ant1 2441", and "DH5 Ant1 2480".

The plots show the power spectrum (dBm) versus frequency (MHz) for a 100% duty cycle signal. The plots are labeled "DH5 Ant1 2402", "DH5 Ant1 2441", and "DH5 Ant1 2480".

Each plot includes the following parameters:

- Ref: 15 dBm
- Offset: 9.1 dB (for 2402 MHz) or 10 dB (for 2441 MHz and 2480 MHz)
- Att: 20 dB
- RBW: 10 MHz
- VBW: 10 MHz
- SWT: 7 ms
- Delta 2 (T1): -15.89 dB (for 2402 MHz) or -0.94 dB (for 2441 MHz and 2480 MHz)
- Delta 2 (T1): 2.900000 ms
- Marker 1 (T1): 0.000000 s
- Delta 2 (T1): 2.900000 ms
- Center: 2.402 GHz (for 2402 MHz) or 2.441 GHz (for 2441 MHz and 2480 MHz)
- 700 μ s/

The plots show the power spectrum (dBm) versus frequency (MHz) for a 100% duty cycle signal. The plots are labeled "DH5 Ant1 2402", "DH5 Ant1 2441", and "DH5 Ant1 2480".




Each plot includes the following parameters:

- Ref: 15 dBm
- Offset: 9.1 dB (for 2402 MHz) or 10 dB (for 2441 MHz and 2480 MHz)
- Att: 20 dB
- RBW: 10 MHz
- VBW: 10 MHz
- SWT: 7 ms
- Delta 2 (T1): -15.89 dB (for 2402 MHz) or -0.94 dB (for 2441 MHz and 2480 MHz)
- Delta 2 (T1): 2.900000 ms
- Marker 1 (T1): 0.000000 s
- Delta 2 (T1): 2.900000 ms
- Center: 2.402 GHz (for 2402 MHz) or 2.441 GHz (for 2441 MHz and 2480 MHz)
- 700 μ s/

The plots show the power spectrum (dBm) versus frequency (MHz) for a 100% duty cycle signal. The plots are labeled "DH5 Ant1 2402", "DH5 Ant1 2441", and "DH5 Ant1 2480".

Each plot includes the following parameters:

- Ref: 15 dBm
- Offset: 9.1 dB (for 2402 MHz) or 10 dB (for 2441 MHz and 2480 MHz)
- Att: 20 dB
- RBW: 10 MHz
- VBW: 10 MHz
- SWT: 7 ms
- Delta 2 (T1): -15.89 dB (for 2402 MHz) or -0.94 dB (for 2441 MHz and 2480 MHz)
- Delta 2 (T1): 2.900000 ms
- Marker 1 (T1): 0.000000 s
- Delta 2 (T1): 2.900000 ms
- Center: 2.402 GHz (for 2402 MHz) or 2.441 GHz (for 2441 MHz and 2480 MHz)
- 700 μ s/





13. Antenna Requirements

13.1. Limit

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. And according to FCC 47 CFR Section 15.247 (b), if transmitting antennas of directional gain greater than 6 dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

For intentional device, according to RSS-Gen issue 5 section 6.8.

The applicant for equipment certification shall provide a list of all antenna types that may be used with the transmitter, where applicable (i.e. for transmitters with detachable antenna), indicating the maximum permissible antenna gain (in dBi) and the required impedance for each antenna. The test report shall demonstrate the compliance of the transmitter with the limit for maximum equivalent isotropically radiated power (e.i.r.p.) specified in the applicable RSS, when the transmitter is equipped with any antenna type, selected from this list.

13.2. Result



The antenna used for this product as Antenna information described in section 2.1 of the report, and there is no other antenna than that furnished by the responsible party shall be used with the device.


14. Radiated Emission

14.1. Test equipment

Equipment	Manufacturer	Model No.	Serial No.	Cal Due To	Cal. Interval
RF Cable	N/A	W13.02 AP1-X2	DDT-ZC04023	2025/03/31	1 Year
High Pass filter	Xi'an Xingbo	XBLBQ-GTA67	DDT-ZC02179	2025/04/22	1 Year
EMI TEST RECEIVER	R&S	ESU26	DDT-ZC01909	2025/03/31	1 Year
RF cable	Yuhu Technology	JCTB810-NJ-NJ-9M	DDT-ZC02538	2025/03/31	1 Year
Active Loop Antenna	Schwarzbeck	FMZB1519	DDT-ZC00524	2025/09/11	2 Year
High pass filter	Micro-Tronics	HPM50102	DDT-ZC00561	2025/04/22	1 Year
PSA Series Spectrum Analyzer	Agilent	E4447A	DDT-ZC00517	2025/03/31	1 Year
Trilog Broadband Antenna	Schwarzbeck	VULB 9163	DDT-ZC02050	2025/07/11	2 Year
Micro-Tronics filters	REBES	BRM50702	DDT-ZC03242	/	/
High pass filter	Micro-Tronics	HPM50108	DDT-ZC00560	2025/04/22	1 Year
Hochgewinn-Hornantenne	SCHWARZBECK	BBHA 9120 D	DDT-ZC02129	2025/09/18	2 Year
RF cable	Zhongke Junchuang	JCT26S-NJ-NJ-1.5M	DDT-ZC02762	2025/03/31	1 Year
Micro-Tronics filters	REBES	BRM50716	DDT-ZC03240	/	1 Year
RF Cable	N/A	W24.02 HL-562	DDT-ZC04022	2025/03/31	1 Year
Pre-amplifier	COM-POWER	PAM-840A	DDT-ZC01693	2025/03/31	1 Year
Broad-Band Horn Antenna	Schwarzbeck	BBHA 9170	DDT-ZC00506	2025/04/26	1 Year
RF cable	Yuhu Technology	ZT26S-SMAJ-SMAJ-1M	DDT-ZC02037	2025/03/31	1 Year

14.2. Block diagram of test setup





14.3. Limits

(1) FCC 15.205 Restricted frequency band

MHz	MHz	MHz	GHz
0.090-0.110	16.42-16.423	399.9-410	4.5-5.15
¹ 0.495-0.505	16.69475-16.69525	608-614	5.35-5.46
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.1772&4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.2072&4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	108-121.94	1718.8-1722.2	13.25-13.4
6.31175-6.31225	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3600-4400	(²)
13.36-13.41			

¹Until February 1, 1999, this restricted band shall be 0.490-0.510 MHz

²Above 38.6

(2) FCC 15.209 Limit

FREQUENCY MHz	DISTANCE Meters	FIELD STRENGTHS LIMIT	
		mV/m	dB(mV)/m
0.009 ~ 0.490	300	2400/F(kHz)	67.6-20log(F)
0.490 ~ 1.705	30	24000/F(kHz)	87.6-20log(F)
1.705 ~ 30.0	30	30	29.54
30~88	3	100	40.0
88~216	3	150	43.5
216~960	3	200	46.0
960~1000	3	500	54.0
Above 1000	3	74.0 dB(mV)/m (Peak) 54.0 dB(mV)/m (Average)	

Note:

(1) The emission limits shown in the above table are based on measurements employing a CISPR QP detector except for the frequency bands 9 - 90 kHz, 110 - 490 kHz and above 1000 MHz, radiated emissions limits in these three bands are based on measurements employing an average detector.

(2) At frequencies below 30 MHz, measurement may be performed at a distance closer than that specified, and the limit at closer measurement distance can be extrapolated by below formula:

$$\text{Limit}_{3\text{m}}(\text{dBuV/m}) = \text{Limit}_{30\text{m}}(\text{dBuV/m}) + 40\text{Log}(30\text{m}/3\text{m})$$

(3) Limit for this EUT

The emissions appearing within 15.205 restricted frequency bands shall not exceed the limits shown in 15.209, all the other emissions shall be at least 20 dB below the fundamental emissions or comply with 15.209 limits

14.4. Assistant equipment used for test

Assistant equipment	Manufacturer	Model number	Description	other
/	/	/	/	/

14.5. Test procedure

(1) EUT was placed on a non-metallic table, 80 cm above the ground plane inside a semi-anechoic chamber for below 1G and 150 cm above the ground plane inside a fully-anechoic chamber for above 1G.

(2) Test antenna was located 3 m from the EUT on an adjustable mast, and the antenna used as below table.

Test frequency range	Test antenna used	Test antenna distance
9 kHz - 30 MHz	Active Loop antenna	3 m
30 MHz - 1 GHz	Trilog Broadband Antenna	3 m
1 GHz - 18 GHz	Double Ridged Horn Antenna (1 GHz-18 GHz)	3 m
18 GHz - 40 GHz	Horn Antenna (18 GHz-40 GHz)	1 m

According ANSI C63.10:2020 clause 6.4.6 and 6.5.3, for measurements below 30 MHz, Antenna was located 3 m from EUT, the loop antenna was positioned in three antenna orientations (parallel, perpendicular, and round-parallel), for each measurement antenna alignment, the EUT shall be rotated through 0° to 360° on a turntable, and the lowest height of the magnetic antenna shall be 1 m above the ground. For measurement above 30MHz, the trilog Broadband Antenna or Horn Antenna was located 3m from EUT, Measurements were made with the antenna positioned in both the horizontal and vertical planes of Polarization, and the measurement antenna was varied from 1 m to 4 m. in height above the reference ground plane to obtain the maximum signal strength.

(3) Below pre-scan procedure was first performed in order to find prominent frequency spectrum radiated emissions from 9 kHz to 25 GHz:

(a) Scanning the peak frequency spectrum with the antenna specified in step (3), and the EUT was rotated 360 degree, the antenna height was varied from 1 m to 4 m (Except loop antenna, it's fixed 1 m above ground.)

(b) Change work frequency or channel of device if practicable.

(c) Change modulation type of device if practicable.

(d) Change power supply range from 85% to 115% of the rated supply voltage

(e) Rotated EUT though three orthogonal axes to determine the attitude of EUT arrangement produces highest emissions.

Spectrum frequency from 9 kHz to 25 GHz (tenth harmonic of fundamental frequency) was investigated, and no any obvious emission were detected from 18 GHz to 25 GHz, so below final test was performed with frequency range from 9 kHz to 18 GHz.

(4) For final emissions measurements at each frequency of interest, the EUT was rotated and the antenna height was varied between 1 m and 4 m in order to maximize the emission. Measurements in both horizontal and vertical polarities were made and the data was recorded. In order to find the maximum emission, the relative positions of equipment and all of the interface cables were changed according to ANSI C63.10:2020 on Radiated Emission test.

(5) The emissions from 9 kHz to 1 GHz were measured based on CISPR QP detector except for the frequency bands 9 - 90 kHz, 110 - 490 kHz, for emissions from 9 kHz - 90 kHz, 110 kHz - 490 kHz and above 1 GHz were measured based on average detector, for emissions above 1 GHz, peak emissions also be measured and need comply with Peak limit.

(6) The emissions from 9 kHz to 1 GHz, QP or average values were measured with EMI receiver with below RBW.

Frequency band	RBW
9 kHz - 150 kHz	200 Hz
150 kHz - 30 MHz	9 kHz
30 MHz - 1 GHz	120 kHz

(7) For emissions above 1GHz, both Peak and Average level were measured with Spectrum Analyzer, and the RBW is set at 1 MHz, VBW is set at 3 MHz for Peak measure; According ANSI C63.10:2020 clause 4.1.4.2.2 procedure for average measure.

(8) According exploratory test, the emission levels are 20 dB below the limit detected from 9 kHz to 30 MHz and 18 GHz to 25 GHz, so the final test was performed with frequency range from 30 MHz to 18 GHz and recorded in below.

(9) For 30 MHz ~ 25 GHz: (Scan with all mode, the worst case is reported)

(10) For emissions below 1 GHz, according exploratory explorer test, when change Tx mode and channel, have no distinct influence on emissions level, so for emissions below 1 GHz, the final test was only performed with EUT working in worst mode.

(11) For 30 MHz ~ 25 GHz: (Scan with GFSK, $\pi/4$ -DQPSK and 8DPSK, the worst case is record and reported)

14.6. Test result

PASS. (See below detailed test result)

14.7. Test data

TR-4-E-009 Radiated Emission Test Result

Test Date:

2024-12-05

Tested By:

Gen Liu

EUT:

Coach smartInfotainment series

Model Number:

Coach smartRadio Gen2

Test Mode:

TX DH5

Power Supply:

DC 24V

Condition:

Temp:21.5°C;Humi:48.4%

Test Site:


DDT 3# Chamber

File Path:

d:\ts\2024 report data\Q24110530-4E\FCC BELOW 1G\20241205-230937_H

Memo:

Sample Numbel:S24110530-001



Data List									
NO.	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable Loss [dB]	Result [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	30.000	41.03	10.30	3.76	23.99	40.00	16.01	QP	Horizontal
2	53.125	34.98	13.44	3.91	21.23	40.00	18.77	QP	Horizontal
3	69.394	32.9	10.22	4.02	16.04	40.00	23.96	QP	Horizontal
4	109.153	24.42	12.10	4.27	9.68	43.50	33.82	QP	Horizontal
5	186.112	27.53	9.89	4.69	10.92	43.50	32.58	QP	Horizontal
6	439.960	24.52	16.10	5.77	14.92	46.00	31.08	QP	Horizontal

Note:

1. Result Level = Reading + Cable loss + Antenna Factor + AMP

2. If Peak Result complies with QP limit, QP Result is deemed to comply with QP limit.

3. Test setup: RBW: 120 kHz, VBW: 300 kHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2024-12-05

Tested By:

Gen Liu

EUT:

Coach smartInfotainment series

Model Number:

Coach smartRadio Gen2

Test Mode:

TX DH5

Power Supply:

DC 24V

Condition:

Temp:21.5°C;Humi:48.4%

Test Site:


DDT 3# Chamber

File Path:

d:\ts\2024 report data\Q24110530-4E\FCC BELOW 1G\20241205-231117_V

Memo:

Sample Numbel:S24110530-001



Data List									
NO.	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable Loss [dB]	Result [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	37.917	45.56	11.43	3.81	29.70	40.00	10.30	QP	Vertical
2	49.737	43.81	12.92	3.88	29.51	40.00	10.49	QP	Vertical
3	59.683	44.52	12.64	3.96	30.02	40.00	9.98	QP	Vertical
4	76.766	39.4	7.92	4.07	20.29	40.00	19.71	QP	Vertical
5	109.614	35.42	12.10	4.27	20.68	43.50	22.82	QP	Vertical
6	302.766	24.1	13.70	5.23	11.63	46.00	34.37	QP	Vertical

Note:

1. Result Level = Reading + Cable loss + Antenna Factor + AMP

2. If Peak Result complies with QP limit, QP Result is deemed to comply with QP limit.

3. Test setup: RBW: 120 kHz, VBW: 300 kHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2024-12-05

Tested By:

Gen Liu

EUT:

Coach smartInfotainment series

Model Number:

Coach smartRadio Gen2

Test Mode:

TX DH5 2402MHz

Power Supply:

DC 24V

Condition:

Temp:21.5°C;Humi:48.4%

Test Site:

DDT 3# Chamber


File Path:

d:\ts\2024 report data\Q24110530-4E\FCC ABOVE 1G\5

Memo:

Sample Numbler:S24110530-001

Test Graph



Data List										
NO.	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	3602.700	50.46	30.01	5.12	-39.58	46.01	74.00	27.99	PK	Vertical
2	4804.600	56.19	32.62	5.53	-39.62	54.72	74.00	19.28	PK	Vertical
3	7426.000	43.93	36.65	6.67	-40.62	46.63	74.00	27.37	PK	Vertical
4	9083.500	42.35	38.47	7.33	-38.87	49.28	74.00	24.72	PK	Vertical
5	11730.400	42.66	38.97	8.59	-39.73	50.49	74.00	23.51	PK	Vertical
6	12327.100	42.72	39.30	8.93	-39.93	51.02	74.00	22.98	PK	Vertical

Data List									
NO.	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	4804.035	51.56	32.62	5.53	50.09	54.00	3.91	AV	Vertical

- Note:
1. Level = Reading + Cable loss + Antenna Factor + AMP

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2024-12-05

Tested By:

Gen Liu

EUT:

Coach smartInfotainment series

Model Number:

Coach smartRadio Gen2

Test Mode:

TX DH5 2402MHz

Power Supply:

DC 24V

Condition:

Temp:21.5°C;Humi:48.4%

Test Site:

DDT 3# Chamber


File Path:

d:\ts\2024 report data\Q24110530-4E\FCC ABOVE 1G\6

Memo:

Sample Numbler:S24110530-001

Test Graph



Data List										
NO.	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	3602.700	49.12	30.01	5.12	-39.58	44.67	74.00	29.33	PK	Horizontal
2	4804.600	52.39	32.62	5.53	-39.62	50.92	74.00	23.08	PK	Horizontal
3	7427.700	43.33	36.64	6.67	-40.62	46.02	74.00	27.98	PK	Horizontal
4	9098.800	42.33	38.50	7.33	-38.88	49.28	74.00	24.72	PK	Horizontal
5	11546.800	42.16	39.11	8.47	-39.55	50.19	74.00	23.81	PK	Horizontal
6	15825.700	40.66	38.25	10.03	-39.40	49.54	74.00	24.46	PK	Horizontal

Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2024-12-05

Tested By:

Gen Liu

EUT:

Coach smartInfotainment series

Model Number:

Coach smartRadio Gen2

Test Mode:

TX DH5 2441MHz

Power Supply:

DC 24V

Condition:

Temp:21.5°C;Humi:48.4%

Test Site:

DDT 3# Chamber


File Path:

d:\ts\2024 report data\Q24110530-4E\FCC ABOVE 1G\7

Memo:

Sample Numbler:S24110530-001

Test Graph



Data List										
NO.	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	3662.200	47.31	30.25	5.11	-39.60	43.07	74.00	30.93	PK	Horizontal
2	4785.900	46.12	32.44	5.52	-39.62	44.46	74.00	29.54	PK	Horizontal
3	7414.100	43.20	36.67	6.66	-40.63	45.90	74.00	28.10	PK	Horizontal
4	11490.700	42.36	39.21	8.44	-39.49	50.52	74.00	23.48	PK	Horizontal
5	12111.200	41.74	39.30	8.82	-39.98	49.88	74.00	24.12	PK	Horizontal
6	15943.000	40.12	38.06	10.11	-39.40	48.89	74.00	25.11	PK	Horizontal

Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2024-12-05

Tested By:

Gen Liu

EUT:

Coach smartInfotainment series

Model Number:

Coach smartRadio Gen2

Test Mode:

TX DH5 2441MHz

Power Supply:

DC 24V

Condition:

Temp:21.5°C;Humi:48.4%

Test Site:

DDT 3# Chamber


File Path:

d:\ts\2024 report data\Q24110530-4E\FCC ABOVE 1G\8

Memo:

Sample Numbler:S24110530-001

Test Graph



Data List										
NO.	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	3662.200	51.01	30.25	5.11	-39.60	46.77	74.00	27.23	PK	Vertical
2	4850.500	44.69	33.79	5.56	-39.61	44.43	74.00	29.57	PK	Vertical
3	7422.600	43.41	36.65	6.66	-40.62	46.10	74.00	27.90	PK	Vertical
4	9455.800	41.93	38.70	7.45	-39.16	48.92	74.00	25.08	PK	Vertical
5	11227.200	41.73	39.20	8.27	-39.23	49.97	74.00	24.03	PK	Vertical
6	12118.000	42.43	39.30	8.82	-39.98	50.57	74.00	23.43	PK	Vertical

Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2024-12-05

Tested By:

Gen Liu

EUT:

Coach smartInfotainment series

Model Number:

Coach smartRadio Gen2

Test Mode:

TX DH5 2480MHz

Power Supply:

DC 24V

Condition:

Temp:21.5°C;Humi:48.4%

Test Site:

DDT 3# Chamber


File Path:

d:\ts\2024 report data\Q24110530-4E\FCC ABOVE 1G\9

Memo:

Sample Numbler:S24110530-001

Test Graph



Data List										
NO.	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	3720.000	48.21	30.44	5.10	-39.61	44.14	74.00	29.86	PK	Horizontal
2	4782.500	45.25	32.43	5.52	-39.62	43.58	74.00	30.42	PK	Horizontal
3	7392.000	42.93	36.72	6.65	-40.65	45.65	74.00	28.35	PK	Horizontal
4	9117.500	41.72	38.50	7.34	-38.89	48.67	74.00	25.33	PK	Horizontal
5	11898.700	42.98	38.90	8.70	-39.90	50.68	74.00	23.32	PK	Horizontal
6	16133.400	40.55	37.87	10.18	-39.49	49.11	74.00	24.89	PK	Horizontal

Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2024-12-05

Tested By:

Gen Liu

EUT:

Coach smartInfotainment series

Model Number:

Coach smartRadio Gen2

Test Mode:

TX DH5 2480MHz

Power Supply:

DC 24V

Condition:

Temp:21.5°C;Humi:48.4%

Test Site:

DDT 3# Chamber


File Path:

d:\ts\2024 report data\Q24110530-4E\FCC ABOVE 1G\10

Memo:

Sample Numbler:S24110530-001

Test Graph



Data List										
NO.	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	3720.000	52.27	30.44	5.10	-39.61	48.20	74.00	25.80	PK	Vertical
2	4959.300	47.45	33.12	5.63	-39.60	46.60	74.00	27.40	PK	Vertical
3	7582.400	43.31	36.46	6.75	-40.48	46.04	74.00	27.96	PK	Vertical
4	11154.100	42.27	39.25	8.23	-39.15	50.60	74.00	23.40	PK	Vertical
5	12306.700	41.51	39.30	8.92	-39.94	49.79	74.00	24.21	PK	Vertical
6	16041.600	39.55	37.96	10.16	-39.43	48.24	74.00	25.76	PK	Vertical

Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.


3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

15. Band Edge Compliance

15.1. Test equipment

Equipment	Manufacturer	Model No.	Serial No.	Cal Due To	Cal. Interval
RF Cable	N/A	W13.02 AP1-X2	DDT-ZC04023	2025/03/31	1 Year
High Pass filter	Xi'an Xingbo	XBLBQ-GTA67	DDT-ZC02179	2025/04/22	1 Year
EMI TEST RECEIVER	R&S	ESU26	DDT-ZC01909	2025/03/31	1 Year
RF cable	Yuhu Technology	JCTB810-NJ-NJ-9M	DDT-ZC02538	2025/03/31	1 Year
Active Loop Antenna	Schwarzbeck	FMZB1519	DDT-ZC00524	2025/09/11	2 Year
High pass filter	Micro-Tronics	HPM50102	DDT-ZC00561	2025/04/22	1 Year
PSA Series Spectrum Analyzer	Agilent	E4447A	DDT-ZC00517	2025/03/31	1 Year
Trilog Broadband Antenna	Schwarzbeck	VULB 9163	DDT-ZC02050	2025/07/11	1 Year
Micro-Tronics filters	REBES	BRM50702	DDT-ZC03242	/	/
High pass filter	Micro-Tronics	HPM50108	DDT-ZC00560	2025/04/22	1 Year
Hochgewinn-Hornantenne	SCHWARZBECK	BBHA 9120 D	DDT-ZC02129	2025/09/18	2 Year
RF cable	Zhongke Junchuang	JCT26S-NJ-NJ-1.5M	DDT-ZC02762	2025/03/31	1 Year
Micro-Tronics filters	REBES	BRM50716	DDT-ZC03240	/	1 Year
RF Cable	N/A	W24.02 HL-562	DDT-ZC04022	2025/03/31	1 Year
Pre-amplifier	COM-POWER	PAM-840A	DDT-ZC01693	2025/03/31	1 Year
Broad-Band Horn Antenna	Schwarzbeck	BBHA 9170	DDT-ZC00506	2025/04/26	1 Year
RF cable	Yuhu Technology	ZT26S-SMAJ-SMAJ-1M	DDT-ZC02037	2025/03/31	1 Year

15.2. Block diagram of test setup



15.3. Limits

All restriction band should comply with 15.209, other emission should be at least 20 dB below the fundamental.

15.4. Assistant equipment used for test

Assistant equipment	Manufacturer	Model number	Description	other
/	/	/	/	/

15.5. Test procedure

Same with Radiated Emission except change investigated frequency range.

Remark 1: All restriction band have been tested, and only the worst case is shown in report.

Remark 2: Both horizontal and vertical polarities have been tested, and only the worst polarities are reported.

15.6. Test result


PASS. (See below detailed test result)

15.7. Test data

TR-4-E-009 Radiated Emission Test Result

Test Date:	2024-12-05	Tested By:	Gen Liu
EUT:	Coach smartInfotainment series	Model Number:	Coach smartRadio Gen2
Test Mode:	TX DH5 2480MHz	Power Supply:	DC 24V
Condition:	Temp:21.5°C;Humi:48.4%	Test Site:	DDT 3# Chamber
File Path:	d:\ts\2024 report data\Q24110530-4E\FCC ABOVE 1G\11		
Memo:	Sample Numbel:S24110530-001		

Test Graph



Data List										
NO.	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	2483.500	16.77	27.53	3.62	0.00	47.92	74.00	26.08	PK	Horizontal
2	2485.063	20.46	27.54	3.62	0.00	51.62	74.00	22.38	PK	Horizontal

- Note:
- Level = Reading + Cable loss + Antenna Factor + AMP
 - If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
 - Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2024-12-05

Tested By:

Gen Liu

EUT:

Coach smartInfotainment series

Model Number:

Coach smartRadio Gen2

Test Mode:

TX DH5 2402MHz

Power Supply:

DC 24V

Condition:

Temp:21.5°C;Humi:48.4%

Test Site:

DDT 3# Chamber


File Path:

d:\ts\2024 report data\Q24110530-4E\FCC ABOVE 1G\12

Memo:

Sample Numbler:S24110530-001

Test Graph



Data List										
NO.	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	2375.590	19.90	27.20	3.56	0.00	50.66	74.00	23.34	PK	Horizontal
2	2390.000	17.44	27.26	3.57	0.00	48.27	74.00	25.73	PK	Horizontal

- Note:
1. Level = Reading + Cable loss + Antenna Factor + AMP

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2024-12-05

Tested By:

Gen Liu

EUT:

Coach smartInfotainment series

Model Number:

Coach smartRadio Gen2

Test Mode:

TX 2DH5 2402MHz

Power Supply:

DC 24V

Condition:

Temp:21.5°C;Humi:48.4%

Test Site:

DDT 3# Chamber


File Path:

d:\ts\2024 report data\Q24110530-4E\FCC ABOVE 1G\13

Memo:

Sample Numbler:S24110530-001

Test Graph



Data List										
NO.	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	2371.000	18.62	27.18	3.56	0.00	49.36	74.00	24.64	PK	Horizontal
2	2390.000	15.73	27.26	3.57	0.00	46.56	74.00	27.44	PK	Horizontal

- Note:
1. Level = Reading + Cable loss + Antenna Factor + AMP

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2024-12-05

Tested By:

Gen Liu

EUT:

Coach smartInfotainment series

Model Number:

Coach smartRadio Gen2

Test Mode:

TX 2DH5 2480MHz

Power Supply:

DC 24V

Condition:

Temp:21.5°C;Humi:48.4%

Test Site:

DDT 3# Chamber


File Path:

d:\ts\2024 report data\Q24110530-4E\FCC ABOVE 1G\14

Memo:

Sample Numbler:S24110530-001

Test Graph



Data List										
NO.	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	2483.500	20.89	27.53	3.62	0.00	52.04	74.00	21.96	PK	Horizontal
2	2487.691	22.50	27.55	3.62	0.00	53.67	74.00	20.33	PK	Horizontal

Data List									
NO.	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	2483.500	15.78	27.53	3.62	46.93	54.00	7.07	AV	Horizontal
2	2487.603	15.08	27.55	3.62	46.25	54.00	7.75	AV	Horizontal

- Note:
1. Level = Reading + Cable loss + Antenna Factor + AMP

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2024-12-05

Tested By:

Gen Liu

EUT:

Coach smartInfotainment series

Model Number:

Coach smartRadio Gen2

Test Mode:

TX 3DH5 2480MHz

Power Supply:

DC 24V

Condition:

Temp:21.5°C;Humi:48.4%

Test Site:

DDT 3# Chamber


File Path:

d:\ts\2024 report data\Q24110530-4E\FCC ABOVE 1G\15

Memo:

Sample Numbler:S24110530-001

Test Graph



Data List										
NO.	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	2483.500	28.92	27.53	3.62	0.00	60.07	74.00	13.93	PK	Horizontal
2	2483.590	30.59	27.53	3.62	0.00	61.74	74.00	12.26	PK	Horizontal
3	2484.151	28.84	27.54	3.62	0.00	60.00	74.00	14.00	PK	Horizontal

Data List										
NO.	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity	
1	2483.500	18.99	27.53	3.62	50.14	54.00	3.86	AV	Horizontal	
2	2483.590	18.95	27.53	3.62	50.10	54.00	3.90	AV	Horizontal	
3	2483.901	17.25	27.54	3.62	48.41	54.00	5.59	AV	Horizontal	

Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2024-12-05

Tested By:

Gen Liu

EUT:

Coach smartInfotainment series

Model Number:

Coach smartRadio Gen2

Test Mode:

TX 3DH5 2402MHz

Power Supply:

DC 24V

Condition:

Temp:21.5°C;Humi:48.4%

Test Site:

DDT 3# Chamber


File Path:

d:\ts\2024 report data\Q24110530-4E\FCC ABOVE 1G\16

Memo:

Sample Numbler:S24110530-001

Test Graph



Data List										
NO.	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	2376.030	19.34	27.20	3.56	0.00	50.10	74.00	23.90	PK	Horizontal
2	2390.000	15.71	27.26	3.57	0.00	46.54	74.00	27.46	PK	Horizontal

- Note:
1. Level = Reading + Cable loss + Antenna Factor + AMP

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.


3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

16. Power Line Conducted Emissions

16.1. Test equipment

Equipment	Manufacturer	Model No.	Serial No.	Cal Due To
/	/	/	/	/

16.2. Block diagram of test setup



16.3. Limits

Frequency	Quasi-Peak Level dB(uV)	Average Level dB(uV)
150 kHz~500 kHz	66 ~ 56*	56 ~ 46*
500 kHz~5 MHz	56	46
5 MHz~30 MHz	60	50

Note 1: * Decreasing linearly with logarithm of frequency.

Note 2: The lower limit shall apply at the transition frequencies.

16.4. Assistant equipment used for test

Assistant equipment	Manufacturer	Model number	Description	other
/	/	/	/	/

16.5. Test procedure

The EUT and Support equipment, if needed, were put placed on a non-metallic table, 80cm above the ground plane.

All support equipment power received from a second LISN.

Emissions were measured on each current carrying line of the EUT using an EMI Test Receiver connected to the LISN powering the EUT.

The Receiver scanned from 150 kHz to 30 MHz for emissions in each of the test modes.

During the above scans, the emissions were maximized by cable manipulation.

The test mode(s) described in clause 2.4 were scanned during the preliminary test.

After the preliminary scan, we found the test mode producing the highest emission level.

The EUT configuration and worse cable configuration of the above highest emission levels were recorded for reference of the final test.

EUT and support equipment were set up on the test bench as per the configuration with highest emission level in the preliminary test.

A scan was taken on both power lines, Neutral and Line, recording at least the six highest emissions.

Emission frequency and amplitude were recorded into a computer in which correction factors were used to calculate the emission level and compare reading to the applicable limit.

The test data of the worst-case condition(s) was recorded.

The bandwidth of test receiver is set at 9 kHz.

16.6. Test result

Not applicable. EUT is DC powered.

18. Photos of the EUT

Please refer to appendix I

-----End Report-----