FCC §15.247 (i) & §2.1091- MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Report No.: SZ1211009-52658E-RFA

Applicable Standard

According to subpart 15.247 (i) and subpart 2.1091 systems operating under the provisions of this section shall be operated in a manner that ensures the public is not exposed to RF energy level in excess of the communication guidelines.

Limits for General Population/Uncontrolled Exposure

Limits for General Population/Uncontrolled Exposure										
Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Averaging Time (Minutes)						
0.3-1.34	614	1.63	*(100)	30						
1.34-30	824/f	2.19/f	$*(180/f^2)$	30						
30-300	27.5	0.073	0.2	30						
300-1500	/	/	f/1500	30						
1500-100,000	/	/	1.0	30						

f = frequency in MHz

* = Plane-wave equivalent power density

a)

Result

Calculated Formulary:

Predication of MPE limit at a given distance

$$S = \frac{PG}{4\pi R^2}$$

S = power density (in appropriate units, e.g. mW/cm²)

P = power input to the antenna (in appropriate units, e.g., mW).

G = power gain of the antenna in the direction of interest relative to an isotropic radiator, the power gain factor, is normally numeric gain.

R = distance to the center of radiation of the antenna (appropriate units, e.g., cm)

For simultaneously transmit system, the calculated power density should comply with:

$$\sum_{i} \frac{S_{i}}{S_{Limit,i}} \le 1$$

Version 15: 2021-11-09 Page 13 of 70 FCC-BT; RSS-BT

Mode	Frequency (MHz)	Antenna Gain		Tune up conducted power		Evaluation Distance	Power Density	MPE Limit
		(dBi)	(numeric)	(dBm)	(mW)	(cm)	(mW/cm^2)	(mW/cm ²)
BT	2402-2480	0	1.00	8.5	7.08	20	0.0014	1
BLE	2402-2480	0	1.00	8.5	7.08	20	0.0014	1
2.4GHz Wi-Fi	2412-2462	2	1.58	18.0	63.10	20	0.0199	1
5GHz Wi-Fi	5150-5250	2	1.58	18.0	63.10	20	0.0199	1
	5250-5350	2	1.58	18.0	63.10	20	0.0199	1
	5470-5725	2	1.58	20.0	100.00	20	0.0315	1
	5725-5850	2	1.58	20.0	100.00	20	0.0315	1

Report No.: SZ1211009-52658E-RFA

Note: 1. The tune up conducted power was declared by the applicant.

2. The BT and Wi-Fi can transmit at the same time.

Simultaneous transmitting consideration (worst case):

The ratio=MPE_{BT}/limit+MPE $_{Wi-Fi}$ /limit =0.0014/1+0.0315/1=0.0329<1.0

To maintain compliance with the FCC's RF exposure guidelines, place the equipment at least 20cm from nearby persons.

Result: Compliant.