

Product Specifications

CUSTOMER Product Name:		Energy S	Energy Stack Transmitter coil			
		Transmi				
Material	code: PART					
No.						
		Inducta	nce: 7.2uH±10% Wire			
Specifications: PRODUCT SPEC			cation: 0.08*80*11Ts (18.5mm			
			pecification: 41.5*5.3*0.8 doul	ole slots + 18*0	0.8 small	
		_	magnetic sheet Wire			
dou	Franch	_ length:	55mm 3mm high temperature	tape/single slo	t wire	<u></u>
day Expect: DATE			August 26, 2024			
version	model:		_			
VEF	RSION	REV 1.	0			
ersion			nges	Responsible Person	date	Remark
/ision		Modified Content		Principle	1	Note
V 1.0		Initial I	elease	Xue Le	i 2024-08-26	
DDE	PARED BY		CHECKED BY		APPROVE) BV
FREI	FARED BT		CHECKED B1		AFFROVEL	761
Custome	er approval signature and	l seal				
Author	ized signature	&				
CC	ompany chop					
•			i e e e e e e e e e e e e e e e e e e e			


Company Name: Shenzhen Chenxing Electronic Technology Co., Ltd.



Product Specifications


SPECIFICATION

1. Product size





2. Schematic diagram



3. Winding parameters

Terminals		Wire diameter	Number of laps	Winding direction	
TERMINAL		WIRE	Turns	Winding Direction	
S	F	2UEW 0.08*80P	11Ts	CCW	

4. Electrical characteristics

TEMPERATURE:25±10°C, RELATIVE HUMIDITY:65±20%

project	Terminals	standard	Test conditions	Test Equipment
ITEM	TERMINAL	SPECIFICATION	TEST FREQUENCY	TEST EQUIPMENTS
IN.	S-F	Lÿ7.2uH±10%	100KHz/1.0V	LCZ METER 1062B
		Qÿÿ70		
		Rÿ<60mohm		

5. Materials List

Serial number	Material	Specification
1	Wire	0.08*80p 2UEW-hot air copper wire
2	Magnetic disk	41.5°5.3°0.5 double slots + 18°0.8 small disc
3	glue	Water-based white latex
4	Tin Bar	Environmentally handley lead have
5	adhesive tape	3mm high temperature tape

Company Name: Shenzhen Chenxing Electronic Technology Co., Ltd.



6. Product pictures (refer to coil only)

