英文







Singal Source Setting

Press the " = " button above the remote control, press "OK" to switch the input source.

FCC Statement

This device complies with Part 15 of the PCC Rules. Operation is subject to the following bacondoxes: (1) this device may not cause harmful interference, and CIII this device must account yill reference the context, chadding interference that may cause undestined operation. Changes or modifications to this unit not expressly approved by the party responsible for compliance could world the user's authority to operate the explainers.

congliance could visit the user's authority to operate the suppliment. NOTE: The explainment has been tested and bound occurring with the inmits for a Cipies B digital donces pursuant to Part 15 of the PCC Rubes. These lents are designed to provide researched proteined upgrant familiar limitations in a residual and residual proteined and accordance with the instruction, many cause harmful inferiorence to addic communications, between the explainment of the proteined proteined accordance with the instruction, many cause harmful inferiorence to addic communications, between the explainment of the proteined accordance with the proteined accordance and the proteined accordance accordance and the proteined accordance and the proteined accordance and the proteined accordance and the proteined accordance accordance accordance and the proteined accordance accordance

Important Safety Precautions

U Disk Support Format

| | File Type | File format supported |
|--|-----------|---|
| | Picture | JPG- BMP- PNG- GIF |
| | Video | H,265 · H,264 · VP9/8/6 · MPEG1/2/4 · VC-1 · AVS/AVS+ (Above based on 1080P@60fps or 30fps) |
| | Audio | FLAC, APE, MP3, WAV, OGG |

Mobile Phone Projection

*Note: Advantage of push is it does not affect normal use of the mobile phone.

1. Ensure the Phone and Projector are under the same WiFI.

2. Open video software of the mobile phone and finds the TV push icon in the fo



Projection Distance Reference

| no keystone correction / Inch) | width (m) | Lens - screen (m) |
|--------------------------------|-------------|-------------------|
| 45 | 0.99 × 0.5 | 1.2 |
| 50 | 1.11 × 0.62 | 1.5 |
| 60 | 1.33 × 0.75 | 1.6 |
| 70 | 1.55 × 0.87 | 1.9 |
| 80 | 1.77 × 0.99 | 2.1 |
| 90 | 1.99 × 1.12 | 2.4 |
| 100 | 2.21 × 1.25 | 3.7 |
| 110 | 2.43 × 1.37 | 3.0 |
| 120 | 2.66 × 1.49 | 3.3 |
| 130 | 2.88 × 1.62 | 3.6 |
| | | |

Projection size (under status of Screen length *

Cleaning Method

Please make sure the power plug is unplugged before cleaning. Do not use pesticides or other volatile chemicals on the projector or lens. Do not let rubber or viryl products contacts the projector for a long time, which will damage the coating and make it peeled off.

- Clean the Projector.

 1. Wipe with a soft, dry cotton cloth, If it's dried seriously, we can wipe with soft cloth that stock with dishard nourial destroyers, then dry with a clean and dry doth. Please pay more attention in stee with chemical fiber dipth.

 2. Don't use thinner, benzane or any other solvents to avoid quality reduction or coating.
- pealing off atc.

 3. A broad can be inserted into the front of the vaccuum cleaner to remove did inside the vaccuum cleaner to remove did inside the vorte. Please don't use vaccuum cleaner with no connector, or clean with vorte directly.

 4. Please don't scrape the machine with neigh or any other hard objects so as to avoid scratches.

- 1. Clean lens with the same method for camera lens: please use professional blow dryer or cleaning paper for glasses, ensure lens are not scratched,
- Inlet and Outlet Dust Cleaning . Dust in the inlet and outlet will prevent ventilation and inc

Poisonous and Harmful Substance, Element Name and Content

| | Hazardous substances | | | | | | |
|-----------------|----------------------|-----------------|-----------------|------------------------------------|---|--|--|
| Part name | Lead (Pb) | Mercury (Hg) | Cadmium (Cd) | Hexavalent chromium (Cr(VI)) | Polybro minated Biphenylis (PBB) | Polybro minated Diphenyl Ethers (PBOE) | |
| Shell | 0 | 0 | 0 | 0 | 0 | 0 | |
| Optical Machine | 0 | 0 | 0 | 0 | 0 | 0 | |
| Circuit Board | 0 | 0 | 0 | 0 | 0 | 0 | |
| Fan | 0 | 0 | 0 | 0 | 0 | 0 | |
| Other Wires | × | 0 | 0 | 0 | 0 | 0 | |
| Remote Control | 0 | 0 | 0 | 0 | 0 | 0 | |
| Power Supply | 0 | 0 | 0 | 0 | 0 | 0 | |

- O. Content of the hazardous substance in all homogeneous materials of the component is under the limits of SUT11305-2000.

 K. Content of the hazardous substance exceeds the limit requirements specified by SUT11305-2000 in a least one homogeneous material of the component. The components labeled "X" have no substitutive due to displat substances are components and the component in the component

The number in the logo represents the normal envir

Warranty Card

- 1. We offer "three guarantees " for this product, One year warranty for norantificial diamaged since purchasing (subject to purchase record).
 2. We will provide warranty service for any default caused by product
 technical reasons during warranty period,
 3. Following shations are out of the nairframe
 3. Endowing shations are out of the nairframe
 4. Unsulvative diassessmithy and repair without our consent.
 5. Damage that caused by settered force and other natural disasters.
 4. Please iff this could not contain the products have quality
 problem.
 5. The swarranty is limited to product meinterance during the warranty period.
 6. This warranty is limited to product meinterance during the warranty period.
 6. This warranty is limited to product meinterance during the warranty period.
 6. This warranty is limited to product meinterance during the warranty period.
 6.



After-Sale Service Card

wanbo



WPD24

Wanbo Projector Introduction Manual

Important Safety Precautions

You are recommended to use the projector in a dark room to achieve the best effect.

- Ensure adequate ventilation and vent are not blocked to prevent heat accumulation inside the machine.
- Please use soft packaging materials to move the projector, keep the projector from vident vibration.
- 7. Please don't watch lens directly when it's on so as to protect our eyes from damage.

Don't expose the machine to rain or moisture so as to prevent misfire or electric shock. The product is applicable to be used under a temperature of 0-35 C for a safe side.















Projector Part Name and Function













Installation and Adjustment


























Projector hanger installation steps 0




Racic Parameters

| Dasic F | alailleteis | | |
|----------------|-------------------------|---------------------|------------------|
| Product Name | Wanbo Projector | Display Principle | LCD |
| Light Source | LED | Hom | 5W*2 |
| Operation Mode | Remote Control | Working Environment | 0-35 ° C |
| Output Port | Headphone Audio Output | Input Port | HDM I USB |
| Net Weight | 1.5kg | Machine Size | 145×142×219mm |
| Power Supply | AC 100-240V 50/60Hz 2A | (Max) | |
| Accessory | User Manual / RemoteCor | ntrol / Power Cord | |

Remote Control

FCC ID: 2A7PIWPD24



Mobile Phone with the Same Screen



- Same Screen User Instruction Android Devices 1, Ensure the Phone and Projector under the same WIFI.
- Find the projection name "TV Stick" corresponding to the projecto dick connect to complete same screen process.

- 1. Ensure the Phone and Projector under the same WIFL
- 2. Download "AirScreen" in Google Play Store of the Projector. 3. Open "AirScreen", follow App prompts. 4. Open console of the Phone, click"AirPlay"to search and connect the device,

| IOS Old Version Airplay | IOS New Version Screen Min |
|-------------------------|----------------------------|



- How to be with the same screen for iPhone under status of No Wifi If there has no WIFI, firstly open 4G network of iPhone, then open WIFI hot spot in the "Settings" interface of the phone.
- 2. Download "AirScreen" in Google Play Store of the Projector.
- 4. Open console of the Phone, dick"AirPlay"to search and connect the device. Find the projection name "AS-TV Stick" corresponding to the projector, dick connect to complete same screen process.

| 封底 | 1 | 2 | 3 | 4 | 5 | 6 | 封面 |
|----|---|---|----|----|----|----|----|
| 7 | 8 | 9 | 10 | 11 | 12 | 13 | 14 |

| 图纸号 | R2(1+1)-SMS01-002 | 类型 | R2(1+1) 英文说明书 |
|------|--------------------|----|---------------------------------|
| 颜色 | 黑白印刷 | 尺寸 | 折前尺寸: 720*120mm; 折后尺寸: 90*120mm |
| 材质工艺 | 128g铜版纸 白色;8页风琴折双面 | | |
| 备注 | | | |