


## **TEST REPORT**

**Applicant:** Queclink Wireless Solutions Co., Ltd.  
**EUT Description:** 4G Industrial Router  
**Model:** WR100LNA  
**Brand:** Queclink  
**FCC ID:** YQD-WR100LNA  
**Standards:** FCC 47 CFR Part 2 Subpart J  
FCC 47 CFR Part 15 Subpart C  
**Date of Receipt:** 2024/05/25  
**Date of Test:** 2024/04/25 to 2024/05/27  
**Date of Issue:** 2024/06/13

TOWE. tested the above equipment in accordance with the requirements set forth in the above standards. The test results show that the equipment tested is capable of demonstrating compliance with the requirements as documented in this report.

the results documented in this report apply only to the tested sample, under the conditions and modes of operation as described herein. It is the manufacturer's responsibility to assure that additional production units of the model are manufactured with identical electrical and mechanical components. All sample tested were in good operating condition throughout the entire test program. Measurement Uncertainties are published for informational purposes only and were not taken into account unless noted otherwise. without written approval of TOWE, the test report shall not be reproduced except in full.



---

**Huang Kun**  
**Approved By:**



---

**Chen Chengfu**  
**Reviewed By:**

## Revision History

Rev.	Issue Date	Description	Revised by
01	2024/06/13	Original	Chen Chengfu

## Summary of Test Results

Clause	FCC Part	Test Items	Result
4.1	§15.203/15.247(b)	Antenna Requirement	PASS
4.2	§15.207	AC Power Line Conducted Emission	PASS
4.3	§15.247 (b)(3)	Output Power	PASS
4.4	§15.247 (a)(2)	Occupied Bandwidth	Reporting purposes only
4.5	§15.247 (e)	Power Spectral Density	PASS
4.6	§15.247(d)	Band Edge for Conducted Emissions	PASS
4.7	§15.247(d)	Spurious RF Conducted Emissions	PASS
4.8	§15.205/15.209	Radiated Spurious emissions and Band Edge	PASS
Test Method: ANSI C63.10-2020, KDB 558074 D01 15.247 Mesa Guidan13/06/2024ce v05r02. Remark: Pass is EUT meets standard requirements.			

## Table of Contents

<b>1</b>	<b>General Description .....</b>	<b>5</b>
1.1	Lab Information .....	5
1.1.1	Testing Location .....	5
1.1.2	Test Facility / Accreditations .....	5
1.2	Client Information .....	5
1.2.1	Applicant .....	5
1.2.2	Manufacturer .....	5
1.3	Product Information .....	6
<b>2</b>	<b>Test Configuration .....</b>	<b>7</b>
2.1	Test Channel .....	7
2.2	Worst-case configuration and Mode .....	7
2.3	Test Duty Cycle .....	8
2.4	Support Unit used in test .....	8
2.5	Test Environment .....	8
2.6	Test RF Cable .....	8
2.7	Modifications .....	8
2.8	Test Setup Diagram .....	9
2.8.1	Conducted Configuration .....	9
2.8.2	Radiated Configuration .....	10
<b>3</b>	<b>Equipment and Measurement Uncertainty .....</b>	<b>11</b>
3.1	Test Equipment List .....	11
3.2	Measurement Uncertainty .....	12
<b>4</b>	<b>Test Results .....</b>	<b>13</b>
4.1	Antenna Requirement .....	13
4.2	AC Power Line Conducted Emissions .....	14
4.3	Output Power .....	17
4.4	Occupied Bandwidth .....	18
4.5	Power Spectral Density .....	19
4.6	Band Edge for Conducted Emissions .....	20
4.7	Spurious RF Conducted Emissions .....	21
4.8	Radiated Spurious Emissions and Band Edge .....	22
<b>5</b>	<b>Test Setup Photos .....</b>	<b>24</b>
	Appendix .....	25

# 1 General Description

## 1.1 Lab Information

### 1.1.1 Testing Location

These measurements tests were conducted at the Sushi TOWE Wireless Testing(Shenzhen) Co., Ltd. facility located at F401 and F101, Building E, Hongwei Industrial Zone, Liuxian 3rd Road, Bao'an District, Shenzhen, China. The measurement facility is compliant with the test site requirements specified in ANSI C63.4-2014  
Tel.: +86-755-27212361

Contact Email: info@towewireless.com

### 1.1.2 Test Facility / Accreditations

#### A2LA (Certificate Number: 7088.01)

This laboratory is accredited in accordance with the recognized International Standard ISO/IEC 17025:2017 General requirements for the competence of testing and calibration laboratories. This accreditation demonstrates technical competence for a defined scope and the operation of a laboratory quality management system (refer to joint ISO-ILAC-IAF Communiqué dated April 2017).

#### FCC Designation No.: CN1353

Sushi TOWE Wireless Testing(Shenzhen) Co., Ltd. has been recognized as an accredited testing laboratory. Designation Number: CN1353.

#### ISED CAB identifier: CN0152

Sushi TOWE Wireless Testing(Shenzhen) Co., Ltd. has been recognized by ISED as an accredited testing laboratory.

CAB identifier: CN0152

Company Number: 31000

## 1.2 Client Information

### 1.2.1 Applicant

Applicant:	Queclink Wireless Solutions Co., Ltd.
Address:	No.30, Lane 500, Xinlong Road , Minhang District, Shanghai, China, 201101

### 1.2.2 Manufacturer

Manufacturer:	Queclink Wireless Solutions Co., Ltd.
Address:	No.30, Lane 500, Xinlong Road , Minhang District, Shanghai, China, 201101

### 1.3 Product Information

EUT Description:	4G Industrial Router		
Model:	WR100LNA		
Brand:	Queclink		
Hardware Version:	V1.02		
Software Version:	WR100_FCTR00A06V02		
IMEI.:	868260051937069 (Only RF) 868260051937432 (Only RSE)		
Smart System:	<input checked="" type="checkbox"/> SISO	802.11b/g/n	/
	<input type="checkbox"/> MIMO	N/A	( )TX( )RX
	<input type="checkbox"/> CDD	N/A	( )TX( )RX
Frequency Range:	2400 ~ 2483.5MHz		
Channel Frequency:	20M bandwidth Channel: 2412 ~ 2462MHz		
	40M bandwidth Channel: 2422 ~ 2452MHz		
Channel Number:	11:	802.11b/g/n20	
	9:	802.11n40	
Antenna Type:	<input type="checkbox"/> Integral, <input checked="" type="checkbox"/> External		
Antenna Gain:	1.09dBi (Provided by Applicant)		
Remark: The above EUT's information was declared by applicant, please refer to the specifications or user's manual for more detailed description.			

## 2 Test Configuration

### 2.1 Test Channel

Frequency Channels							
Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
1	2412MHz	4	2427MHz	7	2442MHz	10	2457MHz
2	2417MHz	5	2432MHz	8	2447MHz	11	2462MHz
3	2422MHz	6	2437MHz	9	2452MHz	/	
Remark:							
In section 15.31(m), regards to the operating frequency range over 10 MHz, the Lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test, and the selected channel see below:							
Modulation Type		Test Channel		Test Frequency			
802.11b/g/n20		The Lowest channel (CH1)		2412MHz			
		The Middle channel (CH6)		2437MHz			
		The Highest channel (CH11)		2462MHz			
Modulation Type		Test Channel		Test Frequency			
802.11n40		The Lowest channel (CH3)		2422MHz			
		The Middle channel (CH6)		2437MHz			
		The Highest channel (CH9)		2452MHz			

### 2.2 Worst-case configuration and Mode

Modulation Type	SISO - Data Rate	MIMO - Data Rate
802.11b	1 Mbps	N/A
802.11g	6 Mbps	N/A
802.11n20	MCS0 (6.5 Mbps)	N/A
802.11n40	MCS0 (13.5 Mbps)	N/A
Transmitting mode:	Keep the EUT was programmed to be in continuously transmitting mode.	

## 2.3 Test Duty Cycle

TestMode	Frequency[MHz]	T(ms)	T Period(ms)	Duty Cycle(%)	1/T	VBW Set
11B	2412	12.19	12.23	99.67	0.082034454	10Hz
11B	2437	12.20	12.24	99.67	0.081967213	10Hz
11B	2462	12.19	12.23	99.67	0.082034454	10Hz
11G	2412	2.02	2.07	97.58	0.495049505	1KHz
11G	2437	2.02	2.07	97.58	0.495049505	1KHz
11G	2462	2.02	2.07	97.58	0.495049505	1KHz
11N20	2412	1.89	1.94	97.42	0.529100529	1KHz
11N20	2437	1.88	1.93	97.41	0.531914894	1KHz
11N20	2462	1.89	1.94	97.42	0.529100529	1KHz

Note: If Duty Cycle>98% VBW is set to 10Hz.

## 2.4 Support Unit used in test

Description	Manufacturer	Model	Serial Number
USB To R232/485 Converter	AMSAMOTION	USB-232/485	/

## 2.5 Test Environment

Temperature:	Normal: 15℃ ~ 35℃
Humidity:	40-75 % RH Ambient
DC Voltage:	DC 12V / 2A (Adapter Output)
AC Voltage:	AC 120V/60Hz
Remark: The testing environment is within the scope of the EUT user manual and meets the requirements of the standard testing environment.	

## 2.6 Test RF Cable

**For all conducted test items:** The offset level is set spectrum analyzer to compensate the RF cable loss and attenuator factor between RF conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level will be exactly the RF output level.

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

*Offset = RF cable loss + attenuator factor.*


## 2.7 Modifications

No modifications were made during testing.




## 2.8 Test Setup Diagram

### 2.8.1 Conducted Configuration



## 2.8.2 Radiated Configuration



### 3 Equipment and Measurement Uncertainty

All test and measuring equipment utilized to perform the tests documented in this report are calibrated on a regular basis, whichever is less, and where applicable is traceable to recognized national standards.

#### 3.1 Test Equipment List

Description	Manufacturer	Model	SN	Last Due	Cal Due
EXA Signal Analyzer, Multi-touch	Keysight	N9010B	MY63440541	2023/06/27	2024/06/26
Power Sensor	Anritsu	MA24408A	12520	2023/07/28	2024/07/27
Measurement Software	Tonscend	JS1120-3	10659	N/A	N/A

Radiated Emission					
Description	Manufacturer	Model	S.N.	Last Due	Cal Due
Biconic Logarithmic Periodic Antennas	Schwarzbeck	VULB9163	1643	2023/06/25	2025/06/24
Double-Ridged Horn Antennas	Schwarzbeck	BBHA 9120D	2809	2023/06/25	2025/06/24
Broad-Band Horn Antenna	Schwarzbeck	BBHA 9170	1290	2023/06/25	2025/06/24
Signal Analyzer	Keysight	N9020A	MY49100252	2024/03/25	2025/03/24
EXA Signal Analyzer, Multi-touch	Keysight	N9010B	MY63440541	2023/06/27	2025/06/26
EMI Tester Receiver	Rohde & Schwarz	ESR7	102719	2023/08/17	2024/08/16
Low Noise Amplifier	Tonscend	TAP9K3G40	AP23A8060273	2023/04/08	2025/04/07
Low Noise Amplifier	Tonscend	TAP01018050	AP22G806258	2023/04/08	2025/04/07
Band Reject Filter Group	Townshend	JS0806-F	23A806F0652	N/A	N/A
Test Software	Tonscend	TS+	Version: 5.0.0	N/A	N/A
N/A: Not applicable, confirmed internally by the laboratory					

Conducted Emission					
Description	Manufacturer	Model	S.N.	Last Due	Cal Due
EMI Tester Receiver	Rohde & Schwarz	ESR3	103108	2023/07/28	2024/07/27
LISN	Rohde & Schwarz	ENV 216	102836	2024/01/10	2025/01/09
Test software	Rohde & Schwarz	ELEKTRA v4.61	N/A	N/A	N/A
N/A: Not applicable, confirmed internally by the laboratory					

### 3.2 Measurement Uncertainty

Parameter	U <sub>lab</sub>
Frequency Error	679.98Hz
Output Power	0.76dB
Conducted Spurious Emissions	2.22dB
Conducted Emissions(150KHz~30MHz)	2.43dB
Radiated Emissions(30MHz~1000MHz)	4.66dB
Radiated Emissions(1GHz~18GHz)	5.42dB
Radiated Emissions(18GHz~40GHz)	5.46dB

Uncertainty figures are valid to a confidence level of 95%

## 4 Test Results

### 4.1 Antenna Requirement

<b>Standard Applicable:</b>	47 CFR Part 15C Section 15.203 /247(b)
<p>15.203 requirement: An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.</p> <p>15.247(b) (4) requirement: The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.</p>	
<p>The antenna gain and type as provided by the manufacturer are as follows: The antenna Type is External. With Ant gain is 1.09dBi. Antenna Anti-Replacement Construction: Using special antenna jack.</p>	

## 4.2 AC Power Line Conducted Emissions

### Limits

Frequency range (MHz)	Limit (dBuV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

\* Decreases with the logarithm of the frequency.


### Test Procedure

ANSI C63.10-2013, Section 6.2.

### Test Settings


1. The EUT was connected to AC power source through a LISN 1 (Line Impedance Stabilization Network) which provides a  $50\Omega/50\mu\text{H} + 5\Omega$  linear impedance. The power cables of all other units of the EUT were connected to a second LISN 2, which was bonded to the ground reference plane in the same way as the LISN 1 for the unit being measured. A multiple socket outlet strip was used to connect multiple power cables to a single LISN provided the rating of the LISN was not exceeded.
2. The tabletop EUT was placed upon a non-metallic table 0.8m above the ground reference plane. And for floor-standing arrangement, the EUT was placed on the horizontal ground reference plane.
3. The test was performed with a vertical ground reference plane. The rear of the EUT shall be 0.4 m from the vertical ground reference plane. The vertical ground reference plane was bonded to the horizontal ground reference plane. The LISN 1 was placed 0.8 m from the boundary of the unit under test and bonded to a ground reference plane for LISNs mounted on top of the ground reference plane. This distance was between the closest points of the LISN 1 and the EUT. All other units of the EUT and associated equipment was at least 0.8 m from the LISN 2.
4. Set the test-receiver system to Peak detect function and specified bandwidth (if bandwidth =9kHz) with maximum hold mode. Then measurement is also conducted by average detector and Quasi-Peak detector function respectively.
5. Both sides of AC line are checked for maximum conducted interference. In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.10 on conducted measurement.

### Test Setup



### Measuring Instruments

The measuring equipment is listed in the section 3.1 of this test report.

**Test Result:**

Test mode:	Transmitting		
Test Voltage:	AC 120V / 60Hz	Phase:	Neutral



Rg	Frequency [MHz]	PK+ Level [dBμV]	PK+: QPK Limit [dBμV]	PK+ Margin [dB]	AVG Level [dBμV]	AVG Limit [dBμV]	AVG Margin [dB]	Correction [dB]	Line
1	0.159	42.61	65.52	22.91	34.71	55.52	20.80	10.73	N
1	0.182	40.78	64.42	23.64	30.90	54.42	23.52	10.69	N
1	0.420	43.35	57.45	14.10	37.23	47.45	10.22	10.87	N
1	0.789	29.67	56.00	26.33	22.46	46.00	23.54	10.57	N
1	6.918	30.74	60.00	29.26	23.50	50.00	26.50	10.28	N

Note: Margin = Limit[dBμV] - Level[dBμV]



## 4.3 Output Power

### Limits

If with directional antenna gains less than 6 dBi, the limit is 30dBm.

### Test Procedure

ANSI C63.10:2013 Section 11.9.1.3(PKPM1) or 11.9.2.3.2(AVGPM-G)

### Test Settings

1. Set to the maximum power setting and enable the EUT transmit continuously.
2. The power output was measured on the EUT antenna port using RF Cable with attenuator connected to a power meter via wideband power sensor. Peak output power was read directly from power meter.
3. Measure and record the results in the test report.

### Test Setup

Refer to section 2.8.1 Setup 1 for details.

### Measuring Instruments

The measuring equipment is listed in the section 3.1 of this test report.

### Test Result

The detailed test data see: **Appendix**.

## 4.4 Occupied Bandwidth

### Limits

DTSBW: The minimum 6 dB bandwidth shall be at least 500 kHz.

99%BW: None, for reporting purposes only.

### Test Procedure

ANSI C63.10:2013 Section 11.8.2 and 6.9.3

### Test Settings

1. Set to the maximum power setting and enable the EUT transmit continuously.
2. The transmitter output is connected to a spectrum analyzer:
3. RBW = 100kHz(DTS)
4. RBW = 1% - 5%(99%BW)
5. VBW  $\geq$  3 times the RBW
6. Sweep = Auto
7. Detector = Peak
8. Trace = Max hold
9. The trace was allowed to stabilize
10. Measure and record the results in the test report.

### Test Notes

DTS: The signal analyzers' automatic bandwidth measurement capability of the spectrum analyzer was used to perform the 6dB bandwidth measurement. The "X" dB bandwidth parameter was set to X= 6. The bandwidth measurement was not influenced by any intermediate power nulls in the fundamental emission.

### Test Setup

Refer to section 2.8.1 Setup 2 for details.

### Measuring Instruments

The measuring equipment is listed in the section 3.1 of this test report.

### Test Result

The detailed test data see: **Appendix**.

## 4.5 Power Spectral Density

### Limits

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

### Test Procedure

ANSI C63.10:2013 Section 11.10.2(PKPSD)

### Test Settings

1. Set to the maximum power setting and enable the EUT transmit continuously
2. The transmitter output is connected to a spectrum analyzer
3.  $3\text{kHz} \leq \text{RBW} \leq 100\text{ kHz}$   
(If measured value exceeds requirement, then reduce RBW (but no less than 3 kHz) and repeat.)
4.  $\text{VBW} \geq 3$  times the RBW
5. Span = 1.5 times the DTS bandwidth
6. Sweep = Auto
7. Detector = Peak
8. Trace = Max hold
9. The trace was allowed to stabilize
10. Measure and record the results in the test report.

### Test Setup

Refer to section 2.8.1 Setup 2 for details.

### Measuring Instruments

The measuring equipment is listed in the section 3.1 of this test report.

### Test Result

The detailed test data see: **Appendix**.

## 4.6 Band Edge for Conducted Emissions

### Limits

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits.

If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph 15.247(b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB.

### Test Procedure

ANSI C63.10:2013 Section 11.11.3

### Test Settings

1. Set to the maximum power setting and enable the EUT transmit continuously
2. The transmitter output is connected to a spectrum analyzer
3. RBW = 100kHz
4. VBW = 300kHz
5. Point  $\geq 2 \times \text{span/RBW}$
6. Sweep = Auto
7. Detector = Peak
8. Trace = Max hold
9. The trace was allowed to stabilize
10. Measure and record the results in the test report

### Test Setup

Refer to section 2.8.1 Setup 2 for details.

### Measuring Instruments

The measuring equipment is listed in the section 3.1 of this test report.

### Test Result

The detailed test data see: **Appendix**.

## 4.7 Spurious RF Conducted Emissions

### Limits

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits.

If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph 15.247(b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB.

### Test Procedure

ANSI C63.10:2013 Section 11.11.3

### Test Settings

1. Set to the maximum power setting and enable the EUT transmit continuously.
2. Activate frequency hopping function if necessary.
3. The transmitter output is connected to a spectrum analyzer
4. The spectrum from 30MHz - 26.5GHz
5. RBW = 100kHz
6. VBW = 300kHz
7. Sweep = Auto
8. Detector = Peak
9. Trace = Max hold
10. The trace was allowed to stabilize
11. Measure and record the results in the test report

### Test Setup

Refer to section 2.8.1 Setup 2 for details.

### Measuring Instruments

The measuring equipment is listed in the section 3.1 of this test report.

### Test Result

The detailed test data see: **Appendix**.

## 4.8 Radiated Spurious Emissions and Band Edge

### Limits

Spurious emissions are permitted in an of the frequency bands:

MHz	MHz	MHz	MHz	GHz	GHz
0.090 - 0.110	12.29 - 12.293	149.9 - 150.05	1660 - 1710	4.5 - 5.15	14.47 - 14.5
0.495 - 0.505	12.51975 - 12.52025	156.52475 - 156.52525	1718.8 - 1722.2	5.35 - 5.46	15.35 - 16.2
2.1735 - 2.1905	12.5767 - 12.57725	156.7 - 156.9	2200 - 2300	7.25 - 7.75	17.7 - 21.4
4.125 - 128	13.36 - 13.41	162.0125 - 167.17	2310 - 2390	8.025 - 8.5	22.01 - 23.12
4.17725 - 4.17775	16.42 - 16.423	167.72 - 173.2	2483.5 - 2500	9.0 - 9.2	23.6 - 24.0
4.20725 - 4.20775	16.69475 - 16.69525	240 - 285	2655 - 2900	9.3 - 9.5	31.2 - 31.8
6.215 - 6.218	1680425 - 1680475	322 - 335.4	3260 - 3267	10.6 - 12.7	36.43 - 36.5
6.26775 - 6.26825	25.5 - 25.67	399.9 - 410	3332 - 3339	13.25 - 13.4	
6.31175 - 6.31225	37.5 - 38.25	608 - 614	3345.8 - 3358		
8.291 - 8.294	73 - 74.6	960 - 1240	3600 - 4400		
8.362 - 8.366	74.8 - 75.2	1300 - 1427			
8.37625 - 8.38675	108 - 121.94	1435 - 1626.5			
8.41425 - 8.41475	123 - 138	1645.5 - 1646.5			

Radiated disturbance of an intentional radiator:

Frequency	Field strength ( $\mu\text{V}/\text{m}$ )	Limit (dB $\mu\text{V}/\text{m}$ )	Remark	Measurement distance (m)
0.009MHz-0.490MHz	2400/F(kHz)	-	-	300
0.490MHz-1.705MHz	24000/F(kHz)	-	-	30
1.705MHz-30MHz	30	-	-	30
30MHz-88MHz	100	40.0	Quasi-peak	3
88MHz-216MHz	150	43.5	Quasi-peak	3
216MHz-960MHz	200	46.0	Quasi-peak	3
960MHz-1GHz	500	54.0	Quasi-peak	3
Above 1GHz	500	74.0	Peak	3
		54.0	Average	

### Test Procedure

ANSI C63.10:2013 Section 6.4 & 6.5 & 6.6

### Test Settings

- For radiated emissions measurements performed at frequencies less than or equal to 1GHz, the EUT shall be placed on a RF-transparent table or support at a nominal height of 80cm above the reference ground plane.
- For radiated emissions measurements performed at frequencies above 1GHz, the EUT shall be placed on a RF-transparent table or support at a nominal height of 150cm above the ground plane.
- Radiated measurements shall be made with the measurement antenna positioned in both horizontal and vertical polarization. The measurement antenna shall be varied from 1m to 4m in height above the reference ground in a search for the relative positioning that produces the maximum radiated signal level (i.e, field strength or received power), when orienting the measurement antenna in vertical polarization, the minimum height of the lowest element of the antenna shall clear the site reference ground plane by at least 25cm.
- For each suspected emission, the EUT was ranged its worst case and then tune the antenna tower(from 1~4m) and turntable(from 0~360°) find the maximum reading. Preamplifier and a high pass filter are used for the test in order get better signal level comply with the guidelines.
- Set to the maximum power setting and enable the EUT transmit continuously.
- The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90 kHz, 110-490 kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector.
- spectrum analyzer setting:  
Measurements 30MHz ~ 1000MHz: RBW = 120 kHz; VBW  $\geq$  300 kHz; Detector = Peak

Measurements Above 1000MHz: RBW = 1 MHz; VBW  $\geq$  3 MHz; Detector = Peak

Average Measurements Above 1000MHz:

RBW = 1 MHz, VBW  $\geq$  1/T, with peak detector for average measurements.

8. The field strength is calculated by adding the Antenna Factor, Cable Factor. The basic equation with a sample calculation is as follows:

Level = Reading(dB $\mu$ V) + AF(dB/m) + Factor(dB):

AF = Antenna Factor(dB/m)

Factor = Cable Factor(dB) - Preamplifier gain(dB)

Margin = Limit(dB $\mu$ V/m) – Level(dB $\mu$ V/m)

9. Repeat above procedures until all frequencies measured was complete.  
10. Measure and record the results in the test report.

### **Test Notes**

1. Emissions below 18GHz were measured at a 3-meter test distance while emissions above 18GHz were measured at a 1-meter test distance with the application of a distance correction factor.
2. Radiated spurious emissions were investigated from 9kHz to 30MHz, 30MHz-1GHz and above 1GHz. the disturbance between 9KHz to 30MHz and 18GHz to 40GHz was very low. The amplitude of spurious emissions from the radiator which are attenuated more than 20dB below the limit need not be recorded, so only the harmonics had been displayed.

### **Test Setup**

Refer to section 2.8.2 for details.

### **Measuring Instruments**

The measuring equipment is listed in the section 3.1 of this test report.

### **Test Result**

The detailed test data see: **Appendix**.

## 5 Test Setup Photos

The detailed test data see: **Test Setup Photos**



# Appendix

## DTS Bandwidth Test Result

TestMode	Antenna	Frequency[MHz]	DTS BW [MHz]	FL[MHz]	FH[MHz]	Limit[MHz]	Verdict
11B	Ant1	2412	9.080	2407.440	2416.520	0.5	PASS
11B	Ant1	2437	9.040	2432.480	2441.520	0.5	PASS
11B	Ant1	2462	9.800	2456.960	2466.760	0.5	PASS
11G	Ant1	2412	15.000	2404.440	2419.440	0.5	PASS
11G	Ant1	2437	14.960	2429.520	2444.480	0.5	PASS
11G	Ant1	2462	15.080	2454.440	2469.520	0.5	PASS
11N20SISO	Ant1	2412	14.960	2404.560	2419.520	0.5	PASS
11N20SISO	Ant1	2437	14.040	2429.480	2443.520	0.5	PASS
11N20SISO	Ant1	2462	15.000	2454.480	2469.480	0.5	PASS
11N40SISO	Ant1	2422	32.480	2406.960	2439.440	0.5	PASS
11N40SISO	Ant1	2437	31.440	2421.880	2453.320	0.5	PASS
11N40SISO	Ant1	2452	33.760	2434.480	2468.240	0.5	PASS

## Test Graphs





11G-Ant1-2437-PASS



11G-Ant1-2462-PASS




11N20SISO-Ant1-2412-PASS



11N20SISO-Ant1-2437-PASS






## Occupied Channel Bandwidth

### Test Result

TestMode	Antenna	Channel Frequency[MHz]	OCB [MHz]	FL[MHz]	FH[MHz]	Limit[MHz]	Verdict
11B	Ant1	2412	13.291	2405.3804	2418.6714	---	---
11B	Ant1	2437	13.278	2430.3693	2443.6473	---	---
11B	Ant1	2462	13.294	2455.3363	2468.6303	---	---
11G	Ant1	2412	16.227	2403.8902	2420.1172	---	---
11G	Ant1	2437	16.231	2428.8688	2445.0998	---	---
11G	Ant1	2462	16.227	2453.8620	2470.0890	---	---
11N20SISO	Ant1	2412	17.269	2403.3655	2420.6345	---	---
11N20SISO	Ant1	2437	17.246	2428.3667	2445.6127	---	---
11N20SISO	Ant1	2462	17.263	2453.3702	2470.6332	---	---
11N40SISO	Ant1	2422	35.784	2404.1569	2439.9409	---	---
11N40SISO	Ant1	2437	35.773	2419.1651	2454.9381	---	---
11N40SISO	Ant1	2452	35.793	2434.1050	2469.8980	---	---

## Test Graphs





11G-Ant1-2437



11G-Ant1-2462




11N20SISO-Ant1-2412



11N20SISO-Ant1-2437







**Maximum conducted output power****Test Result Peak**

TestMode	Antenna	Frequency[MHz]	Set Power	Peak Power[dBm]	Conducted Limit[dBm]	EIRP [dBm]	EIRP Limit[dBm]	Verdict
11B	Ant1	2412	16.0	20.764	≤30.00	21.854	≤36.00	PASS
11B	Ant1	2437	16.0	20.809	≤30.00	21.899	≤36.00	PASS
11B	Ant1	2462	16.5	20.743	≤30.00	21.833	≤36.00	PASS
11G	Ant1	2412	14.0	23.583	≤30.00	24.673	≤36.00	PASS
11G	Ant1	2437	14.0	23.390	≤30.00	24.480	≤36.00	PASS
11G	Ant1	2462	14.0	23.225	≤30.00	24.315	≤36.00	PASS
11N20SISO	Ant1	2412	14.0	23.494	≤30.00	24.584	≤36.00	PASS
11N20SISO	Ant1	2437	14.0	23.620	≤30.00	24.710	≤36.00	PASS
11N20SISO	Ant1	2462	14.0	23.175	≤30.00	24.265	≤36.00	PASS
11N40SISO	Ant1	2422	12.5	20.709	≤30.00	21.799	≤36.00	PASS
11N40SISO	Ant1	2437	13.0	20.852	≤30.00	21.942	≤36.00	PASS
11N40SISO	Ant1	2452	13.5	20.390	≤30.00	21.480	≤36.00	PASS


**Test Result Average**


Test Mode	Antenna	Frequency [MHz]	Duty Cycle [%]	DC Factor [dBm]	Result [dBm]	Limit [dBm]	Gain [dBi]	EIRP [dBm]	EIRP Limit [dBm]	Verdict
11B	Ant1	2412	99.67	0.01	18.045	≤30.00	1.09	19.135	≤36.00	PASS
11B	Ant1	2437	99.67	0.01	18.171	≤30.00	1.09	19.261	≤36.00	PASS
11B	Ant1	2462	99.67	0.01	18.040	≤30.00	1.09	19.130	≤36.00	PASS
11G	Ant1	2412	97.58	0.11	16.415	≤30.00	1.09	17.505	≤36.00	PASS
11G	Ant1	2437	97.58	0.11	16.376	≤30.00	1.09	17.466	≤36.00	PASS
11G	Ant1	2462	97.58	0.11	16.185	≤30.00	1.09	17.275	≤36.00	PASS
11N20SISO	Ant1	2412	97.42	0.11	16.188	≤30.00	1.09	17.278	≤36.00	PASS
11N20SISO	Ant1	2437	97.41	0.11	16.316	≤30.00	1.09	17.406	≤36.00	PASS
11N20SISO	Ant1	2462	97.42	0.11	15.857	≤30.00	1.09	16.947	≤36.00	PASS
11N40SISO	Ant1	2422	95.88	0.18	15.203	≤30.00	1.09	16.293	≤36.00	PASS
11N40SISO	Ant1	2437	95.88	0.18	15.175	≤30.00	1.09	16.265	≤36.00	PASS
11N40SISO	Ant1	2452	95.88	0.18	15.032	≤30.00	1.09	16.122	≤36.00	PASS

**Maximum power spectral density****Test Result**


TestMode	Antenna	Frequency[MHz]	Result[dBm/3kHz]	Limit[dBm/3kHz]	Verdict
11B	Ant1	2412	-3.85	≤8.00	PASS
11B	Ant1	2437	-3.99	≤8.00	PASS
11B	Ant1	2462	-4.41	≤8.00	PASS
11G	Ant1	2412	-6.11	≤8.00	PASS
11G	Ant1	2437	-6.49	≤8.00	PASS
11G	Ant1	2462	-6.86	≤8.00	PASS
11N20SISO	Ant1	2412	-6.27	≤8.00	PASS
11N20SISO	Ant1	2437	-5.87	≤8.00	PASS
11N20SISO	Ant1	2462	-7.27	≤8.00	PASS
11N40SISO	Ant1	2422	-10.56	≤8.00	PASS
11N40SISO	Ant1	2437	-9.53	≤8.00	PASS
11N40SISO	Ant1	2452	-9.89	≤8.00	PASS

## Test Graphs







11G-Ant1-2437-PASS





11G-Ant1-2462-PASS




11N20SISO-Ant1-2412-PASS



11N20SISO-Ant1-2437-PASS





**Band edge measurements****Test Result**

TestMode	Antenna	ChName	Frequency[MHz]	RefLevel[dBm]	Result[dBm]	Limit[dBm]	Verdict
11B	Ant1	Low	2412	9.00	-43.6	≤-11.00	PASS
11B	Ant1	High	2462	8.69	-45.46	≤-11.31	PASS
11G	Ant1	Low	2412	7.05	-41.08	≤-12.95	PASS
11G	Ant1	High	2462	6.28	-45.84	≤-13.72	PASS
11N20SISO	Ant1	Low	2412	6.61	-42.43	≤-13.39	PASS
11N20SISO	Ant1	High	2462	6.14	-45.77	≤-13.86	PASS
11N40SISO	Ant1	Low	2422	1.59	-29.3	≤-18.41	PASS
11N40SISO	Ant1	High	2452	2.87	-46.57	≤-17.13	PASS

## Test Graphs

