

TEST REPORT

of

FCC Part 15 Subpart C AND CANADA RSS-210

Full Modular Approval

☒ New Application; ☐ Class I PC; ☐ Class II PC

Product : RW8200 Serial / USB Embedded WiFi Modules

Brand: Radicom

Model: RW8200a, RW8200c, RW8200Ua, RW8200Uc,
RW8200HMa, RW8200HMc, BPM8200a,
BPM8200c

Model Difference: Please see page 7

FCC ID: K7T- RW8200

IC: 2377A- RW8200

FCC Rule Part: §15.247, Cat: DTS

IC Rule Part: RSS-210 issue 8:2010, Annex 8

Applicant: Radicom Research, Inc.

Address: 2148 Bering Drive, San Jose, CA. USA 95131

Test Performed by:
International Standards Laboratory

<Lung-Tan LAB>

*Site Registration No.

BSMI: SL2-IN-E-0013; MRA TW1036; TAF: 0997; IC: IC4067B-3;

*Address:

No. 120, Lane 180, San Ho Tsuen, Hsin Ho Rd.

Lung-Tan Hsiang, Tao Yuan County 325, Taiwan

*Tel : 886-3-407-1718; Fax: 886-3-407-1738

Report No.: ISL-14LR002FCW

Issue Date : 2014/01/28

Test results given in this report apply only to the specific sample(s) tested and are traceable to national or international standard through calibration of the equipment and evaluating measurement uncertainty herein.

This report MUST not be used to claim product endorsement by TAF, NVLAP or any agency of the Government.

This test report shall not be reproduced except in full, without the written approval of International Standards Laboratory.



VERIFICATION OF COMPLIANCE

Applicant: Radicom Research, Inc.
Product Description: RW8200 Serial / USB Embedded WiFi Modules
Brand Name: Radicom
Model No.: RW8200a, RW8200c, RW8200Ua, RW8200Uc,
RW8200HMa, RW8200HMc, BPM8200a, BPM8200c
Model Difference: Please see page 7
FCC ID: K7T- RW8200
IC: 2377A- RW8200
Date of test: 2014/01/03 ~ 2014/01/25
Date of EUT Received: 2014/01/04

We hereby certify that:

All the tests in this report have been performed and recorded in accordance with the standards described above and performed by an independent electromagnetic compatibility consultant, International Standards Laboratory.

The test results contained in this report accurately represent the measurements of the characteristics and the energy generated by sample equipment under test at the time of the test. The sample equipment tested as described in this report is in compliance with the limits of above standards.

Test By:

Dion Chen

Date:

2014/01/28

Dion Chang / Engineer

Prepared By:

Gigi yeh

Date:

2014/01/28

Gigi Yeh / Specialis

Approved By:

Vincent Su

Date:

2014/01/28

Vincent Su / Technical Manager

Version

| Version No. | Date | Description |
|-------------|------------|------------------------------|
| 00 | 2014/01/28 | Initial creation of document |
| | | |
| | | |

Table of Contents

| | | |
|----------|---|-----------|
| 1 | GENERAL INFORMATION | 6 |
| 1.1 | Related Submittal(s) / Grant (s) | 8 |
| 1.2 | Test Methodology | 8 |
| 1.3 | Test Facility | 8 |
| 1.4 | Special Accessories | 8 |
| 1.5 | Equipment Modifications | 8 |
| 2 | SYSTEM TEST CONFIGURATION | 9 |
| 2.1 | EUT Configuration | 9 |
| 2.2 | EUT Exercise | 9 |
| 2.3 | Test Procedure | 9 |
| 2.4 | Configuration of Tested System | 10 |
| 3 | SUMMARY OF TEST RESULTS | 11 |
| 4 | DESCRIPTION OF TEST MODES | 11 |
| 5 | CONDUCTED EMISSION TEST | 12 |
| 5.1 | Standard Applicable: | 12 |
| 5.2 | Measurement Equipment Used: | 12 |
| 5.3 | EUT Setup: | 12 |
| 5.4 | Measurement Procedure: | 13 |
| 5.5 | Measurement Result: | 13 |
| 6 | PEAK OUTPUT POWER MEASUREMENT | 18 |
| 6.1 | Standard Applicable: | 18 |
| 6.2 | Measurement Equipment Used: | 19 |
| 6.3 | Test Set-up: | 19 |
| 6.4 | Measurement Procedure: | 19 |
| 6.5 | Measurement Result: | 20 |
| 7 | 6dB Bandwidth & 99% Bandwidth | 21 |
| 7.1 | Standard Applicable: | 21 |
| 7.2 | Measurement Equipment Used: | 21 |
| 7.3 | Test Set-up: | 21 |
| 7.4 | Measurement Procedure: | 21 |
| 7.5 | Measurement Result: | 22 |
| 8 | 100KHz BANDWIDTH OF BAND EDGES MEASUREMENT | 34 |
| 8.1 | Standard Applicable: | 34 |
| 8.2 | Measurement Equipment Used: | 35 |
| 8.3 | Test SET-UP: | 36 |
| 8.4 | Measurement Procedure: | 37 |
| 8.5 | Field Strength Calculation: | 37 |
| 8.6 | Measurement Result: | 37 |
| 9 | SPURIOUS RADIATED EMISSION TEST | 47 |
| 9.1 | Standard Applicable | 47 |
| 9.2 | Measurement Equipment Used: | 47 |
| 9.3 | Test SET-UP: | 47 |
| 9.4 | Measurement Procedure: | 48 |
| 9.5 | Field Strength Calculation | 48 |
| 9.6 | Measurement Result: | 48 |

| | | |
|-----------|--|------------|
| 10 | Peak Power Spectral Density | 94 |
| 10.1 | Standard Applicable: | 94 |
| 10.2 | Measurement Equipment Used: | 94 |
| 10.3 | Test Set-up: | 94 |
| 10.4 | Measurement Procedure: | 94 |
| 10.5 | Measurement Result: | 95 |
| 11 | ANTENNA REQUIREMENT | 102 |
| 11.1 | Standard Applicable: | 102 |
| 11.2 | Antenna Connected Construction: | 102 |

1 GENERAL INFORMATION

General:

| | |
|-------------------|---|
| Product Name: | RW8200 Serial / USB Embedded WiFi Modules |
| Brand Name: | Radicom |
| Model Name: | RW8200a, RW8200c, RW8200Ua, RW8200Uc, RW8200HMa, RW8200HMc, BPM8200a, BPM8200c |
| Model Difference: | Please see page 7 |
| Power Supply: | 3.3V |

WLAN: 1TX/1RX

| | |
|-----------------------|--|
| Frequency Range: | 802.11b/g/n HT20: 2412 – 2462MHz |
| Channel number: | 802.11b/g/n HT20: 11 channels |
| Transmit Power: | 802.11b: 19.62dBm (Peak) 802.11g: 21.90dBm (Peak) 802.11n HT20: 21.47dBm (Peak) |
| Modulation Technology | 11b/g: DSSS, OFDM 11n: OFDM |
| Modulation type: | CCK, DQPSK, DBPSK for DSSS 64QAM, 16QAM, QPSK, BPSK for OFDM |
| Transition Rate: | 802.11 b: 1/2/5.5/11 Mbps 802.11 g: 6/9/12/18/24/36/48/54 Mbps 802.11 n HT20MHz: 6.5 – 65Mbps |
| Antenna Designation: | 1. Model: RFANT5220110A2T, Chip Antenna, 2dBi. Connector Type: fixed 2. Model: WF2-47-30, Dipole Antenna, 2dBi, Connector Type: unique detachable |
| Type of Emission: | 802.11b/g: 12M5G1D 802.11n HT20: 17M6D1D |





The EUT is compliance with IEEE 802.11 b/g/n Standard.

Remark: The above DUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.

Model difference table:

RW8200 Serial Embedded Wi-Fi Module is based on the latest BCM43362 Wi-Fi chip to design. The RW8200 Serial Module can also be mounted on a carrier board with a dip interface to create a Wi-Fi Serial Through Hole Module Model RB8200HM.

The models without the U have Serial interface. The models with the U have USB interface. The models with c have external antennae and the a have on board antennae

| | Description | Comments |
|--|--|--|
| RW8200a/RW8200Ua/BPM8200a  | WiFi Surface Mount Serial Module with dual on board chip antenna | On board chip antenna |
| RW8200c /RW8200Uc BPM8200c  | WiFi Surface Mount Serial Module with two U.FL Connectors for attaching antenna cables and antenna | Can use either one or two cables and external antenna |
| RW8200HMa  | WiFi Serial Dip (Through Hole) Module with dual on board chip antenna | On board chip antenna |
| RW8200HMc  | WiFi Serial Dip (Through Hole) Module with two U.FL Connectors for attaching antenna cables and antenna | Can use either one or two cables and external antenna |

1.1 Related Submittal(s) / Grant (s)

This submittal(s) (test report) is intended for **FCC ID: K7T- RW8200** filing to comply with Section 15.247 of the FCC Part 15, Subpart C Rules and **IC: 2377A- RW8200** filing to comply with Industry Canada RSS-210 issue 8: 2010 Annex 8.

1.2 Test Methodology

Both conducted and radiated testing were performed according to the procedures in ANSI C63.4-2009 and RSS-Gen: 2010. Radiated testing was performed at an antenna to EUT distance 3 meters.

D01 DTS Meas Guidance v03r01

1.3 Test Facility

The measurement facilities used to collect the 3m Radiated Emission and AC power line conducted data are located on the address of **International Standards Laboratory** <Lung-Tan LAB> No. 120, Lane 180, San Ho Tsuen, Hsin Ho Rd., Lung-Tan Hsiang, Tao Yuan County 325, Taiwan which are constructed and calibrated to meet the FCC requirements in documents ANSI C63.4: 2003. FCC Registration Number is: TW1036, Canada Registration Number: 4067B-3.

1.4 Special Accessories

Not available for this EUT intended for grant.

1.5 Equipment Modifications

Not available for this EUT intended for grant.

2 SYSTEM TEST CONFIGURATION

2.1 EUT Configuration

The EUT configuration for testing is installed on RF field strength measurement to meet the Commissions requirement and operating in a manner which intends to maximize its emission characteristics in a continuous normal application.

2.2 EUT Exercise

The EUT (Transmitter) was operated in the engineering mode to fix the Tx frequency that was for the purpose of the measurements.

2.3 Test Procedure

2.3.1 Conducted Emissions

The EUT is placed on a turn table which is 0.8 m above ground plane. According to the requirements in Section 7 and 13 of ANSI C63.4-2009, conducted emissions from the EUT measured in the frequency range between 0.15 MHz and 30 MHz using CISPR Quasi-Peak and Average detector mode.

2.3.2 Radiated Emissions

The EUT is placed on a turn table which is 0.8 m above ground plane. The turn table shall rotate 360 degrees to determine the position of maximum emission level. EUT is set 3m away from the receiving antenna which varied from 1m to 4m to find out the highest emission. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical. In order to find out the max. emission, the relative positions of this hand-held transmitter(EUT) was rotated through three orthogonal axes according to the requirements in Section 8 and 13 of ANSI C63.4-2009.

2.4 Configuration of Tested System

Fig. 2-1 AC Power line and Radiated Emission Configuration




Table 2-1 Equipment Used in Tested System

| Item | Equipment | Mfr/Brand | Model/ Type No. | Series No. | Data Cable | Power Cord |
|------|-----------|-----------|--------------------|------------|------------|------------|
| 1 | Notebook | Lenovo | X220i | N/A | Shield | Non-shield |

3 SUMMARY OF TEST RESULTS

| FCC Rules | Description Of Test | Result |
|--|--|-----------|
| §15.207(a) RSS-Gen §7.2.4 | AC Power Line Conducted Emission | Compliant |
| §15.247(b) (3),(4) §A8.4(4) | Peak Output Power | Compliant |
| §15.247(a)(2) §A8.2(a) RSS-Gen §4.6.1 | 6dB Bandwidth & 99% Power Bandwidth | Compliant |
| §15.247(d) §A8.5 | 100 KHz Bandwidth Of Frequency Band Edges | Compliant |
| §15.247(d) §A8.5 | Spurious Emission | Compliant |
| §15.247(e) §A8.2(b) & §A8.3(2) | Peak Power Density | Compliant |
| §15.203 RSS-GEN 7.1.2, RSS-210 issue 8,§A8.4 | Antenna Requirement | Compliant |

4 DESCRIPTION OF TEST MODES

The EUT has been tested under engineering operating condition.

Test program used to control the EUT for staying in continuous transmitting mode is programmed.

802.11 b mode: Channel low (2412MHz)、 mid (2437MHz) and high (2462MHz) with 1Mbps lowest data rate are chosen for full testing.

802.11 g mode: Channel low (2412MHz)、 mid (2437MHz) and high (2462MHz) with 6Mbps lowest data rate are chosen for full testing.

802.11 n _20MHz: Channel low (2412MHz)、 mid (2437MHz) and high (2462MHz) with 6.5Mbps lowest data rate are chosen for full testing.

5 CONDUCTED EMISSION TEST

5.1 Standard Applicable:

According to §15.207 and RSS-Gen §7.2.4, frequency range within 150KHz to 30MHz shall not exceed the Limit table as below.

| Frequency range MHz | Limits dB(uV) | |
|---|------------------|----------|
| | Quasi-peak | Average |
| 0.15 to 0.50 | 66 to 56 | 56 to 46 |
| 0.50 to 5 | 56 | 46 |
| 5 to 30 | 60 | 50 |
| Note | | |
| 1.The lower limit shall apply at the transition frequencies | | |
| 2.The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.50 MHz. | | |

5.2 Measurement Equipment Used:

| AC Power Line Test Site | | | | | |
|--------------------------|--------------------|-----------------|---------------------|--------------|------------|
| EQUIPMENT TYPE | MFR | MODEL NUMBER | SERIAL NUMBER | LAST CAL. | CAL DUE. |
| Conduction 04-1 Cable | WOKEN | CFD 300-NL | Conduction 04 -1 | 09/24/2013 | 09/23/2014 |
| EMI Receiver 16 | Rohde & Schwarz | ESCI | 101221 | 06/13/2013 | 06/12/2014 |
| LISN 18 | ROHDE & SCHWARZ | ENV216 | 101424 | 03/13/2013 | 03/12/2014 |
| LISN 19 | ROHDE & SCHWARZ | ENV216 | 101425 | 03/13/2013 | 03/12/2014 |

5.3 EUT Setup:

1. The conducted emission tests were performed in the test site, using the setup in accordance with the ANSI C63.4-2009.
2. The module itself is connected to PC, and then to LISN. The EUT was placed flushed with the rear of the table.
3. The LISN was connected with 120Vac/60Hz power source.

5.4 Measurement Procedure:

1. The EUT was placed on a table which is 0.8m above ground plane.
2. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
3. Repeat above procedures until all frequency measured were complete.


5.5 Measurement Result:

The initial step in collecting conducted data is a spectrum analyzer peak scan of the measurement range. Significant peaks are then marked as shown on the following data page, and these signals are then quasi-peaked.

Note: Refer to next page for measurement data and plots.

AC POWER LINE CONDUCTED EMISSION TEST DATA

| | | | |
|-----------------|-------------------------------|------------|------------|
| Operation Mode: | Operation Mode (Chip Antenna) | Test Date: | 2014/01/16 |
| Test By: | Lake | | |



Site Conduction 04

Phase: **L1**

Temperature: 26 °C


Condition : Conduction

Humidity: 54 %

| No. | Freq. | Reading_Level (dBuV) | | | Correct Factor (dB) | Measurement (dBuV) | | | Limit (dBuV) | | Margin (dB) | | | |
|-----|---------|-------------------------|-------|-------|---------------------------|-----------------------|-------|-------|-----------------|-------|----------------|--------|-----|-----|
| | | MHz | Peak | QP | | AVG | peak | QP | AVG | P/Q | AVG | P/Q | AVG | P/F |
| 1 | 0.1740 | 36.03 | 32.22 | 16.06 | 9.62 | 45.65 | 41.84 | 25.68 | 64.77 | 54.77 | -22.93 | -29.09 | | |
| 2 | 0.2140 | 30.45 | 26.17 | 11.90 | 9.62 | 40.07 | 35.79 | 21.52 | 63.05 | 53.05 | -27.26 | -31.53 | | |
| 3 | 0.5220 | 24.28 | 21.82 | 15.71 | 9.63 | 33.91 | 31.45 | 25.34 | 56.00 | 46.00 | -24.55 | -20.66 | | |
| 4 | 2.7940 | 29.59 | 23.22 | 17.18 | 9.65 | 39.24 | 32.87 | 26.83 | 56.00 | 46.00 | -23.13 | -19.17 | | |
| 5 * | 3.1300 | 30.24 | 26.69 | 19.45 | 9.67 | 39.91 | 36.36 | 29.12 | 56.00 | 46.00 | -19.64 | -16.88 | | |
| 6 | 18.4820 | 28.25 | 21.46 | 15.00 | 9.81 | 38.06 | 31.27 | 24.81 | 60.00 | 50.00 | -28.73 | -25.19 | | |

Date: 2014/1/16

Operator: Lake Cheng



Site: Conduction 04

Phase: N

Temperature: 26 °C


Condition: Conduction

Humidity: 54 %

| No. | Freq. MHz | Reading_Level (dBuV) | | | Correct Factor (dB) | Measurement (dBuV) | | | Limit (dBuV) | | Margin (dB) | | P/F | Comment |
|-----|--------------|-------------------------|-------|-------|---------------------------|-----------------------|-------|-------|-----------------|-------|----------------|--------|-----|---------|
| | | Peak | QP | AVG | | peak | QP | AVG | P/Q | AVG | P/Q | AVG | | |
| 1 | 0.1540 | 38.06 | 34.27 | 17.04 | 9.60 | 47.66 | 43.87 | 26.64 | 65.78 | 55.78 | -21.91 | -29.14 | | |
| 2 | 0.1980 | 33.27 | 27.25 | 11.16 | 9.59 | 42.86 | 36.84 | 20.75 | 63.69 | 53.69 | -26.85 | -32.94 | | |
| 3 | 0.5580 | 26.19 | 21.21 | 15.61 | 9.60 | 35.79 | 30.81 | 25.21 | 56.00 | 46.00 | -25.19 | -20.79 | | |
| 4 * | 3.0460 | 29.35 | 23.24 | 17.29 | 9.65 | 39.00 | 32.89 | 26.94 | 56.00 | 46.00 | -23.11 | -19.06 | | |
| 5 | 3.6900 | 27.97 | 20.63 | 14.00 | 9.65 | 37.62 | 30.28 | 23.65 | 56.00 | 46.00 | -25.72 | -22.35 | | |
| 6 | 19.5700 | 27.41 | 20.31 | 10.06 | 9.92 | 37.33 | 30.23 | 19.98 | 60.00 | 50.00 | -29.77 | -30.02 | | |

AC POWER LINE CONDUCTED EMISSION TEST DATA

| | | | |
|-----------------|---------------------------------|------------|------------|
| Operation Mode: | Operation Mode (Dipole Antenna) | Test Date: | 2014/01/16 |
| Test By: | Lake | | |



Site Conduction 04

Phase: **L1**

Temperature: 26 °C


Condition : Conduction

Humidity: 54 %

| No. | Freq. MHz | Reading_Level (dBuV) | | | Correct Factor (dB) | Measurement (dBuV) | | | Limit (dBuV) | | Margin (dB) | | P/F | Comment |
|-----|--------------|-------------------------|-------|-------|---------------------------|-----------------------|-------|-------|-----------------|-------|----------------|--------|-----|---------|
| | | Peak | QP | AVG | | peak | QP | AVG | P/Q | AVG | P/Q | AVG | | |
| 1 | 0.1620 | 36.14 | 33.02 | 15.72 | 9.62 | 45.76 | 42.64 | 25.34 | 65.36 | 55.36 | -22.72 | -30.02 | | |
| 2 | 0.1860 | 30.86 | 24.83 | 10.57 | 9.62 | 40.48 | 34.45 | 20.19 | 64.21 | 54.21 | -29.76 | -34.02 | | |
| 3 * | 0.5380 | 25.17 | 21.98 | 16.93 | 9.63 | 34.80 | 31.61 | 26.56 | 56.00 | 46.00 | -24.39 | -19.44 | | |
| 4 | 2.0420 | 25.19 | 18.08 | 12.54 | 9.65 | 34.84 | 27.73 | 22.19 | 56.00 | 46.00 | -28.27 | -23.81 | | |
| 5 | 2.8540 | 27.98 | 21.00 | 13.77 | 9.65 | 37.63 | 30.65 | 23.42 | 56.00 | 46.00 | -25.35 | -22.58 | | |
| 6 | 18.5540 | 27.46 | 20.37 | 13.81 | 9.81 | 37.27 | 30.18 | 23.62 | 60.00 | 50.00 | -29.82 | -26.38 | | |

Date: 2014/1/16

Operator: Lake Cheng



Site Conduction 04

Phase: **N**

Temperature: 26 °C

Condition : Conduction

Humidity: 54 %

| No. | Freq. MHz | Reading_Level (dBuV) | | | Correct Factor (dB) | Measurement (dBuV) | | | Limit (dBuV) | | Margin (dB) | | P/F | Comment |
|-----|--------------|-------------------------|-------|-------|---------------------------|-----------------------|-------|-------|-----------------|-------|----------------|--------|-----|---------|
| | | Peak | QP | AVG | | peak | QP | AVG | P/Q | AVG | P/Q | AVG | | |
| 1 | 0.1620 | 36.46 | 33.21 | 16.62 | 9.60 | 46.06 | 42.81 | 26.22 | 65.36 | 55.36 | -22.55 | -29.14 | | |
| 2 | 0.1780 | 35.07 | 28.62 | 11.69 | 9.59 | 44.66 | 38.21 | 21.28 | 64.58 | 54.58 | -26.37 | -33.30 | | |
| 3 | 0.5780 | 24.84 | 21.11 | 15.64 | 9.60 | 34.44 | 30.71 | 25.24 | 56.00 | 46.00 | -25.29 | -20.76 | | |
| 4 * | 2.6980 | 27.03 | 23.03 | 17.51 | 9.63 | 36.66 | 32.66 | 27.14 | 56.00 | 46.00 | -23.34 | -18.86 | | |
| 5 | 3.2900 | 28.05 | 22.53 | 16.10 | 9.65 | 37.70 | 32.18 | 25.75 | 56.00 | 46.00 | -23.82 | -20.25 | | |
| 6 | 19.6020 | 26.62 | 19.90 | 9.91 | 9.92 | 36.54 | 29.82 | 19.83 | 60.00 | 50.00 | -30.18 | -30.17 | | |

6 PEAK OUTPUT POWER MEASUREMENT

6.1 Standard Applicable:

According to §15.247(b)(3),(4)(b)

(3) For systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt. As an alternative to a peak power measurement, compliance with the one Watt limit can be based on a measurement of the maximum conducted output power. Maximum Conducted Output Power is defined as the total transmit power delivered to all antennas and antenna elements averaged across all symbols in the signaling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements. The average must not include any time intervals during which the transmitter is off or is transmitting at a reduced power level. If multiple modes of operation are possible (e.g., alternative modulation methods), the maximum conducted output power is the highest total transmit power occurring in any mode.

(4) The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

(c) Operation with directional antenna gains greater than 6 dBi.

(1) Fixed point-to-point operation:

(i) Systems operating in the 2400-2483.5 MHz band that are used exclusively for fixed, point-to-point operations may employ transmitting antennas with directional gain greater than 6 dBi provided the maximum conducted output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6 dBi.


(ii) Systems operating in the 5725-5850 MHz band that are used exclusively for fixed, point-to-point operations may employ transmitting antennas with directional gain greater than 6 dBi without any corresponding reduction in transmitter conducted output power.

According to RSS-210 issue 8, §A8.4(4), For systems employing digital modulation techniques operating in the bands 902-928 MHz, 2400-2483.5 MHz and 5725-5850 MHz, the maximum peak conducted output power shall not exceed 1 W. Except as provided in Section A8.4(5), the e.i.r.p. shall not exceed 4 W.

6.2 Measurement Equipment Used:

| Conducted Emission Test Site | | | | | |
|------------------------------|---------|--------------|----------------|------------|------------|
| EQUIPMENT TYPE | MFR | MODEL NUMBER | SERIAL NUMBER | LAST CAL. | CAL DUE. |
| Power Meter 05 | Anritsu | ML2495A | 1116010 | 04/19/2013 | 04/18/2014 |
| Power Sensor 05 | Anritsu | MA2411B | 34NKF50 | 04/19/2013 | 04/18/2014 |
| Power Sensor 06 | DARE | RPR3006W | 13I00030SN O33 | 10/18/2013 | 10/17/2014 |
| Power Meter 07 | DARE | RPR3006W | 13I00030SN O34 | 10/18/2013 | 10/17/2014 |
| Temperature Chamber | KSON | THS-B4H100 | 2287 | 03/15/2013 | 03/14/2014 |
| DC Power supply | ABM | 51850 | N/A | 08/16/2013 | 08/15/2014 |
| AC Power supply | EXTECH | CFC105W | NA | 12/19/2013 | 12/18/2014 |
| Attenuator | Woken | Watt-65m3502 | 11051601 | NA | NA |
| Splitter | MCLI | PS4-199 | 12465 | 12/27/2013 | 12/26/2014 |
| Spectrum analyzer | Agilent | N9030A | MY51360021 | 03/29/2013 | 03/28/2014 |

6.3 Test Set-up:



6.4 Measurement Procedure:

1. Place the EUT on the table and set it in transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the power meter
3. Record the max. reading.
4. Repeat above procedures until all frequency measured were complete.

6.5 Measurement Result:

802.11b

| Cable loss = 0 | | Output Power | | Limit (dBm) |
|----------------|--------------------|--------------|-------------|----------------|
| CH | Frequency (MHz) | Detector | | |
| | | PK (dBm) | AV (dBm) | |
| 1 | 2412 | 19.62 | 16.95 | 30 |
| 6 | 2437 | 19.23 | 16.57 | |
| 11 | 2462 | 19.13 | 16.34 | |

802.11g

| Cable loss = 0 | | Output Power | | Limit (dBm) |
|----------------|--------------------|--------------|-------------|----------------|
| CH | Frequency (MHz) | Detector | | |
| | | PK (dBm) | AV (dBm) | |
| 1 | 2412 | 21.90 | 12.48 | 30 |
| 6 | 2437 | 21.76 | 12.37 | |
| 11 | 2462 | 21.86 | 12.03 | |

802.11N 20MHz

| Cable loss = 0 | | Output Power | | Limit (dBm) |
|----------------|--------------------|--------------|-------------|----------------|
| CH | Frequency (MHz) | Detector | | |
| | | PK (dBm) | AV (dBm) | |
| 1 | 2412 | 21.47 | 11.26 | 30 |
| 6 | 2437 | 21.23 | 11.05 | |
| 11 | 2462 | 21.13 | 10.95 | |

7 6dB Bandwidth & 99% Bandwidth

7.1 Standard Applicable:

According to §15.247(a)(2), Systems using digital modulation techniques may operate in the 902 - 928 MHz, 2400 - 2483.5 MHz, and 5725 - 5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500kHz.

According to RSS 210 issue 8, §8.2(a) Systems employing digital modulation techniques (which includes direct sequence) can now be certified under RSS-210 provided they comply with the following requirements: The minimum -6 dB bandwidth shall be at least 500 kHz.

7.2 Measurement Equipment Used:

Refer to section 6.2 for details.

7.3 Test Set-up:

Refer to section 6.3 for details.

7.4 Measurement Procedure:

1. Place the EUT on the table and set it in transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.
3. Set the spectrum analyzer as RBW=100KHz, VBW = 3*RBW, Span= cover the complete power envelope of the signal of the UUT Sweep=auto
4. Mark the peak frequency and -6dB (upper and lower) frequency.
5. Repeat above procedures until all frequency measured were complete.

7.5 Measurement Result:

802.11b

| Frequency (MHz) | 6dB Bandwidth (MHz) | 99% Bandwidth (MHz) | Bandwidth (KHz) | Result |
|-----------------|---------------------|---------------------|-----------------|--------|
| 2412 | 8.49 | 12.471 | > 500 | PASS |
| 2437 | 7.80 | 12.536 | > 500 | PASS |
| 2462 | 7.81 | 12.542 | > 500 | PASS |

802.11g

| Frequency (MHz) | 6dB Bandwidth (MHz) | 99% Bandwidth (MHz) | Bandwidth (KHz) | Result |
|-----------------|---------------------|---------------------|-----------------|--------|
| 2412 | 15.80 | 16.496 | > 500 | PASS |
| 2437 | 15.77 | 16.521 | > 500 | PASS |
| 2462 | 16.02 | 16.514 | > 500 | PASS |

802.11n_20M


| Frequency (MHz) | 6dB Bandwidth (MHz) | 99% Bandwidth (MHz) | Bandwidth (KHz) | Result |
|-----------------|---------------------|---------------------|-----------------|--------|
| 2412 | 16.70 | 17.585 | > 500 | PASS |
| 2437 | 17.27 | 17.586 | > 500 | PASS |
| 2462 | 17.28 | 17.583 | > 500 | PASS |

offset 10dB


Note: Refer to next page for plots.

802.11b


6dB Band Width Test Data CH-Low



6dB Band Width Test Data CH-Mid




6dB Band Width Test Data CH-High




802.11g


6dB Band Width Test Data CH-Low



6dB Band Width Test Data CH-Mid




6dB Band Width Test Data CH-High




802.11n_20M


6dB Band Width Test Data CH-Low



6dB Band Width Test Data CH-Mid



6dB Band Width Test Data CH-High



802.11b


99% Band Width Test Data CH-Low



99% Band Width Test Data CH-Mid




99% Band Width Test Data CH-High




802.11g


99% Band Width Test Data CH-Low



99% Band Width Test Data CH-Mid



99% Band Width Test Data CH-High



802.11n_20M


99% Band Width Test Data CH-Low



99% Band Width Test Data CH-Mid



99% Band Width Test Data CH-High



8 100KHz BANDWIDTH OF BAND EDGES MEASUREMENT

8.1 Standard Applicable:

According to §15.247(c), in any 100 KHz bandwidth outside the frequency bands in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100KHz bandwidth within the band that contains the highest level of the desired power. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a).

According to RSS-210 issue 8, §A8.5, In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated device is operating, the radio frequency power that is produced shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under section A8.4(4), the attenuation required shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in Tables 2 and 3 is not required. In addition, radiated emissions which fall in the restricted bands of Table 1 must also comply with the radiated emission limits specified in Tables 2 and 3.

8.2 Measurement Equipment Used:

8.2.1 Conducted Emission at antenna port:

Refer to section 6.2 for details.

8.2.2 Radiated emission:

| Chamber 14(966) | | | | | |
|-------------------------------|---------------|--------------------------|-----------------|------------|------------|
| EQUIPMENT TYPE | MFR | MODEL NUMBER | SERIAL NUMBER | LAST CAL. | CAL DUE. |
| Spectrum Analyzer 21(26.5GHz) | Agilent | N9010A | MY49060537 | 07/18/2013 | 07/17/2014 |
| Spectrum Analyzer 20(6.5GHz) | Agilent | E4443A | MY48250315 | 05/26/2013 | 05/25/2014 |
| Spectrum Analyzer 22(43GHz) | R&S | FSU43 | 100143 | 05/03/2013 | 05/02/2014 |
| Dipole antenna | SCHWARZBECK | VHAP,30-300 | 919 | 12/03/2013 | 12/02/2014 |
| Dipole antenna | SCHWARZBECK | UHAP,300-1000 | 1195 | 12/03/2013 | 12/02/2014 |
| Loop Antenna9K-30M | A.H.SYSTEM | SAS-564 | 294 | 03/07/2013 | 03/06/2015 |
| Bilog Antenna30-1G | Schaffner | CBL 6112B | 2756 | 01/15/2014 | 01/14/2015 |
| Horn antenna1-18G(06) | EMCO | 3117 | 0006665 | 11/04/2013 | 11/03/2014 |
| Horn antenna26-40G(05) | Com-power | AH-640 | 100A | 01/09/2013 | 01/08/2015 |
| Horn antenna18-26G(04) | Com-power | AH-826 | 081001 | 05/15/2013 | 05/14/2015 |
| Preamplifier9-1000M | HP | 8447D | NA | 02/19/2013 | 02/18/2014 |
| Preamplifier1-18G | MITEQ | AFS44-00101800-25-10P-44 | 1329256 | 07/18/2013 | 07/17/2014 |
| Preamplifier1-26G | EM | EM01M26G | NA | 02/26/2013 | 02/25/2014 |
| Preamplifier26-40G | MITEQ | JS-26004000-27-5A | 818471 | 05/08/2013 | 05/07/2015 |
| Cable1-18G | HUBER SUHNER | Sucoflex 106 | NA | 02/06/2013 | 02/05/2014 |
| Cable UP to 1G | HUBER SUHNER | RG 214/U | NA | 10/08/2013 | 10/07/2014 |
| SUCOFLEX 1GHz~40GHz cable | HUBER SUHNER | Sucoflex 102 | 27963/2&37421/2 | 10/03/2013 | 10/02/2015 |
| Signal Generator | R&S | SMU200A | 102330 | 02/19/2013 | 02/18/2014 |
| Signal Generator | Anritsu | MG3692A | 20311 | 10/30/2013 | 10/29/2014 |
| 2.4G Filter | Micro-Tronics | Brm50702 | 76 | 12/27/2013 | 12/26/2014 |


8.3 Test SET-UP:

8.3.1 Conducted Emission at antenna port:


Refer to section 6.3 for details.

8.3.2 Radiated emission:

(A) Radiated Emission Test Set-Up, Frequency Below 1000MHz



(B) Radiated Emission Test Set-UP Frequency Over 1 GHz



8.4 Measurement Procedure:

1. Place the EUT on the table and set it in transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.
3. Set center frequency of spectrum analyzer = operating frequency.
4. Set the spectrum analyzer as RBW, VBW=100KHz, Span=25MHz, Sweep = auto
5. Mark Peak, 2.390GHz and 2.4835GHz and record the max. level.
6. Repeat above procedures until all frequency measured were complete.

8.5 Field Strength Calculation:

The field strength is calculated by adding the Antenna Factor and Cable Factor and subtracting the Amplifier Gain and Duty Cycle Correction Factor(if any) from the measured reading. The basic equation with a sample calculation is as follows:

$$FS = RA + AF + CL - AG$$

| | | |
|-------|------------------------|--|
| Where | FS = Field Strength | CL = Cable Attenuation Factor (Cable Loss) |
| | RA = Reading Amplitude | AG = Amplifier Gain |
| | AF = Antenna Factor | |

8.6 Measurement Result:

Note: Refer to next page spectrum analyzer data chart and tabular data sheets.

802.11b

Band Edges Test Data CH-Low



Band Edges Test Data CH-High



Radiated Emission: 802.11 b mode (Chip antenna)

Operation Mode TX CH Low
Fundamental Frequency 2412 MHz
Temperature 25

Test Date 2014/01/08
Test By Lake
Humidity 60 %

| No | Freq MHz | Reading dBuV | Factor dB | Level dBuV/m | Limit dBuV/m | Over Limit dB | Remark | Pol V/H |
|----|-------------|-----------------|--------------|-----------------|-----------------|---------------------|---------|------------|
| 1 | 2367.46 | 15.30 | 31.36 | 46.66 | 54.00 | -7.34 | Average | VERTICAL |
| 2 | 2367.46 | 29.31 | 31.36 | 60.67 | 74.00 | -13.33 | Peak | VERTICAL |
| 3 | 2390.00 | 15.79 | 31.40 | 47.19 | 54.00 | -6.81 | Average | VERTICAL |
| 4 | 2390.00 | 28.40 | 31.40 | 59.80 | 74.00 | -14.20 | Peak | VERTICAL |
| | | | | | | | | |
| 1 | 2385.04 | 15.89 | 31.39 | 47.28 | 54.00 | -6.72 | Average | HORIZONTAL |
| 2 | 2385.04 | 28.93 | 31.39 | 60.32 | 74.00 | -13.68 | Peak | HORIZONTAL |
| 3 | 2390.00 | 16.32 | 31.40 | 47.72 | 54.00 | -6.28 | Average | HORIZONTAL |
| 4 | 2390.00 | 27.54 | 31.40 | 58.94 | 74.00 | -15.06 | Peak | HORIZONTAL |

Operation Mode TX CH High
Fundamental Frequency 2462 MHz
Temperature 25

Test Date 2014/01/08
Test By Lake
Humidity 60 %

| No | Freq MHz | Reading dBuV | Factor dB | Level dBuV/m | Limit dBuV/m | Over Limit dB | Remark | Pol V/H |
|----|-------------|-----------------|--------------|-----------------|-----------------|---------------------|---------|------------|
| 1 | 2483.50 | 15.84 | 31.56 | 47.40 | 54.00 | -6.60 | Average | VERTICAL |
| 2 | 2483.50 | 26.82 | 31.56 | 58.38 | 74.00 | -15.62 | Peak | VERTICAL |
| 3 | 2485.36 | 15.34 | 31.56 | 46.90 | 54.00 | -7.10 | Average | VERTICAL |
| 4 | 2485.36 | 28.77 | 31.56 | 60.33 | 74.00 | -13.67 | Peak | VERTICAL |
| | | | | | | | | |
| 1 | 2483.50 | 15.97 | 31.56 | 47.53 | 54.00 | -6.47 | Average | HORIZONTAL |
| 2 | 2483.50 | 27.20 | 31.56 | 58.76 | 74.00 | -15.24 | Peak | HORIZONTAL |
| 3 | 2488.48 | 15.89 | 31.56 | 47.45 | 54.00 | -6.55 | Average | HORIZONTAL |
| 4 | 2488.48 | 29.46 | 31.56 | 61.02 | 74.00 | -12.98 | Peak | HORIZONTAL |

Remark:

- 1 Measuring frequencies from the lowest internal frequency to the 10th of fundamental frequency
- 2 Field strength limits for frequency above 1000MHz are based on average limits. However, Peak mode field strength shall not exceed the average limits specified plus 20dB.
- 3 Measurement of data within this frequency range shown “ - ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- 4 Spectrum Peak mode IF bandwidth Setting : 1GHz- 26GHz, RBW= 1MHz, Sweep time= 200 ms., the VBW setting was 3 MHz.
- 5 Spectrum AV mode if bandwidth Setting : 1GHz- 26GHz, RBW= 1MHz, VBW= 10Hz, Sweep time= 200 ms.

Radiated Emission: 802.11 b mode (Dipole antenna)

Operation Mode TX CH Low
Fundamental Frequency 2412 MHz
Temperature 25

Test Date 2014/01/08
Test By Lake
Humidity 60 %

| No | Freq MHz | Reading dBuV | Factor dB | Level dBuV/m | Limit dBuV/m | Over Limit dB | Remark | Pol V/H |
|----|-------------|-----------------|--------------|-----------------|-----------------|---------------------|---------|------------|
| 1 | 2385.82 | 18.09 | 31.39 | 49.48 | 54.00 | -4.52 | Average | VERTICAL |
| 2 | 2385.82 | 29.55 | 31.39 | 60.94 | 74.00 | -13.06 | Peak | VERTICAL |
| 3 | 2390.00 | 18.27 | 31.40 | 49.67 | 54.00 | -4.33 | Average | VERTICAL |
| 4 | 2390.00 | 29.03 | 31.40 | 60.43 | 74.00 | -13.57 | Peak | VERTICAL |
| | | | | | | | | |
| 1 | 2382.13 | 15.11 | 31.39 | 46.50 | 54.00 | -7.50 | Average | HORIZONTAL |
| 2 | 2382.13 | 28.81 | 31.39 | 60.20 | 74.00 | -13.80 | Peak | HORIZONTAL |
| 3 | 2390.00 | 15.41 | 31.40 | 46.81 | 54.00 | -7.19 | Average | HORIZONTAL |
| 4 | 2390.00 | 26.85 | 31.40 | 58.25 | 74.00 | -15.75 | Peak | HORIZONTAL |

Operation Mode TX CH High
Fundamental Frequency 2462 MHz
Temperature 25

Test Date 2014/01/08
Test By Lake
Humidity 60 %

| No | Freq MHz | Reading dBuV | Factor dB | Level dBuV/m | Limit dBuV/m | Over Limit dB | Remark | Pol V/H |
|----|-------------|-----------------|--------------|-----------------|-----------------|---------------------|---------|------------|
| 1 | 2483.50 | 17.55 | 31.56 | 49.11 | 54.00 | -4.89 | Average | VERTICAL |
| 2 | 2483.50 | 29.19 | 31.56 | 60.75 | 74.00 | -13.25 | Peak | VERTICAL |
| 3 | 2488.19 | 17.11 | 31.56 | 48.67 | 54.00 | -5.33 | Average | VERTICAL |
| 4 | 2488.19 | 29.75 | 31.56 | 61.31 | 74.00 | -12.69 | Peak | VERTICAL |
| | | | | | | | | |
| 1 | 2483.50 | 15.43 | 31.56 | 46.99 | 54.00 | -7.01 | Average | HORIZONTAL |
| 2 | 2483.50 | 26.32 | 31.56 | 57.88 | 74.00 | -16.12 | Peak | HORIZONTAL |
| 3 | 2497.74 | 14.88 | 31.58 | 46.46 | 54.00 | -7.54 | Average | HORIZONTAL |
| 4 | 2497.74 | 28.77 | 31.58 | 60.35 | 74.00 | -13.65 | Peak | HORIZONTAL |

Remark:

- 1 Measuring frequencies from the lowest internal frequency to the 10th of fundamental frequency
- 2 Field strength limits for frequency above 1000MHz are based on average limits. However, Peak mode field strength shall not exceed the average limits specified plus 20dB.
- 3 Measurement of data within this frequency range shown “ - ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- 4 Spectrum Peak mode IF bandwidth Setting : 1GHz- 26GHz, RBW= 1MHz, Sweep time= 200 ms., the VBW setting was 3 MHz.
- 5 Spectrum AV mode if bandwidth Setting : 1GHz- 26GHz, RBW= 1MHz, VBW= 10Hz, Sweep time= 200 ms.

802.11g

Band Edges Test Data CH-Low



Band Edges Test Data CH-High



Radiated Emission: 802.11 g mode (Chip Antenna)

Operation Mode TX CH Low
Fundamental Frequency 2412 MHz
Temperature 25

Test Date 2014/01/08
Test By Lake
Humidity 60 %

| No | Freq MHz | Reading dBuV | Factor dB | Level dBuV/m | Limit dBuV/m | Over Limit dB | Remark | Pol V/H |
|----|-------------|-----------------|--------------|-----------------|-----------------|---------------------|---------|------------|
| 1 | 2390.00 | 16.77 | 31.40 | 48.17 | 54.00 | -5.83 | Average | VERTICAL |
| 2 | 2390.00 | 30.05 | 31.40 | 61.45 | 74.00 | -12.55 | Peak | VERTICAL |
| | | | | | | | | |
| 1 | 2389.41 | 17.10 | 31.39 | 48.49 | 54.00 | -5.51 | Average | HORIZONTAL |
| 2 | 2389.41 | 31.26 | 31.39 | 62.65 | 74.00 | -11.35 | Peak | HORIZONTAL |
| 3 | 2390.00 | 17.93 | 31.40 | 49.33 | 54.00 | -4.67 | Average | HORIZONTAL |
| 4 | 2390.00 | 30.72 | 31.40 | 62.12 | 74.00 | -11.88 | Peak | HORIZONTAL |

Operation Mode TX CH High
Fundamental Frequency 2462 MHz
Temperature 25

Test Date 2014/01/08
Test By Lake
Humidity 60 %

| No | Freq MHz | Reading dBuV | Factor dB | Level dBuV/m | Limit dBuV/m | Over Limit dB | Remark | Pol V/H |
|----|-------------|-----------------|--------------|-----------------|-----------------|---------------------|---------|------------|
| 1 | 2483.50 | 16.35 | 31.56 | 47.91 | 54.00 | -6.09 | Average | VERTICAL |
| 2 | 2483.50 | 29.03 | 31.56 | 60.59 | 74.00 | -13.41 | Peak | VERTICAL |
| | | | | | | | | |
| 1 | 2483.50 | 16.81 | 31.56 | 48.37 | 54.00 | -5.63 | Average | HORIZONTAL |
| 2 | 2483.50 | 29.36 | 31.56 | 60.92 | 74.00 | -13.08 | Peak | HORIZONTAL |

Remark:

- 1 Measuring frequencies from the lowest internal frequency to the 10th of fundamental frequency
- 2 Field strength limits for frequency above 1000MHz are based on average limits. However, Peak mode field strength shall not exceed the average limits specified plus 20dB.
- 3 Measurement of data within this frequency range shown “ - ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- 4 Spectrum Peak mode IF bandwidth Setting : 1GHz- 26GHz, RBW= 1MHz, Sweep time= 200 ms., the VBW setting was 3 MHz.
- 5 Spectrum AV mode if bandwidth Setting : 1GHz- 26GHz, RBW= 1MHz, VBW= 10Hz, Sweep time= 200 ms.

Radiated Emission: 802.11 g mode (Dipole Antenna)

Operation Mode TX CH Low
Fundamental Frequency 2412 MHz
Temperature 25

Test Date 2014/01/08
Test By Lake
Humidity 60 %

| No | Freq MHz | Reading dBuV | Factor dB | Level dBuV/m | Limit dBuV/m | Over Limit dB | Remark | Pol V/H |
|----|-------------|-----------------|--------------|-----------------|-----------------|---------------------|---------|------------|
| 1 | 2389.63 | 19.55 | 31.39 | 50.94 | 54.00 | -3.06 | Average | VERTICAL |
| 2 | 2389.63 | 33.72 | 31.39 | 65.11 | 74.00 | -8.89 | Peak | VERTICAL |
| 3 | 2390.00 | 20.34 | 31.40 | 51.74 | 54.00 | -2.26 | Average | VERTICAL |
| 4 | 2390.00 | 32.99 | 31.40 | 64.39 | 74.00 | -9.61 | Peak | VERTICAL |
| | | | | | | | | |
| 1 | 2373.39 | 15.25 | 31.37 | 46.62 | 54.00 | -7.38 | Average | HORIZONTAL |
| 2 | 2373.39 | 28.56 | 31.37 | 59.93 | 74.00 | -14.07 | Peak | HORIZONTAL |
| 3 | 2390.00 | 16.35 | 31.40 | 47.75 | 54.00 | -6.25 | Average | HORIZONTAL |
| 4 | 2390.00 | 26.91 | 31.40 | 58.31 | 74.00 | -15.69 | Peak | HORIZONTAL |

Operation Mode TX CH High
Fundamental Frequency 2462 MHz
Temperature 25

Test Date 2014/01/08
Test By Lake
Humidity 60 %

| No | Freq MHz | Reading dBuV | Factor dB | Level dBuV/m | Limit dBuV/m | Over Limit dB | Remark | Pol V/H |
|----|-------------|-----------------|--------------|-----------------|-----------------|---------------------|---------|------------|
| 1 | 2483.50 | 18.53 | 31.56 | 50.09 | 54.00 | -3.91 | Average | VERTICAL |
| 2 | 2483.50 | 34.02 | 31.56 | 65.58 | 74.00 | -8.42 | Peak | VERTICAL |
| | | | | | | | | |
| 1 | 2483.50 | 15.86 | 31.56 | 47.42 | 54.00 | -6.58 | Average | HORIZONTAL |
| 2 | 2483.50 | 26.90 | 31.56 | 58.46 | 74.00 | -15.54 | Peak | HORIZONTAL |
| 3 | 2490.45 | 15.15 | 31.56 | 46.71 | 54.00 | -7.29 | Average | HORIZONTAL |
| 4 | 2490.45 | 28.78 | 31.56 | 60.34 | 74.00 | -13.66 | Peak | HORIZONTAL |

Remark:

- 1 Measuring frequencies from the lowest internal frequency to the 10th of fundamental frequency
- 2 Field strength limits for frequency above 1000MHz are based on average limits. However, Peak mode field strength shall not exceed the average limits specified plus 20dB.
- 3 Measurement of data within this frequency range shown “ - ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- 4 Spectrum Peak mode IF bandwidth Setting : 1GHz- 26GHz, RBW= 1MHz, Sweep time= 200 ms., the VBW setting was 3 MHz.
- 5 Spectrum AV mode if bandwidth Setting : 1GHz- 26GHz, RBW= 1MHz, VBW= 10Hz, Sweep time= 200 ms.

802.11n_20M

Band Edges Test Data CH-Low



Band Edges Test Data CH-High



Radiated Emission: 802.11 n_20M mode (Chip Antenna)

Operation Mode TX CH Low
Fundamental Frequency 2412 MHz
Temperature 25

Test Date 2014/01/08
Test By Lake
Humidity 60 %

| No | Freq MHz | Reading dBuV | Factor dB | Level dBuV/m | Limit dBuV/m | Over Limit dB | Remark | Pol V/H |
|----|-------------|-----------------|--------------|-----------------|-----------------|---------------------|---------|------------|
| 1 | 2388.62 | 15.73 | 31.39 | 47.12 | 54.00 | -6.88 | Average | VERTICAL |
| 2 | 2388.62 | 29.33 | 31.39 | 60.72 | 74.00 | -13.28 | Peak | VERTICAL |
| 3 | 2390.00 | 16.30 | 31.40 | 47.70 | 54.00 | -6.30 | Average | VERTICAL |
| 4 | 2390.00 | 29.28 | 31.40 | 60.68 | 74.00 | -13.32 | Peak | VERTICAL |
| | | | | | | | | |
| 1 | 2390.00 | 17.40 | 31.40 | 48.80 | 54.00 | -5.20 | Average | HORIZONTAL |
| 2 | 2390.00 | 32.18 | 31.40 | 63.58 | 74.00 | -10.42 | Peak | HORIZONTAL |

Operation Mode TX CH High
Fundamental Frequency 2462 MHz
Temperature 25

Test Date 2014/01/08
Test By Lake
Humidity 60 %

| No | Freq MHz | Reading dBuV | Factor dB | Level dBuV/m | Limit dBuV/m | Over Limit dB | Remark | Pol V/H |
|----|-------------|-----------------|--------------|-----------------|-----------------|---------------------|---------|------------|
| 1 | 2483.50 | 16.43 | 31.56 | 47.99 | 54.00 | -6.01 | Average | VERTICAL |
| 2 | 2483.50 | 29.63 | 31.56 | 61.19 | 74.00 | -12.81 | Peak | VERTICAL |
| | | | | | | | | |
| 1 | 2483.50 | 16.79 | 31.56 | 48.35 | 54.00 | -5.65 | Average | HORIZONTAL |
| 2 | 2483.50 | 30.14 | 31.56 | 61.70 | 74.00 | -12.30 | Peak | HORIZONTAL |

Remark:

- 1 Measuring frequencies from the lowest internal frequency to the 10th of fundamental frequency
- 2 Field strength limits for frequency above 1000MHz are based on average limits. However, Peak mode field strength shall not exceed the average limits specified plus 20dB.
- 3 Measurement of data within this frequency range shown “ - ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- 4 Spectrum Peak mode IF bandwidth Setting : 1GHz- 26GHz, RBW= 1MHz, Sweep time= 200 ms., the VBW setting was 3 MHz.
- 5 Spectrum AV mode if bandwidth Setting : 1GHz- 26GHz, RBW= 1MHz, VBW= 10Hz, Sweep time= 200 ms.

Radiated Emission: 802.11 n_20M mode (Dipole Antenna)

Operation Mode TX CH Low
Fundamental Frequency 2412 MHz
Temperature 25

Test Date 2014/01/08
Test By Lake
Humidity 60 %

| No | Freq MHz | Reading dBuV | Factor dB | Level dBuV/m | Limit dBuV/m | Over Limit dB | Remark | Pol V/H |
|----|-------------|-----------------|--------------|-----------------|-----------------|---------------------|---------|------------|
| 1 | 2389.30 | 17.68 | 31.39 | 49.07 | 54.00 | -4.93 | Average | VERTICAL |
| 2 | 2389.30 | 32.73 | 31.39 | 64.12 | 74.00 | -9.88 | Peak | VERTICAL |
| 3 | 2390.00 | 18.29 | 31.40 | 49.69 | 54.00 | -4.31 | Average | VERTICAL |
| 4 | 2390.00 | 31.78 | 31.40 | 63.18 | 74.00 | -10.82 | Peak | VERTICAL |
| | | | | | | | | |
| 1 | 2381.34 | 15.27 | 31.39 | 46.66 | 54.00 | -7.34 | Average | HORIZONTAL |
| 2 | 2381.34 | 28.90 | 31.39 | 60.29 | 74.00 | -13.71 | Peak | HORIZONTAL |
| 3 | 2390.00 | 15.90 | 31.40 | 47.30 | 54.00 | -6.70 | Average | HORIZONTAL |
| 4 | 2390.00 | 27.65 | 31.40 | 59.05 | 74.00 | -14.95 | Peak | HORIZONTAL |

Operation Mode TX CH High
Fundamental Frequency 2462 MHz
Temperature 25

Test Date 2014/01/08
Test By Lake
Humidity 60 %

| No | Freq MHz | Reading dBuV | Factor dB | Level dBuV/m | Limit dBuV/m | Over Limit dB | Remark | Pol V/H |
|----|-------------|-----------------|--------------|-----------------|-----------------|---------------------|---------|------------|
| 1 | 2483.50 | 18.40 | 31.56 | 49.96 | 54.00 | -4.04 | Average | VERTICAL |
| 2 | 2483.50 | 33.79 | 31.56 | 65.35 | 74.00 | -8.65 | Peak | VERTICAL |
| 3 | 2483.97 | 18.00 | 31.56 | 49.56 | 54.00 | -4.44 | Average | VERTICAL |
| 4 | 2483.97 | 33.90 | 31.56 | 65.46 | 74.00 | -8.54 | Peak | VERTICAL |
| | | | | | | | | |
| 1 | 2483.50 | 15.80 | 31.56 | 47.36 | 54.00 | -6.64 | Average | HORIZONTAL |
| 2 | 2483.50 | 27.05 | 31.56 | 58.61 | 74.00 | -15.39 | Peak | HORIZONTAL |
| 3 | 2495.54 | 15.11 | 31.58 | 46.69 | 54.00 | -7.31 | Average | HORIZONTAL |
| 4 | 2495.54 | 28.26 | 31.58 | 59.84 | 74.00 | -14.16 | Peak | HORIZONTAL |

Remark:

- 1 Measuring frequencies from the lowest internal frequency to the 10th of fundamental frequency
- 2 Field strength limits for frequency above 1000MHz are based on average limits. However, Peak mode field strength shall not exceed the average limits specified plus 20dB.
- 3 Measurement of data within this frequency range shown “ - ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- 4 Spectrum Peak mode IF bandwidth Setting : 1GHz- 26GHz, RBW= 1MHz, Sweep time= 200 ms., the VBW setting was 3 MHz.
- 5 Spectrum AV mode if bandwidth Setting : 1GHz- 26GHz, RBW= 1MHz, VBW= 10Hz, Sweep time= 200 ms.

9 SPURIOUS RADIATED EMISSION TEST

9.1 Standard Applicable

According to §15.247(c), all other emissions outside these bands shall not exceed the general radiated emission limits specified in §15.209(a). And according to §15.33(a)(1), for an intentional radiator operates below 10GHz, the frequency range of measurements: to the tenth harmonic of the highest fundamental frequency or to 40GHz, whichever is lower.

According to RSS-210 issue 8, §A8.5, In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated device is operating, the radio frequency power that is produced shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under section A8.4(4), the attenuation required shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in Tables 2 and 3 is not required. In addition, radiated emissions which fall in the restricted bands of Table 1 must also comply with the radiated emission limits specified in Tables 2 and 3.

9.2 Measurement Equipment Used:

9.2.1 Conducted Emission at antenna port:

Refer to section 6.2 for details.

9.2.2 Radiated emission:

Refer to section 7.2 for details.

9.3 Test SET-UP:

9.3.1 Conducted Emission at antenna port:

Refer to section 6.3 for details.

9.3.2 Radiated emission:

Refer to section 7.3 for details.

9.4 Measurement Procedure:

1. The EUT was placed on a turn table which is 0.8m above ground plane.
2. The turn table shall rotate 360 degrees to determine the position of maximum emission level.
3. EUT is set 3m away from the receiving antenna which varied from 1m to 4m to find out the highest emissions.
4. When measurement procedures for electric field radiated emissions above 1 GHz the EUT measurement is to be made “while keeping the antenna in the ‘cone of radiation’ from that area and pointed at the area both in azimuth and elevation, with polarization oriented for maximum response.” is still within the 3dB illumination BW of the measurement antenna.
5. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
6. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
7. Repeat above procedures until all frequency measured were complete.

9.5 Field Strength Calculation

The field strength is calculated by adding the Antenna Factor and Cable Factor and subtracting the Amplifier Gain and Duty Cycle Correction Factor(if any) from the measured reading. The basic equation with a sample calculation is as follows:


$$FS = RA + AF + CL - AG$$

| | | |
|-------|------------------------|--|
| Where | FS = Field Strength | CL = Cable Attenuation Factor (Cable Loss) |
| | RA = Reading Amplitude | AG = Amplifier Gain |
| | AF = Antenna Factor | |


9.6 Measurement Result:

Note: Refer to next page spectrum analyzer data chart and tabular data sheets.


Conducted Spurious Emission Measurement Result (802.11b) Ch Low 30MHz – 3GHz




Ch Low 3GHz – 26.5GHz




Ch Mid 30MHz – 3GHz




Ch Mid 3GHz – 26.5GHz




Ch High 30MHz – 3GHz




Ch High 3GHz – 26.5GHz




Conducted Spurious Emission Measurement Result (802.11g) Ch Low 30MHz – 3GHz




Ch Low 3GHz – 26.5GHz




Ch Mid 30MHz – 3GHz




Ch Mid 3GHz – 26.5GHz




Ch High 30MHz – 3GHz




Ch High 3GHz – 26.5GHz




Conducted Spurious Emission Measurement Result (802.11n_20M) Ch Low 30MHz – 3GHz




Ch Low 3GHz – 26.5GHz




Ch Mid 30MHz – 3GHz




Ch Mid 3GHz – 26.5GHz



Ch High 30MHz – 3GHz



Ch High 3GHz – 26.5GHz



Radiated Spurious Emission Measurement Result (below 1GHz) (Chip Antenna)

Operation Mode 802.11b TX CH Low
Fundamental Frequency 2412MHz
Temperature 25

Test Date 2014/01/08
Test By Lake
Humidity 60 %

| No | Freq MHz | Reading dBuV | Factor dB | Level dBuV/m | Limit dBuV/m | Over Limit dB | Remark | Pol V/H |
|----|-------------|-----------------|--------------|-----------------|-----------------|---------------------|--------|------------|
| 1 | 95.96 | 49.46 | -17.86 | 31.60 | 43.50 | -11.90 | Peak | VERTICAL |
| 2 | 119.24 | 46.78 | -14.61 | 32.17 | 43.50 | -11.33 | Peak | VERTICAL |
| 3 | 143.49 | 46.39 | -12.34 | 34.05 | 43.50 | -9.45 | Peak | VERTICAL |
| 4 | 296.75 | 45.67 | -11.17 | 34.50 | 46.00 | -11.50 | Peak | VERTICAL |
| 5 | 455.83 | 40.07 | -8.12 | 31.95 | 46.00 | -14.05 | Peak | VERTICAL |
| 6 | 813.76 | 34.97 | -2.27 | 32.70 | 46.00 | -13.30 | Peak | VERTICAL |
| | | | | | | | | |
| 1 | 95.96 | 50.26 | -17.86 | 32.40 | 43.50 | -11.10 | Peak | HORIZONTAL |
| 2 | 120.21 | 51.76 | -14.51 | 37.25 | 43.50 | -6.25 | Peak | HORIZONTAL |
| 3 | 191.99 | 50.94 | -14.69 | 36.25 | 43.50 | -7.25 | Peak | HORIZONTAL |
| 4 | 240.49 | 47.69 | -13.24 | 34.45 | 46.00 | -11.55 | Peak | HORIZONTAL |
| 5 | 431.58 | 43.93 | -8.55 | 35.38 | 46.00 | -10.62 | Peak | HORIZONTAL |
| 6 | 740.04 | 33.93 | -3.15 | 30.78 | 46.00 | -15.22 | Peak | HORIZONTAL |

Remark:

- 1 No further spurious emissions detected from the lowest internal frequency and 30MHz.
- 2 Measuring frequencies from the lowest internal frequency to the 1GHz.
- 3 Radiated emissions measured in frequency range from 9MHz to 1000MHz were made with an instrument detector setting 9-90KHz/110-490KHz using PK/AV and other Frequency Band using PK/QP
- 4 Measurement result within this frequency range shown “ - ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- 5 The IF bandwidth of SPA between 9kHz to 30MHz was 10kHz, VBW= 30kHz; between 30MHz to 1GHz was 100KHz, VBW=300KHz.

Radiated Spurious Emission Measurement Result (below 1GHz) (Chip Antenna)

Operation Mode 802.11b TX CH Mid

Test Date 2014/01/08

Fundamental Frequency 2437MHz

Test By Lake

Temperature 25

Humidity 60 %

| No | Freq MHz | Reading dBuV | Factor dB | Level dBuV/m | Limit dBuV/m | Over Limit dB | Remark | Pol V/H |
|----|-------------|-----------------|--------------|-----------------|-----------------|---------------------|--------|------------|
| 1 | 95.96 | 49.56 | -17.86 | 31.70 | 43.50 | -11.80 | Peak | VERTICAL |
| 2 | 143.49 | 46.69 | -12.34 | 34.35 | 43.50 | -9.15 | Peak | VERTICAL |
| 3 | 296.75 | 44.73 | -11.17 | 33.56 | 46.00 | -12.44 | Peak | VERTICAL |
| 4 | 332.64 | 44.48 | -10.50 | 33.98 | 46.00 | -12.02 | Peak | VERTICAL |
| 5 | 455.83 | 40.94 | -8.12 | 32.82 | 46.00 | -13.18 | Peak | VERTICAL |
| 6 | 816.67 | 34.38 | -2.22 | 32.16 | 46.00 | -13.84 | Peak | VERTICAL |
| | | | | | | | | |
| 1 | 95.96 | 50.50 | -17.86 | 32.64 | 43.50 | -10.86 | Peak | HORIZONTAL |
| 2 | 120.21 | 52.17 | -14.51 | 37.66 | 43.50 | -5.84 | Peak | HORIZONTAL |
| 3 | 143.49 | 48.98 | -12.34 | 36.64 | 43.50 | -6.86 | Peak | HORIZONTAL |
| 4 | 191.99 | 50.72 | -14.69 | 36.03 | 43.50 | -7.47 | Peak | HORIZONTAL |
| 5 | 431.58 | 43.36 | -8.55 | 34.81 | 46.00 | -11.19 | Peak | HORIZONTAL |
| 6 | 740.04 | 33.41 | -3.15 | 30.26 | 46.00 | -15.74 | Peak | HORIZONTAL |

Remark:

- 1 No further spurious emissions detected from the lowest internal frequency and 30MHz.
- 2 Measuring frequencies from the lowest internal frequency to the 1GHz.
- 3 Radiated emissions measured in frequency range from 9MHz to 1000MHz were made with an instrument detector setting 9-90KHz/110-490KHz using PK/AV and other Frequency Band using PK/QP
- 4 Measurement result within this frequency range shown “ - ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- 5 The IF bandwidth of SPA between 9kHz to 30MHz was 10kHz, VBW= 30kHz; between 30MHz to 1GHz was 100KHz, VBW=300KHz.

Radiated Spurious Emission Measurement Result (below 1GHz) (Chip Antenna)

Operation Mode 802.11b TX CH High

Test Date 2014/01/08

Fundamental Frequency 2462MHz

Test By Lake

Temperature 25

Humidity 60 %

| No | Freq MHz | Reading dBuV | Factor dB | Level dBuV/m | Limit dBuV/m | Over Limit dB | Remark | Pol V/H |
|----|-------------|-----------------|--------------|-----------------|-----------------|---------------------|--------|------------|
| 1 | 71.71 | 43.78 | -15.10 | 28.68 | 40.00 | -11.32 | Peak | VERTICAL |
| 2 | 95.96 | 49.52 | -17.86 | 31.66 | 43.50 | -11.84 | Peak | VERTICAL |
| 3 | 143.49 | 45.16 | -12.34 | 32.82 | 43.50 | -10.68 | Peak | VERTICAL |
| 4 | 296.75 | 43.84 | -11.17 | 32.67 | 46.00 | -13.33 | Peak | VERTICAL |
| 5 | 455.83 | 40.26 | -8.12 | 32.14 | 46.00 | -13.86 | Peak | VERTICAL |
| 6 | 813.76 | 33.67 | -2.27 | 31.40 | 46.00 | -14.60 | Peak | VERTICAL |
| | | | | | | | | |
| 1 | 120.21 | 52.68 | -14.51 | 38.17 | 43.50 | -5.33 | Peak | HORIZONTAL |
| 2 | 143.49 | 48.64 | -12.34 | 36.30 | 43.50 | -7.20 | Peak | HORIZONTAL |
| 3 | 191.99 | 50.79 | -14.69 | 36.10 | 43.50 | -7.40 | Peak | HORIZONTAL |
| 4 | 432.55 | 43.52 | -8.54 | 34.98 | 46.00 | -11.02 | Peak | HORIZONTAL |
| 5 | 504.33 | 38.61 | -7.56 | 31.05 | 46.00 | -14.95 | Peak | HORIZONTAL |
| 6 | 740.04 | 33.48 | -3.15 | 30.33 | 46.00 | -15.67 | Peak | HORIZONTAL |

Remark:

- 1 No further spurious emissions detected from the lowest internal frequency and 30MHz.
- 2 Measuring frequencies from the lowest internal frequency to the 1GHz.
- 3 Radiated emissions measured in frequency range from 9MHz to 1000MHz were made with an instrument detector setting 9-90KHz/110-490KHz using PK/AV and other Frequency Band using PK/QP
- 4 Measurement result within this frequency range shown “ - ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- 5 The IF bandwidth of SPA between 9kHz to 30MHz was 10kHz, VBW= 30kHz; between 30MHz to 1GHz was 100KHz, VBW=300KHz.

Radiated Spurious Emission Measurement Result (below 1GHz) (Chip Antenna)

Operation Mode 802.11g TX CH Low
Fundamental Frequency 2412MHz
Temperature 25

Test Date 2014/01/08
Test By Lake
Humidity 60 %

| No | Freq MHz | Reading dBuV | Factor dB | Level dBuV/m | Limit dBuV/m | Over Limit dB | Remark | Pol V/H |
|----|-------------|-----------------|--------------|-----------------|-----------------|---------------------|--------|------------|
| 1 | 95.96 | 51.08 | -17.86 | 33.22 | 43.50 | -10.28 | Peak | VERTICAL |
| 2 | 120.21 | 51.75 | -14.51 | 37.24 | 43.50 | -6.26 | Peak | VERTICAL |
| 3 | 143.49 | 48.60 | -12.34 | 36.26 | 43.50 | -7.24 | Peak | VERTICAL |
| 4 | 191.99 | 50.73 | -14.69 | 36.04 | 43.50 | -7.46 | Peak | VERTICAL |
| 5 | 431.58 | 43.06 | -8.55 | 34.51 | 46.00 | -11.49 | Peak | VERTICAL |
| 6 | 740.04 | 33.35 | -3.15 | 30.20 | 46.00 | -15.80 | Peak | VERTICAL |
| | | | | | | | | |
| 1 | 95.96 | 49.61 | -17.86 | 31.75 | 43.50 | -11.75 | Peak | HORIZONTAL |
| 2 | 120.21 | 47.01 | -14.51 | 32.50 | 43.50 | -11.00 | Peak | HORIZONTAL |
| 3 | 144.46 | 46.19 | -12.30 | 33.89 | 43.50 | -9.61 | Peak | HORIZONTAL |
| 4 | 296.75 | 43.71 | -11.17 | 32.54 | 46.00 | -13.46 | Peak | HORIZONTAL |
| 5 | 455.83 | 40.04 | -8.12 | 31.92 | 46.00 | -14.08 | Peak | HORIZONTAL |
| 6 | 813.76 | 34.39 | -2.27 | 32.12 | 46.00 | -13.88 | Peak | HORIZONTAL |

Remark:

- 1 No further spurious emissions detected from the lowest internal frequency and 30MHz.
- 2 Measuring frequencies from the lowest internal frequency to the 1GHz.
- 3 Radiated emissions measured in frequency range from 9MHz to 1000MHz were made with an instrument detector setting 9-90KHz/110-490KHz using PK/AV and other Frequency Band using PK/QP
- 4 Measurement result within this frequency range shown “ - ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- 5 The IF bandwidth of SPA between 9kHz to 30MHz was 10kHz, VBW= 30kHz; between 30MHz to 1GHz was 100KHz, VBW=300KHz.

Radiated Spurious Emission Measurement Result (below 1GHz) (Chip Antenna)

| | | | |
|-----------------------|-------------------|-----------|------------|
| Operation Mode | 802.11g TX CH Mid | Test Date | 2014/01/08 |
| Fundamental Frequency | 2437MHz | Test By | Lake |
| Temperature | 25 | Pol | Ver./Hor |
| Humidity | 60 % | | |

| No | Freq MHz | Reading dBuV | Factor dB | Level dBuV/m | Limit dBuV/m | Over Limit dB | Remark | Pol V/H |
|----|-------------|-----------------|--------------|-----------------|-----------------|---------------------|--------|------------|
| 1 | 120.21 | 51.96 | -14.51 | 37.45 | 43.50 | -6.05 | Peak | VERTICAL |
| 2 | 144.46 | 48.00 | -12.30 | 35.70 | 43.50 | -7.80 | Peak | VERTICAL |
| 3 | 191.99 | 50.57 | -14.69 | 35.88 | 43.50 | -7.62 | Peak | VERTICAL |
| 4 | 432.55 | 44.03 | -8.54 | 35.49 | 46.00 | -10.51 | Peak | VERTICAL |
| 5 | 594.54 | 37.19 | -5.77 | 31.42 | 46.00 | -14.58 | Peak | VERTICAL |
| 6 | 742.95 | 33.79 | -3.08 | 30.71 | 46.00 | -15.29 | Peak | VERTICAL |
| | | | | | | | | |
| 1 | 95.96 | 49.49 | -17.86 | 31.63 | 43.50 | -11.87 | Peak | HORIZONTAL |
| 2 | 120.21 | 47.19 | -14.51 | 32.68 | 43.50 | -10.82 | Peak | HORIZONTAL |
| 3 | 144.46 | 45.30 | -12.30 | 33.00 | 43.50 | -10.50 | Peak | HORIZONTAL |
| 4 | 295.78 | 43.95 | -11.21 | 32.74 | 46.00 | -13.26 | Peak | HORIZONTAL |
| 5 | 594.54 | 38.74 | -5.77 | 32.97 | 46.00 | -13.03 | Peak | HORIZONTAL |
| 6 | 813.76 | 33.93 | -2.27 | 31.66 | 46.00 | -14.34 | Peak | HORIZONTAL |

Remark:

- 1 No further spurious emissions detected from the lowest internal frequency and 30MHz.
- 2 Measuring frequencies from the lowest internal frequency to the 1GHz.
- 3 Radiated emissions measured in frequency range from 9MHz to 1000MHz were made with an instrument detector setting 9-90KHz/110-490KHz using PK/AV and other Frequency Band using PK/QP
- 4 Measurement result within this frequency range shown “ - ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- 5 The IF bandwidth of SPA between 9kHz to 30MHz was 10kHz, VBW= 30kHz; between 30MHz to 1GHz was 100KHz, VBW=300KHz.

Radiated Spurious Emission Measurement Result (below 1GHz) (Chip Antenna)

| | | | |
|-----------------------|--------------------|-----------|------------|
| Operation Mode | 802.11g TX CH High | Test Date | 2014/01/08 |
| Fundamental Frequency | 2462MHz | Test By | Lake |
| Temperature | 25 | Pol | Ver./Hor |
| Humidity | 60 % | | |

| No | Freq MHz | Reading dBuV | Factor dB | Level dBuV/m | Limit dBuV/m | Over Limit dB | Remark | Pol V/H |
|----|-------------|-----------------|--------------|-----------------|-----------------|---------------------|--------|------------|
| 1 | 95.96 | 51.45 | -17.86 | 33.59 | 43.50 | -9.91 | Peak | VERTICAL |
| 2 | 120.21 | 52.29 | -14.51 | 37.78 | 43.50 | -5.72 | Peak | VERTICAL |
| 3 | 143.49 | 47.88 | -12.34 | 35.54 | 43.50 | -7.96 | Peak | VERTICAL |
| 4 | 191.99 | 50.83 | -14.69 | 36.14 | 43.50 | -7.36 | Peak | VERTICAL |
| 5 | 431.58 | 43.64 | -8.55 | 35.09 | 46.00 | -10.91 | Peak | VERTICAL |
| 6 | 742.95 | 33.46 | -3.08 | 30.38 | 46.00 | -15.62 | Peak | VERTICAL |
| | | | | | | | | |
| 1 | 95.96 | 49.71 | -17.86 | 31.85 | 43.50 | -11.65 | Peak | HORIZONTAL |
| 2 | 143.49 | 45.94 | -12.34 | 33.60 | 43.50 | -9.90 | Peak | HORIZONTAL |
| 3 | 295.78 | 44.40 | -11.21 | 33.19 | 46.00 | -12.81 | Peak | HORIZONTAL |
| 4 | 333.61 | 42.67 | -10.48 | 32.19 | 46.00 | -13.81 | Peak | HORIZONTAL |
| 5 | 445.16 | 40.76 | -8.28 | 32.48 | 46.00 | -13.52 | Peak | HORIZONTAL |
| 6 | 813.76 | 36.22 | -2.27 | 33.95 | 46.00 | -12.05 | Peak | HORIZONTAL |

Remark:

- 1 No further spurious emissions detected from the lowest internal frequency and 30MHz.
- 2 Measuring frequencies from the lowest internal frequency to the 1GHz.
- 3 Radiated emissions measured in frequency range from 9MHz to 1000MHz were made with an instrument detector setting 9-90KHz/110-490KHz using PK/AV and other Frequency Band using PK/QP
- 4 Measurement result within this frequency range shown “ - ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- 5 The IF bandwidth of SPA between 9kHz to 30MHz was 10kHz, VBW= 30kHz; between 30MHz to 1GHz was 100KHz, VBW=300KHz.

Radiated Spurious Emission Measurement Result (below 1GHz) (Chip Antenna)

| | | | |
|-----------------------|------------------------|-----------|------------|
| Operation Mode | 802.11 n_20M TX CH Low | Test Date | 2014/01/08 |
| Fundamental Frequency | 2412MHz | Test By | Lake |
| Temperature | 25 | Pol | Ver./Hor |
| Humidity | 60 % | | |

| No | Freq MHz | Reading dBuV | Factor dB | Level dBuV/m | Limit dBuV/m | Over Limit dB | Remark | Pol V/H |
|----|-------------|-----------------|--------------|-----------------|-----------------|---------------------|--------|------------|
| 1 | 95.96 | 49.71 | -17.86 | 31.85 | 43.50 | -11.65 | Peak | VERTICAL |
| 2 | 143.49 | 45.94 | -12.34 | 33.60 | 43.50 | -9.90 | Peak | VERTICAL |
| 3 | 295.78 | 44.40 | -11.21 | 33.19 | 46.00 | -12.81 | Peak | VERTICAL |
| 4 | 333.61 | 42.67 | -10.48 | 32.19 | 46.00 | -13.81 | Peak | VERTICAL |
| 5 | 445.16 | 40.76 | -8.28 | 32.48 | 46.00 | -13.52 | Peak | VERTICAL |
| 6 | 813.76 | 36.22 | -2.27 | 33.95 | 46.00 | -12.05 | Peak | VERTICAL |
| | | | | | | | | |
| 1 | 95.96 | 51.58 | -17.86 | 33.72 | 43.50 | -9.78 | Peak | HORIZONTAL |
| 2 | 120.21 | 51.73 | -14.51 | 37.22 | 43.50 | -6.28 | Peak | HORIZONTAL |
| 3 | 143.49 | 47.86 | -12.34 | 35.52 | 43.50 | -7.98 | Peak | HORIZONTAL |
| 4 | 191.99 | 50.75 | -14.69 | 36.06 | 43.50 | -7.44 | Peak | HORIZONTAL |
| 5 | 431.58 | 43.73 | -8.55 | 35.18 | 46.00 | -10.82 | Peak | HORIZONTAL |
| 6 | 591.63 | 38.07 | -5.85 | 32.22 | 46.00 | -13.78 | Peak | HORIZONTAL |

Remark:

- 1 No further spurious emissions detected from the lowest internal frequency and 30MHz.
- 2 Measuring frequencies from the lowest internal frequency to the 1GHz.
- 3 Radiated emissions measured in frequency range from 9MHz to 1000MHz were made with an instrument detector setting 9-90KHz/110-490KHz using PK/AV and other Frequency Band using PK/QP
- 4 Measurement result within this frequency range shown “ - ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- 5 The IF bandwidth of SPA between 9kHz to 30MHz was 10kHz, VBW= 30kHz; between 30MHz to 1GHz was 100KHz, VBW=300KHz.

Radiated Spurious Emission Measurement Result (below 1GHz) (Chip Antenna)

| | | | |
|-----------------------|------------------------|-----------|------------|
| Operation Mode | 802.11 n_20M TX CH Mid | Test Date | 2014/01/08 |
| Fundamental Frequency | 2437MHz | Test By | Lake |
| Temperature | 25 | Pol | Ver./Hor |
| Humidity | 60 % | | |

| No | Freq MHz | Reading dBuV | Factor dB | Level dBuV/m | Limit dBuV/m | Over Limit dB | Remark | Pol V/H |
|----|-------------|-----------------|--------------|-----------------|-----------------|---------------------|--------|------------|
| 1 | 95.96 | 48.85 | -17.86 | 30.99 | 43.50 | -12.51 | Peak | VERTICAL |
| 2 | 120.21 | 47.46 | -14.51 | 32.95 | 43.50 | -10.55 | Peak | VERTICAL |
| 3 | 143.49 | 45.29 | -12.34 | 32.95 | 43.50 | -10.55 | Peak | VERTICAL |
| 4 | 296.75 | 43.43 | -11.17 | 32.26 | 46.00 | -13.74 | Peak | VERTICAL |
| 5 | 455.83 | 40.71 | -8.12 | 32.59 | 46.00 | -13.41 | Peak | VERTICAL |
| 6 | 816.67 | 33.49 | -2.22 | 31.27 | 46.00 | -14.73 | Peak | VERTICAL |
| | | | | | | | | |
| 1 | 95.96 | 51.57 | -17.86 | 33.71 | 43.50 | -9.79 | Peak | HORIZONTAL |
| 2 | 120.21 | 51.77 | -14.51 | 37.26 | 43.50 | -6.24 | Peak | HORIZONTAL |
| 3 | 143.49 | 47.88 | -12.34 | 35.54 | 43.50 | -7.96 | Peak | HORIZONTAL |
| 4 | 191.99 | 51.32 | -14.69 | 36.63 | 43.50 | -6.87 | Peak | HORIZONTAL |
| 5 | 431.58 | 43.22 | -8.55 | 34.67 | 46.00 | -11.33 | Peak | HORIZONTAL |
| 6 | 591.63 | 39.09 | -5.85 | 33.24 | 46.00 | -12.76 | Peak | HORIZONTAL |

Remark:

- 1 No further spurious emissions detected from the lowest internal frequency and 30MHz.
- 2 Measuring frequencies from the lowest internal frequency to the 1GHz.
- 3 Radiated emissions measured in frequency range from 9MHz to 1000MHz were made with an instrument detector setting 9-90KHz/110-490KHz using PK/AV and other Frequency Band using PK/QP
- 4 Measurement result within this frequency range shown “ - ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- 5 The IF bandwidth of SPA between 9kHz to 30MHz was 10kHz, VBW= 30kHz; between 30MHz to 1GHz was 100KHz, VBW=300KHz.

Radiated Spurious Emission Measurement Result (below 1GHz) (Chip Antenna)

| | | | |
|-----------------------|-------------------------|-----------|------------|
| Operation Mode | 802.11 n_20M TX CH High | Test Date | 2014/01/08 |
| Fundamental Frequency | 2462MHz | Test By | Lake |
| Temperature | 25 | Pol | Ver./Hor |
| Humidity | 60 % | | |

| No | Freq MHz | Reading dBuV | Factor dB | Level dBuV/m | Limit dBuV/m | Over Limit dB | Remark | Pol V/H |
|----|-------------|-----------------|--------------|-----------------|-----------------|---------------------|--------|------------|
| 1 | 71.71 | 44.73 | -15.10 | 29.63 | 40.00 | -10.37 | Peak | VERTICAL |
| 2 | 95.96 | 49.17 | -17.86 | 31.31 | 43.50 | -12.19 | Peak | VERTICAL |
| 3 | 120.21 | 46.95 | -14.51 | 32.44 | 43.50 | -11.06 | Peak | VERTICAL |
| 4 | 143.49 | 46.42 | -12.34 | 34.08 | 43.50 | -9.42 | Peak | VERTICAL |
| 5 | 296.75 | 44.20 | -11.17 | 33.03 | 46.00 | -12.97 | Peak | VERTICAL |
| 6 | 594.54 | 39.75 | -5.77 | 33.98 | 46.00 | -12.02 | Peak | VERTICAL |
| | | | | | | | | |
| 1 | 95.96 | 51.49 | -17.86 | 33.63 | 43.50 | -9.87 | Peak | HORIZONTAL |
| 2 | 120.21 | 51.11 | -14.51 | 36.60 | 43.50 | -6.90 | Peak | HORIZONTAL |
| 3 | 144.46 | 48.47 | -12.30 | 36.17 | 43.50 | -7.33 | Peak | HORIZONTAL |
| 4 | 240.49 | 48.13 | -13.24 | 34.89 | 46.00 | -11.11 | Peak | HORIZONTAL |
| 5 | 432.55 | 43.31 | -8.54 | 34.77 | 46.00 | -11.23 | Peak | HORIZONTAL |
| 6 | 742.95 | 33.62 | -3.08 | 30.54 | 46.00 | -15.46 | Peak | HORIZONTAL |

Remark:

- 1 No further spurious emissions detected from the lowest internal frequency and 30MHz.
- 2 Measuring frequencies from the lowest internal frequency to the 1GHz.
- 3 Radiated emissions measured in frequency range from 9MHz to 1000MHz were made with an instrument detector setting 9-90KHz/110-490KHz using PK/AV and other Frequency Band using PK/QP
- 4 Measurement result within this frequency range shown “ - ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- 5 The IF bandwidth of SPA between 9kHz to 30MHz was 10kHz, VBW= 30kHz; between 30MHz to 1GHz was 100KHz, VBW=300KHz.

Radiated Spurious Emission Measurement Result (above 1GHz) (Chip Antenna)

| | | | |
|-----------------------|-------------------|-----------|------------|
| Operation Mode | 802.11b TX CH Low | Test Date | 2014/01/08 |
| Fundamental Frequency | 2412MHz | Test By | Lake |
| Temperature | 25 | Pol | Ver. |
| Humidity | 60 % | | |

| No | Freq MHz | Reading dBuV | Factor dB | Level dBuV/m | Limit dBuV/m | Over Limit dB | Remark | Pol V/H |
|----|-------------|-----------------|--------------|-----------------|-----------------|---------------------|---------|------------|
| 1 | 4824.00 | 50.34 | 1.33 | 51.67 | 74.00 | -22.33 | Peak | VERTICAL |
| 2 | 7236.00 | 34.87 | 8.26 | 43.13 | 54.00 | -10.87 | Average | VERTICAL |
| 3 | 7236.00 | 45.11 | 8.26 | 53.37 | 74.00 | -20.63 | Peak | VERTICAL |
| 4 | 9648.00 | --- | | | | | | VERTICAL |
| 5 | 12060.00 | --- | | | | | | VERTICAL |
| | | | | | | | | |
| 1 | 1868.00 | 50.96 | -8.68 | 42.28 | 74.00 | -31.72 | Peak | HORIZONTAL |
| 2 | 4824.00 | 48.78 | 1.33 | 50.11 | 74.00 | -23.89 | Peak | HORIZONTAL |
| 3 | 7236.00 | --- | | | | | | HORIZONTAL |
| 4 | 9648.00 | --- | | | | | | HORIZONTAL |
| 5 | 12060.00 | --- | | | | | | HORIZONTAL |

Remark:

- 1 Measuring frequencies from the lowest internal frequency to the 10th of fundamental frequency
- 2 Field strength limits for frequency above 1000MHz are based on average limits. However, Peak mode field strength shall not exceed the average limits specified plus 20dB.
- 3 Measurement of data within this frequency range shown “ - ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- 4 Spectrum Peak mode IF bandwidth Setting : 1GHz- 26GHz, RBW= 1MHz, Sweep time= 200 ms., the VBW setting was 3 MHz.
- 5 Spectrum AV mode if bandwidth Setting : 1GHz- 26GHz, RBW= 1MHz, VBW= 10Hz, Sweep time= 200 ms.

Radiated Spurious Emission Measurement Result (above 1GHz) (Chip Antenna)

| | | | |
|-----------------------|-------------------|-----------|------------|
| Operation Mode | 802.11b TX CH Mid | Test Date | 2014/01/08 |
| Fundamental Frequency | 2437MHz | Test By | Lake |
| Temperature | 25 | Pol | Ver./Hor |
| Humidity | 60 % | | |

| No | Freq MHz | Reading dBuV | Factor dB | Level dBuV/m | Limit dBuV/m | Over Limit dB | Remark | Pol V/H |
|----|-------------|-----------------|--------------|-----------------|-----------------|---------------------|--------|------------|
| 1 | 4874.00 | 50.07 | 1.51 | 51.58 | 74.00 | -22.42 | Peak | VERTICAL |
| 2 | 7311.00 | 43.04 | 8.30 | 51.34 | 74.00 | -22.66 | Peak | VERTICAL |
| 3 | 9748.00 | --- | | | | | | VERTICAL |
| 4 | 12185.00 | --- | | | | | | VERTICAL |
| | | | | | | | | |
| 1 | 1560.00 | 51.04 | -10.57 | 40.47 | 74.00 | -33.53 | Peak | HORIZONTAL |
| 2 | 4874.00 | 49.43 | 1.51 | 50.94 | 74.00 | -23.06 | Peak | HORIZONTAL |
| 3 | 7311.00 | --- | | | | | | HORIZONTAL |
| 4 | 9748.00 | --- | | | | | | HORIZONTAL |
| 5 | 12185.00 | --- | | | | | | HORIZONTAL |

Remark:

- 1 Measuring frequencies from the lowest internal frequency to the 10th of fundamental frequency
- 2 Field strength limits for frequency above 1000MHz are based on average limits. However, Peak mode field strength shall not exceed the average limits specified plus 20dB.
- 3 Measurement of data within this frequency range shown “ - ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- 4 Spectrum Peak mode IF bandwidth Setting : 1GHz- 26GHz, RBW= 1MHz, Sweep time= 200 ms., the VBW setting was 3 MHz.
- 5 Spectrum AV mode if bandwidth Setting : 1GHz- 26GHz, RBW= 1MHz, VBW= 10Hz, Sweep time= 200 ms.

Radiated Spurious Emission Measurement Result (above 1GHz) (Chip Antenna)

| | | | |
|-----------------------|--------------------|-----------|------------|
| Operation Mode | 802.11b TX CH High | Test Date | 2014/01/08 |
| Fundamental Frequency | 2462MHz | Test By | Lake |
| Temperature | 25 | Pol | Ver./Hor |
| Humidity | 60 % | | |

| No | Freq MHz | Reading dBuV | Factor dB | Level dBuV/m | Limit dBuV/m | Over Limit dB | Remark | Pol V/H |
|----|-------------|-----------------|--------------|-----------------|-----------------|---------------------|---------|------------|
| 1 | 1994.00 | 52.35 | -7.94 | 44.41 | 74.00 | -29.59 | Peak | VERTICAL |
| 2 | 4924.00 | 50.17 | 1.68 | 51.85 | 74.00 | -22.15 | Peak | VERTICAL |
| 3 | 7386.00 | --- | | | | | | VERTICAL |
| 4 | 9848.00 | --- | | | | | | VERTICAL |
| 5 | 12310.00 | --- | | | | | | VERTICAL |
| | | | | | | | | |
| 1 | 4924.00 | 38.44 | 1.68 | 40.12 | 54.00 | -13.88 | Average | HORIZONTAL |
| 2 | 4924.00 | 52.01 | 1.68 | 53.69 | 74.00 | -20.31 | Peak | HORIZONTAL |
| 3 | 7386.00 | --- | | | | | | HORIZONTAL |
| 4 | 9848.00 | --- | | | | | | HORIZONTAL |
| 5 | 12310.00 | --- | | | | | | HORIZONTAL |

Remark:

- 1 Measuring frequencies from the lowest internal frequency to the 10th of fundamental frequency
- 2 Field strength limits for frequency above 1000MHz are based on average limits. However, Peak mode field strength shall not exceed the average limits specified plus 20dB.
- 3 Measurement of data within this frequency range shown “ - ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- 4 Spectrum Peak mode IF bandwidth Setting : 1GHz- 26GHz, RBW= 1MHz, Sweep time= 200 ms., the VBW setting was 3 MHz.
- 5 Spectrum AV mode if bandwidth Setting : 1GHz- 26GHz, RBW= 1MHz, VBW= 10Hz, Sweep time= 200 ms.

Radiated Spurious Emission Measurement Result (above 1GHz) (Chip Antenna)

| | | | |
|-----------------------|-------------------|-----------|------------|
| Operation Mode | 802.11g TX CH Low | Test Date | 2014/01/08 |
| Fundamental Frequency | 2412MHz | Test By | Lake |
| Temperature | 25 | Pol | Ver./Hor |
| Humidity | 60 % | | |

| No | Freq MHz | Reading dBuV | Factor dB | Level dBuV/m | Limit dBuV/m | Over Limit dB | Remark | Pol V/H |
|----|-------------|-----------------|--------------|-----------------|-----------------|---------------------|--------|------------|
| 1 | 1994.00 | 52.77 | -7.94 | 44.83 | 74.00 | -29.17 | Peak | VERTICAL |
| 2 | 4824.00 | 42.69 | 1.33 | 44.02 | 74.00 | -29.98 | Peak | VERTICAL |
| 3 | 7236.00 | --- | | | | | | VERTICAL |
| 4 | 9648.00 | --- | | | | | | VERTICAL |
| 5 | 12060.00 | --- | | | | | | VERTICAL |
| | | | | | | | | |
| 1 | 1994.00 | 49.24 | -7.94 | 41.30 | 74.00 | -32.70 | Peak | HORIZONTAL |
| 2 | 4824.00 | 43.53 | 1.33 | 44.86 | 74.00 | -29.14 | Peak | HORIZONTAL |
| 3 | 7236.00 | --- | | | | | | HORIZONTAL |
| 4 | 9648.00 | --- | | | | | | HORIZONTAL |
| 5 | 12060.00 | --- | | | | | | HORIZONTAL |

Remark:

- 1 Measuring frequencies from the lowest internal frequency to the 10th of fundamental frequency
- 2 Field strength limits for frequency above 1000MHz are based on average limits. However, Peak mode field strength shall not exceed the average limits specified plus 20dB.
- 3 Measurement of data within this frequency range shown “ - ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- 4 Spectrum Peak mode IF bandwidth Setting : 1GHz- 26GHz, RBW= 1MHz, Sweep time= 200 ms., the VBW setting was 3 MHz.
- 5 Spectrum AV mode if bandwidth Setting : 1GHz- 26GHz, RBW= 1MHz, VBW= 10Hz, Sweep time= 200 ms.

Radiated Spurious Emission Measurement Result (above 1GHz) (Chip Antenna)

| | | | |
|-----------------------|-------------------|-----------|------------|
| Operation Mode | 802.11g TX CH Mid | Test Date | 2014/01/08 |
| Fundamental Frequency | 2437MHz | Test By | Lake |
| Temperature | 25 | Pol | Ver./Hor |
| Humidity | 60 % | | |

| No | Freq MHz | Reading dBuV | Factor dB | Level dBuV/m | Limit dBuV/m | Over Limit dB | Remark | Pol V/H |
|----|-------------|-----------------|--------------|-----------------|-----------------|---------------------|--------|------------|
| 1 | 4874.00 | 43.02 | 1.51 | 44.53 | 74.00 | -29.47 | Peak | VERTICAL |
| 2 | 7311.00 | 42.68 | 8.30 | 50.98 | 74.00 | -23.02 | Peak | VERTICAL |
| 3 | 9748.00 | --- | | | | | | VERTICAL |
| 4 | 12185.00 | --- | | | | | | VERTICAL |
| | | | | | | | | |
| 1 | 4874.00 | 42.41 | 1.51 | 43.92 | 74.00 | -30.08 | Peak | HORIZONTAL |
| 2 | 7311.00 | 41.55 | 8.30 | 49.85 | 74.00 | -24.15 | Peak | HORIZONTAL |
| 3 | 9748.00 | --- | | | | | | HORIZONTAL |
| 4 | 12185.00 | --- | | | | | | HORIZONTAL |

Remark:

- 1 Measuring frequencies from the lowest internal frequency to the 10th of fundamental frequency
- 2 Field strength limits for frequency above 1000MHz are based on average limits. However, Peak mode field strength shall not exceed the average limits specified plus 20dB.
- 3 Measurement of data within this frequency range shown “ - ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- 4 Spectrum Peak mode IF bandwidth Setting : 1GHz- 26GHz, RBW= 1MHz, Sweep time= 200 ms., the VBW setting was 3 MHz.
- 5 Spectrum AV mode if bandwidth Setting : 1GHz- 26GHz, RBW= 1MHz, VBW= 10Hz, Sweep time= 200 ms.

Radiated Spurious Emission Measurement Result (above 1GHz) (Chip Antenna)

| | | | |
|-----------------------|--------------------|-----------|------------|
| Operation Mode | 802.11g TX CH High | Test Date | 2014/01/08 |
| Fundamental Frequency | 2462MHz | Test By | Lake |
| Temperature | 25 | Pol | Ver./Hor |
| Humidity | 60 % | | |

| No | Freq MHz | Reading dBuV | Factor dB | Level dBuV/m | Limit dBuV/m | Over Limit dB | Remark | Pol V/H |
|----|-------------|-----------------|--------------|-----------------|-----------------|---------------------|--------|------------|
| 1 | 4924.00 | 41.50 | 1.68 | 43.18 | 74.00 | -30.82 | Peak | VERTICAL |
| 2 | 7386.00 | 42.81 | 8.35 | 51.16 | 74.00 | -22.84 | Peak | VERTICAL |
| 3 | 9848.00 | --- | | | | | | VERTICAL |
| 4 | 12310.00 | --- | | | | | | VERTICAL |
| 1 | 1112.00 | 54.23 | -11.84 | 42.39 | 74.00 | -31.61 | Peak | HORIZONTAL |
| 2 | 4924.00 | 43.57 | 1.68 | 45.25 | 74.00 | -28.75 | Peak | HORIZONTAL |
| 3 | 7386.00 | --- | | | | | | HORIZONTAL |
| 4 | 9848.00 | --- | | | | | | HORIZONTAL |
| 5 | 12310.00 | --- | | | | | | HORIZONTAL |

Remark:

- 1 Measuring frequencies from the lowest internal frequency to the 10th of fundamental frequency
- 2 Field strength limits for frequency above 1000MHz are based on average limits. However, Peak mode field strength shall not exceed the average limits specified plus 20dB.
- 3 Measurement of data within this frequency range shown “ - ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- 4 Spectrum Peak mode IF bandwidth Setting : 1GHz- 26GHz, RBW= 1MHz, Sweep time= 200 ms., the VBW setting was 3 MHz.
- 5 Spectrum AV mode if bandwidth Setting : 1GHz- 26GHz, RBW= 1MHz, VBW= 10Hz, Sweep time= 200 ms.

Radiated Spurious Emission Measurement Result (above 1GHz) (Chip Antenna)

| | | | |
|-----------------------|-----------------------|-----------|------------|
| Operation Mode | 802.11n_20M TX CH Low | Test Date | 2014/01/08 |
| Fundamental Frequency | 2412MHz | Test By | Lake |
| Temperature | 25 | Pol | Ver./Hor |
| Humidity | 60 % | | |

| No | Freq MHz | Reading dBuV | Factor dB | Level dBuV/m | Limit dBuV/m | Over Limit dB | Remark | Pol V/H |
|----|-------------|-----------------|--------------|-----------------|-----------------|---------------------|--------|------------|
| 1 | 4824.00 | 42.31 | 1.33 | 43.64 | 74.00 | -30.36 | Peak | VERTICAL |
| 2 | 7236.00 | 42.01 | 8.26 | 50.27 | 74.00 | -23.73 | Peak | VERTICAL |
| 3 | 9648.00 | --- | | | | | | VERTICAL |
| 4 | 12060.00 | --- | | | | | | VERTICAL |
| | | | | | | | | |
| 1 | 4824.00 | 42.65 | 1.33 | 43.98 | 74.00 | -30.02 | Peak | HORIZONTAL |
| 2 | 7236.00 | 41.28 | 8.26 | 49.54 | 74.00 | -24.46 | Peak | HORIZONTAL |
| 4 | 9648.00 | --- | | | | | | HORIZONTAL |
| 5 | 12060.00 | --- | | | | | | HORIZONTAL |

Remark:

- 1 Measuring frequencies from the lowest internal frequency to the 10th of fundamental frequency
- 2 Field strength limits for frequency above 1000MHz are based on average limits. However, Peak mode field strength shall not exceed the average limits specified plus 20dB.
- 3 Measurement of data within this frequency range shown “ - ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- 4 Spectrum Peak mode IF bandwidth Setting : 1GHz- 26GHz, RBW= 1MHz, Sweep time= 200 ms., the VBW setting was 3 MHz.
- 5 Spectrum AV mode if bandwidth Setting : 1GHz- 26GHz, RBW= 1MHz, VBW= 10Hz, Sweep time= 200 ms.

Radiated Spurious Emission Measurement Result (above 1GHz) (Chip Antenna)

| | | | |
|-----------------------|-----------------------|-----------|------------|
| Operation Mode | 802.11n_20M TX CH Mid | Test Date | 2014/01/08 |
| Fundamental Frequency | 2437MHz | Test By | Lake |
| Temperature | 25 | Pol | Ver./Hor |
| Humidity | 60 % | | |

| No | Freq MHz | Reading dBuV | Factor dB | Level dBuV/m | Limit dBuV/m | Over Limit dB | Remark | Pol V/H |
|----|-------------|-----------------|--------------|-----------------|-----------------|---------------------|--------|------------|
| 1 | 4874.00 | 41.30 | 1.51 | 42.81 | 74.00 | -31.19 | Peak | VERTICAL |
| 2 | 7311.00 | 41.69 | 8.30 | 49.99 | 74.00 | -24.01 | Peak | VERTICAL |
| 3 | 9748.00 | --- | | | | | | VERTICAL |
| 4 | 12185.00 | --- | | | | | | VERTICAL |
| 1 | 1560.00 | 51.79 | -10.57 | 41.22 | 74.00 | -32.78 | Peak | HORIZONTAL |
| 2 | 4874.00 | 41.31 | 1.51 | 42.82 | 74.00 | -31.18 | Peak | HORIZONTAL |
| 3 | 7311.00 | --- | | | | | | HORIZONTAL |
| 4 | 9748.00 | --- | | | | | | HORIZONTAL |
| 5 | 12185.00 | --- | | | | | | HORIZONTAL |

Remark:

- 1 Measuring frequencies from the lowest internal frequency to the 10th of fundamental frequency
- 2 Field strength limits for frequency above 1000MHz are based on average limits. However, Peak mode field strength shall not exceed the average limits specified plus 20dB.
- 3 Measurement of data within this frequency range shown “ - ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- 4 Spectrum Peak mode IF bandwidth Setting : 1GHz- 26GHz, RBW= 1MHz, Sweep time= 200 ms., the VBW setting was 3 MHz.
- 5 Spectrum AV mode if bandwidth Setting : 1GHz- 26GHz, RBW= 1MHz, VBW= 10Hz, Sweep time= 200 ms.

Radiated Spurious Emission Measurement Result (above 1GHz) (Chip Antenna)

| | | | |
|-----------------------|------------------------|-----------|------------|
| Operation Mode | 802.11n_20M TX CH High | Test Date | 2014/01/08 |
| Fundamental Frequency | 2462MHz | Test By | Lake |
| Temperature | 25 | Pol | Ver./Hor |
| Humidity | 60 % | | |

| No | Freq MHz | Reading dBuV | Factor dB | Level dBuV/m | Limit dBuV/m | Over Limit dB | Remark | Pol V/H |
|----|-------------|-----------------|--------------|-----------------|-----------------|---------------------|--------|------------|
| 1 | 1973.00 | 52.89 | -8.06 | 44.83 | 74.00 | -29.17 | Peak | VERTICAL |
| 2 | 4924.00 | 42.08 | 1.68 | 43.76 | 74.00 | -30.24 | Peak | VERTICAL |
| 3 | 7386.00 | --- | | | | | | VERTICAL |
| 4 | 9848.00 | --- | | | | | | VERTICAL |
| 5 | 12310.00 | --- | | | | | | VERTICAL |
| | | | | | | | | |
| 1 | 1994.00 | 50.69 | -7.94 | 42.75 | 74.00 | -31.25 | Peak | HORIZONTAL |
| 2 | 4924.00 | 42.04 | 1.68 | 43.72 | 74.00 | -30.28 | Peak | HORIZONTAL |
| 3 | 7386.00 | --- | | | | | | HORIZONTAL |
| 4 | 9848.00 | --- | | | | | | HORIZONTAL |
| 5 | 12310.00 | --- | | | | | | HORIZONTAL |

Remark:

- 1 Measuring frequencies from the lowest internal frequency to the 10th of fundamental frequency
- 2 Field strength limits for frequency above 1000MHz are based on average limits. However, Peak mode field strength shall not exceed the average limits specified plus 20dB.
- 3 Measurement of data within this frequency range shown “ - ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- 4 Spectrum Peak mode IF bandwidth Setting : 1GHz- 26GHz, RBW= 1MHz, Sweep time= 200 ms., the VBW setting was 3 MHz.
- 5 Spectrum AV mode if bandwidth Setting : 1GHz- 26GHz, RBW= 1MHz, VBW= 10Hz, Sweep time= 200 ms.

Radiated Spurious Emission Measurement Result (below 1GHz) (Dipole Antenna)

Operation Mode 802.11b TX CH Low

Test Date 2014/01/08

Fundamental Frequency 2412MHz

Test By Lake

Temperature 25

Humidity 60 %

| No | Freq MHz | Reading dBuV | Factor dB | Level dBuV/m | Limit dBuV/m | Over Limit dB | Remark | Pol V/H |
|----|-------------|-----------------|--------------|-----------------|-----------------|---------------------|--------|------------|
| 1 | 95.96 | 49.48 | -17.86 | 31.62 | 43.50 | -11.88 | Peak | VERTICAL |
| 2 | 120.21 | 47.15 | -14.51 | 32.64 | 43.50 | -10.86 | Peak | VERTICAL |
| 3 | 143.49 | 46.34 | -12.34 | 34.00 | 43.50 | -9.50 | Peak | VERTICAL |
| 4 | 296.75 | 45.12 | -11.17 | 33.95 | 46.00 | -12.05 | Peak | VERTICAL |
| 5 | 455.83 | 40.32 | -8.12 | 32.20 | 46.00 | -13.80 | Peak | VERTICAL |
| 6 | 591.63 | 39.08 | -5.85 | 33.23 | 46.00 | -12.77 | Peak | VERTICAL |
| | | | | | | | | |
| 1 | 95.96 | 51.75 | -17.86 | 33.89 | 43.50 | -9.61 | Peak | HORIZONTAL |
| 2 | 119.24 | 51.59 | -14.61 | 36.98 | 43.50 | -6.52 | Peak | HORIZONTAL |
| 3 | 143.49 | 48.04 | -12.34 | 35.70 | 43.50 | -7.80 | Peak | HORIZONTAL |
| 4 | 191.99 | 50.60 | -14.69 | 35.91 | 43.50 | -7.59 | Peak | HORIZONTAL |
| 5 | 431.58 | 44.36 | -8.55 | 35.81 | 46.00 | -10.19 | Peak | HORIZONTAL |
| 6 | 740.04 | 33.91 | -3.15 | 30.76 | 46.00 | -15.24 | Peak | HORIZONTAL |

Remark:

- 1 No further spurious emissions detected from the lowest internal frequency and 30MHz.
- 2 Measuring frequencies from the lowest internal frequency to the 1GHz.
- 3 Radiated emissions measured in frequency range from 9MHz to 1000MHz were made with an instrument detector setting 9-90KHz/110-490KHz using PK/AV and other Frequency Band using PK/QP
- 4 Measurement result within this frequency range shown “ - ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- 5 The IF bandwidth of SPA between 9kHz to 30MHz was 10kHz, VBW= 30kHz; between 30MHz to 1GHz was 100KHz, VBW=300KHz.

Radiated Spurious Emission Measurement Result (below 1GHz) (Dipole Antenna)

Operation Mode 802.11b TX CH Mid

Test Date 2014/01/08

Fundamental Frequency 2437MHz

Test By Lake

Temperature 25

Humidity 60 %

| No | Freq MHz | Reading dBuV | Factor dB | Level dBuV/m | Limit dBuV/m | Over Limit dB | Remark | Pol V/H |
|----|-------------|-----------------|--------------|-----------------|-----------------|---------------------|--------|------------|
| 1 | 95.96 | 49.16 | -17.86 | 31.30 | 43.50 | -12.20 | Peak | VERTICAL |
| 2 | 120.21 | 48.60 | -14.51 | 34.09 | 43.50 | -9.41 | Peak | VERTICAL |
| 3 | 144.46 | 47.45 | -12.30 | 35.15 | 43.50 | -8.35 | Peak | VERTICAL |
| 4 | 296.75 | 44.59 | -11.17 | 33.42 | 46.00 | -12.58 | Peak | VERTICAL |
| 5 | 455.83 | 40.13 | -8.12 | 32.01 | 46.00 | -13.99 | Peak | VERTICAL |
| 6 | 666.32 | 34.51 | -4.72 | 29.79 | 46.00 | -16.21 | Peak | VERTICAL |
| | | | | | | | | |
| 1 | 120.21 | 51.47 | -14.51 | 36.96 | 43.50 | -6.54 | Peak | HORIZONTAL |
| 2 | 143.49 | 48.68 | -12.34 | 36.34 | 43.50 | -7.16 | Peak | HORIZONTAL |
| 3 | 191.99 | 51.05 | -14.69 | 36.36 | 43.50 | -7.14 | Peak | HORIZONTAL |
| 4 | 239.52 | 47.89 | -13.29 | 34.60 | 46.00 | -11.40 | Peak | HORIZONTAL |
| 5 | 431.58 | 43.32 | -8.55 | 34.77 | 46.00 | -11.23 | Peak | HORIZONTAL |
| 6 | 742.95 | 34.62 | -3.08 | 31.54 | 46.00 | -14.46 | Peak | HORIZONTAL |

Remark:

- 1 No further spurious emissions detected from the lowest internal frequency and 30MHz.
- 2 Measuring frequencies from the lowest internal frequency to the 1GHz.
- 3 Radiated emissions measured in frequency range from 9MHz to 1000MHz were made with an instrument detector setting 9-90KHz/110-490KHz using PK/AV and other Frequency Band using PK/QP
- 4 Measurement result within this frequency range shown “ - ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- 5 The IF bandwidth of SPA between 9kHz to 30MHz was 10kHz, VBW= 30kHz; between 30MHz to 1GHz was 100KHz, VBW=300KHz.

Radiated Spurious Emission Measurement Result (below 1GHz) (Dipole Antenna)

Operation Mode 802.11b TX CH High
Fundamental Frequency 2462MHz
Temperature 25

Test Date 2014/01/08
Test By Lake
Humidity 60 %

| No | Freq MHz | Reading dBuV | Factor dB | Level dBuV/m | Limit dBuV/m | Over Limit dB | Remark | Pol V/H |
|----|-------------|-----------------|--------------|-----------------|-----------------|---------------------|--------|------------|
| 1 | 95.96 | 48.96 | -17.86 | 31.10 | 43.50 | -12.40 | Peak | VERTICAL |
| 2 | 120.21 | 46.94 | -14.51 | 32.43 | 43.50 | -11.07 | Peak | VERTICAL |
| 3 | 144.46 | 47.17 | -12.30 | 34.87 | 43.50 | -8.63 | Peak | VERTICAL |
| 4 | 295.78 | 43.54 | -11.21 | 32.33 | 46.00 | -13.67 | Peak | VERTICAL |
| 5 | 665.35 | 35.14 | -4.74 | 30.40 | 46.00 | -15.60 | Peak | VERTICAL |
| 6 | 816.67 | 33.81 | -2.22 | 31.59 | 46.00 | -14.41 | Peak | VERTICAL |
| | | | | | | | | |
| 1 | 95.96 | 52.19 | -17.86 | 34.33 | 43.50 | -9.17 | Peak | HORIZONTAL |
| 2 | 120.21 | 52.30 | -14.51 | 37.79 | 43.50 | -5.71 | Peak | HORIZONTAL |
| 3 | 143.49 | 48.37 | -12.34 | 36.03 | 43.50 | -7.47 | Peak | HORIZONTAL |
| 4 | 191.02 | 50.73 | -14.66 | 36.07 | 43.50 | -7.43 | Peak | HORIZONTAL |
| 5 | 239.52 | 47.85 | -13.29 | 34.56 | 46.00 | -11.44 | Peak | HORIZONTAL |
| 6 | 432.55 | 43.53 | -8.54 | 34.99 | 46.00 | -11.01 | Peak | HORIZONTAL |

Remark:

- 1 No further spurious emissions detected from the lowest internal frequency and 30MHz.
- 2 Measuring frequencies from the lowest internal frequency to the 1GHz.
- 3 Radiated emissions measured in frequency range from 9MHz to 1000MHz were made with an instrument detector setting 9-90KHz/110-490KHz using PK/AV and other Frequency Band using PK/QP
- 4 Measurement result within this frequency range shown “ - ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- 5 The IF bandwidth of SPA between 9kHz to 30MHz was 10kHz, VBW= 30kHz; between 30MHz to 1GHz was 100KHz, VBW=300KHz.

Radiated Spurious Emission Measurement Result (below 1GHz) (Dipole Antenna)

Operation Mode 802.11g TX CH Low

Test Date 2014/01/08

Fundamental Frequency 2412MHz

Test By Lake

Temperature 25

Humidity 60 %

| No | Freq MHz | Reading dBuV | Factor dB | Level dBuV/m | Limit dBuV/m | Over Limit dB | Remark | Pol V/H |
|----|-------------|-----------------|--------------|-----------------|-----------------|---------------------|--------|------------|
| 1 | 95.96 | 49.67 | -17.86 | 31.81 | 43.50 | -11.69 | Peak | VERTICAL |
| 2 | 120.21 | 47.71 | -14.51 | 33.20 | 43.50 | -10.30 | Peak | VERTICAL |
| 3 | 143.49 | 47.19 | -12.34 | 34.85 | 43.50 | -8.65 | Peak | VERTICAL |
| 4 | 295.78 | 44.20 | -11.21 | 32.99 | 46.00 | -13.01 | Peak | VERTICAL |
| 5 | 455.83 | 40.73 | -8.12 | 32.61 | 46.00 | -13.39 | Peak | VERTICAL |
| 6 | 594.54 | 38.37 | -5.77 | 32.60 | 46.00 | -13.40 | Peak | VERTICAL |
| | | | | | | | | |
| 1 | 95.96 | 52.71 | -17.86 | 34.85 | 43.50 | -8.65 | Peak | HORIZONTAL |
| 2 | 120.21 | 51.71 | -14.51 | 37.20 | 43.50 | -6.30 | Peak | HORIZONTAL |
| 3 | 191.99 | 50.76 | -14.69 | 36.07 | 43.50 | -7.43 | Peak | HORIZONTAL |
| 4 | 239.52 | 47.67 | -13.29 | 34.38 | 46.00 | -11.62 | Peak | HORIZONTAL |
| 5 | 431.58 | 43.54 | -8.55 | 34.99 | 46.00 | -11.01 | Peak | HORIZONTAL |
| 6 | 593.57 | 39.22 | -5.80 | 33.42 | 46.00 | -12.58 | Peak | HORIZONTAL |

Remark:

- 1 No further spurious emissions detected from the lowest internal frequency and 30MHz.
- 2 Measuring frequencies from the lowest internal frequency to the 1GHz.
- 3 Radiated emissions measured in frequency range from 9MHz to 1000MHz were made with an instrument detector setting 9-90KHz/110-490KHz using PK/AV and other Frequency Band using PK/QP
- 4 Measurement result within this frequency range shown “ - ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- 5 The IF bandwidth of SPA between 9kHz to 30MHz was 10kHz, VBW= 30kHz; between 30MHz to 1GHz was 100KHz, VBW=300KHz.

Radiated Spurious Emission Measurement Result (below 1GHz) (Dipole Antenna)

| | | | |
|-----------------------|-------------------|-----------|------------|
| Operation Mode | 802.11g TX CH Mid | Test Date | 2014/01/08 |
| Fundamental Frequency | 2437MHz | Test By | Lake |
| Temperature | 25 | Pol | Ver./Hor |
| Humidity | 60 % | | |

| No | Freq MHz | Reading dBuV | Factor dB | Level dBuV/m | Limit dBuV/m | Over Limit dB | Remark | Pol V/H |
|----|-------------|-----------------|--------------|-----------------|-----------------|---------------------|--------|------------|
| 1 | 95.96 | 49.10 | -17.86 | 31.24 | 43.50 | -12.26 | Peak | VERTICAL |
| 2 | 120.21 | 46.45 | -14.51 | 31.94 | 43.50 | -11.56 | Peak | VERTICAL |
| 3 | 143.49 | 46.13 | -12.34 | 33.79 | 43.50 | -9.71 | Peak | VERTICAL |
| 4 | 296.75 | 44.03 | -11.17 | 32.86 | 46.00 | -13.14 | Peak | VERTICAL |
| 5 | 431.58 | 41.18 | -8.55 | 32.63 | 46.00 | -13.37 | Peak | VERTICAL |
| 6 | 813.76 | 35.34 | -2.27 | 33.07 | 46.00 | -12.93 | Peak | VERTICAL |
| | | | | | | | | |
| 1 | 95.96 | 52.54 | -17.86 | 34.68 | 43.50 | -8.82 | Peak | HORIZONTAL |
| 2 | 120.21 | 52.76 | -14.51 | 38.25 | 43.50 | -5.25 | Peak | HORIZONTAL |
| 3 | 191.99 | 50.98 | -14.69 | 36.29 | 43.50 | -7.21 | Peak | HORIZONTAL |
| 4 | 239.52 | 47.98 | -13.29 | 34.69 | 46.00 | -11.31 | Peak | HORIZONTAL |
| 5 | 431.58 | 43.86 | -8.55 | 35.31 | 46.00 | -10.69 | Peak | HORIZONTAL |
| 6 | 591.63 | 36.71 | -5.85 | 30.86 | 46.00 | -15.14 | Peak | HORIZONTAL |

Remark:

- 1 No further spurious emissions detected from the lowest internal frequency and 30MHz.
- 2 Measuring frequencies from the lowest internal frequency to the 1GHz.
- 3 Radiated emissions measured in frequency range from 9MHz to 1000MHz were made with an instrument detector setting 9-90KHz/110-490KHz using PK/AV and other Frequency Band using PK/QP
- 4 Measurement result within this frequency range shown “ - ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- 5 The IF bandwidth of SPA between 9kHz to 30MHz was 10kHz, VBW= 30kHz; between 30MHz to 1GHz was 100KHz, VBW=300KHz.

Radiated Spurious Emission Measurement Result (below 1GHz) (Dipole Antenna)

| | | | |
|-----------------------|--------------------|-----------|------------|
| Operation Mode | 802.11g TX CH High | Test Date | 2014/01/08 |
| Fundamental Frequency | 2462MHz | Test By | Lake |
| Temperature | 25 | Pol | Ver./Hor |
| Humidity | 60 % | | |

| No | Freq MHz | Reading dBuV | Factor dB | Level dBuV/m | Limit dBuV/m | Over Limit dB | Remark | Pol V/H |
|----|-------------|-----------------|--------------|-----------------|-----------------|---------------------|--------|------------|
| 1 | 95.96 | 49.32 | -17.86 | 31.46 | 43.50 | -12.04 | Peak | VERTICAL |
| 2 | 120.21 | 47.81 | -14.51 | 33.30 | 43.50 | -10.20 | Peak | VERTICAL |
| 3 | 144.46 | 46.46 | -12.30 | 34.16 | 43.50 | -9.34 | Peak | VERTICAL |
| 4 | 296.75 | 44.75 | -11.17 | 33.58 | 46.00 | -12.42 | Peak | VERTICAL |
| 5 | 455.83 | 40.48 | -8.12 | 32.36 | 46.00 | -13.64 | Peak | VERTICAL |
| 6 | 591.63 | 38.08 | -5.85 | 32.23 | 46.00 | -13.77 | Peak | VERTICAL |
| | | | | | | | | |
| 1 | 95.96 | 52.99 | -17.86 | 35.13 | 43.50 | -8.37 | Peak | HORIZONTAL |
| 2 | 120.21 | 51.47 | -14.51 | 36.96 | 43.50 | -6.54 | Peak | HORIZONTAL |
| 3 | 143.49 | 47.73 | -12.34 | 35.39 | 43.50 | -8.11 | Peak | HORIZONTAL |
| 4 | 191.99 | 51.21 | -14.69 | 36.52 | 43.50 | -6.98 | Peak | HORIZONTAL |
| 5 | 430.61 | 43.84 | -8.58 | 35.26 | 46.00 | -10.74 | Peak | HORIZONTAL |
| 6 | 740.04 | 33.01 | -3.15 | 29.86 | 46.00 | -16.14 | Peak | HORIZONTAL |

Remark:

- 1 No further spurious emissions detected from the lowest internal frequency and 30MHz.
- 2 Measuring frequencies from the lowest internal frequency to the 1GHz.
- 3 Radiated emissions measured in frequency range from 9MHz to 1000MHz were made with an instrument detector setting 9-90KHz/110-490KHz using PK/AV and other Frequency Band using PK/QP
- 4 Measurement result within this frequency range shown “ - ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- 5 The IF bandwidth of SPA between 9kHz to 30MHz was 10kHz, VBW= 30kHz; between 30MHz to 1GHz was 100KHz, VBW=300KHz.

Radiated Spurious Emission Measurement Result (below 1GHz) (Dipole Antenna)

| | | | |
|-----------------------|------------------------|-----------|------------|
| Operation Mode | 802.11 n_20M TX CH Low | Test Date | 2014/01/08 |
| Fundamental Frequency | 2412MHz | Test By | Lake |
| Temperature | 25 | Pol | Ver./Hor |
| Humidity | 60 % | | |

| No | Freq MHz | Reading dBuV | Factor dB | Level dBuV/m | Limit dBuV/m | Over Limit dB | Remark | Pol V/H |
|----|-------------|-----------------|--------------|-----------------|-----------------|---------------------|--------|------------|
| 1 | 95.96 | 49.44 | -17.86 | 31.58 | 43.50 | -11.92 | Peak | VERTICAL |
| 2 | 119.24 | 47.32 | -14.61 | 32.71 | 43.50 | -10.79 | Peak | VERTICAL |
| 3 | 143.49 | 46.20 | -12.34 | 33.86 | 43.50 | -9.64 | Peak | VERTICAL |
| 4 | 296.75 | 45.38 | -11.17 | 34.21 | 46.00 | -11.79 | Peak | VERTICAL |
| 5 | 333.61 | 45.80 | -10.48 | 35.32 | 46.00 | -10.68 | Peak | VERTICAL |
| 6 | 813.76 | 34.06 | -2.27 | 31.79 | 46.00 | -14.21 | Peak | VERTICAL |
| | | | | | | | | |
| 1 | 95.96 | 53.14 | -17.86 | 35.28 | 43.50 | -8.22 | Peak | HORIZONTAL |
| 2 | 120.21 | 53.01 | -14.51 | 38.50 | 43.50 | -5.00 | Peak | HORIZONTAL |
| 3 | 191.99 | 50.95 | -14.69 | 36.26 | 43.50 | -7.24 | Peak | HORIZONTAL |
| 4 | 239.52 | 48.78 | -13.29 | 35.49 | 46.00 | -10.51 | Peak | HORIZONTAL |
| 5 | 431.58 | 43.07 | -8.55 | 34.52 | 46.00 | -11.48 | Peak | HORIZONTAL |
| 6 | 742.95 | 34.13 | -3.08 | 31.05 | 46.00 | -14.95 | Peak | HORIZONTAL |

Remark:

- 1 No further spurious emissions detected from the lowest internal frequency and 30MHz.
- 2 Measuring frequencies from the lowest internal frequency to the 1GHz.
- 3 Radiated emissions measured in frequency range from 9MHz to 1000MHz were made with an instrument detector setting 9-90KHz/110-490KHz using PK/AV and other Frequency Band using PK/QP
- 4 Measurement result within this frequency range shown “ - ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- 5 The IF bandwidth of SPA between 9kHz to 30MHz was 10kHz, VBW= 30kHz; between 30MHz to 1GHz was 100KHz, VBW=300KHz.

Radiated Spurious Emission Measurement Result (below 1GHz) (Dipole Antenna)

| | | | |
|-----------------------|------------------------|-----------|------------|
| Operation Mode | 802.11 n_20M TX CH Mid | Test Date | 2014/01/08 |
| Fundamental Frequency | 2437MHz | Test By | Lake |
| Temperature | 25 | Pol | Ver./Hor |
| Humidity | 60 % | | |

| No | Freq MHz | Reading dBuV | Factor dB | Level dBuV/m | Limit dBuV/m | Over Limit dB | Remark | Pol V/H |
|----|-------------|-----------------|--------------|-----------------|-----------------|---------------------|--------|------------|
| 1 | 71.71 | 44.45 | -15.10 | 29.35 | 40.00 | -10.65 | Peak | VERTICAL |
| 2 | 95.96 | 49.40 | -17.86 | 31.54 | 43.50 | -11.96 | Peak | VERTICAL |
| 3 | 120.21 | 47.24 | -14.51 | 32.73 | 43.50 | -10.77 | Peak | VERTICAL |
| 4 | 143.49 | 47.00 | -12.34 | 34.66 | 43.50 | -8.84 | Peak | VERTICAL |
| 5 | 295.78 | 44.21 | -11.21 | 33.00 | 46.00 | -13.00 | Peak | VERTICAL |
| 6 | 455.83 | 40.85 | -8.12 | 32.73 | 46.00 | -13.27 | Peak | VERTICAL |
| | | | | | | | | |
| 1 | 95.96 | 51.04 | -17.86 | 33.18 | 43.50 | -10.32 | Peak | HORIZONTAL |
| 2 | 120.21 | 52.70 | -14.51 | 38.19 | 43.50 | -5.31 | Peak | HORIZONTAL |
| 3 | 144.46 | 47.68 | -12.30 | 35.38 | 43.50 | -8.12 | Peak | HORIZONTAL |
| 4 | 191.99 | 50.57 | -14.69 | 35.88 | 43.50 | -7.62 | Peak | HORIZONTAL |
| 5 | 431.58 | 42.98 | -8.55 | 34.43 | 46.00 | -11.57 | Peak | HORIZONTAL |
| 6 | 668.26 | 34.74 | -4.69 | 30.05 | 46.00 | -15.95 | Peak | HORIZONTAL |

Remark:

- 1 No further spurious emissions detected from the lowest internal frequency and 30MHz.
- 2 Measuring frequencies from the lowest internal frequency to the 1GHz.
- 3 Radiated emissions measured in frequency range from 9MHz to 1000MHz were made with an instrument detector setting 9-90KHz/110-490KHz using PK/AV and other Frequency Band using PK/QP
- 4 Measurement result within this frequency range shown “ - ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- 5 The IF bandwidth of SPA between 9kHz to 30MHz was 10kHz, VBW= 30kHz; between 30MHz to 1GHz was 100KHz, VBW=300KHz.

Radiated Spurious Emission Measurement Result (below 1GHz) (Dipole Antenna)

| | | | |
|-----------------------|-------------------------|-----------|------------|
| Operation Mode | 802.11 n_20M TX CH High | Test Date | 2014/01/08 |
| Fundamental Frequency | 2462MHz | Test By | Lake |
| Temperature | 25 | Pol | Ver./Hor |
| Humidity | 60 % | | |

| No | Freq MHz | Reading dBuV | Factor dB | Level dBuV/m | Limit dBuV/m | Over Limit dB | Remark | Pol V/H |
|----|-------------|-----------------|--------------|-----------------|-----------------|---------------------|--------|------------|
| 1 | 95.96 | 49.70 | -17.86 | 31.84 | 43.50 | -11.66 | Peak | VERTICAL |
| 2 | 120.21 | 47.34 | -14.51 | 32.83 | 43.50 | -10.67 | Peak | VERTICAL |
| 3 | 143.49 | 46.64 | -12.34 | 34.30 | 43.50 | -9.20 | Peak | VERTICAL |
| 4 | 295.78 | 44.47 | -11.21 | 33.26 | 46.00 | -12.74 | Peak | VERTICAL |
| 5 | 431.58 | 40.95 | -8.55 | 32.40 | 46.00 | -13.60 | Peak | VERTICAL |
| 6 | 816.67 | 33.49 | -2.22 | 31.27 | 46.00 | -14.73 | Peak | VERTICAL |
| | | | | | | | | |
| 1 | 95.96 | 53.28 | -17.86 | 35.42 | 43.50 | -8.08 | Peak | HORIZONTAL |
| 2 | 120.21 | 52.53 | -14.51 | 38.02 | 43.50 | -5.48 | Peak | HORIZONTAL |
| 3 | 144.46 | 48.18 | -12.30 | 35.88 | 43.50 | -7.62 | Peak | HORIZONTAL |
| 4 | 191.99 | 50.96 | -14.69 | 36.27 | 43.50 | -7.23 | Peak | HORIZONTAL |
| 5 | 431.58 | 44.09 | -8.55 | 35.54 | 46.00 | -10.46 | Peak | HORIZONTAL |
| 6 | 740.04 | 33.47 | -3.15 | 30.32 | 46.00 | -15.68 | Peak | HORIZONTAL |

Remark:

- 1 No further spurious emissions detected from the lowest internal frequency and 30MHz.
- 2 Measuring frequencies from the lowest internal frequency to the 1GHz.
- 3 Radiated emissions measured in frequency range from 9MHz to 1000MHz were made with an instrument detector setting 9-90KHz/110-490KHz using PK/AV and other Frequency Band using PK/QP
- 4 Measurement result within this frequency range shown “ - ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- 5 The IF bandwidth of SPA between 9kHz to 30MHz was 10kHz, VBW= 30kHz; between 30MHz to 1GHz was 100KHz, VBW=300KHz.

Radiated Spurious Emission Measurement Result (above 1GHz) (Dipole antenna)

Operation Mode 802.11b TX CH Low

Test Date 2014/01/08

Fundamental Frequency 2412MHz

Test By Lake

Temperature 25

Pol Ver.

Humidity 60 %

| No | Freq MHz | Reading dBuV | Factor dB | Level dBuV/m | Limit dBuV/m | Over Limit dB | Remark | Pol V/H |
|----|-------------|-----------------|--------------|-----------------|-----------------|---------------------|---------|------------|
| 1 | 4824.00 | 42.62 | 1.33 | 43.95 | 54.00 | -10.05 | Average | VERTICAL |
| 2 | 4824.00 | 52.81 | 1.33 | 54.14 | 74.00 | -19.86 | Peak | VERTICAL |
| 3 | 7236.00 | 43.37 | 8.26 | 51.63 | 74.00 | -22.37 | Peak | VERTICAL |
| 4 | 9648.00 | --- | | | | | | VERTICAL |
| 5 | 12060.00 | --- | | | | | | VERTICAL |
| | | | | | | | | |
| 1 | 4824.00 | 42.22 | 1.33 | 43.55 | 54.00 | -10.45 | Average | HORIZONTAL |
| 2 | 4824.00 | 54.30 | 1.33 | 55.63 | 74.00 | -18.37 | Peak | HORIZONTAL |
| 3 | 7236.00 | 41.93 | 8.26 | 50.19 | 74.00 | -23.81 | Peak | HORIZONTAL |
| 4 | 9648.00 | --- | | | | | | HORIZONTAL |
| 5 | 12060.00 | --- | | | | | | HORIZONTAL |

Remark:

- 1 Measuring frequencies from the lowest internal frequency to the 10th of fundamental frequency
- 2 Field strength limits for frequency above 1000MHz are based on average limits. However, Peak mode field strength shall not exceed the average limits specified plus 20dB.
- 3 Measurement of data within this frequency range shown “ - ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- 4 Spectrum Peak mode IF bandwidth Setting : 1GHz- 26GHz, RBW= 1MHz, Sweep time= 200 ms., the VBW setting was 3 MHz.
- 5 Spectrum AV mode if bandwidth Setting : 1GHz- 26GHz, RBW= 1MHz, VBW= 10Hz, Sweep time= 200 ms.

Radiated Spurious Emission Measurement Result (above 1GHz) (Dipole Antenna)

| | | | |
|-----------------------|-------------------|-----------|------------|
| Operation Mode | 802.11b TX CH Mid | Test Date | 2014/01/08 |
| Fundamental Frequency | 2437MHz | Test By | Lake |
| Temperature | 25 | Pol | Ver./Hor |
| Humidity | 60 % | | |

| No | Freq MHz | Reading dBuV | Factor dB | Level dBuV/m | Limit dBuV/m | Over Limit dB | Remark | Pol V/H |
|----|-------------|-----------------|--------------|-----------------|-----------------|---------------------|---------|------------|
| 1 | 4874.00 | 42.85 | 1.51 | 44.36 | 54.00 | -9.64 | Average | VERTICAL |
| 2 | 4874.00 | 54.11 | 1.51 | 55.62 | 74.00 | -18.38 | Peak | VERTICAL |
| 3 | 7311.00 | 42.65 | 8.30 | 50.95 | 74.00 | -23.05 | Peak | VERTICAL |
| 4 | 9748.00 | --- | | | | | | VERTICAL |
| 5 | 12185.00 | --- | | | | | | VERTICAL |
| | | | | | | | | |
| 1 | 4874.00 | 43.17 | 1.51 | 44.68 | 54.00 | -9.32 | Average | HORIZONTAL |
| 2 | 4874.00 | 54.76 | 1.51 | 56.27 | 74.00 | -17.73 | Peak | HORIZONTAL |
| 3 | 7311.00 | 41.82 | 8.30 | 50.12 | 74.00 | -23.88 | Peak | HORIZONTAL |
| 4 | 9748.00 | --- | | | | | | HORIZONTAL |
| 5 | 12185.00 | --- | | | | | | HORIZONTAL |

Remark:

- 1 Measuring frequencies from the lowest internal frequency to the 10th of fundamental frequency
- 2 Field strength limits for frequency above 1000MHz are based on average limits. However, Peak mode field strength shall not exceed the average limits specified plus 20dB.
- 3 Measurement of data within this frequency range shown “ - ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- 4 Spectrum Peak mode IF bandwidth Setting : 1GHz- 26GHz, RBW= 1MHz, Sweep time= 200 ms., the VBW setting was 3 MHz.
- 5 Spectrum AV mode if bandwidth Setting : 1GHz- 26GHz, RBW= 1MHz, VBW= 10Hz, Sweep time= 200 ms.

Radiated Spurious Emission Measurement Result (above 1GHz) (Dipole Antenna)

| | | | |
|-----------------------|--------------------|-----------|------------|
| Operation Mode | 802.11b TX CH High | Test Date | 2014/01/08 |
| Fundamental Frequency | 2462MHz | Test By | Lake |
| Temperature | 25 | Pol | Ver./Hor |
| Humidity | 60 % | | |

| No | Freq MHz | Reading dBuV | Factor dB | Level dBuV/m | Limit dBuV/m | Over Limit dB | Remark | Pol V/H |
|----|-------------|-----------------|--------------|-----------------|-----------------|---------------------|---------|------------|
| 1 | 1994.00 | 59.04 | -7.94 | 51.10 | 74.00 | -22.90 | Peak | VERTICAL |
| 2 | 4924.00 | 44.88 | 1.68 | 46.56 | 54.00 | -7.44 | Average | VERTICAL |
| 3 | 4924.00 | 55.26 | 1.68 | 56.94 | 74.00 | -17.06 | Peak | VERTICAL |
| 4 | 7386.00 | --- | | | | | | VERTICAL |
| 5 | 9848.00 | --- | | | | | | VERTICAL |
| 6 | 12310.00 | --- | | | | | | VERTICAL |
| | | | | | | | | |
| 1 | 1560.00 | 52.62 | -10.57 | 42.05 | 74.00 | -31.95 | Peak | HORIZONTAL |
| 2 | 4924.00 | 40.93 | 1.68 | 42.61 | 54.00 | -11.39 | Average | HORIZONTAL |
| 3 | 4924.00 | 55.64 | 1.68 | 57.32 | 74.00 | -16.68 | Peak | HORIZONTAL |
| 4 | 7386.00 | --- | | | | | | HORIZONTAL |
| 5 | 9848.00 | --- | | | | | | HORIZONTAL |
| 6 | 12310.00 | --- | | | | | | HORIZONTAL |

Remark:

- 1 Measuring frequencies from the lowest internal frequency to the 10th of fundamental frequency
- 2 Field strength limits for frequency above 1000MHz are based on average limits. However, Peak mode field strength shall not exceed the average limits specified plus 20dB.
- 3 Measurement of data within this frequency range shown “ - ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- 4 Spectrum Peak mode IF bandwidth Setting : 1GHz- 26GHz, RBW= 1MHz, Sweep time= 200 ms., the VBW setting was 3 MHz.
- 5 Spectrum AV mode if bandwidth Setting : 1GHz- 26GHz, RBW= 1MHz, VBW= 10Hz, Sweep time= 200 ms.

Radiated Spurious Emission Measurement Result (above 1GHz) (Dipole Antenna)

| | | | |
|-----------------------|-------------------|-----------|------------|
| Operation Mode | 802.11g TX CH Low | Test Date | 2014/01/08 |
| Fundamental Frequency | 2412MHz | Test By | Lake |
| Temperature | 25 | Pol | Ver./Hor |
| Humidity | 60 % | | |

| No | Freq MHz | Reading dBuV | Factor dB | Level dBuV/m | Limit dBuV/m | Over Limit dB | Remark | Pol V/H |
|----|-------------|-----------------|--------------|-----------------|-----------------|---------------------|--------|------------|
| 1 | 1980.00 | 54.71 | -8.02 | 46.69 | 74.00 | -27.31 | Peak | VERTICAL |
| 2 | 4824.00 | 47.72 | 1.33 | 49.05 | 74.00 | -24.95 | Peak | VERTICAL |
| 3 | 7236.00 | --- | | | | | | VERTICAL |
| 4 | 9648.00 | --- | | | | | | VERTICAL |
| 5 | 12060.00 | --- | | | | | | VERTICAL |
| | | | | | | | | |
| 1 | 1840.00 | 51.17 | -8.86 | 42.31 | 74.00 | -31.69 | Peak | HORIZONTAL |
| 2 | 4824.00 | 48.97 | 1.33 | 50.30 | 74.00 | -23.70 | Peak | HORIZONTAL |
| 3 | 7236.00 | --- | | | | | | HORIZONTAL |
| 4 | 9648.00 | --- | | | | | | HORIZONTAL |
| 5 | 12060.00 | --- | | | | | | HORIZONTAL |

Remark:

- 1 Measuring frequencies from the lowest internal frequency to the 10th of fundamental frequency
- 2 Field strength limits for frequency above 1000MHz are based on average limits. However, Peak mode field strength shall not exceed the average limits specified plus 20dB.
- 3 Measurement of data within this frequency range shown “ - ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- 4 Spectrum Peak mode IF bandwidth Setting : 1GHz- 26GHz, RBW= 1MHz, Sweep time= 200 ms., the VBW setting was 3 MHz.
- 5 Spectrum AV mode if bandwidth Setting : 1GHz- 26GHz, RBW= 1MHz, VBW= 10Hz, Sweep time= 200 ms.

Radiated Spurious Emission Measurement Result (above 1GHz) (Dipole Antenna)

| | | | |
|-----------------------|-------------------|-----------|------------|
| Operation Mode | 802.11g TX CH Mid | Test Date | 2014/01/08 |
| Fundamental Frequency | 2437MHz | Test By | Lake |
| Temperature | 25 | Pol | Ver./Hor |
| Humidity | 60 % | | |

| No | Freq MHz | Reading dBuV | Factor dB | Level dBuV/m | Limit dBuV/m | Over Limit dB | Remark | Pol V/H |
|----|-------------|-----------------|--------------|-----------------|-----------------|---------------------|--------|------------|
| 1 | 1994.00 | 56.05 | -7.94 | 48.11 | 74.00 | -25.89 | Peak | VERTICAL |
| 2 | 4874.00 | 47.25 | 1.51 | 48.76 | 74.00 | -25.24 | Peak | VERTICAL |
| 3 | 7311.00 | 42.68 | 8.30 | 50.98 | 74.00 | -23.02 | Peak | VERTICAL |
| 4 | 9748.00 | --- | | | | | | VERTICAL |
| 5 | 12185.00 | --- | | | | | | VERTICAL |
| | | | | | | | | |
| 1 | 1560.00 | 51.44 | -10.57 | 40.87 | 74.00 | -33.13 | Peak | HORIZONTAL |
| 2 | 4874.00 | 48.12 | 1.51 | 49.63 | 74.00 | -24.37 | Peak | HORIZONTAL |
| 3 | 7311.00 | 41.55 | 8.30 | 49.85 | 74.00 | -24.15 | Peak | HORIZONTAL |
| 4 | 9748.00 | --- | | | | | | HORIZONTAL |
| 5 | 12185.00 | --- | | | | | | HORIZONTAL |

Remark:

- 1 Measuring frequencies from the lowest internal frequency to the 10th of fundamental frequency
- 2 Field strength limits for frequency above 1000MHz are based on average limits. However, Peak mode field strength shall not exceed the average limits specified plus 20dB.
- 3 Measurement of data within this frequency range shown “ - ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- 4 Spectrum Peak mode IF bandwidth Setting : 1GHz- 26GHz, RBW= 1MHz, Sweep time= 200 ms., the VBW setting was 3 MHz.
- 5 Spectrum AV mode if bandwidth Setting : 1GHz- 26GHz, RBW= 1MHz, VBW= 10Hz, Sweep time= 200 ms.

Radiated Spurious Emission Measurement Result (above 1GHz) (Dipole Antenna)

| | | | |
|-----------------------|--------------------|-----------|------------|
| Operation Mode | 802.11g TX CH High | Test Date | 2014/01/08 |
| Fundamental Frequency | 2462MHz | Test By | Lake |
| Temperature | 25 | Pol | Ver./Hor |
| Humidity | 60 % | | |

| No | Freq MHz | Reading dBuV | Factor dB | Level dBuV/m | Limit dBuV/m | Over Limit dB | Remark | Pol V/H |
|----|-------------|-----------------|--------------|-----------------|-----------------|---------------------|--------|------------|
| 1 | 1994.00 | 55.53 | -7.94 | 47.59 | 74.00 | -26.41 | Peak | VERTICAL |
| 2 | 4924.00 | 48.17 | 1.68 | 49.85 | 74.00 | -24.15 | Peak | VERTICAL |
| 3 | 7386.00 | 42.81 | 8.35 | 51.16 | 74.00 | -22.84 | Peak | VERTICAL |
| 4 | 9848.00 | --- | | | | | | VERTICAL |
| 5 | 12310.00 | --- | | | | | | VERTICAL |
| | | | | | | | | |
| 1 | 1560.00 | 52.24 | -10.57 | 41.67 | 74.00 | -32.33 | Peak | HORIZONTAL |
| 2 | 4924.00 | 49.35 | 1.68 | 51.03 | 74.00 | -22.97 | Peak | HORIZONTAL |
| 3 | 7386.00 | --- | | | | | | HORIZONTAL |
| 4 | 9848.00 | --- | | | | | | HORIZONTAL |
| 5 | 12310.00 | --- | | | | | | HORIZONTAL |

Remark:

- 1 Measuring frequencies from the lowest internal frequency to the 10th of fundamental frequency
- 2 Field strength limits for frequency above 1000MHz are based on average limits. However, Peak mode field strength shall not exceed the average limits specified plus 20dB.
- 3 Measurement of data within this frequency range shown “ - ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- 4 Spectrum Peak mode IF bandwidth Setting : 1GHz- 26GHz, RBW= 1MHz, Sweep time= 200 ms., the VBW setting was 3 MHz.
- 5 Spectrum AV mode if bandwidth Setting : 1GHz- 26GHz, RBW= 1MHz, VBW= 10Hz, Sweep time= 200 ms.

Radiated Spurious Emission Measurement Result (above 1GHz) (Dipole Antenna)

| | | | |
|-----------------------|-----------------------|-----------|------------|
| Operation Mode | 802.11n_20M TX CH Low | Test Date | 2014/01/08 |
| Fundamental Frequency | 2412MHz | Test By | Lake |
| Temperature | 25 | Pol | Ver./Hor |
| Humidity | 60 % | | |

| No | Freq MHz | Reading dBuV | Factor dB | Level dBuV/m | Limit dBuV/m | Over Limit dB | Remark | Pol V/H |
|----|-------------|-----------------|--------------|-----------------|-----------------|---------------------|--------|------------|
| 1 | 1994.00 | 60.05 | -7.94 | 52.11 | 74.00 | -21.89 | Peak | VERTICAL |
| 2 | 4824.00 | 47.32 | 1.33 | 48.65 | 74.00 | -25.35 | Peak | VERTICAL |
| 3 | 7236.00 | --- | | | | | | VERTICAL |
| 4 | 9648.00 | --- | | | | | | VERTICAL |
| 5 | 12060.00 | --- | | | | | | VERTICAL |
| | | | | | | | | |
| 1 | 1959.00 | 47.68 | -8.15 | 39.53 | 74.00 | -34.47 | Peak | HORIZONTAL |
| 2 | 4824.00 | 47.48 | 1.33 | 48.81 | 74.00 | -25.19 | Peak | HORIZONTAL |
| 3 | 7236.00 | --- | | | | | | HORIZONTAL |
| 4 | 9648.00 | --- | | | | | | HORIZONTAL |
| 5 | 12060.00 | --- | | | | | | HORIZONTAL |

Remark:

- 1 Measuring frequencies from the lowest internal frequency to the 10th of fundamental frequency
- 2 Field strength limits for frequency above 1000MHz are based on average limits. However, Peak mode field strength shall not exceed the average limits specified plus 20dB.
- 3 Measurement of data within this frequency range shown “ - ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- 4 Spectrum Peak mode IF bandwidth Setting : 1GHz- 26GHz, RBW= 1MHz, Sweep time= 200 ms., the VBW setting was 3 MHz.
- 5 Spectrum AV mode if bandwidth Setting : 1GHz- 26GHz, RBW= 1MHz, VBW= 10Hz, Sweep time= 200 ms.

Radiated Spurious Emission Measurement Result (above 1GHz) (Dipole Antenna)

| | | | |
|-----------------------|-----------------------|-----------|------------|
| Operation Mode | 802.11n_20M TX CH Mid | Test Date | 2014/01/08 |
| Fundamental Frequency | 2437MHz | Test By | Lake |
| Temperature | 25 | Pol | Ver./Hor |
| Humidity | 60 % | | |

| No | Freq MHz | Reading dBuV | Factor dB | Level dBuV/m | Limit dBuV/m | Over Limit dB | Remark | Pol V/H |
|----|-------------|-----------------|--------------|-----------------|-----------------|---------------------|--------|------------|
| 1 | 1994.00 | 60.15 | -7.94 | 52.21 | 74.00 | -21.79 | Peak | VERTICAL |
| 2 | 4874.00 | 45.28 | 1.51 | 46.79 | 74.00 | -27.21 | Peak | VERTICAL |
| 3 | 7311.00 | --- | | | | | | VERTICAL |
| 4 | 9748.00 | --- | | | | | | VERTICAL |
| 5 | 12185.00 | --- | | | | | | VERTICAL |
| | | | | | | | | |
| 1 | 1560.00 | 49.68 | -10.57 | 39.11 | 74.00 | -34.89 | Peak | HORIZONTAL |
| 2 | 4874.00 | 46.98 | 1.51 | 48.49 | 74.00 | -25.51 | Peak | HORIZONTAL |
| 3 | 7311.00 | --- | | | | | | HORIZONTAL |
| 4 | 9748.00 | --- | | | | | | HORIZONTAL |
| 5 | 12185.00 | --- | | | | | | HORIZONTAL |

Remark:

- 1 Measuring frequencies from the lowest internal frequency to the 10th of fundamental frequency
- 2 Field strength limits for frequency above 1000MHz are based on average limits. However, Peak mode field strength shall not exceed the average limits specified plus 20dB.
- 3 Measurement of data within this frequency range shown “ - ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- 4 Spectrum Peak mode IF bandwidth Setting : 1GHz- 26GHz, RBW= 1MHz, Sweep time= 200 ms., the VBW setting was 3 MHz.
- 5 Spectrum AV mode if bandwidth Setting : 1GHz- 26GHz, RBW= 1MHz, VBW= 10Hz, Sweep time= 200 ms.

Radiated Spurious Emission Measurement Result (above 1GHz) (Dipole Antenna)

| | | | |
|-----------------------|------------------------|-----------|------------|
| Operation Mode | 802.11n_20M TX CH High | Test Date | 2014/01/08 |
| Fundamental Frequency | 2462MHz | Test By | Lake |
| Temperature | 25 | Pol | Ver./Hor |
| Humidity | 60 % | | |

| No | Freq MHz | Reading dBuV | Factor dB | Level dBuV/m | Limit dBuV/m | Over Limit dB | Remark | Pol V/H |
|----|-------------|-----------------|--------------|-----------------|-----------------|---------------------|--------|------------|
| 1 | 2078.00 | 53.63 | -7.74 | 45.89 | 74.00 | -28.11 | Peak | VERTICAL |
| 2 | 4924.00 | 46.50 | 1.68 | 48.18 | 74.00 | -25.82 | Peak | VERTICAL |
| 3 | 7386.00 | --- | | | | | | VERTICAL |
| 4 | 9848.00 | --- | | | | | | VERTICAL |
| 5 | 12310.00 | --- | | | | | | VERTICAL |
| | | | | | | | | |
| 1 | 1994.00 | 53.48 | -7.94 | 45.54 | 74.00 | -28.46 | Peak | HORIZONTAL |
| 2 | 4924.00 | 46.89 | 1.68 | 48.57 | 74.00 | -25.43 | Peak | HORIZONTAL |
| 3 | 7386.00 | --- | | | | | | HORIZONTAL |
| 4 | 9848.00 | --- | | | | | | HORIZONTAL |
| 5 | 12310.00 | --- | | | | | | HORIZONTAL |

Remark:

- 1 Measuring frequencies from the lowest internal frequency to the 10th of fundamental frequency
- 2 Field strength limits for frequency above 1000MHz are based on average limits. However, Peak mode field strength shall not exceed the average limits specified plus 20dB.
- 3 Measurement of data within this frequency range shown “ - ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- 4 Spectrum Peak mode IF bandwidth Setting : 1GHz- 26GHz, RBW= 1MHz, Sweep time= 200 ms., the VBW setting was 3 MHz.
- 5 Spectrum AV mode if bandwidth Setting : 1GHz- 26GHz, RBW= 1MHz, VBW= 10Hz, Sweep time= 200 ms.

Peak Power Spectral Density

9.7 Standard Applicable:

According to §15.247(e) For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of paragraph (b) of this section. The same method of determining the conducted output power shall be used to determine the power spectral density.

According to RSS-210 issue 8, §A8.2(b) and §A8.3(2), The transmitter power spectral density (into the antenna) shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission or over 1.0 second if the transmission exceeds 1.0 second duration.

9.8 Measurement Equipment Used:

Refer to section 6.2 for details.

9.9 Test Set-up:

Refer to section 6.3 for details.

9.10 Measurement Procedure:

1. Place the EUT on the table and set it in transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.
3. Set the spectrum analyzer as RBW =100KHz, VBW = 300KHz, Span =5 to 30% greater than emission BW, Sweep=Auto
4. Record the max. reading.
5. Repeat above procedures until all frequency measured were complete.

9.11 Measurement Result:

802.11b Mode

| Frequency MHz | Power Density Reading (dBm)/100KHz | Maximum Limit (dBm) |
|------------------|--|------------------------|
| 2412 | -7.02 | 8 |
| 2437 | -5.52 | 8 |
| 2462 | -5.87 | 8 |

802.11g Mode


| Frequency MHz | Power Density Reading (dBm)/100KHz | Maximum Limit (dBm) |
|------------------|--|------------------------|
| 2412 | -12.25 | 8 |
| 2437 | -11.39 | 8 |
| 2462 | -10.88 | 8 |

802.11n HT20 Mode


| Frequency MHz | Power Density Reading (dBm)/100KHz | Maximum Limit (dBm) |
|------------------|--|------------------------|
| 2412 | -13.16 | 8 |
| 2437 | -13.29 | 8 |
| 2462 | -13.46 | 8 |

802.11b

Power Spectral Density Test Plot (CH-Low)



Power Spectral Density Test Plot (CH-Mid)




Power Spectral Density Test Plot (CH-High)




802.11g


Power Spectral Density Test Plot (CH-Low)



Power Spectral Density Test Plot (CH-Mid)




Power Spectral Density Test Plot (CH-High)




802.11n_20M


Power Spectral Density Test Plot (CH-Low)



Power Spectral Density Test Plot (CH-Mid)



Power Spectral Density Test Plot (CH-High)



10 ANTENNA REQUIREMENT

10.1 Standard Applicable:

According to §15.203, Antenna requirement.

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of Sections 15.211, 15.213, 15.217, 15.219, or 15.221. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with Section 15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this Part are not exceeded.

According to RSS-GEN 7.1.2, a transmitter can only be sold or operated with antennas with which it was certified. A transmitter may be certified with multiple antenna types. An antenna type comprises antennas having similar in-band and out-of-band radiation patterns. Testing shall be performed using the highest-gain antenna of each combination of transmitter and antenna type for which certification is being sought, with the transmitter output power set at the maximum level. Any antenna of the same type and having equal or lesser gain as an antenna that had been successfully tested for certification with the transmitter, will also be considered certified with the transmitter, and may be used and marketed with the transmitter. The manufacturer shall include with the application for certification a list of acceptable antenna types to be used with the transmitter.

When a measurement at the antenna connector is used to determine RF output power, the effective gain of the device's antenna shall be stated, based on measurement or on data from the antenna manufacturer. Any antenna gain in excess of 6 dBi (6 dB above isotropic gain) shall be added to the measured RF output power before using the power limits specified in RSS-210 or RSS-310 for devices of RF output powers of 10 milliwatts or less. For devices of output powers greater than 10 milliwatts, except devices subject to RSS-210 Annex 8 (Frequency Hopping and Digital Modulation Systems Operating in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz Bands) or RSS-210 Annex 9 (Local Area Network Devices), the total antenna gain shall be added to the measured RF output power before using the specified power limits. For devices subject to RSS-210 Annex 8 or Annex 9, the antenna gain shall not be added.

10.2 Antenna Connected Construction:

The directional gains of antenna used for transmitting is 2 dBi, and the antenna connector is designed with unique type RF connector and no consideration of replacement. Please see EUT photo and antenna spec. for details.