

TEST REPORT

Applicant Name : ZHENGZHOU DEWENWILS NETWORK TECHNOLOGY CO., LTD
Address : No.2602, 26th Floor, Block B, Dongfang Building No. 198-19 Songshan
South Road, Erqi District, Zhengzhou, China
Report Number : RA230506-24402E-RF
FCC ID: 2A4G9-013

Test Standard (s)

FCC Part 15.247

Sample Description

Product: Wi-Fi Landscape Power Unit
Tested Model: TLA-60-12DW Wi-Fi
Trade Mark: 
Date Received: 2023-05-06
Date of Test: 2023-05-10 to 2023-06-07
Report Date: 2023-06-10

Test Result:	Pass*
--------------	-------

* In the configuration tested, the EUT complied with the standards above.

Prepared and Checked By:

Dave Liang

Dave Liang
EMC Engineer

Approved By:

Candy Li

Candy Li
EMC Engineer

Note: This report may contain data that are not covered by the A2LA accreditation and are marked with an asterisk "★".

Shenzhen Accurate Technology Co., Ltd. is not responsible for the authenticity of any test data provided by the applicant. Data included from the applicant that may affect test results are marked with an asterisk '*'. Customer model name, addresses, names, trademarks etc. are not considered data.

This report cannot be reproduced except in full, without prior written approval of the Company. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested. This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0.

Shenzhen Accurate Technology Co., Ltd.

1/F., Building A, Changyuan New Material Port, Science & Industry Park, Nanshan District, Shenzhen, Guangdong, P.R. China

Tel: +86 755-26503290

Fax: +86 755-26503290

Web: www.atc-lab.com

TABLE OF CONTENTS

DOCUMENT REVISION HISTORY	4
GENERAL INFORMATION.....	5
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT).....	5
OBJECTIVE	5
TEST METHODOLOGY	5
MEASUREMENT UNCERTAINTY	6
SYSTEM TEST CONFIGURATION.....	7
DESCRIPTION OF TEST CONFIGURATION	7
EQUIPMENT MODIFICATIONS	8
EUT EXERCISE SOFTWARE	8
DUTY CYCLE	8
SUPPORT EQUIPMENT LIST AND DETAILS	8
EXTERNAL I/O CABLE.....	8
BLOCK DIAGRAM OF TEST SETUP	9
SUMMARY OF TEST RESULTS	10
TEST EQUIPMENT LIST	11
FCC §1.1310 & §2.1091-RF EXPOSURE	12
TEST RESULT:	12
FCC §15.203-ANTENNA REQUIREMENT.....	13
APPLICABLE STANDARD	13
ANTENNA CONNECTOR CONSTRUCTION	13
FCC §15.207 (a)-AC LINE CONDUCTED EMISSIONS.....	14
APPLICABLE STANDARD	14
EUT SETUP	14
EMI TEST RECEIVER SETUP.....	14
TEST PROCEDURE	14
FACTOR & MARGIN CALCULATION	15
TEST DATA	15
FCC §15.209, §15.205 & §15.247(d) - SPURIOUS EMISSIONS.....	20
APPLICABLE STANDARD	20
EUT SETUP	20
EMI TEST RECEIVER & SPECTRUM ANALYZER SETUP	21
TEST PROCEDURE	21
FACTOR & MARGIN CALCULATION	21
TEST DATA	21
FCC §15.247(a) (2)-6 dB EMISSION BANDWIDTH & OCCUPIED BANDWIDTH	33
APPLICABLE STANDARD	33
TEST PROCEDURE	33
TEST DATA	33
FCC §15.247(b) (3)-MAXIMUM CONDUCTED OUTPUT POWER.....	34
APPLICABLE STANDARD	34
TEST PROCEDURE	34
TEST DATA	34
FCC §15.247(d)-100 kHz BANDWIDTH OF FREQUENCY BAND EDGE	35
APPLICABLE STANDARD	35
TEST PROCEDURE	35
TEST DATA	35

FCC §15.247(e)-POWER SPECTRAL DENSITY	36
APPLICABLE STANDARD	36
TEST PROCEDURE	36
TEST DATA	37
APPENDIX Wi-Fi.....	38
APPENDIX A: 6DB EMISSION BANDWIDTH.....	38
APPENDIX B: OCCUPIED CHANNEL BANDWIDTH	43
APPENDIX C: MAXIMUM CONDUCTED OUTPUT POWER.....	48
APPENDIX D: POWER SPECTRAL DENSITY	49
APPENDIX E: BAND EDGE MEASUREMENTS	54
APPENDIX F: DUTY CYCLE	57
APPENDIX BLE.....	62
APPENDIX A: 6dB EMISSION BANDWIDTH.....	62
APPENDIX B: OCCUPIED CHANNEL BANDWIDTH	64
APPENDIX C: MAXIMUM CONDUCTED PEAK OUTPUT POWER	66
APPENDIX D: POWER SPECTRAL DENSITY	68
APPENDIX E: BAND EDGE MEASUREMENTS	70
APPENDIX F: DUTY CYCLE	71

DOCUMENT REVISION HISTORY

Revision Number	Report Number	Description of Revision	Date of Revision
0	RA230506-24402E-RF	Original Report	2023-06-10

GENERAL INFORMATION

Product Description for Equipment under Test (EUT)

Product	Wi-Fi Landscape Power Unit	
Tested Model	TLA-60-12DW Wi-Fi	
Frequency Range	BLE: 2402-2480MHz Wi-Fi: 2412-2462MHz	
Maximum Conducted Peak Output Power	BLE 1M: 3.44dBm	
Maximum Conducted Average Output Power	Wi-Fi	
	13.46dBm(802.11b)	9.82dBm(802.11n20)
	10.08dBm(802.11g)	7.35dBm(802.11n40)
Modulation Technique	BLE: GFSK Wi-Fi: DSSS, OFDM	
Antenna Specification*	Internal Antenna: 2.49dBi(provided by the applicant)	
Voltage Range	AC120V 60Hz	
Sample serial number	RA230506-24402E-RF-S1(CE&RE) RA230506-24402E-RF-S2(RF Conducted Test) (Assigned by ATC, Shenzhen)	
Sample/EUT Status	Good condition	

Objective

This test report is in accordance with Part 2-Subpart J, Part 15-Subparts A and C of the Federal Communication Commission's rules.

The tests were performed in order to determine compliance with FCC Part 15, Subpart C, and section 15.203, 15.205, 15.207, 15.209 and 15.247 rules.

Test Methodology

All measurements contained in this report were conducted with ANSI C63.10-2013, American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices, and KDB 558074 D01 15.247 Meas Guidance v05r02.

All emissions measurement was performed at Shenzhen Accurate Technology Co., Ltd. The radiated testing was performed at an antenna-to-EUT distance of 3 meters.

Measurement Uncertainty

Parameter		Uncertainty
Occupied Channel Bandwidth		5%
RF Frequency		0.082×10^{-7}
RF output power, conducted		0.71dB
Unwanted Emission, conducted		1.6dB
AC Power Lines Conducted Emissions		2.74dB
Emissions, Radiated	30MHz - 1GHz	5.08dB
	1GHz - 18GHz	4.96dB
	18GHz - 26.5GHz	5.16dB
Temperature		1°C
Humidity		6%
Supply voltages		0.4%

Note: The extended uncertainty given in this report is obtained by combining the standard uncertainty times the coverage factor K with the 95% confidence interval. Otherwise required by the applicant or Product Regulations, Decision Rule in this report did not consider the uncertainty.

Test Facility

The test site used by Shenzhen Accurate Technology Co., Ltd. to collect test data is located on the Floor 1, KuMaKe Building, Dongzhou Community, Guangming Street, Guangming District, Shenzhen, Guangdong, China.

The test site has been approved by the FCC under the KDB 974614 D01 and is listed in the FCC Public Access Link (PAL) database, FCC Registration No.: 708358, the FCC Designation No.: CN1189.

Accredited by American Association for Laboratory Accreditation (A2LA). The Certificate Number is 4297.01.

The lab has been recognized by Innovation, Science and Economic Development Canada to test to Canadian radio equipment requirements, the CAB identifier: CN0016. The Registration Number is 30241.

SYSTEM TEST CONFIGURATION

Description of Test Configuration

For 2.4GHz Wi-Fi mode, total 11channels are provided to testing:

Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	2412	7	2442
2	2417	8	2447
3	2422	9	2452
4	2427	10	2457
5	2432	11	2462
6	2437	/	/

802.11b, 802.11g and 802.11n-HT20 mode was tested with Channel 1, 6 and 11.
802.11n-HT40 mode was tested with Channel 3, 6 and 9.

For BLE mode, 40 channels are provided to testing:

Channel	Frequency (MHz)	Channel	Frequency (MHz)
0	2402	20	2442
1	2404	21	2444
2	2406	22	2446
3	2408	23	2448
4	2410	24	2450
5	2412	25	2452
6	2414	26	2454
7	2416	27	2456
8	2418	28	2458
9	2420	29	2460
10	2422	30	2462
11	2424	31	2464
12	2426	32	2466
13	2428	33	2468
14	2430	34	2470
15	2432	35	2472
16	2434	36	2474
17	2436	37	2476
18	2438	38	2478
19	2440	39	2480

EUT was tested with Channel 0, 19 and 39.

Equipment Modifications

No modification was made to the EUT tested.

EUT Exercise Software

Software “WiFi Test Tool v1.6.0”* was used during testing and power level as below, which provided by manufacturer.

Mode	Data Rate	Power Level*		
		Low Channel	Middle Channel	High Channel
802.11 b	1Mbps	18	18	18
802.11 g	6 Mbps	32	32	32
802.11 n20	MCS0	32	32	32
802.11 n40	MCS0	26	26	26
BLE	1 Mbps	8	8	8

The worse-case data rates are determined to be as above for each mode based upon investigations by measuring the output power and PSD across all data rates, bandwidths and modulations.

Duty cycle

Test Result: Compliant. Please refer to the Appendix Wi-Fi and Appendix BLE.

Support Equipment List and Details


Manufacturer	Description	Model	Serial Number
Unknown	Resistor (Full Load for Testing)	Unknown	Unknown

External I/O Cable


Cable Description	Length(m)	From/Port	To
electric wire	0.8	EUT	Resistor
power cords	1.8	LISN	EUT

Block Diagram of Test Setup

For Conducted Emission



For Radiated Emission



SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Result
FCC §1.1310 & §2.1091	RF Exposure	Compliant
§15.203	Antenna Requirement	Compliant
§15.207 (a)	AC Line Conducted Emissions	Compliant
§15.205, §15.209, §15.247(d)	Spurious Emissions	Compliant
§15.247 (a)(2)	6 dB Emission Bandwidth & Occupied Bandwidth	Compliant
§15.247(b)(3)	Maximum Conducted Output Power	Compliant
§15.247(d)	100 kHz Bandwidth of Frequency Band Edge	Compliant
§15.247(e)	Power Spectral Density	Compliant

TEST EQUIPMENT LIST

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Conducted Emission Test					
Rohde & Schwarz	EMI Test Receiver	ESCI	100784	2022/11/25	2023/11/24
Rohde & Schwarz	L.I.S.N.	ENV216	101314	2022/11/25	2023/11/24
Anritsu Corp	50 Coaxial Switch	MP59B	6100237248	2022/12/07	2023/12/06
Unknown	RF Coaxial Cable	No.17	N0350	2022/11/25	2023/11/24
Conducted Emission Test Software: e3 191218 (V9)					
Radiated Emissions Test					
Rohde & Schwarz	Test Receiver	ESR	102725	2022/11/25	2023/11/24
Rohde & Schwarz	Spectrum Analyzer	FSV40	101949	2022/11/25	2023/11/24
SONOMA INSTRUMENT	Amplifier	310 N	186131	2022/11/08	2023/11/07
A.H. Systems, inc.	Preamplifier	PAM-0118P	135	2022/11/08	2023/11/07
Quinstar	Amplifier	QLW-184055 36-J0	15964001002	2022/11/08	2023/11/07
Schwarzbeck	Bilog Antenna	VULB9163	9163-194	2023/02/14	2026/02/13
Schwarzbeck	Horn Antenna	BBHA9120D	837	2023/02/22	2026/02/21
Schwarzbeck	HORN ANTENNA	BBHA9170	9170-359	2022/12/26	2025/12/25
Unknown	RF Coaxial Cable	No.10	N050	2022/11/25	2023/11/24
Unknown	RF Coaxial Cable	No.11	N1000	2022/11/25	2023/11/24
Unknown	RF Coaxial Cable	No.12	N040	2022/11/25	2023/11/24
Unknown	RF Coaxial Cable	No.13	N300	2022/11/25	2023/11/24
Unknown	RF Coaxial Cable	No.14	N800	2022/11/25	2023/11/24
Unknown	RF Coaxial Cable	No.15	N600	2022/11/25	2023/11/24
Unknown	RF Coaxial Cable	No.16	N650	2022/11/25	2023/11/24
Wainwright	High Pass Filter	WHKX3.6/18 G-10SS	5	2022/11/25	2023/11/24
Radiated Emission Test Software: e3 191218 (V9)					
RF Conducted Test					
Rohde & Schwarz	Spectrum Analyzer	FSV-40	101495	2022/11/25	2023/11/24
Agilent	USB wideband power sensor	U2021XA	MY54250003	2022/6/27	2023/06/26
Rohde & Schwarz	Open Switch and Control Unit	OSP120 + OSP-B157	101244 + 100866	2022/11/25	2023/11/24
WEINSCHTEL	10dB Attenuator	5324	AU 3842	2022/11/25	2023/11/24
Unknown	RF Coaxial Cable	No.31	RF-03	Each time	

*** Statement of Traceability:** Shenzhen Accurate Technology Co., Ltd. attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

FCC §1.1310 & §2.1091-RF EXPOSURE

Applicable Standard

According to KDB 447498 D04 Interim General RF Exposure Guidance v01, clause 2.1.4 –MPE-Based Exemption:

An alternative to the SAR-based exemption is provided in § 1.1307(b)(3)(i)(C), for a much wider frequency range, from 300 kHz to 100 GHz, applicable for separation distances greater or equal to $\lambda/2\pi$, where λ is the free-space operating wavelength in meters. The MPE-based test exemption condition is in terms of ERP, defined as the product of the maximum antenna gain and the delivered maximum time-averaged power. For this case, a RF source is an RF exempt device if its ERP (watts) is no more than a frequency-dependent value, as detailed tabular form in Appendix B. These limits have been derived based on the basic specifications on Maximum Permissible Exposure (MPE) considered for the FCC rules in § 1.1310(e)(1).

Table to § 1.1307(b)(3)(i)(C) - Single RF Sources Subject to Routine Environmental Evaluation

RF Source frequency (MHz)	Threshold ERP (watts)
0.3-1.34	$1,920 R^2$.
1.34-30	$3,450 R^2/f^2$.
30-300	$3.83 R^2$.
300-1,500	$0.0128 R^2 f$.
1,500-100,000	$19.2 R^2$.

f = frequency in MHz;

R = minimum separation distance from the body of a nearby person (appropriate units, e.g., m);

Test Result:

For worst case:

Mode	Frequency Range (MHz)	Tune-up Output Power		Antenna Gain		ERP		Evaluation Distance (cm)	ERP Limit (mW)
		(dBm)	(mW)	(dBi)	(dBd)	(dBm)	(mW)		
BLE	2402-2480	3.5	2.24	2.49	0.34	3.84	2.42	20	768
2.4G WIFI	2412-2462	13.5	22.39	2.49	0.34	13.84	24.21	20	768

Note 1: The tune-up power was declared by the applicant.

Note 2: 0dBd=2.15dBi.

Note 3: the BT and Wi-Fi cannot transmit at same time.

To maintain compliance with the FCC's RF exposure guidelines, place the equipment at least 20cm from nearby persons.

Result: Compliant.

FCC §15.203-ANTENNA REQUIREMENT

Applicable Standard

According to § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the user of a standard antenna jack or electrical connector is prohibited. The structure and application of the EUT were analyzed to determine compliance with section §15.203 of the rules. §15.203 state that the subject device must meet the following criteria:

- a. Antenna must be permanently attached to the unit.
- b. Antenna must use a unique type of connector to attach to the EUT.
- c. Unit must be professionally installed, and installer shall be responsible for verifying that the correct antenna is employed with the unit.

And according to FCC 47 CFR section 15.247 (b), if the transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

Antenna Connector Construction

The EUT has one internal antenna arrangement, which was permanently attached and the antenna gain is 2.49dBi, fulfill the requirement of this section. Please refer to the EUT photos.


Result: Compliant.

FCC §15.207 (a)-AC LINE CONDUCTED EMISSIONS

Applicable Standard

FCC§15.207

EUT Setup



Note: 1. Support units were connected to second LISN.
2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

The setup of EUT is according with per ANSI C63.10-2013 measurement procedure. The specification used was with the FCC Part 15.207 limits.

The spacing between the peripherals was 10 cm.

EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

Frequency Range	IF B/W
150 kHz – 30 MHz	9 kHz

Test Procedure

During the conducted emission test, the adapter was connected to the outlet of the LISN.

Maximizing procedure was performed on the six (6) highest emissions of the EUT.

All final data was recorded in the Quasi-peak and average detection mode.

Factor & Margin Calculation

The factor is calculated by adding LISN VDF (Voltage Division Factor) and Cable Loss. The basic equation is as follows:

$$\text{Factor} = \text{LISN VDF} + \text{Cable Loss}$$

The “**Over limit**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, an Over limit of -7 dB means the emission is 7 dB below the limit. The equation for calculation is as follows:

$$\begin{aligned}\text{Over Limit} &= \text{Level} - \text{Limit} \\ \text{Level} &= \text{Read Level} + \text{Factor}\end{aligned}$$


Test Data

Environmental Conditions

Temperature:	23-26°C
Relative Humidity:	49-53%
ATM Pressure:	101.0 kPa

The testing was performed by Jerry Wu on 2023-05-10 and 2023-06-07.


EUT operation mode: Transmitting

BLE: (Worst case for Middle channel)**AC 120V/60 Hz, Line**

Site : Shielding Room
 Condition: Line
 Job No. : RA230506-24402E-RF
 Mode : BLE Transmitting
 Power : AC 120V 60Hz


	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dBuV	dBuV	dBuV	dB	
1	0.169	10.28	30.28	40.56	54.99	-14.43	Average
2	0.169	10.28	41.11	51.39	64.99	-13.60	QP
3	0.202	10.29	26.05	36.34	53.52	-17.18	Average
4	0.202	10.29	36.57	46.86	63.52	-16.66	QP
5	0.360	10.33	18.59	28.92	48.72	-19.80	Average
6	0.360	10.33	26.96	37.29	58.72	-21.43	QP
7	0.530	10.41	16.35	26.76	46.00	-19.24	Average
8	0.530	10.41	25.21	35.62	56.00	-20.38	QP
9	1.062	10.36	23.71	34.07	46.00	-11.93	Average
10	1.062	10.36	33.64	44.00	56.00	-12.00	QP
11	7.930	10.52	21.21	31.73	50.00	-18.27	Average
12	7.930	10.52	22.93	33.45	60.00	-26.55	QP

AC 120V/60 Hz, Neutral



Site : Shielding Room
 Condition: Neutral
 Job No. : RA230506-24402E-RF
 Mode : BLE Transmitting
 Power : AC 120V 60Hz


	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dBuV	dBuV	dBuV	dB	
1	0.154	10.28	35.01	45.29	55.81	-10.52	Average
2	0.154	10.28	43.40	53.68	65.81	-12.13	QP
3	0.202	10.39	27.12	37.51	53.53	-16.02	Average
4	0.202	10.39	34.50	44.89	63.53	-18.64	QP
5	0.375	10.37	23.18	33.55	48.39	-14.84	Average
6	0.375	10.37	28.97	39.34	58.39	-19.05	QP
7	1.062	10.38	19.73	30.11	46.00	-15.89	Average
8	1.062	10.38	27.40	37.78	56.00	-18.22	QP
9	2.655	10.54	20.84	31.38	46.00	-14.62	Average
10	2.655	10.54	20.91	31.45	56.00	-24.55	QP
11	7.872	10.58	22.92	33.50	50.00	-16.50	Average
12	7.872	10.58	23.04	33.62	60.00	-26.38	QP

2.4G WIFI: (worst case 802.11b, Middle channel)**AC 120V/60 Hz, Line**

Site : Shielding Room
 Condition: Line
 Job No. : RA230506-24402E-RF
 Mode : 2.4G WIFI Transmitting
 Power : AC 120V 60Hz

	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dBuV	dBuV	dBuV	dB	
1	0.169	10.28	29.01	39.29	54.99	-15.70	Average
2	0.169	10.28	41.53	51.81	64.99	-13.18	QP
3	0.217	10.29	20.77	31.06	52.93	-21.87	Average
4	0.217	10.29	30.33	40.62	62.93	-22.31	QP
5	0.360	10.33	15.96	26.29	48.72	-22.43	Average
6	0.360	10.33	25.50	35.83	58.72	-22.89	QP
7	1.062	10.36	25.27	35.63	46.00	-10.37	Average
8	1.062	10.36	25.40	35.76	56.00	-20.24	QP
9	2.652	10.46	18.39	28.85	46.00	-17.15	Average
10	2.652	10.46	19.07	29.53	56.00	-26.47	QP
11	7.930	10.52	15.88	26.40	50.00	-23.60	Average
12	7.930	10.52	20.55	31.07	60.00	-28.93	QP

AC 120V/60 Hz, Neutral



Site : Shielding Room
Condition: Neutral
Job No. : RA230506-24402E-RF
Mode : 2.4G WIFI Transmitting
Power : AC 120V 60Hz


	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dBuV	dBuV	dBuV	dB	
1	0.154	10.28	32.07	42.35	55.81	-13.46	Average
2	0.154	10.28	44.60	54.88	65.81	-10.93	QP
3	0.214	10.38	20.48	30.86	53.04	-22.18	Average
4	0.214	10.38	32.29	42.67	63.04	-20.37	QP
5	0.375	10.37	17.60	27.97	48.39	-20.42	Average
6	0.375	10.37	27.38	37.75	58.39	-20.64	QP
7	1.062	10.38	25.74	36.12	46.00	-9.88	Average
8	1.062	10.38	26.01	36.39	56.00	-19.61	QP
9	2.124	10.58	20.63	31.21	46.00	-14.79	Average
10	2.124	10.58	21.38	31.96	56.00	-24.04	QP
11	7.872	10.58	16.32	26.90	50.00	-23.10	Average
12	7.872	10.58	20.68	31.26	60.00	-28.74	QP

FCC §15.209, §15.205 & §15.247(d) - SPURIOUS EMISSIONS**Applicable Standard**


FCC §15.247 (d); §15.209; §15.205;

EUT Setup

Below 1 GHz:



Above 1GHz:



The radiated emission tests were performed in the 3 meters test site, using the setup accordance with the ANSI C63.10-2013. The specification used was the FCC 15.209, and FCC 15.247 limits.

EMI Test Receiver & Spectrum Analyzer Setup

During the radiated emission test, the EMI test receiver & Spectrum Analyzer Setup were set with the following configurations:

Frequency Range	RBW	Video B/W	IF B/W	Measurement
30 MHz – 1000 MHz	100 kHz	300 kHz	120 kHz	QP
Above 1 GHz	1MHz	3 MHz	/	PK
	1MHz	10 Hz ^{Note 1}	/	Average
	1MHz	> 1/T ^{Note 2}	/	Average

Note 1: when duty cycle is no less than 98%

Note 2: when duty cycle is less than 98%

If the maximized peak measured value complies with the limit, then it is unnecessary to perform QP/Average measurement.

Test Procedure

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

Data was recorded in Quasi-peak detection mode for frequency range of 30 MHz-1 GHz, peak and Average detection modes for frequencies above 1 GHz.

Factor & Margin Calculation

The Factor is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain. The basic equation is as follows:

$$\text{Factor} = \text{Antenna Factor} + \text{Cable Loss} - \text{Amplifier Gain}$$

The “**Over Limit/Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, an Over Limit/margin of -7dB means the emission is 7dB below the limit. The equation for calculation is as follows:

$$\begin{aligned} \text{Over Limit/Margin} &= \text{Level} / \text{Corrected Amplitude} - \text{Limit} \\ \text{Level} / \text{Corrected Amplitude} &= \text{Read Level} + \text{Factor} \end{aligned}$$


Test Data

Environmental Conditions

Temperature:	23-24 °C
Relative Humidity:	54-56 %
ATM Pressure:	101.0 kPa

The Below 1G testing was performed by Jason Liu and Jimi Zheng on 2023-05-13 and 2023-06-07.
The Above 1G testing was performed by Jeef Huang on 2023-05-29 and 2023-06-06.

EUT operation mode: Transmitting (Pre-scan in the X, Y and Z axes of orientation, the worst case X-axis of orientation was recorded)

30MHz-1GHz:**BLE (worst case, Middle channel)****Horizontal**

Site : chamber


Condition: 3m HORIZONTAL

Job No. : RA230506-24402E-RF

Test Mode: BLE Transmitting


	Freq Factor		Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	34.517	-11.69	30.70	19.01	40.00	-20.99	Peak
2	59.911	-10.58	28.40	17.82	40.00	-22.18	Peak
3	129.411	-14.84	35.59	20.75	43.50	-22.75	Peak
4	187.096	-11.93	41.24	29.31	43.50	-14.19	Peak
5	291.930	-9.29	37.00	27.71	46.00	-18.29	Peak
6	414.904	-6.23	45.30	39.07	46.00	-6.93	QP

Vertical



Site : chamber
Condition: 3m VERTICAL
Job No. : RA230506-24402E-RF
Test Mode: BLE Transmitting

	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	36.143	-11.17	39.07	27.90	40.00	-12.10	Peak
2	76.311	-16.45	42.37	25.92	40.00	-14.08	Peak
3	165.995	-13.98	37.40	23.42	43.50	-20.08	Peak
4	188.083	-11.81	38.23	26.42	43.50	-17.08	Peak
5	405.199	-6.71	46.63	39.92	46.00	-6.08	Peak
6	787.161	-0.07	29.08	29.01	46.00	-16.99	Peak

2.4G WIFI (worst case 802.11b, Middle channel)**Horizontal**

Site : chamber


Condition: 3m HORIZONTAL

Job No. : RA230506-24402E-RF

Test Mode: 2.4G WIFI Transmitting

	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	94.098	-12.67	33.37	20.70	43.50	-22.80	Peak
2	175.344	-13.10	40.17	27.07	43.50	-16.43	Peak
3	206.488	-11.84	38.71	26.87	43.50	-16.63	Peak
4	266.843	-10.37	37.79	27.42	46.00	-18.58	Peak
5	387.822	-6.96	50.80	43.84	46.00	-2.16	QP
6	404.844	-6.73	49.10	42.37	46.00	-3.63	QP

Vertical



Site : chamber
Condition: 3m VERTICAL
Job No. : RA230506-24402E-RF
Test Mode: 2.4G WIFI Transmitting

	Freq	Factor	Read Level	Level	Limit	Over	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	42.956	-9.96	41.71	31.75	40.00	-8.25	Peak
2	66.938	-13.32	41.77	28.45	40.00	-11.55	Peak
3	92.260	-13.22	43.57	30.35	43.50	-13.15	Peak
4	175.114	-13.11	45.99	32.88	43.50	-10.62	Peak
5	197.546	-11.55	45.57	34.02	43.50	-9.48	Peak
6	386.803	-7.00	45.23	38.23	46.00	-7.77	Peak

1-25 GHz:**BLE:**

Frequency (MHz)	Receiver		Turntable Angle	Rx Antenna		Factor (dB/m)	Absolute Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)
	Reading (dBuV)	PK/AV	Degree	Height	Polar				
				(m)	(H/V)				
BLE 1M, Low Channel									
2310	45.95	PK	166	2.0	H	-10.36	35.59	74	-38.41
2310	48.24	PK	86	1.4	V	-10.36	37.88	74	-36.12
2390	55.07	PK	280	1.7	H	-10.71	44.36	74	-29.64
2390	64.48	PK	340	1.8	V	-10.71	53.77	74	-20.23
4804	47.52	PK	239	2.2	H	-6.11	41.41	74	-32.59
4804	48.16	PK	100	1.8	V	-6.11	42.05	74	-31.95
BLE 1M, Middle Channel									
4880	48.75	PK	122	1.3	H	-5.9	42.85	74	-31.15
4880	48.85	PK	197	1.9	V	-5.9	42.95	74	-31.05
BLE 1M, High Channel									
2483.5	63.39	PK	177	1.8	H	-10.55	52.84	74	-21.16
2483.5	56.56	PK	121	1.8	V	-10.55	46.01	74	-27.99
2500	60.11	PK	274	1.3	H	-10.42	49.69	74	-24.31
2500	49.33	PK	354	1.2	V	-10.42	38.91	74	-35.09
4960	47.58	PK	141	1.8	H	-5.47	42.11	74	-31.89
4960	48.06	PK	356	1.9	V	-5.47	42.59	74	-31.41

Wi-Fi:

Freque ncy (MHz)	Receiver		Turntable Angle Degree	Rx Antenna		Factor (dB/m)	Absolute Level (dBuV/m)	Limit (dBuV/ m)	Margin (dB)
	Reading (dBuV)	PK/Ave		Height (m)	Polar (H/V)				
802.11B, Low Channel									
2310	56.28	PK	280	1.1	H	-10.36	45.92	74	-28.08
2310	55.07	PK	228	1.2	V	-10.36	44.71	74	-29.29
2387.25	71.67	PK	129	1.5	H	-1071	60.96	74	-13.04
2387.25	58.01	AV	129	1.5	H	-10.71	47.30	54	-6.70
2390	65.38	PK	30	1.1	H	-1071	53.61	74	-20.39
2390	58.52	PK	147	1.0	V	-10.71	47.81	74	-26.19
4824	53.26	PK	147	1.0	H	-6.11	47.15	74	-26.85
4824	42.61	PK	321	2.1	V	-6.11	36.50	74	-37.50
802.11B, Middle Channel									
4874	58.2	PK	112	1.6	H	-5.94	52.32	74	-21.68
4874	54.6	PK	63	1.3	V	-5.94	48.72	74	-25.28

Frequency (MHz)	Receiver		Turntable Angle Degree	Rx Antenna		Factor (dB/m)	Absolute Level (dBuV/m)	Limit (dBuV/ m)	Margin (dB)
	Reading (dBuV)	PK/Ave		Height (m)	Polar (H/V)				
11B, High Channel									
2483.5	66.53	PK	173	1.9	H	-10.46	56.07	74	-17.93
2483.5	53.26	AV	173	1.9	H	-10.46	42.80	54	-11.20
2483.5	57.03	PK	297	1.3	V	-10.46	46.57	74	-27.43
2500	59.99	PK	33	1.1	H	-10.45	49.54	74	-24.46
2500	56	PK	271	1.7	V	-10.45	45.55	74	-28.45
2485.46	73.86	PK	264	1.1	H	-10.32	63.54	74	-10.46
2485.46	59.43	AV	264	1.1	H	-10.32	49.11	54	-4.89
4924	50.14	PK	264	1.1	H	-5.67	44.57	74	-29.43
4924	50.14	PK	84	2.0	V	-5.67	44.57	74	-29.43
802.11G, Low Channel									
2310	55.94	PK	201	1.5	H	-10.36	45.58	74	-28.42
2310	55.76	PK	255	1.5	V	-10.36	45.40	74	-28.60
2390	78.96	PK	43	1.5	H	-10.71	68.25	74	-5.75
2390	80.39	AV	43	1.5	H	-10.71	49.68	54	-4.32
2390	66.02	PK	226	1.1	V	-10.71	55.31	74	-18.69
2390	71.98	AV	226	1.1	V	-10.71	61.27	74	-12.73
4824	47.55	PK	101	2.0	H	-6.11	41.44	74	-32.56
4824	48.62	PK	70	1.2	V	-6.11	42.51	74	-31.49
802.11G, Middle Channel									
4874	48.21	PK	108	1.2	H	-5.94	42.33	74	-31.67
4874	42.38	PK	257	1.0	V	-5.94	36.50	74	-37.50
802.11G, High Channel									
2483.5	71.97	PK	257	1.0	H	-10.46	61.51	74	-12.49
2483.5	56.27	AV	257	1.0	H	-10.46	45.81	54	-8.19
2483.5	59.43	PK	269	2.0	V	-10.46	48.97	74	-25.03
2500	57.96	PK	201	1.3	H	-10.32	50.90	74	-23.10
2500	57.96	PK	201	1.3	V	-10.32	47.64	74	-26.36
2485.45	77.68	PK	210	1.0	H	-10.45	67.23	74	-6.77
2485.45	56.37	AV	210	1.0	V	-10.45	45.92	54	-8.08
4924	47.57	PK	210	1.0	H	-5.67	42.00	74	-32.00
4924	48.25	PK	27	2.0	V	-5.67	42.68	74	-31.32
802.11N20, Low Channel									
2310	56.67	PK	226	1.1	H	-10.36	46.31	74	-27.69
2310	55.95	PK	160	1.5	V	-10.36	45.59	74	-28.41
2390	79.31	PK	101	2.0	H	-10.71	68.60	74	-5.40
2390	62.19	AV	101	2.0	H	-10.71	51.48	54	-2.52
2390	68.68	PK	188	2.0	V	-10.71	57.97	74	-16.03
2390	51.56	AV	188	2.0	V	-10.71	40.85	54	-13.15
4824	47.49	PK	108	1.2	H	-6.11	41.38	74	-32.62
4824	47.92	PK	269	2.0	V	-6.11	41.81	74	-32.19

Freque ncy (MHz)	Receiver		Turntable Angle Degree	Rx Antenna		Factor (dB/m)	Absolute Level (dBuV/m)	Limit (dBuV/ m)	Margin (dB)
	Reading (dBuV)	PK/Ave		Height (m)	Polar (H/V)				
802.11N20, Middle Channel									
4874	48.41	PK	53	2.1	H	-5.94	42.53	74	-31.47
4874	48.11	PK	239	1.5	V	-5.94	42.23	74	-31.77
802.11N20, High Channel									
2483.5	75.94	PK	239	1.5	H	-10.46	65.48	74	-8.52
2483.5	58.4	AV	239	1.5	H	-10.46	47.94	54	-6.06
2483.5	60.97	PK	210	1.0	V	-10.46	50.51	74	-23.49
2500	61.52	PK	27	2.0	H	-10.32	51.20	74	-22.80
2500	55.81	PK	27	2.0	V	-10.32	45.49	74	-28.51
4924	48.02	PK	185	1.3	H	-5.67	42.45	74	-31.55
4924	48.55	PK	186	1.3	V	-5.67	42.98	74	-31.02
802.11N40, Low Channel									
2310	56.48	PK	108	1.8	H	-10.36	46.12	74	-27.88
2310	56.91	PK	351	1.3	V	-10.36	46.55	74	-27.45
2390	78.59	PK	108	1.8	H	-10.71	67.88	74	-6.12
2390	58.89	AV	108	1.8	H	-10.71	48.18	54	-5.82
2390	66.02	PK	225	1.4	V	-10.71	55.31	74	-18.69
2390	48.87	AV	225	1.4	V	-10.71	38.16	54	-15.84
4844	49.69	PK	143	1.7	H	-6.09	43.60	74	-30.40
4844	47.21	PK	261	1.1	V	-6.09	41.12	74	-32.88
802.11N40, Middle Channel									
4874	40.55	PK	11	2.0	H	-5.94	34.67	74	-39.33
4874	28.77	PK	152	1.2	V	-5.94	34.65	74	-39.35
802.11N40, High Channel									
2483.5	76.41	PK	307	1.6	H	-10.46	65.95	74	-8.05
2483.5	61.12	AV	307	1.6	H	-10.46	50.66	54	-3.34
2483.5	64.27	PK	221	2.1	V	-10.46	53.81	74	-20.19
2500	72.49	PK	318	1.2	H	-10.32	62.17	74	-11.83
2500	58.1	AV	318	1.2	H	-10.32	47.78	54	-6.22
2500	55.94	PK	36	1.1	V	-10.32	45.62	74	-28.38
2486.28	67.99	PK	281	2.2	V	-10.44	57.55	74	-16.45
2486.28	49.09	AV	281	2.2	V	-10.44	38.65	54	-15.35
4904	47.71	PK	281	2.2	H	-5.78	42.04	74	-31.96
4904	48.21	PK	222	1.9	V	-5.78	42.54	74	-31.46

Note:

Factor = Antenna factor (RX) + Cable Loss – Amplifier Factor

Absolute Level (Corrected Amplitude) = Factor + Reading


Margin = Absolute Level (Corrected Amplitude) – Limit

The other spurious emission which is in the noise floor level was not recorded.


For above 1GHz, when the test result of peak was 20dB below to the limit of peak, which can be compliant to the average limit, just peak value was recorded.

BLE
1 GHz - 18 GHz: (Pre-Scan plots)
Middle Channel (worst case)

Horizontal




Vertical




18-25GHz: (Pre-Scan plots)

Middle Channel (worst case)

Horizontal




Vertical




WIFI:
1-18 GHz: (Pre-scan plots)

802.11 b Middle Channel (Worst case)
Horizontal




Vertical




18 -25GHz: (Pre-scan plots)

802.11 b Middle Channel (Worst case)
Horizontal



Vertical



FCC §15.247(a) (2)-6 dB EMISSION BANDWIDTH & OCCUPIED BANDWIDTH


Applicable Standard

Systems using digital modulation techniques may operate in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

Test Procedure

According to ANSI C63.10-2013, section 11.8 and section 6.9

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.
3. Measure the frequency difference of two frequencies that were attenuated 6 dB from the reference level. Record the frequency difference as the emission bandwidth.
4. Repeat above procedures until all frequencies measured were complete.



Test Data

Environmental Conditions

Temperature:	25°C
Relative Humidity:	43-46%
ATM Pressure:	101.0 kPa

The testing was performed by Matt Liang on 2023-06-03 for Wi-Fi and 2023-06-06 for BLE.

EUT operation mode: Transmitting

Test Result: Compliant. Please refer to the Appendix Wi-Fi and Appendix BLE.

FCC §15.247(b) (3)-MAXIMUM CONDUCTED OUTPUT POWER

Applicable Standard


According to FCC §15.247(b) (3), for systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt. As an alternative to a peak power measurement, compliance with the one Watt limit can be based on a measurement of the maximum conducted output power. Maximum Conducted Output Power is defined as the total transmit power delivered to all antennas and antenna elements averaged across all symbols in the signaling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements. The average must not include any time intervals during which the transmitter is off or is transmitting at a reduced power level. If multiple modes of operation are possible (e.g., alternative modulation methods), the maximum conducted output power is the highest total transmit power occurring in any mode.

Test Procedure


According to ANSI C63.10-2013, section 11.9.1.1 for BLE mode
According to ANSI C63.10-2013, section 11.9.2.3.2 for Wi-Fi mode

1. Place the EUT on a bench and set it in transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to one test equipment.
3. Add a correction factor to the display.

For Wi-Fi mode:



For BLE mode:



Test Data

Environmental Conditions

Temperature:	25°C
Relative Humidity:	43-46%
ATM Pressure:	101.0 kPa

The testing was performed by Matt Liang from 2023-06-03 to 2023-06-05 for Wi-Fi and on 2023-06-06 for BLE.

EUT operation mode: Transmitting

Test Result: Compliant. Please refer to the Appendix Wi-Fi and Appendix BLE.

FCC §15.247(d)-100 kHz BANDWIDTH OF FREQUENCY BAND EDGE


Applicable Standard

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

Test Procedure

According to ANSI C63.10-2013, section 11.11

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range, and make sure the instrument is operated in its linear range.
3. Set RBW to 100 kHz and VBW of spectrum analyzer to 300 kHz with a convenient frequency span including 100 kHz bandwidth from band edge.
4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
5. Repeat above procedures until all measured frequencies were complete.



Test Data

Environmental Conditions

Temperature:	25°C
Relative Humidity:	44-46%
ATM Pressure:	101.0 kPa

The testing was performed by Matt Liang on 2023-06-03 for Wi-Fi and on 2023-06-06 for BLE.

EUT operation mode: Transmitting

Test Result: Compliant.

Conducted Band Edge Result:

Please refer to the Appendix Wi-Fi and Appendix BLE.

FCC §15.247(e)-POWER SPECTRAL DENSITY

Applicable Standard

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of paragraph (b) of this section. The same method of determining the conducted output power shall be used to determine the power spectral density.

Test Procedure

According to ANSI C63.10-2013, section 11.10.2

Method PKPSD (peak PSD)

The following procedure shall be used if maximum peak conducted output power was used to determine compliance, and it is optional if the maximum conducted (average) output power was used to determine compliance:

- a) Set analyzer center frequency to DTS channel center frequency.
- b) Set the span to 1.5 times the DTS bandwidth.
- c) Set the RBW to $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$.
- d) Set the VBW $\geq [3 \times \text{RBW}]$.
- e) Detector = peak.
- f) Sweep time = auto couple.
- g) Trace mode = max hold.
- h) Allow trace to fully stabilize.
- i) Use the peak marker function to determine the maximum amplitude level within the RBW.
- j) If measured value exceeds requirement, then reduce RBW (but no less than 3 kHz) and repeat.

According to ANSI C63.10-2013, section 11.10.3


Method AVGPS-1: (for duty cycle $\geq 98\%$)

1. Use this procedure when the maximum conducted average output power in the fundamental emission is used to demonstrate compliance and with continuous transmission (or at least 98% duty cycle).
2. Set the RBW to: $3\text{kHz} \leq \text{RBW} \leq 100 \text{ kHz}$.
3. Set the VBW $\geq 3 \times \text{RBW}$.
4. Set the span to at least 1.5 times the OBW.
5. Detector = power averaging (rms) or sample detector (when rms not available).
6. Sweep time = auto couple.
7. Ensure that the number of measurement points in the sweep $\geq [2 \cdot \text{span} / \text{RBW}]$.
8. Employ trace averaging (rms) mode over a minimum of 100 traces.
9. Use the peak marker function to determine the maximum amplitude level.
10. If measured value exceeds requirement specified by regulatory agency, then reduce RBW (but no less than 3 kHz) and repeat (note that this may require zooming in on the emission of interest and reducing the span to meet the minimum measurement point requirement as the RBW is reduced).

According to ANSI C63.10-2013, section 11.10.5

Method AVGPDS-2: (for duty cycle < 98% and constant duty cycle)

1. Use this procedure when the maximum conducted average output power in the fundamental emission is used to demonstrate compliance and the continuous transmission (or at least 98% duty cycle) cannot be achieved but exhibit a constant duty cycle during the measurement duration.
2. Measure the duty cycle (D) of the transmitter output signal as described in C63.10-2013 Clause 11.6.
3. Set the RBW to: $3\text{kHz} \leq \text{RBW} \leq 100\text{ kHz}$.
4. Set the VBW $\geq 3 \times \text{RBW}$.
5. Set the span to at least 1.5 times the OBW.
6. Detector = power averaging (rms) or sample detector (when rms not available).
7. Sweep time = auto couple.
8. Ensure that the number of measurement points in the sweep $\geq [2 * \text{span} / \text{RBW}]$.
9. Do not use sweep triggering; allow sweep to “free run.”
10. Employ trace averaging (rms) mode over a minimum of 100 traces.
11. Use the peak marker function to determine the maximum amplitude level.
12. Add $[10 \log (1 / D)]$, where D is the duty cycle measured in step 2), to the measured PSD to compute the average PSD during the actual transmission time.
13. If measured value exceeds requirement specified by regulatory agency, then reduce RBW (but no less than 3 kHz) and repeat (note that this may require zooming in on the emission of interest and reducing the span to meet the minimum measurement point requirement as the RBW is reduced).



Test Data

Environmental Conditions

Temperature:	25°C
Relative Humidity:	44-46%
ATM Pressure:	101.0 kPa

The testing was performed by Matt Liang from 2023-06-03 to 2023-06-05 for Wi-Fi and on 2023-06-06 for BLE.

EUT operation mode: Transmitting

Test Result: Compliant. Please refer to the Appendix Wi-Fi and Appendix BLE.

APPENDIX Wi-Fi


Appendix A: 6dB Emission Bandwidth

Test Result


Test Mode	Antenna	Channel [MHz]	DTS BW [MHz]	Limit[MHz]	Verdict
11B	Ant1	2412	12.56	0.5	PASS
		2437	12.08	0.5	PASS
		2462	12.56	0.5	PASS
11G	Ant1	2412	15.12	0.5	PASS
		2437	15.32	0.5	PASS
		2462	14.72	0.5	PASS
11N20SISO	Ant1	2412	15.12	0.5	PASS
		2437	13.80	0.5	PASS
		2462	15.12	0.5	PASS
11N40SISO	Ant1	2422	35.04	0.5	PASS
		2437	35.04	0.5	PASS
		2452	35.04	0.5	PASS

Test Graphs


11B_Ant1_2412




11B_Ant1_2437




11B_Ant1_2462




11G_Ant1_2412




11G_Ant1_2437



11G_Ant1_2462




11N20SISO_Ant1_2412




Date: 3.JUN.2023 13:08:46

11N20SISO_Ant1_2437




Date: 3.JUN.2023 13:09:42

11N20SISO_Ant1_2462




Date: 3.JUN.2023 13:11:16

11N40SISO_Ant1_2422




Date: 3.JUN.2023 13:12:23

11N40SISO_Ant1_2437



Date: 3.JUN.2023 13:13:20

11N40SISO_Ant1_2452




Date: 3.JUN.2023 13:14:08

Appendix B: Occupied Channel Bandwidth**Test Result**


Test Mode	Antenna	Channel	OCB [MHz]	FL[MHz]	FH[MHz]	Limit[MHz]	Verdict
11B	Ant1	2412	15.504	2404.2078	2419.7123	---	PASS
		2437	15.504	2429.2078	2444.7123	---	PASS
		2462	15.425	2454.2478	2469.6723	---	PASS
11G	Ant1	2412	17.502	2403.2088	2420.7113	---	PASS
		2437	17.582	2428.2088	2445.7912	---	PASS
		2462	17.582	2453.2088	2470.7912	---	PASS
11N20SISO	Ant1	2412	18.501	2402.7293	2421.2308	---	PASS
		2437	18.501	2427.7293	2446.2308	---	PASS
		2462	18.501	2452.7293	2471.2308	---	PASS
11N40SISO	Ant1	2422	36.444	2403.8581	2440.3017	---	PASS
		2437	36.683	2418.6983	2455.3816	---	PASS
		2452	37.083	2433.4585	2470.5415	---	PASS

Test Graphs


11B_Ant1_2412




11B_Ant1_2437




11B_Ant1_2462




11G_Ant1_2412




11G_Ant1_2437




11G_Ant1_2462




11N20SISO_Ant1_2412




11N20SISO_Ant1_2437




11N20SISO_Ant1_2462




11N40SISO_Ant1_2422



11N40SISO_Ant1_2437



11N40SISO_Ant1_2452



Appendix C: Maximum Conducted Output Power**Test Result**

Test Mode	Antenna	Channel	Average Power[dBm]	Limit[dBm]	Verdict
11B	Ant1	2412	13.44	<=30	PASS
		2437	13.46	<=30	PASS
		2462	12.68	<=30	PASS
11G	Ant1	2412	10.08	<=30	PASS
		2437	9.78	<=30	PASS
		2462	9.08	<=30	PASS
11N20SISO	Ant1	2412	9.82	<=30	PASS
		2437	9.62	<=30	PASS
		2462	8.82	<=30	PASS
11N40SISO	Ant1	2422	7.35	<=30	PASS
		2437	6.89	<=30	PASS
		2452	5.68	<=30	PASS


Appendix D: Power Spectral Density**Test Result**

Test Mode	Antenna	Channel[MHz]	Result[dBm/3kHz]	Limit[dBm/3kHz]	Verdict
11B	Ant1	2412	-12.60	<=8	PASS
		2437	-12.81	<=8	PASS
		2462	-13.65	<=8	PASS
11G	Ant1	2412	-16.29	<=8	PASS
		2437	-15.76	<=8	PASS
		2462	-17.18	<=8	PASS
11N20SISO	Ant1	2412	-17.62	<=8	PASS
		2437	-17.29	<=8	PASS
		2462	-18.62	<=8	PASS
11N40SISO	Ant1	2422	-15.24	<=8	PASS
		2437	-16.42	<=8	PASS
		2452	-22.72	<=8	PASS


Note: The Unit of Result is dBm/10kHz for 802.11n40 mode.

Test Graphs


11B_Ant1_2412




11B_Ant1_2437



11B_Ant1_2462




11G_Ant1_2412




Date: 3 JUN 2023 13:05:54

11G_Ant1_2437




Date: 3 JUN 2023 13:17:14

11G_Ant1_2462




Date: 3 JUN 2023 13:07:59


11N20SISO_Ant1_2412




11N20SISO_Ant1_2437




11N20SISO_Ant1_2462




11N40SISO_Ant1_2422



11N40SISO_Ant1_2437




11N40SISO_Ant1_2452



Appendix E: Band Edge Measurements


Test Graphs

11B_Ant1_2412




Date: 3.JUN.2023 13:02:19

11B_Ant1_2462




Date: 3.JUN.2023 13:04:37

11G_Ant1_2412




Date: 3.JUN.2023 13:06:03

11G_Ant1_2462




Date: 3.JUN.2023 13:08:08

11N20SISO_Ant1_2412




Date: 3.JUN.2023 13:09:14

11N20SISO_Ant1_2462




Date: 3.JUN.2023 13:11:43

11N40SISO_Ant1_2422



Date: 3.JUN.2023 13:12:52

11N40SISO_Ant1_2452




Date: 3.JUN.2023 13:14:37

Appendix F: Duty Cycle**Test Result**


Test Mode	Antenna	Channel	Transmission Duration [ms]	Transmission Period [ms]	Duty Cycle [%]
11B	Ant1	2412	8.37	8.46	98.94
		2437	8.40	8.49	98.94
		2462	8.37	8.46	98.94
11G	Ant1	2412	1.39	1.41	98.58
		2437	1.39	1.41	98.58
		2462	1.39	1.41	98.58
11N20SISO	Ant1	2412	1.29	1.31	98.47
		2437	1.30	1.32	98.48
		2462	1.29	1.31	98.47
11N40SISO	Ant1	2422	0.65	0.66	98.48
		2437	0.65	0.66	98.48
		2452	0.65	0.66	98.48

Test Graphs


11B_Ant1_2412




11B_Ant1_2437



11B_Ant1_2462




11G_Ant1_2412




Date: 3.JUN.2023 13:05:27

11G_Ant1_2437




Date: 3.JUN.2023 13:16:48

11G_Ant1_2462




Date: 3.JUN.2023 13:07:33

11N20SISO_Ant1_2412




Date: 3.JUN.2023 13:08:38

11N20SISO_Ant1_2437




Date: 3.JUN.2023 13:09:35

11N20SISO_Ant1_2462




Date: 3.JUN.2023 13:11:08


11N40SISO_Ant1_2422



11N40SISO_Ant1_2437



11N40SISO_Ant1_2452




APPENDIX BLE

Appendix A: 6dB Emission Bandwidth


Test Result

Test Mode	Antenna	Channel	DTS BW [MHz]	Limit[MHz]	Verdict
BLE_1M	Ant1	2402	0.73	0.5	PASS
		2440	0.73	0.5	PASS
		2480	0.73	0.5	PASS


Test Graphs



BLE_1M_Ant1_2440



BLE_1M_Ant1_2480




Appendix B: Occupied Channel Bandwidth


Test Result

Test Mode	Antenna	Channel	OCB [MHz]	Limit[MHz]	Verdict
BLE_1M	Ant1	2402	1.051	---	PASS
		2440	1.047	---	PASS
		2480	1.051	---	PASS


Test Graphs



BLE_1M_Ant1_2440



BLE_1M_Ant1_2480




Appendix C: Maximum Conducted Peak Output Power

Test Result


Test Mode	Antenna	Channel	Result[dBm]	Limit[dBm]	Verdict
BLE_1M	Ant1	2402	3.16	<=30	PASS
		2440	3.44	<=30	PASS
		2480	1.43	<=30	PASS

Test Graphs

BLE_1M_Ant1_2402




BLE_1M_Ant1_2440



Date: 6.JUN.2023 19:35:22

BLE_1M_Ant1_2480



Date: 6.JUN.2023 19:38:10


Appendix D: Power Spectral Density

Test Result

Test Mode	Antenna	Channel	Result[dBm/3kHz]	Limit[dBm/3kHz]	Verdict
BLE_1M	Ant1	2402	-12.88	<=8	PASS
		2440	-12.85	<=8	PASS
		2480	-14.75	<=8	PASS


Test Graphs

BLE_1M_Ant1_2402




Date: 6 JUN. 2023 19:32:29

BLE_1M_Ant1_2440



Date: 6.JUN.2023 19:35:28

BLE_1M_Ant1_2480




Date: 6.JUN.2023 19:38:16


Appendix E: Band Edge Measurements

Test Graphs

BLE_1M_Ant1_Low_2402



BLE_1M_Ant1_High_2480




Appendix F: Duty Cycle

Test Result


Test Mode	Antenna	Channel	Transmission Duration [ms]	Transmission Period [ms]	Duty Cycle [%]
BLE_1M	Ant1	2402	19.00	19.00	100
		2440	19.00	19.00	100
		2480	19.00	19.00	100

Test Graphs


BLE_1M-Ant1-2402



BLE_1M-Ant1-2440



BLE_1M-Ant1-2480



***** END OF REPORT *****