



FCC RF Test Report

APPLICANT : HTC Corporation
EQUIPMENT : Smartphone
MODEL NAME : 2Q3F300
FCC ID : NM82Q3F300
STANDARD : FCC Part 15 Subpart C §15.247
CLASSIFICATION : (DTS) Digital Transmission System

The product was received on May 23, 2017 and testing was completed on Jun. 25, 2017. We, SPORTON INTERNATIONAL INC., would like to declare that the tested sample has been evaluated in accordance with the test procedures and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL INC., the test report shall not be reproduced except in full.

Reviewed by: Joseph Lin / Supervisor

Approved by: Jones Tsai / Manager



SPORTON INTERNATIONAL INC.

No. 52, Hwa Ya 1st Rd., Hwa Ya Technology Park, Kwei-Shan District, Tao Yuan City, Taiwan, R.O.C.



TABLE OF CONTENTS

SUMMARY OF TEST RESULT	4
1 GENERAL DESCRIPTION.....	5
1.1 Applicant.....	5
1.2 Manufacturer.....	5
1.3 Product Feature of Equipment Under Test.....	5
1.4 Modification of EUT	5
1.5 Testing Location	6
1.6 Applicable Standards.....	6
2 TEST CONFIGURATION OF EQUIPMENT UNDER TEST.....	7
2.1 Carrier Frequency Channel	7
2.2 Test Mode.....	8
2.3 Connection Diagram of Test System.....	9
2.4 Support Unit used in test configuration and system	9
2.5 EUT Operation Test Setup	9
2.6 Measurement Results Explanation Example.....	10
3 TEST RESULT	11
3.1 6dB and 99% Bandwidth Measurement	11
3.2 Peak Output Power Measurement	18
3.3 Power Spectral Density Measurement	19
3.4 Conducted Band Edges and Spurious Emission Measurement	26
3.5 Radiated Band Edges and Spurious Emission Measurement	35
3.6 AC Conducted Emission Measurement.....	39
3.7 Antenna Requirements.....	41
4 LIST OF MEASURING EQUIPMENT.....	42
5 UNCERTAINTY OF EVALUATION.....	43
APPENDIX A. CONDUCTED TEST RESULTS	
APPENDIX B. AC CONDUCTED EMISSION TEST RESULT	
APPENDIX C. RADIATED SPURIOUS EMISSION	
APPENDIX D. RADIATED SPURIOUS EMISSION PLOTS	
APPENDIX E. DUTY CYCLE PLOTS	



REVISION HISTORY

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FR752311B	Rev. 01	Initial issue of report	Sep. 04, 2017

SUMMARY OF TEST RESULT

Report Section	FCC Rule	Description	Limit	Result	Remark
3.1	15.247(a)(2)	6dB Bandwidth	$\geq 0.5\text{MHz}$	Pass	-
3.1	-	99% Bandwidth	-	Pass	-
3.2	15.247(b)(3)	Peak Output Power	$\leq 30\text{dBm}$	Pass	-
3.3	15.247(e)	Power Spectral Density	$\leq 8\text{dBm}/3\text{kHz}$	Pass	-
3.4	15.247(d)	Conducted Band Edges and Spurious Emission	$\leq 20\text{dBc}$	Pass	-
3.5	15.247(d)	Radiated Band Edges and Spurious Emission	15.209(a) & 15.247(d)	Pass	Under limit 6.70 dB at 36.750 MHz
3.6	15.207	AC Conducted Emission	15.207(a)	Pass	Under limit 5.50 dB at 13.558 MHz
3.7	15.203 & 15.247(b)	Antenna Requirement	N/A	Pass	-



1 General Description

1.1 Applicant

HTC Corporation

No. 23, Xinghua Rd., Taoyuan District, Taoyuan City, Taiwan 330

1.2 Manufacturer

HTC Corporation

No.23, Xinghua Rd., Taoyuan District, Taoyuan City, Taiwan 330

1.3 Product Feature of Equipment Under Test

GSM/WCDMA/LTE, Bluetooth, Wi-Fi 2.4GHz 802.11b/g/n, Wi-Fi 5GHz 802.11a/n/ac, NFC, and GPS

Product Specification subjective to this standard	
Sample 1	EUT with battery 1 and 1st PCB
Sample 2	EUT with battery 2 and 1st PCB
Sample 3	EUT with battery 1 and 2nd PCB
Antenna Type	WWAN: Fixed Internal Antenna WLAN: PIFA Antenna Bluetooth: PIFA Antenna GPS/GLONASS/BDS: PIFA Antenna NFC: Loop Antenna

Remark:

1. There are 1st PCB and 2nd PCB, the hardware change are USB board, antenna board and speaker module. Regarding the differences, perform full RSE testing on sample 1 and sample 3.
2. For the LTE setting which controlled by software, there are two Skus of device. Sku 1 supports LTE category 9(up to 450 Mbps), and Sku 2 support category 11(up to 600 Mbps) and 256QAM downlink. Since the differences, we only performed on Sku 2 device.
3. All tests were performed with sample 1.

1.4 Modification of EUT

No modifications are made to the EUT during all test items.

1.5 Testing Location

Sporton Lab is accredited to ISO 17025 by Taiwan Accreditation Foundation (TAF code : 1190) and the FCC designation No. TW0007 under the FCC 2.948(e) by Mutual Recognition Agreement (MRA) in FCC Test.

Test Site	SPORTON INTERNATIONAL INC.	
Test Site Location	No. 52, Hwa Ya 1 st Rd., Hwa Ya Technology Park, Kwei-Shan District, Tao Yuan City, Taiwan, R.O.C. TEL: +886-3-327-3456 FAX: +886-3-328-4978	
Test Site No.	Sporton Site No.	
	TH05-HY	CO05-HY

Note: The test site complies with ANSI C63.4 2014 requirement.

Test Site	SPORTON INTERNATIONAL INC.	
Test Site Location	No.58, Aly. 75, Ln. 564, Wenhua 3rd Rd. Guishan Dist, Taoyuan City, Taiwan (R.O.C.) TEL: +886-3-327-0868 FAX: +886-3-327-0855	
Test Site No.	Sporton Site No.	
	03CH12-HY	

Note: The test site complies with ANSI C63.4 2014 requirement.

1.6 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ FCC Part 15 Subpart C §15.247
- ♦ FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v04
- ♦ ANSI C63.10-2013

Remark:

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.



2 Test Configuration of Equipment Under Test

2.1 Carrier Frequency Channel

Frequency Band	Channel	Freq. (MHz)	Channel	Freq. (MHz)
2400-2483.5 MHz	0	2402	21	2444
	1	2404	22	2446
	2	2406	23	2448
	3	2408	24	2450
	4	2410	25	2452
	5	2412	26	2454
	6	2414	27	2456
	7	2416	28	2458
	8	2418	29	2460
	9	2420	30	2462
	10	2422	31	2464
	11	2424	32	2466
	12	2426	33	2468
	13	2428	34	2470
	14	2430	35	2472
	15	2432	36	2474
	16	2434	37	2476
	17	2436	38	2478
	18	2438	39	2480
	19	2440	-	-
	20	2442	-	-


2.2 Test Mode

- a. The EUT has been associated with peripherals and configuration operated in a manner tended to maximize its emission characteristics in a typical application. Frequency range investigated: conduction emission (150 kHz to 30 MHz), radiation emission (9 kHz to the 10th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower). For radiated measurement, pre-scanned in three orthogonal panels, X, Y, Z. The worst cases (Y plane) were recorded in this report.
- b. AC power line Conducted Emission was tested under maximum output power.

The following summary table is showing all test modes to demonstrate in compliance with the standard.

Summary table of Test Cases	
Test Item	Data Rate / Modulation
	Bluetooth – LE / GFSK
Conducted TCs	Mode 1: Bluetooth Tx CH00_2402 MHz_1Mbps for BLE 4.0
	Mode 2: Bluetooth Tx CH19_2440 MHz_1Mbps for BLE 4.0
	Mode 3: Bluetooth Tx CH39_2480 MHz_1Mbps for BLE 4.0
	Mode 4: Bluetooth Tx CH00_2402 MHz_1Mbps for BLE 5.0
	Mode 5: Bluetooth Tx CH19_2440 MHz_1Mbps for BLE 5.0
	Mode 6: Bluetooth Tx CH39_2480 MHz_1Mbps for BLE 5.0
Radiated TCs	Mode 1: Bluetooth Tx CH00_2402 MHz_1Mbps for BLE 4.0
	Mode 2: Bluetooth Tx CH19_2440 MHz_1Mbps for BLE 4.0
	Mode 3: Bluetooth Tx CH39_2480 MHz_1Mbps for BLE 4.0
	Mode 4: Bluetooth Tx CH00_2402 MHz_1Mbps for BLE 5.0
	Mode 5: Bluetooth Tx CH19_2440 MHz_1Mbps for BLE 5.0
	Mode 6: Bluetooth Tx CH39_2480 MHz_1Mbps for BLE 5.0
AC Conducted Emission	Mode 1: Bluetooth Link + WLAN (2.4GHz) Link + Ant+ Link + NFC Link + USB Cable 1 (Charging from Adapter 1)
Remark: For Radiated Test Cases, The tests were performance with Adapter 1 and USB Cable 1.	

2.3 Connection Diagram of Test System



2.4 Support Unit used in test configuration and system

Item	Equipment	Trade Name	Model Name	FCC ID	Data Cable	Power Cord
1.	Bluetooth Earphone	Sony Ericsson	MW600	PY7DDA-2029	N/A	N/A
2.	WLAN AP	ASUS	RT-AC66U	MSQ-RTAC66U	N/A	Unshielded, 1.8m
3.	Notebook	DELL	Latitude E6320	FCC DoC/ Contains FCC ID: QDS-BRCM1054	N/A	AC I/P: Unshielded, 1.2 m DC O/P: Shielded, 1.8 m
4.	NFC Card	N/A	N/A	N/A	N/A	N/A
5.	SD Card	SanDisk	MicroSD HC	FCC DoC	N/A	N/A

2.5 EUT Operation Test Setup

The RF test items utility, "HTC SSD Test Tool" was installed in EUT which was programmed in order to make the EUT get into the engineering modes for continuous transmitting and receiving signals.



2.6 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

Example :

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

Offset = RF cable loss + attenuator factor.

Following shows an offset computation example with cable loss 4.2 dB and 10dB attenuator.

$$\begin{aligned}\text{Offset(dB)} &= \text{RF cable loss(dB)} + \text{attenuator factor(dB)} \\ &= 4.2 + 10 = 14.2 \text{ (dB)}\end{aligned}$$

3 Test Result

3.1 6dB and 99% Bandwidth Measurement

3.1.1 Limit of 6dB and 99% Bandwidth

The minimum 6 dB bandwidth shall be at least 500 kHz.


3.1.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.1.3 Test Procedures

1. The testing follows FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v04.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 100 kHz. Set the Video bandwidth (VBW) = 300 kHz. In order to make an accurate measurement. The 6 dB bandwidth must be greater than 500 kHz.
5. For 99% Bandwidth Measurement, the spectrum analyzer's resolution bandwidth (RBW) is set 30kHz and set the Video bandwidth (VBW) = 100kHz.
6. Measure and record the results in the test report.

3.1.4 Test Setup




3.1.5 Test Result of 6dB Bandwidth

Please refer to Appendix A.


<BLE 4.0>

6 dB Bandwidth Plot on Channel 00




Date: 4.JUN.2017 20:00:09

6 dB Bandwidth Plot on Channel 19



Date: 4.JUN.2017 20:03:22


6 dB Bandwidth Plot on Channel 39



Date: 4.JUN.2017 20:05:26

<BLE 5.0>


6 dB Bandwidth Plot on Channel 00



Date: 5.JUN.2017 16:02:52




6 dB Bandwidth Plot on Channel 19



Date: 5.JUN.2017 16:11:36

6 dB Bandwidth Plot on Channel 39



Date: 6.JUN.2017 15:42:45




3.1.6 Test Result of 99% Occupied Bandwidth

Please refer to Appendix A.


<BLE 4.0>

99% Bandwidth Plot on Channel 00




Date: 4.JUN.2017 20:02:21

99% Occupied Bandwidth Plot on Channel 19




Date: 4.JUN.2017 20:04:39

99% Occupied Bandwidth Plot on Channel 39


Date: 4.JUN.2017 20:07:09


Note: The occupied channel bandwidth is maintained within the band of operation for all of the modulations.

<BLE 5.0>
99% Bandwidth Plot on Channel 00


Date: 5.JUN.2017 15:59:30




99% Occupied Bandwidth Plot on Channel 19



Date: 6.JUN.2017 15:46:12

99% Occupied Bandwidth Plot on Channel 39



Date: 6.JUN.2017 15:45:06

Note: The occupied channel bandwidth is maintained within the band of operation for all of the modulations.

3.2 Peak Output Power Measurement

3.2.1 Limit of Peak Output Power

For systems using digital modulation in the 2400-2483.5MHz, the limit for peak output power is 30dBm. If transmitting antenna of directional gain greater than 6dBi is used, the peak output power from the intentional radiator shall be reduced below the above stated value by the amount in dB that the directional gain of the antenna exceeds 6 dBi. In case of point-to-point operation, the limit has to be reduced by 1dB for every 3dB that the directional gain of the antenna exceeds 6dBi.


3.2.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.2.3 Test Procedures

1. The testing follows the Measurement Procedure of FCC KDB No. 558074 DTS D01 Meas. Guidance v04 section 9.1.2 PKPM1 Peak power meter method.
2. The RF output of EUT was connected to the power meter by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Measure the conducted output power and record the results in the test report.

3.2.4 Test Setup



3.2.5 Test Result of Peak Output Power

Please refer to Appendix A.

3.3 Power Spectral Density Measurement

3.3.1 Limit of Power Spectral Density

The peak power spectral density shall not be greater than 8dBm in any 3kHz band at any time interval of continuous transmission.


3.3.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.3.3 Test Procedures

1. The testing follows Measurement Procedure 10.2 Method PKPSD of FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v04
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 3 kHz. Video bandwidth VBW = 10 kHz In order to make an accurate measurement, set the span to 1.5 times DTS Channel Bandwidth. (6dB BW)
5. Detector = peak, Sweep time = auto couple, Trace mode = max hold, Allow trace to fully stabilize. Use the peak marker function to determine the maximum power level.
6. Measure and record the results in the test report.
7. The Measured power density (dBm)/ 100kHz is a reference level and used as 20dBc down limit line for Conducted Band Edges and Conducted Spurious Emission.

3.3.4 Test Setup




3.3.5 Test Result of Power Spectral Density

Please refer to Appendix A.

3.3.6 Test Result of Power Spectral Density Plots (100kHz)


<BLE 4.0>

PSD 100kHz Plot on Channel 00



Date: 4.JUN.2017 20:00:50


PSD 100kHz Plot on Channel 19



Date: 4.JUN.2017 20:04:00




PSD 100kHz Plot on Channel 39



Date: 4.JUN.2017 20:06:04

<BLE 5.0>


PSD 100kHz Plot on Channel 00



Date: 5.JUN.2017 16:04:30




PSD 100kHz Plot on Channel 19



Date: 5.JUN.2017 16:12:44

PSD 100kHz Plot on Channel 39




Date: 6.JUN.2017 15:43:20



3.3.7 Test Result of Power Spectral Density Plots (3kHz)


<BLE 4.0>

PSD 3kHz Plot on Channel 00



Date: 4.JUN.2017 20:00:32


PSD 3kHz Plot on Channel 19



Date: 4.JUN.2017 20:03:42




PSD 3kHz Plot on Channel 39



Date: 4.JUN.2017 20:05:44

<BLE 5.0>


PSD 3kHz Plot on Channel 00



Date: 5.JUN.2017 16:04:11




PSD 3kHz Plot on Channel 19



Date: 5.JUN.2017 16:12:12

PSD 3kHz Plot on Channel 39



Date: 6.JUN.2017 15:43:01

3.4 Conducted Band Edges and Spurious Emission Measurement

3.4.1 Limit of Conducted Band Edges and Spurious Emission

All harmonics/spurious must be at least 20 dB down from the highest emission level within the authorized band.


3.4.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.4.3 Test Procedure

1. The testing follows FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v04.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Set RBW = 100 kHz, VBW=300 kHz, Peak Detector. Unwanted Emissions measured in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz when maximum peak conducted output power procedure is used. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, the attenuation required under this paragraph shall be 30 dB instead of 20 dB.
5. Measure and record the results in the test report.
6. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.

3.4.4 Test Setup






3.4.5 Test Result of Conducted Band Edges Plots


<BLE 4.0>

Low Band Edge Plot on Channel 00



Date: 4.JUN.2017 20:01:10

High Band Edge Plot on Channel 39




Date: 4.JUN.2017 20:06:22




<BLE 5.0>

Low Band Edge Plot on Channel 00



Date: 5.JUN.2017 16:05:29

High Band Edge Plot on Channel 39




Date: 6.JUN.2017 15:43:42

3.4.6 Test Result of Conducted Spurious Emission Plots

<BLE 4.0>

Conducted Spurious Emission Plot on Bluetooth LE 1Mbps


GFSK Channel 00



Date: 4.JUN.2017 20:01:45

Conducted Spurious Emission Plot on Bluetooth LE 1Mbps

GFSK Channel 00




Date: 4.JUN.2017 20:01:53



Conducted Spurious Emission Plot on Bluetooth LE 1Mbps


GFSK Channel 19



Date: 4.JUN.2017 20:04:11

Conducted Spurious Emission Plot on Bluetooth LE 1Mbps

GFSK Channel 19




Date: 4.JUN.2017 20:04:20



Conducted Spurious Emission Plot on Bluetooth LE 1Mbps


GFSK Channel 39



Date: 4.JUN.2017 20:06:33

Conducted Spurious Emission Plot on Bluetooth LE 1Mbps

GFSK Channel 39




Date: 4.JUN.2017 20:06:41



<BLE 5.0>

Conducted Spurious Emission Plot on Bluetooth LE 1Mbps


GFSK Channel 00



Date: 6.JUN.2017 15:39:12


Conducted Spurious Emission Plot on Bluetooth LE 1Mbps

GFSK Channel 00




Date: 6.JUN.2017 15:39:20

Conducted Spurious Emission Plot on Bluetooth LE 1Mbps GFSK Channel 19



Date: 6.JUN.2017 15:40:01

Conducted Spurious Emission Plot on Bluetooth LE 1Mbps GFSK Channel 19




Date: 6.JUN.2017 15:40:09



Conducted Spurious Emission Plot on Bluetooth LE 1Mbps


GFSK Channel 39



Date: 6.JUN.2017 15:43:56

Conducted Spurious Emission Plot on Bluetooth LE 1Mbps

GFSK Channel 39



Date: 6.JUN.2017 15:44:04



3.5 Radiated Band Edges and Spurious Emission Measurement

3.5.1 Limit of Radiated Band Edges and Spurious Emission

In any 100 kHz bandwidth outside the intentional radiator frequency band, all harmonics/spurious must be at least 20 dB below the highest emission level within the authorized band. If the output power of this device was measured by spectrum analyzer, the attenuation under this paragraph shall be 30 dB instead of 20 dB. In addition, radiated emissions which fall in the restricted bands must also comply with the limits as below.

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

3.5.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.




3.5.3 Test Procedures


1. The testing follows FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v04.
2. The EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level.
3. The EUT was placed on a turntable with 0.8 meter for frequency below 1GHz and 1.5 meter for frequency above 1GHz respectively above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
5. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level
6. For measurement below 1GHz, If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported. Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported.
7. Use the following spectrum analyzer settings:
 - (1) Span shall wide enough to fully capture the emission being measured;
 - (2) Set RBW=100 kHz for $f < 1$ GHz; VBW $\geq$ RBW; Sweep = auto; Detector function = peak; Trace = max hold;
 - (3) Set RBW = 1 MHz, VBW= 3MHz for $f \geq 1$ GHz for peak measurement.
For average measurement:
 - VBW = 10 Hz, when duty cycle is no less than 98 percent.
 - VBW $\geq 1/T$, when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation.

3.5.4 Test Setup


For radiated emissions below 30MHz



For radiated emissions from 30MHz to 1GHz



For radiated emissions above 1GHz



3.5.5 Test Results of Radiated Spurious Emissions (9 kHz ~ 30 MHz)

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line was not reported.

3.5.6 Test Result of Radiated Spurious at Band Edges

Please refer to Appendix C and D.

3.5.7 Duty Cycle

Please refer to Appendix E.

3.5.8 Test Result of Radiated Spurious Emission (30MHz ~ 10th Harmonic)

Please refer to Appendix C and D.

3.6 AC Conducted Emission Measurement

3.6.1 Limit of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

Frequency of emission (MHz)	Conducted limit (dB μ V)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.


3.6.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.6.3 Test Procedures

1. The EUT was placed 0.4 meter from the conducting wall of the shielding room was kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. The FCC states that a 50 ohm, 50 microhenry LISN should be used.
6. Both sides of AC line were checked for maximum conducted interference.
7. The frequency range from 150 kHz to 30 MHz was searched.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth (IF Bandwidth = 9kHz) with Maximum Hold Mode. Then measurement is also conducted by Average Detector and Quasi-Peak Detector Function respectively.

3.6.4 Test Setup



3.6.5 Test Result of AC Conducted Emission

Please refer to Appendix B.



3.7 Antenna Requirements

3.7.1 Standard Applicable

If directional gain of transmitting antennas is greater than 6dBi, the power shall be reduced by the same level in dB comparing to gain minus 6dBi. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the rule.

3.7.2 Antenna Anti-Replacement Construction

An embedded-in antenna design is used.

3.7.3 Antenna Gain

The antenna peak gain of EUT is less than 6 dBi. Therefore, it is not necessary to reduce maximum peak output power limit.



4 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Power Meter	Agilent	E4416A	GB41292344	300MHz~40GHz	Dec. 26, 2016	Jun. 01, 2017 ~ Jun. 05, 2017	Dec. 25, 2017	Conducted (TH05-HY)
Power Sensor	Agilent	E9327A	US40441548	300MHz~40GHz	Dec. 26, 2016	Jun. 01, 2017 ~ Jun. 05, 2017	Dec. 25, 2017	Conducted (TH05-HY)
Spectrum Analyzer	Rohde & Schwarz	FSP40	100055	9kHz-40GHz	Jul. 17, 2016	Jun. 01, 2017 ~ Jun. 05, 2017	Jul. 16, 2017	Conducted (TH05-HY)
Programmable Power Supply	GW Instek	PSS-2005	EL890094	1V~20V 0.5A~5A	Oct. 11, 2016	Jun. 01, 2017 ~ Jun. 05, 2017	Oct. 10, 2017	Conducted (TH05-HY)
AC Power Source	ChainTek	APC-1000W	N/A	N/A	N/A	Jun. 25, 2017	N/A	Conduction (CO05-HY)
EMI Test Receiver	Rohde & Schwarz	ESCI 7	100724	9kHz~7GHz	Aug. 30, 2016	Jun. 25, 2017	Aug. 29, 2017	Conduction (CO05-HY)
LISN	Rohde & Schwarz	ENV216	100080	9kHz~30MHz	Nov. 29, 2016	Jun. 25, 2017	Nov. 28, 2017	Conduction (CO05-HY)
LISN	Rohde & Schwarz	ENV216	100081	9kHz~30MHz	Dec. 06, 2016	Jun. 25, 2017	Dec. 05, 2017	Conduction (CO05-HY)
Preamplifier	COM-POWER	PA-103	161075	10MHz~1GHz	Mar. 23, 2017	Jun. 13, 2017 ~ Jun. 21, 2017	Mar. 22, 2018	Radiation (03CH12-HY)
Loop Antenna	Rohde & Schwarz	HFH2-Z2	100488	9 kHz~30 MHz	Oct. 20, 2016	Jun. 13, 2017 ~ Jun. 21, 2017	Oct. 19, 2018	Radiation (03CH12-HY)
Bilog Antenna	TESEQ	CBL 6111D&00800 N1D01N-06	37059&01	30MHz~1GHz	Oct. 15, 2016	Jun. 13, 2017 ~ Jun. 21, 2017	Oct. 14, 2017	Radiation (03CH12-HY)
EMI Test Receiver	Rohde & Schwarz	ESU26	100390	20Hz~26.5GHz	Dec. 23, 2016	Jun. 13, 2017 ~ Jun. 21, 2017	Dec. 22, 2017	Radiation (03CH12-HY)
Horn Antenna	SCHWARZBECK	BBHA 9120D	9120D-1328	1GHz ~ 18GHz	Oct. 25, 2016	Jun. 13, 2017 ~ Jun. 21, 2017	Oct. 24, 2017	Radiation (03CH12-HY)
Preamplifier	MITEQ	AMF-7D-0010 1800-30-10P	1815698	1GHz~18GHz	Dec. 01, 2016	Jun. 13, 2017 ~ Jun. 21, 2017	Nov. 30, 2017	Radiation (03CH12-HY)
Preamplifier	Keysight	83017A	MY53270148	1GHz~26.5GHz	Jan. 12, 2017	Jun. 13, 2017 ~ Jun. 21, 2017	Jan. 11, 2018	Radiation (03CH12-HY)
Filter	Wainwright	WLJ4-1000-1 530-6000-40S T	SN3	1.53 GHz Lowpass	Jul. 07, 2016	Jun. 13, 2017 ~ Jun. 21, 2017	Jul. 06, 2017	Radiation (03CH12-HY)
Filter	Wainwright	WHKX12-270 0-3000-18000 -60ST	SN2	3 GHz Highpass	Jul. 07, 2016	Jun. 13, 2017 ~ Jun. 21, 2017	Jul. 06, 2017	Radiation (03CH12-HY)
Antenna Mast	EMEC	AM-BS-4500-B	N/A	1m~4m	N/A	Jun. 13, 2017 ~ Jun. 21, 2017	N/A	Radiation (03CH12-HY)
Turn Table	EMEC	TT2000	N/A	0~360 Degree	N/A	Jun. 13, 2017 ~ Jun. 21, 2017	N/A	Radiation (03CH12-HY)
Amplifier	MITEQ	TTA1840-35-HG	1871923	18GHz~40GHz, VSWR : 2.5:1 max	Jul. 16, 2016	Jun. 13, 2017 ~ Jun. 21, 2017	Jul. 15, 2017	Radiation (03CH12-HY)
SHF-EHF Horn Antenna	SCHWARZBECK	BBHA 9170	BBHA9170584	18GHz- 40GHz	Nov. 08, 2016	Jun. 13, 2017 ~ Jun. 21, 2017	Nov. 07, 2017	Radiation (03CH12-HY)

5 Uncertainty of Evaluation

Uncertainty of Conducted Emission Measurement (150 kHz ~ 30 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	2.70
---	------

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	5.1
---	-----

Uncertainty of Radiated Emission Measurement (1000 MHz ~ 18000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	5.2
---	-----

Uncertainty of Radiated Emission Measurement (18000 MHz ~ 40000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	4.7
---	-----



Appendix A. Conducted Test Results

<BLE 4.0>

Bluetooth Low Energy

Test Engineer:	Shiming Liu/Bill Kuo	Temperature:	21~25	°C
Test Date:	2017/06/01 ~ 2017/06/04	Relative Humidity:	51~54	%

TEST RESULTS DATA
6dB and 99% Occupied Bandwidth

Mod.	Data Rate	N _{TX}	CH.	Freq. (MHz)	99% Occupied BW (MHz)	6dB BW (MHz)	6dB BW Limit (MHz)	Pass/Fail
BLE	1Mbps	1	0	2402	1.028	0.660	0.50	Pass
BLE	1Mbps	1	19	2440	1.028	0.672	0.50	Pass
BLE	1Mbps	1	39	2480	1.030	0.664	0.50	Pass

TEST RESULTS DATA
Peak Power Table

Mod.	Data Rate	N _{TX}	CH.	Freq. (MHz)	Peak Conducted Power (dBm)	Conducted Power Limit (dBm)	DG (dBi)	EIRP Power (dBm)	EIRP Power Limit (dBm)	Pass /Fail
BLE	1Mbps	1	0	2402	3.47	30.00	-2.10	1.37	36.00	Pass
BLE	1Mbps	1	19	2440	1.57	30.00	-2.10	-0.53	36.00	Pass
BLE	1Mbps	1	39	2480	3.82	30.00	-2.10	1.72	36.00	Pass

TEST RESULTS DATA
Average Power Table
(Reporting Only)

Mod.	Data Rate	N _{TX}	CH.	Freq. (MHz)	Duty Factor (dB)	Average Conducted Power (dBm)
BLE	1Mbps	1	0	2402	2.06	2.91
BLE	1Mbps	1	19	2440	2.06	0.83
BLE	1Mbps	1	39	2480	2.06	3.29

TEST RESULTS DATA
Peak Power Density

Mod.	Data Rate	N _{TX}	CH.	Freq. (MHz)	Peak PSD (dBm /100kHz)	Peak PSD (dBm /3kHz)	DG (dBi)	Peak PSD Limit (dBm /3kHz)	Pass/Fail
BLE	1Mbps	1	0	2402	3.02	-11.83	-2.10	8.00	Pass
BLE	1Mbps	1	19	2440	0.99	-13.77	-2.10	8.00	Pass
BLE	1Mbps	1	39	2480	2.91	-11.92	-2.10	8.00	Pass

Note: PSD (dBm/ 100kHz) is a reference level used for Conducted Band Edges and Conducted Spurious Emission 20dBc limit.



<BLE 5.0>

Bluetooth Low Energy

Test Engineer:	Shiming Liu	Temperature:	21~25	°C
Test Date:	2017/06/01 ~ 2017/06/05	Relative Humidity:	51~54	%

TEST RESULTS DATA
6dB and 99% Occupied Bandwidth

Mod.	Data Rate	NTx	CH.	Freq. (MHz)	99% Occupied BW (MHz)	6dB BW (MHz)	6dB BW Limit (MHz)	Pass/Fail
BLE	1Mbps	1	0	2402	2.044	1.136	0.50	Pass
BLE	1Mbps	1	19	2440	2.044	1.136	0.50	Pass
BLE	1Mbps	1	39	2480	2.040	1.136	0.50	Pass

TEST RESULTS DATA
Peak Power Table

Mod.	Data Rate	NTx	CH.	Freq. (MHz)	Peak Conducted Power (dBm)	Conducted Power Limit (dBm)	DG (dBi)	EIRP Power (dBm)	EIRP Power Limit (dBm)	Pass /Fail
BLE	1Mbps	1	0	2402	4.84	30.00	-2.10	2.74	36.00	Pass
BLE	1Mbps	1	19	2440	2.61	30.00	-2.10	0.51	36.00	Pass
BLE	1Mbps	1	39	2480	4.75	30.00	-2.10	2.65	36.00	Pass

TEST RESULTS DATA
Average Power Table
(Reporting Only)

Mod.	Data Rate	NTx	CH.	Freq. (MHz)	Duty Factor (dB)	Average Conducted Power (dBm)
BLE	1Mbps	1	0	2402	2.06	1.28
BLE	1Mbps	1	19	2440	2.06	-1.11
BLE	1Mbps	1	39	2480	2.06	1.24

TEST RESULTS DATA
Peak Power Density

Mod.	Data Rate	NTx	CH.	Freq. (MHz)	Peak PSD (dBm /100kHz)	Peak PSD (dBm /3kHz)	DG (dBi)	Peak PSD Limit (dBm /3kHz)	Pass/Fail
BLE	1Mbps	1	0	2402	3.21	-15.10	-2.10	8.00	Pass
BLE	1Mbps	1	19	2440	0.74	-17.50	-2.10	8.00	Pass
BLE	1Mbps	1	39	2480	2.80	-15.50	-2.10	8.00	Pass

Note: PSD (dBm/ 100kHz) is a reference level used for Conducted Band Edges and Conducted Spurious Emission 20dBc limit.




Appendix B. AC Conducted Emission Test Results

Test Engineer :	Kai-Chun Chu	Temperature :	24~25℃
		Relative Humidity :	44~45%

EUT Information

Report NO : 752311
Test Mode : Mode 1
Test Voltage : 120Vac/60Hz
Phase : Line

ENV216 Auto Test FCC Power Bar - L



Final Result 1

Frequency (MHz)	QuasiPeak (dBμV)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
0.166000	44.1	Off	L1	19.6	21.1	65.2
0.246000	35.6	Off	L1	19.6	26.3	61.9
0.342000	31.0	Off	L1	19.6	28.2	59.2
0.830000	26.5	Off	L1	19.6	29.5	56.0
1.398000	28.3	Off	L1	19.6	27.7	56.0
3.414000	31.8	Off	L1	19.6	24.2	56.0
13.558000	48.8	Off	L1	20.2	11.2	60.0


Final Result 2

Frequency (MHz)	Average (dBμV)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
0.166000	31.3	Off	L1	19.6	23.9	55.2
0.246000	23.8	Off	L1	19.6	28.1	51.9
0.342000	20.9	Off	L1	19.6	28.3	49.2
0.830000	19.1	Off	L1	19.6	26.9	46.0
1.398000	19.6	Off	L1	19.6	26.4	46.0
3.414000	18.4	Off	L1	19.6	27.6	46.0
13.558000	44.5	Off	L1	20.2	5.5	50.0

EUT Information

Report NO : 752311
Test Mode : Mode 1
Test Voltage : 120Vac/60Hz
Phase : Neutral

ENV216 Auto Test FCC Power Bar - N



Final Result 1

Frequency (MHz)	QuasiPeak (dBµV)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
0.150000	44.5	Off	N	19.5	21.5	66.0
0.246000	35.0	Off	N	19.5	26.9	61.9
0.342000	31.6	Off	N	19.5	27.6	59.2
0.670000	31.5	Off	N	19.5	24.5	56.0
1.406000	27.9	Off	N	19.6	28.1	56.0
3.550000	32.3	Off	N	19.6	23.7	56.0
13.558000	47.8	Off	N	20.3	12.2	60.0

Final Result 2

Frequency (MHz)	Average (dBµV)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
0.150000	23.8	Off	N	19.5	32.2	56.0
0.246000	23.2	Off	N	19.5	28.7	51.9
0.342000	20.0	Off	N	19.5	29.2	49.2
0.670000	22.5	Off	N	19.5	23.5	46.0
1.406000	20.8	Off	N	19.6	25.2	46.0
3.550000	18.8	Off	N	19.6	27.2	46.0
13.558000	42.9	Off	N	20.3	7.1	50.0



Appendix C. Radiated Spurious Emission

Test Engineer :	Peter Liao and Nick Yu	Temperature :	21~23°C
		Relative Humidity :	54~56%

2.4GHz 2400~2483.5MHz

BLE 4.0 (Band Edge @ 3m)

BLE	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
BLE CH 00 2402MHz		2359.14	53.47	-20.53	74	43.95	26.98	4.01	31.5	299	21	P	H
		2371.215	43.02	-10.98	54	33.46	27.01	4.01	31.49	299	21	A	H
	*	2402	95.17	-	-	85.48	27.11	4.04	31.49	299	21	P	H
	*	2402	94.16	-	-	84.47	27.11	4.04	31.49	299	21	A	H
													H
													H
		2335.62	53.81	-20.19	74	44.4	26.91	3.98	31.51	278	340	P	V
		2381.61	42.94	-11.06	54	33.33	27.04	4.03	31.49	278	340	A	V
	*	2402	95.78	-	-	86.09	27.11	4.04	31.49	278	340	P	V
	*	2402	94.72	-	-	85.03	27.11	4.04	31.49	278	340	A	V
													V
													V
BLE CH 19 2440MHz		2377.76	53.13	-20.87	74	43.53	27.03	4.03	31.49	236	30	P	H
		2389.52	42.68	-11.32	54	33.04	27.07	4.03	31.49	236	30	A	H
	*	2440	93.09	-	-	83.25	27.22	4.07	31.48	236	30	P	H
	*	2440	92.18	-	-	82.34	27.22	4.07	31.48	236	30	A	H
		2497.34	54.68	-19.32	74	44.61	27.39	4.11	31.46	236	30	P	H
		2495.24	42.88	-11.12	54	32.81	27.39	4.11	31.46	236	30	A	H
		2383.92	53.81	-20.19	74	44.19	27.05	4.03	31.49	266	328	P	V
		2374.82	42.82	-11.18	54	33.25	27.02	4.01	31.49	266	328	A	V
	*	2440	95.57	-	-	85.73	27.22	4.07	31.48	266	328	P	V
	*	2440	94.63	-	-	84.79	27.22	4.07	31.48	266	328	A	V
		2497.48	55.55	-18.45	74	45.48	27.39	4.11	31.46	266	328	P	V
		2499.44	43.08	-10.92	54	33	27.4	4.11	31.46	266	328	A	V



BLE CH 39 2480MHz	*	2480	92.78	-	-	82.79	27.34	4.09	31.47	294	11	P	H
	*	2480	91.76	-	-	81.77	27.34	4.09	31.47	294	11	A	H
		2497.32	53.97	-20.03	74	43.9	27.39	4.11	31.46	294	11	P	H
		2488	42.84	-11.16	54	32.81	27.36	4.11	31.47	294	11	A	H
													H
													H
	*	2480	95.06	-	-	85.07	27.34	4.09	31.47	256	337	P	V
	*	2480	94.1	-	-	84.11	27.34	4.09	31.47	256	337	A	V
		2484.08	54.25	-19.75	74	44.23	27.35	4.11	31.47	256	337	P	V
		2485.36	43.22	-10.78	54	33.19	27.36	4.11	31.47	256	337	A	V
													V
													V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



2.4GHz 2400~2483.5MHz
BLE 4.0 (Harmonic @ 3m)

BLE	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
BLE CH 00 2402MHz		4804	39.49	-34.51	74	58.97	32.15	6.16	58.33	100	0	P	H
													H
													H
													H
		4804	40.21	-33.79	74	59.69	32.15	6.16	58.33	100	0	P	V
													V
													V
													V
BLE CH 19 2440MHz		4880	40.49	-33.51	74	59.72	32.28	6.21	58.24	100	0	P	H
		7320	45.58	-28.42	74	59.62	37	7.72	59.1	100	0	P	H
													H
													H
		4880	40.66	-33.34	74	59.89	32.28	6.21	58.24	100	0	P	V
		7320	44.98	-29.02	74	59.02	37	7.72	59.1	100	0	P	V
													V
													V
BLE CH 39 2480MHz		4960	40.57	-33.43	74	59.53	32.43	6.26	58.14	100	0	P	H
		7440	44.6	-29.4	74	58.37	37.33	7.75	59.17	100	0	P	H
													H
													H
		4960	40.7	-33.3	74	59.66	32.43	6.26	58.14	100	0	P	V
		7440	45.11	-28.89	74	58.88	37.33	7.75	59.17	100	0	P	V
													V
													V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												

Emission below 1GHz

2.4GHz BLE 4.0 (LF)

BLE	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
2.4GHz BLE LF		36.75	24.44	-15.56	40	33.2	21.05	0.48	30.27	-	-	P	H
		90.75	20.49	-23.01	43.5	35.12	14.96	0.76	30.41	-	-	P	H
		255.72	21.29	-24.71	46	30.5	19.52	1.32	30.2	-	-	P	H
		667.5	28.95	-17.05	46	29.8	26.56	2.05	29.57	-	-	P	H
		752.9	30.71	-15.29	46	29.63	28.2	2.21	29.43	100	0	P	H
		976.9	34.92	-19.08	54	30.09	31.08	2.53	29.01	-	-	P	H
													H
													H
													H
													H
													H
													H
													H
		36.75	33.3	-6.7	40	42.06	21.05	0.48	30.27	100	0	P	V
		44.31	27.32	-12.68	40	40.25	16.84	0.6	30.38	-	-	P	V
		90.21	21.13	-22.37	43.5	35.88	14.84	0.76	30.41	-	-	P	V
		565.3	28.54	-17.46	46	30.13	26.09	1.92	29.71	-	-	P	V
		755	30.69	-15.31	46	29.58	28.22	2.21	29.42	-	-	P	V
		972	34.53	-19.47	54	29.72	31.09	2.51	29.02	-	-	P	V
													V
													V
													V
													V
													V
												V	
												V	
Remark	1. No other spurious found. 2. All results are PASS against limit line.												



Note symbol

*	Fundamental Frequency which can be ignored. However, the level of any unwanted emissions shall not exceed the level of the fundamental frequency.
!	Test result is over limit line.
P/A	Peak or Average
H/V	Horizontal or Vertical



A calculation example for radiated spurious emission is shown as below:

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
1+2		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
802.11b		2390	55.45	-18.55	74	54.51	32.22	4.58	35.86	103	308	P	H
CH 01													
2412MHz		2390	43.54	-10.46	54	42.6	32.22	4.58	35.86	103	308	A	H

1. Level(dBμV/m) =

Antenna Factor(dB/m) + Cable Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)

2. Over Limit(dB) = Level(dBμV/m) – Limit Line(dBμV/m)

For Peak Limit @ 2390MHz:

1. Level(dBμV/m)

= Antenna Factor(dB/m) + Cable Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)

= 32.22(dB/m) + 4.58(dB) + 54.51(dBμV) – 35.86 (dB)

= 55.45 (dBμV/m)

2. Over Limit(dB)

= Level(dBμV/m) – Limit Line(dBμV/m)

= 55.45(dBμV/m) – 74(dBμV/m)

= -18.55(dB)

For Average Limit @ 2390MHz:

1. Level(dBμV/m)

= Antenna Factor(dB/m) + Cable Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)

= 32.22(dB/m) + 4.58(dB) + 42.6(dBμV) – 35.86 (dB)

= 43.54 (dBμV/m)

2. Over Limit(dB)

= Level(dBμV/m) – Limit Line(dBμV/m)

= 43.54(dBμV/m) – 54(dBμV/m)

= -10.46(dB)

Both peak and average measured complies with the limit line, so test result is “PASS”.



2.4GHz 2400~2483.5MHz

BLE 5.0 (Band Edge @ 3m)

BLE	Note	Frequency	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Cable Loss	Preamplifier Factor	Ant Pos	Table Pos	Peak Avg.	Pol.
		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
BLE CH 00 2402MHz		2332.05	53.76	-20.24	74	44.36	26.9	3.98	31.51	255	40	P	H
		2371.32	42.82	-11.18	54	33.26	27.01	4.01	31.49	255	40	A	H
	*	2402	94.89	-	-	85.2	27.11	4.04	31.49	255	40	P	H
	*	2402	91.89	-	-	82.2	27.11	4.04	31.49	255	40	A	H
													H
													H
		2317.875	53.16	-20.84	74	43.82	26.85	3.97	31.51	266	323	P	V
		2376.465	42.84	-11.16	54	33.24	27.03	4.03	31.49	266	323	A	V
	*	2402	95.52	-	-	85.83	27.11	4.04	31.49	266	323	P	V
	*	2402	92.65	-	-	82.96	27.11	4.04	31.49	266	323	A	V
													V
													V
BLE CH 19 2440MHz		2338.84	53.78	-20.22	74	44.35	26.92	3.98	31.5	182	2	P	H
		2383.22	42.8	-11.2	54	33.18	27.05	4.03	31.49	182	2	A	H
	*	2440	92.74	-	-	82.9	27.22	4.07	31.48	182	2	P	H
	*	2440	89.13	-	-	79.29	27.22	4.07	31.48	182	2	A	H
		2484.11	53.9	-20.1	74	43.88	27.35	4.11	31.47	182	2	P	H
		2498.95	43	-11	54	32.92	27.4	4.11	31.46	182	2	A	H
		2372.72	53.02	-20.98	74	43.45	27.02	4.01	31.49	292	325	P	V
		2373.56	42.84	-11.16	54	33.27	27.02	4.01	31.49	292	325	A	V
	*	2440	95.6	-	-	85.76	27.22	4.07	31.48	292	325	P	V
	*	2440	92.64	-	-	82.8	27.22	4.07	31.48	292	325	A	V
		2492.58	53.3	-20.7	74	43.24	27.38	4.11	31.46	292	325	P	V
		2498.81	43.01	-10.99	54	32.93	27.4	4.11	31.46	292	325	A	V



BLE CH 39 2480MHz	*	2480	90.21	-	-	80.22	27.34	4.09	31.47	368	33	P	H
	*	2480	86.69	-	-	76.7	27.34	4.09	31.47	368	33	A	H
		2491.84	53.75	-20.25	74	43.69	27.38	4.11	31.46	368	33	P	H
		2494.8	43.13	-10.87	54	33.07	27.38	4.11	31.46	368	33	A	H
													H
													H
	*	2480	93.8	-	-	83.81	27.34	4.09	31.47	129	342	P	V
	*	2480	88.89	-	-	78.9	27.34	4.09	31.47	129	342	A	V
		2491.52	54.46	-19.54	74	44.42	27.37	4.11	31.47	129	342	P	V
		2483.84	42.97	-11.03	54	32.95	27.35	4.11	31.47	129	342	A	V
													V
													V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



**2.4GHz 2400~2483.5MHz
BLE 5.0 (Harmonic @ 3m)**

BLE	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
BLE CH 00 2402MHz		4804	39.87	-34.13	74	59.35	32.15	6.16	58.33	100	0	P	H
													H
													H
													H
		4804	40.57	-33.43	74	60.05	32.15	6.16	58.33	100	0	P	V
													V
													V
													V
BLE CH 19 2440MHz		4880	40.61	-33.39	74	59.84	32.28	6.21	58.24	100	0	P	H
		7320	45.2	-28.8	74	59.24	37	7.72	59.1	100	0	P	H
													H
													H
		4880	41.07	-32.93	74	60.3	32.28	6.21	58.24	100	0	P	V
		7320	45.39	-28.61	74	59.43	37	7.72	59.1	100	0	P	V
													V
													V
BLE CH 39 2480MHz		4960	41.07	-32.93	74	60.03	32.43	6.26	58.14	100	0	P	H
		7440	44.39	-29.61	74	58.16	37.33	7.75	59.17	100	0	P	H
													H
													H
		4960	41.19	-32.81	74	60.15	32.43	6.26	58.14	100	0	P	V
		7440	46.23	-27.77	74	60	37.33	7.75	59.17	100	0	P	V
													V
													V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



Note symbol

*	Fundamental Frequency which can be ignored. However, the level of any unwanted emissions shall not exceed the level of the fundamental frequency.
!	Test result is over limit line.
P/A	Peak or Average
H/V	Horizontal or Vertical



A calculation example for radiated spurious emission is shown as below:

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
1+2		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
802.11b		2390	55.45	-18.55	74	54.51	32.22	4.58	35.86	103	308	P	H
CH 01													
2412MHz		2390	43.54	-10.46	54	42.6	32.22	4.58	35.86	103	308	A	H

1. Level(dBμV/m) =

Antenna Factor(dB/m) + Cable Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)

2. Over Limit(dB) = Level(dBμV/m) – Limit Line(dBμV/m)

For Peak Limit @ 2390MHz:

1. Level(dBμV/m)

= Antenna Factor(dB/m) + Cable Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)

= 32.22(dB/m) + 4.58(dB) + 54.51(dBμV) – 35.86 (dB)

= 55.45 (dBμV/m)

2. Over Limit(dB)

= Level(dBμV/m) – Limit Line(dBμV/m)

= 55.45(dBμV/m) – 74(dBμV/m)

= -18.55(dB)

For Average Limit @ 2390MHz:

1. Level(dBμV/m)

= Antenna Factor(dB/m) + Cable Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)

= 32.22(dB/m) + 4.58(dB) + 42.6(dBμV) – 35.86 (dB)

= 43.54 (dBμV/m)

2. Over Limit(dB)

= Level(dBμV/m) – Limit Line(dBμV/m)

= 43.54(dBμV/m) – 54(dBμV/m)

= -10.46(dB)

Both peak and average measured complies with the limit line, so test result is “PASS”.



Appendix D. Radiated Spurious Emission Plots

Test Engineer :	Peter Liao and Nick Yu	Temperature :	21~23℃
		Relative Humidity :	54~56%





Note symbol

-L	Low channel location
-R	High channel location







2.4GHz 2400~2483.5MHz





BLE 4.0 (Band Edge @ 3m)

BLE	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	BLE CH00 2402MHz	
1	Horizontal	Fundamental
Peak	 Site : 03CH12-HY Condition : PEAK_BE_74 3m HORN_9120D_1328 HORIZONTAL Detector : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Project : Peak Mode : 752311 : 4	 Site : 03CH12-HY Condition : PEAK_74 3m HORN_9120D_1328 HORIZONTAL Detector : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Project : Peak Mode : 752311 : 4
Avg.	 Site : 03CH12-HY Condition : AVG_BE_54 3m HORN_9120D_1328 HORIZONTAL Detector : RBW:1000.000KHz VBW:3.000KHz SWT:Auto Project : Peak Mode : 752311 : 4	 Site : 03CH12-HY Condition : AVG_54 3m HORN_9120D_1328 HORIZONTAL Detector : RBW:1000.000KHz VBW:3.000KHz SWT:Auto Project : Peak Mode : 752311 : 4





BLE	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	BLE CH00 2402MHz	
1	Vertical	Fundamental
Peak	 Site : 03CH12-HY Condition : PEAK, BE_74 3m HORN_9120D_1338 VERTICAL Detector : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Project : Peak Mode : 752311 -4	 Site : 03CH12-HY Condition : PEAK, 74 3m HORN_9120D_1338 VERTICAL Detector : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Project : Peak Mode : 752311 -4
Avg	 Site : 03CH12-HY Condition : AVG, BE_54 3m HORN_9120D_1338 VERTICAL Detector : RBW:1000.000KHz VBW:3.000KHz SWT:Auto Project : Peak Mode : 752311 -4	 Site : 03CH12-HY Condition : AVG, 54 3m HORN_9120D_1338 VERTICAL Detector : RBW:1000.000KHz VBW:3.000KHz SWT:Auto Project : Peak Mode : 752311 -4



BLE	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	BLE CH19 2440MHz - L	
1	Horizontal	Fundamental
Peak	 Site : 03CH12-HY Condition : PEAK_BE_74 3m HORN_9120D_1328 HORIZONTAL Detector : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Project : Peak Mode : 752311 : 5	 Site : 03CH12-HY Condition : PEAK_74 3m HORN_9120D_1328 HORIZONTAL Detector : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Project : Peak Mode : 752311 : 5
Avg.	 Site : 03CH12-HY Condition : AVG_BE_54 3m HORN_9120D_1328 HORIZONTAL Detector : RBW:1000.000KHz VBW:3.000KHz SWT:Auto Project : Peak Mode : 752311 : 5	 Site : 03CH12-HY Condition : AVG_54 3m HORN_9120D_1328 HORIZONTAL Detector : RBW:1000.000KHz VBW:3.000KHz SWT:Auto Project : Peak Mode : 752311 : 5





BLE	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	BLE CH19 2440MHz - R	
1	Horizontal	Fundamental
Peak	 Site: 03CH12-HY Condition: PEAK_BE_74 3m HORN_91200_1328 HORIZONTAL Detector: RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Project: Peak Mode: 752311 : 5	Left blank
Avg.	 Site: 03CH12-HY Condition: AVG_BE_54 3m HORN_91200_1328 HORIZONTAL Detector: RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Project: Peak Mode: 752311 : 5	Left blank







BLE	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	BLE CH19 2440MHz - L	
1	Vertical	Fundamental
Peak	Site: 03CH12-HY Condition: PEAK, BE_74 3m HORN_9120D_1378 VERTICAL Detector: RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Project: Peak 752311 Mode: 5	Site: 03CH12-HY Condition: PEAK, 74 3m HORN_9120D_1378 VERTICAL Detector: RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Project: Peak 752311 Mode: 5
Avg.	Site: 03CH12-HY Condition: AVG, BE_54 3m HORN_9120D_1378 VERTICAL Detector: RBW:1000.000KHz VBW:3.000KHz SWT:Auto Project: Peak 752311 Mode: 5	Site: 03CH12-HY Condition: AVG, 54 3m HORN_9120D_1378 VERTICAL Detector: RBW:1000.000KHz VBW:3.000KHz SWT:Auto Project: Peak 752311 Mode: 5







BLE	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	BLE CH19 2440MHz - R	
1	Vertical	Fundamental
Peak	 Site: 03CH12-HY Condition: PEAK_BE_74 3m HORN_91200_1378 VERTICAL Detector: RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Project: Peak Mode: 752311 : 5 Date: 2017-06-17	Left blank
Avg.	 Site: 03CH12-HY Condition: AVG_BE_54 3m HORN_91200_1378 VERTICAL Detector: RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Project: Peak Mode: 752311 : 5 Date: 2017-06-17	Left blank



BLE	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	BLE CH39 2480MHz	
1	Horizontal	Fundamental
Peak	 Site : 03CH12-HY Condition : PEAK_BE_74 3m HORN_9120D_1328 HORIZONTAL Detector : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Project : Peak Mode : 752311 6	 Site : 03CH12-HY Condition : PEAK_74 3m HORN_9120D_1328 HORIZONTAL Detector : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Project : Peak Mode : 752311 6
Avg.	 Site : 03CH12-HY Condition : AVG_BE_54 3m HORN_9120D_1328 HORIZONTAL Detector : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Project : Peak Mode : 752311 6	 Site : 03CH12-HY Condition : AVG_54 3m HORN_9120D_1328 HORIZONTAL Detector : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Project : Peak Mode : 752311 6





BLE	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	BLE CH39 2480MHz	
1	Vertical	Fundamental
Peak	 Site Condition : 03CH12-HY : PEAK_BE_74 3m HORN_9120D_1338 VERTICAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 752311 Mode : 6	 Site Condition : 03CH12-HY : PEAK_74 3m HORN_9120D_1338 VERTICAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 752311 Mode : 6
Avg.	 Site Condition : 03CH12-HY : AVG_BE_54 3m HORN_9120D_1338 VERTICAL : RBW:1000.000KHz VBW:3.000KHz SWT:Auto Detector : Peak Project : 752311 Mode : 6	 Site Condition : 03CH12-HY : AVG_54 3m HORN_9120D_1338 VERTICAL : RBW:1000.000KHz VBW:3.000KHz SWT:Auto Detector : Peak Project : 752311 Mode : 6





2.4GHz 2400~2483.5MHz

BLE 4.0 (Harmonic @ 3m)

BLE	2.4GHz 2400~2483.5MHz Harmonic @ 3m	
ANT	BLE CH00 2402MHz	
1	Horizontal	Vertical
Peak Avg.	 Site : 03CH12-HY Condition : PEAK_74 3m HORN_9120D_1328 HORIZONTAL Detector : Peak Project : 752311 Mode : 4	 Site : 03CH12-HY Condition : PEAK_74 3m HORN_9120D_1328 VERTICAL Detector : Peak Project : 752311 Mode : 4





BLE	2.4GHz 2400~2483.5MHz Harmonic @ 3m	
ANT	BLE CH19 2440MHz	
1	Horizontal	Vertical
Peak Avg.	 Site Condition : 03CH12-HY Detector : PEAK_74 3m HORN_9120D_1328 HORIZONTAL Project : Peak Mode : 752311 : 5	 Site Condition : 03CH12-HY Detector : PEAK_74 3m HORN_9120D_1328 VERTICAL Project : Peak Mode : 752311 : 5



BLE	2.4GHz 2400~2483.5MHz Harmonic @ 3m	
ANT	BLE CH39 2480MHz	
1	Horizontal	Vertical
Peak	Site : 03CH12-HY Condition : PEAK_74 3m HORN_9120D_1328 HORIZONTAL Detector : Peak Project : 752311 Mode : 6	Site : 03CH12-HY Condition : PEAK_74 3m HORN_9120D_1328 VERTICAL Detector : Peak Project : 752311 Mode : 6





Emission below 1GHz
2.4GHz BLE 4.0 (LF)

BLE	2.4GHz 2400~2483.5MHz	
ANT	BLE LF	
1	Horizontal	Vertical
QP / Peak	 Site : 03CH12-HY Condition : QP 3m BILOG_6111D_37059 HORIZONTAL Detector : Peak Project : 752311 Mode : 26	 Site : 03CH12-HY Condition : QP 3m BILOG_6111D_37059 VERTICAL Detector : Peak Project : 752311 Mode : 26



2.4GHz 2400~2483.5MHz

BLE 5.0 (Band Edge @ 3m)

BLE	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	BLE CH00 2402MHz	
1	Horizontal	Fundamental
Peak	 Site Condition : 03CH12-HY : PEAK_BE_74 3m HORN_9120D_1328 HORIZONTAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 752311 Mode : 7	 Site Condition : 03CH12-HY : PEAK_74 3m HORN_9120D_1328 HORIZONTAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 752311 Mode : 7
Avg.	 Site Condition : 03CH12-HY : AVG_BE_54 3m HORN_9120D_1328 HORIZONTAL : RBW:1000.000KHz VBW:3.000KHz SWT:Auto Detector : Peak Project : 752311 Mode : 7	 Site Condition : 03CH12-HY : AVG_54 3m HORN_9120D_1328 HORIZONTAL : RBW:1000.000KHz VBW:3.000KHz SWT:Auto Detector : Peak Project : 752311 Mode : 7





BLE	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	BLE CH00 2402MHz	
1	Vertical	Fundamental
Peak	Site : 03CH12-HY Condition : PEAK, BE_74 3m HORN_9120D_1338 VERTICAL Detector : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Project : Peak Mode : 752311 7	Site : 03CH12-HY Condition : PEAK, 74 3m HORN_9120D_1338 VERTICAL Detector : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Project : Peak Mode : 752311 7
Avg	Site : 03CH12-HY Condition : AVG, BE_54 3m HORN_9120D_1338 VERTICAL Detector : RBW:1000.000KHz VBW:3.000KHz SWT:Auto Project : Peak Mode : 752311 7	Site : 03CH12-HY Condition : AVG, 54 3m HORN_9120D_1338 VERTICAL Detector : RBW:1000.000KHz VBW:3.000KHz SWT:Auto Project : Peak Mode : 752311 7



BLE	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	BLE CH19 2440MHz - L	
1	Horizontal	Fundamental
Peak	Site : 03CH12-HY Condition : PEAK_BE_74 3m HORN_9120D_1328 HORIZONTAL Detector : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Project : Peak Mode : 752311 Date: 2017-06-20	Site : 03CH12-HY Condition : PEAK_74 3m HORN_9120D_1328 HORIZONTAL Detector : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Project : Peak Mode : 752311 Date: 2017-06-20
Avg.	Site : 03CH12-HY Condition : AVG_BE_54 3m HORN_9120D_1328 HORIZONTAL Detector : RBW:1000.000KHz VBW:3.000KHz SWT:Auto Project : Peak Mode : 752311 Date: 2017-06-20	Site : 03CH12-HY Condition : AVG_54 3m HORN_9120D_1328 HORIZONTAL Detector : RBW:1000.000KHz VBW:3.000KHz SWT:Auto Project : Peak Mode : 752311 Date: 2017-06-20





BLE	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	BLE CH19 2440MHz - R	
1	Horizontal	Fundamental
Peak	 Site: 03CH12-HY Condition: PEAK_BE_74 3m HORN_91200_1328 HORIZONTAL Detector: RBW:1000.000KHz VBW:3000.000KHz SWT:auto Project: Peak Mode: 752311 :8	Left blank
Avg.	 Site: 03CH12-HY Condition: AVG_BE_54 3m HORN_91200_1328 HORIZONTAL Detector: RBW:1000.000KHz VBW:3.000KHz SWT:auto Project: Peak Mode: 752311 :8	Left blank







BLE	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	BLE CH19 2440MHz - L	
1	Vertical	Fundamental
Peak	Site : 03CH12-HY Condition : PEAK, BE_74 3m HORN_9120D_1338 VERTICAL Detector : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Project : Peak Mode : 752311 : 8	Site : 03CH12-HY Condition : PEAK, 74 3m HORN_9120D_1338 VERTICAL Detector : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Project : Peak Mode : 752311 : 8
Avg.	Site : 03CH12-HY Condition : AVG, BE_54 3m HORN_9120D_1338 VERTICAL Detector : RBW:1000.000KHz VBW:3.000KHz SWT:Auto Project : Peak Mode : 752311 : 8	Site : 03CH12-HY Condition : AVG, 54 3m HORN_9120D_1338 VERTICAL Detector : RBW:1000.000KHz VBW:3.000KHz SWT:Auto Project : Peak Mode : 752311 : 8







BLE	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	BLE CH19 2440MHz - R	
1	Vertical	Fundamental
Peak	 Site: 03CH12-HY Condition: PEAK_BE_74 3m HORN_91200_1378 VERTICAL Detector: RBW:1000.000KHz VSW:3.000KHz SWT:Auto Project: Peak 752311 Mode: 8 Date: 2017.06.19	Left blank
Avg.	 Site: 03CH12-HY Condition: AVG_BE_54 3m HORN_91200_1378 VERTICAL Detector: RBW:1000.000KHz VSW:3.000KHz SWT:Auto Project: Peak 752311 Mode: 8 Date: 2017.06.19	Left blank



BLE	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	BLE CH39 2480MHz	
1	Horizontal	Fundamental
Peak	 Site : 03CH12-HY Condition : PEAK_BE_74 3m HORN_9120D_1328 HORIZONTAL Detector : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Project : Peak Mode : 752311 -9	 Site : 03CH12-HY Condition : PEAK_74 3m HORN_9120D_1328 HORIZONTAL Detector : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Project : Peak Mode : 752311 -9
Avg.	 Site : 03CH12-HY Condition : AVG_BE_54 3m HORN_9120D_1328 HORIZONTAL Detector : RBW:1000.000KHz VBW:3.000KHz SWT:Auto Project : Peak Mode : 752311 -9	 Site : 03CH12-HY Condition : AVG_54 3m HORN_9120D_1328 HORIZONTAL Detector : RBW:1000.000KHz VBW:3.000KHz SWT:Auto Project : Peak Mode : 752311 -9





BLE	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	BLE CH39 2480MHz	
1	Vertical	Fundamental
Peak	 Site : 03CH12-HY Condition : PEAK_BE_74 3m HORN_9120D_1338 VERTICAL Detector : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Project : Peak Mode : 752311 9	 Site : 03CH12-HY Condition : PEAK_74 3m HORN_9120D_1338 VERTICAL Detector : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Project : Peak Mode : 752311 9
Avg.	 Site : 03CH12-HY Condition : AVG_BE_54 3m HORN_9120D_1338 VERTICAL Detector : RBW:1000.000KHz VBW:3.000KHz SWT:Auto Project : Peak Mode : 752311 9	 Site : 03CH12-HY Condition : AVG_54 3m HORN_9120D_1338 VERTICAL Detector : RBW:1000.000KHz VBW:3.000KHz SWT:Auto Project : Peak Mode : 752311 9





2.4GHz 2400~2483.5MHz

BLE 5.0 (Harmonic @ 3m)

BLE	2.4GHz 2400~2483.5MHz Harmonic @ 3m	
ANT	BLE CH00 2402MHz	
1	Horizontal	Vertical
Peak Avg.	 Site : 03CH12-HY Condition : PEAK_74 3m HORN_9120D_1328 HORIZONTAL Detector : Peak Project : 752311 Mode : 7	 Site : 03CH12-HY Condition : PEAK_74 3m HORN_9120D_1328 VERTICAL Detector : Peak Project : 752311 Mode : 7



BLE	2.4GHz 2400~2483.5MHz Harmonic @ 3m	
ANT	BLE CH19 2440MHz	
1	Horizontal	Vertical
Peak Avg.	 Site Condition : 03CH12-HY Detector : PEAK_74 3m HORN_9120D_1328 HORIZONTAL Project : Peak Mode : 752311 : 8	 Site Condition : 03CH12-HY Detector : PEAK_74 3m HORN_9120D_1328 VERTICAL Project : Peak Mode : 752311 : 8




BLE	2.4GHz 2400~2483.5MHz Harmonic @ 3m	
ANT	BLE CH39 2480MHz	
1	Horizontal	Vertical
Peak	Site : 03CH12-HY Condition : PEAK_74 3m HORN_9120D_1328 HORIZONTAL Detector : Peak Project : 752311 Mode : 9	Site : 03CH12-HY Condition : PEAK_74 3m HORN_9120D_1328 VERTICAL Detector : Peak Project : 752311 Mode : 9

Appendix E. Duty Cycle Plots

Band	Duty Cycle(%)	T(us)	1/T(kHz)	VBW Setting
Bluetooth –LE 4.0/5.0	62.18	388.00	2.58	3kHz

Bluetooth –LE 4.0/5.0



Date: 1.JUN.2017 00:45:35