

FCC ID: PQSWAVENET-DUAL-V
Class II Permissive Changes

Exhibit 2 B

Engineering Report on

Field Strength of Spurious Radiation (2.1053)



Assessment of Compliance

For

Measurement of Field Strength of Spurious Radiation in accordance
with the FCC Rules & Regulations Part 2.1053 and 90

**PDA Wireless Modem attachment for Palm V/V_x
DWV 100D**

Wavenet Technologies Pty Ltd.



March 2002

APREL Project No.:WVTB-Dual Wave V Motient Cradle - 3873

51 Spectrum Way Nepean ON K2R 1E6
Tel: (613) 820-2730 Fax: (613) 820-4161
email: info@aprel.com

Engineering Report

Subject: Measurement of Field Strength of Spurious
Radiation in accordance with the
FCC Rules & Regulations Part 2.1053 and 90

FCC ID: PQSWAVENET-DUAL-V

Equipment: PDA Wireless Modem attachment for Palm V/Vx

Model: DWV 100D

Client: Wavenet Technologies Pty Ltd.
140 Burswood Rd
Burswood, Perth, WA 6100
AUSTRALIA

Project #: WWTB-Dual Wave V Motient Cradle-3873

Prepared By: APREL Laboratories,
Regulatory Compliance Division
51 Spectrum Way
Nepean, Ontario
K2R 1E6

Approved by:



Date:

April 18, 2002

Jay Sarkar:
Technical Director, Standards & Certification

Submitted by:




Date:

April 18, 2002

Jay Sarkar:
Technical Director, Standards & Certification

Released by:


Dr. Jack J. Wojcik, P.Eng.

Date:

April 18/02



FCC ID: PQSWAVENET-DUAL-V
Applicant: Wavenet Technologies Pty Ltd.
Equipment: PDA Wireless Modem attachment for Palm V/V_x
Model: DWV 100D
Standard: FCC Rules and Regulations Part 2.1053 and 90
Application for: Class II Permissive change

ENGINEERING SUMMARY

This report contains the results of Field Strength of Spurious Radiation measurement performed on a Wavenet PDA Wireless Modem attachment for Palm V/V_x, model DWV 100D in accordance with the FCC Rules and Regulations Part 2.1053 and 90. The measurements were carried out using direct method and substitution method both as radiated. The product was evaluated for spurious radiation when it was set at the maximum power level.

The PDA Wireless Modem is an attachment for a Palm PDA and it can also be attached to a PC.

The DWV 100D was evaluated in three configurations:

1. PDA Wireless Modem attached to Palm V
2. PDA Wireless Modem attached to Palm V and connected to PC
3. PDA Wireless Modem (cradle only) connected to PC.

The highest values of Spurious Emissions were obtained in configuration **1** (PDA Wireless Modem attached to Palm V) placed in vertical position. As such, test data using both methods (direct and substitution) for configuration 1 only is presented. The test data for configurations 2 and 3 are given using only substitution method.

The results presented in this report relate only to the sample tested.

Summary of the Results

Test Description	Page No.	Test Set-up Figure No.	Results Summary
Field Strength of Spurious Radiation Ref. Paragraph 2.1053 and 90	8	1	Passed

INTRODUCTION

General

This report describes the results of the Field Strength of Spurious Radiation measurement conducted on a Wavenet PDA Wireless Modem attachment for Palm V/Vx, model DWV 100D.

Test Facility

The tests were performed for Wavenet Technologies Pty Ltd. by APREL Laboratories at APREL's EMI facility located in Nepean, Ontario, Canada. The laboratory operates an (3m and 10m) Open Area Test Site (OATS). The measurement facility is calibrated in accordance with ANSI C63.4-1992.

A description of the measurement facility in accordance with the radiated and AC line conducted test site criteria per ANSI C63.4-1992 is on file with the Federal Communications Commission and is in compliance with the requirements of Section 2.948 of the Commissions rules and regulations.

APREL's registration number is 90416

APREL is accredited by Standard Council of Canada. APREL is also accredited by Industry Canada and recognised by the Federal Communications Commissions (FCC).

Standard

The evaluation and analysis were conducted in accordance with FCC Rules and Regulations Parts 2.1053 and the appropriate limits (90).

Test Equipment

The test equipment used during the evaluation is listed in Appendix A with calibration due dates.

Environmental Conditions

Measurements were conducted in open area test site.

- Temperature: 24 °C ± 2
- Relative Humidity: 30 - 50 %
- Air Pressure: 101 kPa ± 3

FCC SUBMISSION INFORMATION

FCC ID: PQSWAVENET-DUAL-V

Equipment type: PDA Wireless Modem attachment for Palm V/Vx

Model: DWV 100D

For: Certification

Applicant: **Wavenet Technologies Pty Ltd.**
140 Burswood Rd
Burswood, Perth, WA 6100
AUSTRALIA

Manufacturer: **Wavenet Technologies Pty Ltd.**
140 Burswood Rd
Burswood, Perth, WA 6100
AUSTRALIA

Evaluated by: **APREL Laboratories**
51 Spectrum Way
Nepean, Ontario
Canada K2R 1E6

MANUFACTURER'S DATA

FCC ID:	PQSWAVENET-DUAL-V
Equipment Type:	PDA Wireless Modem attachment for Palm V/V _x
Model:	DWV 100D
Reference:	FCC Rules and Regulations Parts 2 and Part 90
Manufacturer:	Wavenet Technologies Pty Ltd
Power Source:	3.6 (nominal) VDC Battery, Lithium-ion
Development Stage of Unit:	Production

GENERAL SPECIFICATIONS

1. Frequency Range: 806.00 to 821.00 MHz (Transmitter)
2. Output Power: 1.820 W (ERP)
3. Emission Designators (See 47 CFR § 2.201 and §2.202): 20K0F1D
4. Antenna Impedance: 50 Ω

Test: Field Strength of Spurious Radiation

Ref: FCC Parts 2.1053 and 90.210

Criteria: Emission Mask G:

The permitted maximum level of spurious emission is $43 + 10 \cdot \log_{10}(P)$ dB below the unmodulated carrier power of the transmitter (P).

Set-up: See Figure 1.a

Conditions: Voltage Supply: DC Battery

Equipment: See Appendix A.


Procedure: A. Direct Method as Radiated (See Section B for Substitution Method).

The final measurements were taken at APREL Laboratory's open area test site (OATS) measurement facility. This open area test site is calibrated to ANSI C63.4 document and a description of the measurement facility is on file with the Federal Communications Commission and is in compliance with the requirements of Section 2.948 of the Commissions rules and regulations.
(FCC Registration No.:90416).

The **DUI** was configured to operate at maximum power with appropriate modulation. Special software was employed in order that the transmitter was processing data in a normal manner.

Prior to final measurement in the OATS, preliminary radiated spurious emissions were scanned in a shielded enclosure at a distance of 1 m using biconical, log-periodic and horn antennas in order to determine the characteristic frequencies of the field strength of spurious emissions. Based on this information, measurements were performed in the OATS at these characteristic frequencies using calibrated antennas.

All field strength measurements were made with a spectrum analyser and the appropriate calibrated antenna for the frequency range from 9 kHz up to 10th harmonics of the transmit frequency (see equipment list for the calibrated antenna used). **The Power of the carrier frequency was also measured in the OATS.**



**Figure 1.a Test set up for the Field Strength of Spurious Radiation Measurement in OATS
(Not to scale)**



Fig. 1.b APREL's OATS (Open Area Test Site)

The equipment under test was placed on a turntable positioned 3 meters away from the calibrated receiving antenna, which in turn was connected to the spectrum analyzer. For each identified frequency, the received signal was maximised by the positioning of the turntable and the height of the antenna. The process was repeated for both horizontal and vertical polarisation.

Information submitted includes the relative radiated power of each spurious emissions with reference to the calculated 87.2 dB μ V/m limit per 90.210 assuming all emissions are radiated from half-wave dipole antenna.

Measurements given in the spurious emissions test result tables contain: analyzer reading, correction factor, and final reading. The final field strength level are derived from the analyzer measurement and the correction factor (antenna factor and cable loss) as shown in the following example:

Sample Calculation for direct method

A. Spectrum analyzer reading

At 1630.00 MHz, a spurious level of 42.5 dB μ V @ 3 meters is measured.

B. Correction factor (antenna factor and cable loss)

Cable loss: 0.7 dB

Antenna Factor: 27.1 dB

Total Correction Factor: $0.7 + 27.1 = 27.8$ dB/m

C. Final reading (Field Strength of spurious emission):

$$C = A + B$$

$$C = 42.5 \text{ dB}\mu\text{V} + 27.8 \text{ dB}$$

$$C = 70.3 \text{ dB}\mu\text{V/m @ 3 meters}$$

D. The criteria level.

The field intensity, which would be produced by the transmitter carrier operating into a half-wave dipole antenna (gain of 1.64), at a distance of 3 m, was calculated using the following formula:

$$\text{Field Strength of Unmodulated Carrier (dB}\mu\text{V/m)} = 10 \log_{10} (P_t G / 4\pi r^2) + 146 \text{ dB}$$

Pt is transmitter carrier power, unmodulated

G is gain, 1.64

R is distance, 3 meters

Criteria (reference) level at 3 meters from 1.820 Watt (ERP) into half-wave dipole antenna is 87.2 dBμV/m.

E = Margin (spurious emission below the reference level)

$$E = D - C$$

$$E = 87.2 \text{ dB}\mu\text{V/m} - 70.3 \text{ dB}\mu\text{V/m}$$

$$E = 16.9 \text{ dB}\mu\text{V/m}$$

B: Substitution Method (Radiated)

The DWV 100D was also tested for spurious radiated emissions using the substitution method with a procedure similar to that used in the ERP measurement and described in the ERP measurement portion of the Test Report. A set of three reference dipoles, a horn antenna and a signal generator to duplicate the signal were used. Signals radiated from the DWV 100D on the fundamental frequency as well as second and third harmonic were evaluated by comparing to the signals transmitted from the reference dipoles. The antenna used for the first three harmonics were a set of three dipoles, $l = 18.5$ cm (first harmonic/fundamental), $l = 9.2$ cm (second harmonic), and $l = 6.0$ cm (third harmonic). For testing the higher frequencies, fourth to 8th harmonics, a calibrated horn antenna with known gain was used as a replacement source of radiation thus substituting the DWV 100D. The duplicated reading (taken in dBm) was then referenced to the dipole.

Criteria: The criteria level using substitution method was calculated to be -13.0 dBm.

This level was obtained by using the following expression:

$$\text{ERP}_{\text{Limit (dBm)}} = \text{ERP}_{\text{Carrier (dBm)}} - [43 + 10 \cdot \log_{10} \text{ERP}_{(W)}]$$

Example:

$$\text{ERP}_{\text{Limit(dBm)}} = 32.6 \text{ dBm} - [43 + 10 \cdot \log_{10}(1.820 \text{ W})]$$

$$\text{ERP}_{\text{Limit(dBm)}} = 32.6 \text{ dBm} - (43 + 2.6) \text{ dB} = -13.0 \text{ dBm}$$

Results: **Passed** **See Tables 1 and 2 for direct method**
 See Tables 3 to 8 for substitution method

Table 1

Field Strength of Spurious Radiation

Transmitter Frequency: 815.00 MHz

Antenna Polarization: **Vertical**

Resolution Bandwidth:

10 kHz (below 1 GHz)

100 kHz (above 1 GHz)

Direct Method as Radiated

Palm V attached to PDA Modem (Configuration 1)

Frequency (MHz)	Measured Level (dB μ V)	Correction Factor (dB/m)	Field Strength (dB μ V/m)	Criteria Level (dB μ V/m)	Margin (dB)
	"A"	"B"	"C"	"D"	"E"
815.00 Carrier	111.8	23.8	135.6	-	-
1630.00 2 nd harmonic	42.5	27.8	70.3	87.2	16.9
2445.00 3 rd harmonic	35.3	30.1	65.4	87.2	21.8
3260.00 4 th harmonic	20.5	32.7	53.2	87.2	34.0
4075.00 5 th harmonic	16.1	34.2	50.3	87.2	36.9
4890.00 6 th harmonic	18.5	35.2	53.7	87.2	33.5
5705.00 7 th harmonic	13.6 noise floor	36.9	50.5	87.2	36.7
6520.00 8 th harmonic	16.2	37.7	53.9	87.2	33.3
7335.00 9 th harmonic	14.0 noise floor	38.9	52.9	87.2	34.3

Test performed by:

Lu Chao Roumen

Date:

March 2002

Table 2

Field Strength of Spurious Radiation

Transmitter Frequency: 815.00 MHz

Antenna Polarization: **Horizontal****Resolution Bandwidth:**

10 kHz (below 1 GHz)

100 kHz (above 1 GHz)

Direct Method as Radiated

Palm V attached to PDA Modem(Configuration 1)

Frequency (MHz)	Measured Level (dB μ V)	Correction Factor (dB/m)	Field Strength (dB μ V/m)	Criteria Level (dB μ V/m)	Margin (dB)
	"A"	"B"	"C"	"D"	"E"
815.00 Carrier	102.1	23.8	125.9	-	-
1630.00 2 nd harmonic	32.6	27.8	60.4	87.2	26.8
2445.00 3 rd harmonic	17.8	30.1	47.9	87.2	39.3
3260.00 4 th harmonic	19.9	32.7	52.6	87.2	34.6
4075.00 5 th harmonic	18.9	34.2	53.1	87.2	34.1
4890.00 6 th harmonic	24.4	35.2	59.6	87.2	27.6
5705.00 7 th harmonic	18.8	36.9	55.7	87.2	31.5
6520.00 8 th harmonic noise floor	13.8	37.7	51.5	87.2	35.7

Test performed by:

Ku Chua Poon

Date:

March 2002

Table 3

Field Strength of Spurious Radiation

Transmitter Frequency: 815.00 MHz

Antenna Polarization: **Vertical****Substitution Method as Radiated**

Palm V attached to PDA Modem(Configuration 1)

Frequency MHz	ERP _V dBm	Limit dBm	Margin dB
1630.00	-29.3	-13.0	16.3
2445.00	-34.3	-13.0	21.3
3260.00	-46.3	-13.0	33.3
4075.00	-48.9	-13.0	35.9
4890.00	-45.0	-13.0	32.0
5705.00	-47.9 noise floor	-13.0	34.9
6520.00	-43.7	-13.0	30.7
7335.00	-44.5 noise floor	-13.0	31.5

Table 4

Field Strength of Spurious Radiation

Transmitter Frequency: 815.00 MHz

Antenna Polarization: **Horizontal****Substitution Method as Radiated**

Palm V attached to PDA Modem(Configuration 1)

f MHz	ERP _H dBm	Limit dBm	Margin dB
1630.00	-39.9	-13.0	26.9
2445.00	-52.1	-13.0	39.1
3260.00	-46.7	-13.0	33.7
4075.00	-46.0	-13.0	33.0
4890.00	-38.8	-13.0	25.8
5705.00	-42.2	-13.0	29.2
6520.00	-45.9 noise floor	-13.0	32.9

Test performed by: Ku Cho PounDate: March 2002

Table 5

Field Strength of Spurious Radiation

Transmitter Frequency: 815.00 MHz

Antenna Polarization: **Vertical****Substitution Method as Radiated**

Palm V attached to PDA Modem and connected to PC (Configuration 2)

Frequency MHz	ERP _V dBm	Limit dBm	Margin dB
1630.00	-32.0	-13.0	19.0
2445.00	-36.2	-13.0	23.2
3260.00	-46.2	-13.0	33.2
4075.00	-51.1	-13.0	38.1
4890.00	-45.2	-13.0	32.2
5705.00	-49.4	-13.0	36.4
	noise floor		
6520.00	-46.6	-13.0	33.6
7335.00	-44.5	-13.0	31.5
	noise floor		

Table 6

Field Strength of Spurious Radiation

Transmitter Frequency: 815.00 MHz

Antenna Polarization: **Horizontal****Substitution Method as Radiated**

Palm V attached to PDA Modem and connected to PC (Configuration 2)

f MHz	ERP _H dBm	Limit dBm	Margin dB
1630.00	-42.3	-13.0	29.3
2445.00	-53.6	-13.0	40.6
3260.00	-47.5	-13.0	34.5
4075.00	-47.0	-13.0	34.0
4890.00	-40.6	-13.0	27.6
5705.00	-44.2	-13.0	31.2
6520.00	-45.9	-13.0	32.9
	noise floor		

Test performed by: Ku Chee PoonDate: March 2002

Table 7

Field Strength of Spurious Radiation

Transmitter Frequency: 815.00 MHz

Antenna Polarization: **Vertical****Substitution Method as Radiated**

Modem (cradle) only connected to PC (Configuration 3)

Frequency MHz	ERP _V dBm	Limit dBm	Margin dB
1630.00	-31.8	-13.0	18.8
2445.00	-36.1	-13.0	23.1
3260.00	-46.6	-13.0	33.6
4075.00	-50.7	-13.0	37.7
4890.00	-45.6	-13.0	32.6
5705.00	-47.9	-13.0	34.9
	noise floor		
6520.00	-46.4	-13.0	33.4
7335.00	-44.5	-13.0	31.5
	noise floor		

Table 8

Field Strength of Spurious Radiation

Transmitter Frequency: 815.00 MHz

Antenna Polarization: **Horizontal****Substitution Method as Radiated**

Modem (cradle) only connected to PC (Configuration 3)

f MHz	ERP _H dBm	Limit dBm	Margin dB
1630.00	-42.6	-13.0	29.6
2445.00	-53.8	-13.0	40.8
3260.00	-47.6	-13.0	34.6
4075.00	-46.9	-13.0	33.9
4890.00	-40.6	-13.0	27.6
5705.00	-44.5	-13.0	31.5
6520.00	-45.9	-13.0	32.9
	noise floor		

Test performed by: Ku Chue PounenDate: March 2002

APPENDIX A

List of Test Equipment

List of Equipment


Description	Range	Manufacturer	Model #	APREL Asset #	Cal. Due Date
Spectrum Analyzer	9 kHz - 3 GHz	Anritsu	MS2661C	301330	Dec 10, 2002
Spectrum Analyzer	9 kHz - 30 GHz	Anritsu	MS2667C	301436	Nov 3, 2002
RF Signal Generator	10 MHz – 26.5 GHz	Hewlett Packard	HP 8340 B	100955	Oct 5, 2002
Amplifier (LNA)	30-1000 MHz	APREL Inc.	APRLNA-001	301415	June 20, 2002
Attenuator	15 dB	Pasternack	PE 7002-20	301370	CBT
Notch Filter	DC - 6 GHz	APREL Inc.	NFLT-835	301470	CBT
RF Power Meter	10 MHz - 18 GHz	Rohde & Schwarz	NRVS	100851	July 21, 2002
Biconical Antenna	20 MHz - 200 MHz	Eaton	94455-1	100890	July 21, 2002
Log - Periodic Antenna	200 MHz -1.0 GHz	Eaton	ALP-1	100761	July 21, 2002
Horn Antenna	1 – 18 GHz	APREL Inc.	AA – 118	100400	March 12, 2002
Anechoic Shielded Room	10 kHz - 10 GHz	APREL Inc.	–	301329	N/A
Reference Half -wave Dipole Antenna	815.00 MHz	APREL Inc.	–	–	N/A
Reference Half -wave Dipole Antenna	1630.00 MHz	APREL Inc.	–	–	N/A
Reference Half -wave Dipole Antenna	2500.00 MHz	APREL Inc.	–	–	N/A
OATS	30 MHz – 1 GHz	APREL Inc.	3 m & 10 m	N/A	N/A
Mast with the Controller	1 m – 4 m	EMCO	1051 – 12	100507	N/A
Turntable with the Controller	0° - 360°	EMCO	1060 – 1.241	100506	N/A

APPENDIX B

PHOTOGRAPHS





Wavenet DWV 100D PDA Wireless modem



**Palm V and WaveNet DWV 100D PDA Wireless modem
Testing for Spurious Emissions from Transmitter
Frequency Range: 30 MHz – 200 MHz**



**Palm V and WaveNet DWV 100D PDA Wireless modem
Testing for Spurious Emissions from Transmitter
in three different configurations
Frequency Range: 200 MHz – 1 GHz**



**Palm V and Wavenet DWV 100D PDA Wireless Modem
Tested for Spurious Emissions from Transmitter
in three different configurations
Frequency Range: 1 GHz – 18 GHz**