



Shenzhen Shuodian Electronic Technology Co.,Ltd
Page number 1-10

SPECIFICATION

for

DoorBell outdoor WiFi antenna

Customer No.

Product No.

WA-DoorBell-out-Left_WiFi- FPC

Author: XiaofengZeng Review: Liming

Release Date: 2024.11.22

ShenZhen Shuodian Electronic Technology Co., Ltd

Room 201, Building 2, Nantaiyun Chuanggu Park, Tangwei Community, Fenghuang Street,
Guangming District, Shenzhen City, Guangdong Province

E-mail: sz_shuodian@163.com

Tel: 0755-86006322

Fax: 0755-86006323

Shenzhen Shuodian Electronic Technology Co.,Ltd



Contents

SPECIFICATION	1
SHENZHEN SHUODIAN ELECTRONIC TECHNOLOGY CO., LTD	1
CONTENTS	2
1. BILATERAL CONFIRMATION PAGE	3
2. GENERAL	4
3. GENERAL PRODUCT SPECIFICATIONS	4
4. SPECIFICATION DETIALS	5
4.1 MECHANICAL PROPERTIES	5
4.2 ELECTRIC PERFORMANCE	7
5. PRODUCT PACKAGING	9
6. DOCUMENT RESUME	10



1. Bilateral Confirmation page

1.1 Customer signature

Customer:

Seapartment/post	Sign	Date
Hardware Engineer/RD		
Mechanical/MD		
Project Manager/PM		
Commercial/Puchasing		
Checker		

1.2 Signature of ShuoDian Technology company

Seapartment/post	Sign	Date
Antenna Engineer/RD		
Mechanical/MD		
Project Manager/PM		
QA		
Checker		



2. General

2.1 Scope of application

This specification is only applicable to WOAN DoorBell outdoor WiFi antenna

2.2 Operating temperature range

Temperature range of this product: -20 ~ +65 °C

2.3 Storage temperature range:

This product is stored at - 30 ~ + 75 °C

3. General product specifications

NO.	ITEMS	DETAILS
1	Type	DoorBell outdoor WiFi antenna
2	Operating Frequency Band	2400-2500MHz
3	VSWR	≤ 2.5
4	Impedance	50Ω
5	Antenna Type	Monopole
6	Antenna composition	FPC
7	Entity Picture	



4. Specification Detials

4.1 Mechanical Properties

4.11 Product Composition:

No.	Material	Size (MM)
1	FPC	28. 5*20. 94 Black
2	CABLE	IPEX-4 ϕ 0.81 L=85 black

4.12 Apperance

Good appearance without scars 、 dirt、 protuberances, etc.

4.13 Antenna Picture and Structure Dimension

Productdrawings:

Shenzhen Shuodian Electronic Technology Co.,Ltd



4.2 Electric Performance


4.21 Test condition


Environment:	Equipment:
Temperature: 10℃——+30℃	Network Analyzer: KEYSIGHT E5071C
Humidity: ≤80% (+40℃)	Multi-probe microwave anechoic
Atmospher: 750mmkg±30mmkg	chamber

4.22 Test Data for Electrical Performance:

4.22.1 S11 of the Antenna:

Marker	2400MHz	2450MHz	2500MHz
Returnloss	-12.76	-15.15	-10.96
VSWR	1.57	1.43	1.81






4. 22. 2 Passive gain、 efficiency and Radiation Pattern:

频率 (MHz)	Gain (dBi)	Efficiency (%)
2400.0	0.62	35.9
2410.0	0.61	36.2
2420.0	0.87	36.9
2430.0	1.06	36.6
2440.0	1.37	37.9
2450.0	1.45	37.4
2460.0	1.26	36.0
2470.0	0.96	34.8
2480.0	0.48	33.0
2490.0	-0.03	32.9
2500.0	-0.24	33.7



Radiation Pattern 2450MHz

@2450MHz



5. Product Packaging

Manner of packing:

Packed in self sealed bags, 200 pcs each.



6. Document Resume

Document No.	
Release Date	2024/11/22
Author	XiofengZeng
Review	LiMing

Revised History

Date	Version	Revised Record
2024/11/22	1.00	New Project