

MPE CALCULATION

RF Exposure Requirements:	47 CFR §1.1307(b)
RF Radiation Exposure Limits:	47 CFR §1.1310
RF Radiation Exposure Guidelines:	FCC OST/OET Bulletin Number 65
EUT Frequency Band:	2412 - 2462 MHz; 5180 - 5825MHz
Limits for General Population/Uncontrolled Exposure in the band of:	1500 - 100,000 MHz
Power Density Limit:	1 mW / cm ²

Equation: $S = PG / 4\pi R^2$ or $R = \sqrt{PG / 4\pi S}$
Where, S = Power Density
P = Power Input to Antenna
G = Antenna Gain
R = distance to the center of radiated antenna

Prediction distance 20cm

EUT: AP 370

(UNII band 2 and band 3): Power = 23.68dBm, Antenna Gain = 4.54 dBi, Power density = 0.132mW/ cm²
(2.4GHz): Power = 28.35dBm, Antenna Gain = 4.42dBi, Power density = 0.377mW/ cm²
Total Ratio= $(P_{2.4GHz}/1) + (P_{5GHz}/1) = 0.132mW/ cm^2 + 0.377mW/ cm^2 = 0.509mW/ cm^2$

EUT: AP 390

(UNII band 2 and band 3): Power = 23.89dBm, Antenna Gain = 3.3 dBi, Power density = 0.104mW/ cm²
(2.4GHz): Power = 26.25dBm, Antenna Gain = 3.6dBi, Power density = 0.192mW/ cm²
Total Ratio= $(P_{2.4GHz}/1) + (P_{5GHz}/1) = 0.104mW/ cm^2 + 0.192mW/ cm^2 = 0.296mW/ cm^2$

The Above Result had shown that Device complied with MPE requirement.

Completed By: Choon Sian Ooi

Date: January 09th, 2014