

Appendix B

CN24XTFJ 003

Prüfbericht - Produkte

Test Report - Products

Page 281 of 308




Shenzhen PSI Testing Co., Ltd.
1-2F, Building 5, Yudafu Industrial Park, No. 10, Xingye West Road,
Shajing Street, Bao'an District, Shenzhen, Guangdong, China 518104

Test Site: PSI EMC Lab-3m Chamber Polarization: **Horizontal** Temperature: 26 °C
EUT: See note Distance: 3m Humidity: 54 %RH
M/N: See note Test Engineer: Felix Pang
Test Mode: n40 5795MHz(MIMO)
Test Voltage: DC 24V
Note: Optical 3D Measuring and Dynamic Tracking System
FreeScan Trak ProW(FreeTrakW)

Radiated Emission Measurement

Test Date: 2024/11/15 19:32:52



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg.)	P/F	Remark
1 *	5607.650	54.02	-17.55	36.47	68.20	-31.73	peak	150	148	P	
2	5971.250	52.86	-16.94	35.92	68.20	-32.28	peak	150	205	P	

Note: *:Maximum data x:Over limit !:over margin Level = Reading + Factor Margin = Level - Limit

Appendix B

CN24XTFJ 003

Prüfbericht - Produkte

Test Report - Products

Page 282 of 308




Shenzhen PSI Testing Co., Ltd.
1-2F, Building 5, Yudafu Industrial Park, No. 10, Xingye West Road,
Shajing Street, Bao'an District, Shenzhen, Guangdong, China 518104

Test Site: PSI EMC Lab-3m Chamber Polarization: **Vertical** Temperature: 26 °C
EUT: See note Distance: 3m Humidity: 54 %RH
M/N: See note Test Engineer: Felix Pang
Test Mode: n40 5795MHz(MIMO)
Test Voltage: DC 24V
Note: Optical 3D Measuring and Dynamic Tracking System
FreeScan Trak ProW(FreeTrakW)

Radiated Emission Measurement

Test Date: 2024/11/15 19:36:01



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg.)	P/F	Remark
1 *	5616.200	54.54	-17.92	36.62	68.20	-31.58	peak	150	217	P	
2	5979.850	52.87	-16.95	35.92	68.20	-32.28	peak	150	138	P	

Note: *:Maximum data x:Over limit !:over margin Level = Reading + Factor Margin = Level - Limit

Appendix B

CN24XTFJ 003

Prüfbericht - Produkte
Test Report - Products

Page 283 of 308




Shenzhen PSI Testing Co., Ltd.
1-2F, Building 5, Yudafu Industrial Park, No. 10, Xingye West Road,
Shajing Street, Bao'an District, Shenzhen, Guangdong, China 518104

Test Site: PSI EMC Lab-3m Chamber Polarization: **Vertical** Temperature: 26 °C
EUT: See note Distance: 3m Humidity: 54 %RH
M/N: See note Test Engineer: Felix Pang
Test Mode: ac40 5755MHz(MIMO)
Test Voltage: DC 24V
Note: Optical 3D Measuring and Dynamic Tracking System
FreeScan Trak ProW(FreeTrakW)

Radiated Emission Measurement

Test Date: 2024/11/15 19:41:43



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg.)	P/F	Remark
1 *	5636.550	54.90	-17.86	37.04	68.20	-31.16	peak	150	78	P	
2	5978.350	53.37	-16.96	36.41	68.20	-31.79	peak	150	245	P	

Note: *:Maximum data x:Over limit !:over margin Level = Reading + Factor Margin = Level - Limit

Appendix B

CN24XTFJ 003

Prüfbericht - Produkte
Test Report - Products

Page 284 of 308




Shenzhen PSI Testing Co., Ltd.
1-2F, Building 5, Yudafu Industrial Park, No. 10, Xingye West Road,
Shajing Street, Bao'an District, Shenzhen, Guangdong, China 518104

Test Site: PSI EMC Lab-3m Chamber Polarization: **Horizontal** Temperature: 26 °C
EUT: See note Distance: 3m Humidity: 54 %RH
M/N: See note Test Engineer: Felix Pang
Test Mode: ac40 5755MHz(MIMO)
Test Voltage: DC 24V
Note: Optical 3D Measuring and Dynamic Tracking System
FreeScan Trak ProW(FreeTrakW)

Radiated Emission Measurement

Test Date: 2024/11/15 19:46:52



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg.)	P/F	Remark
1 *	5622.300	54.79	-17.52	37.27	68.20	-30.93	peak	150	127	P	
2	5956.150	53.97	-16.96	37.01	68.20	-31.19	peak	150	197	P	

Note: *:Maximum data x:Over limit !:over margin Level = Reading + Factor Margin = Level - Limit

Appendix B
CN24XTFJ 003

Prüfbericht - Produkte
Test Report - Products

Page 285 of 308




Shenzhen PSI Testing Co., Ltd.
1-2F, Building 5, Yudafu Industrial Park, No. 10, Xingye West Road,
Shajing Street, Bao'an District, Shenzhen, Guangdong, China 518104

Test Site: PSI EMC Lab-3m Chamber Polarization: **Horizontal** Temperature: 26 °C
EUT: See note Distance: 3m Humidity: 54 %RH
M/N: See note Test Engineer: Felix Pang
Test Mode: ac40 5795MHz(MIMO)
Test Voltage: DC 24V
Note: Optical 3D Measuring and Dynamic Tracking System
FreeScan Trak ProW(FreeTrakW)

Radiated Emission Measurement

Test Date: 2024/11/15 19:51:00



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg.)	P/F	Remark
1 *	5607.500	54.48	-17.55	36.93	68.20	-31.27	peak	150	157	P	
2	5968.300	53.12	-16.94	36.18	68.20	-32.02	peak	150	134	P	

Note: *:Maximum data x:Over limit !:over margin Level = Reading + Factor Margin = Level - Limit

Appendix B

CN24XTFJ 003

Prüfbericht - Produkte
Test Report - Products

Page 286 of 308




Shenzhen PSI Testing Co., Ltd.
1-2F, Building 5, Yudafu Industrial Park, No. 10, Xingye West Road,
Shajing Street, Bao'an District, Shenzhen, Guangdong, China 518104

Test Site: PSI EMC Lab-3m Chamber Polarization: **Vertical** Temperature: 26 °C
EUT: See note Distance: 3m Humidity: 54 %RH
M/N: See note Test Engineer: Felix Pang
Test Mode: ac40 5795MHz(MIMO)
Test Voltage: DC 24V
Note: Optical 3D Measuring and Dynamic Tracking System
FreeScan Trak ProW(FreeTrakW)

Radiated Emission Measurement

Test Date: 2024/11/15 19:56:07



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg.)	P/F	Remark
1	5620.300	54.09	-17.90	36.19	68.20	-32.01	peak	150	148	P	
2 *	5973.600	53.36	-16.97	36.39	68.20	-31.81	peak	150	208	P	

Note: *:Maximum data x:Over limit !:over margin Level = Reading + Factor Margin = Level - Limit

Appendix B

CN24XTFJ 003

Prüfbericht - Produkte
Test Report - Products

Page 287 of 308




Shenzhen PSI Testing Co., Ltd.
1-2F, Building 5, Yudafu Industrial Park, No. 10, Xingye West Road,
Shajing Street, Bao'an District, Shenzhen, Guangdong, China 518104

Test Site: PSI EMC Lab-3m Chamber Polarization: **Vertical** Temperature: 26 °C
EUT: See note Distance: 3m Humidity: 54 %RH
M/N: See note Test Engineer: Felix Pang
Test Mode: ax40 5755MHz(MIMO)
Test Voltage: DC 24V
Note: Optical 3D Measuring and Dynamic Tracking System
FreeScan Trak ProW(FreeTrakW)

Radiated Emission Measurement

Test Date: 2024/11/15 20:02:21



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg.)	P/F	Remark
1 *	5648.750	56.10	-17.83	38.27	68.20	-29.93	peak	150	128	P	
2	5972.800	54.13	-16.97	37.16	68.20	-31.04	peak	150	249	P	

Note: *:Maximum data x:Over limit !:over margin Level = Reading + Factor Margin = Level - Limit

Appendix B

CN24XTFJ 003

Prüfbericht - Produkte

Test Report - Products

Page 288 of 308



Shenzhen PSI Testing Co., Ltd.

1-2F, Building 5, Yudafu Industrial Park, No. 10, Xingye West Road,
Shajing Street, Bao'an District, Shenzhen, Guangdong, China 518104

Test Site: PSI EMC Lab-3m Chamber

Polarization: **Horizontal**

Temperature: 26 °C

EUT: See note

Distance: 3m

Humidity: 54 %RH

M/N: See note

Test Engineer: Felix Pang

Test Mode: ax40 5755MHz(MIMO)


Test Voltage: DC 24V

Note: Optical 3D Measuring and Dynamic Tracking System

FreeScan Trak ProW(FreeTrakW)

Radiated Emission Measurement

Test Date: 2024/11/15 20:07:41



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg.)	P/F	Remark
1 *	5605.550	55.16	-17.55	37.61	68.20	-30.59	peak	150	257	P	
2	5971.600	53.29	-16.94	36.35	68.20	-31.85	peak	150	168	P	

Note: *:Maximum data x:Over limit !:over margin Level = Reading + Factor Margin = Level - Limit

Appendix B

CN24XTFJ 003

Prüfbericht - Produkte

Test Report - Products

Page 289 of 308



Shenzhen PSI Testing Co., Ltd.

1-2F, Building 5, Yudafu Industrial Park, No. 10, Xingye West Road,
Shajing Street, Bao'an District, Shenzhen, Guangdong, China 518104

Test Site: PSI EMC Lab-3m Chamber

Polarization: **Horizontal**

Temperature: 26 °C

EUT: See note

Distance: 3m

Humidity: 54 %RH

M/N: See note

Test Engineer: Felix Pang

Test Mode: ax40 5795MHz(MIMO)


Test Voltage: DC 24V

Note: Optical 3D Measuring and Dynamic Tracking System

FreeScan Trak ProW(FreeTrakW)

Radiated Emission Measurement

Test Date: 2024/11/15 20:12:16



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg.)	P/F	Remark
1 *	5647.150	53.80	-17.49	36.31	68.20	-31.89	peak	150	207	P	
2	5974.450	52.97	-16.94	36.03	68.20	-32.17	peak	150	154	P	

Note: *:Maximum data x:Over limit !:over margin Level = Reading + Factor Margin = Level - Limit

Appendix B
CN24XTFJ 003

Prüfbericht - Produkte
Test Report - Products

Page 290 of 308




Shenzhen PSI Testing Co., Ltd.
1-2F, Building 5, Yudafu Industrial Park, No. 10, Xingye West Road,
Shajing Street, Bao'an District, Shenzhen, Guangdong, China 518104

Test Site: PSI EMC Lab-3m Chamber Polarization: **Vertical** Temperature: 26 °C
EUT: See note Distance: 3m Humidity: 54 %RH
M/N: See note Test Engineer: Felix Pang
Test Mode: ax40 5795MHz(MIMO)
Test Voltage: DC 24V
Note: Optical 3D Measuring and Dynamic Tracking System
FreeScan Trak ProW(FreeTrakW)

Radiated Emission Measurement

Test Date: 2024/11/15 20:16:41



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg.)	P/F	Remark
1	5640.300	53.75	-17.86	35.89	68.20	-32.31	peak	150	12	P	
2 *	5977.000	53.28	-16.96	36.32	68.20	-31.88	peak	150	148	P	

Note: *:Maximum data x:Over limit !:over margin Level = Reading + Factor Margin = Level - Limit

Appendix B

CN24XTFJ 003

Prüfbericht - Produkte

Test Report - Products

Page 291 of 308




Shenzhen PSI Testing Co., Ltd.
1-2F, Building 5, Yudafu Industrial Park, No. 10, Xingye West Road,
Shajing Street, Bao'an District, Shenzhen, Guangdong, China 518104

Test Site: PSI EMC Lab-3m Chamber Polarization: **Vertical** Temperature: 26 °C
EUT: See note Distance: 3m Humidity: 54 %RH
M/N: See note Test Engineer: Felix Pang
Test Mode: ac80 5775MHz(MIMO)
Test Voltage: DC 24V
Note: Optical 3D Measuring and Dynamic Tracking System
FreeScan Trak ProW(FreeTrakW)

Radiated Emission Measurement

Test Date: 2024/11/15 20:24:05



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg.)	P/F	Remark
1 *	5629.450	66.50	-17.88	48.62	68.20	-19.58	peak	150	267	P	
2	5976.350	53.55	-16.96	36.59	68.20	-31.61	peak	150	128	P	

Note: *:Maximum data x:Over limit !:over margin Level = Reading + Factor Margin = Level - Limit

Appendix B

CN24XTFJ 003

Prüfbericht - Produkte
Test Report - Products

Page 292 of 308




Shenzhen PSI Testing Co., Ltd.
1-2F, Building 5, Yudafu Industrial Park, No. 10, Xingye West Road,
Shajing Street, Bao'an District, Shenzhen, Guangdong, China 518104

Test Site: PSI EMC Lab-3m Chamber Polarization: **Horizontal** Temperature: 26 °C
EUT: See note Distance: 3m Humidity: 54 %RH
M/N: See note Test Engineer: Felix Pang
Test Mode: ac80 5775MHz(MIMO)
Test Voltage: DC 24V
Note: Optical 3D Measuring and Dynamic Tracking System
FreeScan Trak ProW(FreeTrakW)

Radiated Emission Measurement

Test Date: 2024/11/15 20:28:40



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg.)	P/F	Remark
1 *	5651.250	70.55	-17.46	53.09	69.13	-16.04	peak	150	187	P	
2	5972.750	56.75	-16.94	39.81	68.20	-28.39	peak	150	210	P	

Note: *:Maximum data x:Over limit !:over margin Level = Reading + Factor Margin = Level - Limit

Appendix B

CN24XTFJ 003

Prüfbericht - Produkte

Test Report - Products

Page 293 of 308



Shenzhen PSI Testing Co., Ltd.

1-2F, Building 5, Yudafu Industrial Park, No. 10, Xingye West Road,
Shajing Street, Bao'an District, Shenzhen, Guangdong, China 518104

Test Site: PSI EMC Lab-3m Chamber

Polarization: **Horizontal**

Temperature: 26 °C

EUT: See note

Distance: 3m

Humidity: 54 %RH

M/N: See note

Test Engineer: Felix Pang

Test Mode: ax80 5775MHz(MIMO)


Test Voltage: DC 24V

Note: Optical 3D Measuring and Dynamic Tracking System

FreeScan Trak ProW(FreeTrakW)

Radiated Emission Measurement

Test Date: 2024/11/15 20:34:23



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg.)	P/F	Remark
1 *	5620.500	63.49	-17.52	45.97	68.20	-22.23	peak	150	128	P	
2	5971.350	54.96	-16.94	38.02	68.20	-30.18	peak	150	217	P	

Note: *:Maximum data x:Over limit !:over margin Level = Reading + Factor Margin = Level - Limit

Appendix B

CN24XTFJ 003

Page 294 of 308


Prüfbericht - Produkte

Test Report - Products



Shenzhen PSI Testing Co., Ltd.
1-2F, Building 5, Yudafu Industrial Park, No. 10, Xingye West Road,
Shajing Street, Bao'an District, Shenzhen, Guangdong, China 518104

Test Site: PSI EMC Lab-3m Chamber Polarization: **Vertical** Temperature: 26 °C
EUT: See note Distance: 3m Humidity: 54 %RH
M/N: See note Test Engineer: Felix Pang
Test Mode: ax80 5775MHz(MIMO)
Test Voltage: DC 24V
Note: Optical 3D Measuring and Dynamic Tracking System
FreeScan Trak ProW(FreeTrakW)



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg.)	P/F	Remark
1 *	5637.750	64.95	-17.86	47.09	68.20	-21.11	peak	150	247	P	
2	5964.700	53.66	-16.98	36.68	68.20	-31.52	peak	150	167	P	

Note: *:Maximum data x:Over limit !:over margin Level = Reading + Factor Margin = Level - Limit

Appendix B

CN24XTFJ 003

Prüfbericht - Produkte

Test Report - Products

Page 295 of 308



Shenzhen PSI Testing Co., Ltd.

1-2F, Building 5, Yudafu Industrial Park, No. 10, Xingye West Road,
Shajing Street, Bao'an District, Shenzhen, Guangdong, China 518104

Test Site: PSI EMC Lab-3m Chamber

Polarization: **Vertical**

Temperature: 26 °C

EUT: See note

Distance: 3m

Humidity: 54 %RH

M/N: See note

Test Engineer: Felix Pang

Test Mode: a 5745MHz(Ant 1)


Test Voltage: DC 24V

Note: Optical 3D Measuring and Dynamic Tracking System

FreeScan Trak ProW(FreeTrakW)

Radiated Emission Measurement

Test Date: 2024/11/15 18:08:58



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg.)	P/F	Remark
1 *	5609.100	56.36	-17.94	38.42	68.20	-29.78	peak	150	124	P	
2	5957.500	53.97	-17.00	36.97	68.20	-31.23	peak	150	247	P	

Note: *:Maximum data x:Over limit !:over margin Level = Reading + Factor Margin = Level - Limit

Appendix B

CN24XTFJ 003

Prüfbericht - Produkte

Test Report - Products

Page 296 of 308



Shenzhen PSI Testing Co., Ltd.

1-2F, Building 5, Yudafu Industrial Park, No. 10, Xingye West Road,
Shajing Street, Bao'an District, Shenzhen, Guangdong, China 518104

Test Site: PSI EMC Lab-3m Chamber

Polarization: **Horizontal**

Temperature: 26 °C

EUT: See note

Distance: 3m

Humidity: 54 %RH

M/N: See note

Test Engineer: Felix Pang

Test Mode: a 5745MHz(Ant 1)


Test Voltage: DC 24V

Note: Optical 3D Measuring and Dynamic Tracking System

FreeScan Trak ProW(FreeTrakW)

Radiated Emission Measurement

Test Date: 2024/11/15 18:14:00



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg.)	P/F	Remark
1 *	5632.350	54.51	-17.50	37.01	68.20	-31.19	peak	150	247	P	
2	5976.450	52.87	-16.94	35.93	68.20	-32.27	peak	150	131	P	

Note: *:Maximum data x:Over limit !:over margin Level = Reading + Factor Margin = Level - Limit

Appendix B
CN24XTFJ 003

Prüfbericht - Produkte
Test Report - Products

Page 297 of 308




Shenzhen PSI Testing Co., Ltd.
1-2F, Building 5, Yudafu Industrial Park, No. 10, Xingye West Road,
Shajing Street, Bao'an District, Shenzhen, Guangdong, China 518104

Test Site: PSI EMC Lab-3m Chamber Polarization: **Horizontal** Temperature: 26 °C
EUT: See note Distance: 3m Humidity: 54 %RH
M/N: See note Test Engineer: Felix Pang
Test Mode: a 5825MHz(Ant 1)
Test Voltage: DC 24V
Note: Optical 3D Measuring and Dynamic Tracking System
FreeScan Trak ProW(FreeTrakW)

Radiated Emission Measurement

Test Date: 2024/11/15 18:18:52



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg.)	P/F	Remark
1 *	5604.050	53.87	-17.56	36.31	68.20	-31.89	peak	150	45	P	
2	5964.500	52.94	-16.95	35.99	68.20	-32.21	peak	150	247	P	

Note: *:Maximum data x:Over limit !:over margin Level = Reading + Factor Margin = Level - Limit


Appendix B
CN24XTFJ 003
Page 298 of 308

Prüfbericht - Produkte
Test Report - Products



Shenzhen PSI Testing Co., Ltd.
1-2F, Building 5, Yudafu Industrial Park, No. 10, Xingye West Road,
Shajing Street, Bao'an District, Shenzhen, Guangdong, China 518104

Test Site: PSI EMC Lab-3m Chamber Polarization: **Vertical** Temperature: 26 °C
EUT: See note Distance: 3m Humidity: 54 %RH
M/N: See note Test Engineer: Felix Pang
Test Mode: a 5825MHz(Ant 1)
Test Voltage: DC 24V
Note: Optical 3D Measuring and Dynamic Tracking System
FreeScan Trak ProW(FreeTrakW)



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg.)	P/F	Remark
1 *	5625.850	54.06	-17.89	36.17	68.20	-32.03	peak	150	165	P	
2	5982.300	52.97	-16.94	36.03	68.20	-32.17	peak	150	258	P	

Note: *:Maximum data x:Over limit !:over margin Level = Reading + Factor Margin = Level - Limit

Appendix B

CN24XTFJ 003

Prüfbericht - Produkte

Test Report - Products

Page 299 of 308




Shenzhen PSI Testing Co., Ltd.
1-2F, Building 5, Yudafu Industrial Park, No. 10, Xingye West Road,
Shajing Street, Bao'an District, Shenzhen, Guangdong, China 518104

Test Site: PSI EMC Lab-3m Chamber Polarization: **Vertical** Temperature: 26 °C
EUT: See note Distance: 3m Humidity: 54 %RH
M/N: See note Test Engineer: Felix Pang
Test Mode: n20 5745MHz(MIMO)
Test Voltage: DC 24V
Note: Optical 3D Measuring and Dynamic Tracking System
FreeScan Trak ProW(FreeTrakW)

Radiated Emission Measurement

Test Date: 2024/11/15 18:25:37



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg.)	P/F	Remark
1	5632.050	54.00	-17.87	36.13	68.20	-32.07	peak	150	102	P	
2 *	5971.500	53.59	-16.97	36.62	68.20	-31.58	peak	150	314	P	

Note: *:Maximum data x:Over limit !:over margin Level = Reading + Factor Margin = Level - Limit

Appendix B

CN24XTFJ 003

Prüfbericht - Produkte
Test Report - Products

Page 300 of 308




Shenzhen PSI Testing Co., Ltd.
1-2F, Building 5, Yudafu Industrial Park, No. 10, Xingye West Road,
Shajing Street, Bao'an District, Shenzhen, Guangdong, China 518104

Test Site: PSI EMC Lab-3m Chamber Polarization: **Horizontal** Temperature: 26 °C
EUT: See note Distance: 3m Humidity: 54 %RH
M/N: See note Test Engineer: Felix Pang
Test Mode: n20 5745MHz(MIMO)
Test Voltage: DC 24V
Note: Optical 3D Measuring and Dynamic Tracking System
FreeScan Trak ProW(FreeTrakW)

Radiated Emission Measurement

Test Date: 2024/11/15 18:31:01



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg.)	P/F	Remark
1 *	5649.850	55.45	-17.47	37.98	68.20	-30.22	peak	150	125	P	
2	5967.500	53.19	-16.95	36.24	68.20	-31.96	peak	150	268	P	

Note: *:Maximum data x:Over limit !:over margin Level = Reading + Factor Margin = Level - Limit

Appendix B
CN24XTFJ 003

Prüfbericht - Produkte
Test Report - Products

Page 301 of 308




Shenzhen PSI Testing Co., Ltd.
1-2F, Building 5, Yudafu Industrial Park, No. 10, Xingye West Road,
Shajing Street, Bao'an District, Shenzhen, Guangdong, China 518104

Test Site: PSI EMC Lab-3m Chamber Polarization: **Horizontal** Temperature: 26 °C
EUT: See note Distance: 3m Humidity: 54 %RH
M/N: See note Test Engineer: Felix Pang
Test Mode: n20 5825MHz(MIMO)
Test Voltage: DC 24V
Note: Optical 3D Measuring and Dynamic Tracking System
FreeScan Trak ProW(FreeTrakW)

Radiated Emission Measurement

Test Date: 2024/11/15 18:35:59



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg.)	P/F	Remark
1	5622.750	53.82	-17.52	36.30	68.20	-31.90	peak	150	178	P	
2 *	5987.200	53.52	-16.90	36.62	68.20	-31.58	peak	150	219	P	

Note: *:Maximum data x:Over limit !:over margin Level = Reading + Factor Margin = Level - Limit

Appendix B

CN24XTFJ 003

Prüfbericht - Produkte
Test Report - Products

Page 302 of 308




Shenzhen PSI Testing Co., Ltd.
1-2F, Building 5, Yudafu Industrial Park, No. 10, Xingye West Road,
Shajing Street, Bao'an District, Shenzhen, Guangdong, China 518104

Test Site: PSI EMC Lab-3m Chamber Polarization: **Vertical** Temperature: 26 °C
EUT: See note Distance: 3m Humidity: 54 %RH
M/N: See note Test Engineer: Felix Pang
Test Mode: n20 5825MHz(MIMO)
Test Voltage: DC 24V
Note: Optical 3D Measuring and Dynamic Tracking System
FreeScan Trak ProW(FreeTrakW)

Radiated Emission Measurement

Test Date: 2024/11/15 18:41:09



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg.)	P/F	Remark
1 *	5645.800	54.48	-17.84	36.64	68.20	-31.56	peak	150	120	P	
2	5962.550	53.60	-16.99	36.61	68.20	-31.59	peak	150	247	P	

Note: *:Maximum data x:Over limit !:over margin Level = Reading + Factor Margin = Level - Limit

Appendix B

CN24XTFJ 003

Prüfbericht - Produkte

Test Report - Products

Page 303 of 308



Shenzhen PSI Testing Co., Ltd.

1-2F, Building 5, Yudafu Industrial Park, No. 10, Xingye West Road,
Shajing Street, Bao'an District, Shenzhen, Guangdong, China 518104

Test Site: PSI EMC Lab-3m Chamber

Polarization: **Vertical**

Temperature: 26 °C

EUT: See note

Distance: 3m

Humidity: 54 %RH

M/N: See note

Test Engineer: Felix Pang

Test Mode: ac20 5745MHz(MIMO)


Test Voltage: DC 24V

Note: Optical 3D Measuring and Dynamic Tracking System

FreeScan Trak ProW(FreeTrakW)

Radiated Emission Measurement

Test Date: 2024/11/15 18:45:20



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg.)	P/F	Remark
1 *	5602.350	55.39	-17.96	37.43	68.20	-30.77	peak	150	154	P	
2	5979.600	53.25	-16.95	36.30	68.20	-31.90	peak	150	132	P	

Note: *:Maximum data x:Over limit !:over margin Level = Reading + Factor Margin = Level - Limit

Appendix B
CN24XTFJ 003

Prüfbericht - Produkte
Test Report - Products

Page 304 of 308




Shenzhen PSI Testing Co., Ltd.
1-2F, Building 5, Yudafu Industrial Park, No. 10, Xingye West Road,
Shajing Street, Bao'an District, Shenzhen, Guangdong, China 518104

Test Site: PSI EMC Lab-3m Chamber Polarization: **Horizontal** Temperature: 26 °C
EUT: See note Distance: 3m Humidity: 54 %RH
M/N: See note Test Engineer: Felix Pang
Test Mode: ac20 5745MHz(MIMO)
Test Voltage: DC 24V
Note: Optical 3D Measuring and Dynamic Tracking System
FreeScan Trak ProW(FreeTrakW)

Radiated Emission Measurement

Test Date: 2024/11/15 18:49:48



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg.)	P/F	Remark
1 *	5617.950	54.22	-17.52	36.70	68.20	-31.50	peak	150	154	P	
2	5972.900	53.15	-16.94	36.21	68.20	-31.99	peak	150	120	P	

Note: *:Maximum data x:Over limit !:over margin Level = Reading + Factor Margin = Level - Limit

Appendix B

CN24XTFJ 003

Prüfbericht - Produkte
Test Report - Products

Page 305 of 308




Shenzhen PSI Testing Co., Ltd.
1-2F, Building 5, Yudafu Industrial Park, No. 10, Xingye West Road,
Shajing Street, Bao'an District, Shenzhen, Guangdong, China 518104

Test Site: PSI EMC Lab-3m Chamber Polarization: **Horizontal** Temperature: 26 °C
EUT: See note Distance: 3m Humidity: 54 %RH
M/N: See note Test Engineer: Felix Pang
Test Mode: ac20 5825MHz(MIMO)
Test Voltage: DC 24V
Note: Optical 3D Measuring and Dynamic Tracking System
FreeScan Trak ProW(FreeTrakW)

Radiated Emission Measurement

Test Date: 2024/11/15 18:54:47



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg.)	P/F	Remark
1	5644.800	53.59	-17.49	36.10	68.20	-32.10	peak	150	135	P	
2 *	5979.750	53.28	-16.93	36.35	68.20	-31.85	peak	150	217	P	

Note: *:Maximum data x:Over limit !:over margin Level = Reading + Factor Margin = Level - Limit

Appendix B

CN24XTFJ 003

Page 306 of 308


Prüfbericht - Produkte

Test Report - Products



Shenzhen PSI Testing Co., Ltd.
1-2F, Building 5, Yudafu Industrial Park, No. 10, Xingye West Road,
Shajing Street, Bao'an District, Shenzhen, Guangdong, China 518104

Test Site: PSI EMC Lab-3m Chamber Polarization: **Vertical** Temperature: 26 °C
EUT: See note Distance: 3m Humidity: 54 %RH
M/N: See note Test Engineer: Felix Pang
Test Mode: ac20 5825MHz(MIMO)
Test Voltage: DC 24V
Note: Optical 3D Measuring and Dynamic Tracking System
FreeScan Trak ProW(FreeTrakW)



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg.)	P/F	Remark
1	5641.900	54.31	-17.85	36.46	68.20	-31.74	peak	150	158	P	
2 *	5978.650	54.03	-16.95	37.08	68.20	-31.12	peak	150	257	P	

Note: *:Maximum data x:Over limit !:over margin Level = Reading + Factor Margin = Level - Limit

File: BD 5\Data :#12

Page: 1

Engineer Signature:

Co-location

modes:

It verified that there are no evident emissions found in co-location modes (2.4GHz SRD+5GHz Wi-Fi), thus no records listed.

Appendix B

CN24XTFJ 003

Prüfbericht - Produkte

Test Report - Products

Page 307 of 308

5. Test Results of AC Conducted Emissions




Shenzhen PSI Testing Co., Ltd.
1-2F, Building 5, Yudafu Industrial Park, No. 10, Xingye West Road,
Shajing Street, Bao'an District, Shenzhen, Guangdong, China 518104

Test Site: PSI EMC Lab-Shielded Room Phase: **L1** Temperature: 26 °C
EUT: See note Humidity: 54 %RH
M/N: FreeScan Trak ProW(FreeTrakW) Test Engineer: Felix Pang
Test Mode: 5G WIFI Link
Test Voltage: AC 120V/60Hz
Note: Optical 3D Measuring and Dynamic Tracking System

Conducted Emission Measurement

Test Date: 2024/9/25 15:05:46



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector	P/F	Remark
1	0.1500	48.27	9.94	58.21	66.00	-7.79	QP	P	
2	0.1500	35.48	9.94	45.42	56.00	-10.58	AVG	P	
3	0.1740	40.21	9.94	50.15	64.77	-14.62	QP	P	
4	0.1740	29.78	9.94	39.72	54.77	-15.05	AVG	P	
5	0.2020	41.67	9.95	51.62	63.53	-11.91	QP	P	
6	0.2020	24.72	9.95	34.67	53.53	-18.86	AVG	P	
7	0.2460	38.65	9.97	48.62	61.89	-13.27	QP	P	
8	0.2460	22.28	9.97	32.25	51.89	-19.64	AVG	P	
9	1.0100	34.94	9.41	44.35	56.00	-11.65	QP	P	
10	1.0100	19.34	9.41	28.75	46.00	-17.25	AVG	P	
11	3.5460	40.30	9.39	49.69	56.00	-6.31	QP	P	
12 *	3.5460	32.53	9.39	41.92	46.00	-4.08	AVG	P	

Note: *:Maximum data x:Over limit !:over margin Level = Reading + Factor Margin = Level - Limit

File: CEData :#15

Page: 1

Engineer Signature:

Appendix B

CN24XTFJ 003

Prüfbericht - Produkte

Test Report - Products

Page 308 of 308




Shenzhen PSI Testing Co., Ltd.
1-2F, Building 5, Yudafu Industrial Park, No. 10, Xingye West Road,
Shajing Street, Bao'an District, Shenzhen, Guangdong, China 518104

Test Site: PSI EMC Lab-Shielded Room Phase: **N** Temperature: 26 °C
EUT: See note Humidity: 54 %RH
M/N: FreeScan Trak ProW(FreeTrakW) Test Engineer: Felix Pang
Test Mode: 5G WIFI Link
Test Voltage: AC 120V/60Hz
Note: Optical 3D Measuring and Dynamic Tracking System

Conducted Emission Measurement

Test Date: 2024/9/25 15:13:03



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector	P/F	Remark
1	0.1539	49.72	9.94	59.66	65.79	-6.13	QP	P	
2	0.1539	42.71	9.94	52.65	55.79	-3.14	AVG	P	
3	0.1620	48.40	9.94	58.34	65.36	-7.02	QP	P	
4	0.1620	34.52	9.94	44.46	55.36	-10.90	AVG	P	
5	0.1780	44.26	9.95	54.21	64.58	-10.37	QP	P	
6	0.1780	31.56	9.95	41.51	54.58	-13.07	AVG	P	
7	0.1900	44.61	9.95	54.56	64.04	-9.48	QP	P	
8	0.1900	36.98	9.95	46.93	54.04	-7.11	AVG	P	
9	0.9420	34.27	9.41	43.68	56.00	-12.32	QP	P	
10	0.9420	26.15	9.41	35.56	46.00	-10.44	AVG	P	
11	3.4740	41.59	9.39	50.98	56.00	-5.02	QP	P	
12 *	3.4740	33.50	9.39	42.89	46.00	-3.11	AVG	P	

Note: *:Maximum data x:Over limit !:over margin Level = Reading + Factor Margin = Level - Limit

File: CE\Data :#16

Page: 1

Engineer Signature: