



SAR TEST REPORT

No. I14Z45296-SEM01

For

TCT Mobile Limited

HSUPA/HSDPA/UMTS dualband / GSM quadband mobile phone

Mode Name: Tigris 3G Lite

Marketing Name: ALCATEL TRIBE 3074A

With

Hardware Version: Proto01

Software Version: E15

FCC ID: RAD480

Issued Date: 2014-04-16



Note:

The test results in this test report relate only to the devices specified in this report. This report shall not be reproduced except in full without the written approval of TMC Beijing.

Test Laboratory:

TMC Beijing, Telecommunication Metrology Center of MIIT

No. 52, Huayuan Bei Road, Haidian District, Beijing, P. R. China 100191.

Tel:+86(0)10-62304633-2079, Fax:+86(0)10-62304633 Email:welcome@emcite.com. www.emcite.com

©Copyright. All rights reserved by TMC Beijing.

Revision Version

Report Number	Revision	Date	Memo
I14Z45296-SEM01	00	2014-03-13	Initial creation of test report
I14Z45296-SEM01	01	2014-03-27	Remove the information of BT/WLAN
I14Z45296-SEM01	02	2014-04-16	Replace some SAR values of spot check

TABLE OF CONTENT

1 TEST LABORATORY	5
1.1 TESTING LOCATION	5
1.2 TESTING ENVIRONMENT.....	5
1.3 PROJECT DATA	5
1.4 SIGNATURE.....	5
2 STATEMENT OF COMPLIANCE	6
3 CLIENT INFORMATION	7
3.1 APPLICANT INFORMATION	7
3.2 MANUFACTURER INFORMATION	7
4 EQUIPMENT UNDER TEST (EUT) AND ANCILLARY EQUIPMENT (AE)	8
4.1 ABOUT EUT	8
4.2 INTERNAL IDENTIFICATION OF EUT USED DURING THE TEST	8
4.3 INTERNAL IDENTIFICATION OF AE USED DURING THE TEST	8
5 TEST METHODOLOGY	9
5.1 APPLICABLE LIMIT REGULATIONS	9
5.2 APPLICABLE MEASUREMENT STANDARDS.....	9
6 SPECIFIC ABSORPTION RATE (SAR).....	10
6.1 INTRODUCTION.....	10
6.2 SAR DEFINITION	10
7 TISSUE SIMULATING LIQUIDS	11
7.1 TARGETS FOR TISSUE SIMULATING LIQUID	11
7.2 DIELECTRIC PERFORMANCE	11
8 SYSTEM VERIFICATION	14
8.1 SYSTEM SETUP.....	14
8.2 SYSTEM VERIFICATION.....	15
9 MEASUREMENT PROCEDURES	16
9.1 TESTS TO BE PERFORMED	16
9.2 GENERAL MEASUREMENT PROCEDURE.....	17
9.3 WCDMA MEASUREMENT PROCEDURES FOR SAR	18
9.4 BLUETOOTH & WI-FI MEASUREMENT PROCEDURES FOR SAR	19
9.5 POWER DRIFT.....	19
10 AREA SCAN BASED 1-G SAR.....	20
10.1 REQUIREMENT OF KDB.....	20
10.2 FAST SAR ALGORITHMS	20
11 CONDUCTED OUTPUT POWER.....	21

11.1 MANUFACTURING TOLERANCE	21
11.2 GSM MEASUREMENT RESULT	24
11.3 WCDMA MEASUREMENT RESULT	25
12 SAR TEST RESULT	26
12.1 THE EVALUATION OF MULTI-BATTERIES	26
12.2 SAR RESULTS FOR FAST SAR	27
12.3 SAR RESULTS FOR STANDARD PROCEDURE	31
13 SAR MEASUREMENT VARIABILITY	33
14 MEASUREMENT UNCERTAINTY	34
15 MAIN TEST INSTRUMENTS	38
ANNEX A GRAPH RESULTS	39
ANNEX B SYSTEM VERIFICATION RESULTS	55
ANNEX C SAR MEASUREMENT SETUP	68
ANNEX D POSITION OF THE WIRELESS DEVICE IN RELATION TO THE PHANTOM	74
ANNEX E EQUIVALENT MEDIA RECIPES	77
ANNEX F SYSTEM VALIDATION	78
ANNEX G PROBE CALIBRATION CERTIFICATE	79
ANNEX H DIPOLE CALIBRATION CERTIFICATE	90
ANNEX I SPOT CHECK TEST	106

1 Test Laboratory

1.1 Testing Location

Company Name:	TMC Beijing, Telecommunication Metrology Center of MIIT
Address:	No 52, Huayuan beilu, Haidian District, Beijing,P.R.China
Postal Code:	100191
Telephone:	+86-10-62304633
Fax:	+86-10-62304793

1.2 Testing Environment

Temperature:	18°C~25 °C,
Relative humidity:	30%~ 70%
Ground system resistance:	< 0.5 Ω
Ambient noise & Reflection:	< 0.012 W/kg


1.3 Project Data

Project Leader:	Qi Dianyuan
Test Engineer:	Lin Xiaojun
Testing Start Date:	October 12, 2013
Testing End Date:	February 18, 2014

1.4 Signature



Lin Xiaojun
(Prepared this test report)



Qi Dianyuan
(Reviewed this test report)



Xiao Li
Deputy Director of the laboratory
(Approved this test report)

2 Statement of Compliance

This EUT is a variant product and the report of original sample is No.2013SAR00150.

According to the client request, we quote the test results of original sample except WLAN.

The results of spot check are presented in the annex I.

The maximum results of Specific Absorption Rate (SAR) found during testing for TCT Mobile Limited HSUPA/HSDPA/UMTS dualband / GSM quadband mobile phone Tigris 3G Lite / ALCATEL TRIBE 3074A are as follows:

Table 2.1: Highest Reported SAR (1g)

Exposure Configuration	Technology Band	Highest Reported SAR 1g (W/Kg) original	Highest Reported SAR 1g (W/Kg) spot check	Equipment Class
Head (Separation Distance 0mm)	GSM 850	0.63	0.59	PCE
	PCS 1900	0.55	0.54	
	UMTS FDD 2	0.81	0.78	
	UMTS FDD 5	0.64	0.60	
Body-worn (Separation Distance 10mm)	GSM 850	1.04	1.02	PCE
	PCS 1900	0.89	0.83	
	UMTS FDD 2	1.11	0.97	
	UMTS FDD 5	0.91	0.96	

The SAR values found for the Mobile Phone are below the maximum recommended levels of 1.6 W/Kg as averaged over any 1g tissue according to the ANSI C95.1-1999.

For body worn operation, this device has been tested and meets FCC RF exposure guidelines when used with any accessory that contains no metal and which provides a minimum separation distance of 10 mm between this device and the body of the user. Use of other accessories may not ensure compliance with FCC RF exposure guidelines.

The EUT battery must be fully charged and checked periodically during the test to ascertain uniform power output.

The measurement together with the test system set-up is described in annex C of this test report. A detailed description of the equipment under test can be found in chapter 4 of this test report.

The highest reported SAR value is obtained at the case of **(Table 2.1)**, and the values are: **1.11 W/kg (1g)**.

3 Client Information

3.1 Applicant Information

Company Name:	TCT Mobile Limited
Address /Post:	5F, C building, No. 232, Liang Jing Road ZhangJiang High-Tech Park, Pudong Area Shanghai, P.R. China. 201203
City:	Shanghai
Postal Code:	201203
Country:	P.R.China
Contact:	Gong Zhizhou
Email:	zhizhou.gong@tcl.com
Telephone:	0086-21-61460890
Fax:	0086-21-61460602

3.2 Manufacturer Information

Company Name:	TCT Mobile Limited
Address /Post:	5F, C building, No. 232, Liang Jing Road ZhangJiang High-Tech Park, Pudong Area Shanghai, P.R. China. 201203
City:	Shanghai
Postal Code:	201203
Country:	P.R.China
Contact:	Gong Zhizhou
Email:	zhizhou.gong@tcl.com
Telephone:	0086-21-61460890
Fax:	0086-21-61460602

4 Equipment Under Test (EUT) and Ancillary Equipment (AE)

4.1 About EUT

Description:	HSUPA/HSDPA/UMTS dualband / GSM quadband mobile phone
Mode Name:	Tigris 3G Lite
Marketing Name:	ALCATEL TRIBE 3074A
Operating mode(s):	GSM 850/900/1800/1900, WCDMA 850/1900
Tested Tx Frequency:	825 – 848.8 MHz (GSM 850)
	1850.2 – 1910 MHz (GSM 1900)
	826.4–846.6 MHz (WCDMA850 Band V)
	1852.4–1907.6 MHz (WCDMA1900 Band II)
GPRS/EGPRS Multislot Class:	12
GPRS capability Class:	B
WCDMA Category:	HSDPA: 8
	HSUPA: 6
Release Version:	GSM: Rel6
	GPRS: Rel5
	UMTS: R6
Test device Production information:	Production unit
Device type:	Portable device
Antenna type:	Integrated antenna
Accessories/Body-worn configurations:	Headset
Hotspot mode:	Support simultaneous transmission of hotspot and voice(or data)
Form factor:	107 mm × 58 mm

4.2 Internal Identification of EUT used during the test

EUT ID*	SN or IMEI	HW Version	SW Version
EUT1	013830000000815	PIO	A18
EUT2	013830000001524	PIO	A18

*EUT ID: is used to identify the test sample in the lab internally.

Note1: It is performed to test SAR with the EUT1 and conducted power with the EUT 2

Note2: The sample information of spot check is presented in the annex I.

4.3 Internal Identification of AE used during the test

AE ID*	Description	Model	SN	Manufacturer
AE1	Battery	CAB3120000C1	/	BYD
AE2	Battery	CAB3120000C3	/	BAK
AE3	Headset	CCB3160A11C1	/	Juwei
AE4	Headset	CCB3160A11C4	/	Meihao

*AE ID: is used to identify the test sample in the lab internally.

5 TEST METHODOLOGY

5.1 Applicable Limit Regulations

ANSI C95.1–1999: IEEE Standard for Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz to 300 GHz.

It specifies the maximum exposure limit of **1.6 W/kg** as averaged over any 1 gram of tissue for portable devices being used within 20 cm of the user in the uncontrolled environment.

5.2 Applicable Measurement Standards

IEEE 1528–2003: Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Body Due to Wireless Communications Devices: Experimental Techniques.

KDB447498 D01: General RF Exposure Guidance v05r01: Mobile and Portable Devices RF Exposure Procedures and Equipment Authorization Policies.

KDB648474 D04 Handset SAR v01r01: SAR Evaluation Considerations for Wireless Handsets.

KDB941225 D06 Hotspot Mode SAR v01r01: SAR Evaluation Procedures for Portable Devices with Wireless Router Capabilities

KDB248227: SAR measurement procedures for 802.112abg transmitters

KDB 865664 D01 SAR measurement 100 MHz to 6 GHz v01r01: SAR Measurement Requirements for 100 MHz to 6 GHz

KDB 865664 D02 RF Exposure Reporting v01r01: RF Exposure Compliance Reporting and Documentation Considerations

6 Specific Absorption Rate (SAR)

6.1 Introduction

SAR is related to the rate at which energy is absorbed per unit mass in an object exposed to a radio field. The SAR distribution in a biological body is complicated and is usually carried out by experimental techniques or numerical modeling. The standard recommends limits for two tiers of groups, occupational/controlled and general population/uncontrolled, based on a person's awareness and ability to exercise control over his or her exposure. In general, occupational/controlled exposure limits are higher than the limits for general population/uncontrolled.

6.2 SAR Definition

The SAR definition is the time derivative (rate) of the incremental energy (dW) absorbed by (dissipated in) an incremental mass (dm) contained in a volume element (dv) of a given density (ρ). The equation description is as below:

$$SAR = \frac{d}{dt} \left(\frac{dW}{dm} \right) = \frac{d}{dt} \left(\frac{dW}{\rho dv} \right)$$

SAR is expressed in units of Watts per kilogram (W/kg)

SAR measurement can be either related to the temperature elevation in tissue by

$$SAR = c \left(\frac{\delta T}{\delta t} \right)$$

Where: C is the specific heat capacity, δT is the temperature rise and δt is the exposure duration, or related to the electrical field in the tissue by

$$SAR = \frac{\sigma |E|^2}{\rho}$$

Where: σ is the conductivity of the tissue, ρ is the mass density of tissue and E is the RMS electrical field strength.

However for evaluating SAR of low power transmitter, electrical field measurement is typically applied.

7 Tissue Simulating Liquids

7.1 Targets for tissue simulating liquid

Table 7.1: Targets for tissue simulating liquid


Frequency (MHz)	Liquid Type	Conductivity (σ)	$\pm 5\%$ Range	Permittivity (ϵ)	$\pm 5\%$ Range
835	Head	0.90	0.86~0.95	41.5	39.4~43.6
835	Body	0.97	0.92~1.02	55.2	52.4~58.0
1900	Head	1.40	1.33~1.47	40.0	38.0~42.0
1900	Body	1.52	1.44~1.60	53.3	50.6~56.0

7.2 Dielectric Performance


Table 7.2: Dielectric Performance of Tissue Simulating Liquid

Measurement Date (yyyy-mm-dd)	Type	Frequency	Permittivity ϵ	Drift (%)	Conductivity σ (S/m)	Drift (%)
2013-10-12	Head	835 MHz	41.86	0.87	0.916	1.78
	Body	835 MHz	56.03	1.50	0.964	-0.62
2013-10-13	Head	1900 MHz	40.58	1.45	1.427	1.93
	Body	1900 MHz	52.36	-1.76	1.538	1.18
2014-02-17	Head	835 MHz	41.73	0.55	0.92	2.22
	Body	835 MHz	54.06	-2.07	0.965	-0.52
2014-02-18	Head	1900 MHz	39.18	-2.05	1.414	1.00
	Body	1900 MHz	52.38	-1.73	1.493	-1.78
2014-04-09	Head	835 MHz	42.27	1.86	0.892	-0.89
	Body	835 MHz	55.01	-0.34	0.979	0.93
	Head	1900 MHz	39.19	-2.03	1.383	-1.21
	Body	1900 MHz	51.98	-2.48	1.546	1.71


Note: The liquid temperature is 22.0 °C




Picture 7-1: Liquid depth in the Head Phantom (835 MHz)



Picture 7-2: Liquid depth in the Flat Phantom (835 MHz)



Picture 7-3: Liquid depth in the Head Phantom (1900 MHz)




Picture 7-4 Liquid depth in the Flat Phantom (1900MHz)


8 System verification

8.1 System Setup

In the simplified setup for system evaluation, the DUT is replaced by a calibrated dipole and the power source is replaced by a continuous wave that comes from a signal generator. The calibrated dipole must be placed beneath the flat phantom section of the SAM twin phantom with the correct distance holder. The distance holder should touch the phantom surface with a light pressure at the reference marking and be oriented parallel to the long side of the phantom. The equipment setup is shown below:



Picture 8.1 System Setup for System Evaluation



Picture 8.2 Photo of Dipole Setup

8.2 System Verification

SAR system verification is required to confirm measurement accuracy, according to the tissue dielectric media, probe calibration points and other system operating parameters required for measuring the SAR of a test device. The system verification must be performed for each frequency band and within the valid range of each probe calibration point required for testing the device.

The system verification results are required that the area scan estimated 1-g SAR is within 3% of the zoom scan 1-g SAR. The details are presented in annex B.

Table 8.1: System Verification of Head

Measurement Date (yyyy-mm-dd)	Frequency	Target value (W/kg)		Measured value (W/kg)		Deviation	
		10 g Average	1 g Average	10 g Average	1 g Average	10 g Average	1 g Average
2013-10-12	835 MHz	6.16	9.44	5.96	9.16	-3.25%	-2.97%
2013-10-13	1900 MHz	21.3	40.4	20.96	39.80	-1.60%	-1.49%
2014-02-17	835 MHz	6.16	9.44	6.04	9.16	-1.95%	-2.97%
2014-02-18	1900 MHz	21.3	40.4	21.36	40.40	0.28%	0.00%
2014-04-09	835 MHz	6.16	9.44	6.00	9.24	-2.60%	-2.12%
2014-04-09	1900 MHz	21.3	40.4	20.60	39.04	-3.29%	-3.37%

Table 8.2: System Verification of Body

Measurement Date (yyyy-mm-dd)	Frequency	Target value (W/kg)		Measured value (W/kg)		Deviation	
		10 g Average	1 g Average	10 g Average	1 g Average	10 g Average	1 g Average
2013-10-12	835 MHz	6.20	9.40	6.28	9.52	1.29%	1.28%
2013-10-13	1900 MHz	21.9	41.3	21.32	40.80	-2.65%	-1.21%
2014-02-17	835 MHz	6.20	9.40	6.32	9.60	1.94%	2.13%
2014-02-18	1900 MHz	21.9	41.3	21.48	40.80	-1.92%	-1.21%
2014-04-09	835 MHz	6.20	9.40	6.36	9.64	2.58%	2.55%
2014-04-09	1900 MHz	21.9	41.3	21.24	40.40	-3.01%	-2.18%

9 Measurement Procedures

9.1 Tests to be performed

In order to determine the highest value of the peak spatial-average SAR of a handset, all device positions, configurations and operational modes shall be tested for each frequency band according to steps 1 to 3 below. A flowchart of the test process is shown in picture 9.1.


Step 1: The tests described in 9.2 shall be performed at the channel that is closest to the centre of the transmit frequency band (f_c) for:

- a) all device positions (cheek and tilt, for both left and right sides of the SAM phantom, as described in annex D),
- b) all configurations for each device position in a), e.g., antenna extended and retracted, and
- c) all operational modes, e.g., analogue and digital, for each device position in a) and configuration in b) in each frequency band.

If more than three frequencies need to be tested according to 11.1 (i.e., $N_c > 3$), then all frequencies, configurations and modes shall be tested for all of the above test conditions.

Step 2: For the condition providing highest peak spatial-average SAR determined in Step 1, perform all tests described in 9.2 at all other test frequencies, i.e., lowest and highest frequencies. In addition, for all other conditions (device position, configuration and operational mode) where the peak spatial-average SAR value determined in Step 1 is within 3 dB of the applicable SAR limit, it is recommended that all other test frequencies shall be tested as well.

Step 3: Examine all data to determine the highest value of the peak spatial-average SAR found in Steps 1 to 2.



Picture 9.1 Block diagram of the tests to be performed

9.2 General Measurement Procedure

The area and zoom scan resolutions specified in the table below must be applied to the SAR measurements and fully documented in SAR reports to qualify for TCB approval. Probe boundary effect error compensation is required for measurements with the probe tip closer than half a probe tip diameter to the phantom surface. Both the probe tip diameter and sensor offset distance must satisfy measurement protocols; to ensure probe boundary effect errors are minimized and the higher fields closest to the phantom surface can be correctly measured and extrapolated to the phantom surface for computing 1-g SAR. Tolerances of the post-processing algorithms must be verified by the test laboratory for the scan resolutions used in the SAR measurements, according to the reference distribution functions specified in IEEE Std 1528-2003. The results should be documented as part of the system validation records and may be requested to support test results

when all the measurement parameters in the following table are not satisfied.

			≤ 3 GHz	> 3 GHz
Maximum distance from closest measurement point (geometric center of probe sensors) to phantom surface			5 ± 1 mm	$\frac{1}{4} \cdot \delta \cdot \ln(2) \pm 0.5$ mm
Maximum probe angle from probe axis to phantom surface normal at the measurement location			$30^\circ \pm 1^\circ$	$20^\circ \pm 1^\circ$
Maximum area scan spatial resolution: Δx_{Area} , Δy_{Area}			≤ 2 GHz: ≤ 15 mm 2 – 3 GHz: ≤ 12 mm	3 – 4 GHz: ≤ 12 mm 4 – 6 GHz: ≤ 10 mm
			When the x or y dimension of the test device, in the measurement plane orientation, is smaller than the above, the measurement resolution must be \leq the corresponding x or y dimension of the test device with at least one measurement point on the test device.	
Maximum zoom scan spatial resolution: Δx_{Zoom} , Δy_{Zoom}			≤ 2 GHz: ≤ 8 mm 2 – 3 GHz: ≤ 5 mm*	3 – 4 GHz: ≤ 5 mm* 4 – 6 GHz: ≤ 4 mm*
Maximum zoom scan spatial resolution, normal to phantom surface	uniform grid: $\Delta z_{Zoom}(n)$		≤ 5 mm	3 – 4 GHz: ≤ 4 mm 4 – 5 GHz: ≤ 3 mm 5 – 6 GHz: ≤ 2 mm
	graded grid	$\Delta z_{Zoom}(1)$: between 1 st two points closest to phantom surface	≤ 4 mm	3 – 4 GHz: ≤ 3 mm 4 – 5 GHz: ≤ 2.5 mm 5 – 6 GHz: ≤ 2 mm
		$\Delta z_{Zoom}(n>1)$: between subsequent points	$\leq 1.5 \cdot \Delta z_{Zoom}(n-1)$	
Minimum zoom scan volume	x, y, z		≥ 30 mm	3 – 4 GHz: ≥ 28 mm 4 – 5 GHz: ≥ 25 mm 5 – 6 GHz: ≥ 22 mm
Note: δ is the penetration depth of a plane-wave at normal incidence to the tissue medium; see draft standard IEEE P1528-2011 for details.				
* When zoom scan is required and the <u>reported</u> SAR from the area scan based <i>I-g SAR estimation</i> procedures of KDB 447498 is ≤ 1.4 W/kg, ≤ 8 mm, ≤ 7 mm and ≤ 5 mm zoom scan resolution may be applied, respectively, for 2 GHz to 3 GHz, 3 GHz to 4 GHz and 4 GHz to 6 GHz.				

9.3 WCDMA Measurement Procedures for SAR

The following procedures are applicable to WCDMA handsets operating under 3GPP Release99, Release 5 and Release 6. The default test configuration is to measure SAR with an established radio link between the DUT and a communication test set using a 12.2kbps RMC (reference measurement channel) configured in Test Loop Mode 1. SAR is selectively confirmed for other physical channel configurations (DPCCH & DPDCH_n), HSDPA and HSPA (HSUPA/HSDPA) modes according to output power, exposure conditions and device operating capabilities. Both uplink and downlink should be configured with the same RMC or AMR, when required. SAR for Release 5 HSDPA and Release 6 HSPA are measured using the applicable FRC (fixed reference channel) and E-DCH reference channel configurations. Maximum output power is verified according to applicable versions of 3GPP TS 34.121 and SAR must be measured according to these maximum output conditions. When Maximum Power Reduction (MPR) is not implemented according to Cubic Metric (CM) requirements for Release 6 HSPA, the following procedures do not apply.

For Release 5 HSDPA Data Devices:

Sub-test	β_c	β_d	β_d (SF)	β_c / β_d	β_{hs}	CM/dB
1	2/15	15/15	64	2/15	4/15	0.0
2	12/15	15/15	64	12/15	24/25	1.0
3	15/15	8/15	64	15/8	30/15	1.5
4	15/15	4/15	64	15/4	30/15	1.5

For Release 6 HSPA Data Devices

Sub-test	β_c	β_d	β_d (SF)	β_c / β_d	β_{hs}	β_{ec}	β_{ed}	β_{ed} (SF)	β_{ed} (codes)	CM (dB)	MPR (dB)	AG Index	E-TFCI
1	11/15	15/15	64	11/15	22/15	209/225	1039/225	4	1	1.0	2.0	20	75
2	6/15	15/15	64	6/15	12/15	12/15	12/15	4	1	3.0	3.0	12	67
3	15/15	9/15	64	15/9	30/15	30/15	$\beta_{ed1}:47/15$ $\beta_{ed2}:47/15$	4	2	2.0	2.5	15	92
4	2/15	15/15	64	2/15	4/15	4/15	56/75	4	1	3.0	2.0	17	71
5	15/15	15/15	64	15/15	24/15	30/15	134/15	4	1	1.0	0.0	21	81

9.4 Bluetooth & Wi-Fi Measurement Procedures for SAR

Normal network operating configurations are not suitable for measuring the SAR of 802.11 transmitters in general. Unpredictable fluctuations in network traffic and antenna diversity conditions can introduce undesirable variations in SAR results. The SAR for these devices should be measured using chipset based test mode software to ensure that the results are consistent and reliable.

Chipset based test mode software is hardware dependent and generally varies among manufacturers. The device operating parameters established in a test mode for SAR measurements must be identical to those programmed in production units, including output power levels, amplifier gain settings and other RF performance tuning parameters. The test frequencies should correspond to actual channel frequencies defined for domestic use. SAR for devices with switched diversity should be measured with only one antenna transmitting at a time during each SAR measurement, according to a fixed modulation and data rate. The same data pattern should be used for all measurements.

9.5 Power Drift

To control the output power stability during the SAR test, DASY4 system calculates the power drift by measuring the E-field at the same location at the beginning and at the end of the measurement for each test position. These drift values can be found in Table 12.2 to Table 12.21 labeled as: (Power Drift [dB]). This ensures that the power drift during one measurement is within 5%.

10 Area Scan Based 1-g SAR

10.1 Requirement of KDB

According to the KDB447498 D01 v05, when the implementation is based the specific polynomial fit algorithm as presented at the 29th Bioelectromagnetics Society meeting (2007) and the estimated 1-g SAR is ≤ 1.2 W/kg, a zoom scan measurement is not required provided it is also not needed for any other purpose; for example, if the peak SAR location required for simultaneous transmission SAR test exclusion can be determined accurately by the SAR system or manually to discriminate between distinctive peaks and scattered noisy SAR distributions from area scans.

There must not be any warning or alert messages due to various measurement concerns identified by the SAR system; for example, noise in measurements, peaks too close to scan boundary, peaks are too sharp, spatial resolution and uncertainty issues etc. The SAR system verification must also demonstrate that the area scan estimated 1-g SAR is within 3% of the zoom scan 1-g SAR (See Annex B). When all the SAR results for each exposure condition in a frequency band and wireless mode are based on estimated 1-g SAR, the 1-g SAR for the highest SAR configuration must be determined by a zoom scan.

10.2 Fast SAR Algorithms

The approach is based on the area scan measurement applying a frequency dependent attenuation parameter. This attenuation parameter was empirically determined by analyzing a large number of phones. The MOTOROLA FAST SAR was developed and validated by the MOTOROLA Research Group in Ft. Lauderdale.

In the initial study, an approximation algorithm based on Linear fit was developed. The accuracy of the algorithm has been demonstrated across a broad frequency range (136-2450 MHz) and for both 1- and 10-g averaged SAR using a sample of 264 SAR measurements from 55 wireless handsets. For the sample size studied, the root-mean-squared errors of the algorithm are 1.2% and 5.8% for 1- and 10-g averaged SAR, respectively. The paper describing the algorithm in detail is expected to be published in August 2004 within the Special Issue of Transactions on MTT.

In the second step, the same research group optimized the fitting algorithm to an Polynomial fit whereby the frequency validity was extended to cover the range 30-6000MHz. Details of this study can be found in the BEMS 2007 Proceedings.

Both algorithms are implemented in DASY software.

11 Conducted Output Power

11.1 Manufacturing tolerance

Table 11.1: GSM Speech

GSM 850			
Channel	Channel 251	Channel 190	Channel 128
Target (dBm)	32.3	32.3	32.3
Tolerance \pm (dB)	0.5	0.5	0.5
GSM 1900			
Channel	Channel 810	Channel 661	Channel 512
Target (dBm)	29.3	29.3	29.3
Tolerance \pm (dB)	0.5	0.5	0.5

Table 11.2: GPRS and EGPRS

GSM 850 GPRS (GMSK)				
Channel		251	190	128
1 Txslot	Target (dBm)	32.3	32.3	32.3
	Tolerance \pm (dB)	0.5	0.5	0.5
2 Txslots	Target (dBm)	29.5	29.5	29.5
	Tolerance \pm (dB)	0.5	0.5	0.5
3Txslots	Target (dBm)	28.5	28.5	28.5
	Tolerance \pm (dB)	0.5	0.5	0.5
4 Txslots	Target (dBm)	27.0	27.0	27.0
	Tolerance \pm (dB)	0.5	0.5	0.5
GSM 850 EGPRS (GMSK)				
Channel		251	190	128
1 Txslot	Target (dBm)	32.3	32.3	32.3
	Tolerance \pm (dB)	0.5	0.5	0.5
2 Txslots	Target (dBm)	29.5	29.5	29.5
	Tolerance \pm (dB)	0.5	0.5	0.5
3Txslots	Target (dBm)	28.5	28.5	28.5
	Tolerance \pm (dB)	0.5	0.5	0.5
4 Txslots	Target (dBm)	27.0	27.0	27.0
	Tolerance \pm (dB)	0.5	0.5	0.5
GSM 1900 GPRS (GMSK)				
Channel		810	661	512
1 Txslot	Target (dBm)	29.3	29.3	29.3
	Tolerance \pm (dB)	0.5	0.5	0.5
2 Txslots	Target (dBm)	26.5	26.5	26.5
	Tolerance \pm (dB)	0.5	0.5	0.5
3Txslots	Target (dBm)	25.5	25.5	25.5
	Tolerance \pm (dB)	0.5	0.5	0.5

4 Txslots	Target (dBm)	24.2	24.2	24.2
	Tolerance \pm (dB)	0.5	0.5	0.5
GSM 1900 EGPRS (GMSK)				
Channel		810	661	512
1 Txslot	Target (dBm)	29.3	29.3	29.3
	Tolerance \pm (dB)	0.5	0.5	0.5
2 Txslots	Target (dBm)	26.5	26.5	26.5
	Tolerance \pm (dB)	0.5	0.5	0.5
3Txslots	Target (dBm)	25.5	25.5	25.5
	Tolerance \pm (dB)	0.5	0.5	0.5
4 Txslots	Target (dBm)	24.2	24.2	24.2
	Tolerance \pm (dB)	0.5	0.5	0.5

Table 11.3: WCDMA

WCDMA 850 CS			
Channel	Channel 4233	Channel 4182	Channel 4132
Target (dBm)	23	23	23
Tolerance \pm (dB)	0.5	0.5	0.5
HSUPA (sub-test 1)			
Channel	Channel 4233	Channel 4182	Channel 4132
Target (dBm)	21	21	21
Tolerance \pm (dB)	0.6	0.6	0.6
HSUPA (sub-test 2)			
Channel	Channel 4233	Channel 4182	Channel 4132
Target (dBm)	20	20	20
Tolerance \pm (dB)	0.6	0.6	0.6
HSUPA (sub-test 3)			
Channel	Channel 4233	Channel 4182	Channel 4132
Target (dBm)	20.5	20.5	20.5
Tolerance \pm (dB)	0.6	0.6	0.6
HSUPA (sub-test 4)			
Channel	Channel 4233	Channel 4182	Channel 4132
Target (dBm)	21	21	21
Tolerance \pm (dB)	0.6	0.6	0.6
HSUPA (sub-test 5)			
Channel	Channel 4233	Channel 4182	Channel 4132
Target (dBm)	23	23	23
Tolerance \pm (dB)	0.6	0.6	0.6
WCDMA 1900 CS			
Channel	Channel 9538	Channel 9400	Channel 9262
Target (dBm)	21.5	22	22
Tolerance \pm (dB)	0.5	0.5	0.5

HSUPA (sub-test 1)			
Channel	Channel 9538	Channel 9400	Channel 9262
Target (dBm)	19.7	19.7	19.7
Tolerance \pm (dB)	0.6	0.6	0.6
HSUPA (sub-test 2)			
Channel	Channel 9538	Channel 9400	Channel 9262
Target (dBm)	18.5	18.5	18.5
Tolerance \pm (dB)	0.6	0.6	0.6
HSUPA (sub-test 3)			
Channel	Channel 9538	Channel 9400	Channel 9262
Target (dBm)	19.3	19.3	19.3
Tolerance \pm (dB)	0.6	0.6	0.6
HSUPA (sub-test 4)			
Channel	Channel 9538	Channel 9400	Channel 9262
Target (dBm)	19.8	19.8	19.8
Tolerance \pm (dB)	0.6	0.6	0.6
HSUPA (sub-test 5)			
Channel	Channel 9538	Channel 9400	Channel 9262
Target (dBm)	21.7	21.7	21.7
Tolerance \pm (dB)	0.6	0.6	0.6

11.2 GSM Measurement result

During the process of testing, the EUT was controlled via Agilent Digital Radio Communication tester (E5515C) to ensure the maximum power transmission and proper modulation. This result contains conducted output power for the EUT. In all cases, the measured peak output power should be greater and within 5% than EMI measurement.

Table 11.6: The conducted power measurement results for GSM850/1900

GSM 850MHz	Conducted Power (dBm)		
	Channel 251(848.8MHz)	Channel 190(836.6MHz)	Channel 128(824.2MHz)
	32.13	32.15	32.11
GSM 1900MHz	Conducted Power (dBm)		
	Channel 810(1909.8MHz)	Channel 661(1880MHz)	Channel 512(1850.2MHz)
	29.07	29.11	29.18

Table 11.7: The conducted power measurement results for GPRS and EGPRS

GSM 850 GPRS (GMSK)	Measured Power (dBm)			calculation	Averaged Power (dBm)		
	251	190	128		251	190	128
1 Txslot	32.14	32.16	32.12	-9.03dB	23.11	23.13	23.09
2 Txslots	29.49	29.46	29.39	-6.02dB	23.47	23.44	23.37
3Txslots	28.54	28.53	28.48	-4.26dB	24.28	24.27	24.22
4 Txslots	27.09	27.06	26.98	-3.01dB	24.08	24.05	23.97
GSM 850 EGPRS (GMSK)	Measured Power (dBm)			calculation	Averaged Power (dBm)		
	251	190	128		251	190	128
1 Txslot	32.12	32.15	32.11	-9.03dB	23.09	23.12	23.08
2 Txslots	29.47	29.44	29.40	-6.02dB	23.45	23.42	23.38
3Txslots	28.55	28.51	28.47	-4.26dB	24.29	24.25	24.21
4 Txslots	27.09	27.07	27.00	-3.01dB	24.08	24.06	23.99
PCS1900 GPRS (GMSK)	Measured Power (dBm)			calculation	Averaged Power (dBm)		
	810	661	512		810	661	512
1 Txslot	29.11	29.14	29.21	-9.03dB	20.08	20.11	20.18
2 Txslots	26.45	26.47	26.51	-6.02dB	20.43	20.45	20.49
3Txslots	25.64	25.66	25.67	-4.26dB	21.38	21.40	21.41
4 Txslots	24.21	24.20	24.20	-3.01dB	21.20	21.19	21.19
PCS1900 EGPRS (GMSK)	Measured Power (dBm)			calculation	Averaged Power (dBm)		
	810	661	512		810	661	512
1 Txslot	29.11	29.15	29.21	-9.03dB	20.08	20.12	20.18
2 Txslots	26.46	26.47	26.52	-6.02dB	20.44	20.45	20.50
3Txslots	25.65	25.67	25.68	-4.26dB	21.39	21.41	21.42
4 Txslots	24.21	24.22	24.21	-3.01dB	21.20	21.21	21.20

NOTES:

1) Division Factors

To average the power, the division factor is as follows:

1TX-slot = 1 transmit time slot out of 8 time slots=> conducted power divided by (8/1) => -9.03dB

2TX-slots = 2 transmit time slots out of 8 time slots=> conducted power divided by (8/2) => -6.02dB
3TX-slots = 3 transmit time slots out of 8 time slots=> conducted power divided by (8/3) => -4.26dB
4TX-slots = 4 transmit time slots out of 8 time slots=> conducted power divided by (8/4) => -3.01dB

According to the conducted power as above, the body measurements are performed with 3Txslots for GPRS and EGPRS.

Note: According to the KDB941225 D03, “when SAR tests for EDGE or EGPRS mode is necessary, GMSK modulation should be used”.

11.3 WCDMA Measurement result

Table 11.8: The conducted Power for WCDMA850/1900

Item	band	FDDV result		
	ARFCN	4233 (846.6MHz)	4182 (836.4MHz)	4132 (826.4MHz)
WCDMA	\	22.71	22.85	22.99
HSUPA	1	20.99	20.86	21.17
	2	20.01	19.85	20.18
	3	20.51	20.36	20.67
	4	20.98	20.82	21.18
	5	22.95	22.80	23.16
Item	band	FDDII result		
	ARFCN	9538 (1907.6MHz)	9400 (1880MHz)	9262 (1852.4MHz)
WCDMA	\	21.44	21.37	21.68
HSUPA	1	19.81	19.53	19.96
	2	18.00	18.57	18.96
	3	19.30	19.06	19.48
	4	19.81	19.58	20.00
	5	21.67	21.52	21.91

Note: HSUPA body SAR for WCDMA850/1900 are not required, because maximum average output power of each RF channel with HSUPA active is not 1/4 dB higher than that measured without HSUPA and the maximum SAR for WCDMA850/1900 are not above 75% of the SAR limit.

12 SAR Test Result

It is determined by user manual for the distance between the EUT and the phantom bottom.

The distance is 10mm and just applied to the condition of body worn accessory.

It is performed for all SAR measurements with area scan based 1-g SAR estimation (Fast SAR). A zoom scan measurement is added when the estimated 1-g SAR is the highest measured SAR in each exposure configuration, wireless mode and frequency band combination or > 1.2W/kg.

The calculated SAR is obtained by the following formula:

$$\text{Reported SAR} = \text{Measured SAR} \times 10^{(P_{\text{Target}} - P_{\text{Measured}})/10}$$

Where P_{Target} is the power of manufacturing upper limit;

P_{Measured} is the measured power in chapter 11.

Table 12.1: Duty Cycle

Mode	Duty Cycle
Speech for GSM850/1900	1:8.3
GPRS&EGPRS for GSM850/1900	1:2.67
WCDMA	1:1

12.1 The evaluation of multi-batteries

We'll perform the head measurement in all bands with the primary battery depending on the evaluation of multi-batteries and retest on highest value point with other batteries. Then, repeat the measurement in the Body test.

Table 12.2: The evaluation of multi-batteries for Head Test

Frequency		Mode/Band	Side	Test Position	Battery Type	SAR(1g)	Power Drift(dB)
MHz	Ch.					(W/kg)	
1852.4	9262	WCDMA1900	Right	Touch	CAB3120000C1	0.614	0.14
1852.4	9262	WCDMA1900	Right	Touch	CAB3120000C3	0.670	-0.13

Note: According to the values in the above table, the battery, CAB3120000C3, is the primary battery. We'll perform the head measurement with this battery and retest on highest value point with others.

Table 12.3: The evaluation of multi-batteries for Body Test

Frequency		Mode/Band	Test Position	Spacing (mm)	Battery Type	SAR(1g)	Power Drift(dB)
MHz	Ch.					(W/kg)	
824.2	128	GSM 850	Rear	10	CAB3120000C1	0.839	0.07
824.2	128	GSM 850	Rear	10	CAB3120000C3	0.920	-0.02

Note: According to the values in the above table, the battery, CAB3120000C3, is the primary battery. We'll perform the Body measurement with this battery and retest on highest value point with others.

12.2 SAR results for Fast SAR

Table 12.4: SAR Values (GSM 850 MHz Band - Head) – CAB3120000C3

Ambient Temperature: 22.5 °C						Liquid Temperature: 22.0 °C					
Frequency		Side	Test Position	Figure No.	Conducted Power (dBm)	Max. tune-up Power (dBm)	Measured SAR(10g) (W/kg)	Reported SAR(10g) (W/kg)	Measured SAR(1g) (W/kg)	Reported SAR(1g) (W/kg)	Power Drift (dB)
MHz	Ch.										
848.8	251	Left	Touch	/	32.13	32.8	0.353	0.41	0.516	0.60	-0.02
836.6	190	Left	Touch	Fig.1	32.15	32.8	0.409	0.48	0.546	0.63	-0.12
824.2	128	Left	Touch	/	32.11	32.8	0.351	0.41	0.510	0.60	-0.02
848.8	251	Left	Tilt	/	32.13	32.8	0.201	0.23	0.290	0.34	0.02
836.6	190	Left	Tilt	/	32.15	32.8	0.215	0.25	0.309	0.36	0.02
824.2	128	Left	Tilt	/	32.11	32.8	0.198	0.23	0.286	0.34	-0.03
848.8	251	Right	Touch	/	32.13	32.8	0.354	0.41	0.520	0.61	0.01
836.6	190	Right	Touch	/	32.15	32.8	0.400	0.46	0.541	0.63	0.03
824.2	128	Right	Touch	/	32.11	32.8	0.342	0.40	0.501	0.59	-0.09
848.8	251	Right	Tilt	/	32.13	32.8	0.204	0.24	0.296	0.35	-0.04
836.6	190	Right	Tilt	/	32.15	32.8	0.206	0.24	0.300	0.35	-0.04
824.2	128	Right	Tilt	/	32.11	32.8	0.191	0.22	0.276	0.32	0.05

Table 12.5: SAR Values (GSM 850 MHz Band - Body) –CAB3120000C3

Ambient Temperature: 22.5 °C						Liquid Temperature: 22.0 °C					
Frequency		Mode (number of timeslots)	Test Position	Figure No.	Conducted Power (dBm)	Max. tune-up Power (dBm)	Measured SAR(10g) (W/kg)	Reported SAR(10g) (W/kg)	Measured SAR(1g) (W/kg)	Reported SAR(1g) (W/kg)	Power Drift (dB)
MHz	Ch.										
836.6	190	GPRS (3)	Front	/	28.53	29	0.389	0.43	0.563	0.63	-0.03
848.8	251	GPRS (3)	Rear	/	28.54	29	0.589	0.65	0.825	0.92	-0.04
836.6	190	GPRS (3)	Rear	/	28.53	29	0.648	0.72	0.911	1.02	-0.11
824.2	128	GPRS (3)	Rear	Fig.2	28.48	29	0.652	0.73	0.920	1.04	-0.02
836.6	190	GPRS (3)	Left	/	28.53	29	0.311	0.35	0.457	0.51	-0.17
836.6	190	GPRS (3)	Right	/	28.53	29	0.293	0.33	0.433	0.48	-0.10
836.6	190	GPRS (3)	Bottom	/	28.53	29	0.055	0.06	0.087	0.10	-0.01
848.8	128	EGPRS (3)	Rear	/	28.47	29	0.630	0.71	0.886	1.00	-0.13
848.8	128	Speech	Rear Headset1	/	32.11	32.8	0.409	0.48	0.602	0.71	0.02
848.8	128	Speech	Rear Headset2	/	32.11	32.8	0.459	0.54	0.669	0.78	0.02

Note1: The distance between the EUT and the phantom bottom is 10mm.

Note2: The Headset1 is CCB3160A11C1, the Headset2 is CCB3160A11C4.

Table 12.6: SAR Values (GSM 1900 MHz Band - Head) –CAB3120000C3

Ambient Temperature: 22.6 °C						Liquid Temperature: 22.1 °C					
Frequency		Side	Test Position	Figure No.	Conducted Power (dBm)	Max. tune-up Power (dBm)	Measured SAR(10g) (W/kg)	Reported SAR(10g) (W/kg)	Measured SAR(1g) (W/kg)	Reported SAR(1g) (W/kg)	Power Drift (dB)
MHz	Ch.										
1909.8	810	Left	Touch	/	29.07	29.8	0.252	0.30	0.394	0.47	0.02
1880	661	Left	Touch	/	29.11	29.8	0.226	0.26	0.378	0.44	0.04
1850.2	512	Left	Touch	/	29.18	29.8	0.212	0.24	0.353	0.41	-0.12
1909.8	810	Left	Tilt	/	29.07	29.8	0.129	0.15	0.223	0.26	-0.12
1880	661	Left	Tilt	/	29.11	29.8	0.118	0.14	0.202	0.24	-0.04
1850.2	512	Left	Tilt	/	29.18	29.8	0.105	0.12	0.179	0.21	-0.02
1909.8	810	Right	Touch	Fig.3	29.07	29.8	0.288	0.34	0.464	0.55	-0.01
1880	661	Right	Touch	/	29.11	29.8	0.263	0.31	0.453	0.53	0.02
1850.2	512	Right	Touch	/	29.18	29.8	0.246	0.28	0.422	0.49	-0.03
1909.8	810	Right	Tilt	/	29.07	29.8	0.135	0.16	0.237	0.28	-0.02
1880	661	Right	Tilt	/	29.11	29.8	0.127	0.15	0.223	0.26	0.03
1850.2	512	Right	Tilt	/	29.18	29.8	0.110	0.13	0.193	0.22	0.06

Table 12.7: SAR Values (GSM 1900 MHz Band - Body) –CAB3120000C3

Ambient Temperature: 22.6 °C						Liquid Temperature: 22.1 °C					
Frequency		Mode (number of timeslots)	Test Position	Figure No.	Conducted Power (dBm)	Max. tune-up Power (dBm)	Measured SAR(10g) (W/kg)	Reported SAR(10g) (W/kg)	Measured SAR(1g) (W/kg)	Reported SAR(1g) (W/kg)	Power Drift (dB)
MHz	Ch.										
1880	661	GPRS (3)	Front	/	25.66	26	0.222	0.24	0.384	0.42	0.04
1909.8	810	GPRS (3)	Rear	Fig.4	25.64	26	0.470	0.51	0.815	0.89	0.11
1880	661	GPRS (3)	Rear	/	25.66	26	0.366	0.40	0.658	0.71	-0.02
1850.2	512	GPRS (3)	Rear	/	25.67	26	0.413	0.45	0.767	0.83	0.05
1880	661	GPRS (3)	Left	/	25.66	26	0.069	0.07	0.120	0.13	0.10
1880	661	GPRS (3)	Right	/	25.66	26	0.103	0.11	0.186	0.20	0.06
1880	661	GPRS (3)	Bottom	/	25.66	26	0.147	0.16	0.268	0.29	0.05
1909.8	810	EGPRS (3)	Rear	/	25.65	26	0.463	0.50	0.799	0.87	0.07
1909.8	810	Speech	Bottom Headset1	/	29.07	29.8	0.348	0.41	0.634	0.75	0.07
1909.8	810	Speech	Bottom Headset2	/	29.07	29.8	0.356	0.42	0.637	0.75	0.06

Note1: The distance between the EUT and the phantom bottom is 10mm.

Note2: The Headset1 is CCB3160A11C1, the Headset2 is CCB3160A11C4.

Table 12.8: SAR Values (WCDMA 850 MHz Band - Head) –CAB3120000C3

Ambient Temperature: 22.5 °C						Liquid Temperature: 22.0 °C					
Frequency		Side	Test Position	Figure No.	Conducted Power (dBm)	Max. tune-up Power (dBm)	Measured SAR(10g) (W/kg)	Reported SAR(10g) (W/kg)	Measured SAR(1g) (W/kg)	Reported SAR(1g) (W/kg)	Power Drift (dB)
MHz	Ch.										
846.6	4233	Left	Touch	/	22.71	23.5	0.303	0.36	0.443	0.53	-0.13
836.4	4182	Left	Touch	/	22.85	23.5	0.407	0.47	0.543	0.63	0.19
826.4	4132	Left	Touch	/	22.99	23.5	0.317	0.36	0.462	0.52	-0.03
846.6	4233	Left	Tilt	/	22.71	23.5	0.172	0.21	0.250	0.30	0.11
836.4	4182	Left	Tilt	/	22.85	23.5	0.204	0.24	0.296	0.34	-0.07
826.4	4132	Left	Tilt	/	22.99	23.5	0.161	0.18	0.246	0.28	-0.09
846.6	4233	Right	Touch	/	22.71	23.5	0.336	0.40	0.492	0.59	0.06
836.4	4182	Right	Touch	Fig.5	22.85	23.5	0.410	0.48	0.553	0.64	0.03
826.4	4132	Right	Touch	/	22.99	23.5	0.328	0.37	0.480	0.54	-0.02
846.6	4233	Right	Tilt	/	22.71	23.5	0.199	0.24	0.290	0.35	0.04
836.4	4182	Right	Tilt	/	22.85	23.5	0.221	0.26	0.322	0.37	0.00
826.4	4132	Right	Tilt	/	22.99	23.5	0.193	0.22	0.280	0.31	0.03

Table 12.9: SAR Values (WCDMA 850 MHz Band - Body) –CAB3120000C3

Ambient Temperature: 22.5 °C						Liquid Temperature: 22.0 °C				
Frequency		Test Position	Figure No.	Conducted Power (dBm)	Max. tune-up Power (dBm)	Measured SAR(10g) (W/kg)	Reported SAR(10g) (W/kg)	Measured SAR(1g) (W/kg)	Reported SAR(1g) (W/kg)	Power Drift (dB)
MHz	Ch.									
836.4	4182	Front	/	22.85	23.5	0.339	0.39	0.490	0.57	0.02
846.6	4233	Rear	/	22.71	23.5	0.422	0.51	0.617	0.74	-0.13
836.4	4182	Rear	Fig.6	22.85	23.5	0.561	0.65	0.785	0.91	0.04
826.4	4132	Rear	/	22.99	23.5	0.475	0.53	0.695	0.78	0.02
836.4	4182	Left	/	22.85	23.5	0.277	0.32	0.407	0.47	0.03
836.4	4182	Right	/	22.85	23.5	0.262	0.30	0.389	0.45	0.00
836.4	4182	Bottom	/	22.85	23.5	0.056	0.07	0.088	0.10	0.02
836.4	4182	Rear Headset1	/	22.85	23.5	0.459	0.53	0.669	0.78	-0.00
836.4	4182	Rear Headset2	/	22.85	23.5	0.472	0.55	0.693	0.80	-0.02

Note1: The distance between the EUT and the phantom bottom is 10mm.

Note2: The Headset1 is CCB3160A11C1, the Headset2 is CCB3160A11C4.