

# FCC TEST REPORT

**REPORT NO.:** RF940606H08

**MODEL NO.:** J07H081

**RECEIVED:** June 06, 2005

**TESTED:** June 06 to 16, 2005

**ISSUED:** June 21, 2005

**APPLICANT:** HON HAI PRECISION IND. CO., LTD.  
HSINCHU SCIENCE PARK BRANCH OFFICE

**ADDRESS:** 5F-1,5 Hsin-An Road Hsinchu, Science-Based  
Industrial Park Taiwan, R.O.C.

**ISSUED BY:** Advance Data Technology Corporation

**LAB LOCATION:** No. 81-1, Lu Liao Keng, 9 Ling, Wu Lung Tsuen,  
Chiung Lin Hsiang, Hsin Chu Hsien,  
Taiwan, R.O.C.

This test report consists of 91 pages in total. It may be duplicated completely for legal use with the approval of the applicant. It should not be reproduced except in full, without the written approval of our laboratory. The client should not use it to claim product endorsement by CNLA, A2LA or any government agencies. The test results in the report only apply to the tested sample. The test results in this report are traceable to the national or international standards.



0536  
ILAC MRA



No. 2177-01

## TABLE OF CONTENTS

1	CERTIFICATION .....	5
2	SUMMARY OF TEST RESULTS.....	6
3	GENERAL INFORMATION .....	7
3.1	GENERAL DESCRIPTION OF EUT.....	7
3.2	DESCRIPTION OF TEST MODES.....	8
3.3	TEST MODE APPLICABILITY AND TESTED CHANNEL DETAIL:.....	8
3.4	GENERAL DESCRIPTION OF APPLIED STANDARDS .....	10
3.5	DESCRIPTION OF SUPPORT UNITS.....	11
3.6	CONFIGURATION OF SYSTEM UNDER TEST .....	12
4	TEST PROCEDURES AND RESULTS .....	13
4.1	CONDUCTED EMISSION MEASUREMENT .....	13
4.1.1	LIMITS OF CONDUCTED EMISSION MEASUREMENT .....	13
4.1.2	TEST INSTRUMENTS .....	13
4.1.3	TEST PROCEDURES.....	14
4.1.4	DEVIATION FROM TEST STANDARD .....	14
4.1.5	TEST SETUP .....	15
4.1.6	EUT OPERATING CONDITIONS.....	15
4.1.7	TEST RESULTS.....	16
4.2	NUMBER OF HOPPING FREQUENCY USED .....	18
4.2.1	LIMIT OF HOPPING FREQUENCY USED .....	18
4.2.2	TEST INSTRUMENTS .....	18
4.2.3	TEST PROCEDURES.....	19
4.2.4	DEVIATION FROM TEST STANDARD .....	19
4.2.5	TEST SETUP .....	20
4.2.6	TEST RESULTS(MODE A) .....	20
4.2.7	TEST RESULTS(MODE B) .....	22
4.2.8	TEST RESULTS(MODE C).....	24
4.3	DWELL TIME ON EACH CHANNEL .....	26
4.3.1	LIMIT OF DWELL TIME USED .....	26
4.3.2	TEST INSTRUMENTS .....	26
4.3.3	TEST PROCEDURES.....	27
4.3.4	DEVIATION FROM TEST STANDARD .....	27
4.3.5	TEST SETUP .....	27
4.3.6	TEST RESULTS.....	28
4.4	CHANNEL BANDWIDTH .....	32
4.4.1	TEST INSTRUMENTS .....	32
4.4.2	TEST PROCEDURE .....	33
4.4.3	DEVIATION FROM TEST STANDARD .....	33
4.4.4	TEST SETUP .....	33

4.4.5	EUT OPERATING CONDITION .....	33
4.4.6	TEST RESULTS(MODE A) .....	34
4.4.7	TEST RESULTS(MODE B) .....	37
4.4.8	TEST RESULTS(MODE C) .....	40
4.5	HOPPING CHANNEL SEPARATION .....	43
4.5.1	LIMIT OF HOPPING CHANNEL SEPARATION .....	43
4.5.2	TEST INSTRUMENTS .....	43
4.5.3	TEST PROCEDURES .....	44
4.5.4	DEVIATION FROM TEST STANDARD .....	44
4.5.5	TEST SETUP .....	44
4.5.6	TEST RESULTS(MODE A) .....	45
4.5.7	TEST RESULTS(MODE B) .....	48
4.5.8	TEST RESULTS(MODE C) .....	51
4.6	MAXIMUM PEAK OUTPUT POWER .....	54
4.6.1	LIMITS OF MAXIMUM PEAK OUTPUT POWER MEASUREMENT .....	54
4.6.2	INSTRUMENTS .....	54
4.6.3	TEST PROCEDURES .....	55
4.6.4	DEVIATION FROM TEST STANDARD .....	55
4.6.5	TEST SETUP .....	56
4.6.6	EUT OPERATING CONDITION .....	56
4.6.7	TEST RESULTS(MODE A) .....	57
4.6.8	TEST RESULTS(MODE B) .....	60
4.6.9	TEST RESULTS(MODE C) .....	63
4.7	RADIATED EMISSION MEASUREMENT .....	66
4.7.1	LIMITS OF RADIATED EMISSION MEASUREMENT .....	66
4.7.2	TEST INSTRUMENTS .....	67
4.7.3	TEST PROCEDURES .....	68
4.7.4	DEVIATION FROM TEST STANDARD .....	68
4.7.5	TEST SETUP .....	69
4.7.6	TEST RESULTS .....	70
4.7.7	TEST RESULTS (MODE A) .....	71
4.7.8	TEST RESULTS (MODE C) .....	74
4.8	BAND EDGES MEASUREMENT .....	77
4.8.1	LIMITS OF BAND EDGES MEASUREMENT .....	77
4.8.2	TEST INSTRUMENTS .....	77
4.8.3	TEST PROCEDURE .....	77
4.8.4	DEVIATION FROM TEST STANDARD .....	77
4.8.5	EUT OPERATING CONDITION .....	77
4.8.6	TEST RESULTS (MODE A) .....	78
4.8.7	TEST RESULTS (MODE C) .....	80
4.9	ANTENNA REQUIREMENT .....	82





4.9.1	STANDARD APPLICABLE .....	82
4.9.2	ANTENNA CONNECTED CONSTRUCTION.....	82
5	PHOTOGRAPHS OF THE TEST CONFIGURATION.....	83
6	INFORMATION ON THE TESTING LABORATORIES .....	91

## 1 CERTIFICATION

**PRODUCT :** ThinkPad Bluetooth with Enhanced Data Rate  
**BRAND NAME :** FOXCONN  
**MODEL NO. :** J07H081  
**APPLICANT :** HON HAI PRECISION IND. CO., LTD. HSINCHU  
SCIENCE PARK BRANCH OFFICE  
**TESTED DATE:** June 06 to 16, 2005  
**TEST ITEM :** ENGINEERING SAMPLE  
**STANDARDS :** 47 CFR Part 15, Subpart C (Section 15.247),  
ANSI C63.4-2003

The above equipment (Model: J07H081) has been tested by **Advance Data Technology Corporation**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

**PREPARED BY :**  , **DATE:** June 21, 2005  
( Midoli Peng )

**TECHNICAL ACCEPTANCE :**  , **DATE:** June 21, 2005  
Responsible for RF ( Hank Chung )

**APPROVED BY :**  , **DATE:** June 21, 2005  
( May Chen, Deputy Manager )

## 2 SUMMARY OF TEST RESULTS

The EUT has been tested according to the following specifications:

APPLIED STANDARD: 47 CFR Part 15, Subpart C			
Standard Section	Test Type and Limit	Result	REMARK
15.207	AC Power Conducted Emission	PASS	Meet the requirement of limit Minimum passing margin is -12.84dB at 0.701 MHz
15.247(a)(1)(I)-(ii)	Number of Hopping Frequency Used Spec.: At least 75 channels	PASS	Meet the requirement of limit
15.247(a)(1)(ii)	Dwell Time on Each Channel Spec. : Max. 0.4 second within 31.6 second	PASS	Meet the requirement of limit
15.247(a)(1)(I)-(ii)	Hopping Channel Separation Spec. : Min. 25 kHz or two-thirds 20 dB bandwidth, which ever is greater	PASS	Meet the requirement of limit
15.247(a)(2)	Spectrum Bandwidth of a Frequency Hopping Sequence Spread Spectrum System Spec.: Max. 1 MHz	PASS	Meet the requirement of limit
15.247(b)	Maximum Peak Output Power Spec.: max. 30dBm	PASS	Meet the requirement of limit
15.247(c)	Transmitter Radiated Emissions Spec.: Table 15.209	PASS	Meet the requirement of limit Minimum passing margin is -7.4dB at 744.00MHz
15.247(c)	Band Edge Measurement	PASS	Meet the requirement of limit

### 3 GENERAL INFORMATION

#### 3.1 GENERAL DESCRIPTION OF EUT

<b>PRODUCT</b>	ThinkPad Bluetooth with Enhanced Data Rate
<b>MODEL NO.</b>	J07H081
<b>POWER SUPPLY</b>	DC 3.3V from host equipment
<b>MODULATION TYPE</b>	1 Mbps: GFSK 2 Mbps(EDR): $\pi/4$ -DQPSK 3 Mbps(EDR):8-DPSK
<b>MODULATION TECHNOLOGY</b>	FHSS
<b>FREQUENCY RANGE</b>	2402MHz ~ 2480MHz
<b>NUMBER OF CHANNEL</b>	79
<b>OUTPUT POWER</b>	4.90dBm
<b>ANTENNA TYPE</b>	Chip Antenna with 2dBi antenna gain
<b>DATA CABLE</b>	NA
<b>I/O PORTS</b>	NA
<b>ASSOCIATED DEVICES</b>	NA

**NOTE:**

1. Bluetooth technology is used for the EUT.
2. The above EUT information was declared by manufacturer and for more detailed features description, please refer to the manufacturer's specifications or User's Manual.

### 3.2 DESCRIPTION OF TEST MODES

Seventy-nine channels are provided to this EUT.

Channel	Freq. (MHz)	Channel	Freq. (MHz)	Channel	Freq. (MHz)	Channel	Freq. (MHz)
0	2402	20	2422	40	2442	60	2462
1	2403	21	2423	41	2443	61	2463
2	2404	22	2424	42	2444	62	2464
3	2405	23	2425	43	2445	63	2465
4	2406	24	2426	44	2446	64	2466
5	2407	25	2427	45	2447	65	2467
6	2408	26	2428	46	2448	66	2468
7	2409	27	2429	47	2449	67	2469
8	2410	28	2430	48	2450	68	2470
9	2411	29	2431	49	2451	69	2471
10	2412	30	2431	50	2452	70	2472
11	2413	31	2433	51	2453	71	2473
12	2414	32	2434	52	2454	72	2474
13	2415	33	2435	53	2455	73	2475
14	2416	34	2436	54	2456	74	2476
15	2417	35	2437	55	2457	75	2477
16	2418	36	2438	56	2458	76	2478
17	2419	37	2439	57	2459	77	2479
18	2420	38	2440	58	2460	78	2480
19	2421	39	2441	59	2461		

### 3.3 TEST MODE APPLICABILITY AND TESTED CHANNEL DETAIL:

EUT configure mode	Applicable to				Description
	PLC	RE<1G	RE≥1G	APCM	
A	Note 1	Note 1	v	v	Modulation Type: GFSK For 1Mbps
B	Note 1	Note 1	Note 2	v	Modulation Type: $\pi/4$ -DQPSK for 2Mbps
C	Note 1	Note 1	Note 2	v	Modulation Type: 8-DPSK for 3Mbps

Where PLC: Power Line Conducted Emission

RE<1G charge function. RE: Radiated Emission below 1GHz

RE≥1G: Radiated Emission above 1GHz

APCM: Antenna Port Conducted Measurement

Note 1: Pre-scan different modulation type were no effect for Power Line Conducted Emission and only the worst case recorded in this report.

Note 2: Pre-Scan  $\pi/4$ -DQPSK for 2Mbps and 8-DPSK for 3Mbps to determine the worst-case mode.



**Power Line Conducted Emission:**

- ☒ Pre-Scan to determine the worst-case mode from all possible combinations between available modulations and packet types.
- ☒ Following channel(s) was (were) selected for the final test as listed below.

Available Channel	Tested Channel	Modulation Technology	Modulation Type	Packet Type
0 to 78	78	FHSS	Note 1	DH5

Note 1: Pre-scan different modulation type were no effect for Power Line Conducted Emission and only the worst case recorded in this report.

**Radiated Emission Test (Below 1 GHz):**

- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, X, Y, Z axis and packet types
- ☒ Following channel(s) was (were) selected for the final test as listed below.

EUT configure mode	Available Channel	Tested Channel	Modulation Technology	Modulation Type	Packet Type	Axis
A	0 to 78	78	FHSS	GFSK	DH5	Z

**Radiated Emission Test (Above 1 GHz):**

- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, X, Y, Z Axis and packet types.
- ☒ Following channel(s) was (were) selected for the final test as listed below.

EUT configure mode	Available Channel	Tested Channel	Modulation Technology	Modulation Type	Packet Type	Axis
A	0 to 78	0,39,78	FHSS	GFSK	DH5	Z
C	0 to 78	0,39,78	FHSS	8-DPSK	DH5	Z

**Bandedge Measurement:**

- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations and packet types.
- ☒ Following channel(s) was (were) selected for the final test as listed below.

Available Channel	Tested Channel	Modulation Technology	Modulation Type	Packet Type
0 to 78	0, 78	FHSS	GFSK	DH5
0 to 78	0, 78	FHSS	8-DPSK	DH5

**Antenna Port Conducted Measurement:**

- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations and packet types.
- ☒ Following channel(s) was (were) selected for the final test as listed below.

Available Channel	Tested Channel	Modulation Technology	Modulation Type	Packet Type
0 to 78	0, 39, 78	FHSS	GFSK	DH5
0 to 78	0, 39, 78	FHSS	$\pi/4$ -DQPSK	DH5
0 to 78	0, 39, 78	FHSS	8-DPSK	DH5

### **3.4 GENERAL DESCRIPTION OF APPLIED STANDARDS**

The EUT is a ThinkPad Bluetooth with Enhanced Data Rate. According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

**FCC Part 15, Subpart C. (15.247)**

**ANSI C63.4 : 2003**

All test items have been performed and recorded as per the above standards.

**NOTE:** The EUT is also considered as a kind of computer peripheral, because the connection to computer is necessary for typical use. It has been verified to comply with the requirements of FCC Part 15, Subpart B, Class B (DoC). The test report has been issued separately.

### 3.5 DESCRIPTION OF SUPPORT UNITS


The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

No.	Product	Brand	Model No.	Serial No.	FCC ID
1	NOTEBOOK COMPUTER	DELL	INSPIRON 5000e	DS/N TW-054UGW-12961-0BR-0670	NA
2	PRINTER	HP	C2642A	MY79F1C3MZ	B94C2642X
3	MODEM	ACEEX	1414	0206026773	IFAXDM1414

No.	Signal cable description
1	NA
2	1.1 m braid shielded wire, terminated with DB25 and Centronics connector via metallic frame, w/o core
3	1.2 m braid shielded wire, terminated with DB25 and DB9 connector via metallic frame, w/o core.

Note: 1. All power cords of the above support units are unshielded (1.8m).

### 3.6 CONFIGURATION OF SYSTEM UNDER TEST



## 4 TEST PROCEDURES AND RESULTS

### 4.1 CONDUCTED EMISSION MEASUREMENT

#### 4.1.1 LIMITS OF CONDUCTED EMISSION MEASUREMENT

FREQUENCY OF EMISSION (MHz)	CONDUCTED LIMIT (dB $\mu$ V)	
	Quasi-peak	Average
0.15-0.5	66 to 56	56 to 46
0.5-5	56	46
5-30	60	50

**Notes:**

1. The lower limit shall apply at the transition frequencies.
2. All emanations from a class A/B digital device or system, including any network of conductors and apparatus connected thereto, shall not exceed the level of field strengths specified above.

#### 4.1.2 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED UNTIL
*ROHDE & SCHWARZ Test Receiver	ESCS 30	847124/029	Dec. 07, 2005
*ROHDE & SCHWARZ LISN (for EUT)	ESHS-Z5	848773/004	Nov. 08, 2005
*KYORITSU LISN (for peripheral)	KNW-407	8/1395/12	Jul. 23, 2005
*RF Cable (JETBAO)	RG233/U	Cable_CA_01	Jul. 02, 2005
*Terminator(for KYORITSU)	50	3	Oct. 12, 2005
*Software	Cond-V2e	NA	NA

**Note:**

1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
2. The test was performed in ADT Shielded Room No. A.
3. The VCCI Con A Registration No. is C-817.
4. \* = These equipment are used for the final measurement.
5. The measurement uncertainty is 2.53 dB, which is calculated as per the document CISPR 16-4


#### 4.1.3 TEST PROCEDURES

- a. The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN. The two LISNs provide 50 ohm/ 50uH of coupling impedance for the measuring instrument.
- b. Both lines of the power mains connected to the EUT were checked for maximum conducted interference.
- c. The frequency range from 150kHz to 30MHz was searched. Emission levels under Limit - 20dB was not recorded.

#### 4.1.4 DEVIATION FROM TEST STANDARD

No deviation

#### 4.1.5 TEST SETUP



- Note:**
1. Support units were connected to second LISN.
  2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

For the actual test configuration, please refer to the related item – Photographs of the Test Configuration.

#### 4.1.6 EUT OPERATING CONDITIONS


- a. Connected the EUT to test board and placed on the testing table.
- b. The support unit 1 (Notebook computer) ran a test program "Broadcom Bluetool" to enable EUT under transmission condition continuously at specific channel frequency.
- c. Notebook computer sends "H" messages to printer, and the printer prints them on paper.
- d. Notebook computer sends "H" messages to modem.

## 4.1.7 TEST RESULTS

<b>EUT</b>	ThinkPad Bluetooth with Enhanced Data Rate		
<b>MODEL</b>	J07H081	<b>6dB BANDWIDTH</b>	9 kHz
<b>INPUT POWER (SYSTEM)</b>	120Vac, 60 Hz	<b>PHASE</b>	Line (L)
<b>ENVIRONMENTAL CONDITIONS</b>	26 deg. C, 58%RH, 963 hPa	<b>TESTED BY</b>	Rex Huang

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value		Emission Level		Limit		Margin	
			[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.154	0.14	46.75	-	46.89	-	65.79	55.79	-18.90	-
2	0.361	0.17	45.34	-	45.51	-	58.71	48.71	-13.20	-
3	<b>0.701</b>	<b>0.19</b>	<b>42.97</b>	-	<b>43.16</b>	-	<b>56.00</b>	<b>46.00</b>	<b>-12.84</b>	-
4	1.291	0.21	40.52	-	40.73	-	56.00	46.00	-15.27	-
5	7.070	0.60	28.37	-	28.97	-	60.00	50.00	-31.03	-
6	10.988	0.80	30.53	-	31.33	-	60.00	50.00	-28.67	-

- REMARKS:**
1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
  2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
  3. The emission levels of other frequencies were very low against the limit.
  4. Margin value = Emission level - Limit value
  5. Correction factor = Insertion loss + Cable loss
  6. Emission Level = Correction Factor + Reading Value.






<b>EUT</b>	ThinkPad Bluetooth with Enhanced Data Rate		
<b>MODEL</b>	J07H081	<b>6dB BANDWIDTH</b>	9 kHz
<b>INPUT POWER (SYSTEM)</b>	120Vac, 60 Hz	<b>PHASE</b>	Neutral (N)
<b>ENVIRONMENTAL CONDITIONS</b>	26 deg. C, 58%RH, 963 hPa	<b>TESTED BY</b>	Rex Huang

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value		Emission Level		Limit		Margin	
			[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.158	0.14	46.28	-	46.42	-	65.58	55.58	-19.16	-
2	0.361	0.17	45.22	-	45.39	-	58.71	48.71	-13.32	-
3	0.689	0.18	39.95	-	40.13	-	56.00	46.00	-15.87	-
4	1.970	0.25	35.87	-	36.12	-	56.00	46.00	-19.88	-
5	6.789	0.54	28.20	-	28.74	-	60.00	50.00	-31.26	-
6	10.766	0.69	31.84	-	32.53	-	60.00	50.00	-27.47	-

- REMARKS:** 1. Q.P. and AV. are abbreviations of quasi-peak and average individually.  
2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.  
3. The emission levels of other frequencies were very low against the limit.  
4. Margin value = Emission level - Limit value  
5. Correction factor = Insertion loss + Cable loss  
6. Emission Level = Correction Factor + Reading Value.



## 4.2 NUMBER OF HOPPING FREQUENCY USED

### 4.2.1 LIMIT OF HOPPING FREQUENCY USED

At least 15 hopping frequencies, and should be equally spaced.

### 4.2.2 TEST INSTRUMENTS

Description & Manufacturer	Model No.	Serial No.	Calibrated Until
R&S SPECTRUM ANALYZER	FSP40	100037	Nov. 23, 2005

**Note:**

1. The measurement uncertainty is 226Hz, which is calculated as per the document ETSI TR 100 028.
2. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.


#### 4.2.3 TEST PROCEDURES

1. Check the calibration of the measuring instrument (SA) using either an internal calibrator or a known signal from an external generator.
2. Turn on the EUT and connect its antenna terminal to measurement via a low loss cable. Then set it to any one measured frequency within its operating range and make sure the instrument is operated in its linear range.
3. Set the SA on MaxHold Mode, and then keep the EUT in hopping mode. Record all the signals from each channel until each one has been recorded.
4. Set the SA on View mode and then plot the result on SA screen.
5. Repeat above procedures until all frequencies measured were complete.

#### 4.2.4 DEVIATION FROM TEST STANDARD



No deviation

#### 4.2.5 TEST SETUP





#### 4.2.6 TEST RESULTS(MODE A)

There are 79 hopping frequencies in the hopping mode. Please refer to next two pages for the test result. On the plots, it shows that the hopping frequencies are equally spaced.



#### 4.2.7 TEST RESULTS(MODE B)



There are 79 hopping frequencies in the hopping mode. Please refer to next two pages for the test result. On the plots, it shows that the hopping frequencies are equally spaced.



#### 4.2.8 TEST RESULTS(MODE C)

There are 79 hopping frequencies in the hopping mode. Please refer to next two pages for the test result. On the plots, it shows that the hopping frequencies are equally spaced.





### 4.3 DWELL TIME ON EACH CHANNEL

#### 4.3.1 LIMIT OF DWELL TIME USED

For FHSS, the average time of occupancy on any frequency shall not be greater than 0.4 seconds within a 31.6 second period. For hybrid systems, the average time of occupancy on any frequency should not exceed 0.4 seconds within a time period in seconds equal to the number of hopping frequencies employed multiplied by 0.4.

#### 4.3.2 TEST INSTRUMENTS

Description & Manufacturer	Model No.	Serial No.	Calibrated Until
R&S SPECTRUM ANALYZER	FSP40	100036	Nov. 23, 2005

**Note:**

1. The measurement uncertainty is 226Hz, which is calculated as per the document ETSI TR 100 028.
2. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

#### 4.3.3 TEST PROCEDURES

1. Check the calibration of the measuring instrument (SA) using either an internal calibrator or a known signal from an external generator.
2. Turn on the EUT and connect its antenna terminal to measurement via a low loss cable. Then set it to any one measured frequency within its operating range and make sure the instrument is operated in its linear range.
3. Adjust the center frequency of SA on any frequency be measured and set SA to zero span mode. And then, set RBW and VBW of spectrum analyzer to proper value.
4. Measure the time duration of one transmission on the measured frequency. And then plot the result with time difference of this time duration.
5. Repeat above procedures until all frequencies measured were complete.

#### 4.3.4 DEVIATION FROM TEST STANDARD

No deviation

#### 4.3.5 TEST SETUP







#### 4.3.6 TEST RESULTS



Mode	Number of transmission in a 31.6 (79Hopping*0.4)	Length of transmission time (msec)	Result (msec)	Limit (msec)
DH1	51 (times / 5 sec) *6.32=322.32 times	0.412	132.80	400
DH3	30 (times / 5 sec) *6.32=189.6 times	1.68	318.53	400
DH5	19 (times / 5 sec) *6.32=120.08 times	2.96	355.44	400

Test plots of the transmitting time slot are shown on next three pages.

## DH1



**DH3**

**DH5**

## 4.4 CHANNEL BANDWIDTH

### 4.4.1 TEST INSTRUMENTS

Description & Manufacturer	Model No.	Serial No.	Calibrated Until
R&S SPECTRUM ANALYZER	FSP40	100036	Nov. 23, 2005

**NOTE:**

- 1.The measurement uncertainty is less than +/- 2.6dB, which is calculated as per the NAMAS document NIS81.
- 2.The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.




#### 4.4.2 TEST PROCEDURE

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.
3. Measure the frequency difference of two frequencies that were attenuated 20dB from the reference level. Record the frequency difference as the emission bandwidth.
4. Repeat above procedures until all frequencies measured were complete.

#### 4.4.3 DEVIATION FROM TEST STANDARD

No deviation

#### 4.4.4 TEST SETUP





#### 4.4.5 EUT OPERATING CONDITION


The software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel frequencies individually.

## 4.4.6 TEST RESULTS(MODE A)

<b>EUT</b>	ThinkPad Bluetooth with Enhanced Data Rate	<b>MODEL</b>	J07H081
<b>ENVIRONMENTAL CONDITIONS</b>	20deg. C, 70%RH, 963 hPa	<b>INPUT POWER (SYSTEM)</b>	120Vac, 60 Hz
<b>TESTED BY</b>	Rex Huang		

<b>CHANNEL</b>	<b>CHANNEL FREQUENCY (MHz)</b>	<b>20dB BANDWIDTH (kHz)</b>
0	2402	966
39	2441	966
78	2480	966



**Channel 0****Channel 39**


**Channel 78**

## 4.4.7 TEST RESULTS(MODE B)

<b>EUT</b>	ThinkPad Bluetooth with Enhanced Data Rate	<b>MODEL</b>	J07H081
<b>ENVIRONMENTAL CONDITIONS</b>	20deg. C, 70%RH, 963 hPa	<b>INPUT POWER (SYSTEM)</b>	120Vac, 60 Hz
<b>TESTED BY</b>	Rex Huang		

<b>CHANNEL</b>	<b>CHANNEL FREQUENCY (MHz)</b>	<b>20dB BANDWIDTH (kHz)</b>
0	2402	1374
39	2441	1368
78	2480	1368

**Channel 0****Channel 39**



**Channel 78**


## 4.4.8 TEST RESULTS(MODE C)

<b>EUT</b>	ThinkPad Bluetooth with Enhanced Data Rate	<b>MODEL</b>	J07H081
<b>ENVIRONMENTAL CONDITIONS</b>	20deg. C, 70%RH, 963 hPa	<b>INPUT POWER (SYSTEM)</b>	120Vac, 60 Hz
<b>TESTED BY</b>	Rex Huang		

<b>CHANNEL</b>	<b>CHANNEL FREQUENCY (MHz)</b>	<b>20dB BANDWIDTH (kHz)</b>
0	2402	1356
39	2441	1356
78	2480	1352



**Channel 0****Channel 39**

**Channel 78**

## 4.5 HOPPING CHANNEL SEPARATION

### 4.5.1 LIMIT OF HOPPING CHANNEL SEPARATION

At least 25 kHz or two-thirds of 20dB hopping channel bandwidth (whichever is greater).

### 4.5.2 TEST INSTRUMENTS

Description & Manufacturer	Model No.	Serial No.	Calibrated Until
R&S SPECTRUM ANALYZER	FSP40	100036	Nov. 23, 2005

**NOTE:**

- 1.The measurement uncertainty is less than +/- 2.6dB, which is calculated as per the NAMAS document NIS81.
- 2.The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.


#### 4.5.3 TEST PROCEDURES

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range.
3. By using the MaxHold function record the separation of two adjacent channels.
4. Measure the frequency difference of these two adjacent channels by SA MARK function. And then plot the result on SA screen.
5. Repeat above procedures until all frequencies measured were complete.

#### 4.5.4 DEVIATION FROM TEST STANDARD

No deviation

#### 4.5.5 TEST SETUP






## 4.5.6 TEST RESULTS(MODE A)

<b>EUT</b>	ThinkPad Bluetooth with Enhanced Data Rate	<b>MODEL</b>	J07H081
<b>ENVIRONMENTAL CONDITIONS</b>	20 deg. C, 70%RH, 963 hPa	<b>INPUT POWER (SYSTEM)</b>	120Vac, 60 Hz
<b>TESTED BY</b>	Rex Huang		

Channel	Frequency (MHz)	Adjacent Channel Separation	Minimum Limit (kHz)	Pass / Fail
0	2402	1.002MHz	644	PASS
39	2441	1.002MHz	644	PASS
78	2480	1.002MHz	644	PASS

The minimum limit is two-thirds of 20dB bandwidth. Test results please refer to next three pages.

**Channel 0****Channel 39**

**Channel 78**



## 4.5.7 TEST RESULTS(MODE B)


<b>EUT</b>	ThinkPad Bluetooth with Enhanced Data Rate	<b>MODEL</b>	J07H081
<b>ENVIRONMENTAL CONDITIONS</b>	20 deg. C, 70%RH, 963 hPa	<b>INPUT POWER (SYSTEM)</b>	120Vac, 60 Hz
<b>TESTED BY</b>	Rex Huang		

Channel	Frequency (MHz)	Adjacent Channel Separation	Minimum Limit (kHz)	Pass / Fail
0	2402	1.002MHz	916	PASS
39	2441	1.002MHz	912	PASS
78	2480	1.008MHz	912	PASS

The minimum limit is two-thirds of 20dB bandwidth. Test results please refer to next three pages.



**Channel 0****Channel 39**



**Channel 78**


## 4.5.8 TEST RESULTS(MODE C)

<b>EUT</b>	ThinkPad Bluetooth with Enhanced Data Rate	<b>MODEL</b>	J07H081
<b>ENVIRONMENTAL CONDITIONS</b>	20 deg. C, 70%RH, 963 hPa	<b>INPUT POWER (SYSTEM)</b>	120Vac, 60 Hz
<b>TESTED BY</b>	Rex Huang		

Channel	Frequency (MHz)	Adjacent Channel Separation	Minimum Limit (kHz)	Pass / Fail
0	2402	1.002MHz	904	PASS
39	2441	1.002MHz	904	PASS
78	2480	1.002MHz	901	PASS

The minimum limit is two-thirds of 20dB bandwidth. Test results please refer to next three pages.

**Channel 0****Channel 39**

**Channel 78**

## 4.6 MAXIMUM PEAK OUTPUT POWER

### 4.6.1 LIMITS OF MAXIMUM PEAK OUTPUT POWER MEASUREMENT

The Maximum Peak Output Power Measurement is 30dBm.

### 4.6.2 INSTRUMENTS

Description & Manufacturer	Model No.	Serial No.	Calibrated Until
R&S SPECTRUM ANALYZER	FSP40	100036	Nov. 23, 2005
Agilent SIGNAL GENERATOR	E8257C	MY43320668	Dec. 07, 2005
TEKTRONIX OSCILLOSCOPE	TDS 220	B027241	Jun. 18, 2005
NARDA DETECTOR	4503A	0306	NA

**NOTE:**

The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

#### 4.6.3 TEST PROCEDURES

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.
3. The center frequency of the spectrum analyzer is set to the fundamental frequency and using 3 MHz RBW and 3 MHz VBW.
4. Measure the frequency difference of two frequencies that were attenuated 20dB from the reference level. Record the frequency difference as the emission bandwidth.
5. Repeat above procedures until all frequencies measured were complete.

#### 4.6.4 DEVIATION FROM TEST STANDARD

No deviation

#### 4.6.5 TEST SETUP



For the actual test configuration, please refer to the related Item – Photographs of the Test Configuration.

#### 4.6.6 EUT OPERATING CONDITION



The software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel frequencies individually.




## 4.6.7 TEST RESULTS(MODE A)

<b>EUT</b>	ThinkPad Bluetooth with Enhanced Data Rate	<b>MODEL</b>	J07H081
<b>ENVIRONMENTAL CONDITIONS</b>	20 deg. C, 70%RH, 963 hPa	<b>INPUT POWER (SYSTEM)</b>	120Vac, 60 Hz
<b>TESTED BY</b>	Rex Huang		

<b>CHANNEL</b>	<b>CHANNEL FREQUENCY (MHz)</b>	<b>PEAK POWER OUTPUT (dBm)</b>	<b>PEAK POWER LIMIT (dBm)</b>	<b>PASS/FAIL</b>
0	2402	2.62	30	PASS
39	2441	2.89	30	PASS
78	2480	2.81	30	PASS



**Channel 0****Channel 39**


**Channel 78**

## 4.6.8 TEST RESULTS(MODE B)

<b>EUT</b>	ThinkPad Bluetooth with Enhanced Data Rate	<b>MODEL</b>	J07H081
<b>ENVIRONMENTAL CONDITIONS</b>	20 deg. C, 70%RH, 963 hPa	<b>INPUT POWER (SYSTEM)</b>	120Vac, 60 Hz
<b>TESTED BY</b>	Rex Huang		

<b>CHANNEL</b>	<b>CHANNEL FREQUENCY (MHz)</b>	<b>PEAK POWER OUTPUT (dBm)</b>	<b>PEAK POWER LIMIT (dBm)</b>	<b>PASS/FAIL</b>
0	2402	4.58	30	PASS
39	2441	4.87	30	PASS
78	2480	4.73	30	PASS



**Channel 0****Channel 39**

**Channel 78**

## 4.6.9 TEST RESULTS(MODE C)


<b>EUT</b>	ThinkPad Bluetooth with Enhanced Data Rate	<b>MODEL</b>	J07H081
<b>ENVIRONMENTAL CONDITIONS</b>	20 deg. C, 70%RH, 963 hPa	<b>INPUT POWER (SYSTEM)</b>	120Vac, 60 Hz
<b>TESTED BY</b>	Rex Huang		

<b>CHANNEL</b>	<b>CHANNEL FREQUENCY (MHz)</b>	<b>PEAK POWER OUTPUT (dBm)</b>	<b>PEAK POWER LIMIT (dBm)</b>	<b>PASS/FAIL</b>
0	2402	4.81	30	PASS
39	2441	4.90	30	PASS
78	2480	4.74	30	PASS

**Channel 0****Channel 39**



## Channel 78



## 4.7 RADIATED EMISSION MEASUREMENT

### 4.7.1 LIMITS OF RADIATED EMISSION MEASUREMENT

Emissions radiated outside of the specified bands, shall be according to the general radiated limits in 15.209 as following:

Frequencies (MHz)	Field strength (microvolts/meter)	Measurement distance (meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

As shown in 15.35(b), for frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.

## 4.7.2 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED UNTIL
HP Spectrum Analyzer	8594E	3710A04861	Sep. 23, 2005
ADVANTEST Spectrum Analyzer	R3271A	85060311	Jun. 29, 2005
CHASE RF Pre_Amplifier	CPA9232	1057	Aug. 06, 2005
HP Pre_Amplifier	8449B	3008A01922	Oct. 13, 2005
ROHDE & SCHWARZ Test Receiver	ESCS30	100287	Dec. 08, 2005
CHASE Broadband Antenna	VULB9168	138	Dec. 21, 2005
Schwarzbeck Horn_Antenna	BBHA9120	D124	Jun. 16, 2005
Schwarzbeck Horn_Antenna	BBHA 9170	BBHA9170153	Jan. 30, 2006
SCHWARZBECK Biconical Antenna	VHBA9123	459	Jun. 26, 2006
SCHWARZBECK Periodic Antenna	UPA6108	1148	Jun. 26, 2006
RF Switches (ARNITSU)	CS-201	1565157	Jul. 15, 2005
RF CABLE (Chaintek) 1GHz-20GHz	SF102	22054-2	Nov. 15, 2005
RF Cable(RICHTEC)	9913-30M	STCCAB-30M-1GHz-021	Jul. 15, 2005
Software	ADT_Radiated_V 5.14	NA	NA
CHANCE MOST Antenna Tower	AT-100	0203	NA
CHANCE MOST Turn Table	TT-100	0203	NA

- Note: 1. The calibration interval of the above test instruments is 12 months (36 months for Periodic Antenna) and the calibrations are traceable to NML/ROC and NIST/USA.
2. The horn antenna and HP preamplifier (model: 8449B) are used only for the measurement of emission frequency above 1GHz if tested.
3. The test was performed in ADT Open Site No. C.
4. The FCC Site Registration No. is 656396.
5. The VCCI Site Registration No. is R-1626.
6. The CANADA Site Registration No. is IC 4824-3.
7. The following table is for the measurement uncertainty, which is calculated as per the document CISPR 16-4.

Measurement	Value
Radiated emissions (30MHz-1GHz)	2.98 dB
Radiated emissions (1GHz ~18GHz)	2.21 dB
Radiated emissions (18GHz ~20GHz)	1.88 dB

#### 4.7.3 TEST PROCEDURES

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 10 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna is a broadband antenna, and its height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. If the emission level of the EUT in peak mode was 10 dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10 dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.


**NOTE:**

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for Peak detection (PK) and Quasi-peak detection (QP) at frequency below 1GHz.
2. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 1 MHz for Peak detection at frequency above 1GHz.
3. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 10 Hz for Average detection (AV) at frequency above 1GHz.

#### 4.7.4 DEVIATION FROM TEST STANDARD

No deviation

#### 4.7.5 TEST SETUP



For the actual test configuration, please refer to the related item – Photographs of the Test Configuration.

## 4.7.6 TEST RESULTS

<b>EUT</b>	ThinkPad Bluetooth with Enhanced Data Rate	<b>MODEL</b>	J07H081
<b>CHANNEL</b>	78	<b>FREQUENCY RANGE</b>	Below 1GHz
<b>INPUT POWER (SYSTEM)</b>	120Vac, 60 Hz	<b>DETECTOR FUNCTION</b>	Quasi-Peak
<b>ENVIRONMENTAL CONDITIONS</b>	24 deg. C, 56%RH, 963 hPa	<b>TESTED BY</b>	Rex Huang

**ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M**

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	144.00	24.40 QP	43.50	-19.10	1.65 H	94	11.10	13.20
2	192.01	24.70 QP	43.50	-18.80	1.00 H	121	12.90	11.70
3	240.00	22.40 QP	46.00	-23.60	1.29 H	22	9.50	12.90
4	384.00	27.40 QP	46.00	-18.60	1.17 H	55	9.50	17.90
5	479.99	29.30 QP	46.00	-16.70	1.26 H	334	8.90	20.40
6	624.00	33.70 QP	46.00	-12.30	1.05 H	274	9.90	23.80

**ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M**

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	144.00	30.50 QP	43.50	-13.00	1.00 V	199	17.20	13.20
2	192.00	27.90 QP	43.50	-15.60	1.00 V	276	16.20	11.70
3	240.00	23.80 QP	46.00	-22.20	1.00 V	14	11.00	12.90
4	384.00	26.00 QP	46.00	-20.00	1.14 V	251	8.20	17.90
5	480.00	28.90 QP	46.00	-17.10	1.42 V	105	8.50	20.40
6	624.00	32.60 QP	46.00	-13.40	1.29 V	57	8.80	23.80

- REMARKS:**
1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB/m)
  2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
  3. The other emission levels were very low against the limit.
  4. Margin value = Emission level – Limit value.

## 4.7.7 TEST RESULTS (MODE A)

<b>EUT</b>	ThinkPad Bluetooth with Enhanced Data Rate	<b>MODEL</b>	J07H081
<b>CHANNEL</b>	Channel 0	<b>FREQUENCY RANGE</b>	1 ~25GHz
<b>INPUT POWER (SYSTEM)</b>	120Vac, 60 Hz	<b>DETECTOR FUNCTION</b>	Peak(PK) Average (AV)
<b>ENVIRONMENTAL CONDITIONS</b>	24 deg. C, 56%RH, 963 hPa	<b>TESTED BY</b>	Rex Huang

**ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M**

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2390.00	40.70 PK	74.00	-33.30	1.05 H	306	7.00	33.70
1	2390.00	10.70 AV	54.00	-43.30	1.05 H	306	-23.00	33.70
2	*2402.00	93.70 PK			1.05 H	306	63.90	29.80
2	*2402.00	63.70 AV			1.05 H	306	33.90	29.80
3	4804.00	54.40 PK	74.00	-19.60	1.09 H	260	19.40	35.00
3	4804.00	24.40 AV	54.00	-29.60	1.09 H	260	-10.60	35.00
4	7206.00	62.90 PK	74.00	-11.10	1.11 H	70	22.40	40.40
4	7206.00	32.90 AV	54.00	-21.10	1.11 H	70	-7.60	40.40

**ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M**

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2390.00	42.30 PK	74.00	-31.70	1.00 V	210	8.60	33.70
1	2390.00	21.30 AV	54.00	-32.70	1.00 V	210	-12.40	33.70
2	*2402.00	95.30 PK			1.00 V	210	65.50	29.80
2	*2402.00	65.30 AV			1.00 V	210	35.50	29.80
3	4804.00	53.40 PK	74.00	-20.60	1.06 V	298	18.40	35.00
3	4804.00	23.40 AV	54.00	-30.60	1.06 V	298	-11.60	35.00
4	7206.00	60.50 PK	74.00	-13.50	1.21 V	213	20.00	40.40
4	7206.00	30.50 AV	54.00	-23.50	1.21 V	213	-10.00	40.40

**REMARKS:**

1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB)
2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. “ \* ” : Fundamental frequency
6. The DH5 packet was the worse case duty cycle for a transmit dwell time on a channel, based upon bluetooth theory the transmitter is on 0.625\*5 per 247 ms per channel. Therefore, the duty cycle be equal to:  $20\log(3.125/100) = -30\text{dB}$
7. Average value = peak reading  $-20\log(\text{duty cycle})$

<b>EUT</b>	ThinkPad Bluetooth with Enhanced Data Rate	<b>MODEL</b>	J07H081
<b>CHANNEL</b>	Channel 39	<b>FREQUENCY RANGE</b>	1 ~25GHz
<b>INPUT POWER (SYSTEM)</b>	120Vac, 60 Hz	<b>DETECTOR FUNCTION</b>	Peak(PK) Average (AV)
<b>ENVIRONMENTAL CONDITIONS</b>	24 deg. C, 56%RH, 963 hPa	<b>TESTED BY</b>	Rex Huang

#### ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2441.00	94.70 PK			1.09 H	311	64.80	29.90
1	*2441.00	64.70 AV			1.09 H	311	34.80	29.90
2	4882.00	54.80 PK	74.00	-19.20	1.11 H	69	19.40	35.30
2	4882.00	24.80 AV	54.00	-29.20	1.11 H	69	-10.60	35.30
3	7323.00	63.70 PK	74.00	-10.30	1.20 H	60	23.00	40.70
3	7323.00	33.70 AV	54.00	-20.30	1.20 H	60	-7.00	40.70

#### ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2441.00	96.60 PK			1.16 V	222	66.70	29.90
1	*2441.00	66.60 AV			1.16 V	222	36.70	29.90
2	4882.00	54.00 PK	74.00	-20.00	1.14 V	273	18.60	35.30
2	4882.00	24.00 AV	54.00	-30.00	1.14 V	273	-11.40	35.30
3	7323.00	61.20 PK	74.00	-12.80	1.23 V	249	20.50	40.70
3	7323.00	31.20 AV	54.00	-22.80	1.23 V	249	-9.40	40.70

#### REMARKS:

1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB)
2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. “ \* ” : Fundamental frequency
6. The DH5 packet was the worse case duty cycle for a transmit dwell time on a channel, based upon bluetooth theory the transmitter is on 0.625\*5 per 247 ms per channel. Therefore, the duty cycle be equal to:  $20\log(3.125/100) = -30\text{dB}$
7. Average value = peak reading  $-20\log(\text{duty cycle})$



<b>EUT</b>	ThinkPad Bluetooth with Enhanced Data Rate	<b>MODEL</b>	J07H081
<b>CHANNEL</b>	Channel 78	<b>FREQUENCY RANGE</b>	1 ~25GHz
<b>INPUT POWER (SYSTEM)</b>	120Vac, 60 Hz	<b>DETECTOR FUNCTION</b>	Peak(PK) Average (AV)
<b>ENVIRONMENTAL CONDITIONS</b>	24 deg. C, 56%RH, 963 hPa	<b>TESTED BY</b>	Rex Huang

#### ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2480.00	95.40 PK			1.01 H	352	65.30	30.10
1	*2480.00	65.40 AV			1.01 H	352	35.30	30.10
2	2483.50	43.60 PK	74.00	-30.40	1.01 H	352	13.50	30.10
2	2483.50	13.60 AV	54.00	-40.40	1.01 H	352	-16.50	30.10
3	4960.00	57.30 PK	74.00	-16.70	1.07 H	238	21.60	35.70
3	4960.00	27.30 AV	54.00	-26.70	1.07 H	238	-8.40	35.70
4	7440.00	65.10 PK	74.00	-8.90	1.07 H	46	24.10	40.90
4	7440.00	35.10 AV	54.00	-18.90	1.07 H	46	-5.90	40.90

#### ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2480.00	97.30 PK			1.36 V	246	67.20	30.10
1	*2480.00	67.30 AV			1.36 V	246	37.20	30.10
2	2483.50	45.50 PK	74.00	-28.50	1.36 V	246	15.40	30.10
2	2483.50	15.50 AV	54.00	-38.50	1.36 V	246	-14.60	30.10
3	4960.00	55.30 PK	74.00	-18.70	1.20 V	50	19.60	35.70
3	4960.00	25.30 AV	54.00	-28.70	1.20 V	50	-10.40	35.70
4	7440.00	63.90 PK	74.00	-10.10	1.18 V	20	22.90	40.90
4	7440.00	33.90 AV	54.00	-20.10	1.18 V	20	-7.10	40.90

- REMARKS:**
1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB)
  2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
  3. The other emission levels were very low against the limit.
  4. Margin value = Emission level – Limit value.
  5. “ \* ” : Fundamental frequency
  6. The DH5 packet was the worse case duty cycle for a transmit dwell time on a channel, based upon bluetooth theory the transmitter is on 0.625\*5 per 247 ms per channel. Therefore, the duty cycle be equal to:  $20\log(3.125/100) = -30\text{dB}$
  7. Average value = peak reading  $-20\log(\text{duty cycle})$

## 4.7.8 TEST RESULTS (MODE C)

<b>EUT</b>	ThinkPad Bluetooth with Enhanced Data Rate	<b>MODEL</b>	J07H081
<b>CHANNEL</b>	Channel 0	<b>FREQUENCY RANGE</b>	1 ~25GHz
<b>INPUT POWER (SYSTEM)</b>	120Vac, 60 Hz	<b>DETECTOR FUNCTION</b>	Peak(PK) Average (AV)
<b>ENVIRONMENTAL CONDITIONS</b>	26 deg. C, 64%RH, 963 hPa	<b>TESTED BY</b>	Rex Huang

**ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M**

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2390.00	43.90 PK	74.00	-30.10	1.11 H	335	10.20	33.70
1	2390.00	13.90 AV	54.00	-40.10	1.11 H	335	-19.80	33.70
2	*2402.00	95.00 PK			1.11 H	335	65.20	29.80
2	*2402.00	65.00 AV			1.11 H	335	35.20	29.80
3	4804.00	56.50 PK	74.00	-17.50	1.16 H	317	21.50	35.00
3	4804.00	26.50 AV	54.00	-27.50	1.16 H	317	-8.50	35.00
4	7206.00	64.90 PK	74.00	-9.10	1.17 H	91	24.40	40.40
4	7206.00	34.90 AV	54.00	-19.10	1.17 H	91	-5.60	40.40

**ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M**

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2390.00	45.50 PK	74.00	-28.50	1.15 V	234	11.80	33.70
1	2390.00	15.50 AV	54.00	-38.50	1.15 V	234	-18.20	33.70
2	*2402.00	96.60 PK			1.15 V	234	66.80	29.80
2	*2402.00	66.60 AV			1.15 V	234	36.80	29.80
3	4804.00	55.30 PK	74.00	-18.70	1.17 V	312	20.30	35.00
3	4804.00	25.30 AV	54.00	-28.70	1.17 V	312	-9.70	35.00
4	7206.00	62.70 PK	74.00	-11.30	1.21 V	251	22.20	40.40
4	7206.00	32.70 AV	54.00	-21.30	1.21 V	251	-7.80	40.40

**REMARKS:**

1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB)
2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. “ \* ”: Fundamental frequency
6. The DH5 packet was the worse case duty cycle for a transmit dwell time on a channel, based upon bluetooth theory the transmitter is on 0.625\*5 per 247 ms per channel. Therefore, the duty cycle be equal to:  $20\log(3.125/100) = -30\text{dB}$
7. Average value = peak reading  $-20\log(\text{duty cycle})$

<b>EUT</b>	ThinkPad Bluetooth with Enhanced Data Rate	<b>MODEL</b>	J07H081
<b>CHANNEL</b>	Channel 39	<b>FREQUENCY RANGE</b>	1 ~25GHz
<b>INPUT POWER (SYSTEM)</b>	120Vac, 60 Hz	<b>DETECTOR FUNCTION</b>	Peak(PK) Average (AV)
<b>ENVIRONMENTAL CONDITIONS</b>	26 deg. C, 64%RH, 963 hPa	<b>TESTED BY</b>	Rex Huang

#### ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2441.00	95.50 PK			1.10 H	326	65.60	29.90
1	*2441.00	65.50 AV			1.10 H	326	35.60	29.90
2	4882.00	57.20 PK	74.00	-16.80	1.14 H	304	21.80	35.30
2	4882.00	27.20 AV	54.00	-26.80	1.14 H	304	-8.20	35.30
3	7323.00	65.60 PK	74.00	-8.40	1.22 H	72	24.90	40.70
3	7323.00	35.60 AV	54.00	-18.40	1.22 H	72	-5.10	40.70

#### ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2441.00	97.70 PK			1.24 V	238	67.80	29.90
1	*2441.00	67.70 AV			1.24 V	238	37.80	29.90
2	4882.00	56.00 PK	74.00	-18.00	1.15 V	284	20.60	35.30
2	4882.00	26.00 AV	54.00	-28.00	1.15 V	284	-9.40	35.30
3	7323.00	63.30 PK	74.00	-10.70	1.23 V	263	22.60	40.70
3	7323.00	33.30 AV	54.00	-20.70	1.23 V	263	-7.40	40.70

#### REMARKS:

1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB)
2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. “ \* ” : Fundamental frequency
6. The DH5 packet was the worse case duty cycle for a transmit dwell time on a channel, based upon bluetooth theory the transmitter is on 0.625\*5 per 247 ms per channel. Therefore, the duty cycle be equal to:  $20\log(3.125/100) = -30\text{dB}$
7. Average value = peak reading  $-20\log(\text{duty cycle})$

<b>EUT</b>	ThinkPad Bluetooth with Enhanced Data Rate	<b>MODEL</b>	J07H081
<b>CHANNEL</b>	Channel 78	<b>FREQUENCY RANGE</b>	1 ~25GHz
<b>INPUT POWER (SYSTEM)</b>	120Vac, 60 Hz	<b>DETECTOR FUNCTION</b>	Peak(PK) Average (AV)
<b>ENVIRONMENTAL CONDITIONS</b>	26 deg. C, 64%RH, 963 hPa	<b>TESTED BY</b>	Rex Huang

#### ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2480.00	96.20 PK			1.07 H	329	66.10	30.10
1	*2480.00	66.20 AV			1.07 H	329	36.10	30.10
2	2483.50	45.50 PK	74.00	-28.50	1.07 H	329	15.40	30.10
2	2483.50	15.40 AV	54.00	-38.60	1.07 H	329	-14.70	30.10
3	4960.00	58.80 PK	74.00	-15.20	1.18 H	315	23.10	35.70
3	4960.00	28.80 AV	54.00	-25.20	1.18 H	315	-6.90	35.70
4	7440.00	66.60 PK	74.00	-7.40	1.09 H	63	25.60	40.90
4	7440.00	36.60 AV	54.00	-17.40	1.09 H	63	-4.40	40.90

#### ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2480.00	98.20 PK			1.29 V	251	68.10	30.10
1	*2480.00	68.20 AV			1.29 V	251	38.10	30.10
2	2483.50	47.50 PK	74.00	-26.50	1.29 V	251	17.40	30.10
2	2483.50	17.50 AV	54.00	-36.50	1.29 V	251	-12.60	30.10
3	4960.00	56.70 PK	74.00	-17.30	1.16 V	288	21.00	35.70
3	4960.00	26.70 AV	54.00	-27.30	1.16 V	288	-9.00	35.70
4	7440.00	65.30 PK	74.00	-8.70	1.27 V	232	24.30	40.90
4	7440.00	35.30 AV	54.00	-18.70	1.27 V	232	-5.70	40.90

- REMARKS:**
1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB)
  2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
  3. The other emission levels were very low against the limit.
  4. Margin value = Emission level – Limit value.
  5. “ \* ” : Fundamental frequency
  6. The DH5 packet was the worse case duty cycle for a transmit dwell time on a channel, based upon bluetooth theory the transmitter is on 0.625\*5 per 247 ms per channel. Therefore, the duty cycle be equal to:  $20\log(3.125/100) = -30\text{dB}$
  7. Average value = peak reading  $-20\log(\text{duty cycle})$

## 4.8 BAND EDGES MEASUREMENT

### 4.8.1 LIMITS OF BAND EDGES MEASUREMENT

Below -20dB of the highest emission level of operating band (in 100KHz RBW).

### 4.8.2 TEST INSTRUMENTS

Description & Manufacturer	Model No.	Serial No.	Calibrated Until
R&S SPECTRUM ANALYZER	FSP40	100036	Nov. 23, 2005

**NOTE:**

- 1.The measurement uncertainty is less than +/- 2.6dB, which is calculated as per the NAMAS document NIS81.
- 2.The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

### 4.8.3 TEST PROCEDURE

The transmitter output was connected to the spectrum analyzer via a low lose cable. Set both RBW and VBW of spectrum analyzer to 100 kHz with suitable frequency span including 100 MHz bandwidth from band edge. The band edges was measured and recorded.

### 4.8.4 DEVIATION FROM TEST STANDARD

No deviation

### 4.8.5 EUT OPERATING CONDITION

The software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel frequencies individually.

#### 4.8.6 TEST RESULTS (MODE A)

The spectrum plots are attached on the following 2 pages. D2 line indicates the highest level, D1 line indicates the 20dB offset below D2. It shows compliance with the requirement in part 15.247(C).

Note - The delta method is only used up to 2 MHz away from the restricted bandage, The radiated emissions which located in other restricted frequency band, the result, please refer to 4.2.

**NOTE (Peak):**



The band edge emission plot on the following first page show 53.04dB delta between carrier maximum power and local maximum emission in restrict band (2.3900GHz). The emission of carrier strength list in the test result of channel 0 at the item 4.2 is 95.30dBuV/m, so the maximum field strength in restrict band is  $95.30 - 53.04 = 42.26$ dBuV/m which is under 74 dBuV/m limit.

The band edge emission plot on the following first page shows 51.69dB delta between carrier maximum power and local maximum emission in restrict band (2.4835GHz). The emission of carrier strength list in the test result of channel 78 at the item 4.2 is 97.30dBuV/m, so the maximum field strength in restrict band is  $97.30 - 51.69 = 45.61$ dBuV/m which is under 74 dBuV/m limit.

**NOTE (Average):**

The band edge emission plot on the following first page shows 53.04dB delta between carrier maximum power and local maximum emission in restrict band (2.3900GHz). The emission of carrier strength list in the test result of channel 0 at the item 4.2 is 65.30dBuV/m, so the maximum field strength in restrict band is  $65.30 - 53.04 = 12.26$ dBuV/m which is under 54 dBuV/m limit.

The band edge emission plot on the following first page shows 51.69dB delta between carrier maximum power and local maximum emission in restrict band (2.4835GHz). The emission of carrier strength list in the test result of channel 78 at the item 4.2 is 67.30dBuV/m, so the maximum field strength in restrict band is  $67.30 - 51.69 = 15.61$ dBuV/m which is under 54 dBuV/m limit.



#### 4.8.7 TEST RESULTS (MODE C)

The spectrum plots are attached on the following 2 pages. D2 line indicates the highest level, D1 line indicates the 20dB offset below D2. It shows compliance with the requirement in part 15.247(C).

Note - The delta method is only used up to 2 MHz away from the restricted bandage, The radiated emissions which located in other restricted frequency band, the result, please refer to 4.2.

**NOTE (Peak):**

The band edge emission plot on the following first page show 51.13dB delta between carrier maximum power and local maximum emission in restrict band (2.3900GHz). The emission of carrier strength list in the test result of channel 0 at the item 4.2 is 96.60dBuV/m, so the maximum field strength in restrict band is  $96.60 - 51.13 = 45.47$  dBuV/m which is under 74 dBuV/m limit.



The band edge emission plot on the following first page shows 50.55dB delta between carrier maximum power and local maximum emission in restrict band (2.4835GHz). The emission of carrier strength list in the test result of channel 78 at the item 4.2 is 98.20dBuV/m, so the maximum field strength in restrict band is  $98.20 - 50.55 = 47.65$  dBuV/m which is under 74 dBuV/m limit.

**NOTE (Average):**

The band edge emission plot on the following first page shows 51.13dB delta between carrier maximum power and local maximum emission in restrict band (2.3900GHz). The emission of carrier strength list in the test result of channel 0 at the item 4.2 is 66.60dBuV/m, so the maximum field strength in restrict band is  $66.60 - 51.13 = 15.47$  dBuV/m which is under 54 dBuV/m limit.

The band edge emission plot on the following first page shows 50.55dB delta between carrier maximum power and local maximum emission in restrict band (2.4835GHz). The emission of carrier strength list in the test result of channel 78 at the item 4.2 is 68.20dBuV/m, so the maximum field strength in restrict band is  $68.20 - 50.55 = 17.65$  dBuV/m which is under 54 dBuV/m limit.





## **4.9 ANTENNA REQUIREMENT**

### **4.9.1 STANDARD APPLICABLE**

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

And according to FCC 47 CFR Section 15.247 (b), if transmitting antennas of directional gain greater than 6 dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

### **4.9.2 ANTENNA CONNECTED CONSTRUCTION**

The antenna used in this product is Chip antenna without connector. The maximum Gain of the antenna is 2 dBi.

## 5 PHOTOGRAPHS OF THE TEST CONFIGURATION

### CONDUCTED EMISSION TEST





### RADIATED EMISSION TEST (X axis)









### RADIATED EMISSION TEST (Y axis)








### RADIATED EMISSION TEST (Z axis)





## 6 INFORMATION ON THE TESTING LABORATORIES

We, ADT Corp., were founded in 1988 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are accredited and approved by the following approval agencies according to ISO/IEC 17025:

<b>USA</b>	FCC, NVLAP, UL, A2LA
<b>Germany</b>	TUV Rheinland
<b>Japan</b>	VCCI
<b>Norway</b>	NEMKO
<b>Canada</b>	INDUSTRY CANADA, CSA
<b>R.O.C.</b>	CNLA, BSMI, DGT
<b>Netherlands</b>	Telefication
<b>Singapore</b>	PSB, GOST-ASIA (MOU)
<b>Russia</b>	CERTIS (MOU)

Copies of accreditation certificates of our laboratories obtained from approval agencies can be downloaded from our web site: [www.adt.com.tw/index.5/phtml](http://www.adt.com.tw/index.5/phtml).

If you have any comments, please feel free to contact us at the following:

**Linko EMC/RF Lab:**

Tel: 886-2-26052180

Fax: 886-2-26052943

**Hsin Chu EMC/RF Lab:**

Tel: 886-3-5935343

Fax: 886-3-5935342

**Hwa Ya EMC/RF/Safety/Telecom Lab:**

Tel: 886-3-3183232

Fax: 886-3-3185050

**Email:** [service@adt.com.tw](mailto:service@adt.com.tw)

**Web Site:** [www.adt.com.tw](http://www.adt.com.tw)

The address and road map of all our labs can be found in our web site also.