

# Safety Human Exposure

## 1.1 Radio Frequency Exposure Compliance

### 1.1.1 Electromagnetic Fields

#### RESULT:

Pass

Test item	: DOMYOS Fitness Treadmill
Identification / Type No.	: RUN100E 110V US CA
Test standard	: CFR47 FCC Part 2: Section 2.1093 CFR47 FCC Part 1: Section 1.1310 FCC KDB Publication 447498 D04 V01 RSS-102 Issue 5 February 2021

#### ➤ Product Classification

This device defined as a transmitting device designed to be used in other than fixed locations and to generally be used in such a way that the RF source's radiating structure(s) is/are within 20 centimeters of the body of the user.

Max -6.50 dBi

#### ➤ Radio Frequency Exposure Limit

For FCC:

According to FCC KDB # 447498 D04 V01, Clause Appendix B.4 and 1.1307(b)(3)(i)(B)

The available maximum time-averaged power or effective radiated power (ERP), whichever is greater, is less than or equal to the threshold  $P_{th}$  (mW) described in the following formula. This method shall only be used at separation distances (cm) from 0.5 centimeters to 40 centimeters and at frequencies from 0.3 GHz to 6 GHz (inclusive).  $P_{th}$  is given by:

$$P_{th} \text{ (mW)} = \begin{cases} ERP_{20 \text{ cm}} (d/20 \text{ cm})^x & d \leq 20 \text{ cm} \\ ERP_{20 \text{ cm}} & 20 \text{ cm} < d \leq 40 \text{ cm} \end{cases}$$

Where

$$x = -\log_{10} \left( \frac{60}{ERP_{20 \text{ cm}} \sqrt{f}} \right) \text{ and } f \text{ is in GHz;}$$

and

$$ERP_{20 \text{ cm}} \text{ (mW)} = \begin{cases} 2040f & 0.3 \text{ GHz} \leq f < 1.5 \text{ GHz} \\ 3060 & 1.5 \text{ GHz} \leq f \leq 6 \text{ GHz} \end{cases}$$

$d$  = the separation distance (cm);

For IC:

**Table 1: SAR evaluation – Exemption limits for routine evaluation based on frequency and separation distance<sup>4,5</sup>**

Frequency (MHz)	Exemption Limits (mW)				
	At separation distance of ≤5 mm	At separation distance of 10 mm	At separation distance of 15 mm	At separation distance of 20 mm	At separation distance of 25 mm
≤300	71 mW	101 mW	132 mW	162 mW	193 mW
450	52 mW	70 mW	88 mW	106 mW	123 mW
835	17 mW	30 mW	42 mW	55 mW	67 mW
1900	7 mW	10 mW	18 mW	34 mW	60 mW
2450	4 mW	7 mW	15 mW	30 mW	52 mW
3500	2 mW	6 mW	16 mW	32 mW	55 mW
5800	1 mW	6 mW	15 mW	27 mW	41 mW

Frequency (MHz)	Exemption Limits (mW)				
	At separation distance of 30 mm	At separation distance of 35 mm	At separation distance of 40 mm	At separation distance of 45 mm	At separation distance of ≥50 mm
≤300	223 mW	254 mW	284 mW	315 mW	345 mW
450	141 mW	159 mW	177 mW	195 mW	213 mW
835	80 mW	92 mW	105 mW	117 mW	130 mW
1900	99 mW	153 mW	225 mW	316 mW	431 mW
2450	83 mW	123 mW	173 mW	235 mW	309 mW
3500	86 mW	124 mW	170 mW	225 mW	290 mW
5800	56 mW	71 mW	85 mW	97 mW	106 mW

If the operating frequency of the device is between two frequencies located in Table 1, linear interpolation shall be applied for the applicable separation distance.

➤ **EUT RF Exposure Evaluation**

**a. Evaluation for Standalone Transmission Operation**

For FCC

Mode	Freq. [GHz]	Maximum Conducted Peak Output Power [dBm]	Antenna Gain [dBi]	E.I.R.P [dBm]	Maximum Conducted Peak Output Power [mW]	d [cm]	ERP <sub>20cm</sub> [mW]	P <sub>th</sub> [mW]
Bluetooth Classic (EW-BLED-26)	2.480	-0.3	-6.5	-6.8	0.93	0.5	3060	2.72
Bluetooth Low Energy (EW-BLED-22)	2.402	2.3	-6.5	-4.2	1.70	0.5	3060	2.78

For IC

Mode	Maximum Conducted Peak Output Power [dBm]	Antenna Gain [dBi]	E.I.R.P [dBm]	Maximum Conducted Peak Output Power [mW]	Distance [mm]	Limit [mW]
Bluetooth Classic (EW-BLED-26)	-0.3	-6.5	-6.8	0.93	5	4.62
Bluetooth Low Energy (EW-BLED-22)	2.3	-6.5	-4.2	1.70	5	3.94

Note:

1. Bluetooth(EW-BLED-26) RF Output Power refer to test report CN22TG87 001
2. Bluetooth(EW-BLED-22) RF Output Power refer to test report CN22Y9WY 001

**b. Evaluation for Simultaneous Transmission Operation**

According to FCC KDB # 447498 D04 V01, Clause 2.2.2 and RSS-102 Issue 5, March 2015, Clause 3.1.2 This case is described in detail in § 1.1307(b)(3)(ii)(B) and covers the situations where both SAR-based and MPE-based exemption may be considered for test exemption in fixed, mobile, or portable device exposure conditions. For these cases, a device with multiple RF sources transmitting simultaneously will be considered an *RF exempt device* if the condition of Formula (1) is satisfied.

$$\sum_{i=1}^a \frac{P_i}{P_{th,i}} + \sum_{j=1}^b \frac{ERP_j}{ERP_{th,j}} + \sum_{k=1}^c \frac{Evaluated_k}{Exposure Limit_k} \leq 1 \quad (1)$$

Simultaneous Transmission Scenarios

For FCC

Mode	P/ P <sub>th</sub>		SUM	Limit
Bluetooth Classic+ Bluetooth Low Energy	EW-BLED-26	EW-BLED-22	0.95	1
	0.34	0.61		

For IC

Mode	P/ P <sub>th</sub>		SUM	Limit
Bluetooth Classic+ Bluetooth Low Energy	EW-BLED-26	EW-BLED-22	0.63	1
	0.20	0.43		

➤ **Conclusion**

The distance 0.5cm was used to determine the SAR test exclusion. But the actually distance in normal using is larger than 0.5cm. So, the device is excluded for SAR test and complies with the FCC and IC exposure requirements.