



TEST REPORT

Eurofins KCTL Co.,Ltd. 65, Sinwon-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16677, Korea TEL: 82-31-285-0894 FAX: 82-505-299-8311 www.kctl.co.kr		Report No.: KR23-SRF0075 Page (1) of (14)	KCTL
--	--	---	-------------

1. Client

- Name : SUPREMA INC
- Address : 17F-5, Parkview officetower,, 248, Jeongjail-ro, Bundang-gu, Seongnam-si, Gyeonggi-do 13554 Korea (Republic Of)
- Date of Receipt : 2022-11-22

2. Use of Report : FCC Class II permissive change

3. Name of Product / Model : FaceStation F2 / FSF2-ODB

4. Manufacturer / Country of Origin : SUPREMA INC / Korea

5. FCC ID : TKWFSF2-ODB

6. IC Certificate No. : 23080-FSF2ODB

7. Date of Test : 2023-01-27 to 2023-02-17

8. Location of Test : ☒ Permanent Testing Lab ☐ On Site Testing
 (Address:65, Sinwon-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16677, Korea)
 FCC Part 15 Subpart C, 15.209

9. Test method used : RSS-210 Issue 10 April 2020
 RSS-Gen Issue 5 February 2021


10. Test Result : Refer to the test result in the test report

Affirmation	Tested by	Technical Manager
	Name : Eunseong Lim (Signature)	Name : Heesu Ahn (Signature)

2023-03-06

Eurofins KCTL Co.,Ltd.

As a test result of the sample which was submitted from the client, this report does not guarantee the whole product quality. This test report should not be used and copied without a written agreement by Eurofins KCTL Co.,Ltd.

Eurofins KCTL Co.,Ltd. 65, Sinwon-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16677, Korea TEL: 82-31-285-0894 FAX: 82-505-299-8311 www.kctl.co.kr	Report No.: KR23-SRF0075 Page (2) of (14)	
--	--	---

REPORT REVISION HISTORY

Date	Revision	Page No
2023-03-06	Originally issued	-

This report shall not be reproduced except in full, without the written approval of Eurofins KCTL Co.,Ltd. This document may be altered or revised by Eurofins KCTL Co.,Ltd. personnel only, and shall be noted in the revision section of the document. Any alteration of this document not carried out by Eurofins KCTL Co.,Ltd. will constitute fraud and shall nullify the document. This test report is a general report that does not use the KOLAS accreditation mark and is not related to KS Q ISO/IEC 17025 and KOLAS accreditation.

General remarks for test reports

Statement concerning the uncertainty of the measurement systems used for the tests

(may be required by the product standard or client)

☐ Internal procedure used for type testing through which traceability of the measuring uncertainty has been established:

Procedure number, issue date and title:

Calculations leading to the reported values are on file with the testing laboratory that conducted the testing.

☒ Statement not required by the standard or client used for type testing

CONTENTS

1.	General information	4
2.	Device information	4
2.1.	Information about derivative model	5
2.2.	Frequency/channel operations	5
3.	Antenna requirement	6
4.	Summary of tests	7
5.	Measurement uncertainty	8
6.	Test results	9
6.1.	Field Strength of Fundamental and Spurious Emission	9
7.	Measurement equipment	14

2.1. Information about derivative model

The difference between basic model and derivative models is:

- Radio Hardware such as circuits and electrical components and Software are the same.

Components	Basic model	Derivative model
LED board	FSF2_WHITE-LED_PS1	FSF2_WHITE-LED_V02
IR LED board	FSF2_IR LED_PS1	FSF2_IR LED_V01
Main board	FSF2_MAIN_PS1	FSF2_MAIN_V04
RF board	FSF2_ODB-RFBD_DB_PS1	FSF2-ODB-RFBD-V01
USB board	FSF2_ODB_USB_PS1	FSF2_ODB_USB_V01
Camera 1 module	SV-SUE1-ET020S	SV-SUE1-ET020S
Camera 2 module	SV-SUE1L-ET020S	SV-SUE1L-ET020S
Finger print module	SFMSLIM-MAIN_02A	SFMSLIM-MAIN_V02A


2.2. Frequency/channel operations

This device contains the following capabilities:

NFC, RFID(125 kHz), Bluetooth Low Energy

Ch.	Frequency (kHz)
01	125

Table 2.2.1. RFID

<p>Eurofins KCTL Co.,Ltd. 65, Sinwon-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16677, Korea TEL: 82-31-285-0894 FAX: 82-505-299-8311 www.kctl.co.kr</p>	<p>Report No.: KR23-SRF0075 Page (6) of (14)</p>	
---	--	---

3. Antenna requirement

Requirement of FCC part section 15.203:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.

Requirement of RSS-Gen Section 6.8:

The applicant for equipment certification shall provide a list of all antenna types that may be used with the transmitter, where applicable (i.e. for transmitters with detachable antenna), indicating the maximum permissible antenna gain (in dBi) and the required impedance for each antenna. The test report shall demonstrate the compliance of the transmitter with the limit for maximum equivalent isotropically radiated power (e.i.r.p.) specified in the applicable RSS, when the transmitter is equipped with any antenna type, selected from this list.

For expediting the testing, measurements may be performed using only the antenna with highest gain of each combination of transmitter and antenna type, with the transmitter output power set at the maximum level. However, the transmitter shall comply with the applicable requirements under all operational conditions and when in combination with any type of antenna from the list provided in the test report (and in the notice to be included in the user manual, provided below).

When measurements at the antenna port are used to determine the RF output power, the effective gain of the device's antenna shall be stated, based on a measurement or on data from the antenna's manufacturer.

The test report shall state the RF power, output power setting and spurious emission measurements with each antenna type that is used with the transmitter being tested.

Immediately following the above notice, the manufacturer shall provide a list of all antenna types which can be used with the transmitter, indicating the maximum permissible antenna gain (in dBi) and the required impedance for each antenna type.

-The transmitter has permanently attached Coil antenna (internal antenna) on board.

4. Summary of tests

FCC Part section(s)	IC Rule reference	Parameter	Test results
15.209(a)	RSS-210 Issue 9 (8.9)	Field Strength of Fundamental and Spurious Emission	Pass
2.1049	-	20dB Bandwidth	N/T ^(Note1)
-	RSS-Gen Issue 5 (6.7)	Occupied Bandwidth	N/T ^(Note1)
15.203	RSS-Gen Issue 5 (6.8)	Antenna requirement	Pass
15.207(a)	RSS-Gen Issue 5 (8.8)	AC Conducted Emission	N/A ^(Note2)

Notes: (N/T: Not Tested, N/A: Not Applicable)

- This is a FCC Class II Permissive Change report.
These test items were performed. (FCC ID: TKWFSF2-ODB,
Test Report No. KR20-SRF0240-E issued on 21, October, 2020 by KCTL Inc.
Test Report No. KR21-SRF0002-A issued on 28, January, 2021 by KCTL Inc.)
- This test is not applicable because the EUT only connects DC power line.
- All modes of operation and data rates were investigated. The test results shown in the following sections represent the worst case emissions.
- These tests were performed other than open field site, adequate comparison measurements were confirmed against 30 m open field site. Therefore sufficient tests were made to demonstrate that the alternative site produces results that correlate with the ones of tests made in an open field based on KDB 414788.
- The fundamental of the EUT was investigated in three orthogonal orientations X, Y and Z. It was determined that **Y** orientation was worst-case orientation. Therefore, all final radiated testing was performed with the EUT in **Y** orientation.
- The test procedure(s) in this report were performed in accordance as following.
 - ◆ ANSI C63.10-2013
- The measurement facility is compliant with the test site requirements specified in ANSI C63.4-2014.
- The radiated test was performed with and without passive tag. The test results shown in the following sections represent the worst case emissions.
 - ◆ Worst Case : Without passive tag

5. Measurement uncertainty

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI C63.10-2013.

All measurement uncertainty values are shown with a coverage factor of $k=2$ to indicated a 95 % level of confidence. The measurement data shown herein meets or exceeds the U_{CISPR} measurement uncertainty values specified in CISPR 16-4-2 and thus, can be compared directly to specified limits to determine compliance.

Parameter	Expanded uncertainty (\pm)	
Radiated spurious emissions	9 kHz ~ 30 MHz	2.3 dB
	30 MHz ~ 1 000 MHz	2.5 dB
	1 000 MHz ~ 18 000 MHz	4.7 dB
	Above 18 000 MHz	4.8 dB
Conducted Emissions	9 kHz ~ 150 kHz	0.9 dB
	150 kHz ~ 30 MHz	1.3 dB




6. Test results

6.1. Field Strength of Fundamental and Spurious Emission

Test setup

The diagram below shows the test setup that is utilized to make the measurements for emission from 9 kHz to 30 MHz Emissions



Limit FCC

According to section 15.209(a), RSS-Gen(8.9) Except as provided elsewhere in this subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

Frequency (MHz)	Field strength ($\mu V/m$)	Measurement distance (m)
0.009 - 0.490	2 400/F(kHz)	300
0.490 - 1.705	24 000/F(kHz)	30
1.705 - 30	30	30
30 - 88	100**	3
88 - 216	150**	3
216 - 960	200**	3
Above 960	500	3

**Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this section shall not be located in the frequency bands 54–72 MHz, 76–88 MHz, 174–216 MHz or 470–806 MHz. However, operation within these frequency bands is permitted under other sections of this part, e.g., Section 15.231 and 15.241.

IC

According to section RSS-Gen(8.9), except where otherwise indicated in the applicable RSS, radiated emissions shall comply with the field strength limits shown in table 5 and table 6. Additionally, the level of any transmitter unwanted emission shall not exceed the level of the transmitter's fundamental emission.

Table 5 – General field strength limits at frequencies above 30 MHz

Frequency (MHz)	Field strength (µV/m at 3 m)
30 – 88	100
88 – 216	150
216 – 960	200
Above 960	500

Table 6 – General field strength limits at frequencies below 30 MHz

Frequency	Magnetic field strength (H-Field) (µA/m)	Measurement distance (m)
9 - 490 kHz ¹	6.37/F (F in kHz)	300
490 - 1705 kHz	63.7/F (F in kHz)	30
1.705 - 30 MHz	0.08	30

Note 1: The emission limits for the ranges 9-90 kHz and 110-490 kHz are based on measurements employing a linear average detector.


Test procedure

ANSI C63.10-2013

Test settings

Test Procedures for emission from 9 kHz to 30 MHz

- The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter anechoic chamber test site. The table was rotated 360 degrees to determine the position of the highest radiation.
- Then antenna is a loop antenna is fixed at one meter above the ground to determine the maximum value of the field strength. Both parallel and perpendicular of the antenna are set to make the measurement.
- For each suspected emission, the EUT was arranged to its worst case and then the table was turned from 0 degrees to 360 degrees to find the maximum reading.
- The test-receiver system was set to peak and average detect function and specified bandwidth with maximum hold mode.
- Below 30 MHz frequency range, all orientations about parallel, perpendicular, and ground-parallel were investigated then reported and the worse orientations of Face-on and Face-off were set for final test.
 - Face-on = Parallel, Face-off = Perpendicular

Eurofins KCTL Co.,Ltd. 65, Sinwon-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16677, Korea TEL: 82-31-285-0894 FAX: 82-505-299-8311 www.kctl.co.kr	Report No.: KR23-SRF0075 Page (11) of (14)	
--	--	---

Notes:

1. $f < 30$ MHz, extrapolation factor of 40 dB/decade of distance. $F_d = 40 \log(D_m/D_s)$

Where:

F_d = Distance factor in dB

D_m = Measurement distance in meters

D_s = Specification distance in meters

2. The test measurement distance is 3 meter

3. Limit (dB(μ V/m)) =
- | | |
|----------------------------|---|
| For 0.009 MHz - 0.490 MHz, | $20 \cdot \log(2\,400/F(\text{kHz}))$ dB(μ V/m) |
| For 0.490 MHz - 1.705 MHz, | $20 \cdot \log(24\,000/F(\text{kHz}))$ dB(μ V/m) |
| For 1.705 MHz - 30 MHz, | $20 \cdot \log(30) = 29.54$ dB(μ V/m) |



Test results

[DC 12 V]

Radiated Emissions Fundamental & 9 kHz to 30 MHz

[Face-on]

Frequency	Reading	Detector Mode	Ant. Factor	Amp. + Cable	Distance factor	Factor	Result	Limit	Margin
(MHz)	(dB(μV))		(dB)	(dB)	(dB)	(dB)	(dB(μV/m))	(dB(μV/m))	(dB)
0.129	98.40	PK	19.90	-32.43	-80.00	-92.53	5.87	45.67	39.80
0.129	93.10	AV	19.90	-32.43	-80.00	-92.53	0.57	25.39	24.82
0.389	61.50	AV	19.90	-32.39	-80.00	-92.49	-30.99	15.81	46.80
0.646	52.30	QP	19.90	-32.33	-40.00	-52.43	-0.13	31.40	31.53

[Face-off]

Frequency	Reading	Detector Mode	Ant. Factor	Amp. + Cable	Distance factor	Factor	Result	Limit	Margin
(MHz)	(dB(μV))		(dB)	(dB)	(dB)	(dB)	(dB(μV/m))	(dB(μV/m))	(dB)
0.129	95.20	PK	19.90	-32.43	-80.00	-92.53	2.67	25.39	22.72
0.129	89.80	AV	19.90	-32.43	-80.00	-92.53	-2.73	25.39	28.12
0.389	58.70	AV	19.90	-32.39	-80.00	-92.49	-33.79	15.81	49.60
0.646	48.70	QP	19.90	-32.33	-40.00	-52.43	-3.73	31.40	35.13


Note.

¹⁾ Factor(dB) = Antenna Factor + Amp. Gain + Cable Loss + distance factor(dB)

²⁾ -80 is distance factor = $40 \cdot \log(3/300)$, -40 is distance factor = $40 \cdot \log(3/30)$

³⁾ The limits in CFR 47, Part 15, Subpart C, paragraph 15.209 (a), are identical to those in RSS-GEN Section 8.9, Table 6, since the measurements are performed in terms of magnetic field strength and converted to electric field strength levels (as reported in the table) using the free space impedance of 377Ω .

For example, the measurement frequency X kHz resulted in a level of Y dBμV/m, which is equivalent to $Y - 51.5 = Z$ dBμA/m, which has the same margin, W dB, to the corresponding RSS-GEN Table 6 limit as it has to the 15.209(a) limit



[DC 24 V]
Radiated Emissions Fundamental & 9 kHz to 30 MHz
[Face-on]


Frequency	Reading	Detector Mode	Ant. Factor	Amp. + Cable	Distance factor	Factor	Result	Limit	Margin
(MHz)	(dB(μV))		(dB)	(dB)	(dB)	(dB)	(dB(μV/m))	(dB(μV/m))	(dB)
0.129	100.70	PK	19.90	-32.43	-80.00	-92.53	8.17	45.67	37.50
0.129	95.40	AV	19.90	-32.43	-80.00	-92.53	2.87	25.39	22.52
0.251	68.20	AV	19.90	-32.42	-80.00	-92.52	-24.32	19.61	43.93
0.646	52.10	QP	19.90	-32.33	-40.00	-52.43	-0.33	31.40	31.73

[Face-off]

Frequency	Reading	Detector Mode	Ant. Factor	Amp. + Cable	Distance factor	Factor	Result	Limit	Margin
(MHz)	(dB(μV))		(dB)	(dB)	(dB)	(dB)	(dB(μV/m))	(dB(μV/m))	(dB)
0.129	97.00	PK	19.90	-32.43	-80.00	-92.53	4.47	25.39	20.92
0.129	91.70	AV	19.90	-32.43	-80.00	-92.53	-0.83	25.39	26.22
0.378	57.90	AV	19.90	-32.39	-80.00	-92.49	-34.59	16.05	50.64
0.646	47.70	QP	19.90	-32.33	-40.00	-52.43	-4.73	31.40	36.13

Note.

- Factor(dB) = Antenna Factor + Amp. Gain + Cable Loss + distance factor(dB)
- 80 is distance factor = $40 \cdot \log(3/300)$, -40 is distance factor = $40 \cdot \log(3/30)$
- The limits in CFR 47, Part 15, Subpart C, paragraph 15.209 (a), are identical to those in RSS-GEN Section 8.9, Table 6, since the measurements are performed in terms of magnetic field strength and converted to electric field strength levels (as reported in the table) using the free space impedance of 377Ω .
 For example, the measurement frequency X kHz resulted in a level of Y dBμV/m, which is equivalent to $Y - 51.5 = Z$ dBμA/m, which has the same margin, W dB, to the corresponding RSS-GEN Table 6 limit as it has to the 15.209(a) limit



7. Measurement equipment

Equipment Name	Manufacturer	Model No.	Serial No.	Next Cal. Date
Vector Signal Generator	R&S	SMBV100A	257566	23.07.04
Signal Generator	R&S	SMB100A	176206	24.01.19
Spectrum Analyzer	R&S	FSV30	100914	23.09.14
DC Power Supply	AGILENT	E3632A	MY40008800	23.07.11
EMI TEST RECEIVER	R&S	ESCI7	100732	*24.03.03
Amplifier	SONOMA INSTRUMENT	310N	300314	24.01.19
Bi-Log Antenna	TESEQ	CBL 6112D	62438	24.08.24
LOOP Antenna	R&S	HFH2-Z2	100355	24.08.10
ATTENUATOR	KEYSIGHT	8491B-6dB	MY39271082	24.04.27
Turn Table	Innco Systems	CO3000	1175/45850319/P	-
Antenna Mast	Innco Systems	MA4000-EP	303	-

*This test was performed prior to calibration.

End of test report