August 25, 2005

ITPD-05-F008A: BT Part 15C / DSS / EA330631 ITPD-05-F008B: WLAN Part 15C / DTS<sup>1</sup>/ EA434626

ITPD-05-F008C: EGPRS Parts 22H, 24E / PCE-PCS / EA906879

Federal Communications Commission 7435 Oakland Mills Road Columbia, MD 21046 USA

Subject:

Authority to Act as FCC Agent and Request for Confidentiality for

Professional Handheld Computer, Model CF-P2mk1 with Alps BT, Sychip WLAN and Siemens EGPRS

FCC Certification for FCC ID: ACJ9TGCF-P21

## To Whom It May Concern:

On behalf of Panasonic Corporation of North America, we herby authorize PCTEST Engineering Laboratory, Inc., to act on our behalf in matters relating to FCC equipment authorization, including the signing of documents relating to these matters. Any and all acts carried out by PCTEST on our behalf shall have the same effect as acts of our own.

This project represents Handheld Computer, Model CF-P2 Series, which will contain three transmitters to be marketed under FCC ID: ACJ9TGCF-P21. This PC combination contains: (1) AC Adaptor Model EB-CA370; (2) Intel Bulverde CPU, type PXA270 at 312 MHz; (3) Alps Blue Tooth Module and Daughter Board Model UGXZ1-116B with Part 15C operation within 2402~2480 MHz at 18.2 mW; (4) Sychip WLAN(b) Module, Model WLAN6065EBC2-HL-TR-01 with Part 15C operation within 2412~2462 MHz at 33.2 mW; and (5) Siemens EGPRS Module, Model MC56 with Part 22H operation within 824.2~848.8 MHz at 1.359 watts ERP (GSM850); and Part 24E operation within 1850.2~1909.8 MHz at 1.604 watts EIRP (GSM1900).

The highest measured SAR values were: (1) Part 15C WLAN Body SAR at 1.5 cm spacing was 0.21 W/kg; (2) Part 22H Head SAR at zero spacing was 0.35 W/kg; (3) Part 22H Body SAR at 1.5 cm spacing was 1.16 W/kg; (4) Part 24E Head SAR at zero spacing was 0.28 W/kg; (3) Part 24E Red SAR at 1.5 cm spacing was 0.65 W/kg;

(4) Part 24E Head SAR at zero spacing was 0.38 W/kg; and (5) Part 24E Body SAR at 1.5 cm spacing was 0.65 W/kg.

This PC contains the 3 Inverter F-type antennas with antenna gains of BT with -1.10 dB, WLAN TX//RX with 0.62 dBi; and EGPRS with 1.55 dBi. This PC may be used while held-to-face or while mounted in police belt-worn leather carrying case, which will not contain any metallic parts and will provide minimum 1.5 cm spacing. The optional following optional parts are not yet available and will be tested and reported under future Class II Permissive Change: (1) police belt-worn leather carrying case; (2) headset with unique connector; and (3) car mounter with external GSM/EGPRS antenna connection for professional installation.

In accordance with provisions of Section 0.457(d) of the Commission's Rules and Section 552(b)(4) of the Freedom of Information Act, we request confidentiality for transmitters exhibits for Operation Description, Parts Lists and Tune-Up Procedure, Block Diagram(s) and Schematic Diagram(s). The BT and WLAN transmitters are not user adjustable and do not have a Tune-Up Procedure. These exhibits contain proprietary, confidential and trade secrets material, which would not be routinely made available for public inspection.

Sincerely yours,

Gichard (\*

Richard Mullen Group Manager

1: Inadventively, WLAN was filed under equipment classification DTS for Digital Transmission System and FCC web site would not allow correction to file under equipment classification DSS for Spread Spectrum Transmitter.