

MPE Test Report					
Report No.:	AAOG-ESH-P24120408B-2				
FCC ID:	2ABEU-YLYDD0091				
Product:	Yeelight Smart LED Strip Lights				
Model:	YLYDD-0091, YLYDD-0092, YLYDD-0093				
Received Date:	Dec.09, 2024				
Test Date:	Dec.09, 2024 to Jan.05, 2025				
Issued Date:	Jan.08, 2025				
Applicant:	Qingdao Yeelink Information Technology Co., Ltd.				
Address:	10F-B4, Building B, Qingdao International Innovation Park, No.1 Keyuan Weiyi Road, Laoshan District, Qingdao City, Shandong Province, P. R. China				
Manufacturer:	Qingdao Yeelink Information Technology Co., Ltd.				
Address:	<ul> <li>10F-B4, Building B, Qingdao International Innovation Park, No.1 Keyuan Weiyi Road, Laoshan District, Qingdao City, Shandong Province, P. R. China</li> </ul>				
Issued By:	BUREAU VERITAS ADT (Shanghai) Corporation				
Lab Address:	No. 829, Xinzhuan Road, Shanghai, P.R.China (201612)				
FCC Registration / Designation Number:	176467/ CN1213				
	Cert 2343.01				
http://www.bureauveritas.com/home/about-us/our-bu- entity, or use of our name or trademark, is permitted in this report are not indicative or representative of th report includes all of the tests requested by you and Statements of conformity are based on simple accep this report to notify us of any material error or omiss	orporates by reference, the Conditions of Testing as posted at the date of issuance of this report at usiness/cps/about-us/terms-conditions/ and is intended for your exclusive use. Any copying or replication of this report to or for any other person or only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth e quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our the results thereof based upon the information that you provided to us. Measurement uncertainty is only provided upon request for accredited tests. tance criteria without taking measurement uncertainty into account, unless otherwise requested in writing. You have 60 days from date of issuance of on caused by our negligence or if you require measurement uncertainty; provided, however, that such notice shall be in writing and shall specifically e such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the				



### **Table of Contents**

Relea	se Control Record	3
1	Certificate of Conformity	4
2	General Information	5
2.1	General Description of EUT	5
3	RF Exposure	6
3.1	Limits For Maximum Permissible Exposure (MPE)	6
3.2	MPE Calculation Formula	6
3.3	MPE Calculation Formula	6
3.4	Calculation Result of Maximum Permissible Exposure	6



### **Release Control Record**

Issue No.	Description	Date Issued
AAOG-ESH-P24120408B-2	Original release	Jan.08, 2025



### 1 Certificate of Conformity

Product: Yeelight Smart LED Strip Lights

# Brand: YEELIGHT

Model: YLYDD-0091, YLYDD-0092, YLYDD-0093

Applicant: Qingdao Yeelink Information Technology Co., Ltd.

Test Date: Dec.09, 2024 to Jan.05, 2025

Standards: FCC Part 2 (Section 2.1091) KDB 447498 D01 General RF Exposure Guidance v06 IEEE C95.1-2019

The above equipment has been tested by **BUREAU VERITAS ADT (Shanghai) Corporation**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

Prepared by :	Jan. 2 hou	, Date:	Jan.08, 2025
Approved by :	Yan ZHOU Project Engineer Secan 74 Sean YU RF Supervisor	, Date:	Jan.08, 2025



## 2 General Information

## 2.1 General Description of EUT

BLE:

Product	Yeelight Smart LED Strip Lights
Brand	YEELIGHT
Test Model	YLYDD-0091, YLYDD-0092, YLYDD-0093
Model Difference	
Power Rating	YLYDD-0091: DC 24V 0.5A, Powered by adaptor YLYDD-0092: DC 24V 1A, Powered by adaptor YLYDD-0093: DC 24V 2A, Powered by adaptor
Modulation Type	GFSK
Modulation Technology	Bluetooth Low Energy 4.2
Operating Frequency	2402MHz ~ 2480MHz
Number of Channel	40
Antenna Type	PCB Antenna
Antenna Connector	
Antenna Gain	1.96dBi

Note:

1. For more details, please refer to the User's manual of the EUT.

### 2.2 Description of Support Unit

DESCRIPTION MANUFACTURER		MODEL NO.	SERIAL NO.	
Adaptor for YLYDD-0091	Guangdong Tiantongjiuheng Technology Co., Ltd	TJ01501L2400500US	NA	
Adaptor for YLYDD-0092	Guangdong Tiantongjiuheng Technology Co., Ltd	TJ02402W2401000US	NA	
Adaptor for YLYDD-0093	Guangdong Tiantongjiuheng Technology Co., Ltd	TJ05301W2402000US	NA	



## 3 RF Exposure

### 3.1 Limits For Maximum Permissible Exposure (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm <sup>2</sup> )	Average Time (minutes)		
Limits For General Population / Uncontrolled Exposure						
300-1,500 -		-	F/1500	30		
1,500-100,000	-	-	1.0	30		

F = Frequency in MHz

### 3.2 MPE Calculation Formula

Power density (S) is calculated according to the formula:

 $S = PG / (4\pi R^2)$ 

Where  $S = power density in mW/cm^2$ 

P = transmit power in mW

G = numeric gain of transmit antenna (numeric gain=Log-1(dB antenna gain/10))

R = distance (cm)

#### 3.3 MPE Calculation Formula

The antenna of this product, under normal use condition, is at least 20cm from the body of the user. So the device is classified as Mobile Device.

#### 3.4 Calculation Result of Maximum Permissible Exposure

Frequency Band (MHz)	Max. Conducted output power(dBm)	Antenna Gain (dBi)	Distance (cm)	Power Density (mW/cm²)	Limit (mW/cm <sup>2</sup> )	
BLE 4.2						
2402-2480	-8.77	1.96	20	0.000041	1	

#### **Conclusion:**

The calculation result of MPE is less than the limit.

--- END ---