

RF EXPOSURE EVALUATION

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency(RF) Radiation as specified in §1.1307(b)

FCC ID: 2AQKA-E10W

EUT Specification

EUT	Hunting camera
Frequency band (Operating)	☒ WLAN: 2.412GHz ~ 2.462GHz / 2.422GHz ~ 2.452GHz ☐ WLAN: 5.18GHz ~ 5.24GHz ☐ WLAN: 5.745GHz ~ 5.825GHz ☒ Others: 2.402GHz~2.480GHz 2.4G
Device category	☐ Portable (<20cm separation) ☒ Mobile (>20cm separation) ☐ Others _____
Exposure classification	☐ Occupational/Controlled exposure (S = 5mW/cm ²) ☒ General Population/Uncontrolled exposure (S=1mW/cm ²)
Antenna diversity	☒ Single antenna ☐ Multiple antennas ☐ Tx diversity ☐ Rx diversity ☐ Tx/Rx diversity
Max. output power	Wifi 2.4G: 12.60dBm (0.0182W) BT 4.2 BLE: 2.781dBm (0.0019W)
Antenna gain (Max)	2.2 dBi
Evaluation applied	☒ MPE Evaluation ☐ SAR Evaluation

Limits for Maximum Permissible Exposure(MPE)

Frequency Range(MHz)	Electric Field Strength(V/m)	Magnetic Field Strength(A/m)	Power Density(mW/cm ²)	Average Time
(A) Limits for Occupational/Control Exposures				
300-1500	--	--	F/300	6
1500-100000	--	--	5	6
(B) Limits for General Population/Uncontrol Exposures				
300-1500	--	--	F/1500	6
1500-100000	--	--	1	30

Friis transmission formula: $P_d = (P_{out} * G) / (4 * \pi * R^2)$

Where

P_d = Power density in mW/cm²

P_{out} = output power to antenna in Mw

G = gain of antenna in linear scale

π = 3.1416

R = distance between observation point and center of the radiator in cm

P_d the limit of MPE, 1mW/cm². If we know the maximum gain of the antenna and total power input to the antenna, through the calculation, we will know the distance where the MPE limit is reached.

Measurement Result

WIFI 2.4GHz :

Channel Frequency	Measured Power	Tune up tolerance	Max. Tune up Power	Antenna Gain	Power density at 20cm	Power density Limits (mW/cm ²)
(MHz)	(dBm)	(dBm)	(dBm)	(dBi)	(mW/ cm ²)	
2412	10.45	10.45±1	11.45	2.2	0.0046	1
2437	10.46	10.46±1	11.46	2.2	0.0046	1
2462	11.55	11.55±1	12.55	2.2	0.0059	1
2412	11.58	11.58±1	12.58	2.2	0.0060	1
2437	11.45	11.45±1	12.45	2.2	0.0058	1
2462	12.60	12.60±1	13.60	2.2	0.0076	1
2412	11.72	11.72±1	12.72	2.2	0.0062	1
2437	11.53	11.53±1	12.53	2.2	0.0059	1
2462	11.71	11.71±1	12.71	2.2	0.0062	1
2422	11.84	11.84±1	12.84	2.2	0.0063	1
2437	11.68	11.68±1	12.68	2.2	0.0061	1
2452	12.27	12.27±1	13.27	2.2	0.0070	1

Note: WIFI 2.4G cannot support simultaneous transmission.

BT

Channel Frequency	Measured Power	Tune up tolerance	Max. Tune up Power	Antenna Gain	Power density at 20cm	Power density Limits (mW/cm ²)
(MHz)	(dBm)	(dBm)	(dBm)	(dBi)	(mW/ cm ²)	
2402	0.418	0.418±1	1.418	2.2	0.0005	1
2440	1.92	1.92±1	2.92	2.2	0.0006	1
2480	2.781	2.781±1	3.781	2.2	0.0008	1

Note: BT cannot support simultaneous transmission.