


# USER MANUAL


## CONTENTS



## BATTERY INSTALLATION




- 1) Unscrew the screw on top of battery cover by screw driver.
- 2) Place (2) 1.5V AA batteries in the battery slots with correct polarity.
- 3) Close the battery cover and tighten the screw with screw driver.



- 1) Unscrew the screw on the top of battery cover with screw driver.
- 2) Place the rechargeable battery in the battery slots and connect it to the vehicle.
- 3) Close the battery cover and tighten the screw with screw driver.

Charging the Battery: 120 minutes



### Note:

If the remote control cannot control the vehicle, first remove the battery from the remote control and re-install the batteries. Then, turn off the power of the remote vehicle, then turn it back on the power, and then the remote control will reset the frequency.

### Warning:

Changes or modifications to this unit not expressly approved by the party responsible for compliance could void the user's authority to operate the equipment.

### NOTE:

This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

### FCC Statement:

This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates, uses and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications. However, there is no guarantee that interference will not occur in a particular installation. If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:

- Reorient or relocate the receiving antenna.
- Increase the separation between the equipment and receiver.
- Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.
- Consult the dealer or an experienced radio/TV technician for help.