

RF Exposure Report

Following FCC KDB 447498 D01 General SAR test exclusion guidelines

The corresponding SAR exclusion threshold condition, listed below:

1) The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation Distances ≤ 50 mm are determined by: $[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f} (\text{GHz})] \leq 3.0$ for 1-g SAR and ≤ 7.5 for 10-g.

Extremity SAR, where

- $f(\text{GHz})$ is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation.
- The result is rounded to one decimal place for comparison The test exclusions are applicable only when the minimum test separation distance is ≤ 50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is < 5 mm, a distance of 5 mm according to 5) in section 4.1 is applied to determine SAR test exclusion(447498 D01 General RF Exposure Guidance v06)

2) At 100 MHz to 6 GHz and for test separation distances > 50 mm, the SAR test exclusion threshold is determined according to the following

- $[\text{Power allowed at numeric threshold for } 50 \text{ mm in step 1)} + (\text{test separation distance} - 50 \text{ mm}) \cdot (f(\text{MHz})/150)] \text{ mW}$, at 100 MHz to 1500 MHz
- $[\text{Power allowed at numeric threshold for } 50 \text{ mm in step 1)} + (\text{test separation distance} - 50 \text{ mm}) \cdot 10] \text{ mW}$ at $> 1500 \text{ MHz}$ and $\leq 6 \text{ GHz}$

3) At frequencies below 100 MHz, the following may be considered for SAR test exclusion,

- The power threshold at the corresponding test separation distance at 100 MHz in step 2) is multiplied by $[1 + \log(100/f(\text{MHz}))]$ for *test separation distances* > 50 mm and < 200 mm
- The power threshold determined by the equation in a) for 50 mm and 100 MHz is multiplied by $\frac{1}{2}$ for *test separation distances* ≤ 50 mm
- SAR measurement procedures are not established below 100 MHz When SAR test exclusion cannot be applied, a KDB inquiry is required to determine SAR evaluation requirements for any test results to be acceptable.

RF Exposure

**Reference Test Report No: ULR-
TC568819300000072F**

Seite 2 von 2
Page 2 of 2

SAR Test Exclusion Thresholds

Maximum Measured Transmitter Power:

| Frequency (GHz) | Max.Power (mW) | Min.Test Separation distance | SAR Test Exclusion Calculation Values | 1-g Extremity SAR Test exclusion Thresholds |
|--------------------|-------------------|------------------------------------|--|--|
| 2.412 – 2.462 | 2.55858 | 5mm | 0.7947 | 3 |

Hence, the EUT is exempted from routine SAR evaluation

Note:

1. Calculate SAR exclusion threshold from condition 1) formulas.