

RF EXPOSURE REPORT

Applicant	ARKON ELECTRONICS (HUIZHOU) CO., LIMITED
Address	NO.4 Taihao Road, High-tech Industrial Park,Sandong Town, Huicheng District, Huizhou, Guangdong, China

Manufacturer or Supplier	ARKON ELECTRONICS (HUIZHOU) CO., LIMITED
Address	NO.4 Taihao Road, High-tech Industrial Park,Sandong Town, Huicheng District, Huizhou, Guangdong, China
Product	2.4GHz Digital Wireless Headphone
Brand Name	ARKON, ARTISTE
Model	DHP380A
Additional Model & Model Difference	DHP380, ADH300; (See item 3.1 note)
Date of tests	Apr. 02, 2020 ~ May. 06, 2020

- **⊠ KDB 447498 D01**
- **⊠** IEEE C95.1

CONCLUSION: The submitted sample was found to COMPLY with the test requirement

Tested by Ryan Lu	Tested by Glyn He	
Project Engineer / EMC Department	Assistant Manager / EMC Department	

Date: May 21, 2020

This report is governed by, and incorporates by reference, CPS Conditions of Service as posted at the date of issuance of this report at http://www.bureauveritas.com/home/about-us/our-business/cps/about-us/terms-conditions/and is intended for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. Measurement uncertainty is only provided upon request for accredited tests. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence or if you require measurement uncertainty; provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute you unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents.

Bureau Veritas Shenzhen Co., Ltd. Dongguan Branch

No. 96, Guantai Road (Houjie Section), Houjie Town, Dongguan City, Guangdong Province. 523942. People's Republic of China.

Tel: +86 769 8998 2098 Fax: +86 769 8593 1080

Email: customerservice.dg@cn.bureauveritas.com



TABLE OF CONTENTS

REL	EASE CONTROL RECORD	3
1.	CERTIFICATION	4
2.	RF EXPOSURE LIMIT	5
3.	MPE CALCULATION FORMULA	5
4.	CLASSIFICATION	5
5.	ANTENNA GAIN	6
6	CALCULATION RESULT OF MAXIMUM CONDUCTED POWER	6

Tel: +86 769 8998 2098 Fax: +86 769 8593 1080

Email: <u>customerservice.dg@cn.bureauveritas.com</u>



RELEASE CONTROL RECORD

ISSUE NO.		REASON FOR CHANGE	DATE ISSUED
FM200402N0	33	Original release	May 21, 2020

Tel: +86 769 8998 2098 Fax: +86 769 8593 1080

Email: customerservice.dg@cn.bureauveritas.com



1. CERTIFICATION

FCC ID:	2APBSDHP381A-01TX		
PRODUCT:	2.4GHz Digital Wireless Headphone		
BRAND NAME:	ARKON, ARTISTE		
MODEL NO.:	DHP380A		
ADDITIONAL NO.:	DHP380, ADH300		
APPLICANT:	ARKON ELECTRONICS (HUIZHOU) CO., LIMITED		
	FCC Part 2 (Section 2.1091)		
STANDARDS:	KDB 447498 D01		
	IEEE C95.1		



2. RF EXPOSURE LIMIT

LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

FREQUENCY RANGE (MHz) ELECTRIC FIELD STRENGTH (V/m) STRENGTH (A/m) POWER I			POWER DENSITY (mW/cm²)	AVERAGE TIME (minutes)	
LIMITS FOR GENERAL POPULATION / UNCONTROLLED EXPOSURE					
300-1500			F/1500	30	
1500-100,000			1.0	30	

F = Frequency in MHz

3. MPE CALCULATION FORMULA

 $Pd = (Pout*G) / (4*pi*r^2)$

Where

Pd = power density in mW/cm²

Pout = output power to antenna in mW

G = gain of antenna in linear scale

Pi = 3.1416

R = distance between observation point and center of the radiator in cm

4. CLASSIFICATION

The antenna of this product, under normal use condition, is at least 20cm away from the body of the user. So, this device is classified as **Mobile Device**.

Tel: +86 769 8998 2098 Fax: +86 769 8593 1080

Email: customerservice.dg@cn.bureauveritas.com



5. ANTENNA GAIN

The antennas provided to the EUT, please refer to the following table:

				0
Function		Transmitter Circuit	Peak Gain (dBi)	Antenna Type
	Wireless (GFSK)	Chain 0	-2.2	FPC Antenna

6. CALCULATION RESULT OF MAXIMUM CONDUCTED AV POWER

The tuned conducted Average Power (declared by client)

Mode	Frequency (MHz)	Target Power (dBm)	Tolerance (dBm)	Lower Tolerance (dBm)	Upper Tolerance (dBm)
Wireless (GFSK)	2406-2472	8.5	+-0.5	8.0	9.0

The measured conducted Average Power

Mode	Frequency (MHz)	Averaged Power (dBm)	
Wireless (GFSK)	2402~2480	8.49	

The final calculation results:

Frequency band (MHz)	Max average power (dBm)	Antenna gain (dBi)	Distance (cm)	Power density (mW/cm²)	Limit (mW/cm²)
Wireless (GFSK)2406-2472	9.0	-2.2	20	0.00095281	1.0

--- END ---