

Test report No:
NIE: 67117RAN.001

Assessment report

RF EXPOSURE REPORT ACCORDING TO FCC 47 CFR Part 2.1091

(*) Identification of item under evaluation	LTE Cat-M Cellular communication module
(*) Trademark	Sequans Communication
(*) Model and /or type reference	GM02S
(*) Other identification of the product	HW version: GM02Sv2 SW version: LR8.0.0.3-51813 FCC ID: 2AAGMGM02SA IC: 12732A-GM02SA IMEI TAC: 01577000
(*) Features	LTE-M, 3GPP LTE Release 14
(*) Manufacturer	SEQUANS COMMUNICATIONS 55 Boulevard Charles de Gaulle, 92700 Colombes France
Test method requested, standard	FCC 47 CFR Part 2.1091 Radiofrequency radiation exposure evaluation: mobile devices.
Summary	IN COMPLIANCE
Approved by (name / position & signature)	Miguel Lacave Antennas Lab Manager
Date of issue	2021-03-12
Report template No	FAN36_01 (*) "Data provided by the client"

Index

- Competences and guarantees3
- General conditions3
- Data provided by the client.....3
- Identification of the client.....3
- Document history3
- Appendix A: FCC RF Exposure assessment result4
 - General description of the equipment under evaluation5
 - Maximum Antenna Gain determination for RF Exposure compliance6
- Appendix B: FCC RF Exposure information8
 - FCC RF Exposure evaluation9
 - FCC MPE Evaluation10
 - FCC EIRP Limits10

Competences and guarantees

In order to assure the traceability to other national and international laboratories, DEKRA Testing and Certification, S.A.U. has a calibration and maintenance program for its measurement equipment.

DEKRA Testing and Certification, S.A.U. guarantees the reliability of the data presented in this report, which is the result of the measurements and the tests performed to the item under test on the date and under the conditions stated on the report and, it is based on the knowledge and technical facilities available at DEKRA Testing and Certification, S.A.U. at the time of performance of the test.

DEKRA Testing and Certification, S.A.U. is liable to the client for the maintenance of the confidentiality of all information related to the item under test and the results of the test.

The results presented in this Assessment Report apply only to the particular item under test established in this document.

IMPORTANT: No parts of this report may be reproduced or quoted out of context, in any form or by any means, except in full, without the previous written permission of DEKRA Testing and Certification, S.A.U.

General conditions

1. This report is only referred to the item that has undergone the assessment.
2. This report does not constitute or imply on its own an approval of the product by the Certification Bodies or competent Authorities.
3. This document is only valid if complete; no partial reproduction can be made without previous written permission of DEKRA Testing and Certification, S.A.U.
4. This test report cannot be used partially or in full for publicity and/or promotional purposes without previous written permission of DEKRA Testing and Certification, S.A.U. and the Accreditation Bodies

Data provided by the client

The following data has been provided by the client:

1. Information relating to the description of the sample ("Identification of the item under evaluation", "Trademark", "Model and/or type reference", "Other identification of the product" and "General description of the device").
2. Maximum output power

DEKRA Testing and Certification S.A.U. declines any responsibility with respect to the information provided by the client and that may affect the validity of results.

Identification of the client

SEQUANS COMMUNICATIONS

55 Boulevard Charles de Gaulle, 92700 Colombes, France

Document history

Report number	Date	Description
67117RAN.001	2021-03-12	First release

Appendix A: FCC RF Exposure assessment result

General description of the equipment under evaluation

The equipment under evaluation consists of a multi-band module supporting cellular LTE-M release 14.

As the equipment under evaluation is a module, a conservative evaluation distance of 20 cm has been used to perform the assessment.

The equipment specifications declared by the manufacturer for each supported technology and band are:

Technology / Mode	Band	Frequency (MHz)	Maximum Conducted Output Power RMS Burst (Incl. Tune-Up) (dBm)
LTE Cat-M1	2	1850 - 1910	25.00
LTE Cat-M1	4	1710 - 1755	25.00
LTE Cat-M1	5	824 - 849	25.00
LTE Cat-M1	12	699 - 716	25.00
LTE Cat-M1	13	777 - 787	25.00
LTE Cat-M1	17	704 - 716	25.00
LTE Cat-M1	25	1850 - 1915	25.00
LTE Cat-M1	66	1710 - 1780	25.00

Table 1: Equipment specifications

Maximum Antenna Gain determination for RF Exposure compliance

Summary of maximum antenna gain values:

Maximum antenna gain for mobile operation to comply with MPE and EIRP limits (see Appendix B) shall not exceed the following values:

Technology / Mode	Band	Frequency (MHz)	Max Gain to comply with MPE Limits (dBi)	Max Gain to comply with EIRP Limits (dBi)	Maximum allowed Gain (worst case) (dBi)
LTE Cat-M1	2	1850 - 1910	12.0	8.0	8.0
LTE Cat-M1	4	1710 - 1755	12.0	5.0	5.0
LTE Cat-M1	5	824 - 849	9.4	15.6	9.4
LTE Cat-M1	12	699 - 716	8.6	11.9	8.6
LTE Cat-M1	13	777 - 787	9.1	11.9	9.1
LTE Cat-M1	17	704 - 716	8.7	11.9	8.7
LTE Cat-M1	25	1850 - 1915	12.0	8.0	8.0
LTE Cat-M1	66	1710 - 1780	12.0	5.0	5.0

Table 2: Maximum Antenna Gain values

Maximum Gain to meet FCC Radiofrequency radiation exposure limits:

Technology / Mode	Band	Frequency (MHz)	Distance (cm)	Power density (mW/cm ²)	FCC General Population Limit (mW/cm ²)	Max Gain to meet MPE Limits (dBi)
LTE Cat-M1	2	1850 - 1910	20.0	0.06	1.0	12.0
LTE Cat-M1	4	1710 - 1755	20.0	0.06	1.0	12.0
LTE Cat-M1	5	824 - 849	20.0	0.06	0.5	9.4
LTE Cat-M1	12	699 - 716	20.0	0.06	0.5	8.6
LTE Cat-M1	13	777 - 787	20.0	0.06	0.5	9.1
LTE Cat-M1	17	704 - 716	20.0	0.06	0.5	8.7
LTE Cat-M1	25	1850 - 1915	20.0	0.06	1.0	12.0
LTE Cat-M1	66	1710 - 1780	20.0	0.06	1.0	12.0

Table 3: Maximum Antenna Gain values based on FCC MPE limits

Maximum Gain to meet FCC EIRP limits

Technology / Mode	Band	Frequency (MHz)	Max Conducted Output Power RMS Burst (Incl. Tune-Up)(dBm)	EIRP Limits (dBm)	Max Gain to meet EIRP Limits (dBi)
LTE Cat-M1	2	1850 - 1910	25.0	33.0	8.0
LTE Cat-M1	4	1710 - 1755	25.0	30.0	5.0
LTE Cat-M1	5	824 - 849	25.0	40.6	15.6
LTE Cat-M1	12	699 - 716	25.0	36.9	11.9
LTE Cat-M1	13	777 - 787	25.0	36.9	11.9
LTE Cat-M1	17	704 - 716	25.0	36.9	11.9
LTE Cat-M1	25	1850 - 1915	25.0	33.0	8.0
LTE Cat-M1	66	1710 - 1780	25.0	30.0	5.0

Table 4: Maximum Antenna Gain values based on FCC EIRP limits

Appendix B: FCC RF Exposure information

FCC RF Exposure evaluation

Devices operating in standalone mobile device exposure conditions may contain a single transmitter or multiple transmitters that do not transmit simultaneously. A minimum test separation distance ≥ 20 cm is required between the antenna and radiating structures of the device and nearby persons to apply mobile device exposure limits. The distance must be at least 20 cm and fully supported by the operating and installation configurations of the transmitter and its antenna(s), according to the source-based time-averaged maximum power requirements of § 2.1091(d)(2). In cases where cable losses or other attenuations are applied to determine compliance, the most conservative operating configurations and exposure conditions must be evaluated. The minimum test separation distance required for a device to comply with mobile device exposure conditions must be clearly identified in the installation and operating instructions, for all installation and exposure conditions, to enable users and installers to comply with RF exposure requirements. For mobile devices that have the potential to operate in portable device exposure conditions, similar to the configurations described in § 2.1091(d)(4), a KDB inquiry is required to determine the SAR test requirements for demonstrating compliance.

When a device qualifies for the categorical exclusion provision of § 2.1091(c), the minimum test separation distance may be estimated, when applicable, by simple calculations according to plane-wave equivalent conditions, to ensure the transmitter and its antenna(s) can operate in manners that meet or exceed the estimated distance. The source-based time-averaged maximum radiated power, according to the maximum antenna gain, must be applied to calculate the field strength and power density required to establish the minimum test separation distance. When the estimated test separation distance becomes overly conservative and does not support compliance, MPE measurement or computational modeling may be used to determine the required minimum separation distance.

According to §1.1310 Radiofrequency radiation exposure limits, paragraph (e), the limits for Maximum Permissible Exposure (MPE) to radiofrequency electromagnetic fields are:

TABLE 1—LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposure				
0.3–3.0	614	1.63	* 100	6
3.0–30	1842/f	4.89/f	* 900/f ²	6
30–300	61.4	0.163	1.0	6
300–1,500	f/300	6
1,500–100,000	5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3–1.34	614	1.63	* 100	30
1.34–30	824/f	2.19/f	* 180/f ²	30
30–300	27.5	0.073	0.2	30
300–1,500	f/1500	30
1,500–100,000	1.0	30

f = frequency in MHz * = Plane-wave equivalent power density

FCC MPE Evaluation

Each supported transmission technology will be evaluated to determine if it is in compliance with limits for Maximum Permissible Exposure (MPE) to radiofrequency electromagnetic fields.

In order to perform the assessment, the following equations have been used for the calculations; these equations are accurate in the far-field of an antenna and will over-predict power density in the near field, where they could be used for making a "worst-case" or conservative prediction:

$$\text{Power density: } S[mW / cm^2] = \frac{P_{\max} [mW]}{4\pi R[cm]^2}$$

$$\text{Maximum gain to meet the MPE limit: } G_{\max} [dBi] = (10 * \log[S[mW / cm^2] * 4\pi R[cm]^2) - P_{\max} [dBm]$$

S = power density

P_{\max} = power input to the antenna

R = distance to the center of radiation of the antenna (evaluation distance)

G_{\max} = power gain of the antenna in the direction of interest relative to an isotropic radiator

FCC EIRP Limits

Maximum FCC EIRP limits are frequency-dependent and are stated into the FCC standards shown in the following table:

Standard	Frequency Band	Technology & Band	EIRP limit (W)	EIRP limit (dBm)
FCC 47 CFR §27.50 (c)	700	LTE 12/17	4.92	36.92
FCC 47 CFR §27.50 (b)	700	LTE 13	4.92	36.92
FCC 47 CFR §22.913	850	LTE 5	11.48	40.6
FCC 47 CFR §27.50 (d)	1700	LTE 4/66	1.0	30.0
FCC 47 CFR §24.232	1900	LTE 2/25	2.0	33.0