



Maximum Permissible Exposure Evaluation

FCC ID: 2AQ5R-WCN3988

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) Radiation as specified in §1.1307(b).

EUT Specification

Product Name:	WiFi Module
Trade Mark:	/
Model/Type Reference:	WCN3988 A1
Listed Model(s):	WCN3988 A2
Model Differences:	All these models are identical in the same PCB, layout, electrical circuit, RF module and antenna. The difference is part of the components.
Frequency Band (Operating)	BT: 2402MHz ~ 2480MHz WLAN: 2412MHz ~ 2462MHz U-NII-1: 5180MHz ~ 5240MHz U-NII-2A: 5260MHz ~ 5320MHz U-NII-2C: 5500MHz ~ 5720MHz U-NII-3: 5745MHz ~ 5825MHz
Device Category	<input type="checkbox"/> Portable (<5mm separation) <input type="checkbox"/> Mobile (>20cm separation) <input checked="" type="checkbox"/> Fixed (>20cm separation) <input type="checkbox"/> Others _____
Exposure Classification	<input type="checkbox"/> Occupational/Controlled exposure ($S=5\text{mW}/\text{cm}^2$) <input checked="" type="checkbox"/> General Population/Uncontrolled exposure ($S=1\text{mW}/\text{cm}^2$)
Antenna Diversity	<input type="checkbox"/> Single antenna <input checked="" type="checkbox"/> Multiple antennas <input type="checkbox"/> TX diversity <input type="checkbox"/> RX diversity <input type="checkbox"/> TX/RX diversity
Antenna Gain (Max)	2.4GHz: 5.64dBi 5GHz: 6.27dBi
Evaluation Applied	<input checked="" type="checkbox"/> MPE Evaluation <input type="checkbox"/> SAR Evaluation

CTC Laboratories, Inc.

Room 101 Building B, No. 7, Lanqing 1st Road, Luhu Community, Guanhu Subdistrict, Longhua District, Shenzhen, Guangdong, China
Tel.: (86)755-27521059 Fax: (86)755-27521011 Http://www.sz-ctc.org.cn

TRF No: CTC-TR-066_A1

For anti-fake verification, please visit the official website of China Inspection And Testing Society : yz.cnca.cn

**Limits for Maximum Permissible Exposure (MPE)**

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Averaging Time (minutes)
(A) Limits for Occupational/Controlled Exposure				
300-1500	--	--	F/300	<6
1500-100000	--	--	5	<6
(B) Limits for General Population/Uncontrolled Exposure				
300-1500	--	--	F/1500	<30
1500-100000	--	--	1	<30

Calculation Method

Friis transmission formula: $P_d = (P_{out} * G) / (4 * \pi * R^2)$

Where:

P_d = Power density in mW/cm²

P_{out} = output power to antenna in mW

G = gain of antenna in linear scale

π = 3.1416

R = distance between observation point and center of the radiator in cm

P_d limit of MPE is 1mW/cm². If we know the maximum gain of the antenna and total power input to the antenna, through the calculation, we will know the distance where the MPE limit is reached.

Measurement Result

Mode	Frequency (MHz)	Antenna Gain (dBi)	Maximum Power (dBm)	Tune Up Tolerance (dB)	Max. Tune Up Power (dBm)	Power Density at 20cm (mW/cm ²)	Limit (mW/cm ²)
BLE	2480	5.64	9.64	±1	10.5	0.0082	1
BR/EDR	2480	5.64	9.31	±1	10.5	0.0082	1
WLAN 802.11g	2437	5.64	18.54	±1	19.5	0.0650	1
RLAN U-NII-2C 802.11ac(VHT40)	5510	6.27	15.86	±1	16.5	0.0376	1

The BT and WIFI can transmit simultaneously.

BT Power density at 20cm (mW/cm ²)	WLAN Power density at 20cm (mW/cm ²)	Total Power density at 20cm (mW/cm ²)	Power density Limit (mW/cm ²)
0.0082	0.0650	0.0732	1

Note:

1. Calculate in the worst-case mode.
2. Max. Tune Up Power is declared by manufacturer, and used to calculate.
3. For a more detailed features description, please refer to the RF Test Report.

*****THE END*****

CTC Laboratories, Inc.

Room 101 Building B, No. 7, Lanqing 1st Road, Luhu Community, Guanhu Subdistrict, Longhua District, Shenzhen, Guangdong, China
Tel.: (86)755-27521059 Fax: (86)755-27521011 Http://www.sz-ctc.org.cn

TRF No: CTC-TR-066_A1

For anti-fake verification, please visit the official website of China Inspection And Testing Society : yz.cnca.cn