US Tech Test Report: FCC ID: IC:

IC: Test Report Number: Customer:

Model:

FCC Part 15/IC RSS Certification 07P-4343 10147A-4343 18-0268 Inventek Systems ISM4343-X

Maximum Public Exposure to RF (MPE) CFR 15.247 (i), CFR 1.1310 (e)

The maximum exposure level to the public from the RF power of the EUT shall not exceed a power density, **S** as per the respective limits in Table 1 below, at a distance, d, of 20 cm (Mobile condition) from the EUT.

TABLE 1—LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm²)	Averaging time (minutes)
Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	*100	30
1.34-30	824/f	2.19/f	*180/f ²	30
30-300	27.5	0.073	0.2	30
300-1,500			f/1500	30
1,500-100,000			1.0	30

f = frequency in MHz * = Plane-wave equivalent power density

Therefore, for:

MPE for 2400 MHz - 2483.5 MHz for BT:

Limit: 1.0 mW/cm²

Peak Power (dBm) = 8.07 dBm (From UST rpt 18-0327)

Peak Power (Watts) = 0.0064 W

Gain of Transmit Antenna = $3.2 dB_i = 2.09$, numeric(Highest Gain Antenna)

d = Distance = 20 cm = 0.2 m

S = (PG/ $4\pi d^2$) = EIRP/4A = 0.0064(2.09)/4* π *0.2*0.2

 $= 0.0134/0.5030 = 0.0266 \text{ W/m}^2$

 $= (0.0266 \text{ W/m}^2) (1\text{m}^2/\text{W}) (0.1 \text{ mW/cm}^2)$

 $= 0.00266 \text{ mW/cm}^2$

which is << less than S = 1.0 mW/cm²

US Tech Test Report: FCC Part 15/IC RSS Certification FCC ID: IC: 10147A-4343 Test Report Number: Customer: Inventek Systems Model:

O7P-4343

18-0268

ISM4343-X

RF Exposure Evaluation – IC

According to RSS-102, 2.5.2 Exemption Limits for Routine Evaluation

At or above 300 MHz and below 6 GHz and the source based time averaged maximum EIRP of the device is equal to or less than 1.31 x 10⁻² x f^{0.6834} in Watts (adjusted for tune up tolerance where applicable), where f= frequency in MHz

For 2.4 GHz Band:

Limit= $1.31 \times 10^{-2} \times 2440^{0.6834} = 2.7 \text{ Watts}$

Max EIRP for WiFi = 8.0 dBm + 3.2 dB = 11.2 dBm = 13.2 mW << 2700 mW