

## INTERTEK TESTING SERVICES

---

### Analysis Report

The equipment under test (EUT) is a transmitter for a Volvo My First RC operating at 49.860 MHz which is controlled by a crystal. The EUT is powered by two 1.5V AAA batteries. For more detail information pls. refer to the user manual.

Antenna Type: Integral antenna

Antenna Gain: 0dBi

The nominal conducted output power specified: -45.0dBm (+/- 3dB)

The nominal radiated output power (e.r.p) specified: -47.15dBm (+/- 3dB)

Modulation Type: Pulse modulation

According to the KDB 447498:

The worst-case peak radiated emission for the EUT is 49.9dBμV/m at 3m in the frequency 49.86MHz

The EIRP =  $[(FS \cdot D)^2 / 30]$  mW = -45.33dBm

The ERP = EIRP - 2.15 = -47.48dBm

which is within the production variation.

The maximum conducted output power specified is -42dBm

= 0.000063mW

The source-based time-averaging conducted output power

=  $0.000063 \cdot \text{Duty Cycle}$  mW < 0.000063mW (Duty Cycle < 100%)

The SAR Exclusion Threshold Level for 49.860MHz when the minimum test separation distance is < 50mm:

=  $474 \cdot [1 + \log(100/f(\text{MHz}))]/2$

= 308.6 mW

Since the source-based time-averaging conducted output power is well below the SAR low threshold level, so the EUT is considered to comply with SAR requirement without testing.

#### Transmitter Duty Cycle Calculation

The duration of one cycle = 61.913ms

Effective period of the cycle =  $1.623\text{ms} \times 4 + 464.0\mu\text{s} \times 52$  = 30.6200ms

DC =  $30.6200\text{ms} / 61.913\text{ms}$  = 0.4946 or 49.46%