

# FCC ID: 2AHFW-UOTUNE1

## RF EXPOSURE EVALUATION

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency(RF) Radiation as specified in §1.1307(b)

Limits for Maximum Permissible Exposure (MPE)

Frequency Range(MHz)	Electric Field Strength(V/m)	Magnetic Field Strength(A/m)	Power Density(mW/cm <sup>2</sup> )	Average Time
<b>(A) Limits for Occupational/Control Exposures</b>				
300-1500	--	--	F/300	6
1500-100000	--	--	5	6
<b>(B) Limits for General Population/Uncontrol Exposures</b>				
300-1500	--	--	F/1500	6
1500-100000	--	--	1	30

### 11.1 Friis transmission formula: $P_d = \frac{P_{out} * G}{4 * \pi * R^2}$

Where

$P_d$  = Power density in mW/cm<sup>2</sup>

$P_{out}$  = output power to antenna in mW

$G$  = Numeric gain of the antenna relative to isotropic antenna

$\pi$  = 3.1416

$R$  = distance between observation point and center of the radiator in cm(20cm)

$P_d$  the limit of MPE, 1mW/cm<sup>2</sup>. If we know the maximum gain of the antenna and total power input to the antenna, through the calculation, we will know the distance where the MPE limit is reached.

$mW = 10^{(dBm/10)}$

## 11.2 Measurement Result

Operation Frequency: 2402MHz~2480MHz

Power density limited:  $1\text{mW}/\text{cm}^2$

Antenna Type: PCB Antenna

Antenna gain: 1.0dBi,

R=20cm

$\text{mW}=10^{(\text{dBm}/10)}$

Bluetooth DSS:

Channel Freq. (MHz)	modulation	conducted power (mW)	conducted power (dBm)	Tune-up power (dBm)	Max tune-up power (dBm)	Antenna Gain Numeric	Evaluation result (mW/cm <sup>2</sup> )	Power density Limits (mW/cm <sup>2</sup> )
2402	GFSK	1.51	1.79	1±1	2	1.26	0.000397	1
2441		1.51	1.80	1±1	2	1.26	0.000397	1
2480		1.53	1.84	1±1	2	1.26	0.000397	1
2402	π/4-DQPSK	1.22	0.87	1±1	2	1.26	0.000397	1
2441		1.23	0.89	1±1	2	1.26	0.000397	1
2480		1.21	0.82	1±1	2	1.26	0.000397	1
2402	8DPSK	1.25	0.96	1±1	2	1.26	0.000397	1
2441		1.27	1.05	1±1	2	1.26	0.000397	1
2480		1.26	1.00	1±1	2	1.26	0.000397	1

emission

Power density Limits (mW/cm <sup>2</sup> ) BT	Calculate Evaluation result (mW/cm <sup>2</sup> )	Power density Limits (mW/cm <sup>2</sup> )
0.000397	0.000397	1

### Conclusion:

For the max result :  $0.000397 \leq 1.0$  for 1g SAR, No SAR is required.

*Jason chen*

Signature:

Date: 2017-08-23

**NAME AND TITLE** (Please print or type): Jason Chen/Manager

**COMPANY** (Please print or type): Shenzhen NTEK Testing Technology Co., Ltd./ 1/F, Building E, Fenda Science Park, Sanwei Community, Xixiang Street Bao'an District, Shenzhen P.R. China.