

Nanoleaf Skylight

Model: NL64K000

120V AC 60Hz 19.5W

RGB+2700K-6500K 1400lm

Made in China

FCC ID: 2AEWY-NL64 IC: 20489-NL64

Contains FCC ID: 2AEWY-NL04A

Contains IC: 20489-NL04A

Conforms to UL STD 1598 Certified to CSA STD C22.2 NO 250.0

SUITABLE FOR DAMP LOCATIONS, INHERENTLY PROTECTED, DO NOT

INSTALL INSULATION WITHIN 76 mm (3 in) OF ANY PART OF THE

LUMINAIRE. ACCESS ABOVE CEILING REQUIRED. FOR USE IN NON-

FIRE-RATED INSTALLATIONS ONLY. MIN 90°C SUPPLY CONDUCTORS.

CONVENT AUX EMPLACEMENTS HUMIDES, INHERENTLY PROTECTED.

PROTECTION INHERENTE NE PAS METTRE L'ISOLANT À MOINS DE 76

mm (3 po) DE TOUTE PARTIE DU LUMINAIRE. ACCÈS REQUIS AU

DESSUS DU PLAFOND. UTILISER SEULEMENT DANS DES INSTALLATIONS

OÙ LE DEGRÉ DE RÉSISTANCE AU FEU N'EST PAS ÉTABLI. LES FILS

D'ALIMENTATION 90 °C MIN.

