



13. Radio Frequency Exposure

13.1.Applicable Standards

The measurements shown in this test report were made in accordance with the procedures given in FCC Part 2 (Section 2.1091)
KDB 447498

13.2.EUT Specification

Frequency band (Operating)	☐ WLAN: 2412MHz ~ 2462MHz ☒ WLAN: 5150MHz ~ 5250MHz ☐ WLAN: 5250MHz ~ 5350MHz ☐ WLAN: 5470MHz ~ 5725MHz ☐ WLAN: 5725MHz ~ 5850MHz ☐ Bluetooth: 2402MHz ~ 2480MHz
Device category	☐ Portable (<20cm separation) ☒ Mobile (>20cm separation)
Exposure classification	☐ Occupational/Controlled exposure (S = 5mW/cm ²) ☒ General Population/Uncontrolled exposure (S=1mW/cm ²)
Antenna diversity	☐ Single antenna ☒ Multiple antennas ☐ Tx diversity ☐ Rx diversity ☒ Tx/Rx diversity
Evaluation applied	☒ MPE Evaluation* ☐ SAR Evaluation ☐ N/A
Remark: 1. The maximum output power is <u>16.43dBm (0.0264mW)</u> at <u>5180MHz</u> (with <u>numeric 4.8 antenna gain.</u>) 2. DTS device is not subject to routine RF evaluation; MPE estimate is used to justify the compliance. 3. For mobile or fixed location transmitters, no SAR consideration applied. The maximum power density is 1.0 mW/cm ² even if the calculation indicates that the power density would be larger.	

13.3.Test Results

No non-compliance noted.



13.4.Calculation

$$\text{Given } E = \frac{\sqrt{30 \times P \times G}}{d} \quad \& \quad S = \frac{E^2}{3770}$$

Where E = Field strength in Volts / meter

P = Power in Watts

G = Numeric antenna gain

d = Distance in meters

S = Power density in milliwatts / square centimeter

Combining equations and re-arranging the terms to express the distance as a function of the remaining variables yields:

$$S = \frac{30 \times P \times G}{3770d^2}$$

Changing to units of mW and cm, using:

$P \text{ (mW)} = P \text{ (W)} / 1000$ and

$d \text{ (cm)} = d \text{ (m)} / 100$

Yields

$$S = \frac{30 \times (P / 1000) \times G}{3770 \times (d / 100)^2} = 0.0796 \times \frac{P \times G}{d^2} \quad \text{Equation 1}$$

Where d = Distance in cm

P = Power in mW

G = Numeric antenna gain

S = Power density in mW / cm²

**13.5.Maximum Permissible Exposure**

Max. output power	Band: 5150MHz ~ 5250MHz 802.11a: 16.43dBm (0.0264mW) 802.11an VHT20: 16.29dBm (0.0256mW) 802.11an VHT40: 16.28dBm (0.0255mW) 802.11ac VHT20: 16.34dBm (0.0258mW) 802.11ac VHT40: 16.20dBm (0.250mW) 802.11ac VHT80: 15.43dBm (0.0210mW)
Antenna gain (Max)	4.8dBi

Maximum Permissible Exposure

Modulation Mode	Frequency band (MHz)	Max. Conducted output power (dBm)	Antenna gain (dBi)	Distance (cm)	Power density (mW/cm ²)	Limit (mW/cm ²)
802.11a	5150-5250	16.43	4.8	20	0.0264	1
802.11an HT20	5150-5250	16.29	4.8	20	0.0256	1
802.11an HT40	5150-5250	16.28	4.8	20	0.0255	1
802.11ac VHT20	5150-5250	16.34	4.8	20	0.0258	1
802.11ac VHT40	5150-5250	16.20	4.8	20	0.0250	1
802.11ac VHT80	5150-5250	15.43	4.8	20	0.0210	1

Maximum Permissible Exposure (Co-location)

Modulation Mode	Frequency band (MHz)	Max. Conducted output power (dBm)	Antenna Gain(dBi)	Distance (cm)	Power Density (mW/cm ²)
2.4G 11g	2412-2462	28.73	4.6	20	0.4283
5G 11a	5725-5850	25.99	4.8	20	0.2385
Co-location Total					0.6668
Maximum Permissible Exposure Limit					1