

TEST REPORT

Test Report Reference: E51079A Edition 1

Equipment under Test: CC-239D RFID cover

Serial Number: -

Applicant: NOKIA CORPORATION

Manufacturer: NOKIA CORPORATION

**Test Laboratory
(CAB)
accredited by
DATech e.V.
in compliance with DIN EN ISO/IEC 17025
under the
Reg. No. DAT-P-105/99-21
and listed by
FCC 31040/SIT1300F2**

TEST REPORT REFERENCE: E51079A Edition 1

Contents:	Page
1 IDENTIFICATION	3
1.1 APPLICANT	3
1.2 MANUFACTURER	3
1.3 DATES	3
1.4 TEST LABORATORY	4
1.5 RESERVATION	4
1.6 NORMATIVE REFERENCES	4
1.7 TEST RESULTS	4
2 TECHNICAL DATA OF EQUIPMENT	5
2.1 DEVICE UNDER TEST	5
2.2 PEREPHERY DEVICES	5
2.3 SPECIAL EMC MEASURES	5
3 OPERATIONAL STATES AND PHYSICAL BOUNDARIES	6
4 LIST OF TEST MODULES	7
4.1 EMISSION	7
5 METHOD OF MEASUREMENT	8
5.1 RADIATED EMISSIONS 9 kHz to 30 MHz	8
5.2 RADIATED EMISSIONS 30 MHz to 1 GHz	10
5.3 FREQUENCY STABILITY WITH RESPECT TO AMBIENT TEMPERATURE AND SUPPLY VOLTAGE	12
6 TEST RESULTS EMISSION TEST	13
6.1 PRELIMINARY RADIATED EMISSION TEST (9 kHz to 30 MHz)	13
6.2 PRELIMINARY RADIATED EMISSION TEST (30 MHz to 1 GHz)	15
6.3 FINAL RADIATED EMISSION TEST (9 kHz to 30 MHz)	17
6.4 OCCUPIED BANDWIDTH	18
6.5 FREQUENCY TOLLERANCE	19
7 TEST EQUIPMENT AND ANCILLARIES USED FOR TESTS	21
8 LIST OF ANNEXES	25

TEST REPORT REFERENCE: E51079A Edition 1

1 IDENTIFICATION

1.1 APPLICANT

Name:	NOKIA CORPORATION
Address:	P.O. BOX 86, FIN-24101 SALO
Country:	Finland
Name for contact purposes:	TCC Salo/ Mr. Arto Hihnala
Phone:	+358 40 759 8936
Fax:	+358 7180 45 220
Mail address:	arto.hihnala@nokia.com
Applicant represented during the test by the following person:	Mr. Vesa Vuorio

1.2 MANUFACTURER

Name:	NOKIA CORPORATION
Address:	P.O. BOX 86, FIN-24101 SALO
Country:	Finland
Name for contact purposes:	TCC Salo/ Mr. Arto Hihnala
Phone:	+358 40 759 8936
Fax:	+358 7180 45 220
Mail address:	arto.hihnala@nokia.com
Manufacturer represented during the test by the following person:	Mr. Vesa Vuorio

1.3 DATES



Date of receipt of test sample:	14 June 2005
Start of test:	14 June 2005
End of test:	15 June 2005

TEST REPORT REFERENCE: E51079A Edition 1

1.4 TEST LABORATORY

The tests were carried out at: **PHOENIX TESTLAB GmbH**
Königswinkel 10
D-32825 Blomberg Phone: **+49 (0) 52 35 / 95 00-0**
Germany Fax: **+49 (0) 52 35 / 95 00-10**

accredited by DATech e.V. in compliance with DIN EN ISO/IEC 17025 under Reg. No. DAT-P-105/99-21 and listed by FCC 31040/SIT1300F2.

Test engineer:	Thomas KÜHN		20 June 2005
	Name	Signature	Date
Test report checked:	Bernd STEINER		20 June 2005
	Name	Signature	Date

PHOENIX TESTLAB GmbH
Königswinkel 10
32825 Blomberg
Tel. 0 52 35 / 95 00-0
Fax 0 52 35 / 95 00-10

Stamp

1.5 RESERVATION

This test report is only valid in its original form.

Any reproduction of its contents without written permission of the accredited test laboratory PHOENIX TESTLAB GmbH is prohibited.

The test results herein refer only to the tested sample. PHOENIX TESTLAB GmbH is not responsible for any generalisations or conclusions drawn from these test results concerning further samples. Any modification of the tested samples is prohibited and leads to the invalidity of this test report. Each page necessarily contains the PHOENIX TESTLAB Logo and the TEST REPORT REFERENCE.

1.6 NORMATIVE REFERENCES

- [1] **ANSI C63.4-2003** American National Standard for Methods of Measuring of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz.
- [2] **FCC 47 CFR Part 15 (January 2005)** Radio Frequency Devices

1.7 TEST RESULTS

The requirements of this test document are fulfilled by the equipment under test. The complete test results are presented in the following.

TEST REPORT REFERENCE: E51079A Edition 1

2 TECHNICAL DATA OF EQUIPMENT

2.1 DEVICE UNDER TEST

Type of equipment:	RFID cover for NOKIA mobile phone 3220
Type designation:	CC-239D
Serial No.:	-
Highest internal frequency:	27.12 MHz
Antenna type:	Integral

The following external I/O cables were used:

Cable	Length	Shielding	Connector
AC / DC adaptor (to the charger of the mobile phone)	1.8 m	No	3.5 mm jack plug
-	-	-	-
-	-	-	-
-	-	-	-
-	-	-	-

2.2 PERIPHERY DEVICES

The following equipment was used as control unit and ancillary equipment:

During all radiated measurements the EUT was connected to a NOKIA mobile phone model 3220, type RH-37, Serial number 353779/00/126015/9. For measurements under extreme conditions the NOKIA mobile phone model 3220, type RH-37, Serial number 355387/00/704162/9 was used. The charger of the mobile phone was connected to an AC / DC adaptor type ACP12E, which was connected to an AC-mains network with 115 V AC/ 60 Hz.

2.3 SPECIAL EMC MEASURES

The following EMC measures were necessary to reach the documented results:

None

TEST REPORT REFERENCE: E51079A Edition 1

3 OPERATIONAL STATES AND PHYSICAL BOUNDARIES

The battery of the mobile phone supplies the EUT in any case. In charging mode the battery is buffered by the AC / DC adaptor. For this reason the voltage variation was carried out within the supply voltage range, in which the mobile phone still operates. This range was 3.145 V DC to 4.23 V DC.

For measurements carried out with a test fixture (frequency error and occupied bandwidth) the mobile phone was supplied by an external power supply instead the mobile phone battery.


The mobile phone and the charger were already tested and not subject of this test report.

All measurements were carried out with a test-software, which set the RFID cover in a continuous operation mode with the maximum modulation rate, because pretests have shown that this mode produces the highest emissions. With this test software no GSM-link was necessary. The mobile phone receiver was not in use during the measurements

For the whole frequency range a preliminary measurement in a fully anechoic chamber with a measuring distance of 3 m was carried out to determine the frequencies, which were radiated by the EUT. The final measurements on the detected frequencies were carried out on an outdoor test site without ground plane (for the frequency range 9 kHz to 30 MHz) and on an open area test site with ground plane (for the frequency range 30 MHz to 1 GHz).

The physical boundaries of the Equipment Under Test are shown below.

Physical boundary of the CC-239D



TEST REPORT REFERENCE: E51079A Edition 1

4 LIST OF TEST MODULES

4.1 EMISSION

Radiated emissions FCC 47 CFR Part 15 section 15.209 [2]						
No.	Application	Frequency range	Limits (microvolts/meter)	Reference standard	Remark	Status
1	Intentional radiator	0.009 to 0.49 MHz 0.490 to 1.705 MHz 1.705 to 30.0 MHz 30 to 88 MHz 88 to 216 MHz 216 to 960 MHz 960 to 1000 MHz	2400/f(kHz) at 300 m 24000/f(kHz) at 30 m 30.0 dB μ V/m at 30 m 40.0 dB μ V/m at 3 m 43.5 dB μ V/m at 3 m 46.0 dB μ V/m at 3 m 54.0 dB μ V/m at 3 m	ANSI C63.4 (2003);	-	Passed
Radiated emissions FCC 47 CFR Part 15 section 15.225 (a)[2]						
No.	Application	Frequency range	Limits (microvolts/meter)	Reference standard	Remark	Status
2	Operation within the band 13.553 – 13.567 MHz	13.553 - 13.567 MHz	15,848 at 30 m	ANSI C63.4 (2003);	-	Passed
Radiated emissions FCC 47 CFR Part 15 section 15.225 (b)[2]						
No.	Application	Frequency range	Limits (microvolts/meter)	Reference standard	Remark	Status
3	Operation within the bands 13.410 – 13.553 MHz and 13.567 – 13.710 MHz	13.410 - 13.553 MHz and 13.567 - 13.710 MHz	334 at 30 m	ANSI C63.4 (2003);	Not carried out, because the carrier is already below these limits.	Passed
Radiated emissions FCC 47 CFR Part 15 section 15.225 (c)[2]						
No.	Application	Frequency range	Limits (microvolts/meter)	Reference standard	Remark	Status
4	Operation within the bands 13.110 – 13.410 MHz and 13.710 – 14.010 MHz	13.110 - 13.410 MHz and 13.710 - 14.010 MHz	106 at 30 m	ANSI C63.4 (2003);	Not carried out, because the carrier is already below these limits.	Passed
Frequency tolerance over temperature and supply voltage FCC 47 CFR Part 15 section 15.225 (e)[2]						
No.	Application		Limits	Reference standard	Remark	Status
5	Temperature range -20°C to +50°C and supply voltage 85 to 115 % or new battery		0.01 %	ANSI C63.4 (2003);	-	Passed

TEST REPORT REFERENCE: E51079A Edition 1

5 METHOD OF MEASUREMENT

5.1 RADIATED EMISSIONS 9 kHz to 30 MHz

The radiated emission measurement is divided into two stages.


Preliminary measurement:

In the first stage a preliminary measurement will be performed in a shielded room with a measuring distance of 3 meters. Tabletop devices will set up on a non-conducting support with a size of 1 m by 1.5 m and a height of 80 cm. Floor-standing devices will be placed directly on the turntable/ground plane. The set up of the Equipment under test will be in accordance to ANSI C63.4-2003 [1].

The frequency range 9 kHz to 30 MHz will be monitored with a spectrum analyser while the system and its cables will be manipulated to find out the configuration with the maximum emission levels if applicable. The EMI Receiver will be set to MAX Hold mode. The EUT and the measuring antenna will be rotated around their vertical axis to found the maximum emissions.

The resolution bandwidth of the spectrum analyser will be set to the following values:

Frequency range	Resolution bandwidth
9 kHz to 150 kHz	200 Hz
150 kHz to 30 MHz	10 kHz



TEST REPORT REFERENCE: E51079A Edition 1

Preliminary measurement procedure:

Prescans were performed in the frequency range 9 kHz to 150 kHz and 150 kHz to 30 MHz.

The following procedure will be used:

- 1) Monitor the frequency range at horizontal polarisation and a EUT azimuth of 0 °.
- 2) Manipulate the system cables within the range to produce the maximum level of emission.
- 3) Rotate the EUT by 360 ° to maximize the detected signals.
- 4) Make a hardcopy of the spectrum.
- 5) Measure the frequencies of highest detected emission with a lower span and resolution bandwidth to increase the accuracy and note the frequency value.
- 6) Repeat steps 1) to 4) with the other orthogonal axes of the EUT.
- 7) Rotate the measuring antenna and repeat steps 1) to 5).


Final measurement:

In the second stage a final measurement will be performed on an open area test site with no conducting ground plane in a measuring distances of 3 m, 10 m and 30 m. In the case where larger measuring distances are required the results will be extrapolated based on the values measured on the closer distances according to Section 15.31 (f) (2) [2]. The final measurement will be performed with a EMI Receiver set to Quasi Peak detector except for the frequency bands 9 kHz to 90 kHz and 110 kHz to 490 kHz where an average detector will be used according Section 15.209 (d) [2].

On the during the preliminary measurement detected frequencies the final measurement will be performed while rotating the EUT and the measuring antenna in the range of 0 ° to 360 ° around their vertical axis until the maximum value is found.

The resolution bandwidth of the EMI Receiver will be set to the following values:

Frequency range	Resolution bandwidth
9 kHz to 150 kHz	200 Hz
150 kHz to 30 MHz	9 kHz



TEST REPORT REFERENCE: E51079A Edition 1

Final measurement procedure:

The following procedure will be used:

- 1) Monitor the frequency range with the measuring antenna at vertical orientation parallel to the EUT at an azimuth of 0 °.
- 2) Rotate the EUT by 360 ° to maximize the detected signals and note the azimuth and orientation.
- 3) Rotate the measuring antenna to find the maximum and note the value.
- 4) Rotate the measuring antenna and repeat steps 1) to 3) until the maximum value is found.
- 5) Repeat steps 1) to 4) with the other orthogonal axes of the EUT if applicable (handheld equipment).

5.2 RADIATED EMISSIONS 30 MHz to 1 GHz

The radiated emission measurement is divided into two stages.


Preliminary measurement:

In the first stage a preliminary measurement will be performed in a fully anechoic chamber with a measuring distance of 3 meter. Tabletop devices will set up on a non-conducting support with a size of 1 m by 1.5 m and a height of 80 cm. Floor-standing devices will be placed directly on the turntable/ground plane. The set up of the Equipment under test will be in accordance to ANSI C63.4-2003 [1].

The frequency range 30 MHz to 1 GHz will be measured with an EMI Receiver set to MAX Hold mode and a resolution bandwidth of 100 kHz. The measurement will be performed in horizontal and vertical polarisation of the measuring antenna and while rotating the EUT in its vertical axis in the range of 0 ° to 360 °.

The resolution bandwidth of the EMI Receiver will be set to the following values:

Frequency range	Resolution bandwidth
30 MHz to 1 GHz	100 kHz



TEST REPORT REFERENCE: E51079A Edition 1

Procedure preliminary measurement:

Prescans were performed in the frequency range 30 MHz to 230 MHz and 230 MHz to 1 GHz.
The following procedure will be used:


1. Monitor the frequency range at horizontal polarisation and a EUT azimuth of 0 °.
2. Manipulate the system cables within the range to produce the maximum level of emission.
3. Rotate the EUT by 360 ° to maximize the detected signals.
4. Make a hardcopy of the spectrum.
5. Measure the frequency of 3 highest detected emissions with a lower span and resolution bandwidth to increase the accuracy and note the frequency value.
6. Repeat steps 1) to 4) with the other orthogonal axes of the EUT.
7. Repeat steps 1) to 5) with the vertical polarisation of the measuring antenna.

Final Measurement:

In the second stage a final measurement on an open area test site will be performed on selected frequencies found in the preliminary measurement. During this test the EUT will be rotated in the range of 0 ° to 360 °, the measuring antenna will be set to horizontal and vertical polarisation and raised and lowered in the range from 1 m to 4 m to find the maximum level of emissions.

The resolution bandwidth of the EMI Receiver will be set to the following values:

Frequency range	Resolution bandwidth
30 MHz to 1 GHz	120 kHz




TEST REPORT REFERENCE: E51079A Edition 1

Procedure final measurement:

The following procedure will be used:

- 1) Measure on the selected frequencies at an antenna height of 1 m and a EUT azimuth of 23 °.
- 2) Move the antenna from 1 m to 4 m and note the maximum value at each frequency.
- 3) Rotate the EUT by 45 ° and repeat 2) until an azimuth of 337 ° is reached.
- 4) Repeat 1) to 3) for the other orthogonal antenna polarization.
- 5) Move the antenna and the turntable to the position where the maximum value is detected.
- 6) Measure while moving the antenna slowly +/- 1 m.
- 7) Set the antenna to the position where the maximum value is found.
- 8) Measure while moving the turntable +/- 45 °.
- 9) Set the turntable to the azimuth where the maximum value is found.
- 10) Measure with Final detector (QP or AV) and note the value.
- 11) Repeat 5) to 10) for each frequency.
- 12) Repeat 1) to 11) for each orthogonal axes of the EUT if handheld equipment.

5.3 FREQUENCY STABILITY WITH RESPECT TO AMBIENT TEMPERATURE AND SUPPLY VOLTAGE



The following procedure will be used:

- 1) Place the EUT in the climatic chamber.
- 2) Switch on the EUT and check the correct function and the settings of the spectrum analyser.
- 3) Switch off the EUT and tune the climatic chamber to a temperature of 50 °C. Wait until the thermal balance is obtained.
- 4) Switch the EUT on and record the frequencies at start-up and 2, 5 and 10 minutes after powering on.
- 5) Repeat 4) with the minimum and the maximum of the supply voltage.
- 6) Switch off the EUT and tune the climatic chamber to a temperature range of 50 °C to –20 °C in ten-degree steps. Wait until the thermal balance is obtained for every step.
- 7) Switch the EUT on and record the frequencies at start-up and 2, 5 and 10 minutes after powering on.
- 8) Repeat 7) with the minimum and the maximum of the supply voltage.
- 9) Repeat 6) with the next temperature step until –20 °C were reached.

TEST REPORT REFERENCE: E51079A Edition 1

6 TEST RESULTS EMISSION TEST

6.1 PRELIMINARY RADIATED EMISSION TEST (9 kHz to 30 MHz)

Ambient temperature	21 °C	Relative humidity	40 %
---------------------	-------	-------------------	------


Position of EUT: The EUT was set-up on a non-conducting table of a height of 0.8 m. The distance between EUT and antenna was 3 m.

Cable guide: The cable of the mobile phone was fixed on the non-conducting table. For further information of the cable guide refer to the pictures in annex A of this test report.

Test record: The test was carried out in test mode of the EUT (transmit mode with modulation). All results are shown in the following.

Remark: The emissions found around 2.5 MHz caused temporary by the charging circuit of the mobile phone with high interval times. The emissions found at 15.5 kHz, 31 kHz, 47.9 kHz and 62.5 kHz caused by the measuring system and not by the EUT.

51079 1.wmf: Spurious emissions from 9 kHz to 150 kHz:




TEST EQUIPMENT USED THE TEST:


29, 31 – 33, 56

TEST REPORT REFERENCE: E51079A Edition 1

51079_2.wmf: Spurious emissions from 150 kHz to 1 MHz:



51079_3.wmf: Spurious emissions from 1 MHz to 30 MHz:



No emissions found in and outside the restricted bands.

The following frequency was found inside the 13.533 to 13.567 MHz band according to FFC 47 CFR Part 15 section 15.225 [2]:

13.560 MHz.

This frequency has to be measured on the outdoor test site. The result of this final measurement is shown in subclause 6.3 of this test report.


TEST REPORT REFERENCE: E51079A Edition 1

6.2 PRELIMINARY RADIATED EMISSION TEST (30 MHz to 1 GHz)

Ambient temperature	21 °C	Relative humidity	40 %
---------------------	-------	-------------------	------


- Position of EUT: The EUT was set-up on a non-conducting table of a height of 0.8 m. The distance between EUT and antenna was 3 m.
- Cable guide: The cable of the mobile phone was fixed on the non-conducting table. For further information of the cable guide refer to the pictures in annex A of this test report.
- Test record: The test was carried out in test mode of the EUT (transmit mode with modulation). All results are shown in the following.

51079_5.wmf: Spurious emissions from 30 MHz to 230 MHz:



TEST REPORT REFERENCE: E51079A Edition 1

51079_6.wmf: Spurious emissions from 230 MHz to 1 GHz:



No significant frequencies above the noise floor of the system were found during the preliminary radiated emission test, so no measurements were carried out the open area test site.

TEST EQUIPMENT USED FOR THE TEST:

29, 31 - 35, 43

TEST REPORT REFERENCE: E51079A Edition 1

6.3 FINAL RADIATED EMISSION TEST (9 kHz to 30 MHz)

Ambient temperature	17 °C	Relative humidity	51 %
---------------------	-------	-------------------	------

Position of EUT: The EUT was set-up on a non-conducting table of a height of 0.8 m. The distance between EUT and antenna was 30 m.

Cable guide: The cable of the mobile phone was fixed on the non-conducting table. For further information of the cable guide refer to the pictures in annex A of this test report.

Test record: The test was carried out in test mode of the EUT (transmit mode with modulation). All results are shown in the following.

Supply voltage: The EUT was supplied with 12 V DC and 5 V DC via suitable AC/DC adaptors.

Test results: The test results were calculated with the following formula:

$$\text{Result [dB}\mu\text{V/m]} = \text{reading [dB}\mu\text{V]} + \text{antenna factor [dB/m]}$$

Results with measuring distance of 3 m						
Frequency MHz	Result dB μ V/m	Limit dB μ V/m	Margin dB	Detector	Readings dB μ V	Antenna factor * dB/m
13.560	39.4	124.0	84.6	QP	19.4	20.0
Results with measuring distance of 10 m						
Frequency MHz	Result dB μ V/m	Limit dB μ V/m	Margin dB	Detector	Readings dB μ V	Antenna factor * dB/m
13.560	24.5	104.0	79.5	QP	4.5	20.0
Results with measuring distance of 30 m						
Frequency MHz	Result dB μ V/m	Limit dB μ V/m	Margin dB	Detector	Readings dB μ V	Antenna factor * dB/m
13.560	No result above the noise floor of the system					

*: Cable loss included

Test: Passed

TEST EQUIPMENT USED FOR THE TEST:

55 – 57

TEST REPORT REFERENCE: E51079A Edition 1

6.4 OCCUPIED BANDWIDTH

Ambient temperature:	21 °C	Relative humidity:	40 %
----------------------	-------	--------------------	------


Test set-up: For this test the test set-up from the preliminary emission measurement test set-up was used.

Cable guide: The cable of the EUT was fixed on the non-conducting table. For further information of the cable guide refer to the pictures in annex A of this test report, because the same test set-up as for the frequency error was used.

Supply voltage: The EUT was supplied with 3.7 V DC by an external power supply instead of the mobile phone battery.

Test record: The test was carried out in test mode of the EUT (transmit mode with modulation). All results are shown in the following.

51079bw.hgl: Occupied bandwidth:



F_L	F_U	BW ($F_U - F_L$)
13.346667 MHz	13.773889 MHz	427.222 kHz

TEST EQUIPMENT USED THE TEST:

22, 58, 59

TEST REPORT REFERENCE: E51079A Edition 1

6.5 FREQUENCY TOLLERANCE

Ambient temperature	20 °C	Relative humidity	39 %
---------------------	-------	-------------------	------

Supply voltage: 4.230 V DC

Temperature:	Minutes after switch on	Frequency:	Allowed tolerance:	Measured tolerance:	Result:
50 °C	0	13.560272 MHz	± 1.35 kHz	-44 Hz	Passed
	2	13.560300 MHz	± 1.35 kHz	-16 Hz	Passed
	5	13.560305 MHz	± 1.35 kHz	-11 Hz	Passed
	10	13.560309 MHz	± 1.35 kHz	-7 Hz	Passed
40 °C	0	13.560283 MHz	± 1.35 kHz	-33 Hz	Passed
	2	13.560300 MHz	± 1.35 kHz	-16 Hz	Passed
	5	13.560294 MHz	± 1.35 kHz	-22 Hz	Passed
	10	13.560300 MHz	± 1.35 kHz	-16 Hz	Passed
30 °C	0	13.560316 MHz	± 1.35 kHz	0 Hz	Passed
	2	13.560305 MHz	± 1.35 kHz	-11 Hz	Passed
	5	13.560300 MHz	± 1.35 kHz	-16 Hz	Passed
	10	13.560300 MHz	± 1.35 kHz	-16 Hz	Passed
20 °C	0	13.560316 MHz	-	0 Hz	For information
	2	13.560327 MHz	-	+11 Hz	For information
	5	13.560322 MHz	-	+ 6 Hz	For information
	10	13.560316 MHz	-	-	Reference
10 °C	0	13.560335 MHz	± 1.35 kHz	+19 Hz	Passed
	2	13.560344 MHz	± 1.35 kHz	+28 Hz	Passed
	5	13.560338 MHz	± 1.35 kHz	+22 Hz	Passed
	10	13.560338 MHz	± 1.35 kHz	+22 Hz	Passed
0 °C	0	13.560355 MHz	± 1.35 kHz	+39 Hz	Passed
	2	13.560355 MHz	± 1.35 kHz	+39 Hz	Passed
	5	13.560350 MHz	± 1.35 kHz	+34 Hz	Passed
	10	13.560355 MHz	± 1.35 kHz	+34 Hz	Passed
- 10 °C	0	13.560344 MHz	± 1.35 kHz	+28 Hz	Passed
	2	13.560361 MHz	± 1.35 kHz	+45 Hz	Passed
	5	13.560361 MHz	± 1.35 kHz	+45 Hz	Passed
	10	13.560361 MHz	± 1.35 kHz	+45 Hz	Passed
- 20 °C	0	13.560294 MHz	± 1.35 kHz	-22 Hz	Passed
	2	13.560338 MHz	± 1.35 kHz	+22 Hz	Passed
	5	13.560344 MHz	± 1.35 kHz	+28 Hz	Passed
	10	13.560356 MHz	± 1.35 kHz	+35 Hz	Passed

Conclusion: The maximum frequency error with a supply voltage of 4.23 V DC was +45 Hz, which is equal to an error of + 0.0003 %.

Continued next page

TEST REPORT REFERENCE: E51079A Edition 1

Supply voltage: 3.145 V DC

Temperature:	Minutes after switch on	Frequency:	Allowed tolerance:	Measured tolerance:	Result:
50 °C	0	13.560294 MHz	± 1.35 kHz	-26 Hz	Passed
	2	13.560300 MHz	± 1.35 kHz	-22 Hz	Passed
	5	13.560305 MHz	± 1.35 kHz	-17 Hz	Passed
	10	13.560311 MHz	± 1.35 kHz	-11 Hz	Passed
40 °C	0	13.560300 MHz	± 1.35 kHz	-22 Hz	Passed
	2	13.560294 MHz	± 1.35 kHz	-26 Hz	Passed
	5	13.560294 MHz	± 1.35 kHz	-26 Hz	Passed
	10	13.560294 MHz	± 1.35 kHz	-26 Hz	Passed
30 °C	0	13.560311 MHz	± 1.35 kHz	-11 Hz	Passed
	2	13.560300 MHz	± 1.35 kHz	-22 Hz	Passed
	5	13.560300 MHz	± 1.35 kHz	-22 Hz	Passed
	10	13.560300 MHz	± 1.35 kHz	-22 Hz	Passed
20 °C	0	13.560333 MHz	-	+11 Hz	For information
	2	13.560322 MHz	-	0 Hz	For information
	5	13.560316 MHz	-	-6 Hz	For information
	10	13.560322 MHz	-	-	Reference
10 °C	0	13.560350 MHz	± 1.35 kHz	+28 Hz	Passed
	2	13.560344 MHz	± 1.35 kHz	+22 Hz	Passed
	5	13.560338 MHz	± 1.35 kHz	+16 Hz	Passed
	10	13.560338 MHz	± 1.35 kHz	+16 Hz	Passed
0 °C	0	13.560344 MHz	± 1.35 kHz	+22 Hz	Passed
	2	13.560361 MHz	± 1.35 kHz	+39 Hz	Passed
	5	13.560355 MHz	± 1.35 kHz	+33 Hz	Passed
	10	13.560355 MHz	± 1.35 kHz	+33 Hz	Passed
- 10 °C	0	13.560350 MHz	± 1.35 kHz	+28 Hz	Passed
	2	13.560361 MHz	± 1.35 kHz	+39 Hz	Passed
	5	13.560355 MHz	± 1.35 kHz	+33 Hz	Passed
	10	13.560361 MHz	± 1.35 kHz	+39 Hz	Passed
- 20 °C	0	13.560322 MHz	± 1.35 kHz	0 Hz	Passed
	2	13.560333 MHz	± 1.35 kHz	+11 Hz	Passed
	5	13.560350 MHz	± 1.35 kHz	+28 Hz	Passed
	10	13.560350 MHz	± 1.35 kHz	+28 Hz	Passed

Conclusion: The maximum frequency error with a supply voltage of 3.145 V DC was +39 Hz, which is equal to an error of + 0.0003 %.

Test result: Passed

TEST EQUIPMENT USED FOR THE TEST:

22, 54, 58, 59, 61

TEST REPORT REFERENCE: E51079A Edition 1

7 TEST EQUIPMENT AND ANCILLARIES USED FOR TESTS

TEST REPORT REFERENCE: E51079A Edition 1

Emission measurement at AC mains and DC in / out ports at M4					
No.	Test equipment	Type	Manufacturer	Serial No.	PM-No
1	Shielded chamber M4	-	Siemens	B83117S1-X158	480088
2	Measuring receiver	ESAI	Rohde & Schwarz	831953/001 833181/018	480025 480026
3	LISN	NSLK8128	Schwarzbeck	8128155	480058
4	LISN	NSLK 8128-	Schwarzbeck	8128161	480138
5	AC-filter	B84299-D87-E3	Siemens	930262292	480097
6	EMI-Software	ES-K1	Rohde & Schwarz	-	480111

Radiated emission measurement at M5					
No.	Test equipment	Type	Manufacturer	Serial No.	PM-No
7	Fully anechoic chamber M5	-	Siemens	B83177-S1-X156	480073
8	Measuring receiver	ESVS30	Rohde & Schwarz	829673/012	480024
9	Controller	HD100	Deisel	100/324	480067
10	Antenna support	MA240	Deisel	228/314	480069
11	Turntable	DS412	Deisel	412/317	480070
12	Antenna	CBL6112C	Chase	2689	480327
13	EMI Software	ES-K1	Rohde & Schwarz	-	480111

Radiated emission measurement at M6					
No.	Test equipment	Type	Manufacturer	Serial No.	PM-No
14	Open area test site	-	Phoenix Test-Lab	-	480085
15	Measuring receiver	ESVS30	Rohde & Schwarz	829673/012	480024
16	Controller	HD100	Deisel	100/670	480139
17	Turntable	DS420HE	Deisel	420/620/80	480087
18	Antenna support	AS615P	Deisel	615/310	480086
19	Antenna	CBL6111 A	Chase	1643	480147
20	EMI Software	ES-K1	Rohde & Schwarz	-	480111

TEST REPORT REFERENCE: E51079A Edition 1

Radiated emission measurement at M8					
No.	Test equipment	Type	Manufacturer	Serial No.	PM-No
21	Fully anechoic chamber M8	-	Siemens	B83117-E7019-T231	480190
22	Measuring receiver	ESMI	Rohde & Schwarz	843977/001 843530/018	480179 480180
23	Measuring receiver	ESCS 30	Rohde & Schwarz	828985/014	480270
24	Controller	HD100	Deisel	100/427	480181
25	Turntable	DS420	Deisel	420/435/97	480186
26	Antenna support	AS615P	Deisel	615/310	480187
27	Antenna	CBL6112 A	Chase	2034	480185
28	EMI Software	ES-K1	Rohde & Schwarz	-	480111

Radiated emission measurement at M20					
No.	Test equipment	Type	Manufacturer	Serial No.	PM-No
29	Fully anechoic chamber M20	-	Albatross Projects	B83107-E2439-T232	480303
30	Measuring receiver	ESMI	Rohde & Schwarz	843977/001 843530/018	480179 480180
31	Measuring receiver	ESI 40	Rohde & Schwarz	100064	480355
32	Controller	HD100	Deisel	100/670	480326
33	Turntable	DS420HE	Deisel	420/620/80	480315
34	Antenna support	AS615P	Deisel	615/310	480187
35	Antenna	CBL6112 B	Chase	2688	480328
36	Antenna	3115 A	EMCO	9609-4918	480183
37	Standard Gain Horn 11.9GHz – 18GHZ	18240-20	Flann Microwave	483	480294
38	Standard Gain Horn 11.9GHz – 18GHZ	18240-20	Flann Microwave	482	480295
39	Standard Gain Horn 17.9GHz – 26.7GHZ	20240-20	Flann Microwave	411	480297
40	Standard Gain Horn 17.9GHz – 26.7GHZ	20240-20	Flann Microwave	410	480296
41	Standard Gain Horn 26.4GHz – 40.1GHZ	22240-20	Flann Microwave	469	480299

TEST REPORT REFERENCE: E51079A Edition 1

No.	Test equipment	Type	Manufacturer	Serial No.	PM-No
42	Standard Gain Horn 26.4GHz – 40.1GHZ	22240-20	Flann Microwave	468	480298
43	RF-cable No. 30	RTK 081	Rosenberger	-	410141
44	RF-cable No. 31	RTK 081	Rosenberger	-	410142
45	RF-cable 1m	KPS-1533- 400-KPS	Insulated Wire	-	480300
46	RF-cable 1m	KPS-1533- 400-KPS	Insulated Wire	-	480301
47	RF-cable 2m	KPS-1533- 400-KPS	Insulated Wire	-	480302
48	RF-cable No. 5	RTK 081	Rosenberger		410097
49	Preamplifier	JS3- 00101200- 23-5A	Miteq	681851	480337
50	Preamplifier	JS3- 12001800- 16-5A	Miteq	571667	480343
51	Preamplifier	JS3- 18002600- 20-5A	Miteq	658697	480342
52	Preamplifier	JS3- 26004000- 25-5A	Miteq	563593	480344
53	EMI Software	ES-K1	Rohde & Schwarz	-	480111

Ancillary equipment used for testing					
No.	Test equipment	Type	Manufacturer	Serial No.	PM-No
54	Power supply	TOE 8852	Toellner	51712	480233
55	Outdoor test site	-	Phoenix Test-Lab	-	480293
56	Loop antenna	HFH2-Z2	Rohde & Schwarz	832609/014	480059
57	EMI test receiver	ESPC	Rohde & Schwarz	843756/006	480150
58	Loop Antenna $\varnothing = 225$ mm	-	Phoenix Test-Lab	-	410085
59	RF-cable No. 10	RG223	Phoenix-Test-Lab	-	410102
60	AC power source / analyser	6813A	Hewlett Packard	3524A-00484	480155
61	Climatic chamber	MK 240	BINDER	05-79022	480462

All used measurement equipment was calibrated (if necessary). The calibration intervals and the calibration history will be given out on request.

TEST REPORT REFERENCE: E51079A Edition 1

8 LIST OF ANNEXES

ANNEX A	PHOTOGRAPHS OF THE TEST SET-UPS:	4 pages
	CC-239D, test set-up fully anechoic chamber	51079_b.jpg
	CC-239D, test set-up fully anechoic chamber	51079_d.jpg
	CC-239D, test set-up outdoor test site	51079_j.jpg
	CC-239D, test set-up climatic chamber	51079_f.jpg
ANNEX B	EXTERNAL PHOTOGRAPHS OF THE TEST SAMPLE:	3 pages
	CC-239D RFID cover at NOKIA 3220 mobile phone, front view	51079_5.jpg
	RFID transponder ISO 14443	51079_4.jpg
	AC / DC adaptor	51079_7.jpg
ANNEX C	INTERNAL PHOTOGRAPHS OF THE TEST SAMPLE:	3 pages
	CC-239D RFID cover and NOKIA 3220 mobile phone internal view	51079_6.jpg
	CC-239D, PCB, top view	51079_2.jpg
	CC-239D, PCB, bottom view	51079_1.jpg