


2405.5-2463.5MHz



Standard Common part for master

Capacitor
(1st priority)

No.	Part Value
1	10PF chip 50v +80-20% SMD 0603
2	20pF chip 50v +80-20% SMD 0603
3	25pF chip 50v +80-20% SMD 0603
4	1000pF chip 50v +80-20% SMD 0603
5	0.1uF chip 50V +80-20% Y5V, 50V SMD0603
6	0.1uF 25V +80-20% Y5V, PKG: Ceramic dia 6mm x 3.5
7	0.033uF 25V Y5V, PKG: dia 4mm x 3.5
8	10uF 25V +/-20% AL EL PKG:5x11mm
9	47uF 25V +/-20% AL EL PKG:5x11mm
10	100uF 25V +/-20% AL EL PKG:5x11mm
11	220uF 25V +/-20% AL EL PKG:5x11mm

Resistor:

1	10 ohm +/-5% 0603
2	100 ohm +/-5% 0603
3	1K ohm +/-5% 0603
4	4.7Kohm +/-5% 0603
5	10k ohm +/-5% 0603
6	47k ohm +/-5% 0603
7	100kohm +/-5% 0603
8	220k ohm +/-5% 0603
9	1M ohm +/-5% 0603
10	2.2M ohm +/-5% 0603

Diode:

1	IN4001PKG: DO-41 50V
2	IN4148 PKG: DO-35 50V
3	1N5817: DO-41 50V
4	BAT54 SOT23 30V

Transistor

1	S8050DNPN (1.5A)SOT-23 V: 40; W: 0.3;
2	S8550D PNP(1.5A)SOT-23 V: 40; W: 0.3;
3	S9014D NPN (1.5A)SOT-23 V: 40; W: 0.3;
4	B772 PNP A: 3; V: 40; Max. W: 1.25; PKG: TO-126;
5	D882 NPN A: 3; V: 40; Max. W: 1.25; PKG: TO-126;

Inductor

1	Choke Coil DESC: 5.6uH 10% 1/2W
---	---------------------------------

PTC

1	MF-R400-0-99
---	--------------

Non Standard parts Guide Line (2nd priority)

Using E3 value for resistor, capacitor and inductor

Standard IEC E3 Decade Value = 100, 220 & 470

Non Standard parts Guide Line (3rd priority)

Using E6 value for resistor, capacitor and inductor

Standard IEC E6 Decade value =100,150,220,330,470 & 680

MATEL MAPS All rights reserved

Size A3	Number FFL31/33/34/79	Project Name HW AI Card	Revision R07
Date 18/1/2017	MAPS Engineer Ivan Chang	Sheet of 1/1	
File : D:\project\FB\83\FFL31 sch1 main R02.SchDoc			

