

FCC PART 15C TEST REPORT FOR CERTIFICATION

On Behalf of

Jiangmen Dascom Computer Peripherals Co., Ltd.

Portable Receipt and Label Printer

Model Number: DP-541

Additional Model: DP-541a, DP-541b, DP-541c, FP-541

FCC ID: Z7ODP5410

Prepared for:	Jiangmen Dascom Computer Peripherals Co., Ltd.
	No 399, Jin Xing Road, Jiang Hai District, Jiangmen City,
	Guang Dong Province, China
Prepared By:	EST Technology Co., Ltd.
	Chilingxiang, Qishantou, Santun, Houjie, Dongguan, Guangdong, China
	Tel: 86-769-83081888-808


Report Number:	ESTE-R1712013
Date of Test:	November 22~December 01, 2017
Date of Report:	December 04, 2017

TABLE OF CONTENTS

Description	Page
TEST REPORT VERIFICATION.....	3
1. GENERAL INFORMATION	5
1.1. Description of Device (EUT)	5
2. SUMMARY OF TEST	6
2.1. Summary of test result.....	6
2.2. Test Facilities	7
2.3. Measurement uncertainty	8
2.4. Assistant equipment used for test	8
2.5. Block Diagram	8
2.6. Test mode	9
2.7. Channel List	9
2.8. Test Equipment.....	10
3 POWER LINE CONDUCTED EMISSION TEST	12
3.1 Limit	12
3.2 Test Procedure	12
3.3 Test Result	12
3.4 Test data	13
4 RADIATED EMISSION TEST	17
4.1 Limit.....	17
4.2 Block Diagram of Test setup	18
4.3 Test Procedure	19
4.4 Test Result	19
4.5 Test Data	20
5 BAND EDGE COMPLIANCE TEST	30
5.1 Limit	30
5.2 Block Diagram of Test setup	30
5.3 Test Procedure	30
5.4 Test Result	30
5.5 Test Data	31
6 6dB Bandwidth Test.....	35
6.1 Limit	35
6.2 Test Procedure	35
6.3 Test Result	35
6.4 Test Data	36
7 OUTPUT POWER TEST	38
7.1 Limit	38
7.2 Test Procedure	38
7.3 Test Result	39
7.4 Test Data	40
8 POWER SPECTRAL DENSITY TEST	42
8.1 Limit	42
8.2 Test Procedure	42
8.3 Test Result	42

8.4	Test Data	43
9	ANTENNA REQUIREMENTS	45
9.1	Limit	45
9.2	Result.....	45
10	TEST SETUP PHOTO	46
11	PHOTO EUT.....	48

EST Technology Co., Ltd.

Applicant:	Jiangmen Dascom Computer Peripherals Co., Ltd.		
Address:	No 399, Jin Xing Road, Jiang Hai District, Jiangmen City, Guang Dong Province, China		
Manufacturer:	Jiangmen Dascom Computer Peripherals Co., Ltd.		
Address:	No 399, Jin Xing Road, Jiang Hai District, Jiangmen City, Guang Dong Province, China		
E.U.T:	Portable Receipt and Label Printer		
Model Number:	DP-541		
Additional Model:	DP-541a, DP-541b, DP-541c, FP-541 (They are identical except model name only)		
Power Supply:	DC 11.1V From Battery DC 19V From Adapter Input AC 100-240V, 50/60Hz		
Test Voltage:	DC 19V From Adapter Input AC 120V/60Hz and AC 240V/60Hz		
Trade Name:	Tally/DASCOM, DASCOM, PRINTEK	Serial No.:	-----
Date of Receipt:	November 22, 2017	Date of Test:	November 22~December 01, 2017
Test Specification:	FCC Rules and Regulations Part 15 Subpart C:2017 ANSI C63.10:2013		
Test Result:	The device described above is tested by EST Technology Co., Ltd. The measurement results were contained in this test report and EST Technology Co., Ltd. was assumed full responsibility for the accuracy and completeness of these measurements. Also, this report shows that the EUT to be technically compliance with the FCC Rules and Regulations Part 15 Subpart C requirements. This report applies to above tested sample only and shall not be reproduced in part without written approval of EST Technology Co., Ltd.		
Date: December 04, 2017			
Prepared by:	Reviewed by:	Approved by:	
			
Amy / Assistant	Tony / Engineer	Iceman Hu / Manager	
Other Aspects:	None.		
Abbreviations: OK/P=passed fail/F=failed n.a/N=not applicable E.U.T=equipment under tested			
This test report is based on a single evaluation of one sample of above mentioned products ,It is not permitted to be duplicated in extracts without written approval of EST Technology Co., Ltd.			

1. GENERAL INFORMATION

1.1. Description of Device (EUT)

Product Name	:	Portable Receipt and Label Printer	
FCC ID	:	Z7ODP5410	
Model Number	:	DP-541	
Operation frequency	:	2402MHz~2480MHz	
Number of channel	:	79	40
Antenna	:	Internal antenna, 0.5 dBi gain	
		Frequency Range	2400~2483.5 MHz
Modulation	:	Dual-mode Bluetooth 4.0 BT BDR: GFSK BT EDR: $\pi/4$ -DQPSK BT EDR: 8-DPSK	Dual-mode Bluetooth 4.0 BLE: GFSK
Sample Type	:	Prototype production	

2. SUMMARY OF TEST

2.1. Summary of test result

Description of Test Item	Standard	Results
Power Line Conducted Emission	FCC Part 15: 15.207 ANSI C63.10:2013	PASS
Radiated Emission	FCC Part 15: 15.209 ANSI C63.10:2013 KDB 558074	PASS
Band Edge Compliance	FCC Part 15: 15.247 ANSI C63.10:2013 KDB 558074	PASS
6dB Bandwidth	FCC Part 15: 15.247 ANSI C63.10:2013 KDB 558074	PASS
Peak Output Power	FCC Part 15: 15.247 ANSI C63.10:2013 KDB 558074	PASS
Power Spectral Density	FCC Part 15: 15.247 ANSI C63.10:2013 KDB 558074	PASS
Antenna requirement	FCC Part 15: 15.203	PASS
Note: KDB 558074 D01 DTS Meas Guidance v04		

2.2. Test Facilities

EMC Lab	:	Certificated by CNAS, CHINA Registration No.: L5288 Date of registration: November 13, 2017 Certificated by A2LA, USA Registration No.: 4366.01 Date of registration: November 07, 2017 Certificated by FCC, USA Designation Number: CN1215 Registration No.: 722932 Date of registration: November 21, 2017 Certificated by Industry Canada Registration No.: 9405A Date of registration: December 03, 2015 Certificated by VCCI, Japan Registration No.: R-13663; C-14103 Date of registration: July 25, 2017 This Certificate is valid until: July 24, 2020 Certificated by TUV Rheinland, Germany Registration No.: UA 50195514 0001 Date of registration: February 07, 2015 Certificated by TUV/PS, Shenzhen Registration No.: SCN1017 Date of registration: January 27, 2011 Certificated by Intertek ETL SEMKO Registration No.: 2011-RTL-L2-64 Date of registration: April 28, 2011 Certificated by Nemko, Hong Kong Registration No.: 175193 Date of registration: May 4, 2011
Name of Firm	:	EST Technology Co., Ltd.
Site Location	:	Chilingxiang, Qishantou, Santun, Houjie, Dongguan, Guangdong, China

2.3. Measurement uncertainty

Test Item	Uncertainty
Uncertainty for Conduction emission test	$\pm 3.48\text{dB}$
Uncertainty for spurious emissions test (30MHz-1GHz)	$\pm 4.60\text{ dB(Polarize: H)}$
	$\pm 4.68\text{ dB(Polarize: V)}$
Uncertainty for spurious emissions test (1GHz to 18GHz)	$\pm 4.96\text{dB}$
Uncertainty for radio frequency	7×10^{-8}
Uncertainty for conducted RF Power	0.20dB
Uncertainty for Power density test	0.26dB

Note: This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

2.4. Assistant equipment used for test

2.4.1. Adapter

M/N	:	GS90A19-P1M
Manufacturer	:	MEAN WELL ENTERPRISES CO., LTD
Input	:	AC 100-240V, 50/60Hz, 2.0A
Output	:	DC 19V, 4.74A, 90W MAX

2.5. Block Diagram

For radiated emissions test: EUT was placed on a turn table, which is 0.8 (or 1.5) meter high above ground. EUT was beset into Bluetooth test mode by software before test.



(EUT: Portable Receipt and Label Printer)

2.6. Test mode

A special test software was used to control EUT work in Continuous TX mode(100% duty cycle), and select test channel, wireless mode and data rate.

Mode	Channel	Frequency
BT 4.0-BLE GFSK	Low	2402MHz
	Middle	2440MHz
	High	2480MHz

2.7. Channel List

Channel No.	Frequency (MHz)	Channel No.	Frequency (MHz)
1	2402	2	2404
3	2406	4	2408
5	2410	6	2412
7	2414	8	2416
9	2418	10	2420
11	2422	12	2424
13	2426	14	2428
15	2430	16	2432
17	2434	18	2436
19	2438	20	2440
21	2442	22	2444
23	2446	24	2448
25	2450	26	2452
27	2454	28	2456
29	2458	30	2460
31	2462	32	2464
33	2466	34	2468
35	2470	36	2472
37	2474	38	2476
39	2478	40	2480

2.8. Test Equipment

2.8.1. For conducted emission test

Equipment	Manufacturer	Model No.	Serial No.	Calibration Body	Last Cal.	Next Cal.
EMI Test Receiver	Rohde & Schwarz	ESHS30	832354	CEPREI	June 17,17	1 Year
Artificial Mains Network	Rohde & Schwarz	ENV216	101260	CEPREI	June 17,17	1 Year
Pulse Limiter	Rohde & Schwarz	ESH3-Z2	101100	CEPREI	June 17,17	1 Year
Test Software	Audix	e3-6.111221a	N/A	N/A	N/A	N/A

2.8.2. For radiated emission test(9 kHz-30MHz)

Equipment	Manufacturer	Model No.	Serial No.	Calibration Body	Last Cal.	Next Cal.
EMI Test Receiver	Rohde & Schwarz	ESR7	101780	CEPREI	June 17,17	1 Year
Active Loop Antenna	SCHWARZB ECK	FMZB1519	1519-038	CEPREI	October 08,17	1 Year
Test Software	Audix	e3-6.111221a	N/A	N/A	N/A	N/A

2.8.3. For radiated emissions test (30-1000MHz)

Equipment	Manufacturer	Model No.	Serial No.	Calibration Body	Last Cal.	Next Cal.
EMI Test Receiver	Rohde & Schwarz	ESR7	101780	CEPREI	June 17,17	1 Year
Bilog Antenna	Teseq	CBL 6111D	27090	CEPREI	June 08,17	1 Year
Test Software	Audix	e3-6.111221a	N/A	N/A	N/A	N/A

2.8.4. For radiated emission test(above 1GHz)

Equipment	Manufacturer	Model No.	Serial No.	Calibration Body	Last Cal.	Next Cal.
Horn Antenna	SCHWARZB ECK	BBHA 9120 D	BBHA912 0D1002	CEPREI	June 08,17	1 Year
Horn Antenna	SCHWARZB ECK	BBHA9170	BBHA917 0242	CEPREI	June 08,17	1 Year
Signal Amplifier	SCHWARZB ECK	BBV9718	9718-212	CEPREI	March 12,17	1 Year
Spectrum Analyzer	Rohde & Schwarz	FSV	103173	CEPREI	June 17,17	1 Year
PSA Series Spectrum Analyzer	Agilent	E4447A	MY50180 031	CEPREI	June 16,17	1 Year
Test Software	Audix	e3-6.111221a	N/A	N/A	N/A	N/A

2.8.5. For connect EUT antenna terminal test

Equipment	Manufacturer	Model No.	Serial No.	Calibration Body	Last Cal.	Next Cal.
Spectrum Analyzer	Rohde & Schwarz	FSV	103173	CEPREI	June 17,17	1 Year
Spectrum Analyzer	Agilent	E4408B	MY44211 139	CEPREI	June 17,17	1 Year

3 POWER LINE CONDUCTED EMISSION TEST

3.1 Limit

Frequency	Maximum RF Line Voltage	
	Quasi-Peak Level dB(μ V)	Average Level dB(μ V)
150kHz ~ 500kHz	66 ~ 56*	56 ~ 46*
500kHz ~ 5MHz	56	46
5MHz ~ 30MHz	60	50

Notes: 1. * Decreasing linearly with logarithm of frequency.

2. The lower limit shall apply at the transition frequencies.

3.2 Test Procedure

The EUT was placed on a non-metallic table, 80cm above the ground plane. The EUT Power connected to the power mains through a line impedance stabilization network (L.I.S.N. 1#). This provides a 50 ohm coupling impedance for the EUT (Please refer the block diagram of the test setup and photographs). The AC line are checked to find out the maximum conducted emission. In order to find the maximum emission levels, the relative positions of equipment and all of the interface cables shall be changed according to ANSI C63.10: 2013 on Conducted Emission Test.

The bandwidth of test receiver (R & S ESHS30) is set at 10kHz.

The frequency range from 150kHz to 30MHz is checked.


3.3. Test Result

PASS. (All emissions not reported below are too low against the prescribed limits.)

3.4. Test data

EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel: +86-769-83081888
Fax: +86-769-83081878



Trace: 147

Site no. : 2# Conduction Shield Room Data no. : 148

Dis. / Ant. : Temp:25.8'C Humi:54.8% Press:101.50kPa Ant. pol. : LINE

Limit : FCC PART 15B QP

Env. / Ins. : Temp:25.8'C Humi:54.8% Press:101.50kPa

Engineer : Seven

EUT : Portable Receipt and Label Printer

Power : DC 19V From Adapter Input AC 240V/60Hz

M/N : DP-541

Test Mode : TX Mode

	Freq. (MHz)	LISN Factor (dB)	Cable Loss (dB)	Reading (dBuV)	Emission Level (dBuV)	Limits (dBuV)	Margin (dB)	Remark
1	0.16	9.61	9.81	4.71	24.13	55.56	31.43	Average
2	0.16	9.61	9.81	12.71	32.13	65.56	33.43	QP
3	1.01	9.64	9.83	7.72	27.19	46.00	18.81	Average
4	1.01	9.64	9.83	10.72	30.19	56.00	25.81	QP
5	25.86	9.68	10.03	19.32	39.03	50.00	10.97	Average
6	25.86	9.68	10.03	26.32	46.03	60.00	13.97	QP

Remarks: 1. Emission Level= LISN Factor + Cable Loss + Reading.
2. If the average limit is met when using a quasi-peak detector, the EUT shall be deemed to meet both limits and measurement with average detector is unnecessary.


EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel: +86-769-83081888
Fax: +86-769-83081878

Data: 150

File: \\Emc-ce-2\Test Data\2017\RFID\IDASCOM.EM6 (154)

Date: 2017-11-30



Trace: 149

Site no. : 2# Conduction Shield Room Data no. : 150
 Dis. / Ant. : Temp:25.8'C Humi:54.8% Press:101.50kPa Ant. pol. : NEUTRAL
 Limit : FCC PART 15B QP
 Env. / Ins. : Temp:25.8'C Humi:54.8% Press:101.50kPa
 Engineer : Seven
 EUT : Portable Receipt and Label Printer
 Power : DC 19V From Adapter Input AC 240V/60Hz
 M/N : DP-541
 Test Mode : TX Mode

	Freq. (MHz)	LISN Factor (dB)	Cable Loss (dB)	Reading (dBuV)	Emission Level (dBuV)	Limits (dBuV)	Margin (dB)	Remark
1	0.15	9.47	9.81	8.31	27.59	55.78	28.19	Average
2	0.15	9.47	9.81	14.31	33.59	65.78	32.19	QP
3	0.99	9.61	9.83	5.73	25.17	46.00	20.83	Average
4	0.99	9.61	9.83	8.73	28.17	56.00	27.83	QP
5	25.86	9.81	10.03	18.39	38.23	50.00	11.77	Average
6	25.86	9.81	10.03	23.39	43.23	60.00	16.77	QP

Remarks: 1. Emission Level= LISN Factor + Cable Loss + Reading.
 2. If the average limit is met when using a quasi-peak detector,
 the EUT shall be deemed to meet both limits and measurement
 with average detector is unnecessary.


EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel: +86-769-83081888
Fax: +86-769-83081878

Data: 152

File: \\Emc-ce-2\Test Data\2017\RFID\IDASCOM.EM6 (154)

Date: 2017-11-30



Trace: 151

Site no. : 2# Conduction Shield Room Data no. : 152
 Dis. / Ant. : Temp:25.8'C Humi:54.8% Press:101.50kPa Ant. pol. : NEUTRAL
 Limit : FCC PART 15B QP
 Env. / Ins. : Temp:25.8'C Humi:54.8% Press:101.50kPa
 Engineer : Seven
 EUT : Portable Receipt and Label Printer
 Power : DC 19V From Adapter Input AC 120V/60Hz
 M/N : DP-541
 Test Mode : TX Mode

	Freq. (MHz)	LISN Factor (dB)	Cable Loss (dB)	Reading (dBUV)	Emission Level (dBUV)	Limits (dBUV)	Margin (dB)	Remark
1	0.15	9.46	9.81	1.64	20.91	55.96	35.05	Average
2	0.15	9.46	9.81	10.64	29.91	65.96	36.05	QP
3	0.96	9.61	9.82	1.39	20.82	46.00	25.18	Average
4	0.96	9.61	9.82	3.39	22.82	56.00	33.18	QP
5	26.00	9.81	10.04	12.04	31.89	50.00	18.11	Average
6	26.00	9.81	10.04	20.04	39.89	60.00	20.11	QP

Remarks: 1. Emission Level= LISN Factor + Cable Loss + Reading.
 2. If the average limit is met when using a quasi-peak detector,
 the EUT shall be deemed to meet both limits and measurement
 with average detector is unnecessary.


EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel: +86-769-83081888
Fax: +86-769-83081878

Data: 154

File: \\Emc-ce-2\Test Data\2017\RFID\IDASCOM.EM6 (154)

Date: 2017-11-30



Trace: 153

Site no. : 2# Conduction Shield Room Data no. : 154
 Dis. / Ant. : Temp:25.8'C Humi:54.8% Press:101.50kPa Ant. pol. : LINE
 Limit : FCC PART 15B QP
 Env. / Ins. : Temp:25.8'C Humi:54.8% Press:101.50kPa
 Engineer : Seven
 EUT : Portable Receipt and Label Printer
 Power : DC 19V From Adapter Input AC 120V/60Hz
 M/N : DP-541
 Test Mode : TX Mode

	Freq. (MHz)	LISN Factor (dB)	Cable Loss (dB)	Reading (dBuV)	Emission Level (dBuV)	Limits (dBuV)	Margin (dB)	Remark
1	0.15	9.61	9.81	2.96	22.38	56.00	33.62	Average
2	0.15	9.61	9.81	12.96	32.38	66.00	33.62	QP
3	0.93	9.63	9.82	0.41	19.86	46.00	26.14	Average
4	0.93	9.63	9.82	2.41	21.86	56.00	34.14	QP
5	25.86	9.68	10.03	12.34	32.05	50.00	17.95	Average
6	25.86	9.68	10.03	20.34	40.05	60.00	19.95	QP

Remarks: 1. Emission Level= LISN Factor + Cable Loss + Reading.
 2. If the average limit is met when using a quasi-peak detector,
 the EUT shall be deemed to meet both limits and measurement
 with average detector is unnecessary.

4 RADIATED EMISSION TEST

4.1 Limit

4.1.1 15.209 limits

Frequency (MHz)	Field Strength($\mu\text{V/m}$)	Distance(m)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

- Remark : (1) Emission level $\text{dB}\mu\text{V} = 20 \log \text{Emission level } \mu\text{V/m}$
 (2) The smaller limit shall apply at the cross point between two frequency bands.
 (3) Distance is the distance in meters between the measuring instrument, antenna and the closest point of any part of the device or system.


4.1.2 15.205 Restricted bands of operation

MHz	MHz	MHz	GHz
0.090 - 0.110	16.42 - 16.423	399.9 - 410	4.5 - 5.15
¹ 0.495 - 0.505	16.69475 - 16.69525	608 - 614	5.35 - 5.46
2.1735 - 2.1905	16.80425 - 16.80475	960 - 1240	7.25 - 7.75
4.125 - 4.128	25.5 - 25.67	1300 - 1427	8.025 - 8.5
4.17725 - 4.17775	37.5 - 38.25	1435 - 1626.5	9.0 - 9.2
4.20725 - 4.20775	73 - 74.6	1645.5 - 1646.5	9.3 - 9.5
6.215 - 6.218	74.8 - 75.2	1660 - 1710	10.6 - 12.7
6.26775 - 6.26825	108 - 121.94	1718.8 - 1722.2	13.25 - 13.4
6.31175 - 6.31225	123 - 138	2200 - 2300	14.47 - 14.5
8.291 - 8.294	149.9 - 150.05	2310 - 2390	15.35 - 16.2
8.362 - 8.366	156.52475 - 156.52525	2483.5 - 2500	17.7 - 21.4
8.37625 - 8.38675	156.7 - 156.9	2690 - 2900	22.01 - 23.12
8.41425 - 8.41475	162.0125 - 167.17	3260 - 3267	23.6 - 24.0
12.29 - 12.293	167.72 - 173.2	3332 - 3339	31.2 - 31.8
12.51975 - 12.52025	240 - 285	3345.8 - 3358	36.43 - 36.5
12.57675 - 12.57725	322 - 335.4	3600 - 4400	(²)


All the emissions appearing within 15.205 restricted frequency bands shall not exceed the limits shown in 15.209, all the other emissions shall be at least 20dB below the fundamental emissions, or comply with 15.209 limits.

4.2. Block Diagram of Test setup


9kHz~30MHz



30~1000MHz



Above 1GHz



4.3. Test Procedure

EUT was placed on a turn table, which is 0.8 meter high above ground for 9kHz~1000MHz test, and which is 1.5 meter high above ground for above 1GHz test. The turn table can rotate 360 degrees to determine the position of the maximum emission level. Power on the EUT and let it working in test mode, then test it. EUT is set 3 meters away from the receiving antenna, which is mounted on a antenna tower. The antenna can be moved up and down between 1 meter and 4 meters to find out the maximum emission level. Both horizontal and vertical polarization of the antenna are set on test.

The test frequency analyzer system was set to Peak Detect (300Hz RBW in 9kHz to 150kHz and 10kHz RBW in 150kHz to 30MHz) Function and Specified Bandwidth with Maximum Hold Mode.

The bandwidth of the EMI test receiver (R&S ESVS10) is set at 120kHz for frequency range from 30MHz to 1000 MHz.

The bandwidth of the Spectrum's VBW is set at 1MHz and RBW is set at 1MHz for peak emissions measurement above 1GHz and 1MHz RBW, 10Hz VBW for average emissions measure above 1GHz

PEAK detector, 1MHz/1MHz for PAEK measurement,

PEAK detector, 1MHz/10Hz for Average measurement

The frequency range from 30MHz to 10th harmonic (25GHz) are checked.

4.4. Test Result

PASS.

All the emissions from 30MHz to 25 GHz were comply with 15.209 limits.

Note: 1、 For emissions above 1GHz, if peak level comply with average limit, then the average level is deemed to comply with average limit.

- 2、 The frequency 2402MHz 、 2440MHz and 2480 MHz is fundamental frequency which no limit, the limit on plots is automatically generated by the software, it's not fundamental limit, we can't remove it.

4.5. Test Data

9 kHz – 30 MHz

Pass

Note: The amplitude of spurious emission that is attenuated by more than 20dB below the permissible limit has no need to be reported.

30-1000 MHz


EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel: +86-769-83081888
Fax: +86-769-83081878

Data: 447

File: \\Emc-966-1\test data\2017\RFID\IDASCOM-RF.EM6 (448)

Date: 2017-11-23



Site no : 1# 966 Chamber Data no. : 447
 Env. / Ins. : Temp:24.2';Humi:54%;Press:101.52kPa LINE Phase : HORIZONTAL
 Limit : FCC PART 15 B(3M)
 Engineer : Seven
 EUT : Portable Receipt and Label Printer
 Power : DC 19V From Adapter Input AC 120V/60Hz
 M/N : DP-541
 Test Mode : TX Mode

	Freq. (MHz)	ANT Factor (dB/m)	Cable Loss (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	209.450	8.82	1.54	13.66	24.02	43.50	19.48	QP
2	296.750	13.68	2.04	11.17	26.89	46.00	19.11	QP
3	395.690	15.92	2.34	9.63	27.89	46.00	18.11	QP
4	660.500	21.10	3.43	4.11	28.64	46.00	17.36	QP
5	709.970	21.30	3.53	3.71	28.54	46.00	17.46	QP
6	792.420	22.80	3.74	3.98	30.52	46.00	15.48	QP

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading.
 2. Margin= Limit - Emission Level.
 3. The emission levels that are 20dB below the official limit are not reported.


EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel: +86-769-83081888
Fax: +86-769-83081878

Data: 448

File: \\Emc-966-1\test data\2017\RF\ID\ASCOM-RF.EM6 (448)

Date: 2017-11-23



Site no : 1# 966 Chamber Data no. : 448
Env. / Ins. : Temp:24.2';Humi:54%;Press:101.52kPa LINE Phase : VERTICAL
Limit : FCC PART 15 B(3M)
Engineer : Seven
EUT : Portable Receipt and Label Printer
Power : DC 19V From Adapter Input AC 120V/60Hz
M/N : DP-541
Test Mode : TX Mode

	Freq. (MHz)	ANT Factor (dB/m)	Cable Loss (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	30.000	18.10	0.31	13.55	31.96	40.00	8.04	QP
2	395.690	15.92	2.34	4.13	22.39	46.00	23.61	QP
3	527.610	18.86	2.97	3.00	24.83	46.00	21.17	QP
4	577.080	19.64	3.13	4.85	27.62	46.00	18.38	QP
5	610.060	20.40	3.24	5.34	28.98	46.00	17.02	QP
6	709.970	21.30	3.53	6.14	30.97	46.00	15.03	QP

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading.
2. Margin= Limit - Emission Level.
3. The emission levels that are 20dB below the official limit are not reported.

1000-18000MHz


EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel: +86-769-83081888
Fax: +86-769-83081878

Data: 313

File: \\Emc-966-1\test data\2017\RFID\IDASCOM-RF-1.EM6 (350)

Date: 2017-11-26



Site no. : 1# 966 Chamber Data no. : 313
 Dis. / Ant. : 3m ANT9120D 1-18G Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : Temp:26.6';Humi:56%;Press:101.52kPa
 Engineer : Seven
 EUT : Portable Receipt and Label Printer
 Power : DC 19V From Adapter Input AC 120V/60Hz
 M/N : DP-541
 Test Mode : GFSK TX 2402MHz

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2402.00	27.35	3.21	27.25	87.40	90.71	74.00	-16.71	Peak
2	4804.00	32.06	4.67	26.93	36.06	45.86	74.00	28.14	Peak
3	7206.00	36.56	5.99	25.80	30.93	47.68	74.00	26.32	Peak
4	10146.00	39.16	9.48	25.03	22.21	45.82	74.00	28.18	Peak
5	12220.00	39.36	8.39	24.67	19.63	42.71	74.00	31.29	Peak
6	14515.00	41.17	10.20	24.32	19.02	46.07	74.00	27.93	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. Margin= Limit - Emission Level.
 3. The emission levels that are 20dB below the official limit are not reported.


EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel: +86-769-83081888
Fax: +86-769-83081878

Data: 314

File: \\Emc-966-1\test data\2017\RF\ID\ASCOM-RF-1.EM6 (350)

Date: 2017-11-26



Site no. : 1# 966 Chamber Data no. : 314
 Dis. / Ant. : 3m ANT9120D 1-18G Ant. pol. : VERTICAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : Temp:26.6';Humi:56%;Press:101.52kPa
 Engineer : Seven
 EUT : Portable Receipt and Label Printer
 Power : DC 19V From Adapter Input AC 120V/60Hz
 M/N : DP-541
 Test Mode : GFSK TX 2402MHz

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2402.00	27.35	3.21	27.25	93.68	96.99	74.00	-22.99	Peak
2	4804.00	32.06	4.67	26.93	37.91	47.71	74.00	26.29	Peak
3	7206.00	36.56	5.99	25.80	33.10	49.85	74.00	24.15	Peak
4	9636.00	38.88	7.71	25.11	21.86	43.34	74.00	30.66	Peak
5	11030.00	39.91	8.55	24.87	18.80	42.39	74.00	31.61	Peak
6	14396.00	41.30	10.18	24.34	15.78	42.92	74.00	31.08	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. Margin= Limit - Emission Level.
 3. The emission levels that are 20dB below the official limit are not reported.


EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel: +86-769-83081888
Fax: +86-769-83081878

Data: 315

File: \\Emc-966-1\test data\2017\RF\ID\ASCOM-RF-1.EM6 (350)

Date: 2017-11-26



Site no. : 1# 966 Chamber Data no. : 315
 Dis. / Ant. : 3m ANT9120D 1-18G Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : Temp:26.6';Humi:56%;Press:101.52kPa
 Engineer : Seven
 EUT : Portable Receipt and Label Printer
 Power : DC 19V From Adapter Input AC 120V/60Hz
 M/N : DP-541
 Test Mode : GFSK TX 2440MHz

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2441.00	27.48	3.26	27.24	88.83	92.33	74.00	-18.33	Peak
2	4880.00	32.18	4.73	26.92	32.96	42.95	74.00	31.05	Peak
3	7320.00	36.82	6.10	25.74	32.82	50.00	74.00	24.00	Peak
4	8684.00	37.46	6.90	25.28	25.48	44.56	74.00	29.44	Peak
5	10724.00	39.57	9.00	24.92	18.67	42.32	74.00	31.68	Peak
6	14090.00	41.61	10.14	24.39	17.38	44.74	74.00	29.26	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. Margin= Limit - Emission Level.
 3. The emission levels that are 20dB below the official limit are not reported.


EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel: +86-769-83081888
Fax: +86-769-83081878

Data: 316

File: \\Emc-966-1\test data\2017\RFID\IDASCOM-RF-1.EM6 (350)

Date: 2017-11-26



Site no. : 1# 966 Chamber Data no. : 316
Dis. / Ant. : 3m ANT9120D 1-18G Ant. pol. : VERTICAL
Limit : FCC PART 15C PEAK
Env. / Ins. : Temp:26.6';Humi:56%;Press:101.52kPa
Engineer : Seven
EUT : Portable Receipt and Label Printer
Power : DC 19V From Adapter Input AC 120V/60Hz
M/N : DP-541
Test Mode : GFSK TX 2440MHz

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2441.00	27.48	3.26	27.24	92.06	95.56	74.00	-21.56	Peak
2	4880.00	32.18	4.73	26.92	38.12	48.11	74.00	25.89	Peak
3	7320.00	36.82	6.10	25.74	31.89	49.07	74.00	24.93	Peak
4	10146.00	39.16	9.48	25.03	21.85	45.46	74.00	28.54	Peak
5	12220.00	39.36	8.39	24.67	20.17	43.25	74.00	30.75	Peak
6	13376.00	41.01	9.50	24.49	18.34	44.36	74.00	29.64	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
2. Margin= Limit - Emission Level.
3. The emission levels that are 20dB below the official limit are not reported.


EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel: +86-769-83081888
Fax: +86-769-83081878

Data: 317

File: \\Emc-966-1\test data\2017\RF\ID\ASCOM-RF-1.EM6 (350)

Date: 2017-11-26



Site no. : 1# 966 Chamber Data no. : 317
 Dis. / Ant. : 3m ANT9120D 1-18G Ant. pol. : VERTICAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : Temp:26.6';Humi:56%;Press:101.52kPa
 Engineer : Seven
 EUT : Portable Receipt and Label Printer
 Power : DC 19V From Adapter Input AC 120V/60Hz
 M/N : DP-541
 Test Mode : GFSK TX 2480MHz

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2480.00	27.56	3.29	27.24	94.40	98.01	74.00	-24.01	Peak
2	4960.00	32.34	4.80	26.90	37.64	47.88	74.00	26.12	Peak
3	7440.00	37.09	6.13	25.68	29.39	46.93	74.00	27.07	Peak
4	10180.00	39.17	9.62	25.02	21.92	45.69	74.00	28.31	Peak
5	11115.00	39.95	8.49	24.85	21.43	45.02	74.00	28.98	Peak
6	14073.00	41.63	10.14	24.39	17.11	44.49	74.00	29.51	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. Margin= Limit - Emission Level.
 3. The emission levels that are 20dB below the official limit are not reported.


EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel: +86-769-83081888
Fax: +86-769-83081878

Data: 318

File: \\Emc-966-1\test data\2017\RF\ID\ASCOM-RF-1.EM6 (350)

Date: 2017-11-26



Site no. : 1# 966 Chamber Data no. : 318
 Dis. / Ant. : 3m ANT9120D 1-18G Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : Temp:26.6';Humi:56%;Press:101.52kPa
 Engineer : Seven
 EUT : Portable Receipt and Label Printer
 Power : DC 19V From Adapter Input AC 120V/60Hz
 M/N : DP-541
 Test Mode : GFSK TX 2480MHz

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2480.00	27.56	3.29	27.24	87.42	91.03	74.00	-17.03	Peak
2	4960.00	32.34	4.80	26.90	33.94	44.18	74.00	29.82	Peak
3	7440.00	37.09	6.13	25.68	28.62	46.16	74.00	27.84	Peak
4	9245.00	38.33	7.05	25.18	25.47	45.67	74.00	28.33	Peak
5	10775.00	39.63	8.85	24.91	21.85	45.42	74.00	28.58	Peak
6	14056.00	41.65	10.13	24.39	19.06	46.45	74.00	27.55	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. Margin= Limit - Emission Level.
 3. The emission levels that are 20dB below the official limit are not reported.

18000MHz – 25000MHz

Pass


Note: The amplitude of spurious emission that is attenuated by more than 20dB below the permissible limit has no need to be reported.

5 BAND EDGE COMPLIANCE TEST

5.1 Limit

All the lower and upper band-edges emissions appearing within 2310MHz to 2390MHz and 2483.5MHz to 2500MHz restricted frequency bands shall not exceed the limits shown in 15.209, all the other emissions outside operation frequency band 2400MHz to 2483.5MHz shall be at least 20dB below the fundamental emissions, or comply with 15.209 limits

5.2 Block Diagram of Test setup



5.3 Test Procedure

1. The EUT is placed on a turntable, which is 1.5m above the ground plane and worked at highest radiated power.
2. The turntable was rotated for 360 degrees to determine the position of maximum emission level.
3. EUT is set 3m away from the receiving antenna, which is varied from 1m to 4m to find out the highest emission.
4. Set the spectrum analyzer in the following setting in order to capture the lower and upper band-edges of the emission:

Peak : RBW = 1MHz, VBW = 1MHz, Detector=PEAK detector, Sweep time = auto.

AV : RBW = 1MHz, VBW = 10Hz, Detector=PEAK detector, Sweep time = auto.

5.4 Test Result

Pass (The testing data was attached in the next pages.)


Note: 1、 For emissions above 1GHz, if peak level comply with average limit, then the average level is deemed to comply with average limit.

- 2、 The frequency 2402MHz and 2480 MHz is fundamental frequency which no limit, the limit on plots is automatically generated by the software, it's not fundamental limit, we can't remove it.

5.5 Test Data

EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel: +86-769-83081888
Fax: +86-769-83081878



Site no. : 1# 966 Chamber Data no. : 319
 Dis. / Ant. : 3m ANT9120D 1-18G Ant. pol. : VERTICAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : Temp:26.6'; Humi:56%; Press:101.52kPa
 Engineer : Seven
 EUT : Portable Receipt and Label Printer
 Power : DC 19V From Adapter Input AC 120V/60Hz
 M/N : DP-541
 Test Mode : GFSK TX 2402MHz

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2390.00	27.35	3.21	27.25	29.51	32.82	74.00	41.18	Peak
2	2400.00	27.35	3.21	27.25	35.78	39.09	74.00	34.91	Peak
3	2402.08	27.35	3.21	27.25	93.42	96.73	74.00	-22.73	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. Margin= Limit - Emission Level.
 3. The emission levels that are 20dB below the official limit are not reported.


EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel: +86-769-83081888
Fax: +86-769-83081878

Data: 320

File: \\Emc-966-1\test data\2017\RFID\ASCOM-RF-1.EM6 (350)

Date: 2017-11-26



Site no. : 1# 966 Chamber Data no. : 320
 Dis. / Ant. : 3m ANT9120D 1-18G Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : Temp:26.6';Humi:56%;Press:101.52kPa
 Engineer : Seven
 EUT : Portable Receipt and Label Printer
 Power : DC 19V From Adapter Input AC 120V/60Hz
 M/N : DP-541
 Test Mode : GFSK TX 2402MHz

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBUV)	Emission Level (dBUV/m)	Limits (dBUV/m)	Margin (dB)	Remark
1	2390.00	27.35	3.21	27.25	29.06	32.37	74.00	41.63	Peak
2	2400.00	27.35	3.21	27.25	30.39	33.70	74.00	40.30	Peak
3	2402.08	27.35	3.21	27.25	86.08	89.39	74.00	-15.39	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. Margin= Limit - Emission Level.
 3. The emission levels that are 20dB below the official limit are not reported.


EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel: +86-769-83081888
Fax: +86-769-83081878

Data: 321

File: \\Emc-966-1\test data\2017\RFID\ASCOM-RF-1.EM6 (350)

Date: 2017-11-26



Site no. : 1# 966 Chamber Data no. : 321
Dis. / Ant. : 3m ANT9120D 1-18G Ant. pol. : HORIZONTAL
Limit : FCC PART 15C PEAK
Env. / Ins. : Temp:26.6';Humi:56%;Press:101.52kPa
Engineer : Seven
EUT : Portable Receipt and Label Printer
Power : DC 19V From Adapter Input AC 120V/60Hz
M/N : DP-541
Test Mode : GFSK TX 2480MHz

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2480.05	27.56	3.29	27.24	85.79	89.40	74.00	-15.40	Peak
2	2483.50	27.56	3.29	27.24	30.11	33.72	74.00	40.28	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
2. Margin= Limit - Emission Level.
3. The emission levels that are 20dB below the official limit are not reported.


EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel: +86-769-83081888
Fax: +86-769-83081878

Data: 322

File: \\Emc-966-1\test data\2017\RFID\ASCOM-RF-1.EM6 (350)

Date: 2017-11-26



Site no. : 1# 966 Chamber Data no. : 322
 Dis. / Ant. : 3m ANT9120D 1-18G Ant. pol. : VERTICAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : Temp:26.6';Humi:56%;Press:101.52kPa
 Engineer : Seven
 EUT : Portable Receipt and Label Printer
 Power : DC 19V From Adapter Input AC 120V/60Hz
 M/N : DP-541
 Test Mode : GFSK TX 2480MHz

	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Amp Factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2480.08	27.56	3.29	27.24	94.00	97.61	74.00	-23.61	Peak
2	2483.50	27.56	3.29	27.24	36.12	39.73	74.00	34.27	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss - Amp Factor + Reading.
 2. Margin= Limit - Emission Level.
 3. The emission levels that are 20dB below the official limit are not reported.

6 6dB Bandwidth Test

6.1 Limit

For direct sequence systems, the minimum 6dB bandwidth shall be at least 500kHz

6.2 Test Procedure


- 1, The transmitter output (antenna port) was connected to the spectrum analyzer. Connect EUT antenna terminal to the spectrum analyzer with a low loss SMA cable.
- 2, Follow the test procedure as described in KDB 558074
 - (1). Set resolution bandwidth (RBW) = 100 kHz.
 - (2). Set the video bandwidth (VBW) $\geq 3 \times$ RBW.
 - (3). Detector = Peak.
 - (4). Trace mode = max hold.
 - (5). Sweep = auto couple.
 - (6). Allow the trace to stabilize.
 - (7). Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

6.3 Test Result


EUT: Portable Receipt and Label Printer			
M/N: DP-541			
Test date: 2017.11.23		Test site: RF Site	Tested by: Seven
Test Mode	CH	6dB bandwidth (MHz)	Limit (KHz)
BT 4.0-BLE GFSK	CH1	0.748	>500
	CH20	0.731	>500
	CH40	0.751	>500
Conclusion : PASS			

6.4 Test Data


Test Mode: BT 4.0-BLE GFSK 2402MHz



Test Mode: BT 4.0-BLE GFSK 2440MHz



Test Mode: BT 4.0-BLE GFSK 2480MHz



7 OUTPUT POWER TEST

7.1 Limit

For systems using digital modulation in the 2400—2483.5MHz, The Peak out put Power shall not exceed 1W(30dBm)

7.2 Test Procedure

- 1, The transmitter output (antenna port) was connected to the spectrum analyzer. Connect EUT antenna terminal to the spectrum analyzer with a low loss SMA cable.
- 2, Follow the test procedure as described in KDB 558074
 - (1). Set the RBW $\geq$ DTS bandwidth.
 - (2). Set VBW $\geq$ 3 x RBW.
 - (3). Set span $\geq$ 3 x RBW.
 - (4). Sweep time = auto couple.
 - (5). Detector = peak.
 - (6). Trace mode = max hold.
 - (7). Allow trace to fully stabilize.
 - (8). Use peak marker function to determine the peak amplitude level.


Note: The cable loss and attenuator loss were offset into measure device as an amplitude offset.

7.3 Test Result


EUT: Portable Receipt and Label Printer			
M/N: DP-541			
Test date: 2017.11.23		Test site: RF Site	Tested by: Seven
Pass			
Test Mode	CH	Peak output Power (dBm)	Limit (dBm)
BT 4.0-BLE GFSK	CH1	4.960	30
	CH20	6.230	30
	CH40	6.810	30
Conclusion : PASS			

7.4 Test Data


Test Mode: BT 4.0-BLE GFSK 2402MHz



Test Mode: BT 4.0-BLE GFSK 2440MHz



Test Mode: BT 4.0-BLE GFSK 2480MHz



8 POWER SPECTRAL DENSITY TEST

8.1 Limit

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8dBm in any 3kHz band during any time interval of continuous transmission.

8.2 Test Procedure


- 1, The transmitter output (antenna port) was connected to the spectrum analyzer. Connect EUT antenna terminal to the spectrum analyzer with a low loss SMA cable.
- 2, Follow the test procedure as described in KDB 558074
 - (1). Set analyzer center frequency to DTS channel center frequency.
 - (2). Set the span to 1.5 times the DTS bandwidth.
 - (3). Set the RBW to: $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$.
 - (4). Set the VBW $\geq 3 \text{ RBW}$.
 - (5). Detector = peak.
 - (6). Sweep time = auto couple.
 - (7). Trace mode = max hold.
 - (8). Allow trace to fully stabilize.
 - (9). Use the peak marker function to determine the maximum amplitude level.
 - (10). If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

8.3 Test Result


EUT: Portable Receipt and Label Printer			
M/N: DP-541			
Test date: 2017.11.23		Test site: RF Site	Tested by: Viking
Pass			
Test Mode	CH	Power density (dBm/3kHz)	Limit (dBm/3kHz)
BT 4.0-BLE GFSK	CH1	-9.469	8
	CH20	-8.034	8
	CH40	-7.542	8
Conclusion : PASS			

8.4 Test Data


Test Mode: BT 4.0-BLE GFSK 2402MHz



Test Mode: BT 4.0-BLE GFSK 2440MHz



Test Mode: BT 4.0-BLE GFSK 2480MHz



9 ANTENNA REQUIREMENTS

9.1 Limit


For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. And according to FCC 47 CFR Section 15.247 (b), if transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

9.2 Result


The antennas used for this product are Internal antenna and that no antenna other than that furnished by the responsible party shall be used with the device, the maximum peak gain of the transmit antenna is only 0.5 dBi.

10 TEST SETUP PHOTO

Conducted Test



Radiated Test (30-1000 MHz)



Radiated Test (Above 1GHz)



11PHOTO EUT

External Photos

M/N: DP-541



External Photos
M/N: DP-541



External Photos
M/N: DP-541



External Photos
M/N: DP-541



External Photos Adapter



Internal Photos
M/N: DP-541





Internal Photos M/N: DP-541





Internal Photos
M/N: DP-541



Internal Photos
M/N: DP-541




Internal Photos
M/N: DP-541



Bluetooth
Antenna

Internal Photos
M/N: DP-541



Internal Photos
M/N: DP-541

