

TEST REPORT

Product Name : TWS Bluetooth headset
Brand Mark : N/A
Model No. : TG31
FCC ID : 2A2ISTG31
Report Number : BLA-EMC-202106-A0502
Date of Sample Receipt : 2021/6/1
Date of Test : 2021/6/2 to 2021/6/16
Date of Issue : 2021/7/12
Test Standard : 47 CFR Part 15, Subpart C 15.247
Test Result : Pass

Prepared for:

Topalong Intelligent Technology (dongguan) Co.,Ltd
302 Room, 3rd Building, No.7 of Xinhua Road, Shijing Stech park,
Dongcheng district, Dongguan city, Guangdong province, PRC

Prepared by:

BlueAsia of Technical Services(Shenzhen) Co.,Ltd.
Building C, No. 107, Shihuan Road, Shiyuan Sub-District, Baoan District,
Shenzhen, Guangdong Province, China
TEL: +86-755-23059481

Compiled by:

Charlie

Review by:

Sueels

Approved by:

Jamen Li

Date: 2021/7/12



REPORT REVISE RECORD

| Version No. | Date | Description |
|-------------|-----------|-------------|
| 00 | 2021/7/12 | Original |

BlueAsia

TABLE OF CONTENTS

| | | |
|----------|---|-----------|
| 1 | TEST SUMMARY | 5 |
| 2 | GENERAL INFORMATION | 6 |
| 3 | GENERAL DESCRIPTION OF E.U.T. | 6 |
| 4 | TEST ENVIRONMENT | 7 |
| 5 | TEST MODE | 7 |
| 6 | MEASUREMENT UNCERTAINTY | 7 |
| 7 | DESCRIPTION OF SUPPORT UNIT..... | 8 |
| 8 | LABORATORY LOCATION..... | 8 |
| 9 | TEST INSTRUMENTS LIST | 9 |
| 1 | ANTENNA REQUIREMENT | 13 |
| 1.1 | CONCLUSION | 13 |
| 2 | CONDUCTED SPURIOUS EMISSIONS | 14 |
| 2.1 | LIMITS | 14 |
| 2.2 | BLOCK DIAGRAM OF TEST SETUP | 14 |
| 2.3 | TEST DATA | 15 |
| 3 | CONDUCTED PEAK OUTPUT POWER | 16 |
| 3.1 | LIMITS | 16 |
| 3.2 | BLOCK DIAGRAM OF TEST SETUP | 16 |
| 3.3 | TEST DATA | 17 |
| 4 | CONDUCTED EMISSIONS AT AC POWER LINE (150KHZ-30MHZ)..... | 18 |
| 4.1 | LIMITS | 18 |
| 4.2 | BLOCK DIAGRAM OF TEST SETUP | 18 |
| 4.3 | PROCEDURE | 18 |
| 4.4 | TEST DATA | 20 |
| 5 | RADIATED SPURIOUS EMISSIONS..... | 22 |
| 5.1 | LIMITS | 22 |
| 5.2 | BLOCK DIAGRAM OF TEST SETUP | 23 |
| 5.3 | PROCEDURE | 23 |
| 5.4 | TEST DATA | 25 |

| | | |
|-----------|---|-----------|
| 6 | RADIATED EMISSIONS WHICH FALL IN THE RESTRICTED BANDS..... | 33 |
| 6.1 | LIMITS | 33 |
| 6.2 | BLOCK DIAGRAM OF TEST SETUP | 34 |
| 6.3 | PROCEDURE | 34 |
| 6.4 | TEST DATA | 36 |
| 7 | CONDUCTED BAND EDGES MEASUREMENT..... | 40 |
| 7.1 | LIMITS | 40 |
| 7.2 | BLOCK DIAGRAM OF TEST SETUP | 40 |
| 7.3 | TEST DATA | 41 |
| 8 | DWELL TIME..... | 42 |
| 8.1 | LIMITS | 42 |
| 8.2 | BLOCK DIAGRAM OF TEST SETUP | 42 |
| 8.3 | TEST DATA | 43 |
| 9 | HOPPING CHANNEL NUMBER | 44 |
| 9.1 | LIMITS | 44 |
| 9.2 | BLOCK DIAGRAM OF TEST SETUP | 44 |
| 9.3 | TEST DATA | 44 |
| 10 | CARRIER FREQUENCIES SEPARATION | 45 |
| 10.1 | LIMITS | 45 |
| 10.2 | BLOCK DIAGRAM OF TEST SETUP | 45 |
| 10.3 | TEST DATA..... | 45 |
| 11 | 20DB BANDWIDTH..... | 46 |
| 11.1 | BLOCK DIAGRAM OF TEST SETUP | 46 |
| 11.2 | TEST DATA..... | 46 |
| 12 | APPENDIX..... | 47 |
| | APPENDIX A: PHOTOGRAPHS OF TEST SETUP | 93 |
| | APPENDIX B: PHOTOGRAPHS OF EUT | 95 |

1 TEST SUMMARY

| Test item | Test Requirement | Test Method | Class/Severity | Result |
|---|----------------------------------|--|--|--------|
| Antenna Requirement | 47 CFR Part 15, Subpart C 15.247 | N/A | 47 CFR Part 15, Subpart C 15.203 & 15.247(c) | Pass |
| Conducted Spurious Emissions | 47 CFR Part 15, Subpart C 15.247 | ANSI C63.10 (2013) Section 7.8.6 & Section 11.11 | 47 CFR Part 15, Subpart C 15.247(d) | Pass |
| Conducted Peak Output Power | 47 CFR Part 15, Subpart C 15.247 | ANSI C63.10 (2013) Section 7.8.5 | 47 CFR Part 15, Subpart C 15.247(b)(3) | Pass |
| Conducted Emissions at AC Power Line (150kHz-30MHz) | 47 CFR Part 15, Subpart C 15.247 | ANSI C63.10 (2013) Section 6.2 | 47 CFR Part 15, Subpart C 15.207 | Pass |
| Radiated Spurious Emissions | 47 CFR Part 15, Subpart C 15.247 | ANSI C63.10 (2013) Section 6.4,6.5,6.6 | 47 CFR Part 15, Subpart C 15.209 & 15.247(d) | Pass |
| Radiated Emissions which fall in the restricted bands | 47 CFR Part 15, Subpart C 15.247 | ANSI C63.10 (2013) Section 6.10.5 | 47 CFR Part 15, Subpart C 15.209 & 15.247(d) | Pass |
| Conducted Band Edges Measurement | 47 CFR Part 15, Subpart C 15.247 | ANSI C63.10 (2013) Section 7.8.8 & Section 11.13.3.2 | 47 CFR Part 15, Subpart C 15.247(d) | Pass |
| Dwell Time | 47 CFR Part 15, Subpart C 15.247 | ANSI C63.10 (2013) Section 7.8.4 | 47 CFR Part 15, Subpart C 15.247a(1)(iii) | Pass |
| Hopping Channel Number | 47 CFR Part 15, Subpart C 15.247 | ANSI C63.10 (2013) Section 7.8.3 | 47 CFR Part 15, Subpart C 15.247a(1)(iii) | Pass |
| Carrier Frequencies Separation | 47 CFR Part 15, Subpart C 15.247 | ANSI C63.10 (2013) Section 7.8.2 | 47 CFR Part 15, Subpart C 15.247a(1) | Pass |
| 20dB Bandwidth | 47 CFR Part 15, Subpart C 15.247 | ANSI C63.10 (2013) Section 7.8.7 | 47 CFR Part 15, Subpart C 15.247(a)(1) | Pass |

2 GENERAL INFORMATION

| | |
|-----------------------|---|
| Applicant | Topalong Intelligent Technology (dongguan) Co.,Ltd |
| Address | 302 Room, 3rd Building, No.7 of Xinhua Road, Shijing Stech park, Dongcheng district, Dongguan city, Guangdong province, PRC |
| Manufacturer | Topalong Intelligent Technology (dongguan) Co.,Ltd |
| Address | 302 Room, 3rd Building, No.7 of Xinhua Road, Shijing Stech park, Dongcheng district, Dongguan city, Guangdong province, PRC |
| Factory | Topalong Intelligent Technology (dongguan) Co.,Ltd |
| Address | 302 Room, 3rd Building, No.7 of Xinhua Road, Shijing Stech park, Dongcheng district, Dongguan city, Guangdong province, PRC |
| Product Name | TWS Bluetooth headset |
| Test Model No. | TG31 |

3 GENERAL DESCRIPTION OF E.U.T.

| | |
|-----------------------------|--|
| Hardware Version | TG31LMBP-V01/ TG31RMBP-V01 |
| Software Version | PAU1606FB-S1R1(G01)3239@AW_L_20210513_TG31_YT_V10_E120 PAU1606FB-S1R1(G01)3239@AW_R_20210513_TG31_YT_V10_106C |
| Operation Frequency: | 2402MHz-2480MHz |
| Modulation Type: | GFSK, $\pi/4$ DQPSK, 8DPSK |
| Channel Spacing: | 1MHz |
| Number of Channels: | 79 |
| Antenna Type: | chip Antenna |
| Antenna Gain: | 0 dBi(Provided by the applicant) |

4 TEST ENVIRONMENT

| Environment | Temperature | Voltage |
|-------------|---------------|-------------------------|
| Normal | 25°C | DC3.7V |
| Extreme | -20°C ~ +55°C | Low 3.5Vdc, High 4.2Vdc |

5 TEST MODE

| TEST MODE | TEST MODE DESCRIPTION |
|--|---|
| Transmitting mode | Keep the EUT in continuously transmitting mode with modulation. (hopping and non hopping mode all have been tested, non hopping mode is worse case for RE) |
| Remark: Full battery is used during all test except ac conducted emission, DH1,DH3, DH5 all have been tested, during the test, GFSK, Pi/4QPSK, 8-DPSK modulation were all pre-scanned Only the 8-DPSK, of the worst mode would be recorded in this report. | |

6 MEASUREMENT UNCERTAINTY

| Parameter | Expanded Uncertainty (Confidence of 95%) |
|--|--|
| Radiated Emission(9kHz-30MHz) | ±4.34dB |
| Radiated Emission(30Mz-1000MHz) | ±4.24dB |
| Radiated Emission(1GHz-18GHz) | ±4.68dB |
| AC Power Line Conducted Emission(150kHz-30MHz) | ±3.45dB |

7 DESCRIPTION OF SUPPORT UNIT

| Device Type | Manufacturer | Model Name | Serial No. | Remark |
|-------------|--------------|------------|------------|--------|
| PC | HASEE | K610D | N/A | N/A |

8 LABORATORY LOCATION

All tests were performed at:
BlueAsia of Technical Services(Shenzhen) Co., Ltd.
Building C, No. 107, Shihuan Road, Shiyan Sub-District, Baoan District, Shenzhen, Guangdong Province, China
Telephone: TEL: +86-755-28682673 FAX: +86-755-28682673
No tests were sub-contracted.

9 TEST INSTRUMENTS LIST

| Test Equipment Of Conducted Spurious Emissions | | | | | |
|--|--------------|--------|------------|------------|------------|
| Equipment | Manufacturer | Model | S/N | Cal.Date | Cal.Due |
| Spectrum | R&S | FSP40 | 100817 | 2020/10/12 | 2021/10/11 |
| Spectrum | Agilent | N9020A | MY49100060 | 2020/10/12 | 2021/10/11 |
| Signal Generator | Agilent | N5182A | MY49060650 | 2020/10/12 | 2021/10/11 |
| Signal Generator | Agilent | E8257D | MY44320250 | 2020/10/12 | 2021/10/11 |

| Test Equipment Of Conducted Peak Output Power | | | | | |
|---|--------------|--------|------------|------------|------------|
| Equipment | Manufacturer | Model | S/N | Cal.Date | Cal.Due |
| Spectrum | R&S | FSP40 | 100817 | 2020/10/12 | 2021/10/11 |
| Spectrum | Agilent | N9020A | MY49100060 | 2020/10/12 | 2021/10/11 |
| Signal Generator | Agilent | N5182A | MY49060650 | 2020/10/12 | 2021/10/11 |
| Signal Generator | Agilent | E8257D | MY44320250 | 2020/10/12 | 2021/10/11 |

| Test Equipment Of Conducted Emissions at AC Power Line (150kHz-30MHz) | | | | | |
|---|--------------|---------|---------------|------------|------------|
| Equipment | Manufacturer | Model | S/N | Cal.Date | Cal.Due |
| Shield room | SKET | 833 | N/A | 2020/11/25 | 2023/11/24 |
| Receiver | R&S | ESPI3 | 101082 | 2020/10/12 | 2021/10/11 |
| LISN | R&S | ENV216 | 3560.6550.15 | 2020/10/12 | 2021/10/11 |
| LISN | AT | AT166-2 | AKK1806000003 | 2020/10/12 | 2021/10/11 |
| EMI software | EZ | EZ-EMC | EEMC-3A1 | N/A | N/A |

| Test Equipment Of Radiated Spurious Emissions | | | | | |
|---|--|--|--|--|--|
|---|--|--|--|--|--|

| Equipment | Manufacturer | Model | S/N | Cal.Date | Cal.Due |
|-------------------|--------------|---------------|------------------|------------|------------|
| Chamber | SKET | 966 | N/A | 2020/11/10 | 2023/11/9 |
| Spectrum | R&S | FSP40 | 100817 | 2020/10/12 | 2021/10/11 |
| Receiver | R&S | ESR7 | 101199 | 2020/10/12 | 2021/10/11 |
| broadband Antenna | Schwarzbeck | VULB9168 | 00836 P:00227 | 2020/9/26 | 2022/9/25 |
| Horn Antenna | Schwarzbeck | 9120D | 01892 P:00331 | 2020/9/26 | 2022/9/25 |
| Amplifier | SKET | PA-000318G-45 | N/A | 2020/10/16 | 2021/10/15 |
| EMI software | EZ | EZ-EMC | EEMC-3A1 | N/A | N/A |
| Loop antenna | SCHNARZBECK | FMZB1519B | 00102 | 2020/9/26 | 2022/9/25 |
| Controller | SKET | N/A | N/A | N/A | N/A |
| Coaxial Cable | BlueAsia | BLA-XC-02 | N/A | N/A | N/A |
| Coaxial Cable | BlueAsia | BLA-XC-03 | N/A | N/A | N/A |
| Coaxial Cable | BlueAsia | BLA-XC-01 | N/A | N/A | N/A |

Test Equipment Of Radiated Emissions which fall in the restricted bands

| Equipment | Manufacturer | Model | S/N | Cal.Date | Cal.Due |
|-------------------|--------------|---------------|------------------|------------|------------|
| Chamber | SKET | 966 | N/A | 2020/11/10 | 2023/11/9 |
| Spectrum | R&S | FSP40 | 100817 | 2020/10/12 | 2021/10/11 |
| Receiver | R&S | ESR7 | 101199 | 2020/10/12 | 2021/10/11 |
| broadband Antenna | Schwarzbeck | VULB9168 | 00836 P:00227 | 2020/9/26 | 2022/9/25 |
| Horn Antenna | Schwarzbeck | 9120D | 01892 P:00331 | 2020/9/26 | 2022/9/25 |
| Amplifier | SKET | PA-000318G-45 | N/A | 2020/10/16 | 2021/10/15 |

| | | | | | |
|---------------|-------------|-----------|----------|-----------|-----------|
| EMI software | EZ | EZ-EMC | EEMC-3A1 | N/A | N/A |
| Loop antenna | SCHNARZBECK | FMZB1519B | 00102 | 2020/9/26 | 2022/9/25 |
| Controller | SKET | N/A | N/A | N/A | N/A |
| Coaxial Cable | BlueAsia | BLA-XC-02 | N/A | N/A | N/A |
| Coaxial Cable | BlueAsia | BLA-XC-03 | N/A | N/A | N/A |
| Coaxial Cable | BlueAsia | BLA-XC-01 | N/A | N/A | N/A |

Test Equipment Of Conducted Band Edges Measurement

| Equipment | Manufacturer | Model | S/N | Cal.Date | Cal.Due |
|------------------|--------------|--------|------------|------------|------------|
| Spectrum | R&S | FSP40 | 100817 | 2020/10/12 | 2021/10/11 |
| Spectrum | Agilent | N9020A | MY49100060 | 2020/10/12 | 2021/10/11 |
| Signal Generator | Agilent | N5182A | MY49060650 | 2020/10/12 | 2021/10/11 |
| Signal Generator | Agilent | E8257D | MY44320250 | 2020/10/12 | 2021/10/11 |

Test Equipment Of Dwell Time

| Equipment | Manufacturer | Model | S/N | Cal.Date | Cal.Due |
|------------------|--------------|--------|------------|------------|------------|
| Spectrum | R&S | FSP40 | 100817 | 2020/10/12 | 2021/10/11 |
| Spectrum | Agilent | N9020A | MY49100060 | 2020/10/12 | 2021/10/11 |
| Signal Generator | Agilent | N5182A | MY49060650 | 2020/10/12 | 2021/10/11 |
| Signal Generator | Agilent | E8257D | MY44320250 | 2020/10/12 | 2021/10/11 |

Test Equipment Of Hopping Channel Number

| Equipment | Manufacturer | Model | S/N | Cal.Date | Cal.Due |
|------------------|--------------|--------|------------|------------|------------|
| Spectrum | R&S | FSP40 | 100817 | 2020/10/12 | 2021/10/11 |
| Spectrum | Agilent | N9020A | MY49100060 | 2020/10/12 | 2021/10/11 |
| Signal Generator | Agilent | N5182A | MY49060650 | 2020/10/12 | 2021/10/11 |

| | | | | | |
|------------------|---------|--------|------------|------------|------------|
| Signal Generator | Agilent | E8257D | MY44320250 | 2020/10/12 | 2021/10/11 |
|------------------|---------|--------|------------|------------|------------|

Test Equipment Of Carrier Frequencies Separation

| Equipment | Manufacturer | Model | S/N | Cal.Date | Cal.Due |
|------------------|--------------|--------|------------|------------|------------|
| Spectrum | R&S | FSP40 | 100817 | 2020/10/12 | 2021/10/11 |
| Spectrum | Agilent | N9020A | MY49100060 | 2020/10/12 | 2021/10/11 |
| Signal Generator | Agilent | N5182A | MY49060650 | 2020/10/12 | 2021/10/11 |
| Signal Generator | Agilent | E8257D | MY44320250 | 2020/10/12 | 2021/10/11 |

Test Equipment Of 20dB Bandwidth

| Equipment | Manufacturer | Model | S/N | Cal.Date | Cal.Due |
|------------------|--------------|--------|------------|------------|------------|
| Spectrum | R&S | FSP40 | 100817 | 2020/10/12 | 2021/10/11 |
| Spectrum | Agilent | N9020A | MY49100060 | 2020/10/12 | 2021/10/11 |
| Signal Generator | Agilent | N5182A | MY49060650 | 2020/10/12 | 2021/10/11 |
| Signal Generator | Agilent | E8257D | MY44320250 | 2020/10/12 | 2021/10/11 |

1 ANTENNA REQUIREMENT

| | |
|---------------|----------------------------------|
| Test Standard | 47 CFR Part 15, Subpart C 15.247 |
| Test Method | N/A |


1.1 CONCLUSION

Standard Requirement:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit permanently attached antenna or of an so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

EUT Antenna:

The antenna is integrated on the main PCB and no consideration of replacement. The best case gain of the antenna is 0 dBi.




2 CONDUCTED SPURIOUS EMISSIONS

| | |
|-------------------------------|--|
| Test Standard | 47 CFR Part 15, Subpart C 15.247 |
| Test Method | ANSI C63.10 (2013) Section 7.8.6 & Section 11.11 |
| Test Mode (Pre-Scan) | TX |
| Test Mode (Final Test) | TX |
| Tester | Charlie |
| Temperature | 25°C |
| Humidity | 52% |

2.1 LIMITS

| | |
|---------------|--|
| Limit: | In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)). |
|---------------|--|

2.2 BLOCK DIAGRAM OF TEST SETUP



2.3 TEST DATA

Pass: Please Refer To Appendix: For Details

BlueAsia


3 CONDUCTED PEAK OUTPUT POWER

| | |
|------------------------|----------------------------------|
| Test Standard | 47 CFR Part 15, Subpart C 15.247 |
| Test Method | ANSI C63.10 (2013) Section 7.8.5 |
| Test Mode (Pre-Scan) | TX |
| Test Mode (Final Test) | TX |
| Tester | Charlie |
| Temperature | 25°C |
| Humidity | 52% |

3.1 LIMITS

| Frequency range(MHz) | Output power of the intentional radiator(watt) |
|----------------------|--|
| 902-928 | 1 for ≥ 50 hopping channels |
| | 0.25 for $25 \leq \text{hopping channels} < 50$ |
| | 1 for digital modulation |
| 2400-2483.5 | 1 for ≥ 75 non-overlapping hopping channels |
| | 0.125 for all other frequency hopping systems |
| | 1 for digital modulation |
| 5725-5850 | 1 for frequency hopping systems and digital modulation |

3.2 BLOCK DIAGRAM OF TEST SETUP



3.3 TEST DATA

Pass: Please Refer To Appendix: For Details

BlueAsia

4 CONDUCTED EMISSIONS AT AC POWER LINE (150KHZ-30MHZ)


| | |
|------------------------|----------------------------------|
| Test Standard | 47 CFR Part 15, Subpart C 15.247 |
| Test Method | ANSI C63.10 (2013) Section 6.2 |
| Test Mode (Pre-Scan) | TX |
| Test Mode (Final Test) | TX |
| Tester | Charlie |
| Temperature | 25°C |
| Humidity | 52% |

4.1 LIMITS

| Frequency of emission(MHz) | Conducted limit(dBμV) | |
|----------------------------|-----------------------|-----------|
| | Quasi-peak | Average |
| 0.15-0.5 | 66 to 56* | 56 to 46* |
| 0.5-5 | 56 | 46 |
| 5-30 | 60 | 50 |

*Decreases with the logarithm of the frequency.

4.2 BLOCK DIAGRAM OF TEST SETUP



4.3 PROCEDURE


- 1) The mains terminal disturbance voltage test was conducted in a shielded room.
- 2) The EUT was connected to AC power source through a LISN 1 (Line Impedance Stabilization Network) which provides a 50ohm/50H + 5ohm linear impedance. The power cables of all other units of the EUT were connected to a second LISN 2, which was bonded to the ground reference plane in the same way as the LISN 1 for the unit being measured. A multiple socket outlet strip was used to connect multiple power cables to a single LISN provided the rating of the LISN was not exceeded.

- 3) The tabletop EUT was placed upon a non-metallic table 0.8m above the ground reference plane. And for floor-standing arrangement, the EUT was placed on the horizontal ground reference plane,
- 4) The test was performed with a vertical ground reference plane. The rear of the EUT shall be 0.4 m from the vertical ground reference plane. The vertical ground reference plane was bonded to the horizontal ground reference plane. The LISN 1 was placed 0.8 m from the boundary of the unit under test and bonded to a ground reference plane for LISNs mounted on top of the ground reference plane. This distance was between the closest points of the LISN 1 and the EUT. All other units of the EUT and associated equipment was at least 0.8 m from the LISN 2.
- 5) In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.10 on conducted measurement.

Remark: $LISN = Read\ Level + Cable\ Loss + LISN\ Factor$

4.4 TEST DATA

[TestMode: TX]; [Line: Line][Power:AC120V/60Hz]




*:Maximum data x:Over limit !:over margin

⟨Reference Only

Test Result: Pass

[TestMode: TX]; [Line: Nutral][Power:AC120V/60Hz]

Conducted Emission Measurement



Site: Phase: **N** Temperature:
Limit: FCC Class B Conduction(QP) Power: AC120V/60Hz Humidity: %
EUT: TWS Bluetooth headset
M/N: TG31
Mode: BT mode
Note:

| No. | Mk. | Freq. | Reading Level | Correct Factor | Measurement | Limit | Over | | |
|-----|-----|--------|---------------|----------------|-------------|-------|--------|----------|---------|
| | | MHz | dBuV | dB | dBuV | dBuV | dB | Detector | Comment |
| 1 | | 0.5060 | 35.90 | 9.79 | 45.69 | 56.00 | -10.31 | QP | |
| 2 | * | 0.5060 | 30.16 | 9.79 | 39.95 | 46.00 | -6.05 | AVG | |
| 3 | | 0.8780 | 34.38 | 9.83 | 44.21 | 56.00 | -11.79 | QP | |
| 4 | | 0.8780 | 27.83 | 9.83 | 37.66 | 46.00 | -8.34 | AVG | |
| 5 | | 0.9660 | 31.74 | 9.84 | 41.58 | 56.00 | -14.42 | QP | |
| 6 | | 0.9660 | 25.04 | 9.84 | 34.88 | 46.00 | -11.12 | AVG | |
| 7 | | 1.4780 | 28.71 | 9.85 | 38.56 | 56.00 | -17.44 | QP | |
| 8 | | 1.4780 | 22.69 | 9.85 | 32.54 | 46.00 | -13.46 | AVG | |
| 9 | | 2.2260 | 28.60 | 9.87 | 38.47 | 56.00 | -17.53 | QP | |
| 10 | | 2.2260 | 21.92 | 9.87 | 31.79 | 46.00 | -14.21 | AVG | |
| 11 | | 2.7980 | 26.80 | 9.89 | 36.69 | 56.00 | -19.31 | QP | |
| 12 | | 2.7980 | 20.14 | 9.89 | 30.03 | 46.00 | -15.97 | AVG | |

*:Maximum data x:Over limit !:over margin

<Reference Only

Test Result: Pass

5 RADIATED SPURIOUS EMISSIONS


| | |
|-------------------------------|---|
| Test Standard | 47 CFR Part 15, Subpart C 15.247 |
| Test Method | ANSI C63.10 (2013) Section 6.4,6.5,6.6 |
| Test Mode (Pre-Scan) | TX;TX middle channel;TX Low channel;TX high channel |
| Test Mode (Final Test) | TX;TX middle channel;TX Low channel;TX high channel |
| Tester | Charlie |
| Temperature | 25℃ |
| Humidity | 45% |

5.1 LIMITS

| Frequency(MHz) | Field strength(microvolts/meter) | Measurement distance(meters) |
|-----------------------|---|-------------------------------------|
| 0.009-0.490 | 2400/F(kHz) | 300 |
| 0.490-1.705 | 24000/F(kHz) | 30 |
| 1.705-30.0 | 30 | 30 |
| 30-88 | 100 | 3 |
| 88-216 | 150 | 3 |
| 216-960 | 200 | 3 |
| Above 960 | 500 | 3 |

Remark: The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90kHz, 110-490kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation.

5.2 BLOCK DIAGRAM OF TEST SETUP



5.3 PROCEDURE

- For below 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 or 10 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter fully-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- The EUT was set 3 or 10 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.

- h. Test the EUT in the lowest channel, the middle channel, the Highest channel.
- i. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.
- j. Repeat above procedures until all frequencies measured was complete.


Remark:

- 1) For emission below 1GHz, through pre-scan found the worst case is the lowest channel. Only the worst case is recorded in the report.
- 2) The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:
Final Test Level = Receiver Reading + Antenna Factor + Cable Factor - Preamplifier Factor
- 3) Scan from 9kHz to 25GHz, the disturbance above 12.75GHz and below 30MHz was very low. The points marked on above plots are the highest emissions could be found when testing, so only above points had been displayed. The amplitude of spurious emissions from the radiator which are attenuated more than 20dB below the limit need not be reported. fundamental frequency is blocked by filter, and only spurious emission is shown.
- 4) For frequencies above 1GHz, the field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. For the emissions whose peak level is lower than the average limit, only the peak measurement is shown in the report.

5.4 TEST DATA

[TestMode: TX]; [Polarity: Horizontal]

| | |
|------------------------------------|--------------------------------|
| Test Lab: BlueAsia EMC Lab (RE #1) | Project: BLA-EMC-202106-A05 |
| EUT: TWS Bluetooth headset | Test Engineer: Charlie |
| M/N: TG31 | Temperature: 25℃ |
| S/N: | Humidity: 45%RH |
| Test Mode: TX mode | Test Voltage: |
| Note: | Test Data: 2021-06-11 15:36:12 |




| No. | Frequency | Limit dBuV/m | Level dBuV/m | Delta dB | Reading dBuV | Factor dB/m | Detector | Polar | Height cm | Angle deg |
|-----|------------|--------------|--------------|----------|--------------|-------------|----------|-------|-----------|-----------|
| 1* | 38.488MHz | 40.0 | 25.8 | -14.2 | 1.9 | 23.9 | QP | Hor | 100.0 | 117.0 |
| 2* | 65.284MHz | 40.0 | 22.2 | -17.8 | -0.2 | 22.4 | QP | Hor | 100.0 | 261.0 |
| 3* | 152.705MHz | 43.5 | 23.7 | -19.8 | 0.3 | 23.4 | QP | Hor | 100.0 | 295.0 |
| 4* | 518.395MHz | 46.0 | 29.6 | -16.4 | 0.7 | 28.9 | QP | Hor | 100.0 | 325.0 |
| 5* | 722.459MHz | 46.0 | 34.6 | -11.4 | 2.2 | 32.4 | QP | Hor | 100.0 | 169.0 |
| 6* | 951.621MHz | 46.0 | 37.3 | -8.7 | 1.7 | 35.6 | QP | Hor | 100.0 | 84.0 |

Test Result: Pass

[TestMode: TX]; [Polarity: Vertical]

| | |
|------------------------------------|--------------------------------|
| Test Lab: BlueAsia EMC Lab (RE #1) | Project: BLA-EMC-202106-A05 |
| EUT: TWS Bluetooth headset | Test Engineer: Charlie |
| M/N: TG31 | Temperature: 25°C |
| S/N: | Humidity: 45%RH |
| Test Mode: TX mode | Test Voltage: |
| Note: | Test Data: 2021-06-11 15:38:23 |



| No. | Frequency | Limit dBuV/m | Level dBuV/m | Delta dB | Reading dBuV | Factor dB/m | Detector | Polar | Height cm | Angle deg |
|-----|------------|--------------|--------------|----------|--------------|-------------|----------|-------|-----------|-----------|
| 1* | 40.913MHz | 40.0 | 24.4 | -15.6 | 0.3 | 24.1 | QP | Ver | 100.0 | 35.0 |
| 2* | 139.125MHz | 43.5 | 24.6 | -18.9 | 0.9 | 23.7 | QP | Ver | 100.0 | 250.0 |
| 3* | 247.159MHz | 46.0 | 23.8 | -22.2 | 1.1 | 22.7 | QP | Ver | 100.0 | 177.0 |
| 4* | 451.708MHz | 46.0 | 31.0 | -15.0 | 3.1 | 27.9 | QP | Ver | 100.0 | 291.0 |
| 5* | 740.161MHz | 46.0 | 34.6 | -11.4 | 1.8 | 32.8 | QP | Ver | 100.0 | 197.0 |
| 6* | 955.986MHz | 46.0 | 36.8 | -9.2 | 1.2 | 35.6 | QP | Ver | 100.0 | 22.0 |

Test Result: Pass

[TestMode: TX Low channel]; [Polarity: Horizontal]

Radiated Emission Measurement



Site Polarization: **Horizontal** Temperature:
Limit: FCC Part15 (PK) Power: Humidity: %
EUT: TWS Bluetooth headset Distance:
M/N: TG31
Mode: TX-L
Note:

| No. | Mk. | Freq. MHz | Reading Level dBuV | Correct Factor dB | Measure- ment dBuV/m | Limit dBuV/m | Over dB | Antenna Height cm | Table Degree | Comment |
|-----|-----|--------------|--------------------------|-------------------------|----------------------------|-----------------|------------|-------------------------|-----------------|---------|
| 1 | | 4807.000 | 54.27 | 3.71 | 57.98 | 74.00 | -16.02 | peak | | |
| 2 | * | 4807.000 | 44.29 | 3.71 | 48.00 | 54.00 | -6.00 | AVG | | |
| 3 | | 7206.000 | 42.15 | 5.96 | 48.11 | 74.00 | -25.89 | peak | | |
| 4 | | 9608.000 | 41.29 | 9.29 | 50.58 | 74.00 | -23.42 | peak | | |


*:Maximum data x:Over limit !:over margin

<Reference Only

Test Result: Pass

[TestMode: TX Low channel]; [Polarity: Vertical]

Radiated Emission Measurement



Site Limit: FCC Part15 (PK) Polarization: **Vertical** Temperature:
EUT: TWS Bluetooth headset Power: Humidity: %
M/N: TG31 Distance:
Mode: TX-L
Note:

| No. | Mk. | Freq. MHz | Reading Level dBuV | Correct Factor dB | Measure- ment dBuV/m | Limit dBuV/m | Over dB | Antenna Height cm | Table Degree | Comment |
|-----|-----|--------------|--------------------------|-------------------------|----------------------------|-----------------|------------|-------------------------|-----------------|---------|
| 1 | | 4807.000 | 52.04 | 3.71 | 55.75 | 74.00 | -18.25 | peak | | |
| 2 | * | 4807.000 | 43.29 | 3.71 | 47.00 | 54.00 | -7.00 | AVG | | |
| 3 | | 7206.000 | 41.65 | 5.96 | 47.61 | 74.00 | -26.39 | peak | | |
| 4 | | 9608.000 | 39.98 | 9.29 | 49.27 | 74.00 | -24.73 | peak | | |


*:Maximum data x:Over limit !:over margin

<Reference Only

Test Result: Pass

[TestMode: TX middle channel]; [Polarity: Horizontal]

Radiated Emission Measurement



Site: Limit: FCC Part15 (PK) EUT: TWS Bluetooth headset M/N: TG31 Mode: TX-M Note:

Polarization: **Horizontal** Temperature: Humidity: % Power: Distance:

| No. | Mk. | Freq. MHz | Reading Level dBuV | Correct Factor dB | Measure- ment dBuV/m | Limit dBuV/m | Over dB | Antenna Height cm | Table Degree | Comment |
|-----|-----|--------------|--------------------------|-------------------------|----------------------------|-----------------|------------|-------------------------|-----------------|---------|
| 1 | * | 4877.000 | 45.86 | 3.37 | 49.23 | 54.00 | -4.77 | AVG | | |
| 2 | | 4877.500 | 53.12 | 3.37 | 56.49 | 74.00 | -17.51 | peak | | |
| 3 | | 7323.000 | 40.50 | 6.43 | 46.93 | 74.00 | -27.07 | peak | | |
| 4 | | 9764.000 | 40.40 | 9.63 | 50.03 | 74.00 | -23.97 | peak | | |


*:Maximum data x:Over limit !:over margin

〈Reference Only

Test Result: Pass

[TestMode: TX middle channel]; [Polarity: Vertical]

Radiated Emission Measurement



Site Limit: FCC Part15 (PK) Polarization: **Vertical** Temperature:
EUT: TWS Bluetooth headset Power: Humidity: %
M/N: TG31 Distance:
Mode: TX-M
Note:

| No. | Mk. | Freq. MHz | Reading Level dBuV | Correct Factor dB | Measure- ment dBuV/m | Limit dBuV/m | Over dB | Antenna Height cm | Table Degree | Comment |
|-----|-----|--------------|--------------------------|-------------------------|----------------------------|-----------------|------------|-------------------------|-----------------|---------|
| 1 | * | 4877.500 | 49.32 | 3.37 | 52.69 | 74.00 | -21.31 | peak | | |
| 2 | | 7323.000 | 40.70 | 6.43 | 47.13 | 74.00 | -26.87 | peak | | |
| 3 | | 9764.000 | 40.31 | 9.63 | 49.94 | 74.00 | -24.06 | peak | | |


*:Maximum data x:Over limit !:over margin

<Reference Only

Test Result: Pass

[TestMode: TX high channel]; [Polarity: Horizontal]

Radiated Emission Measurement



Site: Limit: FCC Part15 (PK) EUT: TWS Bluetooth headset M/N: TG31 Mode: TX-H Note:

Polarization: **Horizontal** Temperature: Humidity: % Distance:

| No. | Mk. | Freq. MHz | Reading Level dBuV | Correct Factor dB | Measure- ment dBuV/m | Limit dBuV/m | Over dB | Antenna Height cm | Table Degree | Comment |
|-----|-----|--------------|--------------------------|-------------------------|----------------------------|-----------------|------------|-------------------------|-----------------|---------|
| 1 | | 4959.750 | 51.47 | 3.75 | 55.22 | 74.00 | -18.78 | peak | | |
| 2 | * | 4960.000 | 45.02 | 3.75 | 48.77 | 54.00 | -5.23 | AVG | | |
| 3 | | 7440.000 | 41.38 | 6.86 | 48.24 | 74.00 | -25.76 | peak | | |
| 4 | | 9920.000 | 39.26 | 10.16 | 49.42 | 74.00 | -24.58 | peak | | |


*:Maximum data x:Over limit !:over margin

<Reference Only

Test Result: Pass

[TestMode: TX high channel]; [Polarity: Vertical]

Radiated Emission Measurement



Site: Limit: FCC Part15 (PK) EUT: TWS Bluetooth headset M/N: TG31 Mode: TX-H Note:

Polarization: **Vertical** Temperature: Humidity: % Power: Distance:

| No. | Mk. | Freq. MHz | Reading Level dBuV | Correct Factor dB | Measure- ment dBuV/m | Limit dBuV/m | Over dB | Antenna Height cm | Table Degree | Comment |
|-----|-----|--------------|--------------------------|-------------------------|----------------------------|-----------------|------------|-------------------------|-----------------|---------|
| 1 | * | 4959.750 | 46.13 | 3.75 | 49.88 | 74.00 | -24.12 | peak | | |
| 2 | | 7440.000 | 41.51 | 6.86 | 48.37 | 74.00 | -25.63 | peak | | |
| 3 | | 9920.000 | 39.22 | 10.16 | 49.38 | 74.00 | -24.62 | peak | | |

*:Maximum data x:Over limit !:over margin

<Reference Only

Test Result: Pass

6 RADIATED EMISSIONS WHICH FALL IN THE RESTRICTED BANDS


| | |
|-------------------------------|-----------------------------------|
| Test Standard | 47 CFR Part 15, Subpart C 15.247 |
| Test Method | ANSI C63.10 (2013) Section 6.10.5 |
| Test Mode (Pre-Scan) | TX Low channel;TX high channel |
| Test Mode (Final Test) | TX Low channel;TX high channel |
| Tester | Charlie |
| Temperature | 25℃ |
| Humidity | 52% |

6.1 LIMITS

| Frequency(MHz) | Field strength(microvolts/meter) | Measurement distance(meters) |
|-----------------------|---|-------------------------------------|
| 0.009-0.490 | 2400/F(kHz) | 300 |
| 0.490-1.705 | 24000/F(kHz) | 30 |
| 1.705-30.0 | 30 | 30 |
| 30-88 | 100 | 3 |
| 88-216 | 150 | 3 |
| 216-960 | 200 | 3 |
| Above 960 | 500 | 3 |

Remark: The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90kHz, 110-490kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation.

6.2 BLOCK DIAGRAM OF TEST SETUP



6.3 PROCEDURE

- For below 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 or 10 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter fully-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- The EUT was set 3 or 10 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.

- h. Test the EUT in the lowest channel, the middle channel, the Highest channel.
- i. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.
- j. Repeat above procedures until all frequencies measured was complete.


Remark 1: $\text{Level} = \text{Read Level} + \text{Cable Loss} + \text{Antenna Factor} - \text{Preamplifier Factor}$

Remark 2: For frequencies above 1GHz, the field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. For the emissions whose peak level is lower than the average limit, only the peak measurement is shown in the report.

BlueAsia

6.4 TEST DATA

[TestMode: TX Low channel]; [Polarity: Horizontal]




*:Maximum data x:Over limit !:over margin

<Reference Only

Test Result: Pass

[TestMode: TX Low channel]; [Polarity: Vertical]

Radiated Emission Measurement



Site: Polarization: **Vertical** Temperature:
Limit: FCC Part15 (PK) Power: Humidity: %
EUT: TWS Bluetooth headset Distance:
M/N: TG31
Mode: TX-L
Note:

| No. | Mk. | Freq. | Reading Level | Correct Factor | Measurement | Limit | Over | Antenna Height | Table Degree | |
|-----|-----|----------|---------------|----------------|-------------|--------|--------|----------------|--------------|--------|
| | | MHz | dBuV | dB | dBuV/m | dBuV/m | dB | Detector | cm | degree |
| 1 | | 2310.000 | 45.61 | -4.61 | 41.00 | 74.00 | -33.00 | peak | | |
| 2 | * | 2390.000 | 49.40 | -4.27 | 45.13 | 74.00 | -28.87 | peak | | |


*:Maximum data x:Over limit !:over margin

<Reference Only

Test Result: Pass

[TestMode: TX high channel]; [Polarity: Horizontal]

Radiated Emission Measurement



Site: Limit: FCC Part15 (PK) EUT: TWS Bluetooth headset M/N: TG31 Mode: TX-H Note:

Polarization: **Horizontal** Temperature: Humidity: % Distance:

| No. | Mk. | Freq. MHz | Reading Level dBuV | Correct Factor dB | Measure- ment dBuV/m | Limit dBuV/m | Over dB | Antenna Height cm | Table Degree | Comment |
|-----|-----|--------------|--------------------------|-------------------------|----------------------------|-----------------|------------|-------------------------|-----------------|---------|
| 1 | * | 2483.500 | 53.02 | -3.84 | 49.18 | 74.00 | -24.82 | peak | | |
| 2 | | 2500.000 | 46.13 | -3.78 | 42.35 | 74.00 | -31.65 | peak | | |


*:Maximum data x:Over limit !:over margin

<Reference Only

Test Result: Pass

[TestMode: TX high channel]; [Polarity: Vertical]

Radiated Emission Measurement



Site: Limit: FCC Part15 (PK) EUT: TWS Bluetooth headset M/N: TG31 Mode: TX-H Note:

Polarization: **Vertical** Temperature: Humidity: % Power: Distance:

| No. | Mk. | Freq. MHz | Reading Level dBuV | Correct Factor dB | Measure- ment dBuV/m | Limit dBuV/m | Over dB | Antenna Height cm | Table Degree | Comment |
|-----|-----|--------------|--------------------------|-------------------------|----------------------------|-----------------|------------|-------------------------|-----------------|---------|
| 1 | * | 2483.500 | 52.40 | -3.84 | 48.56 | 74.00 | -25.44 | peak | | |
| 2 | | 2500.000 | 47.92 | -3.78 | 44.14 | 74.00 | -29.86 | peak | | |

*:Maximum data x:Over limit !:over margin

〈Reference Only

Test Result: Pass


7 CONDUCTED BAND EDGES MEASUREMENT

| | |
|-------------------------------|--|
| Test Standard | 47 CFR Part 15, Subpart C 15.247 |
| Test Method | ANSI C63.10 (2013) Section 7.8.8 & Section 11.13.3.2 |
| Test Mode (Pre-Scan) | TX |
| Test Mode (Final Test) | TX |
| Tester | Charlie |
| Temperature | 25°C |
| Humidity | 52% |

7.1 LIMITS

| | |
|---------------|--|
| Limit: | In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)). |
|---------------|--|

7.2 BLOCK DIAGRAM OF TEST SETUP



7.3 TEST DATA

Pass: Please Refer To Appendix: For Details

BlueAsia


8 DWELL TIME

| | |
|------------------------|----------------------------------|
| Test Standard | 47 CFR Part 15, Subpart C 15.247 |
| Test Method | ANSI C63.10 (2013) Section 7.8.4 |
| Test Mode (Pre-Scan) | TX |
| Test Mode (Final Test) | TX |
| Tester | Charlie |
| Temperature | 25°C |
| Humidity | 52% |

8.1 LIMITS

| Frequency(MHz) | Limit |
|----------------|---|
| 902-928 | 0.4S within a 20S period(20dB bandwidth<250kHz) |
| | 0.4S within a 10S period(20dB bandwidth≥250kHz) |
| 2400-2483.5 | 0.4S within a period of 0.4S multiplied by the number of hopping channels |
| 5725-5850 | 0.4S within a 30S period |

8.2 BLOCK DIAGRAM OF TEST SETUP



8.3 TEST DATA

Pass: Please Refer To Appendix: For Details

BlueAsia


9 HOPPING CHANNEL NUMBER

| | |
|------------------------|----------------------------------|
| Test Standard | 47 CFR Part 15, Subpart C 15.247 |
| Test Method | ANSI C63.10 (2013) Section 7.8.3 |
| Test Mode (Pre-Scan) | TX |
| Test Mode (Final Test) | TX |
| Tester | Charlie |
| Temperature | 25°C |
| Humidity | 52% |

9.1 LIMITS

| Frequency range(MHz) | Number of hopping channels (minimum) |
|----------------------|--------------------------------------|
| 902-928 | 50 for 20dB bandwidth <250kHz |
| | 25 for 20dB bandwidth ≥250kHz |
| 2400-2483.5 | 15 |
| 5725-5850 | 75 |

9.2 BLOCK DIAGRAM OF TEST SETUP



9.3 TEST DATA

Pass: Please Refer To Appendix: For Details


10 CARRIER FREQUENCIES SEPARATION

| | |
|------------------------|----------------------------------|
| Test Standard | 47 CFR Part 15, Subpart C 15.247 |
| Test Method | ANSI C63.10 (2013) Section 7.8.2 |
| Test Mode (Pre-Scan) | TX |
| Test Mode (Final Test) | TX |
| Tester | Charlie |
| Temperature | 25°C |
| Humidity | 52% |

10.1 LIMITS

| | |
|---------------|--|
| Limit: | 2/3 of the 20dB bandwidth base on the transmission power is less than 0.125W |
|---------------|--|

10.2 BLOCK DIAGRAM OF TEST SETUP




10.3 TEST DATA

Pass: Please Refer To Appendix: For Details

11 20DB BANDWIDTH

| | |
|------------------------|----------------------------------|
| Test Standard | 47 CFR Part 15, Subpart C 15.247 |
| Test Method | ANSI C63.10 (2013) Section 7.8.7 |
| Test Mode (Pre-Scan) | TX |
| Test Mode (Final Test) | TX |
| Tester | Charlie |
| Temperature | 25℃ |
| Humidity | 52% |

11.1 BLOCK DIAGRAM OF TEST SETUP



11.2 TEST DATA

Pass: Please Refer To Appendix: For Details