



FCC ID:
VBNAHCA-01

Test Report No:
D555647736

-48	-20	1.991101453	0.002	44	0.05	compliant
-48	-10	2.423202095	0.003	44	0.05	compliant
-48	0	0.876046288	0.001	44	0.05	compliant
-48	10	1.797174773	0.002	44	0.05	compliant
-48	30	1.351237224	0.002	44	0.05	compliant
-48	40	-1.200797997	-0.001	44	0.05	compliant
-48	50	1.906348843	0.002	44	0.05	compliant
64QAM Modulation ANT2						
-48	-30	2.02316769	0.002	44	0.05	compliant
-48	-20	2.078293764	0.002	44	0.05	compliant
-48	-10	1.759560328	0.002	44	0.05	compliant
-48	0	-1.999748129	-0.002	44	0.05	compliant
-48	10	-1.405766307	-0.002	44	0.05	compliant
-48	30	1.50970398	0.002	44	0.05	compliant
-48	40	2.608539726	0.003	44	0.05	compliant
-48	50	1.588987507	0.002	44	0.05	compliant
64QAM Modulation ANT3						
-48	-30	2.217392102	0.003	44	0.05	compliant
-48	-20	2.819224974	0.003	44	0.05	compliant
-48	-10	1.890571439	0.002	44	0.05	compliant
-48	0	1.713329875	0.002	44	0.05	compliant
-48	10	1.715958388	0.002	44	0.05	compliant
-48	30	1.843202335	0.002	44	0.05	compliant
-48	40	1.541191887	0.002	44	0.05	compliant
-48	50	1.938908827	0.002	44	0.05	compliant
64QAM Modulation ANT4						
-48	-30	1.776185527	0.002	44	0.05	compliant
-48	-20	2.323799708	0.003	44	0.05	compliant
-48	-10	1.601607946	0.002	44	0.05	compliant
-48	0	1.743217581	0.002	44	0.05	compliant
-48	10	1.538107826	0.002	44	0.05	compliant
-48	30	2.080268314	0.002	44	0.05	compliant
-48	40	-1.315214686	-0.001	44	0.05	compliant
-48	50	1.505889013	0.002	44	0.05	compliant
16QAM Modulation ANT1						
-48	-30	-1.060362702	-0.001	44	0.05	compliant
-48	-20	-1.422972127	-0.002	44	0.05	compliant
-48	-10	-1.085548574	-0.001	44	0.05	compliant
-48	0	-1.356174253	-0.002	44	0.05	compliant
-48	10	-1.121627429	-0.001	44	0.05	compliant
-48	30	-1.968247234	-0.002	44	0.05	compliant
-48	40	-2.486736048	-0.003	44	0.05	compliant
-48	50	-2.409964363	-0.003	44	0.05	compliant
16QAM Modulation ANT2						
-48	-30	-2.028436502	-0.002	44	0.05	compliant
-48	-20	-1.655092565	-0.002	44	0.05	compliant
-48	-10	-1.400472829	-0.002	44	0.05	compliant
-48	0	-2.816731139	-0.003	44	0.05	compliant
-48	10	-2.469988394	-0.003	44	0.05	compliant
-48	30	-2.364497341	-0.003	44	0.05	compliant

FCC 47 CFR part 22
(2016)

23. May 2017

Page 74 of 427



FCC ID:
VBNAHCA-01

Test Report No:
D555647736

-48	40	-1.527027343	-0.002	44	0.05	compliant
-48	50	-2.636339486	-0.003	44	0.05	compliant
16QAM Modulation ANT3						
-48	-30	-1.580217722	-0.002	44	0.05	compliant
-48	-20	-1.236210228	-0.001	44	0.05	compliant
-48	-10	-2.195670968	-0.002	44	0.05	compliant
-48	0	-1.955526604	-0.002	44	0.05	compliant
-48	10	-0.910637027	-0.001	44	0.05	compliant
-48	30	-2.416273928	-0.003	44	0.05	compliant
-48	40	-2.315626916	-0.003	44	0.05	compliant
-48	50	-2.445343198	-0.003	44	0.05	compliant
16QAM Modulation ANT4						
-48	-30	-1.965052943	-0.002	44	0.05	compliant
-48	-20	-2.262889466	-0.003	44	0.05	compliant
-48	-10	-2.869707823	-0.003	44	0.05	compliant
-48	0	-2.467350714	-0.003	44	0.05	compliant
-48	10	-1.176486112	-0.001	44	0.05	compliant
-48	30	-2.975734969	-0.003	44	0.05	compliant
-48	40	-2.538482513	-0.003	44	0.05	compliant
-48	50	1.81978452	0.002	44	0.05	compliant
256QAM Modulation ANT1						
-48	-30	-1.442123248	-0.002	44	0.05	compliant
-48	-20	-1.701600122	-0.002	44	0.05	compliant
-48	-10	-1.636807574	-0.002	44	0.05	compliant
-48	0	-1.965233896	-0.002	44	0.05	compliant
-48	10	-1.440246706	-0.002	44	0.05	compliant
-48	30	-1.364139243	-0.002	44	0.05	compliant
-48	40	-2.397475546	-0.003	44	0.05	compliant
-48	50	-0.88622277	-0.001	44	0.05	compliant
256QAM Modulation ANT2						
-48	-30	1.059628194	0.001	44	0.05	compliant
-48	-20	-1.655092565	-0.002	44	0.05	compliant
-48	-10	-1.67299404	-0.002	44	0.05	compliant
-48	0	-1.488143607	-0.002	44	0.05	compliant
-48	10	-1.635413319	-0.002	44	0.05	compliant
-48	30	-1.208378599	-0.001	44	0.05	compliant
-48	40	-2.413977636	-0.003	44	0.05	compliant
-48	50	-1.55586371	-0.002	44	0.05	compliant
256QAM Modulation ANT3						
-48	-30	-1.838916651	-0.002	44	0.05	compliant
-48	-20	1.270145149	0.001	44	0.05	compliant
-48	-10	-1.20843797	-0.001	44	0.05	compliant
-48	0	-1.406734373	-0.002	44	0.05	compliant
-48	10	1.133492406	0.001	44	0.05	compliant
-48	30	0.641526476	0.001	44	0.05	compliant
-48	40	-1.612429223	-0.002	44	0.05	compliant
-48	50	-2.065371227	-0.002	44	0.05	compliant
256QAM Modulation ANT4						
-48	-30	-2.412864415	-0.003	44	0.05	compliant
-48	-20	1.30770437	0.001	44	0.05	compliant

FCC 47 CFR part 22
(2016)

23. May 2017

Page 75 of 427



FCC ID:
VBNAHCA-01

Test Report No:
D555647736

-48	-10	-1.3892688	-0.002	44	0.05	compliant
-48	0	-2.171145825	-0.002	44	0.05	compliant
-48	10	1.461764514	0.002	44	0.05	compliant
-48	30	1.472030708	0.002	44	0.05	compliant
-48	40	2.502870775	0.003	44	0.05	compliant
-48	50	-2.304747468	-0.003	44	0.05	compliant

Table 46 Frequency stability with temp. var. (5 MHz Channel BW)

Config D:

Carrier Frequency: 881.5 MHz

Supply Voltage (DC) [V]	Ambient Temperature [°C]	Frequency Deviation		Manufacturer's Specification		Result
		[Hz]	[ppm]	[Hz]	[ppm]	
QPSK Modulation ANT1						
-48	-30	-2.095866512	-0.002	44	0.05	compliant
-48	-20	-1.295298061	-0.001	44	0.05	compliant
-48	-10	-1.592340705	-0.002	44	0.05	compliant
-48	0	1.50576132	0.002	44	0.05	compliant
-48	10	-0.950459798	-0.001	44	0.05	compliant
-48	30	-1.293865716	-0.001	44	0.05	compliant
-48	40	-1.626380754	-0.002	44	0.05	compliant
-48	50	-1.539296463	-0.002	44	0.05	compliant
QPSK Modulation ANT2						
-48	-30	-2.008651063	-0.002	44	0.05	compliant
-48	-20	1.063527307	0.001	44	0.05	compliant
-48	-10	-2.30859092	-0.003	44	0.05	compliant
-48	0	1.109576488	0.001	44	0.05	compliant
-48	10	-1.095788466	-0.001	44	0.05	compliant
-48	30	0.770177066	0.001	44	0.05	compliant
-48	40	-1.153234625	-0.001	44	0.05	compliant
-48	50	-1.443240399	-0.002	44	0.05	compliant
QPSK Modulation ANT3						
-48	-30	-1.626314261	-0.002	44	0.05	compliant
-48	-20	-1.466224712	-0.002	44	0.05	compliant
-48	-10	-1.256982505	-0.001	44	0.05	compliant
-48	0	2.048774841	0.002	44	0.05	compliant
-48	10	1.714803366	0.002	44	0.05	compliant
-48	30	-0.95292482	-0.001	44	0.05	compliant
-48	40	1.434125188	0.002	44	0.05	compliant
-48	50	-1.523586288	-0.002	44	0.05	compliant
QPSK Modulation ANT4						
-48	-30	-1.943835159	-0.002	44	0.05	compliant
-48	-20	1.029092964	0.001	44	0.05	compliant
-48	-10	-2.146787665	-0.002	44	0.05	compliant
-48	0	-1.335092675	-0.002	44	0.05	compliant
-48	10	-1.39280055	-0.002	44	0.05	compliant
-48	30	-1.575838833	-0.002	44	0.05	compliant
-48	40	-0.847722768	-0.001	44	0.05	compliant
-48	50	2.09524158	0.002	44	0.05	compliant

FCC 47 CFR part 22
(2016)

23. May 2017

Page 76 of 427



FCC ID:
VBNAHCA-01

Test Report No:
D555647736

64QAM Modulation ANT1						
-48	-30	1.481381551	0.002	44	0.05	compliant
-48	-20	1.420735862	0.002	44	0.05	compliant
-48	-10	-1.536379714	-0.002	44	0.05	compliant
-48	0	1.508317364	0.002	44	0.05	compliant
-48	10	1.228007095	0.001	44	0.05	compliant
-48	30	-0.868916868	-0.001	44	0.05	compliant
-48	40	-1.75053472	-0.002	44	0.05	compliant
-48	50	-0.917760553	-0.001	44	0.05	compliant
64QAM Modulation ANT2						
-48	-30	-2.05556833	-0.002	44	0.05	compliant
-48	-20	2.016783474	0.002	44	0.05	compliant
-48	-10	-1.30290704	-0.001	44	0.05	compliant
-48	0	-1.426509771	-0.002	44	0.05	compliant
-48	10	-1.945035692	-0.002	44	0.05	compliant
-48	30	0.994392321	0.001	44	0.05	compliant
-48	40	-1.483948072	-0.002	44	0.05	compliant
-48	50	-1.429529548	-0.002	44	0.05	compliant
64QAM Modulation ANT3						
-48	-30	-1.654489897	-0.002	44	0.05	compliant
-48	-20	-2.255413638	-0.003	44	0.05	compliant
-48	-10	-1.258111006	-0.001	44	0.05	compliant
-48	0	2.625115376	0.003	44	0.05	compliant
-48	10	-1.327919599	-0.002	44	0.05	compliant
-48	30	-1.415131774	-0.002	44	0.05	compliant
-48	40	0.729002059	0.001	44	0.05	compliant
-48	50	-1.634793189	-0.002	44	0.05	compliant
64QAM Modulation ANT4						
-48	-30	1.328159487	0.002	44	0.05	compliant
-48	-20	1.112499667	0.001	44	0.05	compliant
-48	-10	-0.820843488	-0.001	44	0.05	compliant
-48	0	-1.334646076	-0.002	44	0.05	compliant
-48	10	-1.368693192	-0.002	44	0.05	compliant
-48	30	-1.164627793	-0.001	44	0.05	compliant
-48	40	-1.051394393	-0.001	44	0.05	compliant
-48	50	-1.196995363	-0.001	44	0.05	compliant
16QAM Modulation ANT1						
-48	-30	-1.94948836	-0.002	44	0.05	compliant
-48	-20	2.360340877	0.003	44	0.05	compliant
-48	-10	-1.663188741	-0.002	44	0.05	compliant
-48	0	1.088577847	0.001	44	0.05	compliant
-48	10	-1.504506872	-0.002	44	0.05	compliant
-48	30	-1.513431198	-0.002	44	0.05	compliant
-48	40	-1.800882237	-0.002	44	0.05	compliant
-48	50	-1.180194231	-0.001	44	0.05	compliant
16QAM Modulation ANT2						
-48	-30	-2.05556833	-0.002	44	0.05	compliant
-48	-20	-1.976905041	-0.002	44	0.05	compliant
-48	-10	0.760023395	0.001	44	0.05	compliant
-48	0	-1.122375033	-0.001	44	0.05	compliant

FCC 47 CFR part 22
(2016)

23. May 2017

Page 77 of 427



FCC ID:
VBNAHCA-01

Test Report No:
D555647736

-48	10	1.344101693	0.002	44	0.05	compliant
-48	30	1.09291308	0.001	44	0.05	compliant
-48	40	1.127594733	0.001	44	0.05	compliant
-48	50	-1.399432513	-0.002	44	0.05	compliant
16QAM Modulation ANT3						
-48	-30	1.199433209	0.001	44	0.05	compliant
-48	-20	-1.198798564	-0.001	44	0.05	compliant
-48	-10	-1.350384191	-0.002	44	0.05	compliant
-48	0	1.076222834	0.001	44	0.05	compliant
-48	10	-1.43451296	-0.002	44	0.05	compliant
-48	30	1.951444792	0.002	44	0.05	compliant
-48	40	-1.71898515	-0.002	44	0.05	compliant
-48	50	-1.040543975	-0.001	44	0.05	compliant
16QAM Modulation ANT4						
-48	-30	0.778587073	0.001	44	0.05	compliant
-48	-20	-1.632524727	-0.002	44	0.05	compliant
-48	-10	-1.527576205	-0.002	44	0.05	compliant
-48	0	1.298950956	0.001	44	0.05	compliant
-48	10	1.506023691	0.002	44	0.05	compliant
-48	30	-1.496654841	-0.002	44	0.05	compliant
-48	40	1.501322404	0.002	44	0.05	compliant
-48	50	-2.037332888	-0.002	44	0.05	compliant
256QAM Modulation ANT1						
-48	-30	-0.800731941	-0.001	44	0.05	compliant
-48	-20	-1.348801234	-0.002	44	0.05	compliant
-48	-10	-1.145318311	-0.001	44	0.05	compliant
-48	0	0.770383558	0.001	44	0.05	compliant
-48	10	-1.063199124	-0.001	44	0.05	compliant
-48	30	1.143566406	0.001	44	0.05	compliant
-48	40	-1.239054945	-0.001	44	0.05	compliant
-48	50	-1.494958269	-0.002	44	0.05	compliant
256QAM Modulation ANT2						
-48	-30	0.940001628	0.001	44	0.05	compliant
-48	-20	-1.954740801	-0.002	44	0.05	compliant
-48	-10	-1.476611396	-0.002	44	0.05	compliant
-48	0	1.301311422	0.001	44	0.05	compliant
-48	10	1.23358619	0.001	44	0.05	compliant
-48	30	2.914398865	0.003	44	0.05	compliant
-48	40	-2.052066266	-0.002	44	0.05	compliant
-48	50	1.351970313	0.002	44	0.05	compliant
256QAM Modulation ANT3						
-48	-30	1.870757187	0.002	44	0.05	compliant
-48	-20	1.429849544	0.002	44	0.05	compliant
-48	-10	1.057658774	0.001	44	0.05	compliant
-48	0	0.657389937	0.001	44	0.05	compliant
-48	10	-2.099203994	-0.002	44	0.05	compliant
-48	30	-1.45764745	-0.002	44	0.05	compliant
-48	40	1.779805352	0.002	44	0.05	compliant
-48	50	1.820778016	0.002	44	0.05	compliant
256QAM Modulation ANT4						

FCC 47 CFR part 22
(2016)

23. May 2017

Page 78 of 427



FCC ID:
VBNAHCA-01

Test Report No:
D555647736

-48	-30	-1.550964444	-0.002	44	0.05	compliant
-48	-20	-1.203112188	-0.001	44	0.05	compliant
-48	-10	-1.527576205	-0.002	44	0.05	compliant
-48	0	-1.421232446	-0.002	44	0.05	compliant
-48	10	-1.419209002	-0.002	44	0.05	compliant
-48	30	1.092162856	0.001	44	0.05	compliant
-48	40	-1.357483707	-0.002	44	0.05	compliant
-48	50	1.18495358	0.001	44	0.05	compliant

Table 47 Frequency stability with temp. var. (10 MHz Channel BW)

Config F:

Continuing Table 1

Carrier Frequency: 881.5 MHz						
Supply Voltage (DC) [V]	Ambient Temperature [°C]	Frequency Deviation		Manufacturer's Specification		Result
		[Hz]	[ppm]	[Hz]	[ppm]	
QPSK Modulation ANT1						
-48.0	-30.0	-5.10833	-0.006	44	0.05	compliant
-48.0	-20.0	-4.84410	-0.005	44	0.05	compliant
-48.0	-10.0	-4.60608	-0.005	44	0.05	compliant
-48.0	0.0	-4.16364	-0.005	44	0.05	compliant
-48.0	10.0	-5.21255	-0.006	44	0.05	compliant
-48.0	30.0	-5.14881	-0.006	44	0.05	compliant
-48.0	40.0	-4.54603	-0.005	44	0.05	compliant
-48.0	50.0	-3.96088	-0.004	44	0.05	compliant
QPSK Modulation ANT3						
-48.0	-30.0	-5.88826	-0.007	44	0.05	compliant
-48.0	-20.0	-4.04211	-0.005	44	0.05	compliant
-48.0	-10.0	-5.33004	-0.006	44	0.05	compliant
-48.0	0.0	-5.35517	-0.006	44	0.05	compliant
-48.0	10.0	-5.63604	-0.006	44	0.05	compliant
-48.0	30.0	-4.38100	-0.005	44	0.05	compliant
-48.0	40.0	-3.96088	-0.004	44	0.05	compliant
-48.0	50.0	-3.91836	-0.004	44	0.05	compliant
16QAM Modulation ANT1						
-48.0	-30.0	-3.92378	-0.004	44	0.05	compliant
-48.0	-20.0	-3.52943	-0.004	44	0.05	compliant
-48.0	-10.0	-4.56532	-0.005	44	0.05	compliant
-48.0	0.0	-2.84678	-0.003	44	0.05	compliant
-48.0	10.0	-5.25395	-0.006	44	0.05	compliant
-48.0	30.0	-4.13804	-0.005	44	0.05	compliant
-48.0	40.0	-3.57788	-0.004	44	0.05	compliant
-48.0	50.0	-3.75582	-0.004	44	0.05	compliant

FCC 47 CFR part 22
(2016)

23. May 2017

Page 79 of 427



FCC ID:
VBNAHCA-01

Test Report No:
D555647736

16QAM Modulation ANT3						
-48.0	-30.0	-4.26195	-0.005	44	0.05	compliant
-48.0	-20.0	-2.86669	-0.003	44	0.05	compliant
-48.0	-10.0	-3.71805	-0.004	44	0.05	compliant
-48.0	0.0	-4.60431	-0.005	44	0.05	compliant
-48.0	10.0	-5.08668	-0.006	44	0.05	compliant
-48.0	30.0	-3.94281	-0.004	44	0.05	compliant
-48.0	40.0	-3.75582	-0.004	44	0.05	compliant
-48.0	50.0	-2.91845	-0.003	44	0.05	compliant
64QAM Modulation ANT1						
-48	-30	3.84916	0.004	44	0.05	compliant
-48	-20	4.92876	0.006	44	0.05	compliant
-48	-10	3.75687	0.004	44	0.05	compliant
-48	0	4.06374	0.005	44	0.05	compliant
-48	10	2.61910	0.003	44	0.05	compliant
-48	30	2.55984	0.003	44	0.05	compliant
-48	40	4.16429	0.005	44	0.05	compliant
-48	50	3.32989	0.004	44	0.05	compliant
64QAM Modulation ANT3						
-48	-30	4.00564	0.005	44	0.05	compliant
-48	-20	3.86214	0.004	44	0.05	compliant
-48	-10	3.74357	0.004	44	0.05	compliant
-48	0	3.93131	0.004	44	0.05	compliant
-48	10	2.52769	0.003	44	0.05	compliant
-48	30	3.50168	0.004	44	0.05	compliant
-48	40	3.32989	0.004	44	0.05	compliant
-48	50	3.72206	0.004	44	0.05	compliant
256QAM Modulation ANT1						
-48	-30	-3.88155	-0.004	44	0.05	compliant
-48	-20	-3.73191	-0.004	44	0.05	compliant
-48	-10	-3.24730	-0.004	44	0.05	compliant
-48	0	-3.68592	-0.004	44	0.05	compliant
-48	10	-4.64719	-0.005	44	0.05	compliant
-48	30	-2.82952	-0.003	44	0.05	compliant
-48	40	-3.77030	-0.004	44	0.05	compliant
-48	50	-2.58021	-0.003	44	0.05	compliant
256QAM Modulation ANT3						
-48	-30	-3.44729	-0.004	44	0.05	compliant
-48	-20	-2.38345	-0.003	44	0.05	compliant
-48	-10	-2.64802	-0.003	44	0.05	compliant
-48	0	-3.57921	-0.004	44	0.05	compliant

FCC 47 CFR part 22
(2016)

23. May 2017

Page 80 of 427



FCC ID:
VBNAHCA-01

Test Report No:
D555647736

-48	10	-4.17883	-0.005	44	0.05	compliant
-48	30	-2.45691	-0.003	44	0.05	compliant
-48	40	-2.58021	-0.003	44	0.05	compliant
-48	50	-3.23100	-0.004	44	0.05	compliant
Measurement Uncertainty:						±1.0 Hz

Table 48 Frequency stability with temp. var. (5MHz Channel BW)

Config I:

ong 1.

Carrier Frequency: 881.5 MHz						
Supply Voltage (DC) [V]	Ambient Temperature [°C]	Frequency Deviation		Manufacturer's Specification		Result
		[Hz]	[ppm]	[Hz]	[ppm]	
QPSK Modulation ANT1						
-48.0	-30.0	2.49004	0.003	44	0.05	compliant
-48.0	-20.0	2.23680	0.003	44	0.05	compliant
-48.0	-10.0	-2.23853	-0.003	44	0.05	compliant
-48.0	0.0	2.88531	0.003	44	0.05	compliant
-48.0	10.0	-2.27421	-0.003	44	0.05	compliant
-48.0	30.0	-2.07673	-0.002	44	0.05	compliant
-48.0	40.0	2.76774	0.003	44	0.05	compliant
-48.0	50.0	2.50931	0.003	44	0.05	compliant
QPSK Modulation ANT3						
-48.0	-30.0	-2.52707	-0.003	44	0.05	compliant
-48.0	-20.0	2.47589	0.003	44	0.05	compliant
-48.0	-10.0	2.46247	0.003	44	0.05	compliant
-48.0	0.0	-2.10588	-0.002	44	0.05	compliant
-48.0	10.0	-2.88306	-0.003	44	0.05	compliant
-48.0	30.0	2.68138	0.003	44	0.05	compliant
-48.0	40.0	2.17141	0.002	44	0.05	compliant
-48.0	50.0	2.58206	0.003	44	0.05	compliant
16QAM Modulation ANT1						
-48.0	-30.0	-2.13818	-0.002	44	0.05	compliant
-48.0	-20.0	2.08818	0.002	44	0.05	compliant
-48.0	-10.0	2.27180	0.003	44	0.05	compliant
-48.0	0.0	2.21580	0.003	44	0.05	compliant
-48.0	10.0	-2.01532	-0.002	44	0.05	compliant
-48.0	30.0	-2.08758	-0.002	44	0.05	compliant
-48.0	40.0	2.25622	0.003	44	0.05	compliant
-48.0	50.0	2.04129	0.002	44	0.05	compliant
16QAM Modulation ANT3						
-48.0	-30.0	2.44835	0.003	44	0.05	compliant

FCC 47 CFR part 22
(2016)

23. May 2017

Page 81 of 427



FCC ID:
VBNAHCA-01

Test Report No:
D555647736

-48.0	-20.0	-2.67468	-0.003	44	0.05	compliant
-48.0	-10.0	-1.93763	-0.002	44	0.05	compliant
-48.0	0.0	3.73781	0.004	44	0.05	compliant
-48.0	10.0	-2.44450	-0.003	44	0.05	compliant
-48.0	30.0	2.74731	0.003	44	0.05	compliant
-48.0	40.0	-1.41795	-0.002	44	0.05	compliant
-48.0	50.0	-1.96905	-0.002	44	0.05	compliant
64QAM Modulation ANT1						
-48	-30	2.04476	0.002	44	0.05	compliant
-48	-20	-1.92876	-0.002	44	0.05	compliant
-48	-10	-1.38841	-0.002	44	0.05	compliant
-48	0	-1.29763	-0.001	44	0.05	compliant
-48	10	-1.43782	-0.002	44	0.05	compliant
-48	30	-1.80996	-0.002	44	0.05	compliant
-48	40	-1.46353	-0.002	44	0.05	compliant
-48	50	-2.01913	-0.002	44	0.05	compliant
64QAM Modulation ANT3						
-48	-30	1.06581	0.001	44	0.05	compliant
-48	-20	-1.98500	-0.002	44	0.05	compliant
-48	-10	-2.17751	-0.002	44	0.05	compliant
-48	0	-1.33491	-0.002	44	0.05	compliant
-48	10	1.96106	0.002	44	0.05	compliant
-48	30	1.38517	0.002	44	0.05	compliant
-48	40	1.90058	0.002	44	0.05	compliant
-48	50	-2.77813	-0.003	44	0.05	compliant
256QAM Modulation ANT1						
-48	-30	2.36946	0.003	44	0.05	compliant
-48	-20	2.20329	0.002	44	0.05	compliant
-48	-10	2.99582	0.003	44	0.05	compliant
-48	0	2.81931	0.003	44	0.05	compliant
-48	10	3.08037	0.003	44	0.05	compliant
-48	30	2.78481	0.003	44	0.05	compliant
-48	40	2.99953	0.003	44	0.05	compliant
-48	50	2.37092	0.003	44	0.05	compliant
256QAM Modulation ANT3						
-48	-30	2.54673	0.003	44	0.05	compliant
-48	-20	1.96207	0.002	44	0.05	compliant
-48	-10	2.27746	0.003	44	0.05	compliant
-48	0	2.70224	0.003	44	0.05	compliant
-48	10	2.73911	0.003	44	0.05	compliant
-48	30	3.04108	0.003	44	0.05	compliant

FCC 47 CFR part 22
(2016)

23. May 2017

Page 82 of 427



Product Service

FCC ID:
VBNAHCA-01

Test Report No:
D555647736

-48	40	2.71299	0.003	44	0.05	compliant
-48	50	-2.05315	-0.002	44	0.05	compliant
Measurement Uncertainty:					±1.0 Hz	

Table 49 Frequency stability with temp. var. (10MHz Channel BW)



FCC ID:
VBNAHCA-01

Test Report No:
D555647736

Frequency Stability with Voltage Variation:

The EUT was placed in a climatic chamber and allowed to stabilize at +20 degrees Celsius for at least 60 minutes. With the supply voltage of the EUT set to 85% of the nominal value, the frequency error was measure. This procedure was repeated at 100% and 115% of the nominal supply voltage value.

Config A:

Carrier Frequency: 881.5 MHz						
Supply Voltage (DC) [V]	Ambient Temperature [°C]	Frequency Deviation		Manufacturer's Specification		Result
		[Hz]	[ppm]	[Hz]	[ppm]	
QPSK Modulation ANT1						
-40.8	20	-2.933078504	-0.003	44	0.05	compliant
-48.0	20	-1.917164554	-0.002	44	0.05	compliant
-55.2	20	3.186110916	0.004	44	0.05	compliant
QPSK Modulation ANT2						
-40.8	20	-1.706880066	-0.002	44	0.05	compliant
-48.0	20	-2.648109075	-0.003	44	0.05	compliant
-55.2	20	-3.928166261	-0.004	44	0.05	compliant
QPSK Modulation ANT3						
-40.8	20	-1.728071657	-0.002	44	0.05	compliant
-48.0	20	-3.388159093	-0.004	44	0.05	compliant
-55.2	20	-1.305024125	-0.001	44	0.05	compliant
QPSK Modulation ANT4						
-40.8	20	-1.3784452	-0.002	44	0.05	compliant
-48.0	20	-3.09136	-0.004	44	0.05	compliant
-55.2	20	-1.67973	-0.002	44	0.05	compliant
64QAM Modulation ANT1						
-40.8	20	2.363939639	0.003	44	0.05	compliant
-48.0	20	0.996849158	0.001	44	0.05	compliant
-55.2	20	-3.296049399	-0.004	44	0.05	compliant
64QAM Modulation ANT2						
-40.8	20	1.573418558	0.002	44	0.05	compliant
-48.0	20	2.64651324	0.003	44	0.05	compliant
-55.2	20	2.355148026	0.003	44	0.05	compliant
64QAM Modulation ANT3						
-40.8	20	1.202210942	0.001	44	0.05	compliant
-48.0	20	1.434903461	0.002	44	0.05	compliant
-55.2	20	-1.802944425	-0.002	44	0.05	compliant
64QAM Modulation ANT4						
-40.8	20	2.661454637	0.003	44	0.05	compliant
-48.0	20	-1.502859632	-0.002	44	0.05	compliant
-55.2	20	-1.765015	-0.002	44	0.05	compliant
64QAM Modulation ANT1						
-40.8	20	2.363939639	0.003	44	0.05	compliant
-48.0	20	0.996849158	0.001	44	0.05	compliant
-55.2	20	-3.296049399	-0.004	44	0.05	compliant
64QAM Modulation ANT2						

FCC 47 CFR part 22
(2016)

23. May 2017

Page 84 of 427



FCC ID:
VBNAHCA-01

Test Report No:
D555647736

-40.8	20	1.573418558	0.002	44	0.05	compliant
-48.0	20	2.64651324	0.003	44	0.05	compliant
-55.2	20	2.355148026	0.003	44	0.05	compliant
64QAM Modulation ANT3						
-40.8	20	1.202210942	0.001	44	0.05	compliant
-48.0	20	1.434903461	0.002	44	0.05	compliant
-55.2	20	-1.802944425	-0.002	44	0.05	compliant
64QAM Modulation ANT4						
-40.8	20	2.661454637	0.003	44	0.05	compliant
-48.0	20	-1.502859632	-0.002	44	0.05	compliant
-55.2	20	-1.765015	-0.002	44	0.05	compliant
16QAM Modulation ANT1						
-40.8	20	-1.662316281	-0.002	44	0.05	compliant
-48.0	20	-3.012837551	-0.003	44	0.05	compliant
-55.2	20	-2.647491783	-0.003	44	0.05	compliant
16QAM Modulation ANT2						
-40.8	20	-2.955688688	-0.003	44	0.05	compliant
-48.0	20	-2.127725602	-0.002	44	0.05	compliant
-55.2	20	-3.037398274	-0.003	44	0.05	compliant
16QAM Modulation ANT3						
-40.8	20	-1.91738829	-0.002	44	0.05	compliant
-48.0	20	2.476485242	0.003	44	0.05	compliant
-55.2	20	-1.728371572	-0.002	44	0.05	compliant
16QAM Modulation ANT4						
-40.8	20	-1.77268893	-0.002	44	0.05	compliant
-48.0	20	-2.172694294	-0.002	44	0.05	compliant
-55.2	20	-2.270889381	-0.003	44	0.05	compliant
256QAM Modulation ANT1						
-40.8	20	-2.351844596	-0.003	44	0.05	compliant
-48.0	20	-1.884997037	-0.002	44	0.05	compliant
-55.2	20	-3.885071492	-0.004	44	0.05	compliant
256QAM Modulation ANT2						
-40.8	20	1.188853021	0.001	44	0.05	compliant
-48.0	20	-1.651852217	-0.002	44	0.05	compliant
-55.2	20	-2.506971141	-0.003	44	0.05	compliant
256QAM Modulation ANT3						
-40.8	20	-1.418791435	-0.002	44	0.05	compliant
-48.0	20	1.684921881	0.002	44	0.05	compliant
-55.2	20	-1.90627983	-0.002	44	0.05	compliant
256QAM Modulation ANT4						
-40.8	20	1.183357308	0.001	44	0.05	compliant
-48.0	20	2.57757536	0.003	44	0.05	compliant
-55.2	20	1.676245083	0.002	44	0.05	compliant

Table 50 Frequency stability with voltage var. (5 MHz Channel BW)



FCC ID:
VBNAHCA-01

Test Report No:
D555647736

Config D:

Carrier Frequency: 881.5 MHz						
Supply Voltage (DC) [V]	Ambient Temperature [°C]	Frequency Deviation		Manufacturer's Specification		Result
		[Hz]	[ppm]	[Hz]	[ppm]	
QPSK Modulation ANT1						
-40.8	20	-1.4422117	-0.002	44	0.05	compliant
-48.0	20	-0.8812522	-0.001	44	0.05	compliant
-55.2	20	-2.0227523	-0.002	44	0.05	compliant
QPSK Modulation ANT2						
-40.8	20	1.7440947	0.002	44	0.05	compliant
-48.0	20	-1.1694417	-0.001	44	0.05	compliant
-55.2	20	-1.2263933	-0.001	44	0.05	compliant
QPSK Modulation ANT3						
-40.8	20	-1.8297243	-0.002	44	0.05	compliant
-48.0	20	1.3477092	0.002	44	0.05	compliant
-55.2	20	-1.3367538	-0.002	44	0.05	compliant
QPSK Modulation ANT4						
-40.8	20	1.6691295	0.002	44	0.05	compliant
-48.0	20	-1.775678	-0.002	44	0.05	compliant
-55.2	20	-1.6774146	-0.002	44	0.05	compliant
64QAM Modulation ANT1						
-40.8	20	0.9117784	0.001	44	0.05	compliant
-48.0	20	-1.2879233	-0.001	44	0.05	compliant
-55.2	20	-1.1733975	-0.001	44	0.05	compliant
64QAM Modulation ANT2						
-40.8	20	1.5684467	0.002	44	0.05	compliant
-48.0	20	-1.433651	-0.002	44	0.05	compliant
-55.2	20	-0.7319063	-0.001	44	0.05	compliant
64QAM Modulation ANT3						
-40.8	20	-1.7706306	-0.002	44	0.05	compliant
-48.0	20	-2.5803471	-0.003	44	0.05	compliant
-55.2	20	-0.8769997	-0.001	44	0.05	compliant
64QAM Modulation ANT4						
-40.8	20	-1.4221219	-0.002	44	0.05	compliant
-48.0	20	-1.4661263	-0.002	44	0.05	compliant
-55.2	20	-1.5939579	-0.002	44	0.05	compliant
16QAM Modulation ANT1						
-40.8	20	2.0449807	0.002	44	0.05	compliant
-48	20	1.8467657	0.002	44	0.05	compliant

FCC 47 CFR part 22
(2016)

23. May 2017

Page 86 of 427



FCC ID:
VBNAHCA-01

Test Report No:
D555647736

-55.2	20	1.1447329	0.001	44	0.05	compliant
16QAM Modulation ANT2						
-40.8	20	-1.2113688	-0.001	44	0.05	compliant
-48.0	20	-1.7120803	-0.002	44	0.05	compliant
-55.2	20	-1.4044767	-0.002	44	0.05	compliant
16QAM Modulation ANT3						
-40.8	20	-1.7749996	-0.002	44	0.05	compliant
-48.0	20	-1.7717993	-0.002	44	0.05	compliant
-55.2	20	1.147552	0.001	44	0.05	compliant
16QAM Modulation ANT4						
-40.8	20	1.8888514	0.002	44	0.05	compliant
-48.0	20	-1.325281	-0.002	44	0.05	compliant
-55.2	20	-2.2907925	-0.003	44	0.05	compliant
256QAM Modulation ANT1						
-40.8	20	2.0649336	0.002	44	0.05	compliant
-48.0	20	1.7471898	0.002	44	0.05	compliant
-55.2	20	-1.452876	-0.002	44	0.05	compliant
256QAM Modulation ANT2						
-40.8	20	1.9663019	0.002	44	0.05	compliant
-48	20	1.5729687	0.002	44	0.05	compliant
-55.2	20	-0.946414	-0.001	44	0.05	compliant
256QAM Modulation ANT3						
-40.8	20	1.9311202	0.002	44	0.05	compliant
-48.0	20	-1.0384429	-0.001	44	0.05	compliant
-55.2	20	1.1124102	0.001	44	0.05	compliant
256QAM Modulation ANT4						
-40.8	20	1.893888	0.002	44	0.05	compliant
-48.0	20	-2.0537252	-0.002	44	0.05	compliant
-55.2	20	-1.0037399	-0.001	44	0.05	compliant

Table 51 Frequency stability with voltage var. (10 MHz Channel BW)

Config F:

Carrier Frequency: 881.5 MHz						
Supply Voltage (DC) [V]	Ambient Temperature [°C]	Frequency Deviation		Manufacturer's Specification		Result
		[Hz]	[ppm]	[Hz]	[ppm]	
QPSK Modulation ANT1						

FCC 47 CFR part 22
(2016)

23. May 2017

Page 87 of 427



FCC ID:
VBNAHCA-01

Test Report No:
D555647736

-40.8	20.0	-5.24319	-0.003	44	0.05	compliant
-48.0	20.0	-3.58320	-0.005	44	0.05	compliant
-55.2	20.0	-4.37091	-0.005	44	0.05	compliant
QPSK Modulation ANT3						
-40.8	20.0	-4.31800	-0.005	44	0.05	compliant
-48.0	20.0	-4.63117	-0.005	44	0.05	compliant
-55.2	20.0	-4.68519	-0.005	44	0.05	compliant
16QAM Modulation ANT1						
-40.8	20.0	-3.59993	-0.004	44	0.05	compliant
-48.0	20.0	-4.26018	-0.005	44	0.05	compliant
-55.2	20.0	-3.49168	-0.004	44	0.05	compliant
16QAM Modulation ANT3						
-40.8	20.0	-2.73028	-0.003	44	0.05	compliant
-48.0	20.0	-4.62577	-0.005	44	0.05	compliant
-55.2	20.0	-4.38630	-0.005	44	0.05	compliant
64QAM Modulation ANT1						
-40.8	20	4.19708	0.005	44	0.05	compliant
-48	20	3.43944	0.004	44	0.05	compliant
-55.2	20	3.10971	0.004	44	0.05	compliant
64QAM Modulation ANT3						
-40.8	20	3.03010	0.003	44	0.05	compliant
-48	20	3.23680	0.004	44	0.05	compliant
-55.2	20	3.10393	0.004	44	0.05	compliant
256QAM Modulation ANT1						
-40.8	20	-2.97941	-0.003	44	0.05	compliant
-48	20	-2.73621	-0.003	44	0.05	compliant
-55.2	20	-4.86761	-0.006	44	0.05	compliant
256QAM Modulation ANT3						
-40.8	20	-3.06775	-0.003	44	0.05	compliant
-48	20	-3.48453	-0.004	44	0.05	compliant
-55.2	20	-3.53413	-0.004	44	0.05	compliant
Measurement Uncertainty:					±1.0 Hz	

Table 52 Frequency stability with voltage var. (5 MHz Channel BW)

Config I:

Carrier Frequency: 881.5 MHz						
Supply Voltage (DC) [V]	Ambient Temperature [°C]	Frequency Deviation		Manufacturer's Specification		Result
		[Hz]	[ppm]	[Hz]	[ppm]	
QPSK Modulation ANT1						
-40.8	20.0	2.57786	0.003	44	0.05	compliant

FCC 47 CFR part 22
(2016)

23. May 2017

Page 88 of 427



FCC ID:
VBNAHCA-01

Test Report No:
D555647736

-48.0	20.0	2.96977	0.003	44	0.05	compliant
-55.2	20.0	2.48808	0.003	44	0.05	compliant
QPSK Modulation ANT3						
-40.8	20.0	1.75619	0.002	44	0.05	compliant
-48.0	20.0	3.15848	0.004	44	0.05	compliant
-55.2	20.0	2.66420	0.003	44	0.05	compliant
16QAM Modulation ANT1						
-40.8	20.0	2.45455	0.003	44	0.05	compliant
-48.0	20.0	-1.88580	-0.002	44	0.05	compliant
-55.2	20.0	2.48690	0.003	44	0.05	compliant
16QAM Modulation ANT3						
-40.8	20.0	-2.25097	-0.003	44	0.05	compliant
-48.0	20.0	-2.34068	-0.003	44	0.05	compliant
-55.2	20.0	2.75481	0.003	44	0.05	compliant
64QAM Modulation ANT1						
-40.8	20	-2.14413	-0.002	44	0.05	compliant
-48	20	-1.44975	-0.002	44	0.05	compliant
-55.2	20	-1.92275	-0.002	44	0.05	compliant
64QAM Modulation ANT3						
-40.8	20	-2.61187	-0.003	44	0.05	compliant
-48	20	-2.28422	-0.003	44	0.05	compliant
-55.2	20	-2.23262	-0.003	44	0.05	compliant
256QAM Modulation ANT1						
-40.8	20	2.66021	0.003	44	0.05	compliant
-48	20	2.36483	0.003	44	0.05	compliant
-55.2	20	2.15252	0.002	44	0.05	compliant
256QAM Modulation ANT3						
-40.8	20	3.70613	0.004	44	0.05	compliant
-48	20	2.76950	0.003	44	0.05	compliant
-55.2	20	2.44173	0.003	44	0.05	compliant
Measurement Uncertainty:					±1.0 Hz	

Table 53 Frequency stability with voltage var. (10 MHz Channel BW)

The measured frequency stability was found to be compliant with the manufacturer's specifications and with all requirements of the FCC rules.



FCC ID:
VBNAHCA-01

Test Report No:
D555647736

5. TEST DATA AND SCREENSHOTS

5.1 Part List of the RF Measurement Test Equipment

No.	Test Equipment	Manufacturer & Type	Serial Number	Calibration date	Calibration due	Test No.
1	Signal Analyzer	Rohde & Schwarz: FSV 13	101041	01/2017	01/2018	1, 2, 3, 4, 6
2	Signal Analyzer	Rohde & Schwarz: FSQ 26	100363	01/2017	01/2018	1, 2, 3, 4, 6
3	Vector Network Analyzer	Rohde & Schwarz: ZVA40	100146	01/2017	01/2018	1, 2, 3, 4, 6
4	Vector Network Analyzer	Rohde & Schwarz: ZVL13	101177	07/2016	07/2017	1, 2, 3, 4, 6
5	Calibration Unit	Rohde & Schwarz: ZV-Z54	100125	06/2016	06/2017	1, 2, 3, 4, 6
6	Calibration Kit	Hewlett-Packard: HP85032B	2919A04843	07/2016	07/2017	1, 2, 3, 4, 6
7	Frequency Standard	Datum 8040	41005473	01/2017	01/2018	6
8	Frequency Standard	Datum 8040	23006282	07/2016	07/2017	6
9	Multimeter	Fluke 83	65870302	12/2016	12/2017	1, 2, 3, 4, 6
10	Humidity and Temperature Indicator	Vaisala: HMI 31	P3730008	01/2017	01/2018	1, 2, 3, 4, 6
11	DC Power Supply	Maxion: EA-PSI 8080-510	13314600001	cnn	-	1, 2, 3, 4, 6
12	DC Power Supply	SGI 80/188	0525A00547	cnn	-	1, 2, 3, 4, 6
13	Attenuator	Aeroflex/Weinschel: 66-20-33	CF0630	cnn	-	1, 2, 3, 4, 6
14	Attenuator	Aeroflex/Weinschel: 66-10-34	CE6853	cnn	-	1, 2, 3, 4, 6
15	Attenuator	Aeroflex/Weinschel: 66-20-33	BW3346	cnn	-	1, 2, 3, 4, 6
16	Attenuator	Aeroflex/Weinschel: 66-10-34	BK1136	cnn	-	1, 2, 3, 4, 6
16	EMI Test Receiver	R&S ESU40	100262/040	05/2016	05/2017	5
17	Horn Antenna	ETS-Lindgren 3116C-PA	00206990	09/2016	09/2017	5
18	Horn Antenna	ETS-Lindgren ETS3115	92148	06/2016	06/2017	5
19	Bilog Antenna	Schaffner Chase CBL6112B	2003	06/2016	06/2017	5
20	Humidity and temperature meter	Vaisala HM34	G3330003	05/2016	05/2017	5
21	Mast Controller	Maturo NCD/180 2	17210416	cnn	-	5
22	4 meter mast	Maturo TAM4.0-E	086/17210915	cnn	-	5



Product Service

FCC ID:
VBNAHCA-01

Test Report No:
D555647736

23	Anechoic Chamber	S&MC	B83317-C6019	09/2016	09/2019	5
24	Amplifier	Miteq 4FSX4	902638	cnn	-	5

Table 54 Part List of the RF Measurement Test Equipment



Product Service

FCC ID:
VBNAHCA-01

Test Report No:
D555647736

5.2 Spectral Plots

5.2.1. Test No. 2: Modulation Characteristics

No additional measurements are required for the modulation characteristics. Please refer to test no. 3, occupied bandwidth on page 28.

Screenshots below shows information about the modulations I/Q constellation form and modulation information table, displaying error to ideal modulation symbols.




Figure 5 I/Q constellation diagram with capture buffer – QPSK (881.5 MHz) (5MHz Channel BW)



Figure 6 I/Q constellation table with I/Q error – QPSK (881.5 MHz) (5 MHz Channel BW)



Product Service

FCC ID:
VBNAHCA-01

Test Report No:
D555647736




Figure 7 I/Q constellation diagram with capture buffer – 16QAM (881.5 MHz) (5 MHz Channel BW)



Figure 8 I/Q constellation table with I/Q error – 16QAM (881.5 MHz) (5 MHz Channel BW)



Product Service

FCC ID:
VBNAHCA-01

Test Report No:
D555647736




Figure 9 I/Q constellation diagram with capture buffer – 64QAM (881.5 MHz) (5 MHz Channel BW)



Figure 10 I/Q constellation table with I/Q error – 64QAM (881.5 MHz) (5 MHz Channel BW)



Product Service

FCC ID:
VBNAHCA-01

Test Report No:
D555647736




Figure 11 I/Q constellation diagram with capture buffer – 256QAM (881.5 MHz) (5 MHz Channel BW)




Figure 12 I/Q constellation table with I/Q error – 16QAM (881.5 MHz) (5 MHz Channel BW)



Product Service

FCC ID:
VBNAHCA-01

Test Report No:
D555647736

5.2.2. Test No. 3: Occupied Bandwidth

The value ‘Occ BW’ is the measured occupied bandwidth.

Config A ANT1:



Figure 13 Occupied Bandwidth – QPSK (881.5 MHz) (5 MHz Channel BW)




Figure 14 Occupied Bandwidth – 16QAM (881.5 MHz) (5 MHz Channel BW)



Product Service

FCC ID:
VBNAHCA-01

Test Report No:
D555647736




Figure 15 Occupied Bandwidth – 64QAM (881.5 MHz) (5 MHz Channel BW)




Figure 16 Occupied Bandwidth – 256QAM (881.5 MHz) (5 MHz Channel BW)



Product Service

FCC ID:
VBNAHCA-01

Test Report No:
D555647736

Config A ANT2:




Figure 17 Occupied Bandwidth – QPSK (881.5 MHz) (5 MHz Channel BW)




Figure 18 Occupied Bandwidth – 16QAM (881.5 MHz) (5MHz Channel BW)



Product Service

FCC ID:
VBNAHCA-01

Test Report No:
D555647736



Figure 19 Occupied Bandwidth – 64QAM (881.5 MHz) (5 MHz Channel BW)



Figure 20 Occupied Bandwidth – 256QAM (881.5 MHz) (5 MHz Channel BW)



Product Service

FCC ID:
VBNAHCA-01

Test Report No:
D555647736

Config A ANT3:




Figure 21 Occupied Bandwidth – QPSK (881.5 MHz) (5 MHz Channel BW)




Figure 22 Occupied Bandwidth – 16QAM (881.5 MHz) (5 MHz Channel BW)



Product Service

FCC ID:
VBNAHCA-01

Test Report No:
D555647736




Figure 23 Occupied Bandwidth – 64QAM (881.5 MHz) (5 MHz Channel BW)




Figure 24 Occupied Bandwidth – 256QAM (881.5 MHz) (5 MHz Channel BW)



Product Service

FCC ID:
VBNAHCA-01

Test Report No:
D555647736

Config A ANT4:




Figure 25 Occupied Bandwidth – QPSK (881.5 MHz) (5 MHz Channel BW)




Figure 26 Occupied Bandwidth – 16QAM (881.5 MHz) (5 MHz Channel BW)



Product Service

FCC ID:
VBNAHCA-01

Test Report No:
D555647736




Figure 27 Occupied Bandwidth – 64QAM (881.5 MHz) (5 MHz Channel BW)




Figure 28 Occupied Bandwidth – 256QAM (881.5 MHz) (5 MHz Channel BW)

Config B ANT1:

FCC 47 CFR part 22
(2016)

23. May 2017

Page 103 of 427



Product Service

FCC ID:
VBNAHCA-01

Test Report No:
D555647736




Figure 29 Occupied Bandwidth – QPSK (879 MHz, 884 MHz) (2 X 5 MHz Channel BW)




Figure 30 Occupied Bandwidth – 16QAM (879 MHz, 884 MHz) (2 X 5 MHz Channel BW)



Product Service

FCC ID:
VBNAHCA-01

Test Report No:
D555647736




Figure 31 Occupied Bandwidth – 64QAM (879 MHz, 884 MHz) (2 X 5 MHz Channel BW)




Figure 32 Occupied Bandwidth – 256QAM (879 MHz, 884 MHz) (2 X 5 MHz Channel BW)