



RF Exposure Evaluation Declaration

Report No.: S20240724240903 Issue Date: 09-09-2024

Applicant: Shanghai Ortek Electronics Co., Ltd.

Address: No.1 Jiefangdao Road, Bridge 16 Southern, Caoan Road, Jiading District, Shanghai, China

FCC ID: 2AT62TN-100

Application Type: Certification

Product: Car Audio

Model No.: TN-100

Trade Mark: /

FCC Rule Part(s):

CFR 47, FCC Part 2.1091 Radio frequency radiation exposure evaluation: mobile devices.

Item Receipt date: Jul. 24, 2024

Test Date: Aug. 06 ~ Aug. 27, 2024

Stone Compiled By (Stone Zhang) Senior Test Engineer InP. Approved By (Line Chen) Engineer Manage

APPRON

The test results relate only to the samples tested.

This equipment has been shown to be capable of compliance with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in KDB 558074 D01. Test results reported herein relate only to the item(s) tested.

The test report shall not be reproduced except in full without the written approval of Fangguang Inspection & Testing Co., Ltd. Wuxi Branch

The test report must not be used by the client to claim product certifications, approval, or endorsement by NVLAP, NIST or any agency of U.S. Government.



Revision History

Report No.	Version	Description	Issue Date
S20240724240903	Rev. 01	1	09-09-2024



CONTENTS

Des	cription		Page
1.	PRODU	CT INFORMATION	4
	1.1.	Equipment Description	4
	1.2.	Product Specification Subjective to this Report	4
2.	RF Expo	osure Evaluation	5
	2.1.	Limits	5
	2.2.	Calculation Method	6



1. PRODUCT INFORMATION

1.1. Equipment Description

Product Name:	Car Audio
Model Name:	TN-100
Trade Mark:	/
Input Voltage Range:	DC12V/24V

1.2. Product Specification Subjective to this Report

Frequency Range:	BT:2402~2480MHz		
	BLE: 2402~2480MHz		
Data Rate:	BT:1Mbps (GFSK), 2Mbps (Π/4 DQPSK), 3Mbps (8DPSK)		
	BLE_1M:1Mbps		
Antenna Type:	PCB Antenna		
Antenna Gain:	2.81dBi		



2. **RF Exposure Evaluation**

2.1. Limits

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in 1.1307(b)

Frequency Range	Electric Field	Magnetic Field	Power Density	Average Time		
(MHz)	Strength (V/m) Strength (A/m) (mW/cm ²)		(Minutes)			
	(A) Limits for Occupational/ Control Exposures					
300-1500			f/300 6			
1500-100,000		5		6		
(B) Limits for General Population/ Uncontrolled Exposures						
300-1500 f/150		f/1500	6			
1500-100,000			1	30		

LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (M	PE)
--	-----

f= Frequency in MHz

Calculation Formula: Pd = (Pout*G)/(4*pi*r²)

Where

 $Pd = power density in mW/cm^2$

Pout = output power to antenna in mW

G = gain of antenna in linear scale

Pi = 3.1416

r = distance between observation point and center of the radiator in cm

Pd is the limit of MPE, 1mW/cm². If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance r where the MPE limit is reached.





2.2. Calculation Method

Product	Car Audio
Test Item	RF Exposure Evaluation

Mode	Frequency (MHz)	Maximum Conducted Output Power (dBm)	Antenna Gain (dBi)	P (dBm)	G (mW)	MPE (mW/cm²)	MPE Limits (mW/cm ²)
BT	2402 - 2480	-1.38	2.81	1.43	1.39	0.003	1.00
BLE_1M	2402 - 2480	6.00	2.81	8.81	7.60	0.015	1.00

Remark: 1. MPE use distance is 20cm from manufacturer declaration of user manual.

Remark: 2. Use the maximum gain of all bands when evaluating

CONCULISON:

The measurement results comply with the FCC Limit per 47 CFR 2.1093 for the uncontrolled RF Exposure and SAR Exclusion Threshold per KDB 447498 v06.

—— The End