




Acknowledgment Letter

SPECIFICATION FOR APPROVAL

Customer Name	Yihua		
Customer Project Name	TA188	SDC Project Name	TA188-改壳
Antenna type	Four in one antenna	SDC P/N	WG4604B-0813R-90
Band	WiFi2. 4G/5. 8G/BT/GPS		
Version	A0		
Designer Information			
RF Engineer		R&D Director	
ME Engineer			

Approval				ustomer Approval	
	Prepared By	Checked By	Approval By	Checked By	Approval By
Signature	Huang Zongbao	Fu Xuerong	Xia Chenglei		
Date	2023. 5. 25	2023. 5. 25	2023. 5. 25		

hange Log				
Version	Change Description	Person in Charge	Approval By	Date



Catalogue

No.	Item	Page No.
1	Drawing or Product Image	3
2	Dimensions Test Report	4
3	RF Performance Test Report	5-7
4	Reliability Test Report1	8
5	Package Document	9
6	RoHS Control list for Sample	10
7	Install Wizard or Other	10

[illegible]

Company Address: 4th Floor, Building B5, Xinfu Industrial Park, Chongqing Road, Fuyong Town, Bao'an District, Shenzhen TEL:0755-27211658 FAX:0755-29485750



SHUN DA CHENG TECHNOLOGY CO., LTD

Sample Dimensions Test Report

Test Date	2023. 5. 25	Sample Qty.	3	Inspector	Xu Yanfang
Dimension No.	Standard	Sample 1	Sample 2	Sample 3	Pass/NG
①length	38.5±0.2mm	38.5	38.5	38.6	Pass
②width	21.98±0.2mm	21.98	22.05	22	Pass
③thickness	0.1±0.03mm	0.1	0.1	0.1	Pass
④Line length	90±2mm	90	91	90	Pass
⑤					
⑥					
⑦					
Conclusion					PASS
Inspector & Date	Xu Yanfang 2023. 5. 25		Approval & Date		



RF Performance Test Report

Antenna Test Equipment Introduction

Test of antenna input characteristics using **Agilent E5071C** and **Agilent 5062A** vector network analyzer; The radiation pattern of the antenna are tested using the guangping 3D near field Anechoic Chamber, and the instrument is used to agilent8960 E5515 and Agilent E4438C. The test coordinates of the darkroom are as follows:




图 4 3D 微波暗室测试坐标系 (back view)

1. **S11 Parameter-VSWR**


Measuring Method is a 50Ω coaxial cable is connected to the antenna. Then this cable is connected to a network analyzer to measure the S11 parameter, Keeping this fixture away from metal at least 20cm.



SHUN DA CHENG TECHNOLOGY CO., LTD


S11 Parameter-VSWR

Frequency(MHz)	1570	1575	1580	2400	2450	2500	5150	5720	5850
VSWR	1.54	1.53	1.57	2.12	1.10	1.98	1.52	1.36	1.59



2. Antenna Matching Network

Antenna





3. Electrical parameter:

Electrical parameter	
(Frequency range)	1575-5850Mhz
Polarization mode	Horizontal and vertical polarization
Measurement program	Wide screen
Test equipment	Agilent(5071B) /Agilent (8960) /ROHDE&SCHWARZ(CMW500)
Test Settings	Insert the testing white card, fix the entire machine on the testing turntable, open the testing software, and select the corresponding testing frequency band
Testing location	OTA microwave anechoic chamber
Antenna manufacturer	Shenzhen Shundacheng Technology Co., Ltd
Debugging mode	PIFA
Antenna material	FPC+coaxial line


4. Gain & Efficiency

Frequency (MHz)	Efficiency (%)	Peak GAIN (dBi)
1575	38. 85	0. 81
2400	43. 91	1. 84
2450	44. 86	2. 13
2500	45. 49	2. 16
5100	39. 74	2. 1
5207	38. 44	0. 91



SHUN DA CHENG TECHNOLOGY CO., LTD

5314	37. 76	1. 73
5421	39. 05	1. 73
5528	44. 37	2. 03
5635	39. 14	1. 05
5742	42. 37	2. 27
5850	41. 95	2. 04



5. OTA data

Company Address: 4th Floor, Building B5, Xinfu Industrial Park, Chongqing Road, Fuyong Town, Bao'an District, Shenzhen TEL:0755-27211658 FAX:0755-29485750



2.4G	802.11b, (2.4G) 11M		
Channel	CH1	CH6	CH11
TRP	13.53	14.41	14.62
TIS	-80.28	-81.49	-81.22
5.8G	802.11A, (5.8G) 54M		
Channel	CH36	CH60	CH165
TRP	10.52	9.39	10.76
TIS	-68.37	-68.62	-70.39

6. GPS measurement map



Measured on the rooftop of the fifth floor, the positioning time is about 70 seconds, and the maximum value of two stars is 40

Reliability Test Report



SHUN DA CHENG TECHNOLOGY CO., LTD

Test Date	2023. 5. 25	Sample Qty.	3	Inspector	Xu Yanfang	
Test Item	Requirement	testing equipment	Sample 1	Sample 2	Sample 3	PASS/NG
high temperature storage	Expose to +85 °C for 24 hours, recover for 2 hours, and conduct testing	Constant temperature and humidity box	OK	OK	OK	Pass
low temperature storage	Expose to -40 °C for 24 hours, recover for 2 hours, and perform testing	Constant temperature and humidity box	OK	OK	OK	Pass
High temperature operation	Powered on for 24 hours at +60 °C	Constant temperature and humidity box	OK	OK	OK	Pass
Low temperature operation	Powered on for 24 hours at -20 °C	Constant temperature and humidity box	OK	OK	OK	Pass
Salt spray test	(5 ± 0. 5)%sodium chloride、pH Value is 6. 5~7. 2, Temperature of experimental chamber (35 ± 2) °C ☐ 24H ☒ 48H	Salt spray testing machine	OK	OK	OK	Pass
Connector riveting and pulling force	1. 13Wire diameter ≥ 10N 0. 81Wire diameter ≥ 8N RG174 ≥ 60N RG178 ≥ 50N	Push-pull force gauge	≥ 10N	≥ 10N	≥ 10N	Pass
Conclusion						Pass
Inspector & Date	Xu Yanfang 2023. 5. 25		Approval & Date			



SHUN DA CHENG TECHNOLOGY CO., LTD

Install Wizard or Other


setup script:

Take 1 PCS of product, tear off the release paper on the back of the FPC by hand, and then align the FPC positioning hole position with the shell positioning hole position (positioning rib position or positioning line), and attach it flat to the shell, as shown in the following figure:

Installation process precautions:

- ☐ Ensure that the FPC is fully attached to the housing after pasting the antenna;
- ☐ Align the positioning hole with the position of the casing positioning column;
- ☐ Align FPC edge with shell edge;
- ☐ When attaching the terminal to the PCBA end of the motherboard, please first align the terminals and then snap them vertically;
- ☐ When disassembling antenna terminals, it is necessary to use a tool (such as a special pry bar) to vertically lift the terminals and not directly pull the wires for disassembly


Test equipment



Company Address: 4th Floor, Building B5, Xinfu Industrial Park, Chongqing Road, Fuyong Town, Bao'an District, Shenzhen TEL:0755-27211658 FAX:0755-29485750



SHUN DA CHENG TECHNOLOGY CO., LTD





SHUN DA CHENG TECHNOLOGY CO., LTD

Product ROHS certificate

Certificate

Certificate Number: UNIB22051904HC-01



Certificate of Compliance

Product:	Fpc antenna
Applicant:	ShenZhen ShunDaCheng Technology Co., Ltd. 4th Floor, Building B5, Xinfu Industrial Zone, Fuyong Chongqing Road, Bao'an District, Shenzhen
Manufacturer:	ShenZhen ShunDaCheng Technology Co., Ltd.
Model No.:	N/A
Trade Name:	N/A
Test Methods:	IEC 62321-2:2021, IEC 62321-3-1:2013, IEC 62321-4:2013 +A1:2017, IEC 62321-5:2013, IEC 62321-6:2015, IEC 62321-7-1:2015 IEC 62321-7-2:2017, IEC 62321-8:2017

The laboratory tested the product provided by the applicant according to the above test methods. According to the test results, the product conforms to RoHS Directive [(2011/65/EU and Amendment (EU) 2015/863)] issued by the European Commission. It is possible to use CE marking to demonstrate the compliance with RoHS Directive.

The certificate applies to the tested sample above mentioned only and shall not imply an assessment of the whole production. It is only valid in connection with the test report number: UNIB22051904HR-01.

Note: According to the requirements of the applicant for testing, details are shown in the test report.

RoHS

May 27, 2022
Issue Date



Hoffer-Kau

CE

Shenzhen United Testing Technology Co., Ltd.

Shenzhen: 2/F., Annex Building, Jiahuangyuan Tech Park, No.365, Baotian 1st Road, Bao'an District, Shenzhen, Guangdong, China/518050

Guangzhou: No.47-3, Industrial Road, Zhushan, Dalong Street, Panyu District, Guangzhou, Guangdong, China/511450

Tel: +86-755-86180996 / +86-020-39277769 Fax: +86-0755-86180156

Web Site: www.uni-lab.hk/ E-mail: hofferku@uni-lab.hk

